T21

The Collection

TARGETTI

TARGETTI

Index

Chapter		Page
01	**Us Targetti**	**16**
02	**Indoor Collection**	**70**
	Recessed	**71**
	Projectors	**206**
	Systems	**332**
	Ceiling and suspensions	**446**
	Wall mounted luminaires	**524**
03	**Outdoor Collection**	**544**
	Inground recessed	**545**
	Projectors	**646**
	Wall recessed luminaires	**726**
	Surface luminaires	**746**
	Bollards	**776**
04	**Light Management System**	**798**
05	**Technical data**	**822**

Indoor

New Upgrade

Recessed

Linear recessed

72
LOGICO SA
Recessed
Opal/UGR/WW

72
LOGICO SA
Recessed+flange
Opal/UGR/WW

Recessed

88
CCTEvo
Downlight
UGR/VWF Ø 214mm

88
CCTEvo
Downlight
UGR/VWF Ø 160mm

88
CCTEvo
Downlight
UGR/VWF Ø 105mm

88
CCTEvo
Downlight
Ø 78mm

88
CCTEvo
Downlight
Ø 58mm

104
CCTEvo
Wall Washer
Ø 160mm

104
CCTEvo
Wall Washer
Ø 105mm

104
CCTEvo
Wall Washer
Ø 78mm

112
CCTEvo
Architectural
Ø 160mm

112
CCTEvo
Architectural
Ø 105mm

112
CCTEvo
Architectural
Ø 78mm

112
CCTEvo
Architectural
Ø 58mm

128
CCTEvo
Extractable
Ø 162mm

128
CCTEvo
Extractable
Ø 125mm

128
CCTEvo
Gimbal
Ø 125mm

128
CCT EVO
Gimbal
Ø 105mm

146
OZ Stand Alone
Recessed
Small 1x

146
OZ Stand Alone
Recessed
Small 3x

146
OZ Stand Alone
Recessed
Small 5x

146
OZ Stand Alone
Recessed
Large 1x

146
OZ Stand Alone
Recessed
Large 3x

146
OZ Stand Alone
Recessed
Large 5x

146
OZ Stand Alone
Trimless
Small 1x

146
OZ Stand Alone
Trimless
Small 3x

146
OZ Stand Alone
Trimless
Small 5x

146
OZ Stand Alone
Trimless
Large 1x

146
OZ Stand Alone
Trimless
Large 3x

146
OZ Stand Alone
Trimless
Large 5x

490
THREESIXTY
Ø384mm
Opal/UGR/HALO

490
THREESIXTY
Ø590mm
Opal/UGR/Halo

490
THREESIXTY
Ø870mm
Opal/UGR/Halo

490
THREESIXTY
Ø1150mm
Opal/UGR/Halo

166
T-PANEL
60x60

166
T-PANEL
30x120

170
STORE Gimbal

170
STORE Gimbal
Mini

186
ZENO Small
Extractable

192
COZY

196
BEBOP

200
QUICKLED

202
OTTO
Semi-Recessed

202
OTTO
Recessed
Extractable

Online
CCTLED
Downlight

Online
CCTLED
Architectural

Online
CLOUD

New Upgrade

Projectors

Track projectors

208
ZENO Large
Ø 184mm

208
ZENO Medium
Ø 134mm

208
ZENO Small
Ø 105mm

232
LABEL 9
Ø 87mm

232
LABEL 7
Ø 74mm

232
LABEL 6
Ø 59mm

242
CAPSULE 7
Ø 70mm

242
CAPSULE 6
Ø 60mm

246
STORE
Ø 93mm

246
STORE
Mini
Ø 75mm

258
LEDÒ

258
LEDÒ
Tunable

268
RAY
Ø 144mm

268
RAY
Mini
Ø 115mm

268
RAY
Micro
Ø 76mm

Tracks

278
EUROSTANDARD
Plus

Surface projectors

286
JEDI
Compact

296
ZENO Applique
Large
Ø 184mm

296
ZENO Applique
Medium
Ø 134mm

300
VOLTA

306
CORO
Large
Ø 119mm

306
CORO
Small
Ø 82mm

326
OTTO
Ceiling

326
OTTO
Multi-Optic

Systems

Systems 48V

334
OZ
Power Track

334
OZ
Single module
Small Fixed

334
OZ
Single module
Small Adjustable

334
OZ
Single module
Large Fixed



334
OZ
Single module
Large Adjustable

334
OZ
Multiple Module
Small 5x

334
OZ
Multiple Module
Large 3x

334
OZ
Module Linear

334
OZ
Recessed profile
Small/Large

334
OZ
Ceiling/ Suspen-
sion installation
profile Small/
Large

374
FORTYEIGHT
H section
track Ceiling/
Suspension

374
FORTYEIGHT
Track Trimless
Recessed



374
FORTYEIGHT
Track Trimless
Deep Recessed

374
FORTYEIGHT
Logico 30

374
FORTYEIGHT
Label 7
Ø74mm

374
FORTYEIGHT
Label 6
Ø59mm

374
FORTYEIGHT
Label 4
Ø40mm

374
FORTYEIGHT
Label 2
Ø23mm

Systems 230V

398
LOGICO System
Ceiling/ Suspen-
sion Continuous
Light module

398
LOGICO System
Ceiling/
Suspension
Projector module

398
LOGICO System
Ceiling/
Suspension
Spot module

398
LOGICO System
Trimless Recessed
Continuous light
module

398
LOGICO System
Trimless Recessed
Projector module

398
LOGICO System
Trimless Recessed
Spot module

398
LOGICO System
Recessed
with flange
Continuous
Light module

398
LOGICO System
Recessed
with flange
Projector
module

398
LOGICO System
Recessed
with flange
Spot module

New Upgrade

Ceiling/Suspension

Linear Ceiling/ Suspension

448
ISO

454
OMEGA

460
LOGICO SA
Ceiling/
Suspension
Opal/UGR/WW

468
CARTESIO

472
DIVA

476
SLIM Line

476
SLIM Rectangle

Ceiling/ Suspension

482
OZ Stand Alone
Ceiling Large 3x

482
OZ Stand Alone
Ceiling Large 5x

490
THREESIXTY
Ø384mm
Opal/UGR/Halo

490
THREESIXTY
Ø590mm
Opal/UGR/Halo

490
THREESIXTY
Ø870mm
Opal/UGR/Halo

490
THREESIXTY
Ø1150mm
Opal/UGR/Halo

502
CCTLED
Pendant

504
CCTLED
Tube Smart

504
CCTLED
Tube Tech

504
CCTLED
Tube Feel

504
CCTLED
Tube Deep

514
BEBOP
Ceiling/
Suspension

516
GLOBO

518
WASABI

522
DECANTER

Wall



454
OMEGA
Applique

526
FLOOD



528
HALL



530
SLIM
Wall

532
MINIMINIMA

534
BRAQUE

536
OSIRIDE
Ø 200mm

536
OSIRIDE
Ø 260mm

536
OSIRIDE
Ø 320mm

536
OSIRIDE
Ø 400mm

536
OSIRIDE
Ø 500mm

540
PROFESSIONAL
120x220

540
PROFESSIONAL
235X235mm

540
PROFESSIONAL
275X275mm

540
PROFESSIONAL
350X350mm

Inground recessed

Linear inground recessed



546
JEDI



546
JEDI RGBW



558
JEDI Compact

574
MERCURE
Light-line

574
MINIMERCURE
LED - RGB

574
MICROMERCURE

Inground recessed



582
KEPLERO
Zoom



582
KEPLERO
Zoom RGBW



582
KEPLERO
Gimbal



582
KEPLERO
Gimbal HP



582
KEPLERO
WW



582
KEPLERO
WW RGBW

582
KEPLERO
Mini Zoom

582
KEPLERO
Mini Gimbal

582
KEPLERO
Mini HE

582
KEPLERO
Mini HE RGBW



582
KEPLERO
Mini WW

622
JUPITER
Ø 80mm

622
JUPITER
Mini
Ø 50mm

632
SATURN
Ø 60mm



632
SATURN
Mini
Ø 35mm



638
LED.Y
Multiled
Ø60mm Ø68mm



638
LED.Y
Monoled
Ø 63mm



638
LED.Y
Monoled RGB
Ø 63mm

644
TITANO

Projectors

Linear projectors

648
JEDI

648
JEDI RGBW

662
JEDI Compact

Projectors

300
VOLTA



678
DART Maxi
214x214mm

678
DART Medium
134x134mm

678
DART Small
76x76mm

678
DART Small
Remote driver
76x76mm

696
PYROS
Ø 186mm

696
PYROS
RGBW
Ø 186mm

696
NANO PYROS
Ø 107mm

696
NANO PYROS
RGB
Ø 107mm

696
PICO PYROS
Ø 45mm

708
JUPITER PRO
Ø 50mm

708
JUPITER PRO
Small
Ø 40mm

708
JUPITER Mini
Ø 38mm

722
LED.Y
Ø50mm

722
LED.Y
RGB
Ø 50mm

Wall recessed

728
ZEDGE PRO

736
ZEDGE
Line

736
ZEDGE
Line Opal

742
ZEDGE

New Upgrade

Surface luminaires



748
MR SMITH

748
MRS SMITH

756
FEBO EVO



760
Q-BO

762
STILO
Wall/Ceiling

774
HOCKEY
Wall/Ceiling

728
ZEDGE PRO

736
ZEDGE
Line

736
ZEDGE
Line Opal

Bollard

778
MR. BO
H 400mm

778
MR. BO
H 800mm

778
MR. BO
H 1000mm

786
CHIODINO
H 890

790
STILO
Bollard Path
H 800mm

790
STILO
Bollard Path
H 1100mm

790
STILO
Bollard Raised
H 864mm

794
ZEDGE
Bollard
H 400mm

794
ZEDGE PRO
Bollard
H 400mm

794
ZEDGE PRO
Bollard
H 800mm

794
ZEDGE PRO
Bollard
H 1000mm

Light Management System

802
TARGETTI CONTROL

814
DMX SYSTEM

The Group

3F Filippi and Targetti, two companies that have shaped the history of lighting in Italy are now a cohesive Group acting as sole partner for lighting professionals and designers looking for quality solutions.

With extensive experience and the combination of their respective expertise in technical and architectural lighting the two brands together provide a complete portfolio of products that proudly bringMade in Italy to more than 50 countries worldwide.
Today the 3F Filippi-Targetti Group can meet and satisfy any kind of design and project requirements. Our partners can choose from a huge selection of products and solutions; from high-tech and functional products from the 3F Filippi catalogue to indoor and outdoor architectural lighting fixtures designed by Targetti, right up to a wide range of LED lamps and fixtures from the Duralamp brand.

We are Targetti

We started in Florence in 1928 and since then we have been designing and creating architectural light fixtures that we export all over the world. Our approach to “light” is profoundly influenced by the links we have with our city.

The unique architectural artistic heritage that surrounds us deeply inspires our ideas, tastes, and creativity and makes us aware of the skills and respect necessary to light architecture.



Us and light

To us light is technical refinement and scientific precision as well as feelings, atmosphere and the possibility to adorn space with emotions and to positively influence the well-being of mankind.

Dialogue is at the heart of our work

Working with light implies a multidisciplinary approach and dialogue between the various players for a common goal: the best results for every project.

We provide our customers with the experience and skills we have acquired in almost a century of working in the industry. We do this through dialogue and support at every stage of the journey, paving the way to sharing and listening while respecting reciprocal roles.


icon
idea
MIGLIORE SERVIZIO

The ideas behind our products

Handcrafted care, attention to details, intuition and an accurate search for the best technical solutions are the factors that make our products recognisable expressions of Made in Italy.

Every one of our fixtures is the result of our desire to equip lighting designers with tools that are able to give shape to their ideas. Every stage of product development from concept design to scale production takes place in our plants. The ability to interpret light intelligently is the expression of Targetti style.



Worldwide

We are an international team with identity, culture and different skills united by a common language: light.



Headquarter

Subsidiaries and Sales Offices

Targetti USA, Inc.
Costa Mesa, California – USA

Targetti Latin America
Cali – Colombia

Production plans

Costa Mesa, California – USA

Legend

Headquarter



Production plan

Subsidiary



Targetti Sankey S.p.A.
Firenze – Italia

Targetti France S.a.S
Paris – France
Targetti Spain S.A.U.
Barcelona – Spain
Targetti UK Limited
London – United Kingdom

Targetti Sankey S.p.A.
Dubai – EAU

Targetti Lighting Co., Ltd
Beijing – China
Shanghai – China

Firenze – Italy
Nusco – Italy

Changzhou – China

Competence

The creative process at Targetti is the result of team work composed of different skills: optics, thermodynamics, mechanics, electronics and design.

Our R&D department has highly specialised divisions and teams. Our internal testing laboratory, certified by third-party bodies, carries out photometric, electric, thermal and mechanical measurements to ensure product quality and lasting reliability.
Our Optic Division carries out advanced studies on optical systems to achieve the perfect synthesis between quantity and quality of light; between beam perfection and performance.

The results of our creative process has led to the filing of 27 patents.

Chapelle du Collège
Carpentras, France

Installer BRES SA Electricité
Photographer Hugo Hebrard

Artist: Sacha Leray Exposition

Optic division

We design and create our optics starting from the effect we want to obtain and we design them around the source chosen for our fixtures. For this reason we are able to optimise the performance of the source and obtain effects of absolute precision. Everything is studied right down to the smallest detail.

It could appear that museums and shops need the same type of focused lighting but technically this is not the case.
Exhibitions spaces favour perfect, clean beams without any blurred edges and precise light directed at the works on display, with moderate luminance values of projects based on luminance contrast. Retail space on the other hand requires high luminance values and lighting effects with softer gradient tones to attract people's attention without creating sharp boundaries.

The Targetti Optic Division continuously develops optical systems that are able to favour the performance or precision of the effect according to actual needs. The quality of the lighting effect, available in different gradient tones is an essential feature of every one of our optical systems.

Indirect optics

Millimetre beam precision
for evocative effects

Makes it possible to obtain an extremely narrow light beam (up to 6°) that is precise and well defined even at great distances. It uses the principle of lighting technology where a parabolic reflector is lit by a light source that is turned backwards and completely hidden from view. The reflected light is highly collimated and creates a focused and defined effect with no falloff - a normal result of uncontrolled light – for maximum visual comfort.
Given its sophisticated shape this optic is only available in a Narrow Spot version.

Lenticular optics

Sophisticated geometries
for precise beams

These are most commonly used in museums because they make it possible to obtain precise and defined beams that frame works of art without “interfering with” the background. They are available from Narrow Spot right up to Flood openings. Unlike reflector optics lenticular optics control the light produced by the source and direct it inside the beam. The high quality materials used and sophisticated geometries ensure precision and high performance.

Hybrid optics

The ideal compromise between beam efficiency and definition

The light emission of these type of optics is the result of the combined use of reflectors and lenses. The reflector controls peripheral light while one or more lenses manage the central part of the beam which is usually uncontrolled. Cancelling “spurious” light is combined with flow recovery and an increase in intensity inside the beam. These optics are available for Spot and Flood emissions.

Reflector optics

Precise and enveloping light

These optics ensure excellent performance and are available with all beam openings (spot, flood, medium wide flood and wide flood). They allow for excellent light mixing with broad, soft tones between light and shade. They are particularly suitable when a homogeneous balance between luminance and a more neutral and less dramatic effect is required. The reflective aluminium or metallised polycarbonate they are made of ensure high optical efficiency.

Wall washer optics

Uniform light and contemporary atmosphere

These optics allow for completely uniform effects even on large wall surfaces. What makes them unique is the ability to direct the light right to the top of the surface and to its full height. The distance between different fixtures will provide uniformity along the entire length of the wall. This type of effect is ideal where uniformity is required in the entire space or where particular emphasis on a large work of art displayed on a wall is needed.The contrast with the rest of the space will emphasize the dramatic effect.



Grazing optics

Grazing lighting is a kind of light used to enhance vertical surfaces in a uniform way

The effect has a gradient tone that moves away from the source softly and is used for linear fixtures. Fixtures with this type of optic must be positioned near to the surface to be illuminated because the photometric solid is in reality a blade with maximum intensity at the emission point which then fades as it moves out. In the Targetti collection the Grazing optic was created thanks to an intuition by our optical department which studied a simple yet highly effective solution: a cylindrical lens positioned above the LED source along the entire length of the fixture. The result is a soft continuous light effect that “attaches” to the wall near the fixture without any unpleasant scorching and able to reach long distances thanks to its high performance.

DBS

Uniform light and contemporary atmosphere

Dynamic Beam Shaper (DBS) optical technology was created from the desire to give designers a sophisticated yet simple to use tool. Technology that we were the first to develop in the lighting sector together with Lens Vector – a leading American company in lens design - that makes it possible to vary the beam opening of fixtures via digital input without any mechanical system. With DBS we combined LED sources, collimated optics and lenses equipped with liquid crystal molecules that can be activated and oriented using an electric field thus creating a light diffusion process.

Liquid crystal materials are widely used in projectors and LC (LCD) displays. They are elongated molecules that are naturally aligned in the same direction. The DBS lens is composed of two glass substrates separated by spacers that are sealed to contain the liquid crystal materials in a kind of "sandwich". When an electric field is applied to the lens the molecules change direction and refocus the light that passes through the lens. Managing the electric field and the direction of the molecules it is possible to shape the light beam.

Dynamic Beam Shaper provides beam control from 15° to 55°, allowing designers to create scenes and manage lighting in different environments using Targetti Control by Casambi, without the use of mechanical systems, scales or replacement optics.

Using the Casambi app, available for IOS and Android, it is possible to dim the sources, set the desired beam opening and create dynamic scenes.
The same fixture controlled from any smart device provides infinite possibilities.




Off


On


TARGETTI

Today DBS technology is available for a wide range of products including for the OZ system, the smallest fixture in the collection to have a miniaturised optical system with dynamic beam shaping:

Projectors



ZENO Medium

CORO

LEDO

OZ 48V

Recessed

CCTLED Architectural
CCTLED Architectural Mini

*Online



CLOUD

*Online

Quality

The quality of a fixture is provided in part by objectively measurable and immediately comparable values such as performance or the type of luminous effect, as well as the result of choosing technical solutions that ensure safety and reliability over time.

The mechanical solutions we use are able to ensure the characteristics of our products remain unchanged over time and to make installation easier, especially outdoors.

TARGETTI

Waterblock

Waterblock solutions for outdoor products

To limit the risk of compromising watertight integrity we have created the Waterblock system. The system does not include the use of accessory elements it is rather a solution used in the production phase that by acting on the input power cable makes it possible to prevent water and humidity from reaching the inside of products.

When it comes to outdoor fixtures, above all inground ones a high IP rating is often not enough to provide a moisture barrier. In addition to the mechanical characteristics of fixtures external factors come into play like the state of the terrain or the installation method. If a connector is not well tightened or connections are not carried out to perfection humidity can reach the driver or the fixture through capillary action and irreversibly impair function.
To limit this risk we have designed an Waterblock system differentiated according to the type of product.



Waterblock Smart

This is a procedure applied during the assembly of products: the power cable is cut, unsheathed and re-welded and the ends are sealed using a special thermo-retractable adhesive sheath. The part of the cable fitted with the thermo-retractable sheath is then immersed into a special resin sleeve used for outdoor products.

This type of treatment is carried out on all products in the outdoor collection.

Waterblock Plus

In addition to resin coating the cable, the Waterblock Plus solution also involves completely resin coating the integrated driver. This prevents humidity from reaching the body of the fixture and impairing function.

Fixtures that use the Waterblock Plus systems are KEPLERO, MR.BO and FEBO EVO.

Treatments and resistance tests

We develop solutions that allow our products, especially recessed ones, to last even when they are installed in unfavourable conditions.



High resistance to corrosion is an essential characteristic of outdoor professional fixtures. Close proximity to the sea or exposure to corrosive agents highly increases the corrosion of materials in a significant way. All our die-cast fixtures are subjected to a series of treatments that improve resistance to corrosion.

Sample products are then tested using a "salt spray test" in a special chamber where salt spray is vapourised (5% NaCl) at a temperature of 35° C. This way the materials undergo the same (possible) changes they would if they were exposed to air for a long time. The test makes it possible to check the resistance of the materials to corrosion over time.

These treatments and tests allow us to be sure to provide quality and long-lasting products.

Cataphoresis

We wanted to increase the resistance of die-cast recessed fixtures to corrosion further to make them suitable for installation in “hostile” environments and up to 5 m from the sea. After anodising products undergo cataphoresis painting, one of the most ecological industrial painting systems. This treatment ensures elevated protection against chemical and environmental agents for a long time.

The procedure consists of emerging pieces which are connected to a negative pole with an electrical generator in a bath where some electrodes are connected to a positive pole. The electrical field and the electrochemical phenomena which result cause the deposition of at least µm25 of epoxy resin on the pieces which are then polymerised in an oven. Subsequently the treatment proceeds with finishing paint.

The product ranges that undergo Cataphoresis treatment are **KEPLERO** and **MERCURE**.

It is possible for other outdoor non-recessed products with die-cast components that need to be installed near to the sea to undergo cataphoresis treatment on request.

Digital

We have made designing and controlling light simple and within everyone’s reach so as to allow large-scale application of its incredible benefits. We did this by combining it with digital technology, not only to control it but also to change its shape in an extremely natural way.

How we control our fixtures

DALI
Fixtures are equipped with a driver that allows them to be connected to a BUS DALI global plant management system.

TARGETTI CONTROL
Fixtures are controlled via wireless or Bluetooth from a smartphone or a tablet without the need for any other hardware.

Dimm on board
Fixtures are dimmed using a switch inside the fixtures.

DMX
RGB and RGBW fixtures are controlled using a DMX protocol. Software and touch screen interfaces are available to manage and create static and dynamic lighting scenes.

Indoor

	DALI	TARGETTI CONTROL	DIMM ON BOARD	DMX
BEBOP	●	● with accessories		
CARTESIO	●	● with accessories		
CCTEvo	●	● with accessories		
CCTLED Pendant	●	● with accessories		
CCTLED Tube	●	● with accessories		
CORO	●	● with accessories		
COZY	●	● with accessories		
DIVA	●	● with accessories		
FORTYEIGHT	●	● with accessories		
GLOBO		● with accessories		
HALL	●	●		
ISO	●	● with accessories		
JEDI COMPACT IP40	●	● with accessories		
LABEL 230V	●	● with accessories		
LEDÒ	●	●	●	
LOGICO	●	● with accessories		
OMEGA	●	● with accessories		
OSIRIDE LED		● with accessories		
OZ	●			
PANTHEON		● with accessories		
PROFESSIONAL LED		● with accessories		
QUICKLED	●	● with accessories		
RAY	●	● with accessories		
STORE Gimbal	●	● with accessories		
THREESIXTY	●	● with accessories		

	DALI	TARGETTI CONTROL	DIMM ON BOARD	DMX
TPANEL	●	●		
VOLTA	●	● with accessories		
WASABI		● with accessories		
ZENO	●	●	●	
ZENO Estraibile	●	● with accessories		
ZENO Applique	●	● with accessories		

Outdoor

	DALI	TARGETTI CONTROL	DIMM ON BOARD	DMX
DART	●	● with accessories		
FEBO	●	● with accessories		
JEDI	●	● with accessories		
JEDI COMPACT	●	● with accessories		
JEDI RGBW				●
JUPITER	●	● with accessories		
JUPITER PRO	●	● with accessories		
KEPLERO	●	● with accessories		
KEPLERO RGBW				●
KEPLERO MINI RGBW				●
LED.Y RGB				●
MINIMERCURE RGB				●
MR. BO	●	● with accessories		
MR. SMITH	●	● with accessories		
MRS. SMITH	●	● with accessories		
SATURN	●	● with accessories		
ZEDGE	●	● with accessories		

Control systems

LMS Casambi

When we were the first in the lighting industry to choose Casambi as a partner to control light our aim was to have a simple, intuitive language within everyone's reach. As a result Targetti Control by Casambi was created to make it possible to control light via Bluetooth Low Energy without the use of any special cables.

This wireless technology is compatible with all modern smart devices: smartphones, tablets and even smartwatches. Targetti fixtures are equipped with a special interface that allows them to communicate with each other to create a remotely controllable "smart" network.

The advantages are manifold, first of all the possibility for users to interact with lighting – varying intensity, tone and shape in complete freedom and autonomy according to their needs – secondly the design approach known as Human Centric Lighting that places people at the centre of lighting projects.

Another advantage is the possibility to create different scenes according to the fruition needs of the space and energy saving.
Think of conference rooms, shops, offices and churches.

The Targetti Control application is designed that anyone can use it in an intuitive way regardless of their technical skills.

Once the fixture networks and desired scenes have been created it is possible to recall them using simple wireless buttons and wall switches as well as by using the app.
The technology is easy to implement depending on the complexity of the system and can be applied and adapted to even the most complex ones.

Transparency

Transparency in communicating data is an important commitment for us. In our certified internal laboratory we carry out measurements on our fixtures and we share the results transparently. This way we provide lighting designers with absolutely real and reliable values on performance in actual operating conditions.

All of our fixtures have identity cards showing their technical features and performance. Once products have been configured on the targetti.com website it is possible to download their data sheets that are now accompanied by new information such as:

A **Lifetime**

B **Tm30 with values expressed in R_f and R_g**



Ultimo aggiornamento: 30/10/2020 - Pagina 1 di 2

1T9030 | OZ Stand Alone Trimless
Proiettori da incasso a LED trimless

	2700K		H[m]	D[lm]	D[lx]@max[lx]
	Ra90			17°	48°
Fixture Power	5W	1	0.30	0.90	880
Source Flux	451lm	2	0.61	1.80	220
Fixture Flux	320lm	3	0.91	2.70	98
Efficacy	62lm/W	4	1.22	3.60	55
T51249	Imax=1951cd/klm	Imax	880cd	5	1.52	4.50	35

Le quote riportate sul disegno sono espresse in mm.

SORGENTE

LED emitter alta efficienza Ra90.

Potenza nominale	5,2W
Flusso nominale	451lm
Indice resa cromatica	90
Rf	87,6
Rg	103,9
CCT nominale	2700K
SDCM	2
Durata utile (L80/B10)	>60000h tq +25°C

CARATTERISTICHE ILLUMINOTECNICHE

Ottica ELT. Riflettore in policarbonato metallizzato, filtro olografico e frame in policarbonato nero. L'apparecchio è idoneo per l'installazione in ambienti di lavoro UGR<22 (EN12464-1).

Ottica	RIFLETTORE
Apertura di fascio	ELT
Rendimento ottico	71%
Flusso apparecchio	320lm
Efficienza luminosa	61lm/W
Sicurezza fotobiologica	Conforme al gruppo di rischio basso RG1

CARATTERISTICHE MECCANICHE

Corpo in pressofusione di alluminio anodizzato nero. Versione Small 3X.

Dimensioni	AxB=80x30mm
Peso	0,17Kg
Versione	3X
Grado di protezione H	IP20

CARATTERISTICHE ELETTRICHE

Driver remoto elettronico e DALI.

Potenza apparecchio	5W
Alimentazione	600mA
Classe di isolamento	CLASSE 3
Driver incluso	NO
Classe F	SI
Classe energetica	A++, A+, A

INSTALLAZIONE

Sistema di installazione trimless idoneo per pannelli in cartongesso di 13, 15 e 17mm.

NOTE

Sistema di controllo Casambi disponibile tramite accessorio (solo per prodotti con driver DALI). I valori relativi alla potenza dell'apparecchio non tengono conto dell'assorbimento del driver accessorio. Tale valore dipende dalla scelta del driver.

GARANZIA

5 anni.

A motivo dell'evoluzione tecnologica dei componenti elettronici i dati indicati sono soggetti ad aggiornamento e quindi deve essere richiesta conferma in fase d'ordine. Flusso luminoso e potenza elettrica presentano tolleranze di +/-10% rispetto al valore indicato. tq +25°C (CIE 121).

Si riserva la facoltà di apportare modifiche tecniche.

Targetti Sankey S.p.A.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
Fax: +39 055 3791266
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
05137660480
R.E.A: FI-275656

TARGETTI



Ultimo aggiornamento: 16/11/2020 - Pagina 1 di 2

1T7997EL | ZENO Medium
Proiettore professionale a LED con apertura di fascio fissa

	3000K		H[m]	D[lm]	Emax[lx]
	Ra97			9°	
Fixture Power	20W	1	0.15	44136	
Source Flux	2211lm	2	0.31	11034	
Fixture Flux	1308lm	3	0.46	4904	
Efficacy	65lm/W	4	0.62	2759	
T51219	Imax=19964cd/klm	Imax	44136cd	5	0.77	1765	

Le quote riportate sul disegno sono espresse in mm.

SORGENTE

LED Chip on Board alta efficienza Ra97, Ra84 su richiesta.

Potenza nominale	18W
Flusso nominale	2211lm
Indice resa cromatica	97
CCT nominale	3000K
SDCM	2

CARATTERISTICHE ILLUMINOTECNICHE

Versione NSP con ottica indiretta con modulo LED rivolto verso il riflettore, dissipazione con heat-pipe, riflettore parabolico in alluminio anodizzato ad alta riflettanza, schermo olografico in PMMA trasparente.

Ottica	INDIRETTA
Apertura di fascio	NSP
Rendimento ottico	0%
Flusso apparecchio	0lm
Efficienza luminosa	0lm/W
Sicurezza fotobiologica	Conforme al gruppo di rischio basso RG1

CARATTERISTICHE MECCANICHE

Corpo ottico realizzato in pressofusione di alluminio verniciato. Adattatore integrato. Orientabilità del corpo ottico da 0 a -90° sul piano verticale e di 360° su quello orizzontale, con possibilità di bloccaggio del puntamento.

Colore e finitura	Bianco gesso
Grado di protezione H	IP20

CARATTERISTICHE ELETTRICHE

Potenza apparecchio	20W
Alimentazione	220-240Vac 50/60Hz
Classe di isolamento	CLASSE 2
Tipo driver / Controllo	ELETTRONICO
Driver incluso	SI
Classe F	SI
Classe energetica	A++, A+, A

INSTALLAZIONE

Disponibile con accessori meccanici ed accessori ottici, installabili tramite anello di supporto.

NOTE

Disponibile su richiesta in versione 110-277Vac.

GARANZIA

5 anni.

A motivo dell'evoluzione tecnologica dei componenti elettronici i dati indicati sono soggetti ad aggiornamento e quindi deve essere richiesta conferma in fase d'ordine. Flusso luminoso e potenza elettrica presentano tolleranze di +/-10% rispetto al valore indicato. tq +25°C (CIE 121).

Si riserva la facoltà di apportare modifiche tecniche.

Targetti Sankey S.p.A.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
Fax: +39 055 3791266
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
05137660480
R.E.A: FI-275656

TARGETTI

Duration of LED sources

Unlike other light sources LED have a slow decrease in the flux emitted until they run out in a more or less long period based on two main factors:

- **The quality of the LED source**
- **Operating temperature of the source inside the fixture**



Targetti has always chosen the best sources on the market and works continuously to look for technical solutions aimed at optimising the "thermal management" of fixtures so that heat can dissipate in the correct way.
The life of LED sources is defined using the parameter "L" that indicates the flux decrease percentage referred to in operating hours (normally 50,000 hours), to which a "B" value is added usually between 10 and 50 which is an important indicator about the quality of the source because it indicates the percentage of LED sources that upon reaching the indicated hours do not maintain the declared characteristics of luminous flux. Having said that with the same number of hours the lower the B value the better the LED source.

All our LED sources guarantee the binomials L80/B10 for a lifespan of at least 50,000 hours (upon reaching 50,000 hours the luminous emission is ≥%80% for 10% of LED sources. For the majority of Targetti products (60%) the binomial L80/B10 is guaranteed for a lifespan of between 50,000 to 80,000 and for 40% a duration of more than 100,000 hours is even guaranteed.

On product data sheets there is detailed analysis of the flux trend of fixtures over time. Referring to this analysis lighting designers and end customers have credible information about the reliability and the duration of lighting systems.

Nominal average useful life	**30,000 h Tq+25°C**	**50,000 h Tq+25°C**	**80,000 h Tq+25°C**	**100,000 h Tq+25°C**
	Example L93/B10	**Example L90/B10**	**Example L85/B10**	**Example L80/B10**
	At 30,000 hours only 10% of fixtures have a flow of 93% of the initial output with Tq=25°C	At 50,000 hours 10% of fixtures have a flow of 90% of the initial output with Tq=25°C	At 80,000 hours 10% of fixtures have a flow of 85% of the initial output with Tq=25°C	At 100,000 hours 10% of fixtures have a flow of 80% of the initial output with Tq=25°C

Colour rendering: Ra and TM30



All our fixtures have “identity cards” that express colour rendering using both Ra as well as TM30. Knowing the colour rendering of a source is fundamental in lighting design because it expresses the ability of a source to faithfully reproduce the colours of a lit object. Almost all our fixtures can be equipped with Ra>90 LED.

Ra is the most common parameter to identify the colour quality of a source and Ra is a dimensionless index that varies from 0 to 100 that uses 8 colour samples (unsaturated colours) to determine the average Ra value. In recent years, a new parameter has also been introduced defined as TM30, that allows for a more complete reading of the way a source is able to reproduce colour.

TM30 extends the colour samples to 99 divided into 7 reference areas between saturated and “natural” colours and uses a balanced mix between an incandescent source and sunlight as a sample source. It is identified using two different parameters: an Rf fidelity index (Fidelity) and a Rg (Gamut) index range.

The datasheets of all our fixtures clearly and precisely indicate the colour rendering of LED sources using Ra, Rf and Rg (TM30) values.

Rf (Fidelity)

The Fidelity index indicates colour fidelity. It varies on a scale from 0 to 100 where 100 is perfect adherence to the sample source. A source with a score of less than 60 is not suitable for indoor use while a score of over 90 is ideal because the colorimetric characteristics of the source are similar to daylight.

Rg (Gamut)

The gamut index introduces the concept of saturation by evaluating the intensity of colours under a certain light (width of the colour range).
It varies on a scale from 60 to 140 where a gamut score of 100 indicates that the light source does not change the hue and the colour saturation that are reproduced in the same way as the sample source.

R>100 indicates an increase in colour saturation therefore they appear more intense than they really are.

R<100 indicates a decrease in saturation.

The shift is saturation is represented by a vector graphic.
The black circle represents the sample light, while the red “circle” is the light being tested.
The areas that extend beyond the black circle indicate that the colours are more intense compared to the sample, however those that remain inside represent colours that appear desaturated.





This colour shift graph makes it possible to read both parameters of TM30 in a single image.

Scouting

We choose the LED sources for our fixtures very carefully to ensure performance, long lifespan and excellent light quality. This does not mean only choosing one type of source for the entire collection but the ones that are considered the most suitable to equip particular fixtures or new optical systems while still maintaining the same shade of light for all our fixtures.

Galleria delle statue e delle Pitture degli Uffizi **Ligting Design** Massimo Iarussi **Photographer** Officine fotografiche
Florence, Italy

We choose the best LED sources on the market and we design our fixtures around the sources to enhance their performance.



LED
COB (chip on board)

This type provides maximum performance in terms of lumen, efficiency and density.
They are typically made of a matrix of small blue chips covered in phosphorous. The large number of chips used makes it possible to achieve excellent efficiency while maintaining low current in individual chips.

COLOUR TEMPERATURE
2700K • 3000K
3500K • 4000K

EFFICACY
100 • 150 lm/W

COLOUR RENDERING
Ra84 • Ra92 • Ra97

COLOUR CONSISTENCY
1,5 SDCM (Steps MacAdam)

LED
Mid power

Characterised by high efficiency and low unit power (< 1W). This makes it possible to create large light sources. It is typically used in linear fixtures and in fixtures that have large emission areas of diffused light in order to obtain excellent performance while maintaining lower wattage.

COLOUR TEMPERATURE
2700K • 3000K
3500K • 4000K

EFFICACY
100 • 150 lm/W

COLOUR RENDERING
Ra84 • Ra92 • Ra97

COLOUR CONSISTENCY
2 SDCM (Steps MacAdam)



LED
Emitter

Characterised by a very small light emitting area and high unit power (2-9W), it is typically used to make fixtures with predefined light beams.

COLOUR TEMPERATURE
2700K • 3000K
3500K • 4000K

EFFICACY
100 • 150 lm/W

COLOUR RENDERING
Ra84 • Ra92

COLOUR CONSISTENCY
3 SDCM (Steps MacAdam)
2 SDCM on request

LED COB
Ra84 2700K

SOURCE 2700K	
R_f	86
R_g	95
CCT (K)	2742
D_{uv}	0,0009
x	0,4587
y	0,4102
CIE R_a	82,9
CIE R9	6,5

COLOUR DISTORTION GRAPHIC





LED COB
Ra84 3000K

SOURCE 3000K	
R_f	85
R_g	96
CCT (K)	3050
D_{uv}	0,0021
x	0,4356
y	0,4050
CIE R_a	84,2
CIE R9	16,1

COLOUR DISTORTION GRAPHIC





LED COB
Ra84 4000K

SOURCE 4000K	
R_f	84
R_g	95
CCT (K)	4060
D_{uv}	0,0048
x	0,3823
y	0,3780
CIE R_a	85,2
CIE R9	20,9

COLOUR DISTORTION GRAPHIC





LED COB
Ra90 3000K

SOURCE 3000K	
R_f	94
R_g	100
CCT (K)	3005
D_{uv}	0,0024
x	0,4340
y	0,4032
CIE R_a	93,7
CIE R9	61,5

COLOUR DISTORTION GRAPHIC





LED COB
Ra90 4000K

SOURCE 4000K	
R_f	93
R_g	100
CCT (K)	4017
D_{uv}	0,0030
x	0,3821
y	0,3800
CIE R_a	93,5
CIE R9	66,4

COLOUR DISTORTION GRAPHIC





LED COB
Ra97 3000K

SOURCE 3000K	
R_f	96
R_g	100
CCT (K)	3031
D_{uv}	0,0012
x	0,4364
y	0,4036
CIE R_a	88,1
CIE R9	97,8

COLOUR DISTORTION GRAPHIC





LED COB
Ra97 4000K

SOURCE 4000K	
R_f	97
R_g	100
CCT (K)	4007
D_{uv}	0,0031
x	0,3849
y	0,3800
CIE R_a	98,4
CIE R9	99,2

COLOUR DISTORTION GRAPHIC





A

Spectral Power Distribution Comparison

Reference source

Targetti LED

Customization

We provide solutions that can give shape to the design ideas and lighting effects as imagined by our customers. Solutions can be from among the thousands of standards products in the catalogue but they can also need to be refined, customised and created.

Our origins are rooted in the tradition of Florentine craftsmanship. It is from here that we have inherited our Italian “know-how”, our natural ability to produce products tailor-made for projects.

Inside our R&D department a special team develops custom products for large projects. It is team work with customers to create custom-made products for each project.

Colours

Some product ranges in the Indoor and Outdoor collection can have a customised finish upon specific request from lighting designers.
The finishes available can be selected from those in the Targetti Colours range and from more than 200 standard RAL colours.

The Targetti Colours Range
Colours is a colour palette specially designed for lighting designers featuring neutral tones in matt or brilliant finish that allows lighting fixtures to become furnishing elements to all effects with their own precise identity.

RAL Colours
It is possible to request products with a custom finish by choosing from 90 matt colours for the indoor collection and 80 textured colours for outdoor products.



Download the RAL colours palette from the website and choose the most suitable colour for your project

targetti.com/it/Servizi/downloads

Highlights Indoor

CCTEvo



Fortyeight



Zeno



OZ System
OZ Stand Alone

Highlights Outdoor

Keplero

Zedge



Jupiter

Dart

Jedi Compact

Recessed

Indoor

New Upgrade

Linear recessed

72
LOGICO SA
Recessed
Opal/UGR/WW

72
LOGICO SA
Recessed+flange
Opal/UGR/WW

Recessed

88
CCTEvo
Downlight
UGR/VWF Ø 214mm

88
CCTEvo
Downlight
UGR/VWF Ø 160mm

88
CCTEvo
Downlight
UGR/VWF Ø 105mm

88
CCTEvo
Downlight
Ø 78mm



88
CCTEvo
Downlight
Ø 58mm

104
CCTEvo
Wall Washer
Ø 160mm

104
CCTEvo
Wall Washer
Ø 105mm

104
CCTEvo
Wall Washer
Ø 78mm

112
CCTEvo
Architectural
Ø 160mm

112
CCTEvo
Architectural
Ø 105mm

112
CCTEvo
Architectural
Ø 78mm



112
CCTEvo
Architectural
Ø 58mm

128
CCTEvo
Extractable
Ø 162mm



128
CCTEvo
Extractable
Ø 125mm

128
CCTEvo
Gimbal
Ø 125mm

128
CCT EVO
Gimbal
Ø 105mm



146
OZ Stand Alone
Recessed
Small 1x



146
OZ Stand Alone
Recessed
Small 3x

146
OZ Stand Alone
Recessed
Small 5x



146
OZ Stand Alone
Recessed
Large 1x

146
OZ Stand Alone
Incasso
Large 3x

146
OZ Stand Alone
Recessed
Large 5x



146
OZ Stand Alone
Trimless
Small 1x



146
OZ Stand Alone
Trimless
Small 3x

146
OZ Stand Alone
Trimless
Small 5x

146
OZ Stand Alone
Trimless
Large 1x

146
OZ Stand Alone
Trimless
Large 3x

146
OZ Stand Alone
Trimless
Large 5x

490
THREESIXTY
Ø384mm
Opal/UGR/Halo

490
THREESIXTY
Ø590mm
Opal/UGR/Halo

490
THREESIXTY
Ø870mm
Opal/UGR/Halo

490
THREESIXTY
Ø1150mm
Opal/UGR/Halo

166
T-PANEL
60x60

166
T-PANEL
30x120

170
STORE Gimbal

170
STORE Gimbal
Mini

186
ZENO Small
Extractable

192
COZY

196
BEBOP

200
QUICKLED

202
OTTO
Semi-Recessed

202
OTTO
Recessed
Extractable

LOGICO

Stand Alone
Recessed

GENERAL INFO
Modules of variable lengths with flange or trimless installation without visible frames.
Lenghts: 1135mm – 1695mm – 3377mm
Recessed with flange lenghts: 1146mm, 1706mm, 3386mm

LED
LED engine
From 2520lm to 21600lm
3000K – 4000K
Ra84-Ra90

PRODUCT EFFICACY
Up to 109lm/W

OPTICS
OPAL – UGR – WW

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Powder coated, extruded, calendered aluminium.

ON DEMAND

Tunable White

110-277Vac power supply

A versatile fixture available in three different lengths, each with Low- Power and High-Power lumen and different finishes and installation types.

Two recessed versions available. One version is already equipped with a flange and does not need an outer casing for installation; the other must be completed with a special trimless outer casing or flange. Both outer casings also allow for semi-recessed installation.

It is available with diffused light, UGR<19 controlled light ideal for lighting workplaces (EN-12464 - L65<3000 cd/m^2), or wall-washer for lighting large vertical surfaces.

There are also versions available for ceiling, wall or suspension installation.

Emergency versions available on request after checking feasibility.



Zonamerica
Montevideo, Uruguay

Architect Estudio Dovat Arquitectos
Lighting Design Estudio Hofstadter

Photographer Ferrés - Cánepa

Plus

Magnetic assembling
A magnet makes it possible to fix the light unit complete with a reflector to the housing, while the screen is attached with a simple “click”. No need to use tools. This particular fastening system means that the fixture can also be wall mounted.

Recessed version with or without a flange
The version without the flange allows for a trimless finish that totally disappears into the ceiling or for semi-recessed installations. Just accessorise the fixture with a special casing to be fitted flush into the ceiling.

Solutions available on request
Custom tailor made length modules and emergency modules.



Daiichi Sankyo
Roma, Italia

Architect Studio Unispace,
Salvatore Marinaro

Photographer Ramy Leon Lorenco

LOGICO



Stand Alone Recessed
L. 1135mm



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		27W	1	2.66	903
Source Flux		3480lm	2	5.33	226
Fixture Flux		2370lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS991	Imax=259cd/klm	Imax	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T5779EL**	**1T5780EL**
EL.	●	**1T5781EL**	**1T5782EL**
DALI	○	**1T5779DA**	**1T5780DA**
DALI	●	**1T5781DA**	**1T5782DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		54W	1	2.66	1785
Source Flux		6880lm	2	5.33	446
Fixture Flux		4685lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS996	Imax=259cd/klm	Imax	5	13.32	71

Driver	Colour	3000K	4000K
EL.	○	**1T5783EL**	**1T5784EL**
EL.	●	**1T5785EL**	**1T5786EL**
DALI	○	**1T5783DA**	**1T5784DA**
DALI	●	**1T5785DA**	**1T5786DA**

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		18W	1	1.51	1113
Source Flux		2520lm	2	3.02	278
Fixture Flux		1631lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS992	Imax=442cd/klm	Imax	5	7.54	45

Driver	Colour	3000K	4000K
EL.	○	**1T5787EL**	**1T5788EL**
EL.	●	**1T5789EL**	**1T5790EL**
DALI	○	**1T5787DA**	**1T5788DA**
DALI	●	**1T5789DA**	**1T5790DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		27W	1	2.28	2.55	2801
Source Flux		3480lm	2	4.56	5.10	700
Fixture Flux		2739lm	3	6.84	7.64	311
Efficacy		101lm/W	4	9.12	10.19	175
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	112

Driver	Colour	3000K	4000K
EL.	○	**1T5791EL**	**1T5792EL**
EL.	●	**1T5793EL**	**1T5794EL**
DALI	○	**1T5791DA**	**1T5792DA**
DALI	●	**1T5793DA**	**1T5794DA**

LED / 48W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		54W	1	2.28	2.55	5537
Source Flux		6880lm	2	4.56	5.10	1384
Fixture Flux		5415lm	3	6.84	7.64	615
Efficacy		100lm/W	4	9.12	10.19	346
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	221

Driver	Colour	3000K	4000K
EL.	○	**1T5795EL**	**1T5796EL**
EL.	●	**1T5797EL**	**1T5798EL**
DALI	○	**1T5795DA**	**1T5796DA**
DALI	●	**1T5797DA**	**1T5798DA**

LOGICO



Stand Alone Recessed
L. 1695mm



LED / 36W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		40W	1	2.66	1354
Source Flux		5220lm	2	5.33	338
Fixture Flux		3555lm	3	7.99	150
Efficacy		89lm/W	4	10.65	85
TS991	Imax=259cd/klm	Imax	5	13.32	54

Driver	Colour	3000K	4000K
EL.	○	**1T5799EL**	**1T5800EL**
EL.	●	**1T5801EL**	**1T5802EL**
DALI	○	**1T5799DA**	**1T5800DA**
DALI	●	**1T5801DA**	**1T5802DA**

LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2677
Source Flux		10320lm	2	5.33	669
Fixture Flux		7028lm	3	7.99	297
Efficacy		87lm/W	4	10.65	167
TS996	Imax=259cd/klm	Imax	5	13.32	107

Driver	Colour	3000K	4000K
EL.	○	**1T5803EL**	**1T5804EL**
EL.	●	**1T5805EL**	**1T5806EL**
DALI	○	**1T5803DA**	**1T5804DA**
DALI	●	**1T5805DA**	**1T5806DA**

LED / 24W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		27W	1	1.51	1669
Source Flux		3780lm	2	3.02	417
Fixture Flux		2447lm	3	4.52	185
Efficacy		91lm/W	4	6.03	104
TS992	Imax=442cd/klm	Imax	5	7.54	67

Driver	Colour	3000K	4000K
EL.	○	**1T5807EL**	**1T5808EL**
EL.	●	**1T5809EL**	**1T5810EL**
DALI	○	**1T5807DA**	**1T5808DA**
DALI	●	**1T5809DA**	**1T5810DA**

LED / 36W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		40W	1	2.28	2.55	4201
Source Flux		5220lm	2	4.56	5.10	1050
Fixture Flux		4108lm	3	6.84	7.64	467
Efficacy		103lm/W	4	9.12	10.19	263
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	168

Driver	Colour	3000K	4000K
EL.	○	**1T5811EL**	**1T5812EL**
EL.	●	**1T5813EL**	**1T5814EL**
DALI	○	**1T5811DA**	**1T5812DA**
DALI	●	**1T5813DA**	**1T5814DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		81W	1	2.28	2.55	8305
Source Flux		10320lm	2	4.56	5.10	2076
Fixture Flux		8122lm	3	6.84	7.64	923
Efficacy		100lm/W	4	9.12	10.19	519
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	332

Driver	Colour	3000K	4000K
EL.	○	**1T5815EL**	**1T5816EL**
EL.	●	**1T5817EL**	**1T5818EL**
DALI	○	**1T5815DA**	**1T5816DA**
DALI	●	**1T5817DA**	**1T5818DA**



Stand Alone Recessed
L. 3377mm



LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2708
Source Flux		10440lm	2	5.33	677
Fixture Flux		7110lm	3	7.99	301
Efficacy		88lm/W	4	10.65	169
TS991	Imax=259cd/klm	Imax	5	13.32	108

Driver	Colour	3000K	4000K
EL.	○	**1T5819EL**	**1T5820EL**
EL.	●	**1T5821EL**	**1T5822EL**
DALI	○	**1T5819DA**	**1T5820DA**
DALI	●	**1T5821DA**	**1T5822DA**

LED / 144W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		163W	1	2.66	5354
Source Flux		20640lm	2	5.33	1338
Fixture Flux		14056lm	3	7.99	595
Efficacy		86lm/W	4	10.65	335
TS996	Imax=259cd/klm	Imax	5	13.32	214

Driver	Colour	3000K	4000K
EL.	○	**1T5823EL**	**1T5824EL**
EL.	●	**1T5825EL**	**1T5826EL**
DALI	○	**1T5823DA**	**1T5824DA**
DALI	●	**1T5825DA**	**1T5826DA**

LED / 48W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		54W	1	1.51	3338
Source Flux		7560lm	2	3.02	834
Fixture Flux		4894lm	3	4.52	371
Efficacy		91lm/W	4	6.03	209
TS992	Imax=442cd/klm	Imax	5	7.54	134

Driver	Colour	3000K	4000K
EL.	○	**1T5827EL**	**1T5828EL**
EL.	●	**1T5829EL**	**1T5830EL**
DALI	○	**1T5827DA**	**1T5828DA**
DALI	●	**1T5829DA**	**1T5830DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		81W	1	2.28	2.55	8402
Source Flux		10440lm	2	4.56	5.10	2101
Fixture Flux		8216lm	3	6.84	7.64	934
Efficacy		101lm/W	4	9.12	10.19	525
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	336

Driver	Colour	3000K	4000K
EL.	○	**1T5831EL**	**1T5832EL**
EL.	●	**1T5833EL**	**1T5834EL**
DALI	○	**1T5831DA**	**1T5832DA**
DALI	●	**1T5833DA**	**1T5834DA**

LED / 144W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		163W	1	2.28	2.55	16611
Source Flux		20640lm	2	4.56	5.10	4153
Fixture Flux		16244lm	3	6.84	7.64	1846
Efficacy		100lm/W	4	9.12	10.19	1038
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	664

Driver	Colour	3000K	4000K
EL.	○	**1T5835EL**	**1T5836EL**
EL.	●	**1T5837EL**	**1T5838EL**
DALI	○	**1T5835DA**	**1T5836DA**
DALI	●	**1T5837DA**	**1T5838DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

To be completed with a special trimless or flange outer casing for recessed or semi-recessed installation.

Related codes

Insertion Box



Kg	Cutout hole	L	Colour	Code
3.2	80x1150	1171	◯	**1T5918**
3.8	80x1710	1731	◯	**1T5919**
7.5	80x3390	3416	◯	**1T5920**

Outer casing for recessed and semi-recessed installation with a flange.



Kg	Cutout hole	L	Code
3.2	80x1150	1172	**1T6012**
3.8	80x1710	1732	**1T6013**
7.5	80x3390	3414	**1T6014**

Outer casing for recessed and semi-recessed trimless installation.

Accessories

Screen



Code
1T6502

Accessory designed to improve the visual comfort of the Wall Washer version.
To be installed on a standard reflector.
Made of matte black painted aluminium.
280mm in length; to be ordered in the following quantities for every fixture length: 2 for the 562mm version, 4 for the 1122/1135/1146mm versions, 6 for the 1682/1695/1706mm versions and 12 for the 3364/3377/3386mm versions.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

LOGICO



Stand Alone Recessed with flange L. 1146mm



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	27W		1	2.66	903
Source Flux	3480lm		2	5.33	226
Fixture Flux	2370lm		3	7.99	100
Efficacy	88lm/W		4	10.65	56
TS991	Imax=259cd/klm	Imax	5	13.32	36

Driver	Colour	3000K	4000K
EL.	◯	**1T5431EL**	**1T5432EL**
DALI	◯	**1T5431DA**	**1T5432DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	54W		1	2.66	1785
Source Flux	6880lm		2	5.33	446
Fixture Flux	4685lm		3	7.99	198
Efficacy	87lm/W		4	10.65	112
TS996	Imax=259cd/klm	Imax	5	13.32	71

Driver	Colour	3000K	4000K
EL.	◯	**1T5433EL**	**1T5434EL**
DALI	◯	**1T5433DA**	**1T5434DA**

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	18W		1	1.51	1113
Source Flux	2520lm		2	3.02	278
Fixture Flux	1631lm		3	4.52	124
Efficacy	91lm/W		4	6.03	70
TS992	Imax=442cd/klm	Imax	5	7.54	45

Driver	Colour	3000K	4000K
EL.	◯	**1T5435EL**	**1T5436EL**
DALI	◯	**1T5435DA**	**1T5436DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	27W		1	2.28	2.55	2801
Source Flux	3480lm		2	4.56	5.10	700
Fixture Flux	2739lm		3	6.84	7.64	311
Efficacy	101lm/W		4	9.12	10.19	175
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	112

Driver	Colour	3000K	4000K
EL.	◯	**1T5437EL**	**1T5438EL**
DALI	◯	**1T5437DA**	**1T5438DA**

LED / 48W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	54W		1	2.28	2.55	5537
Source Flux	6880lm		2	4.56	5.10	1384
Fixture Flux	5415lm		3	6.84	7.64	615
Efficacy	100lm/W		4	9.12	10.19	346
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	221

Driver	Colour	3000K	4000K
EL.	◯	**1T5439EL**	**1T5440EL**
DALI	◯	**1T5439DA**	**1T5440DA**

LOGICO



Stand Alone Recessed with flange L. 1706mm



LED / 36W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	40W		1	2.66	1354
Source Flux	5220lm		2	5.33	338
Fixture Flux	3555lm		3	7.99	150
Efficacy	89lm/W		4	10.65	85
TS991	Imax=259cd/klm	Imax	5	13.32	54

Driver	Colour	3000K	4000K
EL.	◯	**1T5441EL**	**1T5442EL**
DALI	◯	**1T5441DA**	**1T5442DA**

LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	81W		1	2.66	2677
Source Flux	10320lm		2	5.33	669
Fixture Flux	7028lm		3	7.99	297
Efficacy	87lm/W		4	10.65	167
TS996	Imax=259cd/klm	Imax	5	13.32	107

Driver	Colour	3000K	4000K
EL.	◯	**1T5443EL**	**1T5444EL**
DALI	◯	**1T5443DA**	**1T5444DA**

LED / 24W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	27W		1	1.51	1669
Source Flux	3780lm		2	3.02	417
Fixture Flux	2447lm		3	4.52	185
Efficacy	91lm/W		4	6.03	104
TS992	Imax=442cd/klm	Imax	5	7.54	67

Driver	Colour	3000K	4000K
EL.	◯	**1T5445EL**	**1T5446EL**
DALI	◯	**1T5445DA**	**1T5446DA**

LED / 36W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	40W		1	2.28	2.55	4201
Source Flux	5220lm		2	4.56	5.10	1050
Fixture Flux	4108lm		3	6.84	7.64	467
Efficacy	103lm/W		4	9.12	10.19	263
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	168

Driver	Colour	3000K	4000K
EL.	◯	**1T5447EL**	**1T5448EL**
DALI	◯	**1T5447DA**	**1T5448DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	81W		1	2.28	2.55	8305
Source Flux	10320lm		2	4.56	5.10	2076
Fixture Flux	8122lm		3	6.84	7.64	923
Efficacy	100lm/W		4	9.12	10.19	519
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	332

Driver	Colour	3000K	4000K
EL.	◯	**1T5449EL**	**1T5450EL**
DALI	◯	**1T5449DA**	**1T5450DA**

LOGICO



Stand Alone Recessed with flange L. 3386mm



LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2708
Source Flux		10440lm	2	5.33	677
Fixture Flux		7110lm	3	7.99	301
Efficacy		88lm/W	4	10.65	169
TS991	Imax=259cd/klm	Imax	5	13.32	108

Driver	Colour	3000K	4000K
EL.	◯	**1T5451EL**	**1T5452EL**
DALI	◯	**1T5451DA**	**1T5452DA**

LED / 144W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		163W	1	2.66	5354
Source Flux		20640lm	2	5.33	1338
Fixture Flux		14056lm	3	7.99	595
Efficacy		86lm/W	4	10.65	335
TS996	Imax=259cd/klm	Imax	5	13.32	214

Driver	Colour	3000K	4000K
EL.	◯	**1T5453EL**	**1T5454EL**
DALI	◯	**1T5453DA**	**1T5454DA**

LED / 48W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		54W	1	1.51	3338
Source Flux		7560lm	2	3.02	834
Fixture Flux		4894lm	3	4.52	371
Efficacy		91lm/W	4	6.03	209
TS992	Imax=442cd/klm	Imax	5	7.54	134

Driver	Colour	3000K	4000K
EL.	◯	**1T5455EL**	**1T5456EL**
DALI	◯	**1T5455DA**	**1T5456DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		81W	1	2.28	2.55	8402
Source Flux		10440lm	2	4.56	5.10	2101
Fixture Flux		8216lm	3	6.84	7.64	934
Efficacy		101lm/W	4	9.12	10.19	525
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	336

Driver	Colour	3000K	4000K
EL.	◯	**1T5457EL**	**1T5458EL**
DALI	◯	**1T5457DA**	**1T5458DA**

LED / 144W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		163W	1	2.28	2.55	16611
Source Flux		20640lm	2	4.56	5.10	4153
Fixture Flux		16244lm	3	6.84	7.64	1846
Efficacy		100lm/W	4	9.12	10.19	1038
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	664

Driver	Colour	3000K	4000K
EL.	◯	**1T5459EL**	**1T5460EL**
DALI	◯	**1T5459DA**	**1T5460DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Accessories

Screen



	Code
	1T6502

Accessory designed to improve the visual comfort of the Wall Washer version.
To be installed on a standard reflector.
Made of matte black painted aluminium.
280mm in length; to be ordered in the following quantities for every fixture length: 2 for the 562mm version, 4 for the 1122/1135/1146mm versions, 6 for the 1682/1695/1706mm versions and 12 for the 3364/3377/3386mm versions.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo

Family

CCTEvo is the latest range of recessed LED fixtures. A wide range in terms of the breadth and depth of the product family with five different types of product on offer, each available in different sizes and luminous distributions. The CCTEvo range stands out for its design with pure and essential shapes for a coordinated and recognisable offer.

All fixtures are designed with a family feeling that is common to the latest additions to the Targetti collection- in particular for the series of Label track projectors – for aesthetic continuity and quality of light with recessed and track lighting solutions. CCTEvo is the evolution of CCTLED, the iconic, historic range of Targetti fixtures from whom it takes the baton and puts its legacy to good use. An evolution in terms of extending the range and performance that makes CCTEvo a complete suite of professional lighting tools available for our partners. All fixtures in the CCTLED range can still be ordered.

The technical specifications and order codes can be found at **targetti.com**.

mm	Ø214	Ø160	Ø125	Ø105	Ø78	Ø58
CCTEvo Downlight Trim / Trimless						
CCTEvo Architectural Trim / Trimless						
CCTEvo Wall Washer Trim / Trimless						
CCTEvo Extractable						
CCTEvo Gimbal						

CCTEvo DOWNLIGHT

A range of recessed fixtures characterised by minimalist shapes, a depth of range, excellent performance and high efficiency. Available in five different sizes with a coordinated design and with different lumen packages, the CCTEvo Downlight range comes in a double version, trim (with a ring) or trimless, for complete integration into the architecture.

Source Flux
From 1098lm to 6478lm

5
Sizes

214mm 160mm 105mm 78mm 58mm

4
Available optics

FL | WFL (UGR) | WFL | VWFL

Colour temperature

2700 K 3000 K 3500 K 4000 K

Tunable white

2700 K 5000 K

LED source
White LED Ra90
Tunable White Ra90

Trim Trimless

CCTEvo ARCHITECTURAL

A range of recessed projectors for professional lighting in the CCTEvo range. Real professional tools for projected light characterised by application flexibility, high performance and quality optical systems. Available in four different sizes with different lumen packages and four luminous emissions, CCTEvo Architectural comes in a double version, trim (with a ring) or trimless, for complete integration into the architecture.

Source Flux
From 528lm to 7313lm

4
Sizes

160mm 105mm 78mm 58mm

5
Available optics

NSP | SP | FL | MWFL | WFL

Colour temperature

2700 K 3000 K 3500 K 4000 K

LED source
White LED Ra90

Trim Trimless

CCTEvo WALL WASHER

A range of recessed fixtures for uniform lighting of large surfaces. Equipped with an innovative wall washer optical system it provides very clean, wide and uniform beams with excellent light diffusion from very close to the floor.

Source Flux
From 1156lm to 4049lm

3
Sizes

160mm 105mm 78mm

1
Available optic

WW

Colour temperature

2700 K 3000 K 3500 K 4000 K

LED source
White LED Ra90

Trim Trimless

CCTEVO EXTRACTABLE

A range of professional performance extractable recessed projectors with extensive flexibility. The projector can be set back completely for maximum formal simplicity or extracted up to 75°.

Source Flux
From 516lm to 6354lm

2
Sizes

162mm 125mm

5
Available optics

NSP SP FL MWFL WFL

Colour temperature

2700 K 3000 K 3500 K 4000 K

LED source
White LED Ra90

CCTEvo GIMBAL

The simplest product in the range, CCTEvo Gimbal is a recessed fixture in two different sizes – ø125mm and ø105mm - designed to meet the particular lighting needs of retail applications.

Source Flux
From 1266lm to 3180lm

2
Sizes

125mm 105mm

3
Available optics

SP FL MWFL

Colour temperature

2700 K 3000 K 3500 K 4000 K

LED source
White LED Ra90

CCTEvo DOWNLIGHT

GENERAL INFO
Recessed LED Downlight in a trim or trimless version. ø214mm ø160mm ø105mm ø78mm ø58mm

LED
High efficiency LED Chip on Board with Ra90
LED Chip on Board Tunable White Ra90 for ø160mm ø105mm.
From 1098lm to 6478lm
2700K – 3000K – 3500K - 4000K
From 2700K to 5000K for Tunable white version

PRODUCT EFFICACY
Up to 120lm/W

OPTICS
NSP - SP - FL - MWFL - WFL (UGR) - VWFL

POWER SUPPLY
Electronic – DALI Casambi – DALI8 for Tunable White versions.
Casambi control system available using a dedicated accessory (only for DALI version products)

MATERIAL
Die-cast aluminium dissipator Silicone seal to make it watertight and dust-proof (IP54).
Available in a trim version with an integrated ring or trimless with a supporting element for installation and smoothing in plasterboard.
ø214mm ø160mm ø105mm - Reflector in a highly reflective metallised thermoplastic material.
ø78mm ø58mm – Cut-off cover in painted black or white thermoplastic material.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

A range of recessed fixtures characterised by minimalist shapes, a depth of range, excellent performance and high efficiency. Available in five different sizes with a coordinated design and with different lumen packages, the CCTEvo Downlight range comes in a double version, trim (with a ring) or trimless, for complete integration into the architecture.

The IP54 protection rating makes CCTEvo Downlight suitable for installation in humid environments for aesthetic continuity between indoor and outdoor spaces. The optical systems available are suitable for installation in work environments UGR<19 (EN12464-1) L65<1000 cd/m^2.

Sizes ø160mm and ø105mm are also available with Tunable White technology.

		Ø 214mm	Ø 160mm	Ø 105mm	Ø 78mm	Ø 58mm
LED	Flux (lm)	3393-6478	2011-4419	1200-2160	1492-1577	1098-1161
	Power	23-49W	13-30W	8,4-15W	12W	8,2W
OPTICS						
FL	Reflector				•	•
WFL (UGR)	Reflector	•	•	•		
WFL	Reflector					•
VWFL	Reflector	•	•	•		



Plus

Ø214mm

Ø160mm

Ø105mm

Ø78mm

Ø58mm

A complete and coordinated range.

Five sizes, four colour temperatures, four optical solutions and different lumen packages for all sizes.
All solutions are available in a trimless version and with a ring and have the same family feeling and colour consistency in terms of colour quality. A complete range particularly suitable for lighting work and retail environments where reliability, high efficiency and quality of light are fundamental requirements.

Tunable White Versions.

Tunable White technology, available for sizes ø 160mm and ø 105mm, makes it possible to remotely modulate the colour temperature of the fixtures from 2700K to 5000K with continuity. The high quality of the COB selected for the Tunable White version of CCTEvo Downlight makes it possible to select and dynamically modulate colour temperature while still guaranteeing high standards in terms of light and colour quality.

Integration, comfort and versatility.

Developed to provide the best performance and maximum integration into the lighting environment, CCTEvo Downlight fixtures have different characteristics: in the smaller sizes - ø 78mm and ø 58mm – the black or white cover hides the source from sight for maximum visual comfort and total integration; in the larger sizes the reflector is mirrored to optimise the performance of the optical system."

Coordinated aesthetics for indoor and outdoor.

The IP54 protection rating makes it possible to install CCTEvo even in humid environments while ensuring aesthetic consistency in lighting projects that involve indoor and outdoor spaces.



IP54 V.O.

Ø	214mm	160mm	105mm	78mm	58mm
Ring	○●	○●	○●	○●	○●
Reflector/Cover	◌◌	◌◌	◌◌	○●	○●

○ Plaster White ● Deep Black ◌ Reflective Aluminium



Plus

Trim and Trimless.
CCTEvo Downlight is supplied equipped with a ring (for the trim version) or with a special element for trimless installation. Installation is quick and easy. Even in the trimless version the fixture remains perfectly inspectable even after installation.

Pure shapes.
A simple, minimalist design with pure and essential shapes. In the trim version the ring integrated into the fixture has been made even thinner to allow for total integration into the environment.

CCTEvo Downlight

214 WFL (UGR)



LED / 23W / REFLECTOR / WFL (UGR)



3000K		H(m)	D(m)	Emax(lx)
Ra90			62°	
Fixture Power	26W	1	1.20	2950
Source Flux	3530lm	2	2.41	738
Fixture Flux	2876lm	3	3.61	328
Efficacy	111lm/W	4	4.82	184
Imax	3036cd	5	6.02	118

TS1375 Imax=860cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8218EL**	**1T8221EL**	**1T8224EL**	**1T8227EL**
EL.	●	**1T8242EL**	**1T8245EL**	**1T8248EL**	**1T8251EL**
DALI	○	**1T8218DA**	**1T8221DA**	**1T8224DA**	**1T8227DA**
DALI	●	**1T8242DA**	**1T8245DA**	**1T8248DA**	**1T8251DA**

LED / 36W / REFLECTOR / WFL (UGR)



3000K		H(m)	D(m)	Emax(lx)
Ra90			62°	
Fixture Power	40W	1	1.20	4179
Source Flux	5000lm	2	2.41	1045
Fixture Flux	4074lm	3	3.61	464
Efficacy	102lm/W	4	4.82	261
Imax	4300cd	5	6.02	167

TS1376 Imax=860cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8219EL**	**1T8222EL**	**1T8225EL**	**1T8228EL**
EL.	●	**1T8243EL**	**1T8246EL**	**1T8249EL**	**1T8252EL**
DALI	○	**1T8219DA**	**1T8222DA**	**1T8225DA**	**1T8228DA**
DALI	●	**1T8243DA**	**1T8246DA**	**1T8249DA**	**1T8252DA**

LED / 49W / REFLECTOR / WFL (UGR)



3000K		H(m)	D(m)	Emax(lx)
Ra90			62°	
Fixture Power	54W	1	1.20	5333
Source Flux	6381lm	2	2.41	1333
Fixture Flux	5199lm	3	3.61	593
Efficacy	96lm/W	4	4.82	333
Imax	5488cd	5	6.02	213

TS1377 Imax=860cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8220EL**	**1T8223EL**	**1T8226EL**	**1T8229EL**
EL.	●	**1T8244EL**	**1T8247EL**	**1T8250EL**	**1T8253EL**
DALI	○	**1T8220DA**	**1T8223DA**	**1T8226DA**	**1T8229DA**
DALI	●	**1T8244DA**	**1T8247DA**	**1T8250DA**	**1T8253DA**

214 VWFL



LED / 23W / REFLECTOR / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			88°	
Fixture Power	26W	1	1.92	1714
Source Flux	3530lm	2	3.85	428
Fixture Flux	2958lm	3	5.77	190
Efficacy	114lm/W	4	7.69	107
Imax	1714cd	5	9.61	69

TS1372 Imax=485cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8230EL**	**1T8233EL**	**1T8236EL**	**1T8239EL**
EL.	●	**1T8254EL**	**1T8257EL**	**1T8260EL**	**1T8263EL**
DALI	○	**1T8230DA**	**1T8233DA**	**1T8236DA**	**1T8239DA**
DALI	●	**1T8254DA**	**1T8257DA**	**1T8260DA**	**1T8263DA**

CCTEvo Downlight

LED / 36W / REFLECTOR / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			88°	
Fixture Power		40W	1	1.92	2427
Source Flux		5000lm	2	3.85	607
Fixture Flux		4190lm	3	5.77	270
Efficacy		105lm/W	4	7.69	152
Imax		2427cd	5	9.61	97

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8231EL**	**1T8234EL**	**1T8237EL**	**1T8240EL**
EL.	◐	**1T8255EL**	**1T8258EL**	**1T8261EL**	**1T8264EL**
DALI	○	**1T8231DA**	**1T8234DA**	**1T8237DA**	**1T8240DA**
DALI	◐	**1T8255DA**	**1T8258DA**	**1T8261DA**	**1T8264DA**

LED / 49W / REFLECTOR / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			88°	
Fixture Power		54W	1	1.92	3098
Source Flux		6381lm	2	3.85	774
Fixture Flux		5348lm	3	5.77	344
Efficacy		99lm/W	4	7.69	194
Imax		3098cd	5	9.61	124

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8232EL**	**1T8235EL**	**1T8238EL**	**1T8241EL**
EL.	◐	**1T8256EL**	**1T8259EL**	**1T8262EL**	**1T8265EL**
DALI	○	**1T8232DA**	**1T8235DA**	**1T8238DA**	**1T8241DA**
DALI	◐	**1T8256DA**	**1T8259DA**	**1T8262DA**	**1T8265DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Downlight

160 WFL (UGR)



LED / 13W / REFLECTOR / WFL (UGR)

	3000K		H(m)	D(m)	Emax(lx)
	Ra90			63°	
Fixture Power		15W	1	1.23	1569
Source Flux		2092lm	2	2.45	392
Fixture Flux		1563lm	3	3.68	174
Efficacy		106lm/W	4	4.91	98
TS1258	Imax=767cd/klm	Imax	1604cd	5	6.13	63

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8290EL**	**1T8293EL**	**1T8296EL**	**1T8299EL**
EL.	●	**1T8326EL**	**1T8329EL**	**1T8332EL**	**1T8335EL**
DALI	○	**1T8290DA**	**1T8293DA**	**1T8296DA**	**1T8299DA**
DALI	●	**1T8326DA**	**1T8329DA**	**1T8332DA**	**1T8335DA**

LED / 20W / REFLECTOR / WFL (UGR)

	3000K		H(m)	D(m)	Emax(lx)
	Ra90			63°	
Fixture Power		23W	1	1.23	2279
Source Flux		3038lm	2	2.45	570
Fixture Flux		2269lm	3	3.68	253
Efficacy		100lm/W	4	4.91	142
TS1258	Imax=767cd/klm	Imax	2329cd	5	6.13	91

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8291EL**	**1T8294EL**	**1T8297EL**	**1T8300EL**
EL.	●	**1T8327EL**	**1T8330EL**	**1T8333EL**	**1T8336EL**
DALI	○	**1T8291DA**	**1T8294DA**	**1T8297DA**	**1T8300DA**
DALI	●	**1T8327DA**	**1T8330DA**	**1T8333DA**	**1T8336DA**

LED / 30W / REFLECTOR / WFL (UGR)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			63°	
Fixture Power		34W	1	1.23	3265
Source Flux		4353lm	2	2.45	816
Fixture Flux		3251lm	3	3.68	363
Efficacy		96lm/W	4	4.91	204
TS1258	Imax=767cd/klm	Imax	3337cd	5	6.13	131

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8292EL**	**1T8295EL**	**1T8298EL**	**1T8301EL**
EL.	●	**1T8328EL**	**1T8331EL**	**1T8334EL**	**1T8337EL**
DALI	○	**1T8292DA**	**1T8295DA**	**1T8298DA**	**1T8301DA**
DALI	●	**1T8328DA**	**1T8331DA**	**1T8334DA**	**1T8337DA**

LED CTC / 30W / REFLECTOR / WFL (UGR)



	2700K		H(m)	D(m)	Emax(lx)
	Ra90			63°	
Fixture Power		33W	1	1.22	2420
Source Flux		3016lm	2	2.44	605
Fixture Flux		2364lm	3	3.66	269
Efficacy		72lm/W	4	4.88	151
TS1388	Imax=808cd/klm	Imax	2436cd	5	6.10	97

Driver	Colour	2700-5000K
DT8	○	**1T9500DA8**
DT8	●	**1T9503DA8**



	3850K		H(m)	D(m)	Emax(lx)
	Ra90			63°	
Fixture Power		33W	1	1.22	2584
Source Flux		3207lm	2	2.44	646
Fixture Flux		2514lm	3	3.66	287
Efficacy		76lm/W	4	4.88	162
TS1389	Imax=808cd/klm	Imax	2591cd	5	6.10	103



	5000K		H(m)	D(m)	Emax(lx)
	Ra90			63°	
Fixture Power		33W	1	1.22	2732
Source Flux		3398lm	2	2.44	683
Fixture Flux		2664lm	3	3.66	304
Efficacy		81lm/W	4	4.89	171
TS1387	Imax=807cd/klm	Imax	2742cd	5	6.11	109

CCTEvo Downlight

160 VWFL



LED / 13W / REFLECTOR / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			89°	
Fixture Power	15W	1	1.98	990
Source Flux	2092lm	2	3.95	247
Fixture Flux	1741lm	3	5.93	110
Efficacy	118lm/W	4	7.90	62
TS1259 Imax=473cd/klm	Imax	990cd	5	9.88	40

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8302EL**	**1T8305EL**	**1T8308EL**	**1T8311EL**
EL.	●	**1T8338EL**	**1T8341EL**	**1T8344EL**	**1T8347EL**
DALI	○	**1T8302DA**	**1T8305DA**	**1T8308DA**	**1T8311DA**
DALI	●	**1T8338DA**	**1T8341DA**	**1T8344DA**	**1T8347DA**

LED / 20W / REFLECTOR / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			89°	
Fixture Power	23W	1	1.98	1438
Source Flux	3038lm	2	3.95	359
Fixture Flux	2529lm	3	5.93	160
Efficacy	111lm/W	4	7.90	90
TS1259 Imax=473cd/klm	Imax	1438cd	5	9.88	58

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8303EL**	**1T8306EL**	**1T8309EL**	**1T8312EL**
EL.	●	**1T8339EL**	**1T8342EL**	**1T8345EL**	**1T8348EL**
DALI	○	**1T8303DA**	**1T8306DA**	**1T8309DA**	**1T8312DA**
DALI	●	**1T8339DA**	**1T8342DA**	**1T8345DA**	**1T8348DA**

LED / 30W / REFLECTOR / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			89°	
Fixture Power	34W	1	1.98	2060
Source Flux	4353lm	2	3.95	515
Fixture Flux	3623lm	3	5.93	229
Efficacy	108lm/W	4	7.90	129
TS1259 Imax=473cd/klm	Imax	2060cd	5	9.88	82

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8304EL**	**1T8307EL**	**1T8310EL**	**1T8313EL**
EL.	●	**1T8340EL**	**1T8343EL**	**1T8346EL**	**1T8349EL**
DALI	○	**1T8304DA**	**1T8307DA**	**1T8310DA**	**1T8313DA**
DALI	●	**1T8340DA**	**1T8343DA**	**1T8346DA**	**1T8349DA**

LED CTC / 30W / REFLECTOR / VWFL



2700K		H(m)	D(m)	Emax(lx)
Ra90			90°	
Fixture Power	33W	1	2.01	1198
Source Flux	3016lm	2	4.02	300
Fixture Flux	2193lm	3	6.02	133
Efficacy	66lm/W	4	8.03	75
TS1391 Imax=397cd/klm	Imax	1198cd	5	10.04	48

Driver	Colour	2700-5000K
DT8	○	**1T9501DA8**
DT8	●	**1T9504DA8**



3850K		H(m)	D(m)	Emax(lx)
Ra90			90°	
Fixture Power	33W	1	2.01	1273
Source Flux	3207lm	2	4.02	318
Fixture Flux	2332lm	3	6.03	141
Efficacy	71lm/W	4	8.04	80
TS1392 Imax=397cd/klm	Imax	1273cd	5	10.05	51



5000K		H(m)	D(m)	Emax(lx)
Ra90			90°	
Fixture Power	33W	1	2.01	1348
Source Flux	3398lm	2	4.02	337
Fixture Flux	2470lm	3	6.03	150
Efficacy	75lm/W	4	8.04	84
TS1390 Imax=397cd/klm	Imax	1348cd	5	10.05	54

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

CCTEvo Downlight

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

	Code
	1T5349DA8

Wireless control unit for DALI8 fixtures.
It generates a local DALI8 bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352DA8

IP20 Extender for wireless control of DALI8 fixtures.
It generates a local DALI8 bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Downlight

105 WFL (UGR)



LED / 8,4W / REFLECTOR / WFL (UGR)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			61°	
Fixture Power		10W	1	1.19	1032
Source Flux		1247lm	2	2.37	258
Fixture Flux		986lm	3	3.56	115
Efficacy		103lm/W	4	4.75	65
TS1270	Imax=835cd/klm	Imax	1042cd	5	5.93	41

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8398EL**	**1T8400EL**	**1T8402EL**	**1T8404EL**
EL.	●	**1T8422EL**	**1T8424EL**	**1T8426EL**	**1T8428EL**
DALI	○	**1T8398DA**	**1T8400DA**	**1T8402DA**	**1T8404DA**
DALI	●	**1T8422DA**	**1T8424DA**	**1T8426DA**	**1T8428DA**

LED / 15W / REFLECTOR / WFL (UGR)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			61°	
Fixture Power		17W	1	1.19	1760
Source Flux		2127lm	2	2.37	440
Fixture Flux		1681lm	3	3.56	196
Efficacy		99lm/W	4	4.75	110
TS1271	Imax=835cd/klm	Imax	1777cd	5	5.93	70

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8399EL**	**1T8401EL**	**1T8403EL**	**1T8405EL**
EL.	●	**1T8423EL**	**1T8425EL**	**1T8427EL**	**1T8429EL**
DALI	○	**1T8399DA**	**1T8401DA**	**1T8403DA**	**1T8405DA**
DALI	●	**1T8423DA**	**1T8425DA**	**1T8427DA**	**1T8429DA**

LED CTC / 15W / REFLECTOR / WFL (UGR)



	2700K		H(m)	D(m)	Emax(lx)
	Ra90			62°	
Fixture Power		19W	1	1.20	1013
Source Flux		1420lm	2	2.39	253
Fixture Flux		1027lm	3	3.59	113
Efficacy		54lm/W	4	4.79	63
TS1382	Imax=747cd/klm	Imax	1061cd	5	5.98	41

Driver	Colour	2700-5000K
DT8	○	**1T9506DA8**
DT8	●	**1T9509DA8**



	3850K		H(m)	D(m)	Emax(lx)
	Ra90			61°	
Fixture Power		19W	1	1.18	1113
Source Flux		1497lm	2	2.35	278
Fixture Flux		1082lm	3	3.53	124
Efficacy		57lm/W	4	4.70	70
TS1383	Imax=770cd/klm	Imax	1153cd	5	5.88	45



	5000K		H(m)	D(m)	Emax(lx)
	Ra90			61°	
Fixture Power		19W	1	1.18	1169
Source Flux		1573lm	2	2.35	292
Fixture Flux		1137lm	3	3.53	130
Efficacy		60lm/W	4	4.70	73
TS1381	Imax=770cd/klm	Imax	1211cd	5	5.88	47

105 VWFL



LED / 8,4W / REFLECTOR / VWFL

	3000K		H(m)	D(m)	Emax(lx)
	Ra90			87°	
Fixture Power		10W	1	1.89	589
Source Flux		1247lm	2	3.78	147
Fixture Flux		1064lm	3	5.66	65
Efficacy		111lm/W	4	7.55	37
TS1272	Imax=472cd/klm	Imax	589cd	5	9.44	24

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8406EL**	**1T8408EL**	**1T8410EL**	**1T8412EL**
EL.	●	**1T8430EL**	**1T8432EL**	**1T8434EL**	**1T8436EL**
DALI	○	**1T8406DA**	**1T8408DA**	**1T8410DA**	**1T8412DA**
DALI	●	**1T8430DA**	**1T8432DA**	**1T8434DA**	**1T8436DA**

CCTEvo Downlight

LED / 15W / REFLECTOR / VWFL

3000K		H(m)	D(m)	Emax(lx)
Ra90			87°	
Fixture Power	17W	1	1.89	1004
Source Flux	2127lm	2	3.78	251
Fixture Flux	1815lm	3	5.66	112
Efficacy	107lm/W	4	7.55	63
TS1273 Imax=472cd/klm	Imax 1004cd	5	9.44	40

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8407EL**	**1T8409EL**	**1T8411EL**	**1T8413EL**
EL.	◐	**1T8431EL**	**1T8433EL**	**1T8435EL**	**1T8437EL**
DALI	○	**1T8407DA**	**1T8409DA**	**1T8411DA**	**1T8413DA**
DALI	◐	**1T8431DA**	**1T8433DA**	**1T8435DA**	**1T8437DA**

LED CTC / 15W / REFLECTOR / VWFL



2700K		H(m)	D(m)	Emax(lx)
Ra90			88°	
Fixture Power	19W	1	1.93	630
Source Flux	1420lm	2	3.86	157
Fixture Flux	1150lm	3	5.78	70
Efficacy	61lm/W	4	7.71	39
TS1385 Imax=444cd/klm	Imax 630cd	5	9.64	25



3850K		H(m)	D(m)	Emax(lx)
Ra90			88°	
Fixture Power	19W	1	1.93	663
Source Flux	1497lm	2	3.86	166
Fixture Flux	1213lm	3	5.79	74
Efficacy	64lm/W	4	7.72	41
TS1386 Imax=443cd/klm	Imax 663cd	5	9.65	27



5000K		H(m)	D(m)	Emax(lx)
Ra90			88°	
Fixture Power	19W	1	1.93	698
Source Flux	1573lm	2	3.85	174
Fixture Flux	1274lm	3	5.78	78
Efficacy	67lm/W	4	7.71	44
TS1384 Imax=444cd/klm	Imax 698cd	5	9.63	28

Driver	Colour	2700-5000K
DT8	○	**1T9507DA8**
DT8	◐	**1T9510DA8**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Emergency Kit



Code
1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Downlight

	Code
	1T5349DA8

Wireless control unit for DALI8 fixtures.
It generates a local DALI8 bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352DA8

IP20 Extender for wireless control of DALI8 fixtures.
It generates a local DALI8 bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Downlight

78



LED / 12W / REFLECTOR / FL (29°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			29°	
	Fixture Power	13W	1	0.52	3558
	Source Flux	1553lm	2	1.03	890
	Fixture Flux	1179lm	3	1.55	395
	Efficacy	91lm/W	4	2.06	222
TS1265	Imax=2291cd/klm	Imax	5	2.58	142

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8542EL**	**1T8543EL**	**1T8544EL**	**1T8545EL**
EL.	●	**1T8554EL**	**1T8555EL**	**1T8556EL**	**1T8557EL**
DALI	○	**1T8542DA**	**1T8543DA**	**1T8544DA**	**1T8545DA**
DALI	●	**1T8554DA**	**1T8555DA**	**1T8556DA**	**1T8557DA**

LED / 12W / REFLECTOR / FL (39°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			39°	
	Fixture Power	13W	1	0.71	2654
	Source Flux	1553lm	2	1.42	664
	Fixture Flux	1278lm	3	2.14	295
	Efficacy	98lm/W	4	2.85	166
TS1266	Imax=1709cd/klm	Imax	5	3.56	106

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8546EL**	**1T8547EL**	**1T8548EL**	**1T8549EL**
EL.	●	**1T8558EL**	**1T8559EL**	**1T8560EL**	**1T8561EL**
DALI	○	**1T8546DA**	**1T8547DA**	**1T8548DA**	**1T8549DA**
DALI	●	**1T8558DA**	**1T8559DA**	**1T8560DA**	**1T8561DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Downlight

58



LED / 8,2W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			38°	
	Fixture Power	10W	1	0.69	1946
	Source Flux	1143lm	2	1.39	487
	Fixture Flux	836lm	3	2.08	216
	Efficacy	86lm/W	4	2.77	122
	Imax	1946cd	5	3.46	78

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8266EL**	**1T8267EL**	**1T8268EL**	**1T8269EL**
EL.	●	**1T8274EL**	**1T8275EL**	**1T8276EL**	**1T8277EL**
DALI	○	**1T8266DA**	**1T8267DA**	**1T8268DA**	**1T8269DA**
DALI	●	**1T8274DA**	**1T8275DA**	**1T8276DA**	**1T8277DA**

LED / 8,2W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			55°	
	Fixture Power	10W	1	1.04	1115
	Source Flux	1143lm	2	2.09	279
	Fixture Flux	864lm	3	3.13	124
	Efficacy	89lm/W	4	4.18	70
	Imax	1125cd	5	5.22	45

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8270EL**	**1T8271EL**	**1T8272EL**	**1T8273EL**
EL.	●	**1T8278EL**	**1T8279EL**	**1T8280EL**	**1T8281EL**
DALI	○	**1T8270DA**	**1T8271DA**	**1T8272DA**	**1T8273DA**
DALI	●	**1T8278DA**	**1T8279DA**	**1T8280DA**	**1T8281DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

CCTEvo Downlight

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo WALL WASHER

GENERAL INFO
Recessed LED downlight in a trim or trimless version.
Ø160mm Ø105mm Ø78mm

LED
High efficiency LED Chip on Board with Ra90
From 1156lm to 4049lm
2700K – 3000K – 3500K - 4000K

PRODUCT EFFICACY
Up to 87lm/W

OPTICS
WW

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Die-cast aluminium dissipator. Reflector in a reflective metallised thermoplastic material with high luminous efficiency and visual comfort.
Silicone seal to make it watertight and dust proof.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

A range of recessed fixtures for uniform lighting of large vertical surfaces. Equipped with an innovative wall washer optical system it provides very clean, wide and uniform beams with excellent light diffusion from very close to the floor. Available in three different sizes (ø160mm, ø105mm and ø78mm), in a trim (with a ring) and a trimless version in two different finishes with a carefully studied design for maximum integration into the architecture.

The 160mm and 105mm diameter versions are available with Tunable White technology.

		Ø 160mm	Ø 105mm	Ø 78mm
LED	Flux (lm)	1908-4049	1156-2035	1496-1581
	Power	14-32W	8,5-15W	12W
OPTICS				
WW	Reflector	•	•	•



Plus



Maximum integration

The design of CCTEvo Wall Washer was carefully studied to ensure the best lighting performance and total formal simplicity for perfect integration into the environment.

Ideal for lighting large vertical surfaces.

The Wall Washer optical system was designed for particular vertical light distribution. On installation with the right ratio of 1 to 3 between the distance from the wall and the height of the same a uniform effect can be obtained thanks to a clean and well controlled beam that avoids light dispersion where not necessary. The optic also guarantees accurate luminance control towards the observer.





Illuminance [lx]

CCTEvo Wall Washer

160



LED / 14W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			42°	77°	
Fixture Power	16W	1	0.86	1.70	1087
Source Flux	1983lm	2	1.73	3.40	272
Fixture Flux	1374lm	3	2.59	5.11	121
Efficacy	86lm/W	4	3.46	6.81	68
TS1396 Imax=633cd/klm	Imax 1256cd	5	4.32	8.51	43

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8314EL**	**1T8317EL**	**1T8320EL**	**1T8323EL**
EL.	●	**1T8350EL**	**1T8353EL**	**1T8356EL**	**1T8359EL**
DALI	○	**1T8314DA**	**1T8317DA**	**1T8320DA**	**1T8323DA**
DALI	●	**1T8350DA**	**1T8353DA**	**1T8356DA**	**1T8359DA**

LED / 21W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			42°	77°	
Fixture Power	24W	1	0.86	1.70	1549
Source Flux	2827lm	2	1.73	3.40	387
Fixture Flux	1958lm	3	2.59	5.11	172
Efficacy	82lm/W	4	3.46	6.81	97
TS1397 Imax=633cd/klm	Imax 1790cd	5	4.32	8.51	62

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8315EL**	**1T8318EL**	**1T8321EL**	**1T8324EL**
EL.	●	**1T8351EL**	**1T8354EL**	**1T8357EL**	**1T8360EL**
DALI	○	**1T8315DA**	**1T8318DA**	**1T8321DA**	**1T8324DA**
DALI	●	**1T8351DA**	**1T8354DA**	**1T8357DA**	**1T8360DA**

LED / 32W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			42°	77°	
Fixture Power	36W	1	0.86	1.70	2157
Source Flux	3935lm	2	1.73	3.40	539
Fixture Flux	2726lm	3	2.59	5.11	240
Efficacy	76lm/W	4	3.46	6.81	135
TS1398 Imax=633cd/klm	Imax 2492cd	5	4.32	8.51	86

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8316EL**	**1T8319EL**	**1T8322EL**	**1T8325EL**
EL.	●	**1T8352EL**	**1T8355EL**	**1T8358EL**	**1T8361EL**
DALI	○	**1T8316DA**	**1T8319DA**	**1T8322DA**	**1T8325DA**
DALI	●	**1T8352DA**	**1T8355DA**	**1T8358DA**	**1T8361DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

CCTEvo Wall Washer

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Wall Washer

105



LED / 8,5W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			43°	77°	
Fixture Power		10W	1	0.86	1.68	563
Source Flux		1203lm	2	1.72	3.36	141
Fixture Flux		680lm	3	2.58	5.05	63
Efficacy		70lm/W	4	3.44	6.73	35
Imax		644cd	5	4.30	8.41	23

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8414EL**	**1T8416EL**	**1T8418EL**	**1T8420EL**
EL.	●	**1T8438EL**	**1T8440EL**	**1T8442EL**	**1T8444EL**
DALI	○	**1T8414DA**	**1T8416DA**	**1T8418DA**	**1T8420DA**
DALI	●	**1T8438DA**	**1T8440DA**	**1T8442DA**	**1T8444DA**

LED / 15W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			43°	76°	
Fixture Power		18W	1	0.86	1.66	944
Source Flux		2003lm	2	1.72	3.31	236
Fixture Flux		1133lm	3	2.58	4.97	105
Efficacy		63lm/W	4	3.44	6.62	59
Imax		1082cd	5	4.30	8.28	38

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8415EL**	**1T8417EL**	**1T8419EL**	**1T8421EL**
EL.	●	**1T8439EL**	**1T8441EL**	**1T8443EL**	**1T8445EL**
DALI	○	**1T8415DA**	**1T8417DA**	**1T8419DA**	**1T8421DA**
DALI	●	**1T8439DA**	**1T8441DA**	**1T8443DA**	**1T8445DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Wall Washer

78



LED / 12W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			42°	74°	
Fixture Power	13W	1	0.83	1.58	841
Source Flux	1557lm	2	1.65	3.16	210
Fixture Flux	943lm	3	2.48	4.74	93
Efficacy	73lm/W	4	3.31	6.32	53
Imax	964cd	5	4.13	7.90	34

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8550EL**	**1T8551EL**	**1T8552EL**	**1T8553EL**
EL.	●	**1T8562EL**	**1T8563EL**	**1T8564EL**	**1T8565EL**
DALI	○	**1T8550DA**	**1T8551DA**	**1T8552DA**	**1T8553DA**
DALI	●	**1T8562DA**	**1T8563DA**	**1T8564DA**	**1T8565DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo ARCHITECTURAL

GENERAL INFO
Adjustable recessed
LED projector
in a trim or trimless version
ø160mm ø105mm ø78mm
ø58mm

LED
High efficiency LED Chip
on Board with Ra90
From 528lm to 7313lm
2700K – 3000K – 3500K
- 4000K

PRODUCT EFFICACY
Up to 103lm/W

OPTICS
NSP - SP - FL - MWFL -
WFL

POWER SUPPLY
Electronic – DALI
Casambi control system
available using a dedicated
accessory (only for DALI
version products).

MATERIAL
ø160mm and ø105mm
- Painted black or white
die-cast aluminium body
and dissipator.
ø78mm - Die-cast
aluminium body and
dissipator.
ø58mm - Black or white
moulded plastic optic
holders and die-cast
aluminium dissipator.
Available in a trim version
with an integrated ring or
trimless with a supporting
element for installation and
smoothing in plasterboard.

ON DEMAND

Easy Custom Colour

110-277Vac
power supply

A range of recessed projectors in the CCTEvo range. Available in four different sizes with different lumen packages and four luminous emissions, CCTEvo Architectural comes in a double version, trim (with a ring) or trimless, for complete integration into the architecture.

It is fitted with a special VCR – Virtual Center Rotation – aiming system that makes it possible to adjust the projector up to 40° on the vertical plane and 358° on the horizontal plane with a mechanical blocking system. The ø58 version allows the optical body to be adjusted on the vertical plane only (maximum 30 °).

It is also possible to choose from different colour combinations for wide design flexibility.

		Ø 160mm	Ø 105mm	Ø 78mm	Ø 58mm
LED	Flux (lm)	611-7313	528-2227	849-1577	816-1158
	Power	7,1-64W	5,7-19W	9,3-12W	8,2-9,5W
OPTICS					
NSP	Reflector	•	•		
	Lens	•	•		
SP	Reflector	•	•	•	•
	Lens	•	•		
FL	Reflector	•	•	•	•
	Lens	•	•		
MWFL	Reflector	•	•	•	
	Lens	•	•		
WFL	Reflector	•			

Plus

A real recessed projector

The heart of CCTEvo Architectural is a really versatile and professional performance projector. Four different sizes, two optical systems, four different emissions and different lumen packages for all sizes. A really complete range.

Family feeling

CCTEvo Architectural is designed to coordinate with projectors in the Label range with the aim of creating aesthetic and performance continuity between products with different installation types (track projectors, adjustable recesses projectors and recessed extractable projectors).





Maximum project flexibility
The VCR – Virtual Center Rotation – aiming system makes it possible to adjust the optical unit up to 40° on the vertical plane and 355° on the horizontal plane. The mechanical blocking system and the graduated ring make it possible to replicate the aim with ease. The ø 58mm version can only be adjusted on the vertical plane (maximum 30°)"

Plus



Optic system
with lense

Optic system
with reflector

Two optical systems

CCTEvo Architectural is an extremely flexible tool. The different optical systems available allow for NSP, SP, FL and MWFL beam openings. Sizes ø 160mm and ø 105mm provide the possibility to choose from two different optical systems – with a reflector for soft effects with low visual contrast and lenses for more defined beams – extending the choice of solutions on offer further.

A

B

C

Each project with its own finish

To provide maximum integration with all environments the CCTEvo Architectural ring, cover and projector are available in black or white in different colour combinations for maximum flexibility.

	A	B	C
Projector	●	○	○
Cover	●	●	○
Ring	●	○	○

○ Plaster White ● Deep Black



CCTEvo Architectural

160



LED / 12W / REFLECTOR / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			10°	
Fixture Power		14W	1	0.18	15651
Source Flux		1082lm	2	0.35	3913
Fixture Flux		852lm	3	0.53	1739
Efficacy		61lm/W	4	0.70	978
TS1371	Imax=14464cd/klm	Imax	15651cd	5	0.88	626

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8578EL**	**1T8579EL**	**1T8580EL**	**1T8581EL**
EL.	●	**1T8618EL**	**1T8619EL**	**1T8620EL**	**1T8621EL**
EL.	◑	**1T8370EL**	**1T8371EL**	**1T8372EL**	**1T8373EL**
DALI	○	**1T8578DA**	**1T8579DA**	**1T8580DA**	**1T8581DA**
DALI	●	**1T8618DA**	**1T8619DA**	**1T8620DA**	**1T8621DA**
DALI	◑	**1T8370DA**	**1T8371DA**	**1T8372DA**	**1T8373DA**

LED / 25W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power		28W	1	0.28	15617
Source Flux		2953lm	2	0.56	3904
Fixture Flux		1963lm	3	0.84	1735
Efficacy		70lm/W	4	1.11	976
TS1274	Imax=5288cd/klm	Imax	15617cd	5	1.39	625

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8582EL**	**1T8585EL**	**1T8588EL**	**1T8591EL**
EL.	●	**1T8622EL**	**1T8625EL**	**1T8628EL**	**1T8631EL**
EL.	◑	**1T8374EL**	**1T8377EL**	**1T8380EL**	**1T8383EL**
DALI	○	**1T8582DA**	**1T8585DA**	**1T8588DA**	**1T8591DA**
DALI	●	**1T8622DA**	**1T8625DA**	**1T8628DA**	**1T8631DA**
DALI	◑	**1T8374DA**	**1T8377DA**	**1T8380DA**	**1T8383DA**

LED / 31W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			21°	
Fixture Power		35W	1	0.37	15506
Source Flux		4028lm	2	0.75	3876
Fixture Flux		2868lm	3	1.12	1723
Efficacy		82lm/W	4	1.50	969
TS1277	Imax=3849cd/klm	Imax	15506cd	5	1.87	620

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8583EL**	**1T8586EL**	**1T8589EL**	**1T8592EL**
EL.	●	**1T8623EL**	**1T8626EL**	**1T8629EL**	**1T8632EL**
EL.	◑	**1T8375EL**	**1T8378EL**	**1T8381EL**	**1T8384EL**
DALI	○	**1T8583DA**	**1T8586DA**	**1T8589DA**	**1T8592DA**
DALI	●	**1T8623DA**	**1T8626DA**	**1T8629DA**	**1T8632DA**
DALI	◑	**1T8375DA**	**1T8378DA**	**1T8381DA**	**1T8384DA**

LED / 25W / REFLECTOR / FL (27°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		28W	1	0.49	7497
Source Flux		2953lm	2	0.98	1874
Fixture Flux		2034lm	3	1.47	833
Efficacy		73lm/W	4	1.96	469
TS1275	Imax=2539cd/klm	Imax	7497cd	5	2.45	300

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8594EL**	**1T8597EL**	**1T8600EL**	**1T8603EL**
EL.	●	**1T8634EL**	**1T8637EL**	**1T8640EL**	**1T8643EL**
EL.	◑	**1T8386EL**	**1T8389EL**	**1T8392EL**	**1T8395EL**
DALI	○	**1T8594DA**	**1T8597DA**	**1T8600DA**	**1T8603DA**
DALI	●	**1T8634DA**	**1T8637DA**	**1T8640DA**	**1T8643DA**
DALI	◑	**1T8386DA**	**1T8389DA**	**1T8392DA**	**1T8395DA**

LED / 31W / REFLECTOR / FL (33°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			33°	
Fixture Power		35W	1	0.59	8753
Source Flux		4028lm	2	1.18	2188
Fixture Flux		2969lm	3	1.77	973
Efficacy		85lm/W	4	2.36	547
TS1278	Imax=2173cd/klm	Imax	8753cd	5	2.95	350

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8595EL**	**1T8598EL**	**1T8601EL**	**1T8604EL**
EL.	●	**1T8635EL**	**1T8638EL**	**1T8641EL**	**1T8644EL**
EL.	◑	**1T8387EL**	**1T8390EL**	**1T8393EL**	**1T8396EL**
DALI	○	**1T8595DA**	**1T8598DA**	**1T8601DA**	**1T8604DA**
DALI	●	**1T8635DA**	**1T8638DA**	**1T8641DA**	**1T8644DA**
DALI	◑	**1T8387DA**	**1T8390DA**	**1T8393DA**	**1T8396DA**

CCTEvo Architectural

LED / 25W / REFLECTOR / FL (40°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			40°	
Fixture Power		28W	1	0.73	4734
Source Flux		2953lm	2	1.46	1184
Fixture Flux		2072lm	3	2.19	526
Efficacy		74lm/W	4	2.93	296
TS1276	Imax=1603cd/klm	Imax	4734cd	5	3.66	189

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8606EL**	**1T8609EL**	**1T8612EL**	**1T8615EL**
EL.	●	**1T8646EL**	**1T8649EL**	**1T8652EL**	**1T8655EL**
EL.	◑	**1T8494EL**	**1T8497EL**	**1T8500EL**	**1T8503EL**
DALI	○	**1T8606DA**	**1T8609DA**	**1T8612DA**	**1T8615DA**
DALI	●	**1T8646DA**	**1T8649DA**	**1T8652DA**	**1T8655DA**
DALI	◑	**1T8494DA**	**1T8497DA**	**1T8500DA**	**1T8503DA**

LED / 31W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			55°	
Fixture Power		35W	1	1.04	3834
Source Flux		4028lm	2	2.08	959
Fixture Flux		3037lm	3	3.13	426
Efficacy		87lm/W	4	4.17	240
TS1279	Imax=975cd/klm	Imax	3926cd	5	5.21	153

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8607EL**	**1T8610EL**	**1T8613EL**	**1T8616EL**
EL.	●	**1T8647EL**	**1T8650EL**	**1T8653EL**	**1T8656EL**
EL.	◑	**1T8495EL**	**1T8498EL**	**1T8501EL**	**1T8504EL**
DALI	○	**1T8607DA**	**1T8610DA**	**1T8613DA**	**1T8616DA**
DALI	●	**1T8647DA**	**1T8650DA**	**1T8653DA**	**1T8656DA**
DALI	◑	**1T8495DA**	**1T8498DA**	**1T8501DA**	**1T8504DA**

LED / 7,1W / LENS / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			10°	
Fixture Power		9W	1	0.18	12902
Source Flux		646lm	2	0.37	3225
Fixture Flux		588lm	3	0.55	1434
Efficacy		68lm/W	4	0.73	806
TS1370	Imax=19971cd/klm	Imax	12902cd	5	0.92	516

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8506EL**	**1T8507EL**	**1T8508EL**	**1T8509EL**
EL.	●	**1T8570EL**	**1T8571EL**	**1T8572EL**	**1T8573EL**
EL.	◑	**1T8666EL**	**1T8667EL**	**1T8668EL**	**1T8669EL**
DALI	○	**1T8506DA**	**1T8507DA**	**1T8508DA**	**1T8509DA**
DALI	●	**1T8570DA**	**1T8571DA**	**1T8572DA**	**1T8573DA**
DALI	◑	**1T8666DA**	**1T8667DA**	**1T8668DA**	**1T8669DA**

LED / 25W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			17°	
Fixture Power		28W	1	0.30	22179
Source Flux		2927lm	2	0.60	5545
Fixture Flux		2441lm	3	0.90	2464
Efficacy		87lm/W	4	1.19	1386
TS1267	Imax=7577cd/klm	Imax	22179cd	5	1.49	887

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8510EL**	**1T8511EL**	**1T8512EL**	**1T8513EL**
EL.	●	**1T8574EL**	**1T8575EL**	**1T8576EL**	**1T8577EL**
EL.	◑	**1T8670EL**	**1T8671EL**	**1T8672EL**	**1T8673EL**
DALI	○	**1T8510DA**	**1T8511DA**	**1T8512DA**	**1T8513DA**
DALI	●	**1T8574DA**	**1T8575DA**	**1T8576DA**	**1T8577DA**
DALI	◑	**1T8670DA**	**1T8671DA**	**1T8672DA**	**1T8673DA**

LED / 25W / LENS / FL (26°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		28W	1	0.47	9678
Source Flux		2927lm	2	0.94	2420
Fixture Flux		2386lm	3	1.41	1075
Efficacy		85lm/W	4	1.88	605
TS1268	Imax=3307cd/klm	Imax	9678cd	5	2.35	387

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8514EL**	**1T8515EL**	**1T8516EL**	**1T8517EL**
EL.	●	**1T8658EL**	**1T8659EL**	**1T8660EL**	**1T8661EL**
EL.	◑	**1T8674EL**	**1T8675EL**	**1T8676EL**	**1T8677EL**
DALI	○	**1T8514DA**	**1T8515DA**	**1T8516DA**	**1T8517DA**
DALI	●	**1T8658DA**	**1T8659DA**	**1T8660DA**	**1T8661DA**
DALI	◑	**1T8674DA**	**1T8675DA**	**1T8676DA**	**1T8677DA**

LED / 25W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power		28W	1	0.75	4648
Source Flux		2927lm	2	1.49	1162
Fixture Flux		2277lm	3	2.24	516
Efficacy		81lm/W	4	2.99	291
TS1269	Imax=1622cd/klm	Imax	4749cd	5	3.73	186

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8566EL**	**1T8567EL**	**1T8568EL**	**1T8569EL**
EL.	●	**1T8662EL**	**1T8663EL**	**1T8664EL**	**1T8665EL**
EL.	◑	**1T8678EL**	**1T8679EL**	**1T8680EL**	**1T8681EL**
DALI	○	**1T8566DA**	**1T8567DA**	**1T8568DA**	**1T8569DA**
DALI	●	**1T8662DA**	**1T8663DA**	**1T8664DA**	**1T8665DA**
DALI	◑	**1T8678DA**	**1T8679DA**	**1T8680DA**	**1T8681DA**

CCTEvo Architectural

160



LED / 64W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			22°	
	Fixture Power	72W	1	0.39	21884
	Source Flux	7203lm	2	0.77	5471
	Fixture Flux	4866lm	3	1.16	2432
	Efficacy	68lm/W	4	1.55	1368
	Imax	21884cd	5	1.94	875

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8584EL**	**1T8587EL**	**1T8590EL**	**1T8593EL**
EL.	●	**1T8624EL**	**1T8627EL**	**1T8630EL**	**1T8633EL**
EL.	◑	**1T8376EL**	**1T8379EL**	**1T8382EL**	**1T8385EL**
DALI	○	**1T8584DA**	**1T8587DA**	**1T8590DA**	**1T8593DA**
DALI	●	**1T8624DA**	**1T8627DA**	**1T8630DA**	**1T8633DA**
DALI	◑	**1T8376DA**	**1T8379DA**	**1T8382DA**	**1T8385DA**

LED / 64W / REFLECTOR / FL (33°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			33°	
	Fixture Power	72W	1	0.60	13782
	Source Flux	7203lm	2	1.20	3445
	Fixture Flux	5225lm	3	1.80	1531
	Efficacy	73lm/W	4	2.40	861
	Imax	13782cd	5	3.00	551

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8596EL**	**1T8599EL**	**1T8602EL**	**1T8605EL**
EL.	●	**1T8636EL**	**1T8639EL**	**1T8642EL**	**1T8645EL**
EL.	◑	**1T8388EL**	**1T8391EL**	**1T8394EL**	**1T8397EL**
DALI	○	**1T8596DA**	**1T8599DA**	**1T8602DA**	**1T8605DA**
DALI	●	**1T8636DA**	**1T8639DA**	**1T8642DA**	**1T8645DA**
DALI	◑	**1T8388DA**	**1T8391DA**	**1T8394DA**	**1T8397DA**

LED / 64W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			47°	
	Fixture Power	72W	1	0.87	9159
	Source Flux	7203lm	2	1.74	2290
	Fixture Flux	5404lm	3	2.61	1018
	Efficacy	75lm/W	4	3.47	572
	Imax	9161cd	5	4.34	366

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8608EL**	**1T8611EL**	**1T8614EL**	**1T8617EL**
EL.	●	**1T8648EL**	**1T8651EL**	**1T8654EL**	**1T8657EL**
EL.	◑	**1T8496EL**	**1T8499EL**	**1T8502EL**	**1T8505EL**
DALI	○	**1T8608DA**	**1T8611DA**	**1T8614DA**	**1T8617DA**
DALI	●	**1T8648DA**	**1T8651DA**	**1T8654DA**	**1T8657DA**
DALI	◑	**1T8496DA**	**1T8499DA**	**1T8502DA**	**1T8505DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Filter

Ø	Code
63	**1T8094**

Holographic PMMA filter with blade of light effect.
Allows the beam to be made oval; combined with spot and flood optics the effect appears more pronounced.

Grid

Ø	Code
63	**1T8093**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

CCTEvo Architectural

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Architectural

105



LED / 5,7W / REFLECTOR / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			10°	
	Fixture Power	7W	1	0.17	6377
	Source Flux	558lm	2	0.34	1594
	Fixture Flux	357lm	3	0.52	709
	Efficacy	49lm/W	4	0.69	399
TS1357	Imax=11429cd/klm	Imax	6377cd	5	0.86	255

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8698EL**	**1T8699EL**	**1T8700EL**	**1T8701EL**
EL.	●	**1T8738EL**	**1T8739EL**	**1T8740EL**	**1T8741EL**
EL.	◑	**1T8728EL**	**1T8731EL**	**1T8734EL**	**1T8737EL**
DALI	○	**1T8698DA**	**1T8699DA**	**1T8700DA**	**1T8701DA**
DALI	●	**1T8738DA**	**1T8739DA**	**1T8740DA**	**1T8741DA**
DALI	◑	**1T8728DA**	**1T8731DA**	**1T8734DA**	**1T8737DA**

LED / 13,1W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
	Fixture Power	15W	1	0.24	9343
	Source Flux	1367lm	2	0.49	2336
	Fixture Flux	970lm	3	0.73	1038
	Efficacy	65lm/W	4	0.97	584
TS1303	Imax=6835cd/klm	Imax	9343cd	5	1.21	374

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8702EL**	**1T8705EL**	**1T8708EL**	**1T8711EL**
EL.	●	**1T8742EL**	**1T8745EL**	**1T8748EL**	**1T8751EL**
EL.	◑	**1T8744EL**	**1T8750EL**	**1T8756EL**	**1T8762EL**
DALI	○	**1T8702DA**	**1T8705DA**	**1T8708DA**	**1T8711DA**
DALI	●	**1T8742DA**	**1T8745DA**	**1T8748DA**	**1T8751DA**
DALI	◑	**1T8744DA**	**1T8750DA**	**1T8756DA**	**1T8762DA**

LED / 19W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
	Fixture Power	21W	1	0.24	12186
	Source Flux	1783lm	2	0.49	3047
	Fixture Flux	1265lm	3	0.73	1354
	Efficacy	60lm/W	4	0.97	762
TS1304	Imax=6835cd/klm	Imax	12186cd	5	1.21	487

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8703EL**	**1T8706EL**	**1T8709EL**	**1T8712EL**
EL.	●	**1T8743EL**	**1T8746EL**	**1T8749EL**	**1T8752EL**
EL.	◑	**1T8747EL**	**1T8753EL**	**1T8759EL**	**1T8765EL**
DALI	○	**1T8703DA**	**1T8706DA**	**1T8709DA**	**1T8712DA**
DALI	●	**1T8743DA**	**1T8746DA**	**1T8749DA**	**1T8752DA**
DALI	◑	**1T8747DA**	**1T8753DA**	**1T8759DA**	**1T8765DA**

LED / 12W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
	Fixture Power	12W	1	0.56	4009
	Source Flux	1630lm	2	1.12	1002
	Fixture Flux	1260lm	3	1.67	445
	Efficacy	105lm/W	4	2.23	251
TS1305	Imax=2459cd/klm	Imax	4009cd	5	2.79	160

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8714EL**	**1T8717EL**	**1T8720EL**	**1T8723EL**
EL.	●	**1T8754EL**	**1T8757EL**	**1T8760EL**	**1T8763EL**
EL.	◑	**1T8768EL**	**1T8774EL**	**1T8778EL**	**1T8780EL**
DALI	○	**1T8714DA**	**1T8717DA**	**1T8720DA**	**1T8723DA**
DALI	●	**1T8754DA**	**1T8757DA**	**1T8760DA**	**1T8763DA**
DALI	◑	**1T8768DA**	**1T8774DA**	**1T8778DA**	**1T8780DA**

LED / 18W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
	Fixture Power	20W	1	0.56	5391
	Source Flux	2192lm	2	1.12	1348
	Fixture Flux	1694lm	3	1.67	599
	Efficacy	85lm/W	4	2.23	337
TS1306	Imax=2459cd/klm	Imax	5391cd	5	2.79	216

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8715EL**	**1T8718EL**	**1T8721EL**	**1T8724EL**
EL.	●	**1T8755EL**	**1T8758EL**	**1T8761EL**	**1T8764EL**
EL.	◑	**1T8771EL**	**1T8777EL**	**1T8779EL**	**1T8781EL**
DALI	○	**1T8715DA**	**1T8718DA**	**1T8721DA**	**1T8724DA**
DALI	●	**1T8755DA**	**1T8758DA**	**1T8761DA**	**1T8764DA**
DALI	◑	**1T8771DA**	**1T8777DA**	**1T8779DA**	**1T8781DA**

CCTEvo Architectural

LED / 12W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power		14W	1	0.88	2234
Source Flux		1630lm	2	1.77	559
Fixture Flux		1249lm	3	2.65	248
Efficacy		89lm/W	4	3.53	140
TS1307	Imax=1378cd/klm	Imax	2247cd	5	4.41	89

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8726EL**	**1T8729EL**	**1T8732EL**	**1T8735EL**
EL.	●	**1T8766EL**	**1T8769EL**	**1T8772EL**	**1T8775EL**
EL.	◑	**1T8782EL**	**1T8784EL**	**1T8786EL**	**1T8788EL**
DALI	○	**1T8726DA**	**1T8729DA**	**1T8732DA**	**1T8735DA**
DALI	●	**1T8766DA**	**1T8769DA**	**1T8772DA**	**1T8775DA**
DALI	◑	**1T8782DA**	**1T8784DA**	**1T8786DA**	**1T8788DA**

LED / 18W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power		20W	1	0.88	3005
Source Flux		2192lm	2	1.77	751
Fixture Flux		1680lm	3	2.65	334
Efficacy		84lm/W	4	3.53	188
TS1308	Imax=1378cd/klm	Imax	3022cd	5	4.41	120

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8727EL**	**1T8730EL**	**1T8733EL**	**1T8736EL**
EL.	●	**1T8767EL**	**1T8770EL**	**1T8773EL**	**1T8776EL**
EL.	◑	**1T8783EL**	**1T8785EL**	**1T8787EL**	**1T8789EL**
DALI	○	**1T8727DA**	**1T8730DA**	**1T8733DA**	**1T8736DA**
DALI	●	**1T8767DA**	**1T8770DA**	**1T8773DA**	**1T8776DA**
DALI	◑	**1T8783DA**	**1T8785DA**	**1T8787DA**	**1T8789DA**

LED / 5,7W / LENS / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			10°	
Fixture Power		7W	1	0.18	12437
Source Flux		558lm	2	0.35	3109
Fixture Flux		513lm	3	0.53	1382
Efficacy		70lm/W	4	0.71	777
TS1356	Imax=22289cd/klm	Imax	12437cd	5	0.88	497

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7830EL**	**1T7831EL**	**1T7832EL**	**1T7833EL**
EL.	●	**1T7882EL**	**1T7883EL**	**1T7884EL**	**1T7885EL**
EL.	◑	**1T8790EL**	**1T8791EL**	**1T8792EL**	**1T8793EL**
DALI	○	**1T7830DA**	**1T7831DA**	**1T7832DA**	**1T7833DA**
DALI	●	**1T7882DA**	**1T7883DA**	**1T7884DA**	**1T7885DA**
DALI	◑	**1T8790DA**	**1T8791DA**	**1T8792DA**	**1T8793DA**

LED / 13,1W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
Fixture Power		15W	1	0.25	13948
Source Flux		1367lm	2	0.49	3487
Fixture Flux		1125lm	3	0.74	1550
Efficacy		75lm/W	4	0.99	872
TS1297	Imax=10204cd/klm	Imax	13948cd	5	1.23	558

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7834EL**	**1T7836EL**	**1T7838EL**	**1T7840EL**
EL.	●	**1T8682EL**	**1T8684EL**	**1T8686EL**	**1T8688EL**
EL.	◑	**1T8794EL**	**1T8796EL**	**1T8798EL**	**1T8800EL**
DALI	○	**1T7834DA**	**1T7836DA**	**1T7838DA**	**1T7840DA**
DALI	●	**1T8682DA**	**1T8684DA**	**1T8686DA**	**1T8688DA**
DALI	◑	**1T8794DA**	**1T8796DA**	**1T8798DA**	**1T8800DA**

LED / 19W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
Fixture Power		21W	1	0.25	18194
Source Flux		1783lm	2	0.49	4548
Fixture Flux		1467lm	3	0.74	2022
Efficacy		70lm/W	4	0.99	1137
TS1298	Imax=10204cd/klm	Imax	18194cd	5	1.23	728

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7835EL**	**1T7837EL**	**1T7839EL**	**1T7841EL**
EL.	●	**1T8683EL**	**1T8685EL**	**1T8687EL**	**1T8689EL**
EL.	◑	**1T8795EL**	**1T8797EL**	**1T8799EL**	**1T8801EL**
DALI	○	**1T7835DA**	**1T7837DA**	**1T7839DA**	**1T7841DA**
DALI	●	**1T8683DA**	**1T8685DA**	**1T8687DA**	**1T8689DA**
DALI	◑	**1T8795DA**	**1T8797DA**	**1T8799DA**	**1T8801DA**

LED / 12W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		14W	1	0.47	5685
Source Flux		1630lm	2	0.94	1421
Fixture Flux		1395lm	3	1.40	632
Efficacy		100lm/W	4	1.87	355
TS1299	Imax=3488cd/klm	Imax	5685cd	5	2.34	227

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7854EL**	**1T7856EL**	**1T7858EL**	**1T7860EL**
EL.	●	**1T8690EL**	**1T8692EL**	**1T8694EL**	**1T8696EL**
EL.	◑	**1T8802EL**	**1T8804EL**	**1T8806EL**	**1T8808EL**
DALI	○	**1T7854DA**	**1T7856DA**	**1T7858DA**	**1T7860DA**
DALI	●	**1T8690DA**	**1T8692DA**	**1T8694DA**	**1T8696DA**
DALI	◑	**1T8802DA**	**1T8804DA**	**1T8806DA**	**1T8808DA**

CCTEvo Architectural

LED / 18W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		20W	1	0.47	7646
Source Flux		2192lm	2	0.94	1911
Fixture Flux		1876lm	3	1.40	850
Efficacy		94lm/W	4	1.87	478
TS1300	Imax=3488cd/klm	Imax	5	2.34	306

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7855EL**	**1T7857EL**	**1T7859EL**	**1T7861EL**
EL.	●	**1T8691EL**	**1T8693EL**	**1T8695EL**	**1T8697EL**
EL.	◑	**1T8803EL**	**1T8805EL**	**1T8807EL**	**1T8809EL**
DALI	○	**1T7855DA**	**1T7857DA**	**1T7859DA**	**1T7861DA**
DALI	●	**1T8691DA**	**1T8693DA**	**1T8695DA**	**1T8697DA**
DALI	◑	**1T8803DA**	**1T8805DA**	**1T8807DA**	**1T8809DA**

LED / 12W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power		14W	1	0.75	2652
Source Flux		1630lm	2	1.50	663
Fixture Flux		1311lm	3	2.24	295
Efficacy		94lm/W	4	2.99	166
TS1301	Imax=1661cd/klm	Imax	5	3.74	106

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7862EL**	**1T7864EL**	**1T7878EL**	**1T7880EL**
EL.	●	**1T8704EL**	**1T8710EL**	**1T8716EL**	**1T8722EL**
EL.	◑	**1T8810EL**	**1T8812EL**	**1T8814EL**	**1T8816EL**
DALI	○	**1T7862DA**	**1T7864DA**	**1T7878DA**	**1T7880DA**
DALI	●	**1T8704DA**	**1T8710DA**	**1T8716DA**	**1T8722DA**
DALI	◑	**1T8810DA**	**1T8812DA**	**1T8814DA**	**1T8816DA**

LED / 18W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power		20W	1	0.75	3566
Source Flux		2192lm	2	1.50	892
Fixture Flux		1763lm	3	2.24	396
Efficacy		88lm/W	4	2.99	223
TS1302	Imax=1661cd/klm	Imax	5	3.74	143

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7863EL**	**1T7865EL**	**1T7879EL**	**1T7881EL**
EL.	●	**1T8707EL**	**1T8713EL**	**1T8719EL**	**1T8725EL**
EL.	◑	**1T8811EL**	**1T8813EL**	**1T8815EL**	**1T8817EL**
DALI	○	**1T7863DA**	**1T7865DA**	**1T7879DA**	**1T7881DA**
DALI	●	**1T8707DA**	**1T8713DA**	**1T8719DA**	**1T8725DA**
DALI	◑	**1T8811DA**	**1T8813DA**	**1T8815DA**	**1T8817DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Filter



Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Architectural

78



LED / 9,3W / REFLECTOR / SP

3000K		H(m)	D(m)	Emax(lx)
Ra90			18°	
Fixture Power	11W	1	0.31	4255
Source Flux	896lm	2	0.62	1064
Fixture Flux	604lm	3	0.92	473
Efficacy	55lm/W	4	1.23	266
Imax	4255cd	5	1.54	170

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7886EL**	**1T7887EL**	**1T7888EL**	**1T7889EL**
EL.	●	**1T8826EL**	**1T8827EL**	**1T8828EL**	**1T8829EL**
EL.	◑	**1T8838EL**	**1T8839EL**	**1T8840EL**	**1T8841EL**
DALI	○	**1T7886DA**	**1T7887DA**	**1T7888DA**	**1T7889DA**
DALI	●	**1T8826DA**	**1T8827DA**	**1T8828DA**	**1T8829DA**
DALI	◑	**1T8838DA**	**1T8839DA**	**1T8840DA**	**1T8841DA**

LED / 12W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			27°	
Fixture Power	13W	1	0.48	4402
Source Flux	1553lm	2	0.95	1101
Fixture Flux	1109lm	3	1.43	489
Efficacy	85lm/W	4	1.91	275
Imax	4402cd	5	2.38	176

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8818EL**	**1T8819EL**	**1T8820EL**	**1T8821EL**
EL.	●	**1T8830EL**	**1T8831EL**	**1T8832EL**	**1T8833EL**
EL.	◑	**1T8842EL**	**1T8843EL**	**1T8844EL**	**1T8845EL**
DALI	○	**1T8818DA**	**1T8819DA**	**1T8820DA**	**1T8821DA**
DALI	●	**1T8830DA**	**1T8831DA**	**1T8832DA**	**1T8833DA**
DALI	◑	**1T8842DA**	**1T8843DA**	**1T8844DA**	**1T8845DA**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			42°	
Fixture Power	13W	1	0.76	2517
Source Flux	1553lm	2	1.52	629
Fixture Flux	1148lm	3	2.28	280
Efficacy	88lm/W	4	3.04	157
Imax	2517cd	5	3.80	101

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8822EL**	**1T8823EL**	**1T8824EL**	**1T8825EL**
EL.	●	**1T8834EL**	**1T8835EL**	**1T8836EL**	**1T8837EL**
EL.	◑	**1T8846EL**	**1T8847EL**	**1T8848EL**	**1T8849EL**
DALI	○	**1T8822DA**	**1T8823DA**	**1T8824DA**	**1T8825DA**
DALI	●	**1T8834DA**	**1T8835DA**	**1T8836DA**	**1T8837DA**
DALI	◑	**1T8846DA**	**1T8847DA**	**1T8848DA**	**1T8849DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Filter

Ø	Code
34	**1T6931**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Grid

Ø	Code
34	**1T6930**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

CCTEvo Architectural

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Architectural

58



LED / 9,5W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			23°	
	Fixture Power	11W	1	0.41	3386
	Source Flux	862lm	2	0.81	847
	Fixture Flux	665lm	3	1.22	376
	Efficacy	60lm/W	4	1.63	212
	Imax	3386cd	5	2.03	135

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8446EL**	**1T8447EL**	**1T8448EL**	**1T8449EL**
EL.	●	**1T8470EL**	**1T8471EL**	**1T8472EL**	**1T8473EL**
EL.	◑	**1T8458EL**	**1T8459EL**	**1T8460EL**	**1T8461EL**
DALI	○	**1T8446DA**	**1T8447DA**	**1T8448DA**	**1T8449DA**
DALI	●	**1T8470DA**	**1T8471DA**	**1T8472DA**	**1T8473DA**
DALI	◑	**1T8458DA**	**1T8459DA**	**1T8460DA**	**1T8461DA**

LED / 8,2W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			37°	
	Fixture Power	10W	1	0.67	2053
	Source Flux	1140lm	2	1.35	513
	Fixture Flux	787lm	3	2.02	228
	Efficacy	81lm/W	4	2.69	128
	Imax	2053cd	5	3.37	82

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8450EL**	**1T8451EL**	**1T8452EL**	**1T8453EL**
EL.	●	**1T8474EL**	**1T8475EL**	**1T8476EL**	**1T8477EL**
EL.	◑	**1T8462EL**	**1T8463EL**	**1T8464EL**	**1T8465EL**
DALI	○	**1T8450DA**	**1T8451DA**	**1T8452DA**	**1T8453DA**
DALI	●	**1T8474DA**	**1T8475DA**	**1T8476DA**	**1T8477DA**
DALI	◑	**1T8462DA**	**1T8463DA**	**1T8464DA**	**1T8465DA**

LED / 8,2W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			53°	
	Fixture Power	10W	1	0.99	1157
	Source Flux	1140lm	2	1.99	289
	Fixture Flux	834lm	3	2.98	129
	Efficacy	86lm/W	4	3.98	72
	Imax	1165cd	5	4.97	46

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8454EL**	**1T8455EL**	**1T8456EL**	**1T8457EL**
EL.	●	**1T8478EL**	**1T8479EL**	**1T8480EL**	**1T8481EL**
EL.	◑	**1T8466EL**	**1T8467EL**	**1T8468EL**	**1T8469EL**
DALI	○	**1T8454DA**	**1T8455DA**	**1T8456DA**	**1T8457DA**
DALI	●	**1T8478DA**	**1T8479DA**	**1T8480DA**	**1T8481DA**
DALI	◑	**1T8466DA**	**1T8467DA**	**1T8468DA**	**1T8469DA**

Note

Trimless version: to order this version it is necessary to add the suffix “TR” to the end of the standard code.

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo EXTRACTABLE

GENERAL INFO
Adjustable extractable recessed LED projector. Ø162mm Ø125mm

LED
High efficiency LED Chip on Board with Ra90. From 516lm to 6354lm 2700K – 3000K – 3500K - 4000K

EFFICACIA PRODOTTO
Up to 96lm/W

OPTICS
NSP - SP - FL - MWFL - WFL

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Black or white painted die-cast aluminium body and dissipator. Available in a trim version with an integrated black or white ring.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

A range of professional performance extractable recessed projectors with extensive flexibility. The projector can be set back completely for maximum formal simplicity or extracted up to 75° and adjusted up to -25°/+75° on the vertical plane and 355° on the horizontal one with a manual aiming system.

Available in two different sizes ø162mm and ø125mm, four colour temperatures, two optical systems and five different luminous emissions.

A complete range of professional lighting solutions. Size ø125mm can be equipped with two different optical systems, with a reflector for softer beams and with lenses for more precise, defined beams.

		Ø 162mm	Ø 125mm
LED	Flux (lm)	3012-6354	516-2216
	Power	24-48W	5,7-19W
OPTICS			
NSP	Reflector		•
	Lens		•
SP	Reflector	•	•
	Lens		•
FL	Reflector	•	•
	Lens		•
MWFL	Reflector	•	•
	Lens		•
WFL	Reflector	•	

Plus

Two optical systems

CCTEvo Extractable is an extremely flexible tool. The different optical systems available allow for NSP, SP, FL, MWFL and WFL beam openings. Size ø 125mm can be equipped with two different optical systems - with a reflector for soft effects with low visual contrast and lenses for more defined beams – extending the choice of solutions on offer further.

Maximum adjustability

For both sizes the optical unit can be adjusted from 75° to -25° on the vertical plane and 355° on the horizontal plane. The optical unit can even be setback into the false ceiling.

Optic system
with lense

Optic system
with reflector

CCTEvo Extractable



162



LED / 24W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			17°	
Fixture Power		27W	1	0.31	16337
Source Flux		3132lm	2	0.61	4084
Fixture Flux		2411lm	3	0.92	1815
Efficacy		89lm/W	4	1.22	1021
TS1309	Imax=5216cd/klm	Imax	16337cd	5	1.53	653

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9100EL**	**1T9103EL**	**1T9106EL**	**1T9109EL**
EL.	●	**1T9148EL**	**1T9151EL**	**1T9154EL**	**1T9157EL**
DALI	○	**1T9100DA**	**1T9103DA**	**1T9106DA**	**1T9109DA**
DALI	●	**1T9148DA**	**1T9151DA**	**1T9154DA**	**1T9157DA**

LED / 36W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			17°	
Fixture Power		40W	1	0.31	23614
Source Flux		4527lm	2	0.61	5903
Fixture Flux		3484lm	3	0.92	2624
Efficacy		87lm/W	4	1.22	1476
TS1310	Imax=5216cd/klm	Imax	23614cd	5	1.53	945

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9101EL**	**1T9104EL**	**1T9107EL**	**1T9110EL**
EL.	●	**1T9149EL**	**1T9152EL**	**1T9155EL**	**1T9158EL**
DALI	○	**1T9101DA**	**1T9104DA**	**1T9107DA**	**1T9110DA**
DALI	●	**1T9149DA**	**1T9152DA**	**1T9155DA**	**1T9158DA**

LED / 48W / REFLECTOR / FL (27°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		54W	1	0.47	16179
Source Flux		6259lm	2	0.94	4045
Fixture Flux		4449lm	3	1.42	1798
Efficacy		82lm/W	4	1.89	1011
TS1311	Imax=2585cd/klm	Imax	16179cd	5	2.36	647

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9102EL**	**1T9105EL**	**1T9108EL**	**1T9111EL**
EL.	●	**1T9150EL**	**1T9153EL**	**1T9156EL**	**1T9159EL**
DALI	○	**1T9102DA**	**1T9105DA**	**1T9108DA**	**1T9111DA**
DALI	●	**1T9150DA**	**1T9153DA**	**1T9156DA**	**1T9159DA**

LED / 24W / REFLECTOR / FL (32°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			32°	
Fixture Power		27W	1	0.57	7394
Source Flux		3132lm	2	1.13	1849
Fixture Flux		2418lm	3	1.70	822
Efficacy		90lm/W	4	2.27	462
TS1312	Imax=2361cd/klm	Imax	7394cd	5	2.83	296

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9112EL**	**1T9115EL**	**1T9118EL**	**1T9121EL**
EL.	●	**1T9160EL**	**1T9163EL**	**1T9166EL**	**1T9169EL**
DALI	○	**1T9112DA**	**1T9115DA**	**1T9118DA**	**1T9121DA**
DALI	●	**1T9160DA**	**1T9163DA**	**1T9166DA**	**1T9169DA**

LED / 36W / REFLECTOR / FL (32°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			32°	
Fixture Power		40W	1	0.57	10688
Source Flux		4527lm	2	1.13	2672
Fixture Flux		3496lm	3	1.70	1188
Efficacy		87lm/W	4	2.27	668
TS1313	Imax=2361cd/klm	Imax	10688cd	5	2.83	428

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9113EL**	**1T9116EL**	**1T9119EL**	**1T9122EL**
EL.	●	**1T9161EL**	**1T9164EL**	**1T9167EL**	**1T9170EL**
DALI	○	**1T9113DA**	**1T9116DA**	**1T9119DA**	**1T9122DA**
DALI	●	**1T9161DA**	**1T9164DA**	**1T9167DA**	**1T9170DA**

CCTEvo Extractable

LED / 48W / REFLECTOR / FL (37°)



3000K		H(m)	D(m)	Emax(lx)
Ra90			37°	
Fixture Power	54W	1	0.67	11510
Source Flux	6259lm	2	1.35	2878
Fixture Flux	4670lm	3	2.02	1279
Efficacy	86lm/W	4	2.70	719
TS1314 Imax=1839cd/klm	Imax	11510cd	5	3.37	460

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9114EL**	**1T9117EL**	**1T9120EL**	**1T9123EL**
EL.	●	**1T9162EL**	**1T9165EL**	**1T9168EL**	**1T9171EL**
DALI	○	**1T9114DA**	**1T9117DA**	**1T9120DA**	**1T9123DA**
DALI	●	**1T9162DA**	**1T9165DA**	**1T9168DA**	**1T9171DA**

LED / 24W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			48°	
Fixture Power	27W	1	0.89	4160
Source Flux	3132lm	2	1.78	1040
Fixture Flux	2456lm	3	2.66	462
Efficacy	91lm/W	4	3.55	260
TS1315 Imax=1365cd/klm	Imax	4274cd	5	4.44	166

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9124EL**	**1T9127EL**	**1T9130EL**	**1T9133EL**
EL.	●	**1T9172EL**	**1T9175EL**	**1T9178EL**	**1T9181EL**
DALI	○	**1T9124DA**	**1T9127DA**	**1T9130DA**	**1T9133DA**
DALI	●	**1T9172DA**	**1T9175DA**	**1T9178DA**	**1T9181DA**

LED / 36W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			48°	
Fixture Power	40W	1	0.89	6013
Source Flux	4527lm	2	1.78	1503
Fixture Flux	3549lm	3	2.66	668
Efficacy	89lm/W	4	3.55	376
TS1316 Imax=1365cd/klm	Imax	6178cd	5	4.44	241

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9125EL**	**1T9128EL**	**1T9131EL**	**1T9134EL**
EL.	●	**1T9173EL**	**1T9176EL**	**1T9179EL**	**1T9182EL**
DALI	○	**1T9125DA**	**1T9128DA**	**1T9131DA**	**1T9134DA**
DALI	●	**1T9173DA**	**1T9176DA**	**1T9179DA**	**1T9182DA**

LED / 48W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			47°	
Fixture Power	54W	1	0.87	8787
Source Flux	6259lm	2	1.74	2197
Fixture Flux	5035lm	3	2.61	976
Efficacy	93lm/W	4	3.48	549
TS1317 Imax=1407cd/klm	Imax	8806cd	5	4.34	351

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9126EL**	**1T9129EL**	**1T9132EL**	**1T9135EL**
EL.	●	**1T9174EL**	**1T9177EL**	**1T9180EL**	**1T9183EL**
DALI	○	**1T9126DA**	**1T9129DA**	**1T9132DA**	**1T9135DA**
DALI	●	**1T9174DA**	**1T9177DA**	**1T9180DA**	**1T9183DA**

LED / 24W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			57°	
Fixture Power	27W	1	1.09	2925
Source Flux	3132lm	2	2.19	731
Fixture Flux	2440lm	3	3.28	325
Efficacy	90lm/W	4	4.37	183
TS1318 Imax=967cd/klm	Imax	3028cd	5	5.46	117

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9136EL**	**1T9139EL**	**1T9142EL**	**1T9145EL**
EL.	●	**1T9184EL**	**1T9187EL**	**1T9190EL**	**1T9193EL**
DALI	○	**1T9136DA**	**1T9139DA**	**1T9142DA**	**1T9145DA**
DALI	●	**1T9184DA**	**1T9187DA**	**1T9190DA**	**1T9193DA**

LED / 36W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			57°	
Fixture Power	40W	1	1.09	4228
Source Flux	4527lm	2	2.19	1057
Fixture Flux	3527lm	3	3.28	470
Efficacy	88lm/W	4	4.37	264
TS1319 Imax=967cd/klm	Imax	4377cd	5	5.46	169

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9137EL**	**1T9140EL**	**1T9143EL**	**1T9146EL**
EL.	●	**1T9185EL**	**1T9188EL**	**1T9191EL**	**1T9194EL**
DALI	○	**1T9137DA**	**1T9140DA**	**1T9143DA**	**1T9146DA**
DALI	●	**1T9185DA**	**1T9188DA**	**1T9191DA**	**1T9194DA**

CCTEvo Extractable

LED / 48W / REFLECTOR / WFL



Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9138EL**	**1T9141EL**	**1T9144EL**	**1T9147EL**
EL.	●	**1T9186EL**	**1T9189EL**	**1T9192EL**	**1T9195EL**
DALI	○	**1T9138DA**	**1T9141DA**	**1T9144DA**	**1T9147DA**
DALI	●	**1T9186DA**	**1T9189DA**	**1T9192DA**	**1T9195DA**

Accessories

Filter



Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.



Ø	Code
70	**1T1709**

Flat glass wired refractive diffusive filter.
This softens the luminous effect.
To be completed with an additional holder ring for Cloud, Ray Mini, Sore, Label 9 and CCTEvo Extractable 162.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Holder Ring

Code
1T3727

Transparent polycarbonate accessory holder ring.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Extractable

125



LED / 5,7W / REFLECTOR / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra90			10°	
Fixture Power	7W	1	0.18	6301
Source Flux	560lm	2	0.36	1575
Fixture Flux	401lm	3	0.54	700
Efficacy	62lm/W	4	0.73	394
Imax	6301cd	5	0.91	252

TS1321 Imax=11252cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9196EL**	**1T9197EL**	**1T9198EL**	**1T9199EL**
EL.	●	**1T9252EL**	**1T9253EL**	**1T9254EL**	**1T9255EL**
DALI	○	**1T9196DA**	**1T9197DA**	**1T9198DA**	**1T9199DA**
DALI	●	**1T9252DA**	**1T9253DA**	**1T9254DA**	**1T9255DA**

LED / 13W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			12°	
Fixture Power	15W	1	0.22	10870
Source Flux	1364lm	2	0.44	2717
Fixture Flux	960lm	3	0.65	1208
Efficacy	64lm/W	4	0.87	679
Imax	10870cd	5	1.09	435

TS1322 Imax=7969cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9200EL**	**1T9202EL**	**1T9204EL**	**1T9206EL**
EL.	●	**1T9256EL**	**1T9258EL**	**1T9260EL**	**1T9262EL**
DALI	○	**1T9200DA**	**1T9202DA**	**1T9204DA**	**1T9206DA**
DALI	●	**1T9256DA**	**1T9258DA**	**1T9260DA**	**1T9262DA**

LED / 19W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			12°	
Fixture Power	21W	1	0.22	14177
Source Flux	1779lm	2	0.44	3544
Fixture Flux	1252lm	3	0.65	1575
Efficacy	60lm/W	4	0.87	886
Imax	14177cd	5	1.09	567

TS1323 Imax=7969cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9201EL**	**1T9203EL**	**1T9205EL**	**1T9207EL**
EL.	●	**1T9257EL**	**1T9259EL**	**1T9261EL**	**1T9263EL**
DALI	○	**1T9201DA**	**1T9203DA**	**1T9205DA**	**1T9207DA**
DALI	●	**1T9257DA**	**1T9259DA**	**1T9261DA**	**1T9263DA**

LED / 12W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			33°	
Fixture Power	14W	1	0.60	3217
Source Flux	1620lm	2	1.20	804
Fixture Flux	1162lm	3	1.80	357
Efficacy	83lm/W	4	2.40	201
Imax	3217cd	5	2.99	129

TS1324 Imax=1986cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9208EL**	**1T9210EL**	**1T9212EL**	**1T9214EL**
EL.	●	**1T9264EL**	**1T9266EL**	**1T9268EL**	**1T9270EL**
DALI	○	**1T9208DA**	**1T9210DA**	**1T9212DA**	**1T9214DA**
DALI	●	**1T9264DA**	**1T9266DA**	**1T9268DA**	**1T9270DA**

LED / 17W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			33°	
Fixture Power	20W	1	0.60	4334
Source Flux	2182lm	2	1.20	1083
Fixture Flux	1565lm	3	1.80	482
Efficacy	78lm/W	4	2.40	271
Imax	4334cd	5	2.99	173

TS1325 Imax=1986cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9209EL**	**1T9211EL**	**1T9213EL**	**1T9215EL**
EL.	●	**1T9265EL**	**1T9267EL**	**1T9269EL**	**1T9271EL**
DALI	○	**1T9209DA**	**1T9211DA**	**1T9213DA**	**1T9215DA**
DALI	●	**1T9265DA**	**1T9267DA**	**1T9269DA**	**1T9271DA**

CCTEvo Extractable

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			45°	
Fixture Power	14W	1	0.84	2211
Source Flux	1620lm	2	1.67	553
Fixture Flux	1193lm	3	2.51	246
Efficacy	85lm/W	4	3.35	138
TS1326 Imax=1365cd/klm	Imax	2211cd	5	4.18	88

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9216EL**	**1T9218EL**	**1T9220EL**	**1T9222EL**
EL.	●	**1T9272EL**	**1T9274EL**	**1T9276EL**	**1T9278EL**
DALI	○	**1T9216DA**	**1T9218DA**	**1T9220DA**	**1T9222DA**
DALI	●	**1T9272DA**	**1T9274DA**	**1T9276DA**	**1T9278DA**

LED / 17W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			45°	
Fixture Power	20W	1	0.84	2978
Source Flux	2182lm	2	1.67	745
Fixture Flux	1606lm	3	2.51	331
Efficacy	80lm/W	4	3.35	186
TS1327 Imax=1365cd/klm	Imax	2978cd	5	4.18	119

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9217EL**	**1T9219EL**	**1T9221EL**	**1T9223EL**
EL.	●	**1T9273EL**	**1T9275EL**	**1T9277EL**	**1T9279EL**
DALI	○	**1T9217DA**	**1T9219DA**	**1T9221DA**	**1T9223DA**
DALI	●	**1T9273DA**	**1T9275DA**	**1T9277DA**	**1T9279DA**

LED / 5,7W / LENS / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra90			10°	
Fixture Power	7W	1	0.18	11259
Source Flux	546lm	2	0.35	2815
Fixture Flux	502lm	3	0.53	1251
Efficacy	70lm/W	4	0.71	704
TS1380 Imax=20620cd/klm	Imax	11259cd	5	0.88	450

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9224EL**	**1T9225EL**	**1T9226EL**	**1T9227EL**
EL.	●	**1T9280EL**	**1T9281EL**	**1T9282EL**	**1T9283EL**
DALI	○	**1T9224DA**	**1T9225DA**	**1T9226DA**	**1T9227DA**
DALI	●	**1T9280DA**	**1T9281DA**	**1T9282DA**	**1T9283DA**

LED / 13W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			14°	
Fixture Power	15W	1	0.25	13816
Source Flux	1364lm	2	0.50	3454
Fixture Flux	1149lm	3	0.74	1535
Efficacy	77lm/W	4	0.99	863
TS1328 Imax=10129cd/klm	Imax	13816cd	5	1.24	553

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9228EL**	**1T9230EL**	**1T9232EL**	**1T9234EL**
EL.	●	**1T9284EL**	**1T9286EL**	**1T9288EL**	**1T9290EL**
DALI	○	**1T9228DA**	**1T9230DA**	**1T9232DA**	**1T9234DA**
DALI	●	**1T9284DA**	**1T9286DA**	**1T9288DA**	**1T9290DA**

LED / 19W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			14°	
Fixture Power	21W	1	0.25	18019
Source Flux	1779lm	2	0.50	4505
Fixture Flux	1499lm	3	0.74	2002
Efficacy	71lm/W	4	0.99	1126
TS1329 Imax=10129cd/klm	Imax	18019cd	5	1.24	721

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9229EL**	**1T9231EL**	**1T9233EL**	**1T9235EL**
EL.	●	**1T9285EL**	**1T9287EL**	**1T9289EL**	**1T9291EL**
DALI	○	**1T9229DA**	**1T9231DA**	**1T9233DA**	**1T9235DA**
DALI	●	**1T9285DA**	**1T9287DA**	**1T9289DA**	**1T9291DA**

LED / 12W / LENS / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	14W	1	0.52	4538
Source Flux	1620lm	2	1.03	1135
Fixture Flux	1304lm	3	1.55	504
Efficacy	93lm/W	4	2.06	284
TS1330 Imax=2801cd/klm	Imax	4538cd	5	2.58	182

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9236EL**	**1T9238EL**	**1T9240EL**	**1T9242EL**
EL.	●	**1T9292EL**	**1T9294EL**	**1T9296EL**	**1T9298EL**
DALI	○	**1T9236DA**	**1T9238DA**	**1T9240DA**	**1T9242DA**
DALI	●	**1T9292DA**	**1T9294DA**	**1T9296DA**	**1T9298DA**

CCTEvo Extractable

LED / 17W / LENS / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	20W	1	0.52	6112
Source Flux	2182lm	2	1.03	1528
Fixture Flux	1756lm	3	1.55	679
Efficacy	88lm/W	4	2.06	382
TS1331 Imax=2801cd/klm	Imax	6112cd	5	2.58	244

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9237EL**	**1T9239EL**	**1T9241EL**	**1T9243EL**
EL.	●	**1T9293EL**	**1T9295EL**	**1T9297EL**	**1T9299EL**
DALI	○	**1T9237DA**	**1T9239DA**	**1T9241DA**	**1T9243DA**
DALI	●	**1T9293DA**	**1T9295DA**	**1T9297DA**	**1T9299DA**

LED / 12W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	14W	1	0.74	2251
Source Flux	1620lm	2	1.49	563
Fixture Flux	1235lm	3	2.23	250
Efficacy	88lm/W	4	2.97	141
TS1332 Imax=1390cd/klm	Imax	2251cd	5	3.71	90

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9244EL**	**1T9246EL**	**1T9248EL**	**1T9250EL**
EL.	●	**1T9300EL**	**1T9302EL**	**1T9304EL**	**1T9306EL**
DALI	○	**1T9244DA**	**1T9246DA**	**1T9248DA**	**1T9250DA**
DALI	●	**1T9300DA**	**1T9302DA**	**1T9304DA**	**1T9306DA**

LED / 17W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	20W	1	0.74	3032
Source Flux	2182lm	2	1.49	758
Fixture Flux	1663lm	3	2.23	337
Efficacy	83lm/W	4	2.97	189
TS1333 Imax=1389cd/klm	Imax	3032cd	5	3.71	121

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9245EL**	**1T9247EL**	**1T9249EL**	**1T9251EL**
EL.	●	**1T9301EL**	**1T9303EL**	**1T9305EL**	**1T9307EL**
DALI	○	**1T9245DA**	**1T9247DA**	**1T9249DA**	**1T9251DA**
DALI	●	**1T9301DA**	**1T9303DA**	**1T9305DA**	**1T9307DA**

Accessories

Filter



Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo GIMBAL

GENERAL INFO
Recessed adjustable LED projector.
ø125mm ø105mm

LED
High efficiency LED Chip on Board with Ra90.
From 1266lm to 3180lm
2700K – 3000K – 3500K - 4000K

PRODUCT EFFICACY
Up to 102lm/W

OPTICS
SP - FL - MWFL

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Die-cast black or white painted anodised aluminium body.
Available with a black or white integrated ring.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

The simplest product in the range, CCTEvo Gimbal is a recessed fixture in two different sizes - ø125mm and ø105mm - designed to meet the particular lighting needs of the retail sector. A real recessed projector with professional performance and minimal design that can be adjusted up to a +/-25°. It can be equipped with two different optical systems: with lenses for more precise, defined beams and with a reflector for softer and more uniform emissions.

		Ø 125mm	Ø 105mm
LED	Flux (lm)	2120-3180	1266-2222
	Power	18-25W	12-19W
OPTICS			
SP	Reflector	•	•
	Lens	•	•
FL	Reflector	•	•
	Lens	•	•
MWFL	Reflector	•	•
	Lens	•	•



SWISS WATER PROCESS
Guatemala
CAFÉ DO
ARABICA
%
BRAZIL #1
WATARU
MARAR STAR

CCTEvo Gimbal

125



LED / 18W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			16°	
Fixture Power	20W	1	0.28	11671
Source Flux	2207lm	2	0.56	2918
Fixture Flux	1467lm	3	0.84	1297
Efficacy	73lm/W	4	1.11	729
Imax	11671cd	5	1.39	467

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9308EL**	**1T9310EL**	**1T9312EL**	**1T9314EL**
EL.	●	**1T9356EL**	**1T9358EL**	**1T9360EL**	**1T9362EL**
DALI	○	**1T9308DA**	**1T9310DA**	**1T9312DA**	**1T9314DA**
DALI	●	**1T9356DA**	**1T9358DA**	**1T9360DA**	**1T9362DA**

LED / 24W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			21°	
Fixture Power	28W	1	0.37	12058
Source Flux	3132lm	2	0.75	3015
Fixture Flux	2230lm	3	1.12	1340
Efficacy	80lm/W	4	1.50	754
Imax	12058cd	5	1.87	482

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9309EL**	**1T9311EL**	**1T9313EL**	**1T9315EL**
EL.	●	**1T9357EL**	**1T9359EL**	**1T9361EL**	**1T9363EL**
DALI	○	**1T9309DA**	**1T9311DA**	**1T9313DA**	**1T9315DA**
DALI	●	**1T9357DA**	**1T9359DA**	**1T9361DA**	**1T9363DA**

LED / 18W / REFLECTOR / FL (27°)



3000K		H(m)	D(m)	Emax(lx)
Ra90			27°	
Fixture Power	20W	1	0.49	5604
Source Flux	2207lm	2	0.98	1401
Fixture Flux	1520lm	3	1.47	623
Efficacy	76lm/W	4	1.96	350
Imax	5604cd	5	2.45	224

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9316EL**	**1T9318EL**	**1T9320EL**	**1T9322EL**
EL.	●	**1T9364EL**	**1T9366EL**	**1T9368EL**	**1T9370EL**
DALI	○	**1T9316DA**	**1T9318DA**	**1T9320DA**	**1T9322DA**
DALI	●	**1T9364DA**	**1T9366DA**	**1T9368DA**	**1T9370DA**

LED / 24W / REFLECTOR / FL (33°)



3000K		H(m)	D(m)	Emax(lx)
Ra90			33°	
Fixture Power	28W	1	0.59	6806
Source Flux	3132lm	2	1.18	1701
Fixture Flux	2309lm	3	1.77	756
Efficacy	82lm/W	4	2.36	425
Imax	6806cd	5	2.95	272

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9317EL**	**1T9319EL**	**1T9321EL**	**1T9323EL**
EL.	●	**1T9365EL**	**1T9367EL**	**1T9369EL**	**1T9371EL**
DALI	○	**1T9317DA**	**1T9319DA**	**1T9321DA**	**1T9323DA**
DALI	●	**1T9365DA**	**1T9367DA**	**1T9369DA**	**1T9371DA**

LED / 18W / REFLECTOR / FL (40°)



3000K		H(m)	D(m)	Emax(lx)
Ra90			40°	
Fixture Power	20W	1	0.73	3539
Source Flux	2207lm	2	1.46	885
Fixture Flux	1549lm	3	2.19	393
Efficacy	77lm/W	4	2.93	221
Imax	3539cd	5	3.66	142

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9324EL**	**1T9326EL**	**1T9328EL**	**1T9330EL**
EL.	●	**1T9372EL**	**1T9374EL**	**1T9376EL**	**1T9378EL**
DALI	○	**1T9324DA**	**1T9326DA**	**1T9328DA**	**1T9330DA**
DALI	●	**1T9372DA**	**1T9374DA**	**1T9376DA**	**1T9378DA**

CCTEvo Gimbal

LED / 24W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			46°	
Fixture Power	28W	1	0.85	4353
Source Flux	3132lm	2	1.70	1088
Fixture Flux	2359lm	3	2.55	484
Efficacy	84lm/W	4	3.40	272
TS1363 Imax=1390cd/klm	Imax	4354cd	5	4.25	174

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9325EL**	**1T9327EL**	**1T9329EL**	**1T9331EL**
EL.	●	**1T9373EL**	**1T9375EL**	**1T9377EL**	**1T9379EL**
DALI	○	**1T9325DA**	**1T9327DA**	**1T9329DA**	**1T9331DA**
DALI	●	**1T9373DA**	**1T9375DA**	**1T9377DA**	**1T9379DA**

LED / 18W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			17°	
Fixture Power	20W	1	0.30	16722
Source Flux	2207lm	2	0.60	4180
Fixture Flux	1840lm	3	0.90	1858
Efficacy	92lm/W	4	1.19	1045
TS1364 Imax=7577cd/klm	Imax	16722cd	5	1.49	669

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9332EL**	**1T9334EL**	**1T9336EL**	**1T9338EL**
EL.	●	**1T9380EL**	**1T9382EL**	**1T9384EL**	**1T9386EL**
DALI	○	**1T9332DA**	**1T9334DA**	**1T9336DA**	**1T9338DA**
DALI	●	**1T9380DA**	**1T9382DA**	**1T9384DA**	**1T9386DA**

LED / 25W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			17°	
Fixture Power	28W	1	0.30	22177
Source Flux	2927lm	2	0.60	5544
Fixture Flux	2441lm	3	0.90	2464
Efficacy	87lm/W	4	1.19	1386
TS1365 Imax=7577cd/klm	Imax	22177cd	5	1.49	887

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9333EL**	**1T9335EL**	**1T9337EL**	**1T9339EL**
EL.	●	**1T9381EL**	**1T9383EL**	**1T9385EL**	**1T9387EL**
DALI	○	**1T9333DA**	**1T9335DA**	**1T9337DA**	**1T9339DA**
DALI	●	**1T9381DA**	**1T9383DA**	**1T9385DA**	**1T9387DA**

LED / 18W / LENS / FL (26°)



3000K		H(m)	D(m)	Emax(lx)
Ra90			26°	
Fixture Power	20W	1	0.47	7296
Source Flux	2207lm	2	0.94	1824
Fixture Flux	1799lm	3	1.41	811
Efficacy	90lm/W	4	1.88	456
TS1366 Imax=3306cd/klm	Imax	7296cd	5	2.35	292

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9340EL**	**1T9342EL**	**1T9344EL**	**1T9346EL**
EL.	●	**1T9388EL**	**1T9390EL**	**1T9392EL**	**1T9394EL**
DALI	○	**1T9340DA**	**1T9342DA**	**1T9344DA**	**1T9346DA**
DALI	●	**1T9388DA**	**1T9390DA**	**1T9392DA**	**1T9394DA**

LED / 25W / LENS / FL (26°)



3000K		H(m)	D(m)	Emax(lx)
Ra90			26°	
Fixture Power	28W	1	0.47	9676
Source Flux	2927lm	2	0.94	2419
Fixture Flux	2385lm	3	1.41	1075
Efficacy	85lm/W	4	1.88	605
TS1367 Imax=3306cd/klm	Imax	9676cd	5	2.35	387

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9341EL**	**1T9343EL**	**1T9345EL**	**1T9347EL**
EL.	●	**1T9389EL**	**1T9391EL**	**1T9393EL**	**1T9395EL**
DALI	○	**1T9341DA**	**1T9343DA**	**1T9345DA**	**1T9347DA**
DALI	●	**1T9389DA**	**1T9391DA**	**1T9393DA**	**1T9395DA**

LED / 18W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	20W	1	0.75	3505
Source Flux	2207lm	2	1.49	876
Fixture Flux	1717lm	3	2.24	389
Efficacy	86lm/W	4	2.99	219
TS1368 Imax=1622cd/klm	Imax	3581cd	5	3.73	140

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9348EL**	**1T9350EL**	**1T9352EL**	**1T9354EL**
EL.	●	**1T9396EL**	**1T9398EL**	**1T9400EL**	**1T9402EL**
DALI	○	**1T9348DA**	**1T9350DA**	**1T9352DA**	**1T9354DA**
DALI	●	**1T9396DA**	**1T9398DA**	**1T9400DA**	**1T9402DA**

CCTEvo Gimbal

LED / 25W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	28W	1	0.75	4649
Source Flux	2927lm	2	1.49	1162
Fixture Flux	2277lm	3	2.24	517
Efficacy	81lm/W	4	2.99	291
Imax	4749cd	5	3.73	186

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9349EL**	**1T9351EL**	**1T9353EL**	**1T9355EL**
EL.	◐	**1T9397EL**	**1T9399EL**	**1T9401EL**	**1T9403EL**
DALI	○	**1T9349DA**	**1T9351DA**	**1T9353DA**	**1T9355DA**
DALI	◐	**1T9397DA**	**1T9399DA**	**1T9401DA**	**1T9403DA**

Accessories

Filter



Ø	Code
63	**1T8094**

Holographic PMMA filter with blade of light effect.
Allows the beam to be made oval; combined with spot and flood optics the effect appears more pronounced.

Grid



Ø	Code
63	**1T8093**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTEvo Gimbal

105



LED / 13W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			14°	
Fixture Power	15W	1	0.24	9321
Source Flux	1364lm	2	0.49	2330
Fixture Flux	968lm	3	0.73	1036
Efficacy	65lm/W	4	0.97	583
TS1344 Imax=6834cd/klm	Imax	9321cd	5	1.21	373

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9404EL**	**1T9406EL**	**1T9408EL**	**1T9410EL**
EL.	●	**1T9452EL**	**1T9454EL**	**1T9456EL**	**1T9458EL**
DALI	○	**1T9404DA**	**1T9406DA**	**1T9408DA**	**1T9410DA**
DALI	●	**1T9452DA**	**1T9454DA**	**1T9456DA**	**1T9458DA**

LED / 19W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			14°	
Fixture Power	21W	1	0.24	12159
Source Flux	1779lm	2	0.49	3040
Fixture Flux	1262lm	3	0.73	1351
Efficacy	60lm/W	4	0.97	760
TS1345 Imax=6835cd/klm	Imax	12159cd	5	1.21	486

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9405EL**	**1T9407EL**	**1T9409EL**	**1T9411EL**
EL.	●	**1T9453EL**	**1T9455EL**	**1T9457EL**	**1T9459EL**
DALI	○	**1T9405DA**	**1T9407DA**	**1T9409DA**	**1T9411DA**
DALI	●	**1T9453DA**	**1T9455DA**	**1T9457DA**	**1T9459DA**

LED / 12W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			31°	
Fixture Power	14W	1	0.56	4002
Source Flux	1627lm	2	1.12	1000
Fixture Flux	1258lm	3	1.67	445
Efficacy	90lm/W	4	2.23	250
TS1346 Imax=2459cd/klm	Imax	4002cd	5	2.79	160

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9412EL**	**1T9414EL**	**1T9416EL**	**1T9418EL**
EL.	●	**1T9460EL**	**1T9462EL**	**1T9464EL**	**1T9466EL**
DALI	○	**1T9412DA**	**1T9414DA**	**1T9416DA**	**1T9418DA**
DALI	●	**1T9460DA**	**1T9462DA**	**1T9464DA**	**1T9466DA**

LED / 18W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			31°	
Fixture Power	20W	1	0.56	5379
Source Flux	2187lm	2	1.12	1345
Fixture Flux	1691lm	3	1.67	598
Efficacy	85lm/W	4	2.23	336
TS1347 Imax=2460cd/klm	Imax	5379cd	5	2.79	215

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9413EL**	**1T9415EL**	**1T9417EL**	**1T9419EL**
EL.	●	**1T9461EL**	**1T9463EL**	**1T9465EL**	**1T9467EL**
DALI	○	**1T9413DA**	**1T9415DA**	**1T9417DA**	**1T9419DA**
DALI	●	**1T9461DA**	**1T9463DA**	**1T9465DA**	**1T9467DA**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			48°	
Fixture Power	14W	1	0.88	2230
Source Flux	1627lm	2	1.77	558
Fixture Flux	1247lm	3	2.65	248
Efficacy	89lm/W	4	3.53	139
TS1348 Imax=1378cd/klm	Imax	2243cd	5	4.41	89

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9420EL**	**1T9422EL**	**1T9424EL**	**1T9426EL**
EL.	●	**1T9468EL**	**1T9470EL**	**1T9472EL**	**1T9474EL**
DALI	○	**1T9420DA**	**1T9422DA**	**1T9424DA**	**1T9426DA**
DALI	●	**1T9468DA**	**1T9470DA**	**1T9472DA**	**1T9474DA**

CCTEvo Gimbal

LED / 18W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power		20W	1	0.88	2998
Source Flux		2187lm	2	1.77	749
Fixture Flux		1676lm	3	2.65	333
Efficacy		84lm/W	4	3.53	187
TS1349	Imax=1378cd/klm	Imax	3015cd	5	4.41	120

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9421EL**	**1T9423EL**	**1T9425EL**	**1T9427EL**
EL.	●	**1T9469EL**	**1T9471EL**	**1T9473EL**	**1T9475EL**
DALI	○	**1T9421DA**	**1T9423DA**	**1T9425DA**	**1T9427DA**
DALI	●	**1T9469DA**	**1T9471DA**	**1T9473DA**	**1T9475DA**

LED / 13W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
Fixture Power		15W	1	0.25	13919
Source Flux		1364lm	2	0.49	3480
Fixture Flux		1123lm	3	0.74	1547
Efficacy		75lm/W	4	0.99	870
TS1350	Imax=10204cd/klm	Imax	13919cd	5	1.23	557

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9428EL**	**1T9430EL**	**1T9432EL**	**1T9434EL**
EL.	●	**1T9476EL**	**1T9478EL**	**1T9480EL**	**1T9482EL**
DALI	○	**1T9428DA**	**1T9430DA**	**1T9432DA**	**1T9434DA**
DALI	●	**1T9476DA**	**1T9478DA**	**1T9480DA**	**1T9482DA**

LED / 19W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
Fixture Power		21W	1	0.25	18153
Source Flux		1779lm	2	0.49	4538
Fixture Flux		1464lm	3	0.74	2017
Efficacy		70lm/W	4	0.99	1135
TS1351	Imax=10204cd/klm	Imax	18153cd	5	1.23	726

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9429EL**	**1T9431EL**	**1T9433EL**	**1T9435EL**
EL.	●	**1T9477EL**	**1T9479EL**	**1T9481EL**	**1T9483EL**
DALI	○	**1T9429DA**	**1T9431DA**	**1T9433DA**	**1T9435DA**
DALI	●	**1T9477DA**	**1T9479DA**	**1T9481DA**	**1T9483DA**

LED / 12W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		14W	1	0.47	5675
Source Flux		1627lm	2	0.94	1419
Fixture Flux		1393lm	3	1.40	631
Efficacy		99lm/W	4	1.87	355
TS1352	Imax=3488cd/klm	Imax	5675cd	5	2.34	227

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9436EL**	**1T9438EL**	**1T9440EL**	**1T9442EL**
EL.	●	**1T9484EL**	**1T9486EL**	**1T9488EL**	**1T9490EL**
DALI	○	**1T9436DA**	**1T9438DA**	**1T9440DA**	**1T9442DA**
DALI	●	**1T9484DA**	**1T9486DA**	**1T9488DA**	**1T9490DA**

LED / 18W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		20W	1	0.47	7628
Source Flux		2187lm	2	0.94	1907
Fixture Flux		1872lm	3	1.40	848
Efficacy		94lm/W	4	1.87	477
TS1353	Imax=3488cd/klm	Imax	7628cd	5	2.34	305

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9437EL**	**1T9439EL**	**1T9441EL**	**1T9443EL**
EL.	●	**1T9485EL**	**1T9487EL**	**1T9489EL**	**1T9491EL**
DALI	○	**1T9437DA**	**1T9439DA**	**1T9441DA**	**1T9443DA**
DALI	●	**1T9485DA**	**1T9487DA**	**1T9489DA**	**1T9491DA**

LED / 12W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power		14W	1	0.75	2647
Source Flux		1627lm	2	1.50	662
Fixture Flux		1309lm	3	2.24	294
Efficacy		93lm/W	4	2.99	165
TS1354	Imax=1661cd/klm	Imax	2702cd	5	3.74	106

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9444EL**	**1T9446EL**	**1T9448EL**	**1T9450EL**
EL.	●	**1T9492EL**	**1T9494EL**	**1T9496EL**	**1T9498EL**
DALI	○	**1T9444DA**	**1T9446DA**	**1T9448DA**	**1T9450DA**
DALI	●	**1T9492DA**	**1T9494DA**	**1T9496DA**	**1T9498DA**

CCTEvo Gimbal

LED / 18W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	20W	1	0.75	3558
Source Flux	2187lm	2	1.50	890
Fixture Flux	1759lm	3	2.24	395
Efficacy	88lm/W	4	2.99	222
Imax	3632cd	5	3.74	142

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T9445EL**	**1T9447EL**	**1T9449EL**	**1T9451EL**
EL.	◐	**1T9493EL**	**1T9495EL**	**1T9497EL**	**1T9499EL**
DALI	○	**1T9445DA**	**1T9447DA**	**1T9449DA**	**1T9451DA**
DALI	◐	**1T9493DA**	**1T9495DA**	**1T9497DA**	**1T9499DA**

Accessories

Filter



Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

OZ Stand Alone

Recessed

GENERAL INFO
Recessed fixed LED single or multi-optic projectors.
Small
Trimless
1x 30x30mm h.50mm
3x 80x30mm h.50mm
5x 130x30mm h.50mm
Trim
1x 35x35mm h.49mm
3x 85x35mm h.49mm
5x 135x35mm h.49mm

Large
Trimless
1x 53x53mm h.61mm
3x 153x53mm h.61mm
5x 253x53mm h.61mm
Trim
1x 60x60mm h.59mm
3x 160x60mm h.59mm
5x 260x60mm h.59mm

LED
LED emitter for the Small version
LED Chip on Board for the Large version
From 224lm to 4260lm
2700K – 3000K – 3500K - 4000K
Ra90

PRODUCT EFFICACY
Up to 99lm/W

OPTICS
SP – FL – MWFL
AM – ELT – ELL

POWER SUPPLY
Electronic remote and DALI driver for the Small versions. Electronic and DALI driver integrated into the body of the fixture for the Large versions.
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
White painted die-cast aluminium body and black polycarbonate frame.

ON DEMAND
Easy Custom Colour
110-277Vac power supply

Single or multiple downlights with miniature optical systems inspired by the 48V Oz version. Available in two different sizes, Small and Large for recessed installations. The range is enriched with the addition of three new optical systems AM for soft and diffused general lighting, ELT and ELL - with a transversal elliptical (ELT) or longitudinal beam (ELL)- , ideal for controlled lighting in corridors and passage ways.

All the optical systems available make Oz Stand Alone suitable for installation in work environments (EN12464-1).

The Large version is also available in a ceiling version with 3x and 5x modules.

		SMALL			LARGE		
		1x	3x	5x	1x	3x	5x
Ambient Optics	AM	•	•	•	•	•	•
Roto-symmetric Optics	SP				•	•	•
	FL	•	•	•	•	•	•
	WFL	•	•	•	•	•	•
Elliptical Optics	ELL		•	•		•	•
	ELT		•	•		•	•

Plus

Small
1x

Small
3x

Small Trimless
1x

Small Trimless
3x

Large
1x

Large
3x

Large Trimless
1x

Large Trimless
3x



Ceiling Luminaire
3x

Oz Stand Alone is also available
in a ceiling version
(see page 148)

Small
5x

Small Trimless
5x

Large
5x

Large Trimless
5x

Ceiling Luminaire
5x

Great variety of solutions

Different solutions in terms of size, aesthetics, performance and installation to provide a valid solution for all project needs.

Very narrow installation depth

Both the Small and the Large versions have a very narrow installation depth. 5cm for Small solutions and 6.1cm for Large solutions.

New optical systems to interpret space

The new optical systems in the Oz Stand Alone range are designed to light space while enhancing flexibility. It is possible to select the desired optical system according to the conformation of the environment and furnishings to obtain comfortable and functional light distribution in compliance with regulations governing lighting in working environments.

The different optical systems available make it possible to interpret space in different ways to satisfy different requirements and tastes.

		SMALL		LARGE	
Ambient Optics	AM	UGR<14		UGR<14	
Roto-symmetric Optics	SP	UGR<13		UGR<17	
	FL	UGR<13		UGR<17	
	WFL	UGR<13		UGR<17	
Elliptical Optics	ELL	UGR<13	UGR<22	UGR<13	UGR<22
	ELT	UGR<22	UGR<13	UGR<22	UGR<13



Transversal Elliptical Optic
(ELT)
for passage ways

Longitudinal Elliptical Optic
(ELL)
for work environments



Longitudinal Elliptical Optic
(ELL)
for passage ways

Longitudinal Elliptical Optic
(ELL)
for work environments



Ambient Optic
(AM)
for passage ways

Longitudinal Elliptical Optic
(ELL)
for work environments

Stand Alone Recessed Small 1X (35x35mm)



LED / 2,6W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	3W	1	0.51	752
Source Flux	236lm	2	1.02	188
Fixture Flux	197lm	3	1.53	84
Efficacy	76lm/W	4	2.04	47
TS1192 Imax=3188cd/klm	Imax 752cd	5	2.55	30

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
900mA		○	**1T7606**	**1T7607**	**1T7608**	**1T7609**
900mA		●	**1T7618**	**1T7619**	**1T7620**	**1T7621**

LED / 2,6W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			56°	
Fixture Power	3W	1	1.07	268
Source Flux	236lm	2	2.14	67
Fixture Flux	198lm	3	3.21	30
Efficacy	76lm/W	4	4.28	17
TS1193 Imax=1171cd/klm	Imax 276cd	5	5.35	11

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
900mA		○	**1T7610**	**1T7611**	**1T7612**	**1T7613**
900mA		●	**1T7622**	**1T7623**	**1T7624**	**1T7625**

LED / 2,6W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			60°	
Fixture Power	3W	1	1.15	189
Source Flux	236lm	2	2.29	47
Fixture Flux	177lm	3	3.44	21
Efficacy	68lm/W	4	4.58	12
TS1244 Imax=870cd/klm	Imax 205cd	5	5.73	8

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
900mA		○	**1T8962**	**1T8963**	**1T8964**	**1T8965**
900mA		●	**1T8966**	**1T8967**	**1T8968**	**1T8969**

Stand Alone Recessed Small 3X (85x35mm)



LED / 5,2W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	5W	1	0.51	1511
Source Flux	474lm	2	1.02	378
Fixture Flux	397lm	3	1.53	168
Efficacy	76lm/W	4	2.04	94
TS1192 Imax=3188cd/klm	Imax 1511cd	5	2.55	60

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T7630**	**1T7631**	**1T7632**	**1T7633**
600mA		●	**1T7642**	**1T7643**	**1T7644**	**1T7645**

OZ

LED / 5,2W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			56°	
Fixture Power	5W	1	1.07	538
Source Flux	474lm	2	2.14	134
Fixture Flux	397lm	3	3.21	60
Efficacy	76lm/W	4	4.28	34
TS1193 Imax=1171cd/klm	Imax	555cd	5	5.35	22

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T7634**	**1T7635**	**1T7636**	**1T7637**
600mA		●	**1T7646**	**1T7647**	**1T7648**	**1T7649**

LED / 5,2W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			60°	
Fixture Power	5W	1	1.15	379
Source Flux	474lm	2	2.29	95
Fixture Flux	356lm	3	3.44	42
Efficacy	69lm/W	4	4.58	24
TS1245 Imax=870cd/klm	Imax	412cd	5	5.73	15

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T8970**	**1T8971**	**1T8972**	**1T8973**
600mA		●	**1T8982**	**1T8983**	**1T8984**	**1T8985**

LED / 5,2W / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			48°	17°	
Fixture Power	5W	1	0.90	0.30	925
Source Flux	474lm	2	1.80	0.61	231
Fixture Flux	336lm	3	2.70	0.91	103
Efficacy	65lm/W	4	3.60	1.22	58
TS1247 Imax=1951cd/klm	Imax	925cd	5	4.50	1.52	37

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T8974**	**1T8975**	**1T8976**	**1T8977**
600mA		●	**1T8986**	**1T8987**	**1T8988**	**1T8989**

LED / 5,2W / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			17°	48°	
Fixture Power	5W	1	0.30	0.90	925
Source Flux	474lm	2	0.61	1.80	231
Fixture Flux	336lm	3	0.91	2.70	103
Efficacy	65lm/W	4	1.22	3.60	58
TS1249 Imax=1951cd/klm	Imax	925cd	5	1.52	4.50	37

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T8978**	**1T8979**	**1T8980**	**1T8981**
600mA		●	**1T8990**	**1T8991**	**1T8992**	**1T8993**

Stand Alone Recessed Small 5X (135x35mm)



LED / 8,7W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	9W	1	0.51	2522
Source Flux	791lm	2	1.02	630
Fixture Flux	662lm	3	1.53	280
Efficacy	76lm/W	4	2.04	158
TS1192 Imax=3188cd/klm	Imax	2522cd	5	2.55	101

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T7654**	**1T7655**	**1T7656**	**1T7657**
600mA		●	**1T7666**	**1T7667**	**1T7668**	**1T7669**

OZ

LED / 8,7W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			56°	
Fixture Power	9W	1	1.07	898
Source Flux	791lm	2	2.14	224
Fixture Flux	663lm	3	3.21	100
Efficacy	76lm/W	4	4.28	56
Imax	926cd	5	5.35	36

TS1193 Imax=1171cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T7658**	**1T7659**	**1T7660**	**1T7661**
600mA		●	**1T7670**	**1T7671**	**1T7672**	**1T7673**

LED / 8,7W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			60°	
Fixture Power	9W	1	1.15	632
Source Flux	791lm	2	2.29	158
Fixture Flux	595lm	3	3.44	70
Efficacy	68lm/W	4	4.58	40
Imax	688cd	5	5.73	25

TS813 Imax=870cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T8994**	**1T8995**	**1T8996**	**1T8997**
600mA		●	**1T9006**	**1T9007**	**1T9008**	**1T9009**

LED / 8,7W / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			48°	17°	
Fixture Power	9W	1	0.90	0.30	1544
Source Flux	791lm	2	1.80	0.61	386
Fixture Flux	561lm	3	2.70	0.91	172
Efficacy	64lm/W	4	3.60	1.22	96
Imax	1544cd	5	4.50	1.52	62

TS1248 Imax=1951cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T8998**	**1T8999**	**1T9000**	**1T9001**
600mA		●	**1T9010**	**1T9011**	**1T9012**	**1T9013**

LED / 8,7W / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			17°	48°	
Fixture Power	9W	1	0.30	0.90	1544
Source Flux	791lm	2	0.61	1.80	386
Fixture Flux	561lm	3	0.91	2.70	172
Efficacy	64lm/W	4	1.22	3.60	96
Imax	1544cd	5	1.52	4.50	62

TS1250 Imax=1951cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
600mA		○	**1T9002**	**1T9003**	**1T9004**	**1T9005**
600mA		●	**1T9014**	**1T9015**	**1T9016**	**1T9017**

Stand Alone Recessed Large 1X (60x60mm)



LED / 6W / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	7W	1	0.33	3138
Source Flux	656lm	2	0.66	785
Fixture Flux	513lm	3	0.99	349
Efficacy	74lm/W	4	1.32	196
Imax	3138cd	5	1.65	126

TS1194 Imax=4784cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7746EL**	**1T7747EL**	**1T7748EL**	**1T7749EL**
220-240Vac	EL.	●	**1T7758EL**	**1T7759EL**	**1T7760EL**	**1T7761EL**
220-240Vac	DALI	○	**1T7746DA**	**1T7747DA**	**1T7748DA**	**1T7749DA**
220-240Vac	DALI	●	**1T7758DA**	**1T7759DA**	**1T7760DA**	**1T7761DA**

OZ

LED / 6W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			34°	
Fixture Power		7W	1	0.61	1748
Source Flux		839lm	2	1.22	437
Fixture Flux		599lm	3	1.83	194
Efficacy		87lm/W	4	2.43	109
TS1195	Imax=2083cd/klm	Imax	1748cd	5	3.04	70

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7750EL**	**1T7751EL**	**1T7752EL**	**1T7753EL**
220-240Vac	EL.	●	**1T7762EL**	**1T7763EL**	**1T7764EL**	**1T7765EL**
220-240Vac	DALI	○	**1T7750DA**	**1T7751DA**	**1T7752DA**	**1T7753DA**
220-240Vac	DALI	●	**1T7762DA**	**1T7763DA**	**1T7764DA**	**1T7765DA**

LED / 6W / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			50°	
Fixture Power		7W	1	0.93	1052
Source Flux		839lm	2	1.85	263
Fixture Flux		649lm	3	2.78	117
Efficacy		94lm/W	4	3.71	66
TS1196	Imax=1254cd/klm	Imax	1052cd	5	4.64	42

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7754EL**	**1T7755EL**	**1T7756EL**	**1T7757EL**
220-240Vac	EL.	●	**1T7766EL**	**1T7767EL**	**1T7768EL**	**1T7769EL**
220-240Vac	DALI	○	**1T7754DA**	**1T7755DA**	**1T7756DA**	**1T7757DA**
220-240Vac	DALI	●	**1T7766DA**	**1T7767DA**	**1T7768DA**	**1T7769DA**

LED / 6W / AM



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			49°	
Fixture Power		7W	1	0.92	967
Source Flux		839lm	2	1.83	242
Fixture Flux		601lm	3	2.75	107
Efficacy		87lm/W	4	3.67	60
TS1251	Imax=1153cd/klm	Imax	967cd	5	4.59	39

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T8482EL**	**1T8483EL**	**1T8484EL**	**1T8485EL**
220-240Vac	EL.	●	**1T8486EL**	**1T8487EL**	**1T8488EL**	**1T8489EL**
220-240Vac	DALI	○	**1T8482DA**	**1T8483DA**	**1T8484DA**	**1T8485DA**
220-240Vac	DALI	●	**1T8486DA**	**1T8487DA**	**1T8488DA**	**1T8489DA**

Stand Alone Recessed Large 3X (160x60mm)



LED / 18W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		20W	1	0.33	9415
Source Flux		1968lm	2	0.66	2354
Fixture Flux		1538lm	3	0.99	1046
Efficacy		77lm/W	4	1.32	588
TS1194	Imax=4784cd/klm	Imax	9415cd	5	1.65	377

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7770EL**	**1T7771EL**	**1T7772EL**	**1T7773EL**
220-240Vac	EL.	●	**1T7782EL**	**1T7783EL**	**1T7784EL**	**1T7785EL**
220-240Vac	DALI	○	**1T7770DA**	**1T7771DA**	**1T7772DA**	**1T7773DA**
220-240Vac	DALI	●	**1T7782DA**	**1T7783DA**	**1T7784DA**	**1T7785DA**

LED / 18W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			34°	
Fixture Power		20W	1	0.61	5243
Source Flux		2517lm	2	1.22	1311
Fixture Flux		1797lm	3	1.83	583
Efficacy		90lm/W	4	2.43	328
TS1195	Imax=2083cd/klm	Imax	5243cd	5	3.04	210

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7774EL**	**1T7775EL**	**1T7776EL**	**1T7777EL**
220-240Vac	EL.	●	**1T7786EL**	**1T7787EL**	**1T7788EL**	**1T7789EL**
220-240Vac	DALI	○	**1T7774DA**	**1T7775DA**	**1T7776DA**	**1T7777DA**
220-240Vac	DALI	●	**1T7786DA**	**1T7787DA**	**1T7788DA**	**1T7789DA**

OZ

LED / 18W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			50°	
Fixture Power	20W	1	0.93	3157
Source Flux	2517lm	2	1.85	789
Fixture Flux	1947lm	3	2.78	351
Efficacy	97lm/W	4	3.71	197
Imax	3157cd	5	4.64	126

TS1196 Imax=1254cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7778EL**	**1T7779EL**	**1T7780EL**	**1T7781EL**
220-240Vac	EL.	●	**1T7790EL**	**1T7791EL**	**1T7792EL**	**1T7793EL**
220-240Vac	DALI	○	**1T7778DA**	**1T7779DA**	**1T7780DA**	**1T7781DA**
220-240Vac	DALI	●	**1T7790DA**	**1T7791DA**	**1T7792DA**	**1T7793DA**

LED / 18W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	20W	1	0.92	2902
Source Flux	2517lm	2	1.83	726
Fixture Flux	1804lm	3	2.75	322
Efficacy	90lm/W	4	3.67	181
Imax	2902cd	5	4.59	116

TS1252 Imax=1153cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T8490EL**	**1T8491EL**	**1T8492EL**	**1T8493EL**
220-240Vac	EL.	●	**1T8526EL**	**1T8527EL**	**1T8528EL**	**1T8529EL**
220-240Vac	DALI	○	**1T8490DA**	**1T8491DA**	**1T8492DA**	**1T8493DA**
220-240Vac	DALI	●	**1T8526DA**	**1T8527DA**	**1T8528DA**	**1T8529DA**

LED / 18W / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			25°	58°	
Fixture Power	20W	1	0.44	1.11	3209
Source Flux	2280lm	2	0.88	2.21	802
Fixture Flux	1641lm	3	1.32	3.32	357
Efficacy	82lm/W	4	1.76	4.43	201
Imax	3209cd	5	2.19	5.54	128

TS1254 Imax=1408cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T8518EL**	**1T8519EL**	**1T8520EL**	**1T8521EL**
220-240Vac	EL.	●	**1T8530EL**	**1T8531EL**	**1T8532EL**	**1T8533EL**
220-240Vac	DALI	○	**1T8518DA**	**1T8519DA**	**1T8520DA**	**1T8521DA**
220-240Vac	DALI	●	**1T8530DA**	**1T8531DA**	**1T8532DA**	**1T8533DA**

LED / 18W / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			58°	25°	
Fixture Power	20W	1	1.11	0.44	3209
Source Flux	2280lm	2	2.21	0.88	802
Fixture Flux	1641lm	3	3.32	1.32	357
Efficacy	82lm/W	4	4.43	1.76	201
Imax	3209cd	5	5.54	2.19	128

TS1256 Imax=1408cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T8522EL**	**1T8523EL**	**1T8524EL**	**1T8525EL**
220-240Vac	EL.	●	**1T8534EL**	**1T8535EL**	**1T8536EL**	**1T8537EL**
220-240Vac	DALI	○	**1T8522DA**	**1T8523DA**	**1T8524DA**	**1T8525DA**
220-240Vac	DALI	●	**1T8534DA**	**1T8535DA**	**1T8536DA**	**1T8537DA**

Stand Alone Recessed Large 5X (260x60mm)



LED / 30W / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	34W	1	0.33	15692
Source Flux	3280lm	2	0.66	3923
Fixture Flux	2563lm	3	0.99	1744
Efficacy	75lm/W	4	1.32	981
Imax	15692cd	5	1.65	628

TS1194 Imax=4784cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7794EL**	**1T7795EL**	**1T7796EL**	**1T7797EL**
220-240Vac	EL.	●	**1T7806EL**	**1T7807EL**	**1T7808EL**	**1T7809EL**
220-240Vac	DALI	○	**1T7794DA**	**1T7795DA**	**1T7796DA**	**1T7797DA**
220-240Vac	DALI	●	**1T7806DA**	**1T7807DA**	**1T7808DA**	**1T7809DA**

OZ

LED / 30W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			34°	
Fixture Power	34W	1	0.61	8739
Source Flux	4195lm	2	1.22	2185
Fixture Flux	2996lm	3	1.83	971
Efficacy	88lm/W	4	2.43	546
Imax	8739cd	5	3.04	350

TS1195 Imax=2083cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7798EL**	**1T7799EL**	**1T7800EL**	**1T7801EL**
220-240Vac	EL.	●	**1T7810EL**	**1T7811EL**	**1T7812EL**	**1T7813EL**
220-240Vac	DALI	○	**1T7798DA**	**1T7799DA**	**1T7800DA**	**1T7801DA**
220-240Vac	DALI	●	**1T7810DA**	**1T7811DA**	**1T7812DA**	**1T7813DA**

LED / 30W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			50°	
Fixture Power	34W	1	0.93	5262
Source Flux	4195lm	2	1.85	1315
Fixture Flux	3246lm	3	2.78	585
Efficacy	95lm/W	4	3.71	329
Imax	5262cd	5	4.64	210

TS1196 Imax=1254cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T7802EL**	**1T7803EL**	**1T7804EL**	**1T7805EL**
220-240Vac	EL.	●	**1T7814EL**	**1T7815EL**	**1T7816EL**	**1T7817EL**
220-240Vac	DALI	○	**1T7802DA**	**1T7803DA**	**1T7804DA**	**1T7805DA**
220-240Vac	DALI	●	**1T7814DA**	**1T7815DA**	**1T7816DA**	**1T7817DA**

LED / 30W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	34W	1	0.92	4837
Source Flux	4195lm	2	1.83	1209
Fixture Flux	3007lm	3	2.75	537
Efficacy	88lm/W	4	3.67	302
Imax	4837cd	5	4.59	193

TS1253 Imax=1153cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T8538EL**	**1T8539EL**	**1T8540EL**	**1T8541EL**
220-240Vac	EL.	●	**1T8858EL**	**1T8859EL**	**1T8860EL**	**1T8861EL**
220-240Vac	DALI	○	**1T8538DA**	**1T8539DA**	**1T8540DA**	**1T8541DA**
220-240Vac	DALI	●	**1T8858DA**	**1T8859DA**	**1T8860DA**	**1T8861DA**

LED / 30W / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			25°	58°	
Fixture Power	34W	1	0.44	1.11	5349
Source Flux	3800lm	2	0.88	2.21	1337
Fixture Flux	2735lm	3	1.32	3.32	594
Efficacy	80lm/W	4	1.76	4.43	334
Imax	5349cd	5	2.19	5.54	214

TS1255 Imax=1408cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T8850EL**	**1T8851EL**	**1T8852EL**	**1T8853EL**
220-240Vac	EL.	●	**1T8862EL**	**1T8863EL**	**1T8864EL**	**1T8865EL**
220-240Vac	DALI	○	**1T8850DA**	**1T8851DA**	**1T8852DA**	**1T8853DA**
220-240Vac	DALI	●	**1T8862DA**	**1T8863DA**	**1T8864DA**	**1T8865DA**

LED / 30W / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			58°	25°	
Fixture Power	34W	1	1.11	0.44	5349
Source Flux	3800lm	2	2.21	0.88	1337
Fixture Flux	2735lm	3	3.32	1.32	594
Efficacy	80lm/W	4	4.43	1.76	334
Imax	5349cd	5	5.54	2.19	214

TS1257 Imax=1408cd/klm

Power supply	Driver	Colour	2700K	3000K	3500K	4000K
220-240Vac	EL.	○	**1T8854EL**	**1T8855EL**	**1T8856EL**	**1T8857EL**
220-240Vac	EL.	●	**1T8866EL**	**1T8867EL**	**1T8868EL**	**1T8869EL**
220-240Vac	DALI	○	**1T8854DA**	**1T8855DA**	**1T8856DA**	**1T8857DA**
220-240Vac	DALI	●	**1T8866DA**	**1T8867DA**	**1T8868DA**	**1T8869DA**

Note

Small version: to be completed with an electronic or DALI driver. Values relating to the power of the fixture do not take into account the absorption of the accessory driver. This value depends on the choice of driver.

OZ

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
110x22x52	20W	110-240Vac	600mA	IP20	**1T8172EL**
110x22x52	20W	110-240Vac	900mA	IP20	**1T5295EL**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
156x26x52	20W	230Vac	600mA	IP20	**1T8172DA**
156x26x52	20W	230Vac	900mA	IP20	**1T7686DA**

DALI power supply.

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.



Stand Alone Trimless Small 1X (30x30mm)



LED / 2,6W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	3W	1	0.51	752
Source Flux	236lm	2	1.02	188
Fixture Flux	197lm	3	1.53	84
Efficacy	76lm/W	4	2.04	47
TS1192 Imax=3188cd/klm	Imax	752cd	5	2.55	30

Power supply	Driver	2700K	3000K	3500K	4000K
900mA		**1T7678**	**1T7679**	**1T7680**	**1T7681**

LED / 2,6W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			56°	
Fixture Power	3W	1	1.07	268
Source Flux	236lm	2	2.14	67
Fixture Flux	198lm	3	3.21	30
Efficacy	76lm/W	4	4.28	17
TS1193 Imax=1171cd/klm	Imax	276cd	5	5.35	11

Power supply	Driver	2700K	3000K	3500K	4000K
900mA		**1T7682**	**1T7683**	**1T7684**	**1T7685**

LED / 2,6W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			60°	
Fixture Power	3W	1	1.15	189
Source Flux	236lm	2	2.29	47
Fixture Flux	177lm	3	3.44	21
Efficacy	68lm/W	4	4.58	12
TS1244 Imax=870cd/klm	Imax	205cd	5	5.73	8

Power supply	Driver	2700K	3000K	3500K	4000K
900mA		**1T9018**	**1T9019**	**1T9020**	**1T9021**

Stand Alone Trimless Small 3X (80x30mm)



LED / 5,2W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	5W	1	0.51	1511
Source Flux	474lm	2	1.02	378
Fixture Flux	397lm	3	1.53	168
Efficacy	76lm/W	4	2.04	94
TS1192 Imax=3188cd/klm	Imax	1511cd	5	2.55	60

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T7702**	**1T7703**	**1T7704**	**1T7705**

OZ

LED / 5,2W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			56°	
Fixture Power	5W	1	1.07	538
Source Flux	474lm	2	2.14	134
Fixture Flux	397lm	3	3.21	60
Efficacy	76lm/W	4	4.28	34
Imax	555cd	5	5.35	22

TS1193 Imax=1171cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T7706**	**1T7707**	**1T7708**	**1T7709**

LED / 5,2W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			60°	
Fixture Power	5W	1	1.15	379
Source Flux	474lm	2	2.29	95
Fixture Flux	356lm	3	3.44	42
Efficacy	69lm/W	4	4.58	24
Imax	412cd	5	5.73	15

TS1245 Imax=870cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T9022**	**1T9023**	**1T9024**	**1T9025**

LED / 5,2W / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			48°	17°	
Fixture Power	5W	1	0.90	0.30	925
Source Flux	474lm	2	1.80	0.61	231
Fixture Flux	336lm	3	2.70	0.91	103
Efficacy	65lm/W	4	3.60	1.22	58
Imax	925cd	5	4.50	1.52	37

TS1247 Imax=1951cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T9026**	**1T9027**	**1T9028**	**1T9029**

LED / 5,2W / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			17°	48°	
Fixture Power	5W	1	0.30	0.90	925
Source Flux	474lm	2	0.61	1.80	231
Fixture Flux	336lm	3	0.91	2.70	103
Efficacy	65lm/W	4	1.22	3.60	58
Imax	925cd	5	1.52	4.50	37

TS1249 Imax=1951cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T9030**	**1T9031**	**1T9032**	**1T9033**

Stand Alone Trimless Small 5X (130x30mm)



LED / 8,7W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			29°	
Fixture Power	9W	1	0.51	2522
Source Flux	791lm	2	1.02	630
Fixture Flux	662lm	3	1.53	280
Efficacy	76lm/W	4	2.04	158
Imax	2522cd	5	2.55	101

TS1192 Imax=3188cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T7726**	**1T7727**	**1T7728**	**1T7729**

OZ

LED / 8,7W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			56°	
Fixture Power	9W	1	1.07	898
Source Flux	791lm	2	2.14	224
Fixture Flux	663lm	3	3.21	100
Efficacy	76lm/W	4	4.28	56
Imax	926cd	5	5.35	36

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T7730**	**1T7731**	**1T7732**	**1T7733**

LED / 8,7W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			60°	
Fixture Power	9W	1	1.15	632
Source Flux	791lm	2	2.29	158
Fixture Flux	595lm	3	3.44	70
Efficacy	68lm/W	4	4.58	40
Imax	688cd	5	5.73	25

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T9034**	**1T9035**	**1T9036**	**1T9037**

LED / 8,7W / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			48°	17°	
Fixture Power	9W	1	0.90	0.30	1544
Source Flux	791lm	2	1.80	0.61	386
Fixture Flux	561lm	3	2.70	0.91	172
Efficacy	64lm/W	4	3.60	1.22	96
Imax	1544cd	5	4.50	1.52	62

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T9038**	**1T9039**	**1T9040**	**1T9041**

LED / 8,7W / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			17°	48°	
Fixture Power	9W	1	0.30	0.90	1544
Source Flux	791lm	2	0.61	1.80	386
Fixture Flux	561lm	3	0.91	2.70	172
Efficacy	64lm/W	4	1.22	3.60	96
Imax	1544cd	5	1.52	4.50	62

Power supply	Driver	2700K	3000K	3500K	4000K
600mA		**1T9042**	**1T9043**	**1T9044**	**1T9045**

Stand Alone Trimless Large 1X (53x53mm)



LED / 6W / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	7W	1	0.33	3138
Source Flux	656lm	2	0.66	785
Fixture Flux	513lm	3	0.99	349
Efficacy	74lm/W	4	1.32	196
Imax	3138cd	5	1.65	126

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7818EL**	**1T7819EL**	**1T7820EL**	**1T7821EL**
220-240Vac	DALI	**1T7818DA**	**1T7819DA**	**1T7820DA**	**1T7821DA**

OZ

LED / 6W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			34°	
Fixture Power	7W	1	0.61	1748
Source Flux	839lm	2	1.22	437
Fixture Flux	599lm	3	1.83	194
Efficacy	87lm/W	4	2.43	109
TS1195 Imax=2083cd/klm	Imax 1748cd	5	3.04	70

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7822EL**	**1T7823EL**	**1T7824EL**	**1T7825EL**
220-240Vac	DALI	**1T7822DA**	**1T7823DA**	**1T7824DA**	**1T7825DA**

LED / 6W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			50°	
Fixture Power	7W	1	0.93	1052
Source Flux	839lm	2	1.85	263
Fixture Flux	649lm	3	2.78	117
Efficacy	94lm/W	4	3.71	66
TS1196 Imax=1254cd/klm	Imax 1052cd	5	4.64	42

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7826EL**	**1T7827EL**	**1T7828EL**	**1T7829EL**
220-240Vac	DALI	**1T7826DA**	**1T7827DA**	**1T7828DA**	**1T7829DA**

LED / 6W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	7W	1	0.92	967
Source Flux	839lm	2	1.83	242
Fixture Flux	601lm	3	2.75	107
Efficacy	87lm/W	4	3.67	60
TS1251 Imax=1153cd/klm	Imax 967cd	5	4.59	39

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T8870EL**	**1T8871EL**	**1T8872EL**	**1T8873EL**
220-240Vac	DALI	**1T8870DA**	**1T8871DA**	**1T8872DA**	**1T8873DA**

Stand Alone Trimless Large 3X (153x53mm)



LED / 18W / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	20W	1	0.33	9415
Source Flux	1968lm	2	0.66	2354
Fixture Flux	1538lm	3	0.99	1046
Efficacy	77lm/W	4	1.32	588
TS1194 Imax=4784cd/klm	Imax 9415cd	5	1.65	377

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7842EL**	**1T7843EL**	**1T7844EL**	**1T7845EL**
220-240Vac	DALI	**1T7842DA**	**1T7843DA**	**1T7844DA**	**1T7845DA**

LED / 18W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			34°	
Fixture Power	20W	1	0.61	5243
Source Flux	2517lm	2	1.22	1311
Fixture Flux	1797lm	3	1.83	583
Efficacy	90lm/W	4	2.43	328
TS1195 Imax=2083cd/klm	Imax 5243cd	5	3.04	210

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7846EL**	**1T7847EL**	**1T7848EL**	**1T7849EL**
220-240Vac	DALI	**1T7846DA**	**1T7847DA**	**1T7848DA**	**1T7849DA**

OZ

LED / 18W / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			50°	
Fixture Power		20W	1	0.93	3157
Source Flux		2517lm	2	1.85	789
Fixture Flux		1947lm	3	2.78	351
Efficacy		97lm/W	4	3.71	197
Imax		3157cd	5	4.64	126

TS1196 Imax=1254cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7850EL**	**1T7851EL**	**1T7852EL**	**1T7853EL**
220-240Vac	DALI	**1T7850DA**	**1T7851DA**	**1T7852DA**	**1T7853DA**

LED / 18W / AM



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			49°	
Fixture Power		20W	1	0.92	2902
Source Flux		2517lm	2	1.83	726
Fixture Flux		1804lm	3	2.75	322
Efficacy		90lm/W	4	3.67	181
Imax		2902cd	5	4.59	116

TS1252 Imax=1153cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T8874EL**	**1T8875EL**	**1T8876EL**	**1T8877EL**
220-240Vac	DALI	**1T8874DA**	**1T8875DA**	**1T8876DA**	**1T8877DA**

LED / 18W / ELL



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			25°	58°	
Fixture Power		20W	1	0.44	1.11	3209
Source Flux		2280lm	2	0.88	2.21	802
Fixture Flux		1641lm	3	1.32	3.32	357
Efficacy		82lm/W	4	1.76	4.43	201
Imax		3209cd	5	2.19	5.54	128

TS1254 Imax=1408cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T8878EL**	**1T8879EL**	**1T8880EL**	**1T8881EL**
220-240Vac	DALI	**1T8878DA**	**1T8879DA**	**1T8880DA**	**1T8881DA**

LED / 18W / ELT



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			58°	25°	
Fixture Power		20W	1	1.11	0.44	3209
Source Flux		2280lm	2	2.21	0.88	802
Fixture Flux		1641lm	3	3.32	1.32	357
Efficacy		82lm/W	4	4.43	1.76	201
Imax		3209cd	5	5.54	2.19	128

TS1256 Imax=1408cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T8882EL**	**1T8883EL**	**1T8884EL**	**1T8885EL**
220-240Vac	DALI	**1T8882DA**	**1T8883DA**	**1T8884DA**	**1T8885DA**

Stand Alone Trimless Large 5X (253x53mm)



LED / 30W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		34W	1	0.33	15692
Source Flux		3280lm	2	0.66	3923
Fixture Flux		2563lm	3	0.99	1744
Efficacy		75lm/W	4	1.32	981
Imax		15692cd	5	1.65	628

TS1194 Imax=4784cd/klm

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7866EL**	**1T7867EL**	**1T7868EL**	**1T7869EL**
220-240Vac	DALI	**1T7866DA**	**1T7867DA**	**1T7868DA**	**1T7869DA**

OZ

LED / 30W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			34°	
Fixture Power	34W	1	0.61	8739
Source Flux	4195lm	2	1.22	2185
Fixture Flux	2996lm	3	1.83	971
Efficacy	88lm/W	4	2.43	546
TS1195 Imax=2083cd/klm	Imax	8739cd	5	3.04	350

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7870EL**	**1T7871EL**	**1T7872EL**	**1T7873EL**
220-240Vac	DALI	**1T7870DA**	**1T7871DA**	**1T7872DA**	**1T7873DA**

LED / 30W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			50°	
Fixture Power	34W	1	0.93	5262
Source Flux	4195lm	2	1.85	1315
Fixture Flux	3246lm	3	2.78	585
Efficacy	95lm/W	4	3.71	329
TS1196 Imax=1254cd/klm	Imax	5262cd	5	4.64	210

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T7874EL**	**1T7875EL**	**1T7876EL**	**1T7877EL**
220-240Vac	DALI	**1T7874DA**	**1T7875DA**	**1T7876DA**	**1T7877DA**

LED / 30W / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	34W	1	0.92	4837
Source Flux	4195lm	2	1.83	1209
Fixture Flux	3007lm	3	2.75	537
Efficacy	88lm/W	4	3.67	302
TS1253 Imax=1153cd/klm	Imax	4837cd	5	4.59	193

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T8886EL**	**1T8887EL**	**1T8888EL**	**1T8889EL**
220-240Vac	DALI	**1T8886DA**	**1T8887DA**	**1T8888DA**	**1T8889DA**

LED / 30W / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			25°	58°	
Fixture Power	34W	1	0.44	1.11	5349
Source Flux	3800lm	2	0.88	2.21	1337
Fixture Flux	2735lm	3	1.32	3.32	594
Efficacy	80lm/W	4	1.76	4.43	334
TS1255 Imax=1408cd/klm	Imax	5349cd	5	2.19	5.54	214

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T8890EL**	**1T8891EL**	**1T8892EL**	**1T8893EL**
220-240Vac	DALI	**1T8890DA**	**1T8891DA**	**1T8892DA**	**1T8893DA**

LED / 30W / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			58°	25°	
Fixture Power	34W	1	1.11	0.44	5349
Source Flux	3800lm	2	2.21	0.88	1337
Fixture Flux	2735lm	3	3.32	1.32	594
Efficacy	80lm/W	4	4.43	1.76	334
TS1257 Imax=1408cd/klm	Imax	5349cd	5	5.54	2.19	214

Power supply	Driver	2700K	3000K	3500K	4000K
220-240Vac	EL.	**1T8894EL**	**1T8895EL**	**1T8896EL**	**1T8897EL**
220-240Vac	DALI	**1T8894DA**	**1T8895DA**	**1T8896DA**	**1T8897DA**

Note

Small version: to be completed with an electronic or DALI driver. Values relating to the power of the fixture do not take into account the absorption of the accessory driver. This value depends on the choice of driver.

OZ

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
110x22x52	20W	110-240Vac	600mA	IP20	**1T8172EL**
110x22x52	20W	110-240Vac	900mA	IP20	**1T5295EL**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
156x26x52	20W	230Vac	600mA	IP20	**1T8172DA**
156x26x52	20W	230Vac	900mA	IP20	**1T7686DA**

DALI power supply.

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

T-PANEL

GENERAL INFO
Direct emission Led fixtures available in two different sizes
595x595x9mm
295x1195x9mm

LED
Ra90 high efficiency LED
From 3008 lm to 3200 lm
4000K

PRODUCT EFFICACY
Up to 128lm/W

OPTICS
UGR

POWER SUPPLY
DALI - Casambi

MATERIAL
Painted white aluminium body; high transmittance optical PMMA screen with UGR<19 controlled luminance.

A range of high-efficiency, excellent performance, direct emission LED fixtures ideal for lighting working environments. Available in two different sizes – 595x595 and 295x1195 – T-Panel fixtures have an aluminium body that allows for surface installation on modular panels of 600x600mm and 300x1200mm. The PMMA optical screen makes it possible to perfectly control the emission of the fixtures making them suitable for installation in work environments – UGR<19 (EN12464-1) L65<3000 cd/m^2.

All fixtures in the range are equipped with anti-fall safety cables and quick connection terminal blocks.

Using special frame accessories it is possible to install T-Panels directly on the ceiling while the cable kit allows for suspension installation. Emergency kit available as an accessory.

Accessory for installation on continuous ceilings available on request.

T-PANEL

T-Panel Recessed



LED / 21W / UGR



	4000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			93°	91°	
Fixture Power		25W	1	2.10	2.04	1487
Source Flux		3200lm	2	4.19	4.08	372
Fixture Flux		3200lm	3	6.29	6.12	165
Efficacy		128lm/W	4	8.38	8.16	93
Imax		1532cd	5	10.48	10.20	59

Driver	Colour	4000K
DALI	◯	**1T9585DA**

T-Panel Recessed



LED / 21W / UGR



	4000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			93°	91°	
Fixture Power		25W	1	2.10	2.04	1398
Source Flux		3008lm	2	4.19	4.08	349
Fixture Flux		3008lm	3	6.29	6.12	155
Efficacy		120lm/W	4	8.38	8.16	87
Imax		1440cd	5	10.48	10.20	56

Driver	Colour	4000K
DALI	◯	**1T9586DA**

Accessories

Mounting System

	Code
	1T9589

Ceiling installation kit.
595x595mm version.
Sizes 602x602x60mm.

	Code
	1T9590

Ceiling installation kit.
295x1195mm version.
Sizes 310x1210x60mm.

T-PANEL

	Code
	1T9588

Kit of 4 suspension cables.
L=1500mm.

Power Supply Kit



	L	Driver	Colour	Code
	4000	DALI	◯	**1T5905DA**

Suspension installation kit: power cable complete with a painted polycarbonate rosette.
Max 0.6kW.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Emergency Kit

	Code
	1T9591

Emergency kit for reserve lighting.
3 hours battery life.
7% residual flux in emergency lighting.
LxHxP=166.5x25x46mm.

STORE

Gimbal

GENERAL INFO
Recessed adjustable projector.
Gimbal System to adjust the optical unit 30° vertically and 355° horizontally.

LED
Chip on board
From 200lm to 4385lm
3000K – 4000K
Ra84 - Ra97

PRODUCT EFFICACY
Up to 119lm/W

OPTICS
NSP – SP – FL – MWFL – WFL

OPTICS
Electronic - DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Painted die-cast aluminium projector body and external ring.
Polycarbonate internal ring.

ON DEMAND

Easy custom color

110-277Vac power supply

Ra90

Range of recessed fixtures available in two different sizes, designed to meet the particular needs of the retail market where excellent performance, minimal design and controlled light are required.

The light units can be single, and multi-optic 1x, 2x and 3x. Mini versions available with a frame with a Trimless finish.

Also available in a projector version.

	STORE with springs	STORE with magnets	STORE MINI with springs	STORE MINI with magnets
	160x160mm	160x160mm	145x145mm	145x145mm
1x	without a frame	only with a frame accessory	with or without a trimless frame accessory	only with a frame accessory
2x	no	only with a frame accessory	with or without a trimless frame accessory	only with a frame accessory
3x	no	only with a frame accessory	with or without a trimless frame accessory	only with a frame accessory

Bruyninx DS Store
Hasselt, Belgium

Photographer Eddy Vanoppen

Gimbal
Versions with springs



LED / 19W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		22W	1	0.24	23022
Source Flux		2935lm	2	0.48	5755
Fixture Flux		2494lm	3	0.72	2558
Efficacy		112lm/W	4	0.96	1439
TS947	Imax=7844cd/klm	Imax	23022cd	5	1.20	921

Driver	Colour	3000K	4000K
EL.	○	**1T5114EL**	**1T5116EL**
EL.	●	**1T5098EL**	**1T5100EL**
DALI	○	**1T5114DA**	**1T5116DA**
DALI	●	**1T5098DA**	**1T5100DA**

LED / 19W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		22W	1	0.24	17704
Source Flux		2257lm	2	0.48	4426
Fixture Flux		1918lm	3	0.72	1967
Efficacy		86lm/W	4	0.96	1106
TS947	Imax=7844cd/klm	Imax	17704cd	5	1.20	708

Driver	Colour	3000K	4000K
EL.	○	**1T5115EL**	**1T5117EL**
EL.	●	**1T5099EL**	**1T5101EL**
DALI	○	**1T5115DA**	**1T5117DA**
DALI	●	**1T5099DA**	**1T5101DA**

LED / 19W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			27°	
Fixture Power		22W	1	0.49	9061
Source Flux		2935lm	2	0.97	2265
Fixture Flux		2486lm	3	1.46	1007
Efficacy		112lm/W	4	1.95	566
TS948	Imax=3087cd/klm	Imax	9061cd	5	2.43	362

Driver	Colour	3000K	4000K
EL.	○	**1T5118EL**	**1T5120EL**
EL.	●	**1T5102EL**	**1T5104EL**
DALI	○	**1T5118DA**	**1T5120DA**
DALI	●	**1T5102DA**	**1T5104DA**

LED / 19W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			27°	
Fixture Power		22W	1	0.49	6968
Source Flux		2257lm	2	0.97	1742
Fixture Flux		1912lm	3	1.46	774
Efficacy		86lm/W	4	1.95	435
TS948	Imax=3087cd/klm	Imax	6968cd	5	2.43	279

Driver	Colour	3000K	4000K
EL.	○	**1T5119EL**	**1T5121EL**
EL.	●	**1T5103EL**	**1T5105EL**
DALI	○	**1T5119DA**	**1T5121DA**
DALI	●	**1T5103DA**	**1T5105DA**

LED / 19W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		22W	1	0.82	4770
Source Flux		2935lm	2	1.64	1193
Fixture Flux		2550lm	3	2.46	530
Efficacy		115lm/W	4	3.28	298
TS949	Imax=1655cd/klm	Imax	4856cd	5	4.10	191

Driver	Colour	3000K	4000K
EL.	○	**1T5122EL**	**1T5124EL**
EL.	●	**1T5106EL**	**1T5108EL**
DALI	○	**1T5122DA**	**1T5124DA**
DALI	●	**1T5106DA**	**1T5108DA**

STORE

LED / 19W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
Fixture Power		22W	1	0.82	3668
Source Flux		2257lm	2	1.64	917
Fixture Flux		1961lm	3	2.46	408
Efficacy		88lm/W	4	3.28	229
TS949	Imax=1655cd/klm	Imax	3734cd	5	4.10	147

Driver	Colour	3000K	4000K
EL.	○	**1T5123EL**	**1T5125EL**
EL.	●	**1T5107EL**	**1T5109EL**
DALI	○	**1T5123DA**	**1T5125DA**
DALI	●	**1T5107DA**	**1T5109DA**

LED / 19W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			59°	
Fixture Power		22W	1	1.13	3318
Source Flux		2935lm	2	2.26	830
Fixture Flux		2585lm	3	3.39	369
Efficacy		116lm/W	4	4.51	207
TS950	Imax=1141cd/klm	Imax	3350cd	5	5.64	133

Driver	Colour	3000K	4000K
EL.	○	**1T5126EL**	**1T5128EL**
EL.	●	**1T5110EL**	**1T5112EL**
DALI	○	**1T5126DA**	**1T5128DA**
DALI	●	**1T5110DA**	**1T5112DA**

LED / 19W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power		22W	1	1.13	2552
Source Flux		2257lm	2	2.26	638
Fixture Flux		1988lm	3	3.39	284
Efficacy		90lm/W	4	4.51	159
TS950	Imax=1141cd/klm	Imax	2576cd	5	5.64	102

Driver	Colour	3000K	4000K
EL.	○	**1T5127EL**	**1T5129EL**
EL.	●	**1T5111EL**	**1T5113EL**
DALI	○	**1T5127DA**	**1T5129DA**
DALI	●	**1T5111DA**	**1T5113DA**

LED / 33W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		36W	1	0.24	33552
Source Flux		4277lm	2	0.48	8388
Fixture Flux		3635lm	3	0.72	3728
Efficacy		102lm/W	4	0.96	2097
TS951	Imax=7845cd/klm	Imax	33552cd	5	1.20	1342

Driver	Colour	3000K	4000K
EL.	○	**1T5146EL**	**1T5148EL**
EL.	●	**1T5130EL**	**1T5132EL**
DALI	○	**1T5146DA**	**1T5148DA**
DALI	●	**1T5130DA**	**1T5132DA**

LED / 33W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		36W	1	0.24	25809
Source Flux		3290lm	2	0.48	6452
Fixture Flux		2796lm	3	0.72	2868
Efficacy		78lm/W	4	0.96	1613
TS951	Imax=7845cd/klm	Imax	25809cd	5	1.20	1032

Driver	Colour	3000K	4000K
EL.	○	**1T5147EL**	**1T5149EL**
EL.	●	**1T5131EL**	**1T5133EL**
DALI	○	**1T5147DA**	**1T5149DA**
DALI	●	**1T5131DA**	**1T5133DA**

LED / 33W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			27°	
Fixture Power		36W	1	0.49	13204
Source Flux		4277lm	2	0.97	3301
Fixture Flux		3622lm	3	1.46	1467
Efficacy		101lm/W	4	1.95	825
TS952	Imax=3087cd/klm	Imax	13204cd	5	2.43	528

Driver	Colour	3000K	4000K
EL.	○	**1T5150EL**	**1T5152EL**
EL.	●	**1T5134EL**	**1T5136EL**
DALI	○	**1T5150DA**	**1T5152DA**
DALI	●	**1T5134DA**	**1T5136DA**

STORE

LED / 33W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			27°	
Fixture Power		36W	1	0.49	10157
Source Flux		3290lm	2	0.97	2539
Fixture Flux		2786lm	3	1.46	1129
Efficacy		78lm/W	4	1.95	635
TS952	Imax=3087cd/klm	Imax	10157cd	5	2.43	406

Driver	Colour	3000K	4000K
EL.	○	**1T5151EL**	**1T5153EL**
EL.	●	**1T5135EL**	**1T5137EL**
DALI	○	**1T5151DA**	**1T5153DA**
DALI	●	**1T5135DA**	**1T5137DA**

LED / 33W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		36W	1	0.82	6951
Source Flux		4277lm	2	1.64	1738
Fixture Flux		3716lm	3	2.46	772
Efficacy		104lm/W	4	3.28	434
TS953	Imax=1655cd/klm	Imax	7076cd	5	4.10	278

Driver	Colour	3000K	4000K
EL.	○	**1T5154EL**	**1T5156EL**
EL.	●	**1T5138EL**	**1T5140EL**
DALI	○	**1T5154DA**	**1T5156DA**
DALI	●	**1T5138DA**	**1T5140DA**

LED / 33W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
Fixture Power		36W	1	0.82	5347
Source Flux		3290lm	2	1.64	1337
Fixture Flux		2859lm	3	2.46	594
Efficacy		80lm/W	4	3.28	334
TS953	Imax=1655cd/klm	Imax	5443cd	5	4.10	214

Driver	Colour	3000K	4000K
EL.	○	**1T5155EL**	**1T5157EL**
EL.	●	**1T5139EL**	**1T5141EL**
DALI	○	**1T5155DA**	**1T5157DA**
DALI	●	**1T5139DA**	**1T5141DA**

LED / 33W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			59°	
Fixture Power		36W	1	1.13	4836
Source Flux		4277lm	2	2.26	1209
Fixture Flux		3768lm	3	3.39	537
Efficacy		106lm/W	4	4.51	302
TS954	Imax=1142cd/klm	Imax	4882cd	5	5.64	193

Driver	Colour	3000K	4000K
EL.	○	**1T5158EL**	**1T5160EL**
EL.	●	**1T5142EL**	**1T5144EL**
DALI	○	**1T5158DA**	**1T5160DA**
DALI	●	**1T5142DA**	**1T5144DA**

LED / 33W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power		36W	1	1.13	3720
Source Flux		3290lm	2	2.26	930
Fixture Flux		2898lm	3	3.39	413
Efficacy		81lm/W	4	4.51	233
TS954	Imax=1142cd/klm	Imax	3756cd	5	5.64	149

Driver	Colour	3000K	4000K
EL.	○	**1T5159EL**	**1T5161EL**
EL.	●	**1T5143EL**	**1T5145EL**
DALI	○	**1T5159DA**	**1T5161DA**
DALI	●	**1T5143DA**	**1T5145DA**

Gimbal
Versions with magnets



LED / 19W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		22W	1	0.24	23022
Source Flux		2935lm	2	0.48	5755
Fixture Flux		2494lm	3	0.72	2558
Efficacy		112lm/W	4	0.96	1439
TS947	Imax=7844cd/klm	Imax	23022cd	5	1.20	921

Driver	Colour	3000K	4000K
EL.	○	**1T6445EL**	**1T6447EL**
EL.	●	**1T6429EL**	**1T6431EL**
DALI	○	**1T6445DA**	**1T6447DA**
DALI	●	**1T6429DA**	**1T6431DA**

LED / 19W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		22W	1	0.24	17704
Source Flux		2257lm	2	0.48	4426
Fixture Flux		1918lm	3	0.72	1967
Efficacy		86lm/W	4	0.96	1106
TS947	Imax=7844cd/klm	Imax	17704cd	5	1.20	708

Driver	Colour	3000K	4000K
EL.	○	**1T6446EL**	**1T6448EL**
EL.	●	**1T6430EL**	**1T6432EL**
DALI	○	**1T6446DA**	**1T6448DA**
DALI	●	**1T6430DA**	**1T6432DA**

LED / 19W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			27°	
Fixture Power		22W	1	0.49	9061
Source Flux		2935lm	2	0.97	2265
Fixture Flux		2486lm	3	1.46	1007
Efficacy		112lm/W	4	1.95	566
TS948	Imax=3087cd/klm	Imax	9061cd	5	2.43	362

Driver	Colour	3000K	4000K
EL.	○	**1T6449EL**	**1T6451EL**
EL.	●	**1T6433EL**	**1T6435EL**
DALI	○	**1T6449DA**	**1T6451DA**
DALI	●	**1T6433DA**	**1T6435DA**

LED / 19W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			27°	
Fixture Power		22W	1	0.49	6968
Source Flux		2257lm	2	0.97	1742
Fixture Flux		1912lm	3	1.46	774
Efficacy		86lm/W	4	1.95	435
TS948	Imax=3087cd/klm	Imax	6968cd	5	2.43	279

Driver	Colour	3000K	4000K
EL.	○	**1T6450EL**	**1T6452EL**
EL.	●	**1T6434EL**	**1T6436EL**
DALI	○	**1T6450DA**	**1T6452DA**
DALI	●	**1T6434DA**	**1T6436DA**

LED / 19W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		22W	1	0.82	4770
Source Flux		2935lm	2	1.64	1193
Fixture Flux		2550lm	3	2.46	530
Efficacy		115lm/W	4	3.28	298
TS949	Imax=1655cd/klm	Imax	4856cd	5	4.10	191

Driver	Colour	3000K	4000K
EL.	○	**1T6453EL**	**1T6455EL**
EL.	●	**1T6437EL**	**1T6439EL**
DALI	○	**1T6453DA**	**1T6455DA**
DALI	●	**1T6437DA**	**1T6439DA**

STORE

LED / 19W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
Fixture Power		22W	1	0.82	3668
Source Flux		2257lm	2	1.64	917
Fixture Flux		1961lm	3	2.46	408
Efficacy		88lm/W	4	3.28	229
TS949	Imax=1655cd/klm	Imax	3734cd	5	4.10	147

Driver	Colour	3000K	4000K
EL.	○	**1T6454EL**	**1T6456EL**
EL.	●	**1T6438EL**	**1T6440EL**
DALI	○	**1T6454DA**	**1T6456DA**
DALI	●	**1T6438DA**	**1T6440DA**

LED / 19W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			59°	
Fixture Power		22W	1	1.13	3318
Source Flux		2935lm	2	2.26	830
Fixture Flux		2585lm	3	3.39	369
Efficacy		116lm/W	4	4.51	207
TS950	Imax=1141cd/klm	Imax	3350cd	5	5.64	133

Driver	Colour	3000K	4000K
EL.	○	**1T6457EL**	**1T6459EL**
EL.	●	**1T6441EL**	**1T6443EL**
DALI	○	**1T6457DA**	**1T6459DA**
DALI	●	**1T6441DA**	**1T6443DA**

LED / 19W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power		22W	1	1.13	2552
Source Flux		2257lm	2	2.26	638
Fixture Flux		1988lm	3	3.39	284
Efficacy		90lm/W	4	4.51	159
TS950	Imax=1141cd/klm	Imax	2576cd	5	5.64	102

Driver	Colour	3000K	4000K
EL.	○	**1T6458EL**	**1T6460EL**
EL.	●	**1T6442EL**	**1T6444EL**
DALI	○	**1T6458DA**	**1T6460DA**
DALI	●	**1T6442DA**	**1T6444DA**

LED / 33W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		36W	1	0.24	33552
Source Flux		4277lm	2	0.48	8388
Fixture Flux		3635lm	3	0.72	3728
Efficacy		102lm/W	4	0.96	2097
TS951	Imax=7845cd/klm	Imax	33552cd	5	1.20	1342

Driver	Colour	3000K	4000K
EL.	○	**1T6477EL**	**1T6479EL**
EL.	●	**1T6461EL**	**1T6463EL**
DALI	○	**1T6477DA**	**1T6479DA**
DALI	●	**1T6461DA**	**1T6463DA**

LED / 33W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		36W	1	0.24	25809
Source Flux		3290lm	2	0.48	6452
Fixture Flux		2796lm	3	0.72	2868
Efficacy		78lm/W	4	0.96	1613
TS951	Imax=7845cd/klm	Imax	25809cd	5	1.20	1032

Driver	Colour	3000K	4000K
EL.	○	**1T6478EL**	**1T6480EL**
EL.	●	**1T6462EL**	**1T6464EL**
DALI	○	**1T6478DA**	**1T6480DA**
DALI	●	**1T6462DA**	**1T6464DA**

LED / 33W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			27°	
Fixture Power		36W	1	0.49	13204
Source Flux		4277lm	2	0.97	3301
Fixture Flux		3622lm	3	1.46	1467
Efficacy		101lm/W	4	1.95	825
TS952	Imax=3087cd/klm	Imax	13204cd	5	2.43	528

Driver	Colour	3000K	4000K
EL.	○	**1T6481EL**	**1T6483EL**
EL.	●	**1T6465EL**	**1T6467EL**
DALI	○	**1T6481DA**	**1T6483DA**
DALI	●	**1T6465DA**	**1T6467DA**

STORE

LED / 33W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			27°	
Fixture Power		36W	1	0.49	10157
Source Flux		3290lm	2	0.97	2539
Fixture Flux		2786lm	3	1.46	1129
Efficacy		78lm/W	4	1.95	635
TS952	Imax=3087cd/klm	Imax	10157cd	5	2.43	406

Driver	Colour	3000K	4000K
EL.	○	**1T6482EL**	**1T6484EL**
EL.	●	**1T6466EL**	**1T6468EL**
DALI	○	**1T6482DA**	**1T6484DA**
DALI	●	**1T6466DA**	**1T6468DA**

LED / 33W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		36W	1	0.82	6951
Source Flux		4277lm	2	1.64	1738
Fixture Flux		3716lm	3	2.46	772
Efficacy		104lm/W	4	3.28	434
TS953	Imax=1655cd/klm	Imax	7076cd	5	4.10	278

Driver	Colour	3000K	4000K
EL.	○	**1T6485EL**	**1T6487EL**
EL.	●	**1T6469EL**	**1T6471EL**
DALI	○	**1T6485DA**	**1T6487DA**
DALI	●	**1T6469DA**	**1T6471DA**

LED / 33W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
Fixture Power		36W	1	0.82	5347
Source Flux		3290lm	2	1.64	1337
Fixture Flux		2859lm	3	2.46	594
Efficacy		80lm/W	4	3.28	334
TS953	Imax=1655cd/klm	Imax	5443cd	5	4.10	214

Driver	Colour	3000K	4000K
EL.	○	**1T6486EL**	**1T6488EL**
EL.	●	**1T6470EL**	**1T6472EL**
DALI	○	**1T6486DA**	**1T6488DA**
DALI	●	**1T6470DA**	**1T6472DA**

LED / 33W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			59°	
Fixture Power		36W	1	1.13	4836
Source Flux		4277lm	2	2.26	1209
Fixture Flux		3768lm	3	3.39	537
Efficacy		106lm/W	4	4.51	302
TS954	Imax=1142cd/klm	Imax	4882cd	5	5.64	193

Driver	Colour	3000K	4000K
EL.	○	**1T6489EL**	**1T6491EL**
EL.	●	**1T6473EL**	**1T6475EL**
DALI	○	**1T6489DA**	**1T6491DA**
DALI	●	**1T6473DA**	**1T6475DA**

LED / 33W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power		36W	1	1.13	3720
Source Flux		3290lm	2	2.26	930
Fixture Flux		2898lm	3	3.39	413
Efficacy		81lm/W	4	4.51	233
TS954	Imax=1142cd/klm	Imax	3756cd	5	5.64	149

Driver	Colour	3000K	4000K
EL.	○	**1T6490EL**	**1T6492EL**
EL.	●	**1T6474EL**	**1T6476EL**
DALI	○	**1T6490DA**	**1T6492DA**
DALI	●	**1T6474DA**	**1T6476DA**

Note

Versions with springs for single installation without a frame. Versions with magnets for single installation without a frame or single or multioptic installation with a trimless accessory frame (for the recessed hole of this version please refer to that of the accessory frame.

STORE

Related codes

Insertion Box





Cutout hole	Colour	Code
180x180	○	**1T6496**
180x180	●	**1T6493**

Frame 1x.





Cutout hole	Colour	Code
335x180	○	**1T6497**
335x180	◐	**1T6494**

Frame 2x.





Cutout hole	Colour	Code
485x180	○	**1T6498**
485x180	●	**1T6495**

Frame 3x.

Accessories

Filter



Filter	Ø	Code
Red	70	**1T1712**
Green	70	**1T1713**
Blue	70	**1T1714**
Yellow	70	**1T1715**
Magenta	70	**1T1716**

Flat glass interference chromatic filter.
To be completed with an additional holder ring for Cloud, Ray Mini, Store and Keplero Mini HE.



Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.



Ø	Code
70	**1T1709**

Flat glass wired refractive diffusive filter.
This softens the luminous effect.
To be completed with an additional holder ring for Cloud, Ray Mini, Sore, Label 9 and CCTEvo Extractable 162.



Filter	Ø	Code
Halogen +	70	**1T6506**
Vivid +	70	**1T6507**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.

STORE



Filter	Ø	Code
Meat	70	**1T6508**
Fish	70	**1T6509**
Bread	70	**1T6510**
Vegetables	70	**1T6511**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.
1T6508 - To be used only with 3000K and Ra84 fixtures.
1T6509 - To be used only with 4000K and Ra84 fixtures.
1T6510 - To be used only with 3000K and Ra84 fixtures.
1T6511 - To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Beauty	70	**1T6512**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.

Screen



Ø	Code
80	**1T6522**

Protective screen.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Zoom



Ø	Code
80	**1T3432**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It makes it possible to obtain a variable beam from 15° to 60°.
It can not be used with NSP and hybrid optics; no for DBS version.

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Screen

Ø	Code
80	**1T3143**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Holder Ring

Code
1T3727

Transparent polycarbonate accessory holder ring.

STORE

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

Mini Gimbal
Versions with springs



LED / 2,7W / LENS / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra80			9°	
Fixture Power	5W	1	0.15	4436
Source Flux	200lm	2	0.30	1109
Fixture Flux	163lm	3	0.45	493
Efficacy	31lm/W	4	0.60	277
Imax	4436cd	5	0.75	177

TS965 Imax=22178cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4934EL**	**1T4935EL**
EL.	●	**1T4926EL**	**1T4927EL**
DALI	○	**1T4934DA**	**1T4935DA**
DALI	●	**1T4926DA**	**1T4927DA**

LED / 11W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra84			15°	
Fixture Power	15W	1	0.27	16914
Source Flux	1786lm	2	0.53	4229
Fixture Flux	1336lm	3	0.80	1879
Efficacy	90lm/W	4	1.07	1057
Imax	16914cd	5	1.33	677

TS966 Imax=9470cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4936EL**	**1T4937EL**
EL.	●	**1T4928EL**	**1T4929EL**
DALI	○	**1T4936DA**	**1T4937DA**
DALI	●	**1T4928DA**	**1T4929DA**

LED / 18W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra84			24°	
Fixture Power	20W	1	0.43	8803
Source Flux	2466lm	2	0.87	2201
Fixture Flux	1800lm	3	1.30	978
Efficacy	89lm/W	4	1.73	550
Imax	8803cd	5	2.17	352

TS969 Imax=3570cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4948EL**	**1T4949EL**
EL.	●	**1T4942EL**	**1T4943EL**
DALI	○	**1T4948DA**	**1T4949DA**
DALI	●	**1T4942DA**	**1T4943DA**

LED / 12W / LENS / FL



3000K		H(m)	D(m)	Emax(lx)
Ra84			30°	
Fixture Power	14W	1	0.54	4825
Source Flux	1837lm	2	1.09	1206
Fixture Flux	1315lm	3	1.63	536
Efficacy	97lm/W	4	2.17	302
Imax	4825cd	5	2.72	193

TS967 Imax=2627cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4938EL**	**1T4939EL**
EL.	●	**1T4930EL**	**1T4931EL**
DALI	○	**1T4938DA**	**1T4939DA**
DALI	●	**1T4930DA**	**1T4931DA**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			48°	
Fixture Power	14W	1	0.90	2476
Source Flux	1837lm	2	1.80	619
Fixture Flux	1520lm	3	2.69	275
Efficacy	113lm/W	4	3.59	155
Imax	2520cd	5	4.49	99

TS968 Imax=1372cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4940EL**	**1T4941EL**
EL.	●	**1T4932EL**	**1T4933EL**
DALI	○	**1T4940DA**	**1T4941DA**
DALI	●	**1T4932DA**	**1T4933DA**

STORE

LED / 18W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		20W	1	0.90	3323
Source Flux		2466lm	2	1.80	831
Fixture Flux		2041lm	3	2.69	369
Efficacy		101lm/W	4	3.59	208
TS970	Imax=1372cd/klm	Imax	3383cd	5	4.49	133

Driver	Colour	3000K	4000K
EL.	○	**1T4950EL**	**1T4951EL**
EL.	●	**1T4944EL**	**1T4945EL**
DALI	○	**1T4950DA**	**1T4951DA**
DALI	●	**1T4944DA**	**1T4945DA**

LED / 18W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			60°	
Fixture Power		20W	1	1.16	2406
Source Flux		2466lm	2	2.32	601
Fixture Flux		1979lm	3	3.47	267
Efficacy		98lm/W	4	4.63	150
TS971	Imax=976cd/klm	Imax	2407cd	5	5.79	96

Driver	Colour	3000K	4000K
EL.	○	**1T4952EL**	**1T4953EL**
EL.	●	**1T4946EL**	**1T4947EL**
DALI	○	**1T4952DA**	**1T4953DA**
DALI	●	**1T4946DA**	**1T4947DA**

Mini Gimbal
Versions with magnets



LED / 2,7W / LENS / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		5W	1	0.15	4436
Source Flux		200lm	2	0.30	1109
Fixture Flux		163lm	3	0.45	493
Efficacy		31lm/W	4	0.60	277
TS965	Imax=22178cd/klm	Imax	4436cd	5	0.75	177

Driver	Colour	3000K	4000K
EL.	○	**1T5960EL**	**1T5961EL**
EL.	●	**1T5952EL**	**1T5953EL**
DALI	○	**1T5960DA**	**1T5961DA**
DALI	●	**1T5952DA**	**1T5953DA**

LED / 11W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			15°	
Fixture Power		15W	1	0.27	16914
Source Flux		1786lm	2	0.53	4229
Fixture Flux		1336lm	3	0.80	1879
Efficacy		90lm/W	4	1.07	1057
TS966	Imax=9470cd/klm	Imax	16914cd	5	1.33	677

Driver	Colour	3000K	4000K
EL.	○	**1T5962EL**	**1T5963EL**
EL.	●	**1T5954EL**	**1T5955EL**
DALI	○	**1T5962DA**	**1T5963DA**
DALI	●	**1T5954DA**	**1T5955DA**

LED / 18W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			24°	
Fixture Power		20W	1	0.43	8803
Source Flux		2466lm	2	0.87	2201
Fixture Flux		1800lm	3	1.30	978
Efficacy		89lm/W	4	1.73	550
TS969	Imax=3570cd/klm	Imax	8803cd	5	2.17	352

Driver	Colour	3000K	4000K
EL.	○	**1T5974EL**	**1T5975EL**
EL.	●	**1T5968EL**	**1T5969EL**
DALI	○	**1T5974DA**	**1T5975DA**
DALI	●	**1T5968DA**	**1T5969DA**

STORE

LED / 12W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			30°	
Fixture Power		14W	1	0.54	4825
Source Flux		1837lm	2	1.09	1206
Fixture Flux		1315lm	3	1.63	536
Efficacy		97lm/W	4	2.17	302
TS967	Imax=2627cd/klm	Imax	4825cd	5	2.72	193

Driver	Colour	3000K	4000K
EL.	○	**1T5964EL**	**1T5965EL**
EL.	●	**1T5956EL**	**1T5957EL**
DALI	○	**1T5964DA**	**1T5965DA**
DALI	●	**1T5956DA**	**1T5957DA**

LED / 12W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		14W	1	0.90	2476
Source Flux		1837lm	2	1.80	619
Fixture Flux		1520lm	3	2.69	275
Efficacy		113lm/W	4	3.59	155
TS968	Imax=1372cd/klm	Imax	2520cd	5	4.49	99

Driver	Colour	3000K	4000K
EL.	○	**1T5966EL**	**1T5967EL**
EL.	●	**1T5958EL**	**1T5959EL**
DALI	○	**1T5966DA**	**1T5967DA**
DALI	●	**1T5958DA**	**1T5959DA**

LED / 18W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		20W	1	0.90	3323
Source Flux		2466lm	2	1.80	831
Fixture Flux		2041lm	3	2.69	369
Efficacy		101lm/W	4	3.59	208
TS970	Imax=1372cd/klm	Imax	3383cd	5	4.49	133

Driver	Colour	3000K	4000K
EL.	○	**1T6419EL**	**1T6420EL**
EL.	●	**1T5970EL**	**1T5971EL**
DALI	○	**1T6419DA**	**1T6420DA**
DALI	●	**1T5970DA**	**1T5971DA**

LED / 18W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			60°	
Fixture Power		20W	1	1.16	2406
Source Flux		2466lm	2	2.32	601
Fixture Flux		1979lm	3	3.47	267
Efficacy		98lm/W	4	4.63	150
TS971	Imax=976cd/klm	Imax	2407cd	5	5.79	96

Driver	Colour	3000K	4000K
EL.	○	**1T6421EL**	**1T6422EL**
EL.	●	**1T5972EL**	**1T5973EL**
DALI	○	**1T6421DA**	**1T6422DA**
DALI	●	**1T5972DA**	**1T5973DA**

Note

Versions with springs for single installation without a frame or single or multioptic installation with a trimless accessory frame. Versions with magnets for single or multioptic installation with an accessory frame. For installations with frames for the recessed hole please refer to that of the accessory frame.

Related codes

Insertion Box



Cutout hole	Colour	Code
150x150	○	**1T6426**
150x150	●	**1T6423**

Frame 1x.
For version with magnets.





Cutout hole	Colour	Code
300x150	○	**1T6427**
300x150	●	**1T6424**

Frame 2x.
For version with magnets.

STORE





Cutout hole	Colour	Code
450x150	○	**1T6428**
450x150	●	**1T6425**

Frame 3x.
For version with magnets.



Cutout hole	Code
149x149	**1T7404**

Trimless frame 1x.
For version with springs.





Cutout hole	Code
149x295	**1T7405**

Trimless frame 2x.
For version with springs.





Cutout hole	Code
149x441	**1T7406**

Trimless frame 3x.
For version with springs.

Accessories

Filter



Filter	Ø	Code
Red	50	**49881**
Green	50	**49882**
Blue	50	**49886**
Yellow	50	**49887**
Magenta	50	**49959**

Flat glass interference chromatic filter.

Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.



Filter	Ø	Code
Halogen +	50	**1T6381**
Vivid +	50	**1T6383**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Meat	50	**1T6385**
Fish	50	**1T6387**
Bread	50	**1T6389**
Vegetables	50	**1T6391**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
1T6385 - To be used only with 3000K and Ra84 fixtures.
1T6387 - To be used only with 4000K and Ra84 fixtures.
1T6389 - To be used only with 3000K and Ra84 fixtures.
1T6391 - To be used only with 3000K and Ra84 fixtures.

STORE

Filter



Filter	Ø	Code
Beauty	50	**1T6393**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.

Zoom



Ø	Code
50	**1T4324**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It can not be used with a narrow spot optic.
It makes it possible to obtain a variable beam from 15° to 60°.

Screen



Ø	Code
50	**1T4325**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.



Ø	Code
50	**1T6521**

Protective screen.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Emergency Kit



Code
1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

ZENO

Small Extractable

GENERAL INFO
Recessed, extractable and adjustable LED professional projector. The optical unit can be adjusted from 0 to 90° on the vertical plane and 360° on the orizontal plane with the possibility to block beam.
ø105mm

LED
COB Chip on board
From 825lm to 1478lm
3000K – 4000K
Ra97

PRODUCT EFFICACY
Up to 90lm/W

OPTICS
NSP – SP – FL – MWFL – WFL

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Die-cast painted aluminium body.

ON DEMAND

Easy Custom Colour

Ra90

110-277Vac power supply

A range of professional projectors especially for museum lighting, given the quality of the LED sources, the cutting edge optics and installation flexibility.

The optical unit can be moved to four different positions from total recessed to complete extraction.

Also available in a projector version in three different sizes.

		SMALL
		Ø105mm
LED	Flux (lm)	825-1478
	Power	9.4W - 12W
OPTICS		
NSP	Lens+Honeycomb	•
SP	Lens+Honeycomb	•
FL	Reflector	•
MWFL	Reflector	•
WFL	Reflector	•

Plus



Trimless or with a decorative ring

Zeno extractable combines the flexibility and performance of a projector with the ability to blend into the architecture. It is possible to choose from installation with a trimless finish or with a decorative ring (to be ordered separately).

The optical body

To be moved into four different positions.

- Step 0 - recessed and non-adjustable;
- Step 1 -partially extracted but non-adjustable;
- Step 2 - the optical unit can be adjusted from 15 to 90° on the vertical plane and 360° on the horizontal plane;
- Step 3 - when the fixture is completely extracted the optical unit can be adjusted from 0 to 90° on the vertical plane and 360° on the horizontal plane with the possibility to block the beam.

ZENO

Small Extractable



LED / 9,4W / LENS+HONEYCOMB / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			7°	
Fixture Power	11W	1	0.13	20546
Source Flux	825lm	2	0.25	5137
Fixture Flux	574lm	3	0.38	2283
Efficacy	52lm/W	4	0.51	1284
Imax	20546cd	5	0.63	822

TS1409 Imax=24905cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T8206EL**	**1T8207EL**
EL.	●	**1T8208EL**	**1T8209EL**
DALI	○	**1T8206DA**	**1T8207DA**
DALI	●	**1T8208DA**	**1T8209DA**

LED / 12W / LENS+HONEYCOMB / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	14W	1	0.28	6374
Source Flux	1427lm	2	0.56	1593
Fixture Flux	726lm	3	0.84	708
Efficacy	52lm/W	4	1.12	398
Imax	6374cd	5	1.40	255

TS1410 Imax=4467cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T8210EL**	**1T8211EL**
EL.	●	**1T8212EL**	**1T8213EL**
DALI	○	**1T8210DA**	**1T8211DA**
DALI	●	**1T8212DA**	**1T8213DA**

LED / 12W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			28°	
Fixture Power	14W	1	0.49	4527
Source Flux	1427lm	2	0.99	1132
Fixture Flux	1113lm	3	1.48	503
Efficacy	79lm/W	4	1.98	283
Imax	4527cd	5	2.47	181

TS1411 Imax=3172cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T8214EL**	**1T8215EL**
EL.	●	**1T8216EL**	**1T8217EL**
DALI	○	**1T8214DA**	**1T8215DA**
DALI	●	**1T8216DA**	**1T8217DA**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			48°	
Fixture Power	14W	1	0.90	1860
Source Flux	1430lm	2	1.79	465
Fixture Flux	1178lm	3	2.69	207
Efficacy	87lm/W	4	3.59	116
Imax	1870cd	5	4.48	74

TS1066 Imax=1307cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T6563EL**	**1T6564EL**
EL.	●	**1T6565EL**	**1T6566EL**
DALI	○	**1T6563DA**	**1T6564DA**
DALI	●	**1T6565DA**	**1T6566DA**

LED / 12W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			58°	
Fixture Power	14W	1	1.11	1400
Source Flux	1430lm	2	2.21	350
Fixture Flux	1188lm	3	3.32	156
Efficacy	88lm/W	4	4.43	88
Imax	1432cd	5	5.53	56

TS1067 Imax=1001cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T6567EL**	**1T6568EL**
EL.	●	**1T6569EL**	**1T6570EL**
DALI	○	**1T6567DA**	**1T6568DA**
DALI	●	**1T6569DA**	**1T6570DA**

ZENO

Related codes

Decorative Ring



Ø	Colour	Code
146	○	**1T6579**
146	●	**1T6580**

Round ring.

Accessories

Filter



Code
1T6572

Blade of light filter.
Methacrylate holographic filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with a dedicated holder ring.

Grid



Colour	Code
◐	**1T6573**

Anti-glare louver.
Black lacquered aluminium honeycomb structure.
To be completed with a dedicated holder ring.
Not to be used with NSP and SP optics.

Cut-off



Colour	Code
●	**1T6574**

Black painted steel cut-off.
To be completed with a dedicated holder ring.



Colour	Code
◐	**1T6575**

Black painted steel asymmetric cut-off.
To be completed with a dedicated holder ring.

Ray Shade

Colour	Code
●	**1T6576**

Adjustable barn doors flaps made of black painted steel.
To be completed with a dedicated holder ring.

Holder Ring



Colour	Code
◐	**1T6571**

Black painted aluminium accessory holder ring.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

Inwhite Medical
Moscow - Russia

COZY

GENERAL INFO
Small recessed downlight, trimless or complete with decorative ring.

LED
Chip on board
From 1798lm to 1855lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 35lm/W

OPTIC
SP

POWER SUPPLY
Remote: Electronic - DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Turned aluminium body and integrated dissipator. Trimless or painted flange versions with a painted turned aluminium, removable front ring.

ON DEMAND

Alimentazione
110-277Vac

Ra Ra90

Cozy is the smallest recessed downlight in the Targetti Collection. Just 40mm in diameter (version with ring) it has an anti-glare solution thanks to the LED lamp that is set back 40mm from the emission surface.

The spot optic makes this recessed projector perfect for decorative accent lighting.

Simple and rapid installation in plasterboard ceilings of thicknesses starting from 4mm using the AISI steel spring mounting system for the ring version and screws for the trimless version.

COZY

Trim



LED / 12W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			25°	
Fixture Power		14W	1	0.45	1814
Source Flux		1798lm	2	0.90	453
Fixture Flux		476lm	3	1.35	202
Efficacy		34lm/W	4	1.80	113
Imax		1814cd	5	2.25	73

Power supply	Colour	3000K	4000K
350mA	○	**1T6377**	**1T6378**
350mA	●	**1T6379**	**1T6380**

Trimless



LED / 12W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			25°	
Fixture Power		14W	1	0.45	1814
Source Flux		1798lm	2	0.90	453
Fixture Flux		476lm	3	1.35	202
Efficacy		34lm/W	4	1.80	113
Imax		1814cd	5	2.25	73

Power supply	Colour	3000K	4000K
350mA	○	**1T7400**	**1T7401**

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
158x19x22	max 15W	220-240Vac	350mA	IP20	**1T6505**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
147x30x44	max 15W	220-240Vac	350mA	IP20	**1T6504**

DALI power supply.

COZY

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

BEBOP

Recessed

GENERAL INFO
Recessed downlight
Ø90mm

LED
Chip on board
From 1302lm to 1909lm
3000K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 88lm/W

OPTICS
MWFL - WFL

POWER SUPPLY
Eletctronic - DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Painted polycarbonate body and rounded ring. Die-cast aluminium finned heat sink, side wiring complete with power supply.

ON DEMAND

Easy Custom Colour

110-277Vac
power supply

2700K-3500K

A range of high performance characterised by simple, soft and rounded lines. Available in three different versions for ceiling mounted, suspension and recessed installation. In all versions the LED lamps are retracted and hidden from view to ensure optimum visual comfort. The flexible installation makes it possible to use the same type of light in environments with different architectural characteristics.

The recessed version has a reduced depth and a polycarbonate finishing ring with a white finish that “disappears” into ceilings creating the illusion of a plaster finish.

BEBOP

Recessed



LED / 9W / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			48°	
Fixture Power	12W	1	0.90	1391
Source Flux	1302lm	2	1.79	348
Fixture Flux	1000lm	3	2.69	155
Efficacy	86lm/W	4	3.59	87
Imax	1404cd	5	4.48	56

TS897 Imax=1079cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4756EL**	**1T4757EL**
EL.	●	**1T5406EL**	**1T5407EL**
DALI	○	**1T4756DA**	**1T4757DA**
DALI	●	**1T5406DA**	**1T5407DA**

LED / 9W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			64°	
Fixture Power	12W	1	1.24	830
Source Flux	1302lm	2	2.49	207
Fixture Flux	980lm	3	3.73	92
Efficacy	85lm/W	4	4.98	52
Imax	896cd	5	6.22	33

TS896 Imax=688cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4754EL**	**1T4755EL**
EL.	●	**1T5408EL**	**1T5409EL**
DALI	○	**1T4754DA**	**1T4755DA**
DALI	●	**1T5408DA**	**1T5409DA**

LED / 15W / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			48°	
Fixture Power	16W	1	0.90	1990
Source Flux	1863lm	2	1.79	498
Fixture Flux	1431lm	3	2.69	221
Efficacy	87lm/W	4	3.59	124
Imax	2010cd	5	4.48	80

TS899 Imax=1079cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4760EL**	**1T4761EL**
EL.	●	**1T5410EL**	**1T5411EL**
DALI	○	**1T4760DA**	**1T4761DA**
DALI	●	**1T5410DA**	**1T5411DA**

LED / 15W / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			64°	
Fixture Power	16W	1	1.24	1187
Source Flux	1863lm	2	2.49	297
Fixture Flux	1403lm	3	3.73	132
Efficacy	86lm/W	4	4.98	74
Imax	1282cd	5	6.22	47

TS898 Imax=688cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T4758EL**	**1T4759EL**
EL.	●	**1T5412EL**	**1T5413EL**
DALI	○	**1T4758DA**	**1T4759DA**
DALI	●	**1T5412DA**	**1T5413DA**

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

BEBOP

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

QUICKLED

GENERAL INFO
Compact rrecessed downlight
Ø85mm

LED
Chip on board
From 1302lm to 1909lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 92lm/W

OPTICS
MWFL

POWER SUPPLY
Electronic - DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Metallised polycarbonate body with decorative ring in anodised aluminium or painted white. Finned heat sink made of die-cast aluminium, side wiring complete with power supply.

ON DEMAND

Easy Custom Colour

110-277Vac
power supply

Ra90 - Ra97

2700K - 3500K

A high performance compact downlight with excellent light distribution.

The special diffuser screen ensures extremely soft and homogeneous light distribution and also gives the fixture an IP44 rating making it suitable for installation in public spaces.

QUICKLED



LED / 9W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			44°	
	Fixture Power	12W	1	0.81	1937
	Source Flux	1302lm	2	1.63	484
	Fixture Flux	1025lm	3	2.44	215
	Efficacy	88lm/W	4	3.26	121
	Imax	1937cd	5	4.07	77

	Driver	Colour	3000K	4000K
	EL.	○	**1T4770EL**	**1T4771EL**
	EL.	●	**1T4772EL**	**1T4773EL**
	DALI	○	**1T4770DA**	**1T4771DA**
	DALI	●	**1T4772DA**	**1T4773DA**

LED / 15W / MWFL

	3000K		H(m)	D(m)	Emax(lx)
	Ra84			44°	
	Fixture Power	16W	1	0.81	2772
	Source Flux	1863lm	2	1.63	693
	Fixture Flux	1466lm	3	2.44	308
	Efficacy	89lm/W	4	3.26	173
	Imax	2772cd	5	4.07	111

	Driver	Colour	3000K	4000K
	EL.	○	**1T4774EL**	**1T4775EL**
	EL.	●	**1T4776EL**	**1T4777EL**
	DALI	○	**1T4774DA**	**1T4775DA**
	DALI	●	**1T4776DA**	**1T4777DA**

Accessories

Emergency Kit



	Code
	1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

OTTO

Recessed

GENERAL INFO
Extractable recessed projector
ø30mm

LED
LED Emitter
From 370lm to 397lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 30lm/W

OPTIC
ZOOM: from SP to FL

POWER SUPPLY
Electronic remote

MATERIAL
Painted or anodised aluminium body.

ON DEMAND
110-277Vac power supply

A range of projectors with a minimal footprint with different installation types characterised by manual focus.

Available also in a single or multi-optical pole mounted version.

Projector version also available.



Museo Stibbert – Le sale giapponesi
Firenze, Italia

OTTO

Semi-Recessed



LED / 3W / ZOOM / SP-FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
	Fixture Power	5W	1	0.24	2069
	Source Flux	370lm	2	0.49	517
	Fixture Flux	117lm	3	0.73	230
	Efficacy	23lm/W	4	0.98	129
TS1039	Imax=5593cd/klm	Imax	2069cd	5	1.22	83



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			34°	
	Fixture Power	5W	1	0.62	481
	Source Flux	370lm	2	1.23	120
	Fixture Flux	141lm	3	1.85	53
	Efficacy	28lm/W	4	2.46	30
TS1040	Imax=1301cd/klm	Imax	481cd	5	3.08	19

Power supply	Colour	3000K	4000K
1050mA	○	**1T6335**	**1T6336**
1050mA	◐	**1T6347**	**1T6348**
1050mA	●	**1T6359**	**1T6360**

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
129x30x42	42W	220-240Vac	1050mA	IP20	**1T6524**

Electronic power supply.

OTTO

Recessed extractable



LED / 3W / ZOOM / SP-FL

	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		5W	1	0.24	2069
Source Flux		370lm	2	0.49	517
Fixture Flux		117lm	3	0.73	230
Efficacy		23lm/W	4	0.98	129
Imax		2069cd	5	1.22	83



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			34°	
Fixture Power		5W	1	0.62	481
Source Flux		370lm	2	1.23	120
Fixture Flux		141lm	3	1.85	53
Efficacy		28lm/W	4	2.46	30
Imax		481cd	5	3.08	19

Power supply	Colour	3000K	4000K
1050mA	○	**1T6333**	**1T6334**
1050mA	◐	**1T6345**	**1T6346**
1050mA	●	**1T6357**	**1T6358**

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
129x30x42	42W	220-240Vac	1050mA	IP20	**1T6524**

Electronic power supply.

Projectors

Indoor

● New ○ Upgrade

Track projectors

208
ZENO Large
Ø 184mm

208
ZENO Medium
Ø 134mm

208
ZENO Small
Ø 105mm

232
LABEL 9
Ø 87mm

232
LABEL 7
Ø 74mm

232
LABEL 6
Ø 59mm

242
CAPSULE 7
Ø 70mm

242
CAPSULE 6
Ø 60mm

246
STORE
Ø 93mm

246
STORE
Mini
Ø 75mm

258
LEDÒ

258
LEDÒ
Tunable

268
RAY
Ø 144mm

268
RAY
Mini
Ø 115mm

268
RAY
Micro
Ø 76mm

Track

278
EUROSTANDARD
Plus

Surface projectors

286
JEDI
Compact

296
ZENO Applique
Large
Ø 184mm

296
ZENO Applique
Medium
Ø 134mm

300
VOLTA

306
CORO
Large
Ø 119mm

306
CORO
Small
Ø 82mm

326
OTTO
Ceiling

326
OTTO
Multi-Optic

ZENO

GENERAL INFO
Professional LED projector. The optical unit can be adjusted from 0 to -90° on the vertical plane; and 355° on the horizontal plane with aiming blocking system.
Small ø105mm
Medium ø134mm
Large ø184mm

LED
Chip on board
From 825lm to 5121lm
3000K – 4000K
Ra97

PRODUCT EFFICACY
Up to 90lm/W

OPTICS
NSP – SP – FL – MWFL – WFL – WW – ZOOM
DBS - Digital beam opening control

POWER SUPPLY
Electronic - DALI - 1-10V dimmer on board
Versions with integrated Casambi control system available (Casambi Ready).

MATERIAL
Painted die-cast aluminium body. Painted ABS driver Box or integrated adapter.

ON DEMAND
Easy Custom Colour
Ra90
2700K - 3500K (Zeno Zoom)
110-277Vac power supply (Zeno Large)

A range of projectors for professional lighting ideal in particular for museum environments thanks to the quality of the LED sources, the avant-garde optical systems and installation flexibility. Ten different optical systems for different luminous effects, three installation types and three different sizes. Today the design of Zeno is even more discrete thanks to the retractable adapters that allow for perfect integration of the projector with the architecture. The 1-10V version has a driver box with a dimmer on board. Zeno Medium is also available in a DBS – Dynamic Beam Shaper version. The Zeno range also includes an applique and a recessed extractable version.

		SMALL	MEDIUM	LARGE
		Ø105mm	Ø134mm	Ø184mm
LED	Flux (lm)	825-1478	2407-5121	2407-5121
	Power	9,4W - 12W	18W - 26W	26W - 52W
OPTICS				
NSP	Lens	•		
	Indirect		•	•
SP	Lens	•		
	Hybrid			•
FL	Reflector	•		
	Hybrid		•	•
MWFL	Reflector	•	•	•
WFL	Reflector	•	•	•
WW	Reflector		•	•
DBS	Variable	•	•	

Palazzo Merendoni
Bologna, Italy

Photographer Ivan Rossi

Plus



Studied in detail
No detail of Zeno was left to chance: the depth of the projector is reduced to the minimum while still maintaining excellent heat dissipation, the geometry of the bracket, a really distinctive element is designed to disappear and become an integral part of the body of the fixture.

Controlled and modular light
The Zeno range is also available in a DALI version or already equipped with a Casambi control system (Casambi ready products) for perfect control of lighting systems. Zeno Small, Zeno Medium and Zeno Large are also available with a 1-10V driver box with a dimmer on board that makes it possible to adjust the emission of individual fixtures with extreme simplicity.


MILANO
TARGETTI

Plus

A
NSP - SP (Lens+Honeycomb)
Zeno Small

B
NSP (Indirect)
Zeno Large, Zeno Medium

C
SP - FL (Hybrid)
Zeno Medium, Zeno Large

D
FL - MWFL - WFL (Reflector)
Zeno Small, Zeno Medium, Zeno Large

Different optical systems

The different optical systems for Zeno were designed to optimise the performance of the different beam openings.

A A new optical system was designed for the Zeno Small NSP and SP versions composed of a special PMMA lens with metallisation on the back surface, a holographic diffusion filter and a black painted aluminium honeycomb structure.

B The Large and Medium Zeno versions have an indirect Narrow spot optic that works by reflection and makes it possible to obtain extremely narrow (9°), precise and defined beams. The source is hidden from view and directed towards a parabolic reflector that collimates the beams and emits a cone of particularly precise and defined light. This makes Zeno ideal for museum lighting and where there is a need to have narrow beams with minimal fall-off.

C Zeno Medium and Large in the SP and FL versions are equipped with a hybrid optical system composed of a mirrored reflector, an optical glass lens and a holographic screen.

D All Zeno versions with MWFL and WFL optical systems are equipped with a faceted reflector and a holographic screen.
Zeno Small even in the FL version has a reflector optic.

E

WW (Reflector)
Zeno Medium, Zeno Large

F

ZOOM (Hybrid)
Zeno Medium

G

DBS (Variable)
Zeno Medium

E The WW versions have a highly reflective aluminium optical system that combines with a holographic screen and a painted plastic cover element to ensure maximum lighting uniformity.

F Zen Zoom is the manual solution to change beams. Just one optical system makes it possible to have a variable beam with continuity from Spot to Flood emission.

G Zeno DBS (Dynamic Beam Shaper) is the dynamic light version with remote control that makes it possible to activate a light diffusion process from a minimum of 16° and a maximum of 59° using the Casambi Application that is compatible with IOS and Android systems.



DBS - Digital beam opening control

Plus

Anti-glare louver

Black painted steel asymmetric cut-off

Black painted steel cut-off

Adjustable barn doors flaps

A large variety of optical accessories available for all sizes

Like barn door flaps, anti-glare grids and cut-off and corrective filters to meet the demands of more complex lighting needs.

Samsung kx London
London, United Kingdom

Architect Heatherwick Studio

Lighting Design Nulty Lightting

ZENO

Large EL/DALI/CASAMBI



LED / 26W / INDIRECT / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			9°	
Fixture Power		28W	1	0.15	48054
Source Flux		2407lm	2	0.31	12013
Fixture Flux		1425lm	3	0.46	5339
Efficacy		51lm/W	4	0.62	3003
TS1227	Imax=19964cd/klm	Imax	48054cd	5	0.77	1922

Driver	Colour	3000K	4000K
EL.	○	**1T8025EL**	**1T8026EL**
EL.	●	**1T8027EL**	**1T8028EL**
DALI	○	**1T8025DA**	**1T8026DA**
DALI	●	**1T8027DA**	**1T8028DA**
CASAMBI	○	**1T8025CA**	**1T8026CA**
CASAMBI	●	**1T8027CA**	**1T8028CA**

LED / 51W / HYBRID / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			17°	
Fixture Power		54W	1	0.30	26788
Source Flux		4985lm	2	0.60	6697
Fixture Flux		2817lm	3	0.89	2976
Efficacy		52lm/W	4	1.19	1674
TS1228	Imax=5374cd/klm	Imax	26788cd	5	1.49	1072

Driver	Colour	3000K	4000K
EL.	○	**1T8029EL**	**1T8030EL**
EL.	●	**1T8031EL**	**1T8032EL**
DALI	○	**1T8029DA**	**1T8030DA**
DALI	●	**1T8031DA**	**1T8032DA**
CASAMBI	○	**1T8029CA**	**1T8030CA**
CASAMBI	●	**1T8031CA**	**1T8032CA**

LED / 51W / HYBRID / FL (27°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			27°	
Fixture Power		54W	1	0.47	15064
Source Flux		4985lm	2	0.94	3766
Fixture Flux		3194lm	3	1.42	1674
Efficacy		59lm/W	4	1.89	942
TS1229	Imax=3022cd/klm	Imax	15064cd	5	2.36	603

Driver	Colour	3000K	4000K
EL.	○	**1T8033EL**	**1T8034EL**
EL.	●	**1T8035EL**	**1T8036EL**
DALI	○	**1T8033DA**	**1T8034DA**
DALI	●	**1T8035DA**	**1T8036DA**
CASAMBI	○	**1T8033CA**	**1T8034CA**
CASAMBI	●	**1T8035CA**	**1T8036CA**

LED / 51W / REFLECTOR / FL (38°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			38°	
Fixture Power		54W	1	0.69	7001
Source Flux		4985lm	2	1.38	1750
Fixture Flux		4088lm	3	2.07	778
Efficacy		75lm/W	4	2.76	438
TS1230	Imax=1417cd/klm	Imax	7066cd	5	3.44	280

Driver	Colour	3000K	4000K
EL.	○	**1T8037EL**	**1T8038EL**
EL.	●	**1T8039EL**	**1T8040EL**
DALI	○	**1T8037DA**	**1T8038DA**
DALI	●	**1T8039DA**	**1T8040DA**
CASAMBI	○	**1T8037CA**	**1T8038CA**
CASAMBI	●	**1T8039CA**	**1T8040CA**

LED / 51W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			52°	
Fixture Power		54W	1	0.97	5123
Source Flux		4985lm	2	1.94	1281
Fixture Flux		4078lm	3	2.91	569
Efficacy		75lm/W	4	3.88	320
TS1231	Imax=1028cd/klm	Imax	5123cd	5	4.85	205

Driver	Colour	3000K	4000K
EL.	○	**1T8041EL**	**1T8042EL**
EL.	●	**1T8043EL**	**1T8044EL**
DALI	○	**1T8041DA**	**1T8042DA**
DALI	●	**1T8043DA**	**1T8044DA**
CASAMBI	○	**1T8041CA**	**1T8042CA**
CASAMBI	●	**1T8043CA**	**1T8044CA**

ZENO

LED / 52W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra97			34°	80°	
Fixture Power	56W	1	0.98	1.98	1758
Source Flux	4995lm	2	1.96	3.97	440
Fixture Flux	2410lm	3	2.94	5.95	195
Efficacy	43lm/W	4	3.92	7.94	110
TS1232 Imax=520cd/klm	Imax 2599cd	5	4.91	9.92	70

Driver	Colour	3000K	4000K
EL.	○	**1T8045EL**	**1T8046EL**
EL.	●	**1T8047EL**	**1T8048EL**
DALI	○	**1T8045DA**	**1T8046DA**
DALI	●	**1T8047DA**	**1T8048DA**
CASAMBI	○	**1T8045CA**	**1T8046CA**
CASAMBI	●	**1T8047CA**	**1T8048CA**

Large
1-10V(DIMM ON BOARD)



LED / 26W / INDIRECT / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	28W	1	0.15	48054
Source Flux	2407lm	2	0.31	12013
Fixture Flux	1425lm	3	0.46	5339
Efficacy	51lm/W	4	0.62	3003
TS1227 Imax=19964cd/klm	Imax 48054cd	5	0.77	1922

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8025D**	**1T8026D**
1-10V (DIMM ON BOARD)	●	**1T8027D**	**1T8028D**

LED / 51W / HYBRID / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			17°	
Fixture Power	54W	1	0.30	26788
Source Flux	4985lm	2	0.60	6697
Fixture Flux	2817lm	3	0.89	2976
Efficacy	52lm/W	4	1.19	1674
TS1228 Imax=5374cd/klm	Imax 26788cd	5	1.49	1072

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8029D**	**1T8030D**
1-10V (DIMM ON BOARD)	●	**1T8031D**	**1T8032D**

LED / 51W / HYBRID / FL (27°)



3000K		H(m)	D(m)	Emax(lx)
Ra97			27°	
Fixture Power	54W	1	0.47	15064
Source Flux	4985lm	2	0.94	3766
Fixture Flux	3194lm	3	1.42	1674
Efficacy	59lm/W	4	1.89	942
TS1229 Imax=3022cd/klm	Imax 15064cd	5	2.36	603

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8033D**	**1T8034D**
1-10V (DIMM ON BOARD)	●	**1T8035D**	**1T8036D**

LED / 51W / REFLECTOR / FL (38°)



3000K		H(m)	D(m)	Emax(lx)
Ra97			38°	
Fixture Power	54W	1	0.69	7001
Source Flux	4985lm	2	1.38	1750
Fixture Flux	4088lm	3	2.07	778
Efficacy	75lm/W	4	2.76	438
TS1230 Imax=1417cd/klm	Imax 7066cd	5	3.44	280

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8037D**	**1T8038D**
1-10V (DIMM ON BOARD)	●	**1T8039D**	**1T8040D**

ZENO

LED / 51W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			52°	
Fixture Power		54W	1	0.97	5123
Source Flux		4985lm	2	1.94	1281
Fixture Flux		4078lm	3	2.91	569
Efficacy		75lm/W	4	3.88	320
TS1231	Imax=1028cd/klm	Imax	5	4.85	205

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8041D**	**1T8042D**
1-10V (DIMM ON BOARD)	◐	**1T8043D**	**1T8044D**

LED / 52W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra97			34°	80°	
Fixture Power		56W	1	0.98	1.98	1758
Source Flux		4995lm	2	1.96	3.97	440
Fixture Flux		2410lm	3	2.94	5.95	195
Efficacy		43lm/W	4	3.92	7.94	110
TS1232	Imax=520cd/klm	Imax	5	4.91	9.92	70

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8045D**	**1T8046D**
1-10V (DIMM ON BOARD)	◐	**1T8047D**	**1T8048D**

Accessories

Filter



Code
1T6054

Blade of light filter.
Methacrylate holographic filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with a dedicated holder ring.

Grid



Colour	Code
◐	**1T6055**

Anti-glare louver.
Black lacquered aluminium honeycomb structure.
To be completed with a dedicated holder ring.

Cut-off

Colour	Code
◐	**1T6056**

Black painted steel cut-off.
To be completed with a dedicated holder ring.



Colour	Code
◐	**1T6057**

Black painted steel asymmetric cut-off.
To be completed with a dedicated holder ring.

Ray Shade



Colour	Code
◐	**1T6058**

Adjustable barn doors flaps made of black painted steel.
To be completed with a dedicated holder ring.

Holder Ring



Colour	Code
○	**1T6053**
◐	**1T6500**

Black painted aluminium accessory holder ring.

ZENO

Medium ELECTRONIC



LED / 18W / INDIRECT / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	20W	1	0.15	44136
Source Flux	2211lm	2	0.31	11034
Fixture Flux	1308lm	3	0.46	4904
Efficacy	65lm/W	4	0.62	2759
TS1219 Imax=19964cd/klm	Imax	44136cd	5	0.77	1765

Driver	Colour	3000K	4000K
EL.	○	**1T7997EL**	**1T7998EL**
EL.	●	**1T7999EL**	**1T8000EL**

LED / 26W / HYBRID / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	28W	1	0.27	17721
Source Flux	2602lm	2	0.55	4430
Fixture Flux	1719lm	3	0.82	1969
Efficacy	61lm/W	4	1.10	1108
TS1220 Imax=6811cd/klm	Imax	17721cd	5	1.37	709

Driver	Colour	3000K	4000K
EL.	○	**1T8001EL**	**1T8002EL**
EL.	●	**1T8003EL**	**1T8004EL**

LED / 26W / HYBRID / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			32°	
Fixture Power	28W	1	0.56	5622
Source Flux	2602lm	2	1.13	1405
Fixture Flux	1554lm	3	1.69	625
Efficacy	55lm/W	4	2.26	351
TS1221 Imax=2161cd/klm	Imax	5622cd	5	2.82	225

Driver	Colour	3000K	4000K
EL.	○	**1T8005EL**	**1T8006EL**
EL.	●	**1T8007EL**	**1T8008EL**

LED / 26W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			46°	
Fixture Power	28W	1	0.84	3642
Source Flux	2602lm	2	1.68	911
Fixture Flux	2128lm	3	2.52	405
Efficacy	76lm/W	4	3.37	228
TS1222 Imax=1417cd/klm	Imax	3687cd	5	4.21	146

Driver	Colour	3000K	4000K
EL.	○	**1T8009EL**	**1T8010EL**
EL.	●	**1T8011EL**	**1T8012EL**

LED / 26W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			59°	
Fixture Power	28W	1	1.12	2590
Source Flux	2602lm	2	2.24	648
Fixture Flux	2136lm	3	3.36	288
Efficacy	76lm/W	4	4.48	162
TS1223 Imax=996cd/klm	Imax	2592cd	5	5.60	104

Driver	Colour	3000K	4000K
EL.	○	**1T8013EL**	**1T8014EL**
EL.	●	**1T8015EL**	**1T8016EL**

ZENO

LED / 26W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra97			34°	54°	
Fixture Power	28W	1	1.06	1.16	1335
Source Flux	2602lm	2	2.11	2.33	334
Fixture Flux	1473lm	3	3.17	3.49	148
Efficacy	53lm/W	4	4.23	4.65	83
TS1224 Imax=745cd/klm	Imax 1939cd	5	5.28	5.81	53

Driver	Colour	3000K	4000K
EL.	○	**1T8017EL**	**1T8018EL**
EL.	●	**1T8019EL**	**1T8020EL**

Medium
1-10V (DIMM ON BOARD)



LED / 18W / INDIRECT / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	20W	1	0.15	44136
Source Flux	2211lm	2	0.31	11034
Fixture Flux	1308lm	3	0.46	4904
Efficacy	65lm/W	4	0.62	2759
TS1219 Imax=19964cd/klm	Imax 44136cd	5	0.77	1765

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T7997D**	**1T7998D**
1-10V (DIMM ON BOARD)	●	**1T7999D**	**1T8000D**

LED / 26W / HYBRID / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	28W	1	0.27	17721
Source Flux	2602lm	2	0.55	4430
Fixture Flux	1719lm	3	0.82	1969
Efficacy	61lm/W	4	1.10	1108
TS1220 Imax=6811cd/klm	Imax 17721cd	5	1.37	709

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8001D**	**1T8002D**
1-10V (DIMM ON BOARD)	●	**1T8003D**	**1T8004D**

LED / 26W / HYBRID / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			32°	
Fixture Power	28W	1	0.56	5622
Source Flux	2602lm	2	1.13	1405
Fixture Flux	1554lm	3	1.69	625
Efficacy	55lm/W	4	2.26	351
TS1221 Imax=2161cd/klm	Imax 5622cd	5	2.82	225

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8005D**	**1T8006D**
1-10V (DIMM ON BOARD)	●	**1T8007D**	**1T8008D**

LED / 26W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			46°	
Fixture Power	28W	1	0.84	3642
Source Flux	2602lm	2	1.68	911
Fixture Flux	2128lm	3	2.52	405
Efficacy	76lm/W	4	3.37	228
TS1222 Imax=1417cd/klm	Imax 3687cd	5	4.21	146

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8009D**	**1T8010D**
1-10V (DIMM ON BOARD)	●	**1T8011D**	**1T8012D**

ZENO

LED / 26W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			59°	
Fixture Power	28W	1	1.12	2590
Source Flux	2602lm	2	2.24	648
Fixture Flux	2136lm	3	3.36	288
Efficacy	76lm/W	4	4.48	162
TS1223 Imax=996cd/klm	Imax	2592cd	5	5.60	104

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8013D**	**1T8014D**
1-10V (DIMM ON BOARD)	●	**1T8015D**	**1T8016D**

LED / 26W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra97			34°	54°	
Fixture Power	28W	1	1.06	1.16	1335
Source Flux	2602lm	2	2.11	2.33	334
Fixture Flux	1473lm	3	3.17	3.49	148
Efficacy	53lm/W	4	4.23	4.65	83
TS1224 Imax=745cd/klm	Imax	1939cd	5	5.28	5.81	53

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8017D**	**1T8018D**
1-10V (DIMM ON BOARD)	●	**1T8019D**	**1T8020D**

Medium DALI



LED / 18W / INDIRECT / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	20W	1	0.15	44136
Source Flux	2211lm	2	0.31	11034
Fixture Flux	1308lm	3	0.46	4904
Efficacy	65lm/W	4	0.62	2759
TS1219 Imax=19964cd/klm	Imax	44136cd	5	0.77	1765

Driver	Colour	3000K	4000K
DALI	○	**1T7997DA**	**1T7998DA**
DALI	●	**1T7999DA**	**1T8000DA**

LED / 26W / HYBRID / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	28W	1	0.27	17721
Source Flux	2602lm	2	0.55	4430
Fixture Flux	1719lm	3	0.82	1969
Efficacy	61lm/W	4	1.10	1108
TS1220 Imax=6811cd/klm	Imax	17721cd	5	1.37	709

Driver	Colour	3000K	4000K
DALI	○	**1T8001DA**	**1T8002DA**
DALI	●	**1T8003DA**	**1T8004DA**

LED / 26W / HYBRID / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			32°	
Fixture Power	28W	1	0.56	5622
Source Flux	2602lm	2	1.13	1405
Fixture Flux	1554lm	3	1.69	625
Efficacy	55lm/W	4	2.26	351
TS1221 Imax=2161cd/klm	Imax	5622cd	5	2.82	225

Driver	Colour	3000K	4000K
DALI	○	**1T8005DA**	**1T8006DA**
DALI	●	**1T8007DA**	**1T8008DA**

ZENO

LED / 26W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			46°	
Fixture Power	28W	1	0.84	3642
Source Flux	2602lm	2	1.68	911
Fixture Flux	2128lm	3	2.52	405
Efficacy	76lm/W	4	3.37	228
TS1222 Imax=1417cd/klm	Imax	3687cd	5	4.21	146

Driver	Colour	3000K	4000K
DALI	○	**1T8009DA**	**1T8010DA**
DALI	◐	**1T8011DA**	**1T8012DA**

LED / 26W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			59°	
Fixture Power	28W	1	1.12	2590
Source Flux	2602lm	2	2.24	648
Fixture Flux	2136lm	3	3.36	288
Efficacy	76lm/W	4	4.48	162
TS1223 Imax=996cd/klm	Imax	2592cd	5	5.60	104

Driver	Colour	3000K	4000K
DALI	○	**1T8013DA**	**1T8014DA**
DALI	◐	**1T8015DA**	**1T8016DA**

LED / 26W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra97			34°	54°	
Fixture Power	28W	1	1.06	1.16	1335
Source Flux	2602lm	2	2.11	2.33	334
Fixture Flux	1473lm	3	3.17	3.49	148
Efficacy	53lm/W	4	4.23	4.65	83
TS1224 Imax=745cd/klm	Imax	1939cd	5	5.28	5.81	53

Driver	Colour	3000K	4000K
DALI	○	**1T8017DA**	**1T8018DA**
DALI	◐	**1T8019DA**	**1T8020DA**

Medium CASAMBI



LED / 18W / INDIRECT / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	20W	1	0.15	44136
Source Flux	2211lm	2	0.31	11034
Fixture Flux	1308lm	3	0.46	4904
Efficacy	65lm/W	4	0.62	2759
TS1219 Imax=19964cd/klm	Imax	44136cd	5	0.77	1765

Driver	Colour	3000K	4000K
CASAMBI	○	**1T7997CA**	**1T7998CA**
CASAMBI	◐	**1T7999CA**	**1T8000CA**

LED / 26W / HYBRID / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	28W	1	0.27	17721
Source Flux	2602lm	2	0.55	4430
Fixture Flux	1719lm	3	0.82	1969
Efficacy	61lm/W	4	1.10	1108
TS1220 Imax=6811cd/klm	Imax	17721cd	5	1.37	709

Driver	Colour	3000K	4000K
CASAMBI	○	**1T8001CA**	**1T8002CA**
CASAMBI	◐	**1T8003CA**	**1T8004CA**

ZENO

LED / 26W / HYBRID / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			32°	
Fixture Power	28W		1	0.56	5622
Source Flux	2602lm		2	1.13	1405
Fixture Flux	1554lm		3	1.69	625
Efficacy	55lm/W		4	2.26	351
TS1221	Imax=2161cd/klm	Imax	5622cd	2.82	225

Driver	Colour	3000K	4000K
CASAMBI	○	**1T8005CA**	**1T8006CA**
CASAMBI	◐	**1T8007CA**	**1T8008CA**

LED / 26W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			46°	
Fixture Power	28W		1	0.84	3642
Source Flux	2602lm		2	1.68	911
Fixture Flux	2128lm		3	2.52	405
Efficacy	76lm/W		4	3.37	228
TS1222	Imax=1417cd/klm	Imax	3687cd	4.21	146

Driver	Colour	3000K	4000K
CASAMBI	○	**1T8009CA**	**1T8010CA**
CASAMBI	◐	**1T8011CA**	**1T8012CA**

LED / 26W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power	28W		1	1.12	2590
Source Flux	2602lm		2	2.24	648
Fixture Flux	2136lm		3	3.36	288
Efficacy	76lm/W		4	4.48	162
TS1223	Imax=996cd/klm	Imax	2592cd	5.60	104

Driver	Colour	3000K	4000K
CASAMBI	○	**1T8013CA**	**1T8014CA**
CASAMBI	◐	**1T8015CA**	**1T8016CA**

LED / 26W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra97			34°	54°	
Fixture Power	28W		1	1.06	1.16	1335
Source Flux	2602lm		2	2.11	2.33	334
Fixture Flux	1473lm		3	3.17	3.49	148
Efficacy	53lm/W		4	4.23	4.65	83
TS1224	Imax=745cd/klm	Imax	1939cd	5.28	5.81	53

Driver	Colour	3000K	4000K
CASAMBI	○	**1T8017CA**	**1T8018CA**
CASAMBI	◐	**1T8019CA**	**1T8020CA**

Medium DBS



LED / 26W / DBS



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			16°	
Fixture Power	28W		1	0.27	17721
Source Flux	2602lm		2	0.55	4430
Fixture Flux	1719lm		3	0.82	1969
Efficacy	61lm/W		4	1.10	1108
TS1225	Imax=6811cd/klm	Imax	17721cd	1.37	709



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power	28W		1	1.12	2590
Source Flux	2602lm		2	2.24	648
Fixture Flux	2136lm		3	3.36	288
Efficacy	76lm/W		4	4.48	162
TS1225	Imax=996cd/klm	Imax	2592cd	5.60	104

Driver	Colour	3000K	4000K
CASAMBI	○	**1T8021CA**	**1T8022CA**
CASAMBI	◐	**1T8023CA**	**1T8024CA**

Accessories

Filter



Code
1T6060

Blade of light filter.
Methacrylate holographic filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with a dedicated holder ring.

Grid



Colour	Code
●	**1T6061**

Anti-glare louver.
Black lacquered aluminium honeycomb structure.
To be completed with a dedicated holder ring.

Cut-off

Colour	Code
●	**1T6062**

Black painted steel cut-off.
To be completed with a dedicated holder ring.



Colour	Code
◐	**1T6063**

Black painted steel asymmetric cut-off.
To be completed with a dedicated holder ring.

Ray Shade



Colour	Code
●	**1T6064**

Adjustable barn doors flaps made of black painted steel.
To be completed with a dedicated holder ring.

Holder Ring



Colour	Code
○	**1T6059**
◐	**1T6501**

Black painted aluminium accessory holder ring.

ZENO

Medium Zoom ELECTRONIC



LED / 26W / ZOOM / SP-WFL

	Driver	Colour	3000K	4000K
	EL.	○	**1T8174EL**	**1T8175EL**
	EL.	◐	**1T8176EL**	**1T8177EL**



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	29W	1	0.16	11378
Source Flux	2556lm	2	0.32	2845
Fixture Flux	396lm	3	0.49	1264
Efficacy	14lm/W	4	0.65	711
Imax	11378cd	5	0.81	455

TS1226 Imax=4452cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra97			13°	
Fixture Power	29W	1	0.23	10919
Source Flux	2556lm	2	0.45	2730
Fixture Flux	641lm	3	0.68	1213
Efficacy	22lm/W	4	0.91	682
Imax	10919cd	5	1.14	437

TS1233 Imax=4272cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra97			31°	
Fixture Power	29W	1	0.55	3706
Source Flux	2556lm	2	1.10	927
Fixture Flux	978lm	3	1.65	412
Efficacy	34lm/W	4	2.19	232
Imax	3815cd	5	2.74	148

TS1234 Imax=1493cd/klm

Medium Zoom 1-10V (DIMM ON BOARD)



LED / 26W / ZOOM / SP-WFL

	Driver	Colour	3000K	4000K
	1-10V (DIMM ON BOARD)	○	**1T8174D**	**1T8175D**
	1-10V (DIMM ON BOARD)	◐	**1T8176D**	**1T8177D**



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	29W	1	0.16	11378
Source Flux	2556lm	2	0.32	2845
Fixture Flux	396lm	3	0.49	1264
Efficacy	14lm/W	4	0.65	711
Imax	11378cd	5	0.81	455

TS1226 Imax=4452cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra97			13°	
Fixture Power	29W	1	0.23	10919
Source Flux	2556lm	2	0.45	2730
Fixture Flux	641lm	3	0.68	1213
Efficacy	22lm/W	4	0.91	682
Imax	10919cd	5	1.14	437

TS1233 Imax=4272cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra97			31°	
Fixture Power	29W	1	0.55	3706
Source Flux	2556lm	2	1.10	927
Fixture Flux	978lm	3	1.65	412
Efficacy	34lm/W	4	2.19	232
Imax	3815cd	5	2.74	148

TS1234 Imax=1493cd/klm

ZENO

Medium Zoom DALI



LED / 26W / ZOOM / SP-WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	29W	1	0.16	11378
Source Flux	2556lm	2	0.32	2845
Fixture Flux	396lm	3	0.49	1264
Efficacy	14lm/W	4	0.65	711
TS1226 Imax=4452cd/klm	Imax	11378cd	5	0.81	455

	Driver	Colour	3000K	4000K
	DALI	○	**1T8174DA**	**1T8175DA**
	DALI	◐	**1T8176DA**	**1T8177DA**



3000K		H(m)	D(m)	Emax(lx)
Ra97			13°	
Fixture Power	29W	1	0.23	10919
Source Flux	2556lm	2	0.45	2730
Fixture Flux	641lm	3	0.68	1213
Efficacy	22lm/W	4	0.91	682
TS1233 Imax=4272cd/klm	Imax	10919cd	5	1.14	437



3000K		H(m)	D(m)	Emax(lx)
Ra97			31°	
Fixture Power	29W	1	0.55	3706
Source Flux	2556lm	2	1.10	927
Fixture Flux	978lm	3	1.65	412
Efficacy	34lm/W	4	2.19	232
TS1234 Imax=1493cd/klm	Imax	3815cd	5	2.74	148

Medium Zoom CASAMBI



LED / 26W / ZOOM / SP-WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			9°	
Fixture Power	29W	1	0.16	11378
Source Flux	2556lm	2	0.32	2845
Fixture Flux	396lm	3	0.49	1264
Efficacy	14lm/W	4	0.65	711
TS1226 Imax=4452cd/klm	Imax	11378cd	5	0.81	455

	Driver	Colour	3000K	4000K
	CASAMBI	○	**1T8174CA**	**1T8175CA**
	CASAMBI	◐	**1T8176CA**	**1T8177CA**



3000K		H(m)	D(m)	Emax(lx)
Ra97			13°	
Fixture Power	29W	1	0.23	10919
Source Flux	2556lm	2	0.45	2730
Fixture Flux	641lm	3	0.68	1213
Efficacy	22lm/W	4	0.91	682
TS1233 Imax=4272cd/klm	Imax	10919cd	5	1.14	437



3000K		H(m)	D(m)	Emax(lx)
Ra97			31°	
Fixture Power	29W	1	0.55	3706
Source Flux	2556lm	2	1.10	927
Fixture Flux	978lm	3	1.65	412
Efficacy	34lm/W	4	2.19	232
TS1234 Imax=1493cd/klm	Imax	3815cd	5	2.74	148

ZENO

Small ELECTRONIC



LED / 9,4W / LENS+HONEYCOMB / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			7°	
	Fixture Power	11W	1	0.13	20546
	Source Flux	825lm	2	0.25	5137
	Fixture Flux	574lm	3	0.38	2283
	Efficacy	52lm/W	4	0.51	1284
TS1409	Imax=24905cd/klm	Imax	20546cd	5	0.63	822

Driver	Colour	3000K	4000K
EL.	○	**1T8178EL**	**1T8179EL**
EL.	●	**1T8180EL**	**1T8181EL**

LED / 12W / LENS+HONEYCOMB / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			16°	
	Fixture Power	14W	1	0.28	6374
	Source Flux	1427lm	2	0.56	1593
	Fixture Flux	726lm	3	0.84	708
	Efficacy	52lm/W	4	1.12	398
TS1410	Imax=4467cd/klm	Imax	6374cd	5	1.40	255

Driver	Colour	3000K	4000K
EL.	○	**1T8182EL**	**1T8183EL**
EL.	●	**1T8184EL**	**1T8185EL**

LED / 12W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			28°	
	Fixture Power	14W	1	0.49	4527
	Source Flux	1427lm	2	0.99	1132
	Fixture Flux	1113lm	3	1.48	503
	Efficacy	79lm/W	4	1.98	283
TS1411	Imax=3172cd/klm	Imax	4527cd	5	2.47	181

Driver	Colour	3000K	4000K
EL.	○	**1T8186EL**	**1T8187EL**
EL.	●	**1T8188EL**	**1T8189EL**

LED / 12W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			48°	
	Fixture Power	14W	1	0.90	1860
	Source Flux	1430lm	2	1.79	465
	Fixture Flux	1178lm	3	2.69	207
	Efficacy	87lm/W	4	3.59	116
TS1066	Imax=1307cd/klm	Imax	1870cd	5	4.48	74

Driver	Colour	3000K	4000K
EL.	○	**1T6543EL**	**1T6544EL**
EL.	●	**1T6545EL**	**1T6546EL**

LED / 12W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			58°	
	Fixture Power	14W	1	1.11	1400
	Source Flux	1430lm	2	2.21	350
	Fixture Flux	1188lm	3	3.32	156
	Efficacy	88lm/W	4	4.43	88
TS1067	Imax=1001cd/klm	Imax	1432cd	5	5.53	56

Driver	Colour	3000K	4000K
EL.	○	**1T6547EL**	**1T6548EL**
EL.	●	**1T6549EL**	**1T6550EL**

ZENO

Small
1-10V (DIMM ON BOARD)



LED / 9,4W / LENS+HONEYCOMB / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			7°	
Fixture Power	11W	1	0.13	20546
Source Flux	825lm	2	0.25	5137
Fixture Flux	574lm	3	0.38	2283
Efficacy	52lm/W	4	0.51	1284
Imax	20546cd	5	0.63	822

TS1409 Imax=24905cd/klm

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8178D**	**1T8179D**
1-10V (DIMM ON BOARD)	●	**1T8180D**	**1T8181D**

LED / 12W / LENS+HONEYCOMB / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	14W	1	0.28	6374
Source Flux	1427lm	2	0.56	1593
Fixture Flux	726lm	3	0.84	708
Efficacy	52lm/W	4	1.12	398
Imax	6374cd	5	1.40	255

TS1410 Imax=4467cd/klm

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8182D**	**1T8183D**
1-10V (DIMM ON BOARD)	●	**1T8184D**	**1T8185D**

LED / 12W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			28°	
Fixture Power	14W	1	0.49	4527
Source Flux	1427lm	2	0.99	1132
Fixture Flux	1113lm	3	1.48	503
Efficacy	79lm/W	4	1.98	283
Imax	4527cd	5	2.47	181

TS1411 Imax=3172cd/klm

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T8186D**	**1T8187D**
1-10V (DIMM ON BOARD)	●	**1T8188D**	**1T8189D**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			48°	
Fixture Power	14W	1	0.90	1860
Source Flux	1430lm	2	1.79	465
Fixture Flux	1178lm	3	2.69	207
Efficacy	87lm/W	4	3.59	116
Imax	1870cd	5	4.48	74

TS1066 Imax=1307cd/klm

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T6543D**	**1T6544D**
1-10V (DIMM ON BOARD)	●	**1T6545D**	**1T6546D**

LED / 12W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			58°	
Fixture Power	14W	1	1.11	1400
Source Flux	1430lm	2	2.21	350
Fixture Flux	1188lm	3	3.32	156
Efficacy	88lm/W	4	4.43	88
Imax	1432cd	5	5.53	56

TS1067 Imax=1001cd/klm

Driver	Colour	3000K	4000K
1-10V (DIMM ON BOARD)	○	**1T6547D**	**1T6548D**
1-10V (DIMM ON BOARD)	●	**1T6549D**	**1T6550D**

ZENO

Small DALI



LED / 9,4W / LENS+HONEYCOMB / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			7°	
Fixture Power	11W	1	0.13	20546
Source Flux	825lm	2	0.25	5137
Fixture Flux	574lm	3	0.38	2283
Efficacy	52lm/W	4	0.51	1284
Imax	20546cd	5	0.63	822

TS1409 Imax=24905cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T8178DA**	**1T8179DA**
DALI	●	**1T8180DA**	**1T8181DA**

LED / 12W / LENS+HONEYCOMB / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	14W	1	0.28	6374
Source Flux	1427lm	2	0.56	1593
Fixture Flux	726lm	3	0.84	708
Efficacy	52lm/W	4	1.12	398
Imax	6374cd	5	1.40	255

TS1410 Imax=4467cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T8182DA**	**1T8183DA**
DALI	●	**1T8184DA**	**1T8185DA**

LED / 12W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			28°	
Fixture Power	14W	1	0.49	4527
Source Flux	1427lm	2	0.99	1132
Fixture Flux	1113lm	3	1.48	503
Efficacy	79lm/W	4	1.98	283
Imax	4527cd	5	2.47	181

TS1411 Imax=3172cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T8186DA**	**1T8187DA**
DALI	●	**1T8188DA**	**1T8189DA**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			48°	
Fixture Power	14W	1	0.90	1860
Source Flux	1430lm	2	1.79	465
Fixture Flux	1178lm	3	2.69	207
Efficacy	87lm/W	4	3.59	116
Imax	1870cd	5	4.48	74

TS1066 Imax=1307cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T6543DA**	**1T6544DA**
DALI	●	**1T6545DA**	**1T6546DA**

LED / 12W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			58°	
Fixture Power	14W	1	1.11	1400
Source Flux	1430lm	2	2.21	350
Fixture Flux	1188lm	3	3.32	156
Efficacy	88lm/W	4	4.43	88
Imax	1432cd	5	5.53	56

TS1067 Imax=1001cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T6547DA**	**1T6548DA**
DALI	●	**1T6549DA**	**1T6550DA**

ZENO

Small CASAMBI



LED / 9,4W / LENS+HONEYCOMB / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra97			7°	
Fixture Power	11W	1	0.13	20546
Source Flux	825lm	2	0.25	5137
Fixture Flux	574lm	3	0.38	2283
Efficacy	52lm/W	4	0.51	1284
Imax	20546cd	5	0.63	822

TS1409 Imax=24905cd/klm

Driver	Colour	3000K	4000K
CASAMBI	○	**1T7977CA**	**1T7978CA**
CASAMBI	●	**1T7979CA**	**1T7980CA**

LED / 12W / LENS+HONEYCOMB / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	14W	1	0.28	6374
Source Flux	1427lm	2	0.56	1593
Fixture Flux	726lm	3	0.84	708
Efficacy	52lm/W	4	1.12	398
Imax	6374cd	5	1.40	255

TS1410 Imax=4467cd/klm

Driver	Colour	3000K	4000K
CASAMBI	○	**1T7981CA**	**1T7982CA**
CASAMBI	●	**1T7983CA**	**1T7984CA**

LED / 12W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			28°	
Fixture Power	14W	1	0.49	4527
Source Flux	1427lm	2	0.99	1132
Fixture Flux	1113lm	3	1.48	503
Efficacy	79lm/W	4	1.98	283
Imax	4527cd	5	2.47	181

TS1411 Imax=3172cd/klm

Driver	Colour	3000K	4000K
CASAMBI	○	**1T7985CA**	**1T7986CA**
CASAMBI	●	**1T7987CA**	**1T7988CA**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			48°	
Fixture Power	14W	1	0.90	1817
Source Flux	1397lm	2	1.79	454
Fixture Flux	1151lm	3	2.69	202
Efficacy	82lm/W	4	3.59	114
Imax	1827cd	5	4.48	73

TS1238 Imax=1307cd/klm

Driver	Colour	3000K	4000K
CASAMBI	○	**1T7989CA**	**1T7990CA**
CASAMBI	●	**1T7991CA**	**1T7992CA**

LED / 12W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			58°	
Fixture Power	14W	1	1.11	1368
Source Flux	1397lm	2	2.21	342
Fixture Flux	1161lm	3	3.32	152
Efficacy	83lm/W	4	4.43	86
Imax	1399cd	5	5.53	55

TS1239 Imax=1001cd/klm

Driver	Colour	3000K	4000K
CASAMBI	○	**1T7993CA**	**1T7994CA**
CASAMBI	●	**1T7995CA**	**1T7996CA**

Accessories

Filter

	Code
	1T6572

Blade of light filter.
Methacrylate holographic filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with a dedicated holder ring.

Grid

	Colour	Code
	●	**1T6573**

Anti-glare louver.
Black lacquered aluminium honeycomb structure.
To be completed with a dedicated holder ring.
Not to be used with NSP and SP optics.

Cut-off

	Colour	Code
	●	**1T6574**

Black painted steel cut-off.
To be completed with a dedicated holder ring.

	Colour	Code
	●	**1T6575**

Black painted steel asymmetric cut-off.
To be completed with a dedicated holder ring.

Ray Shade

	Colour	Code
	●	**1T6576**

Adjustable barn doors flaps made of black painted steel.
To be completed with a dedicated holder ring.

Holder Ring

	Colour	Code
	●	**1T6571**

Black painted aluminium accessory holder ring.

LABEL 230V

GENERAL INFO
Adjustable professional LED projector.
The optical unit can be adjusted from 0° a 90° on the vertical plane and 355° on the horizontal plane with the possibility to block the beam on the horizontal plane (friction blocking system on the vertical plane).
Ø60mm – Ø74mm – Ø88mm

LED
Chip on board
From 2100lm to 3287lm
3000K – 4000K
Ra97

PRODUCT EFFICACY
Up to 90lm/W

OPTICS
SP – FL – MWFL

POWER SUPPLY
Electronic – DALI
Casambi control system available as an accessory (only for DALI versions).

MATERIAL
Die-cast painted aluminium body.

ON DEMAND
Easy Custom Colour
2700K - 3500K

A range of coordinated projectors for track installation with retractable power supplies designed for application in retail, interior and hospitality environments. Available in three different sizes - Label 6, Label 7 and Label 9.

Label 6 and Label 7 can be equipped with two different optical systems: with a reflector for soft effects with low visual contrast and lenses for more defined beams. Label 9 is available with a reflector optical system. The LED source is particularly setback to ensure excellent visual comfort.

		Label 6	Label 7	Label 9
		Ø 59mm	Ø 74mm	Ø 88mm
LED	Flux (lm)	1683-2223	2550-2818	2769-3287
	Power	19W	25W	25-31W
OPTICS				
SP	Lenticular	•	•	
	Reflector	•	•	•
FL	Lenticular	•	•	
	Reflector	•	•	•
MWFL	Lenticular	•	•	
	Reflector	•	•	•

Rinascimento Store Teddy Spa Group
Cremona, Italy

Architect WOMArchitettura

Arch. Teresa D'Alessandro
Arch. Caterina Pulcinella

LABEL

Label 9 ELECTRONIC



LED / 31W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			16°	
Fixture Power		34W	1	0.29	17467
Source Flux		3207lm	2	0.57	4367
Fixture Flux		2322lm	3	0.86	1941
Efficacy		69lm/W	4	1.14	1092
TS1060	Imax=5446cd/klm	Imax	17467cd	5	1.43	699

Driver	Colour	3000K	4000K
EL.	○	**1T6600EL**	**1T6601EL**
EL.	◐	**1T6602EL**	**1T6603EL**
EL.	●	**1T6604EL**	**1T6605EL**

LED / 31W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			29°	
Fixture Power		34W	1	0.52	8572
Source Flux		3207lm	2	1.03	2143
Fixture Flux		2427lm	3	1.55	952
Efficacy		72lm/W	4	2.07	536
TS1061	Imax=2673cd/klm	Imax	8572cd	5	2.58	343

Driver	Colour	3000K	4000K
EL.	○	**1T6606EL**	**1T6607EL**
EL.	◐	**1T6608EL**	**1T6609EL**
EL.	●	**1T6610EL**	**1T6611EL**

LED / 31W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			46°	
Fixture Power		34W	1	0.85	4471
Source Flux		3207lm	2	1.70	1118
Fixture Flux		2384lm	3	2.55	497
Efficacy		71lm/W	4	3.40	279
TS1062	Imax=1426cd/klm	Imax	4572cd	5	4.25	179

Driver	Colour	3000K	4000K
EL.	○	**1T6612EL**	**1T6613EL**
EL.	◐	**1T6614EL**	**1T6615EL**
EL.	●	**1T6616EL**	**1T6617EL**

Label 9 DALI



LED / 25W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			16°	
Fixture Power		28W	1	0.29	15081
Source Flux		2769lm	2	0.57	3770
Fixture Flux		2005lm	3	0.86	1676
Efficacy		72lm/W	4	1.14	943
TS1060	Imax=5446cd/klm	Imax	15081cd	5	1.43	603

Driver	Colour	3000K	4000K
DALI	○	**1T6600DA**	**1T6601DA**
DALI	◐	**1T6602DA**	**1T6603DA**
DALI	●	**1T6604DA**	**1T6605DA**

LABEL

LED / 25W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			29°	
Fixture Power		28W	1	0.52	7401
Source Flux		2769lm	2	1.03	1850
Fixture Flux		2096lm	3	1.55	822
Efficacy		75lm/W	4	2.07	463
Imax		7401cd	5	2.58	296

Driver	Colour	3000K	4000K
DALI	○	**1T6606DA**	**1T6607DA**
DALI	◐	**1T6608DA**	**1T6609DA**
DALI	●	**1T6610DA**	**1T6611DA**

LED / 25W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			46°	
Fixture Power		28W	1	0.85	3860
Source Flux		2769lm	2	1.70	965
Fixture Flux		2058lm	3	2.55	429
Efficacy		74lm/W	4	3.40	241
Imax		3947cd	5	4.25	154

Driver	Colour	3000K	4000K
DALI	○	**1T6612DA**	**1T6613DA**
DALI	◐	**1T6614DA**	**1T6615DA**
DALI	●	**1T6616DA**	**1T6617DA**

Accessories

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Filter



Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.



Ø	Code
70	**1T1709**

Flat glass wired refractive diffusive filter.
This softens the luminous effect.
To be completed with an additional holder ring for Cloud, Ray Mini, Sore, Label 9 and CCTEvo Extractable 162.

Holder Ring

Code
1T3727

Transparent polycarbonate accessory holder ring.

Control systems

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

LABEL

Label 7 ELECTRONIC



LED / 25W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			21°	
	Fixture Power	29W	1	0.37	10484
	Source Flux	2723lm	2	0.75	2621
	Fixture Flux	1939lm	3	1.12	1165
	Efficacy	68lm/W	4	1.50	655
TS1240	Imax=3850cd/klm	Imax	10484cd	5	1.87	419

Driver	Colour	3000K	4000K
EL.	○	**1T8136EL**	**1T8137EL**
EL.	◐	**1T8138EL**	**1T8139EL**
EL.	●	**1T8140EL**	**1T8141EL**

LED / 25W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			33°	
	Fixture Power	29W	1	0.59	5917
	Source Flux	2723lm	2	1.18	1479
	Fixture Flux	2007lm	3	1.77	657
	Efficacy	70lm/W	4	2.36	370
TS1241	Imax=2173cd/klm	Imax	5917cd	5	2.95	237

Driver	Colour	3000K	4000K
EL.	○	**1T8142EL**	**1T8143EL**
EL.	◐	**1T8144EL**	**1T8145EL**
EL.	●	**1T8146EL**	**1T8147EL**

LED / 25W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			46°	
	Fixture Power	29W	1	0.85	3785
	Source Flux	2723lm	2	1.69	946
	Fixture Flux	2051lm	3	2.54	421
	Efficacy	71lm/W	4	3.39	237
TS1242	Imax=1390cd/klm	Imax	3786cd	5	4.23	151

Driver	Colour	3000K	4000K
EL.	○	**1T8148EL**	**1T8149EL**
EL.	◐	**1T8150EL**	**1T8151EL**
EL.	●	**1T8152EL**	**1T8153EL**

LED / 25W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			17°	
	Fixture Power	29W	1	0.30	19320
	Source Flux	2550lm	2	0.60	4830
	Fixture Flux	2126lm	3	0.90	2147
	Efficacy	73lm/W	4	1.19	1208
TS1260	Imax=7577cd/klm	Imax	19320cd	5	1.49	773

Driver	Colour	3000K	4000K
EL.	○	**1T8154EL**	**1T8155EL**
EL.	◐	**1T8156EL**	**1T8157EL**
EL.	●	**1T8158EL**	**1T8159EL**

LED / 25W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			26°	
	Fixture Power	29W	1	0.47	8430
	Source Flux	2550lm	2	0.94	2107
	Fixture Flux	2078lm	3	1.41	937
	Efficacy	72lm/W	4	1.88	527
TS1261	Imax=3306cd/klm	Imax	8430cd	5	2.35	337

Driver	Colour	3000K	4000K
EL.	○	**1T8160EL**	**1T8161EL**
EL.	◐	**1T8162EL**	**1T8163EL**
EL.	●	**1T8164EL**	**1T8165EL**

LABEL

LED / 25W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			41°	
Fixture Power	29W	1	0.75	4050
Source Flux	2550lm	2	1.49	1012
Fixture Flux	1984lm	3	2.24	450
Efficacy	68lm/W	4	2.99	253
Imax	4137cd	5	3.73	162

TS1262 Imax=1623cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T8166EL**	**1T8167EL**
EL.	◐	**1T8168EL**	**1T8169EL**
EL.	●	**1T8170EL**	**1T8171EL**

Label 7 DALI



LED / 25W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			21°	
Fixture Power	29W	1	0.37	10484
Source Flux	2723lm	2	0.75	2621
Fixture Flux	1939lm	3	1.12	1165
Efficacy	68lm/W	4	1.50	655
Imax	10484cd	5	1.87	419

TS1240 Imax=3850cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T8136DA**	**1T8137DA**
DALI	◐	**1T8138DA**	**1T8139DA**
DALI	●	**1T8140DA**	**1T8141DA**

LED / 25W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			33°	
Fixture Power	29W	1	0.59	5917
Source Flux	2723lm	2	1.18	1479
Fixture Flux	2007lm	3	1.77	657
Efficacy	70lm/W	4	2.36	370
Imax	5917cd	5	2.95	237

TS1241 Imax=2173cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T8142DA**	**1T8143DA**
DALI	◐	**1T8144DA**	**1T8145DA**
DALI	●	**1T8146DA**	**1T8147DA**

LED / 25W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			46°	
Fixture Power	29W	1	0.85	3785
Source Flux	2723lm	2	1.69	946
Fixture Flux	2051lm	3	2.54	421
Efficacy	71lm/W	4	3.39	237
Imax	3786cd	5	4.23	151

TS1242 Imax=1390cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T8148DA**	**1T8149DA**
DALI	◐	**1T8150DA**	**1T8151DA**
DALI	●	**1T8152DA**	**1T8153DA**

LED / 25W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			17°	
Fixture Power	29W	1	0.30	19320
Source Flux	2550lm	2	0.60	4830
Fixture Flux	2126lm	3	0.90	2147
Efficacy	73lm/W	4	1.19	1208
Imax	19320cd	5	1.49	773

TS1260 Imax=7577cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T8154DA**	**1T8155DA**
DALI	◐	**1T8156DA**	**1T8157DA**
DALI	●	**1T8158DA**	**1T8159DA**

LABEL

LED / 25W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			26°	
Fixture Power		29W	1	0.47	8430
Source Flux		2550lm	2	0.94	2107
Fixture Flux		2078lm	3	1.41	937
Efficacy		72lm/W	4	1.88	527
TS1261	Imax=3306cd/klm	Imax	8430cd	5	2.35	337

Driver	Colour	3000K	4000K
DALI	○	**1T8160DA**	**1T8161DA**
DALI	◐	**1T8162DA**	**1T8163DA**
DALI	●	**1T8164DA**	**1T8165DA**

LED / 25W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			41°	
Fixture Power		29W	1	0.75	4050
Source Flux		2550lm	2	1.49	1012
Fixture Flux		1984lm	3	2.24	450
Efficacy		68lm/W	4	2.99	253
TS1262	Imax=1623cd/klm	Imax	4137cd	5	3.73	162

Driver	Colour	3000K	4000K
DALI	○	**1T8166DA**	**1T8167DA**
DALI	◐	**1T8168DA**	**1T8169DA**
DALI	●	**1T8170DA**	**1T8171DA**

Accessories

Grid



Ø	Code
63	**1T8093**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Filter



Ø	Code
63	**1T8094**

Holographic PMMA filter with blade of light effect.
Allows the beam to be made oval; combined with spot and flood optics the effect appears more pronounced.

Control systems

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

LABEL

Label 6 ELECTRONIC



LED / 19W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			16°	
Fixture Power		21W	1	0.28	12581
Source Flux		2100lm	2	0.55	3145
Fixture Flux		1542lm	3	0.83	1398
Efficacy		73lm/W	4	1.11	786
TS1057	Imax=5991cd/klm	Imax	12581cd	5	1.39	503

Driver	Colour	3000K	4000K
EL.	○	**1T6582EL**	**1T6583EL**
EL.	◐	**1T6584EL**	**1T6585EL**
EL.	●	**1T6586EL**	**1T6587EL**

LED / 19W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			31°	
Fixture Power		21W	1	0.56	5165
Source Flux		2100lm	2	1.12	1291
Fixture Flux		1623lm	3	1.67	574
Efficacy		77lm/W	4	2.23	323
TS1058	Imax=2459cd/klm	Imax	5165cd	5	2.79	207

Driver	Colour	3000K	4000K
EL.	○	**1T6588EL**	**1T6589EL**
EL.	◐	**1T6590EL**	**1T6591EL**
EL.	●	**1T6592EL**	**1T6593EL**

LED / 19W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			48°	
Fixture Power		21W	1	0.88	2879
Source Flux		2100lm	2	1.77	720
Fixture Flux		1609lm	3	2.65	320
Efficacy		76lm/W	4	3.53	180
TS1059	Imax=1379cd/klm	Imax	2895cd	5	4.41	115

Driver	Colour	3000K	4000K
EL.	○	**1T6594EL**	**1T6595EL**
EL.	◐	**1T6596EL**	**1T6597EL**
EL.	●	**1T6598EL**	**1T6599EL**

LED / 21W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		23W	1	0.25	17173
Source Flux		1683lm	2	0.49	4293
Fixture Flux		1385lm	3	0.74	1908
Efficacy		60lm/W	4	0.99	1073
TS1294	Imax=10204cd/klm	Imax	17173cd	5	1.23	687

Driver	Colour	3000K	4000K
EL.	○	**1T9082EL**	**1T9083EL**
EL.	◐	**1T9084EL**	**1T9085EL**
EL.	●	**1T9086EL**	**1T9087EL**

LED / 19W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			26°	
Fixture Power		21W	1	0.47	7325
Source Flux		2100lm	2	0.94	1831
Fixture Flux		1798lm	3	1.40	814
Efficacy		86lm/W	4	1.87	458
TS1295	Imax=3488cd/klm	Imax	7325cd	5	2.34	293

Driver	Colour	3000K	4000K
EL.	○	**1T9088EL**	**1T9089EL**
EL.	◐	**1T9090EL**	**1T9091EL**
EL.	●	**1T9092EL**	**1T9093EL**

LABEL

LED / 19W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			41°	
Fixture Power	21W	1	0.75	3417
Source Flux	2100lm	2	1.50	854
Fixture Flux	1689lm	3	2.24	380
Efficacy	80lm/W	4	2.99	214
Imax	3488cd	5	3.74	137

TS1296 Imax=1661cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T9094EL**	**1T9095EL**
EL.	◐	**1T9096EL**	**1T9097EL**
EL.	●	**1T9098EL**	**1T9099EL**

Label 6 DALI



LED / 19W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			16°	
Fixture Power	21W	1	0.28	12581
Source Flux	2100lm	2	0.55	3145
Fixture Flux	1542lm	3	0.83	1398
Efficacy	73lm/W	4	1.11	786
Imax	12581cd	5	1.39	503

TS1057 Imax=5991cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T6582DA**	**1T6583DA**
DALI	◐	**1T6584DA**	**1T6585DA**
DALI	●	**1T6586DA**	**1T6587DA**

LED / 19W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra97			31°	
Fixture Power	21W	1	0.56	5165
Source Flux	2100lm	2	1.12	1291
Fixture Flux	1623lm	3	1.67	574
Efficacy	77lm/W	4	2.23	323
Imax	5165cd	5	2.79	207

TS1058 Imax=2459cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T6588DA**	**1T6589DA**
DALI	◐	**1T6590DA**	**1T6591DA**
DALI	●	**1T6592DA**	**1T6593DA**

LED / 19W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			48°	
Fixture Power	21W	1	0.88	2879
Source Flux	2100lm	2	1.77	720
Fixture Flux	1609lm	3	2.65	320
Efficacy	76lm/W	4	3.53	180
Imax	2895cd	5	4.41	115

TS1059 Imax=1379cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T6594DA**	**1T6595DA**
DALI	◐	**1T6596DA**	**1T6597DA**
DALI	●	**1T6598DA**	**1T6599DA**

LED / 21W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra97			14°	
Fixture Power	23W	1	0.25	17173
Source Flux	1683lm	2	0.49	4293
Fixture Flux	1385lm	3	0.74	1908
Efficacy	60lm/W	4	0.99	1073
Imax	17173cd	5	1.23	687

TS1294 Imax=10204cd/klm

Driver	Colour	3000K	4000K
DALI	○	**1T9082DA**	**1T9083DA**
DALI	◐	**1T9084DA**	**1T9085DA**
DALI	●	**1T9086DA**	**1T9087DA**

LABEL

LED / 19W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			26°	
	Fixture Power	21W	1	0.47	7325
	Source Flux	2100lm	2	0.94	1831
	Fixture Flux	1798lm	3	1.40	814
	Efficacy	86lm/W	4	1.87	458
	Imax	7325cd	5	2.34	293

Driver	Colour	3000K	4000K
DALI	○	**1T9088DA**	**1T9089DA**
DALI	◐	**1T9090DA**	**1T9091DA**
DALI	●	**1T9092DA**	**1T9093DA**

LED / 19W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			41°	
	Fixture Power	21W	1	0.75	3417
	Source Flux	2100lm	2	1.50	854
	Fixture Flux	1689lm	3	2.24	380
	Efficacy	80lm/W	4	2.99	214
	Imax	3488cd	5	3.74	137

Driver	Colour	3000K	4000K
DALI	○	**1T9094DA**	**1T9095DA**
DALI	◐	**1T9096DA**	**1T9097DA**
DALI	●	**1T9098DA**	**1T9099DA**

Accessories

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Filter



Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Control systems

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CAPSULE

GENERAL INFO
An adjustable professional LED projector. The optical unit can be adjusted from 0° to 90° on the vertical plane and 355° on the horizontal plane
Ø60mm – Ø70mm

LED
Chip on board
From 2095lm to 3700lm
3000K – 4000K
Ra90

PRODUCT EFFICACY
Up to 98lm/W

OPTICS
SP15 – SP24 - FL

POWER SUPPLY
Electronic

MATERIAL
Painted die-cast aluminium body.

A range of adjustable versatile projectors available in two different sizes, Capsule 6 (Ø60mm) and Capsule 7 (Ø70mm)
The optical unit can be adjusted from 0° to 90° on the vertical plane and 355° on the horizontal plane.

The projectors in the Capsule range are equipped with FL optics. The lens supplied has a 36° beam opening but it is easy to replace the lens to obtain a narrower beam. Already included in the package is a lens (SP15 optic) with a 15° beam and a lens for 24° beam openings is available as an accessory (SP24 optic). The LED source remains set back to ensure excellent visual comfort.

Capsule

Ø 60



LED / 18W / LENS / SP-FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			15°	
	Fixture Power	20W	1	0.35	6631
	Source Flux	2095lm	2	0.70	1658
	Fixture Flux	1706lm	3	1.05	737
	Efficacy	85lm/W	4	1.39	414
TS1129	Imax=3165cd/klm	Imax	6631cd	5	1.74	265



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			36°	
	Fixture Power	20W	1	0.72	3718
	Source Flux	2095lm	2	1.43	930
	Fixture Flux	1769lm	3	2.15	413
	Efficacy	88lm/W	4	2.87	232
TS1128	Imax=1776cd/klm	Imax	3720cd	5	3.59	149

	Driver	Colour	3000K	4000K
	EL.	○	**1TD0001EL**	**1TD0002EL**
	EL.	●	**1TD0003EL**	**1TD0004EL**

Ø 70



LED / 31W / LENS / SP-FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			15°	
	Fixture Power	35W	1	0.35	11561
	Source Flux	3150lm	2	0.70	2890
	Fixture Flux	2975lm	3	1.05	1285
	Efficacy	85lm/W	4	1.39	723
TS1141	Imax=3670cd/klm	Imax	11561cd	5	1.74	462



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			36°	
	Fixture Power	35W	1	0.66	6942
	Source Flux	3150lm	2	1.31	1735
	Fixture Flux	2975lm	3	1.97	771
	Efficacy	85lm/W	4	2.63	434
TS1140	Imax=2204cd/klm	Imax	6942cd	5	3.28	278

	Driver	Colour	3000K	4000K
	EL.	○	**1TD0005EL**	**1TD0006EL**
	EL.	●	**1TD0007EL**	**1TD0008EL**

Capsule

Accessories

Optic

	Ø	Code
	60	**1TD0017**
	70	**1TD0018**

SP (24°) opening lens optic.

STORE

GENERAL INFO
Professional projector for LED sources.
Optical chamber adjustable 0° - 90° vertically and 355° horizontally.
Mechanical aiming lock in the horizontal plane and blocking equipped with a friction system in the vertical plane.
Store ø93mm
Store Mini ø75mm

LED
Chip on board
From 1786lm to 4385lm
3000K – 4000K
Ra84 - Ra97

PRODUCT EFFICACY
Up to 119lm/W

OPTICS
SP – FL – MWFL – WFL

POWER SUPPLY
Electronic – DALI

MATERIAL
Optical chamber and power box in painted die-cast aluminium. Front ring for accessories in painted aluminium.

ON DEMAND
Easy Custom Colour

110-277Vac power supply (Store)

A range of projectors designed to meet the particular requirements of the Retail market where excellent performance, minimal design and controlled light are required. Available in a projector and recessed versions, both in two different sizes.

The projector version comes in two different sizes: a large version with a separate driver box and a Mini version with a driver hidden in the track.

		STORE	STORE MINI
		Ø 93mm	Ø 75mm
LED	Flux (lm)	2257- 4385	1786 - 2532
	Power	19W - 33W	11W - 18W
OPTICS			
SP	Lenticular		•
	Reflector	•	
FL	Lenticular		•
	Reflector	•	
MWFL	Reflector	•	•
WFL	Reflector	•	•

Mc Laren Showroom
Milan, Italy

Projector



LED / 19W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		22W	1	0.24	23022
Source Flux		2935lm	2	0.48	5755
Fixture Flux		2494lm	3	0.72	2558
Efficacy		112lm/W	4	0.96	1439
TS947	Imax=7844cd/klm	Imax	23022cd	5	1.20	921

Driver	Colour	3000K	4000K
EL.	○	**1T5050EL**	**1T5052EL**
EL.	●	**1T5034EL**	**1T5036EL**
DALI	○	**1T5050DA**	**1T5052DA**
DALI	●	**1T5034DA**	**1T5036DA**

LED / 19W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		22W	1	0.24	17704
Source Flux		2257lm	2	0.48	4426
Fixture Flux		1918lm	3	0.72	1967
Efficacy		86lm/W	4	0.96	1106
TS947	Imax=7844cd/klm	Imax	17704cd	5	1.20	708

Driver	Colour	3000K	4000K
EL.	○	**1T5051EL**	**1T5053EL**
EL.	●	**1T5035EL**	**1T5037EL**
DALI	○	**1T5051DA**	**1T5053DA**
DALI	●	**1T5035DA**	**1T5037DA**

LED / 19W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			27°	
Fixture Power		22W	1	0.49	9061
Source Flux		2935lm	2	0.97	2265
Fixture Flux		2486lm	3	1.46	1007
Efficacy		112lm/W	4	1.95	566
TS948	Imax=3087cd/klm	Imax	9061cd	5	2.43	362

Driver	Colour	3000K	4000K
EL.	○	**1T5054EL**	**1T5056EL**
EL.	●	**1T5038EL**	**1T5040EL**
DALI	○	**1T5054DA**	**1T5056DA**
DALI	●	**1T5038DA**	**1T5040DA**

LED / 19W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			27°	
Fixture Power		22W	1	0.49	6968
Source Flux		2257lm	2	0.97	1742
Fixture Flux		1912lm	3	1.46	774
Efficacy		86lm/W	4	1.95	435
TS948	Imax=3087cd/klm	Imax	6968cd	5	2.43	279

Driver	Colour	3000K	4000K
EL.	○	**1T5055EL**	**1T5057EL**
EL.	●	**1T5039EL**	**1T5041EL**
DALI	○	**1T5055DA**	**1T5057DA**
DALI	●	**1T5039DA**	**1T5041DA**

LED / 19W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		22W	1	0.82	4770
Source Flux		2935lm	2	1.64	1193
Fixture Flux		2550lm	3	2.46	530
Efficacy		115lm/W	4	3.28	298
TS949	Imax=1655cd/klm	Imax	4856cd	5	4.10	191

Driver	Colour	3000K	4000K
EL.	○	**1T5058EL**	**1T5060EL**
EL.	●	**1T5042EL**	**1T5044EL**
DALI	○	**1T5058DA**	**1T5060DA**
DALI	●	**1T5042DA**	**1T5044DA**

STORE

LED / 19W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
Fixture Power		22W	1	0.82	3668
Source Flux		2257lm	2	1.64	917
Fixture Flux		1961lm	3	2.46	408
Efficacy		88lm/W	4	3.28	229
TS949	Imax=1655cd/klm	Imax	3734cd	5	4.10	147

Driver	Colour	3000K	4000K
EL.	○	**1T5059EL**	**1T5061EL**
EL.	●	**1T5043EL**	**1T5045EL**
DALI	○	**1T5059DA**	**1T5061DA**
DALI	●	**1T5043DA**	**1T5045DA**

LED / 19W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			59°	
Fixture Power		22W	1	1.13	3318
Source Flux		2935lm	2	2.26	830
Fixture Flux		2585lm	3	3.39	369
Efficacy		116lm/W	4	4.51	207
TS950	Imax=1141cd/klm	Imax	3350cd	5	5.64	133

Driver	Colour	3000K	4000K
EL.	○	**1T5062EL**	**1T5064EL**
EL.	●	**1T5046EL**	**1T5048EL**
DALI	○	**1T5062DA**	**1T5064DA**
DALI	●	**1T5046DA**	**1T5048DA**

LED / 19W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power		22W	1	1.13	2552
Source Flux		2257lm	2	2.26	638
Fixture Flux		1988lm	3	3.39	284
Efficacy		90lm/W	4	4.51	159
TS950	Imax=1141cd/klm	Imax	2576cd	5	5.64	102

Driver	Colour	3000K	4000K
EL.	○	**1T5063EL**	**1T5065EL**
EL.	●	**1T5047EL**	**1T5049EL**
DALI	○	**1T5063DA**	**1T5065DA**
DALI	●	**1T5047DA**	**1T5049DA**

LED / 33W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		36W	1	0.24	33552
Source Flux		4277lm	2	0.48	8388
Fixture Flux		3635lm	3	0.72	3728
Efficacy		102lm/W	4	0.96	2097
TS951	Imax=7845cd/klm	Imax	33552cd	5	1.20	1342

Driver	Colour	3000K	4000K
EL.	○	**1T5082EL**	**1T5084EL**
EL.	●	**1T5066EL**	**1T5068EL**
DALI	○	**1T5082DA**	**1T5084DA**
DALI	●	**1T5066DA**	**1T5068DA**

LED / 33W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		36W	1	0.24	25809
Source Flux		3290lm	2	0.48	6452
Fixture Flux		2796lm	3	0.72	2868
Efficacy		78lm/W	4	0.96	1613
TS951	Imax=7845cd/klm	Imax	25809cd	5	1.20	1032

Driver	Colour	3000K	4000K
EL.	○	**1T5083EL**	**1T5085EL**
EL.	●	**1T5067EL**	**1T5069EL**
DALI	○	**1T5083DA**	**1T5085DA**
DALI	●	**1T5067DA**	**1T5069DA**

LED / 33W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			27°	
Fixture Power		36W	1	0.49	13204
Source Flux		4277lm	2	0.97	3301
Fixture Flux		3622lm	3	1.46	1467
Efficacy		101lm/W	4	1.95	825
TS952	Imax=3087cd/klm	Imax	13204cd	5	2.43	528

Driver	Colour	3000K	4000K
EL.	○	**1T5086EL**	**1T5088EL**
EL.	●	**1T5070EL**	**1T5072EL**
DALI	○	**1T5086DA**	**1T5088DA**
DALI	●	**1T5070DA**	**1T5072DA**

STORE

LED / 33W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			27°	
Fixture Power		36W	1	0.49	10157
Source Flux		3290lm	2	0.97	2539
Fixture Flux		2786lm	3	1.46	1129
Efficacy		78lm/W	4	1.95	635
TS952	Imax=3087cd/klm	Imax	10157cd	5	2.43	406

Driver	Colour	3000K	4000K
EL.	○	**1T5087EL**	**1T5089EL**
EL.	●	**1T5071EL**	**1T5073EL**
DALI	○	**1T5087DA**	**1T5089DA**
DALI	●	**1T5071DA**	**1T5073DA**

LED / 33W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		36W	1	0.82	6951
Source Flux		4277lm	2	1.64	1738
Fixture Flux		3716lm	3	2.46	772
Efficacy		104lm/W	4	3.28	434
TS953	Imax=1655cd/klm	Imax	7076cd	5	4.10	278

Driver	Colour	3000K	4000K
EL.	○	**1T5090EL**	**1T5092EL**
EL.	●	**1T5074EL**	**1T5076EL**
DALI	○	**1T5090DA**	**1T5092DA**
DALI	●	**1T5074DA**	**1T5076DA**

LED / 33W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
Fixture Power		36W	1	0.82	5347
Source Flux		3290lm	2	1.64	1337
Fixture Flux		2859lm	3	2.46	594
Efficacy		80lm/W	4	3.28	334
TS953	Imax=1655cd/klm	Imax	5443cd	5	4.10	214

Driver	Colour	3000K	4000K
EL.	○	**1T5091EL**	**1T5093EL**
EL.	●	**1T5075EL**	**1T5077EL**
DALI	○	**1T5091DA**	**1T5093DA**
DALI	●	**1T5075DA**	**1T5077DA**

LED / 33W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			59°	
Fixture Power		36W	1	1.13	4836
Source Flux		4277lm	2	2.26	1209
Fixture Flux		3768lm	3	3.39	537
Efficacy		106lm/W	4	4.51	302
TS954	Imax=1142cd/klm	Imax	4882cd	5	5.64	193

Driver	Colour	3000K	4000K
EL.	○	**1T5094EL**	**1T5096EL**
EL.	●	**1T5078EL**	**1T5080EL**
DALI	○	**1T5094DA**	**1T5096DA**
DALI	●	**1T5078DA**	**1T5080DA**

LED / 33W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power		36W	1	1.13	3720
Source Flux		3290lm	2	2.26	930
Fixture Flux		2898lm	3	3.39	413
Efficacy		81lm/W	4	4.51	233
TS954	Imax=1142cd/klm	Imax	3756cd	5	5.64	149

Driver	Colour	3000K	4000K
EL.	○	**1T5095EL**	**1T5097EL**
EL.	●	**1T5079EL**	**1T5081EL**
DALI	○	**1T5095DA**	**1T5097DA**
DALI	●	**1T5079DA**	**1T5081DA**

STORE

Accessories

Filter

Filter	Ø	Code
Red	70	**1T1712**
Green	70	**1T1713**
Blue	70	**1T1714**
Yellow	70	**1T1715**
Magenta	70	**1T1716**

Flat glass interference chromatic filter.
To be completed with an additional holder ring for Cloud, Ray Mini, Store and Keplero Mini HE.

Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Ø	Code
70	**1T1709**

Flat glass wired refractive diffusive filter.
This softens the luminous effect.
To be completed with an additional holder ring for Cloud, Ray Mini, Sore, Label 9 and CCTEvo Extractable 162.

Filter	Ø	Code
Halogen +	70	**1T6506**
Vivid +	70	**1T6507**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.



Filter	Ø	Code
Meat	70	**1T6508**
Fish	70	**1T6509**
Bread	70	**1T6510**
Vegetables	70	**1T6511**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.
1T6508 - To be used only with 3000K and Ra84 fixtures.
1T6509 - To be used only with 4000K and Ra84 fixtures.
1T6510 - To be used only with 3000K and Ra84 fixtures.
1T6511 - To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Beauty	70	**1T6512**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.

STORE

Screen



Ø	Code
80	**1T6522**

Protective screen.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Zoom



Ø	Code
80	**1T3432**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It makes it possible to obtain a variable beam from 15° to 60°.
It can not be used with NSP and hybrid optics; no for DBS version.

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Screen



Ø	Code
80	**1T3143**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Holder Ring

Code
1T3727

Transparent polycarbonate accessory holder ring.

Adapter



Ø	H	Driver	Colour	Code
100	32	EL.	○	**1T2221**
100	32	EL.	●	**1T2220**
100	32	EL.	◍	**1T2219**

Base for ceiling installation of projectors with an adapter for electrified track.



Ø	H	Driver	Colour	Code
118	38	DALI	○	**9000/BPU-D-W**
118	38	DALI	◑	**9000/BPU-D-B**
118	38	DALI	◍	**9000/BPU-D-G**

Base for ceiling installation of projectors with an adapter for electrified track.

STORE



Cutout hole	Ø	H	Driver	Colour	Code
Ø105/125	130	60	EL.	○	**1T2223**
Ø105/125	130	60	EL.	●	**1T2222**
Ø105/125	130	60	EL.	◌	**1T2224**

Adapter for recessed installation of the base.
1T2222 - To be completed with 1T2220.
1T2223 - To be completed with 1T2221.
1T2224 - To be completed with 1T2219.



Cutout hole	Ø	H	Driver	Colour	Code
Ø125/130	144	67	DALI	○	**9000/BRU-W**
Ø125/130	144	67	DALI	◐	**9000/BRU-B**
Ø125/130	144	67	DALI	◌	**9000/BRU-G**

Adapter for recessed installation of the base.
9000/BRU-G - To be completed with 9000/BPU-D-G.
9000/BRU-W - To be completed with 9000/BPU-D-W.
9000/BRU-B - To be completed with 9000/BPU-D-B.

Mini Projector



LED / 11W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			15°	
Fixture Power		15W	1	0.27	16914
Source Flux		1786lm	2	0.53	4229
Fixture Flux		1336lm	3	0.80	1879
Efficacy		90lm/W	4	1.07	1057
TS966	Imax=9470cd/klm	Imax	16914cd	5	1.33	677

Driver	Colour	3000K	4000K
EL.	○	**1T5016EL**	**1T5017EL**
EL.	●	**1T5010EL**	**1T5011EL**

LED / 12W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			30°	
Fixture Power		14W	1	0.54	4825
Source Flux		1837lm	2	1.09	1206
Fixture Flux		1315lm	3	1.63	536
Efficacy		97lm/W	4	2.17	302
TS967	Imax=2627cd/klm	Imax	4825cd	5	2.72	193

Driver	Colour	3000K	4000K
EL.	○	**1T5018EL**	**1T5019EL**
EL.	●	**1T5012EL**	**1T5013EL**

LED / 12W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		14W	1	0.90	2476
Source Flux		1837lm	2	1.80	619
Fixture Flux		1520lm	3	2.69	275
Efficacy		113lm/W	4	3.59	155
TS968	Imax=1372cd/klm	Imax	2520cd	5	4.49	99

Driver	Colour	3000K	4000K
EL.	○	**1T5020EL**	**1T5021EL**
EL.	●	**1T5014EL**	**1T5015EL**

LED / 18W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			24°	
Fixture Power		20W	1	0.43	8803
Source Flux		2466lm	2	0.87	2201
Fixture Flux		1800lm	3	1.30	978
Efficacy		89lm/W	4	1.73	550
TS969	Imax=3570cd/klm	Imax	8803cd	5	2.17	352

Driver	Colour	3000K	4000K
EL.	○	**1T5028EL**	**1T5029EL**
EL.	●	**1T5022EL**	**1T5023EL**

LED / 18W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		20W	1	0.90	3323
Source Flux		2466lm	2	1.80	831
Fixture Flux		2041lm	3	2.69	369
Efficacy		101lm/W	4	3.59	208
TS970	Imax=1372cd/klm	Imax	3383cd	5	4.49	133

Driver	Colour	3000K	4000K
EL.	○	**1T5030EL**	**1T5031EL**
EL.	●	**1T5024EL**	**1T5025EL**

STORE

LED / 18W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			60°	
Fixture Power	20W	1	1.16	2406
Source Flux	2466lm	2	2.32	601
Fixture Flux	1979lm	3	3.47	267
Efficacy	98lm/W	4	4.63	150
TS971 Imax=976cd/klm	Imax	2407cd	5	5.79	96

Driver	Colour	3000K	4000K
EL.	○	**1T5032EL**	**1T5033EL**
EL.	●	**1T5026EL**	**1T5027EL**

Mini Projector



LED / 11W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra84			15°	
Fixture Power	15W	1	0.27	16914
Source Flux	1786lm	2	0.53	4229
Fixture Flux	1336lm	3	0.80	1879
Efficacy	90lm/W	4	1.07	1057
TS966 Imax=9470cd/klm	Imax	16914cd	5	1.33	677

Driver	Colour	3000K	4000K
DALI	○	**1T5016DA**	**1T5017DA**
DALI	●	**1T5010DA**	**1T5011DA**

LED / 12W / LENS / FL



3000K		H(m)	D(m)	Emax(lx)
Ra84			30°	
Fixture Power	14W	1	0.54	4825
Source Flux	1837lm	2	1.09	1206
Fixture Flux	1315lm	3	1.63	536
Efficacy	97lm/W	4	2.17	302
TS967 Imax=2627cd/klm	Imax	4825cd	5	2.72	193

Driver	Colour	3000K	4000K
DALI	○	**1T5018DA**	**1T5019DA**
DALI	●	**1T5012DA**	**1T5013DA**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			48°	
Fixture Power	14W	1	0.90	2476
Source Flux	1837lm	2	1.80	619
Fixture Flux	1520lm	3	2.69	275
Efficacy	113lm/W	4	3.59	155
TS968 Imax=1372cd/klm	Imax	2520cd	5	4.49	99

Driver	Colour	3000K	4000K
DALI	○	**1T5020DA**	**1T5021DA**
DALI	●	**1T5014DA**	**1T5015DA**

LED / 18W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra84			24°	
Fixture Power	20W	1	0.43	8803
Source Flux	2466lm	2	0.87	2201
Fixture Flux	1800lm	3	1.30	978
Efficacy	89lm/W	4	1.73	550
TS969 Imax=3570cd/klm	Imax	8803cd	5	2.17	352

Driver	Colour	3000K	4000K
DALI	○	**1T5028DA**	**1T5029DA**
DALI	●	**1T5022DA**	**1T5023DA**

STORE

LED / 18W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			48°	
Fixture Power	20W	1	0.90	3323
Source Flux	2466lm	2	1.80	831
Fixture Flux	2041lm	3	2.69	369
Efficacy	101lm/W	4	3.59	208
TS970 Imax=1372cd/klm	Imax 3383cd	5	4.49	133

Driver	Colour	3000K	4000K
DALI	○	**1T5030DA**	**1T5031DA**
DALI	◐	**1T5024DA**	**1T5025DA**

LED / 18W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			60°	
Fixture Power	20W	1	1.16	2406
Source Flux	2466lm	2	2.32	601
Fixture Flux	1979lm	3	3.47	267
Efficacy	98lm/W	4	4.63	150
TS971 Imax=976cd/klm	Imax 2407cd	5	5.79	96

Driver	Colour	3000K	4000K
DALI	○	**1T5032DA**	**1T5033DA**
DALI	◐	**1T5026DA**	**1T5027DA**

Accessories

Filter



Filter	Ø	Code
Red	50	**49881**
Green	50	**49882**
Blue	50	**49886**
Yellow	50	**49887**
Magenta	50	**49959**

Flat glass interference chromatic filter.



Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.



Filter	Ø	Code
Halogen +	50	**1T6381**
Vivid +	50	**1T6383**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Meat	50	**1T6385**
Fish	50	**1T6387**
Bread	50	**1T6389**
Vegetables	50	**1T6391**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
1T6385 - To be used only with 3000K and Ra84 fixtures.
1T6387 - To be used only with 4000K and Ra84 fixtures.
1T6389 - To be used only with 3000K and Ra84 fixtures.
1T6391 - To be used only with 3000K and Ra84 fixtures.

STORE



Filter	Ø	Code
Beauty	50	**1T6393**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.

Screen



Ø	Code
50	**1T4325**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.



Ø	Code
50	**1T6521**

Protective screen.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Zoom



Ø	Code
50	**1T4324**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It can not be used with a narrow spot optic.
It makes it possible to obtain a variable beam from 15° to 60°.

LEDÒ

GENERAL INFO
Professional adjustable LED projector.
The body can be adjusted from 0° to 90° on a vertical plane and by 355° on a horizontal plane with double blocking equipped with a friction system.
Ledò L. 178mm
Ledò Tunable
and DBS L. 213mm

LED
Standard e DBS
Chip on board
From 2524lm to 3155lm
3000K – 4000K
Ra97
Tunable
Chip on board
From 1960lm to 2290lm
From 2700K to 5700K
Ra90

PRODUCT EFFICACY
Up to 92lm/W

OPTICS
SP – FL – MWFL – WFL
DBS - Digital beam opening control

POWER SUPPLY
Electronic – DALI
Control: Dimmer on board – Casambi on board

MATERIAL
Painted die-cast aluminium body (L=178 mm) or extruded painted aluminium body (L=213 mm).
Front interchangeable optic camera in black polycarbonate for the standard version and in the same colour of the body for the LOF version, back ring with radial grid for heat dissipation.

ON DEMAND
Easy Custom Colour

110-277Vac power supply

Track projectors designed for museum lighting given the precise beam modelling, the high colour quality of the light and excellent colour rendering. Available with a fixed optic with a DBS system to modulate the beam on the object to be lit up to 50°.

The Tunable version on the other hand allows to vary the colour temperature from 2700K to 5700K.

The different versions are available with an electronic driver, a dimmable on board driver or can be controlled with a smartphone using the Casambi app to manage the luminous intensity of every single fixture.
The electronic, DALI and DBS versions have an integrated driver. The Tunable version has a separate driver.

		178mm	213mm Tunable	213mm DBS
LED	Flux (lm)	2524 - 2805	1960 - 2290	2524
	Power	25W	25W	25W
OPTICS				
SP	Hybrid	•		
	Reflector		•	
FL	Hybrid	•		
	Reflector		•	
MWFL	Reflector	•	•	
WFL	Reflector	•	•	
DBS	Variable			•

Saint Germain des Prés
Paris, France

Lighting Design Armand Zadkian

Photographer Hugo Hebrard

LEDÒ

L. 178mm



LED / 25W / HYBRID / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			13°	
	Fixture Power	27W	1	0.23	23221
	Source Flux	2524lm	2	0.46	5805
	Fixture Flux	1637lm	3	0.69	2580
	Efficacy	61lm/W	4	0.92	1451
	Imax	23221cd	5	1.14	929

Certificate	Driver	Colour	3000K	4000K
	EL.	○	**1T4882**	**1T4883**
	EL.	◐	**1T4886**	**1T4887**
	EL.	◐	**1T4878**	**1T4879**
	DIMM ON BOARD	○	**1T4890**	
	DIMM ON BOARD	○	**1T4892**	
	DIMM ON BOARD	◐	**1T4894**	
	DALI	○	**1T4896**	
	DALI	○	**1T4898**	
	DALI	◐	**1T4900**	

LED / 25W / HYBRID / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			33°	
	Fixture Power	27W	1	0.58	5627
	Source Flux	2524lm	2	1.17	1407
	Fixture Flux	1541lm	3	1.75	625
	Efficacy	57lm/W	4	2.33	352
	Imax	5627cd	5	2.92	225

Certificate	Driver	Colour	3000K	4000K
	EL.	○	**1T4884**	**1T4885**
	EL.	◐	**1T4888**	**1T4889**
	EL.	◐	**1T4880**	**1T4881**
	DIMM ON BOARD	○	**1T4891**	
	DIMM ON BOARD	○	**1T4893**	
	DIMM ON BOARD	◐	**1T4895**	
	DALI	○	**1T4897**	
	DALI	○	**1T4899**	
	DALI	◐	**1T4901**	

LED / 25W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
	Fixture Power	27W	1	0.82	4412
	Source Flux	2714lm	2	1.64	1103
	Fixture Flux	2358lm	3	2.46	490
	Efficacy	87lm/W	4	3.28	276
	Imax	4491cd	5	4.10	176

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T3491**	**1T3492**
ENEC	EL.	◐	**1T3499**	**1T3500**
ENEC	EL.	◐	**1T3483**	**1T3484**
	DIMM ON BOARD	○	**1T4369**	
	DIMM ON BOARD	○	**1T4373**	
	DIMM ON BOARD	◐	**1T4377**	
	DALI	○	**1T4381**	
	DALI	○	**1T4385**	
	DALI	◐	**1T4389**	

LED / 25W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
	Fixture Power	27W	1	1.13	3071
	Source Flux	2714lm	2	2.26	768
	Fixture Flux	2392lm	3	3.39	341
	Efficacy	89lm/W	4	4.51	192
	Imax	3100cd	5	5.64	123

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T3493**	**1T3494**
ENEC	EL.	◐	**1T3501**	**1T3502**
ENEC	EL.	◐	**1T3485**	**1T3486**
	DIMM ON BOARD	○	**1T4370**	
	DIMM ON BOARD	○	**1T4374**	
	DIMM ON BOARD	◐	**1T4378**	
	DALI	○	**1T4382**	
	DALI	○	**1T4386**	
	DALI	◐	**1T4390**	

LEDÒ

L. 178mm CASAMBI



LED / 25W / HYBRID / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			13°	
Fixture Power		27W	1	0.23	23221
Source Flux		2524lm	2	0.46	5805
Fixture Flux		1637lm	3	0.69	2580
Efficacy		61lm/W	4	0.92	1451
TS928	Imax=9200cd/klm	Imax	5	1.14	929

Certificate	Driver	Colour	3000K	4000K
	CASAMBI		**1T4896CA**	
	CASAMBI		**1T4898CA**	
	CASAMBI		**1T4900CA**	

LED / 25W / HYBRID / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			33°	
Fixture Power		27W	1	0.58	5627
Source Flux		2524lm	2	1.17	1407
Fixture Flux		1541lm	3	1.75	625
Efficacy		57lm/W	4	2.33	352
TS929	Imax=2230cd/klm	Imax	5	2.92	225

Certificate	Driver	Colour	3000K	4000K
	CASAMBI		**1T4897CA**	
	CASAMBI		**1T4899CA**	
	CASAMBI		**1T4901CA**	

LED / 25W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			45°	
Fixture Power		27W	1	0.82	4412
Source Flux		2714lm	2	1.64	1103
Fixture Flux		2358lm	3	2.46	490
Efficacy		87lm/W	4	3.28	276
TS930	Imax=1655cd/klm	Imax	5	4.10	176

Certificate	Driver	Colour	3000K	4000K
	CASAMBI		**1T4381CA**	
	CASAMBI		**1T4385CA**	
	CASAMBI		**1T4389CA**	

LED / 25W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			59°	
Fixture Power		27W	1	1.13	3071
Source Flux		2714lm	2	2.26	768
Fixture Flux		2392lm	3	3.39	341
Efficacy		89lm/W	4	4.51	192
TS931	Imax=1142cd/klm	Imax	5	5.64	123

Certificate	Driver	Colour	3000K	4000K
	CASAMBI		**1T4382CA**	
	CASAMBI		**1T4386CA**	
	CASAMBI		**1T4390CA**	

LEDÒ

L. 213mm DBS



LED / 25W / DBS



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			16°	
Fixture Power	27W	1	0.28	11780	
Source Flux	2524lm	2	0.56	2945	
Fixture Flux	1206lm	3	0.84	1309	
Efficacy	45lm/W	4	1.12	736	
Imax	11780cd	5	1.40	471	

TS1114 Imax=4667cd/klm



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			25°	
Fixture Power	27W	1	0.45	4530	
Source Flux	2524lm	2	0.89	1132	
Fixture Flux	1166lm	3	1.34	503	
Efficacy	43lm/W	4	1.79	283	
Imax	4530cd	5	2.24	181	

TS1115 Imax=1795cd/klm



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			34°	
Fixture Power	27W	1	0.61	2485	
Source Flux	2524lm	2	1.23	621	
Fixture Flux	1133lm	3	1.84	276	
Efficacy	42lm/W	4	2.45	155	
Imax	2485cd	5	3.07	99	

TS1116 Imax=984cd/klm



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			42°	
Fixture Power	27W	1	0.78	1566	
Source Flux	2524lm	2	1.55	392	
Fixture Flux	1075lm	3	2.33	174	
Efficacy	40lm/W	4	3.11	98	
Imax	1566cd	5	3.88	63	

TS1117 Imax=620cd/klm

	Certificate	Driver	Colour	3000K	4000K
		CASAMBI		**1T6958CA**	**1T6962CA**
		CASAMBI		**1T6955CA**	**1T6959CA**
		CASAMBI		**1T6956CA**	**1T6960CA**
		CASAMBI		**1T6957CA**	**1T6961CA**

Accessories

Filter



	Filter	Ø	Code
	Red	80	**1T3424**
	Green	80	**1T3425**
	Blue	80	**1T3426**
	Yellow	80	**1T3427**
	Magenta	80	**1T3428**

Flat glass interference chromatic filter.



	Ø	Code
	80	**1T3141**

Flat glass, grooved refractive blade light filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.



	Ø	Code
	80	**1T3140**

Flat glass micro prismatic refractive diffusive filter.
This softens the luminous effect.

LEDÒ

Screen



Ø	Code
80	**1T6522**

Protective screen.

Grid



Ø	Code
80	**1T3423**

Anti-glare louver.
Black painted metal honeycomb structure.

Zoom



Ø	Code
80	**1T3432**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It makes it possible to obtain a variable beam from 15° to 60°.
It can not be used with NSP and hybrid optics; no for DBS version.

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Screen



Ø	Code
80	**1T3143**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Adapter



Ø	H	Driver	Colour	Code
100	32	EL.	○	**1T2221**
100	32	EL.	●	**1T2220**
100	32	EL.	◍	**1T2219**

Base for ceiling installation of projectors with an adapter for electrified track.



Ø	H	Driver	Colour	Code
118	38	DALI	○	**9000/BPU-D-W**
118	38	DALI	◑	**9000/BPU-D-B**
118	38	DALI	◍	**9000/BPU-D-G**

Base for ceiling installation of projectors with an adapter for electrified track.

LEDÒ



Cutout hole	Ø	H	Driver	Colour	Code
Ø105/125	130	60	EL.	○	**1T2223**
Ø105/125	130	60	EL.	●	**1T2222**
Ø105/125	130	60	EL.	◌	**1T2224**

Adapter for recessed installation of the base.
1T2222 - To be completed with 1T2220.
1T2223 - To be completed with 1T2221.
1T2224 - To be completed with 1T2219.

Cutout hole	Ø	H	Driver	Colour	Code
Ø125/130	144	67	DALI	○	**9000/BRU-W**
Ø125/130	144	67	DALI	◐	**9000/BRU-B**
Ø125/130	144	67	DALI	◌	**9000/BRU-G**

Adapter for recessed installation of the base.
9000/BRU-G - To be completed with 9000/BPU-D-G.
9000/BRU-W - To be completed with 9000/BPU-D-W.
9000/BRU-B - To be completed with 9000/BPU-D-B.

LEDÒ

Tunable 2700-5700K



LED / 25W / SP



	5000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
	Fixture Power	29W	1	0.24	17965
	Source Flux	2290lm	2	0.48	4491
	Fixture Flux	1947lm	3	0.72	1996
	Efficacy	67lm/W	4	0.96	1123
TS1022	Imax=7845cd/klm	Imax	5	1.20	719

Driver	Colour	CTC
CASAMBI		**1T4439CA**
CASAMBI		**1T4443CA**
CASAMBI		**1T4447CA**

LED / 25W / FL



	5000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
	Fixture Power	29W	1	0.49	7070
	Source Flux	2290lm	2	0.97	1768
	Fixture Flux	1940lm	3	1.46	786
	Efficacy	67lm/W	4	1.95	442
TS1023	Imax=3087cd/klm	Imax	5	2.43	283

Driver	Colour	CTC
CASAMBI		**1T4440CA**
CASAMBI		**1T4444CA**
CASAMBI		**1T4448CA**

LED / 25W / MWFL



	5000K		H(m)	D(m)	Emax(lx)
	Ra90			45°	
	Fixture Power	29W	1	0.82	3722
	Source Flux	2290lm	2	1.64	931
	Fixture Flux	1990lm	3	2.46	414
	Efficacy	69lm/W	4	3.28	233
TS1024	Imax=1655cd/klm	Imax	5	4.10	149

Driver	Colour	CTC
CASAMBI		**1T4441CA**
CASAMBI		**1T4445CA**
CASAMBI		**1T4449CA**

LED / 25W / WFL



	5000K		H(m)	D(m)	Emax(lx)
	Ra90			59°	
	Fixture Power	29W	1	1.13	2590
	Source Flux	2290lm	2	2.26	647
	Fixture Flux	2018lm	3	3.39	288
	Efficacy	70lm/W	4	4.51	162
TS1025	Imax=1142cd/klm	Imax	5	5.64	104

Driver	Colour	CTC
CASAMBI		**1T4442CA**
CASAMBI		**1T4446CA**
CASAMBI		**1T4450CA**

Accessories

Filter



Ø	Code
80	**1T3141**

Flat glass, grooved refractive blade light filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.



Ø	Code
80	**1T3140**

Flat glass micro prismatic refractive diffusive filter.
This softens the luminous effect.

LEDÒ

Screen



Ø	Code
80	**1T6522**

Protective screen.

Grid



Ø	Code
80	**1T3423**

Anti-glare louver.
Black painted metal honeycomb structure.

Zoom



Ø	Code
80	**1T3432**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It makes it possible to obtain a variable beam from 15° to 60°.
It can not be used with NSP and hybrid optics; no for DBS version.

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Screen



Ø	Code
80	**1T3143**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Adapter



Ø	H	Driver	Colour	Code
100	32	EL.	○	**1T2221**
100	32	EL.	●	**1T2220**
100	32	EL.	◍	**1T2219**

Base for ceiling installation of projectors with an adapter for electrified track.



Cutout hole	Ø	H	Driver	Colour	Code
Ø105/125	130	60	EL.	○	**1T2223**
Ø105/125	130	60	EL.	◑	**1T2222**
Ø105/125	130	60	EL.	◍	**1T2224**

Adapter for recessed installation of the base.
1T2222 - To be completed with 1T2220.
1T2223 - To be completed with 1T2221.
1T2224 - To be completed with 1T2219.

Saint Germain des Prés
Paris, France

Lighting Design Armand Zadkian

Photographer Hugo Hebrard



RAY

GENERAL INFO
Professional adjustable LED projector.
Adjustable from 0° to -90° in the vertical plane and 359° in the horizontal plane. Mechanical beam locking system on the vertical plane and graduated ring nut for beam locking on the horizontal plane (only for Ray Ø163mm).
Ray Ø163mm
Ray Mini Ø115mm
Ray Micro Ø89mm

LED
Chip on board
From 1949lm to 7232lm
3000K – 4000K
Ra84-Ra97

PRODUCT EFFICACY
Up to 125lm/W

OPTICS
SP – FL – MWFL - WFL

POWER SUPPLY
Electronic – DALI
DALI on request - Ray Micro

MATERIAL
Die-cast aluminium body painted. Front ring made of black ryton.

ON DEMAND

Easy Custom Colour

Ra97 (Ray Micro)

110-277Vac power supply (Ray Mini)

A range of projectors characterised by an essential design and high performance. Clearly intended for the Retail environment there are three different sizes and with four different power supplies to satisfy size and performance requirements within the same project.

All versions have optics with reflectors to obtain soft, delicate tones on all beam openings.

Almacruz Hotel
Santiago, Cile

Ligting Design Katerina Jofre
Photographer Nicolás Saieh

Project Mas Fernades arquitectos asociados

RAY



LED / 32W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			12°	
Fixture Power	35W		1	0.21	59854
Source Flux	4522lm		2	0.41	14963
Fixture Flux	3861lm		3	0.62	6650
Efficacy	111lm/W		4	0.82	3741
TS742	Imax=13236cd/klm	Imax	59854cd	5	1.03	2394

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T3684**	
ENEC	EL.	●	**1T3685**	
	DALI	○	**1T3684DA**	**1T5321DA**
	DALI	●	**1T3685DA**	**1T5322DA**
	EL.	○		**1T5321**
	EL.	●		**1T5322**

LED / 32W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			12°	
Fixture Power	35W		1	0.21	45757
Source Flux	3457lm		2	0.41	11439
Fixture Flux	2952lm		3	0.62	5084
Efficacy	85lm/W		4	0.82	2860
TS742	Imax=13236cd/klm	Imax	45757cd	5	1.03	1830

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4249**	
ENEC	EL.	●	**1T4250**	
	DALI	○	**1T4249DA**	**1T5329DA**
	DALI	●	**1T4250DA**	**1T5330DA**
	EL.	○		**1T5329**
	EL.	●		**1T5330**

LED / 32W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			25°	
Fixture Power	35W		1	0.45	15416
Source Flux	4522lm		2	0.90	3854
Fixture Flux	3776lm		3	1.35	1713
Efficacy	109lm/W		4	1.80	964
TS740	Imax=3409cd/klm	Imax	15416cd	5	2.25	617

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T3686**	
ENEC	EL.	●	**1T3687**	
	DALI	○	**1T3686DA**	**1T5323DA**
	DALI	●	**1T3687DA**	**1T5324DA**
	EL.	○		**1T5323**
	EL.	●		**1T5324**

LED / 32W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			25°	
Fixture Power	35W		1	0.45	11785
Source Flux	3457lm		2	0.90	2946
Fixture Flux	2887lm		3	1.35	1309
Efficacy	83lm/W		4	1.80	737
TS740	Imax=3409cd/klm	Imax	11785cd	5	2.25	471

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4251**	
ENEC	EL.	●	**1T4252**	
	DALI	○	**1T4251DA**	**1T5331DA**
	DALI	●	**1T4252DA**	**1T5332DA**
	EL.	○		**1T5331**
	EL.	●		**1T5332**

LED / 50W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			24°	
Fixture Power	54W		1	0.43	24335
Source Flux	7050lm		2	0.85	6084
Fixture Flux	5851lm		3	1.28	2704
Efficacy	109lm/W		4	1.70	1521
TS741	Imax=3452cd/klm	Imax	24335cd	5	2.13	973

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T3692**	
ENEC	EL.	●	**1T3693**	
	DALI	○	**1T3692DA**	**1T5325DA**
	DALI	●	**1T3693DA**	**1T5326DA**
	EL.	○		**1T5325**
	EL.	●		**1T5326**

RAY

LED / 50W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			24°	
Fixture Power		54W	1	0.43	18729
Source Flux		5426lm	2	0.85	4682
Fixture Flux		4503lm	3	1.28	2081
Efficacy		84lm/W	4	1.70	1171
TS741	Imax=3452cd/klm	Imax	5	2.13	749

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4253**	
ENEC	EL.	●	**1T4254**	
	DALI	○	**1T4253DA**	**1T5333DA**
	DALI	●	**1T4254DA**	**1T5334DA**
	EL.	○		**1T5333**
	EL.	●		**1T5334**

LED / 50W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			53°	
Fixture Power		54W	1	0.99	9030
Source Flux		7050lm	2	1.97	2257
Fixture Flux		5781lm	3	2.96	1003
Efficacy		108lm/W	4	3.95	564
TS743	Imax=1284cd/klm	Imax	5	4.93	361

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T3694**	
ENEC	EL.	●	**1T3695**	
	DALI	○	**1T3694DA**	**1T5327DA**
	DALI	●	**1T3695DA**	**1T5328DA**
	EL.	○		**1T5327**
	EL.	●		**1T5328**

LED / 50W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			53°	
Fixture Power		54W	1	0.99	6950
Source Flux		5426lm	2	1.97	1737
Fixture Flux		4449lm	3	2.96	772
Efficacy		83lm/W	4	3.95	434
TS743	Imax=1284cd/klm	Imax	5	4.93	278

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4255**	
ENEC	EL.	●	**1T4256**	
	DALI	○	**1T4255DA**	**1T5335DA**
	DALI	●	**1T4256DA**	**1T5336DA**
	EL.	○		**1T5335**
	EL.	●		**1T5336**

Accessories

Screen

Code
1T6523

Protective screen.

Grid

Code
1T6918

Anti-glare louver.
Black painted metal honeycomb structure.

Ray Shade

Code
1T3696

Adjustable barn doors flaps.

RAY

Mini



LED / 30W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		32W	1	0.24	33623
Source Flux		4141lm	2	0.48	8406
Fixture Flux		3520lm	3	0.72	3736
Efficacy		111lm/W	4	0.96	2101
TS832	Imax=8119cd/klm	Imax	33623cd	5	1.20	1345

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4201**	
ENEC	EL.	●	**1T4197**	
	DALI	○	**1T4201DA**	**1T5340DA**
	DALI	●	**1T4197DA**	**1T5337DA**
	EL.	○		**1T5340**
	EL.	●		**1T5337**

LED / 30W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			14°	
Fixture Power		32W	1	0.24	25276
Source Flux		3113lm	2	0.48	6319
Fixture Flux		2646lm	3	0.72	2808
Efficacy		83lm/W	4	0.96	1580
TS832	Imax=8119cd/klm	Imax	25276cd	5	1.20	1011

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4260**	
ENEC	EL.	●	**1T4257**	
	DALI	○	**1T4260DA**	**1T5346DA**
	DALI	●	**1T4257DA**	**1T5343DA**
	EL.	○		**1T5346**
	EL.	●		**1T5343**

LED / 30W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			25°	
Fixture Power		32W	1	0.44	14085
Source Flux		4141lm	2	0.88	3521
Fixture Flux		3505lm	3	1.32	1565
Efficacy		110lm/W	4	1.76	880
TS833	Imax=3401cd/klm	Imax	14085cd	5	2.20	563

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4202**	
ENEC	EL.	●	**1T4198**	
	DALI	○	**1T4202DA**	**1T5341DA**
	DALI	●	**1T4198DA**	**1T5338DA**
	EL.	○		**1T5341**
	EL.	●		**1T5338**

LED / 30W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			25°	
Fixture Power		32W	1	0.44	10588
Source Flux		3113lm	2	0.88	2647
Fixture Flux		2635lm	3	1.32	1176
Efficacy		83lm/W	4	1.76	662
TS833	Imax=3401cd/klm	Imax	10588cd	5	2.20	424

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4261**	
ENEC	EL.	●	**1T4258**	
	DALI	○	**1T4261DA**	**1T5347DA**
	DALI	●	**1T4258DA**	**1T5344DA**
	EL.	○		**1T5347**
	EL.	●		**1T5344**

LED / 30W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		32W	1	0.84	6295
Source Flux		4141lm	2	1.67	1574
Fixture Flux		3599lm	3	2.51	699
Efficacy		113lm/W	4	3.35	393
TS834	Imax=1528cd/klm	Imax	6327cd	5	4.18	252

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4203**	
ENEC	EL.	●	**1T4199**	
	DALI	○	**1T4203DA**	**1T5342DA**
	DALI	●	**1T4199DA**	**1T5339DA**
	EL.	○		**1T5342**
	EL.	●		**1T5339**

RAY

LED / 30W / REFLECTOR / MWFL / CRI97



3000K		H(m)	D(m)	Emax(lx)
Ra97			45°	
Fixture Power	32W	1	0.84	4733
Source Flux	3113lm	2	1.67	1183
Fixture Flux	2705lm	3	2.51	526
Efficacy	85lm/W	4	3.35	296
Imax	4757cd	5	4.18	189

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.	○	**1T4262**	
ENEC	EL.	●	**1T4259**	
	DALI	○	**1T4262DA**	**1T5348DA**
	DALI	●	**1T4259DA**	**1T5345DA**
	EL.	○		**1T5348**
	EL.	●		**1T5345**

Accessories

Filter



Filter	Ø	Code
Red	70	**1T1712**
Green	70	**1T1713**
Blue	70	**1T1714**
Yellow	70	**1T1715**
Magenta	70	**1T1716**

Flat glass interference chromatic filter.
To be completed with an additional holder ring for Cloud, Ray Mini, Store and Keplero Mini HE.



Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.



Ø	Code
70	**1T1709**

Flat glass wired refractive diffusive filter.
This softens the luminous effect.
To be completed with an additional holder ring for Cloud, Ray Mini, Sore, Label 9 and CCTEvo Extractable 162.



Filter	Ø	Code
Halogen +	70	**1T6506**
Vivid +	70	**1T6507**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.



Filter	Ø	Code
Meat	70	**1T6508**
Fish	70	**1T6509**
Bread	70	**1T6510**
Vegetables	70	**1T6511**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.
1T6508 - To be used only with 3000K and Ra84 fixtures.
1T6509 - To be used only with 4000K and Ra84 fixtures.
1T6510 - To be used only with 3000K and Ra84 fixtures.
1T6511 - To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Beauty	70	**1T6512**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9.

RAY

Screen



Ø	Code
80	**1T6522**

Protective screen.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Zoom



Ø	Code
80	**1T3432**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It makes it possible to obtain a variable beam from 15° to 60°.
It can not be used with NSP and hybrid optics; no for DBS version.

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Screen



Ø	Code
80	**1T3143**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Holder Ring

Code
1T3727

Transparent polycarbonate accessory holder ring.

RAY

Micro



LED / 12W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			17°	
	Fixture Power	13W	1	0.30	9777
	Source Flux	1949lm	2	0.59	2444
	Fixture Flux	1501lm	3	0.89	1086
	Efficacy	113lm/W	4	1.19	611
TS989	Imax=5017cd/klm	Imax	9777cd	5	1.48	391

	Driver	Colour	3000K	4000K
	EL.	○	**1T6317**	**1T6319**
	EL.	◐	**1T6318**	**1T6320**

LED / 12W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
	Fixture Power	13W	1	0.90	2626
	Source Flux	1949lm	2	1.80	657
	Fixture Flux	1613lm	3	2.69	292
	Efficacy	121lm/W	4	3.59	164
TS990	Imax=1372cd/klm	Imax	2673cd	5	4.49	105

	Driver	Colour	3000K	4000K
	EL.	○	**1T6321**	**1T6323**
	EL.	◐	**1T6322**	**1T6324**

Note

DALI on request.

Accessories

Filter



	Filter	Ø	Code
	Red	50	**49881**
	Green	50	**49882**
	Blue	50	**49886**
	Yellow	50	**49887**
	Magenta	50	**49959**

Flat glass interference chromatic filter.



	Ø	Code
	50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

RAY



Filter	Ø	Code
Halogen +	50	**1T6381**
Vivid +	50	**1T6383**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Beauty	50	**1T6393**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Meat	50	**1T6385**
Fish	50	**1T6387**
Bread	50	**1T6389**
Vegetables	50	**1T6391**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
1T6385 - To be used only with 3000K and Ra84 fixtures.
1T6387 - To be used only with 4000K and Ra84 fixtures.
1T6389 - To be used only with 3000K and Ra84 fixtures.
1T6391 - To be used only with 3000K and Ra84 fixtures.

Screen



Ø	Code
50	**1T6521**

Protective screen.



Ø	Code
50	**1T4325**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Zoom



Ø	Code
50	**1T4324**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It can not be used with a narrow spot optic.
It makes it possible to obtain a variable beam from 15° to 60°.

RAY

Adapter



Ø	H	Driver	Colour	Code
100	32	EL.	○	**1T2221**
100	32	EL.	●	**1T2220**
100	32	EL.	◍	**1T2219**

Base for ceiling installation of projectors with an adapter for electrified track.



Ø	H	Driver	Colour	Code
118	38	DALI	○	**9000/BPU-D-W**
118	38	DALI	◍	**9000/BPU-D-B**
118	38	DALI	◍	**9000/BPU-D-G**

Base for ceiling installation of projectors with an adapter for electrified track.



Cutout hole	Ø	H	Driver	Colour	Code
Ø125/130	144	67	DALI	○	**9000/BRU-W**
Ø125/130	144	67	DALI	●	**9000/BRU-B**
Ø125/130	144	67	DALI	◍	**9000/BRU-G**

Adapter for recessed installation of the base.
9000/BRU-G - To be completed with 9000/BPU-D-G.
9000/BRU-W - To be completed with 9000/BPU-D-W.
9000/BRU-B - To be completed with 9000/BPU-D-B.



Cutout hole	Ø	H	Driver	Colour	Code
Ø105/125	130	60	EL.	○	**1T2223**
Ø105/125	130	60	EL.	◍	**1T2222**
Ø105/125	130	60	EL.	◍	**1T2224**

Adapter for recessed installation of the base.
1T2222 - To be completed with 1T2220.
1T2223 - To be completed with 1T2221.
1T2224 - To be completed with 1T2219.

EUROSTANDARD

Plus

GENERAL INFO
Eurostandard Plus 230V track.
L. 1000mm – 2000mm – 3000mm

POWER SUPPLY
Electronic – DALI
Frequency: 50Hz

MATERIAL
A 3 phase mixed system with two additional conductors intended to manage a general data signal (for example DALI, DMX).
Electrified track in three lengths in extruded anodized aluminum or in extruded painted aluminium. Conductors in copper insulated in PVC.

The Eurostandard Plus is a universal 230V track that is compatible with all projectors in the Targetti collection and with all projectors that conform with European standards.

A standard double and recessed version in three different lengths. It has a double fixing systems for ceiling and suspension installations with joints of various sizes and configurations to obtain infinite compositions.



EUROSTANDARD PLUS



STANDARD

Kg	L	Colour	Code
1.1	1000	○	**9000-1/W-ST**
1.1	1000	●	**9000-1/B-ST**
1.1	1000	◍	**9000-1/G-ST**
2.1	2000	○	**9000-2/W-ST**
2.1	2000	●	**9000-2/B-ST**
2.1	2000	◍	**9000-2/G-ST**
3.1	3000	○	**9000-3/W-ST**
3.1	3000	●	**9000-3/B-ST**
3.1	3000	◍	**9000-3/G-ST**

RECESSED

Kg	L	Colour	Code
1.1	1000	○	**9000-1/W-R**
1.1	1000	●	**9000-1/B-R**
1.1	1000	◍	**9000-1/G-R**
2.2	2000	○	**9000-2/W-R**
2.2	2000	●	**9000-2/B-R**
2.2	2000	◍	**9000-2/G-R**
3.4	3000	○	**9000-3/W-R**
3.4	3000	●	**9000-3/B-R**
3.4	3000	◍	**9000-3/G-R**

Related codes

End Caps



Colour	Code
○	**9004/W**
●	**9004/B**
◍	**9004/G**

Dead end - Standard.



Colour	Code
○	**9004-R/W**
●	**9004-R/B**
◍	**9004-R/G**

Dead end - recessed.

EUROSTANDARD PLUS

Mounting System



Code
S-9000KIT

Suspension kit.
L=2000mm



Code
S-9000/111

Ceiling mounting bracket.
Galvanized steel.

Power Supply



Colour	Code
○	**9001/W**
●	**9001/B**
●	**9001/G**

Lateral power supply.
Polarity on the right.



Colour	Code
○	**9002/W**
◐	**9002/B**
●	**9002/G**

Lateral power supply.
Polarity on the left.

Colour	Code
○	**9010/W**
●	**9010/B**
●	**9010/G**

Central power supply.

Accessories

End Caps

Colour	Code
○	**S-9001/115-W**
●	**S-9001/115-B**

Seal for lateral power supply.
PVC.
For: 9001/...; 9002/...

EUROSTANDARD PLUS

Bracket

Colour	Code
○	**S-9000/123**

Rigid support bracket.

Driver	Colour	Code
EL.	○	**1T7007**
EL.	◐	**1T7005**
EL.	●	**1T7009**
DALI	○	**1T7006**
DALI	◐	**1T7004**
DALI	●	**1T7008**

Straight coupler for stability. For projectors with Eurostandard Plus joints.
For wall installation please refer to the assembly instructions.

Tool

Code
S-9000/T

Tool for shearing conductors, to be used if necessary to cut the track during installation.

Electrical Connector

Colour	Code
○	**9003/W**
●	**9003/B**
◐	**9003/G**

Linear joint.

Colour	Code
○	**9018/W**
●	**9018/B**
◐	**9018/G**

Flexible joint.

Colour	Code
○	**9011/W**
●	**9011/B**
◐	**9011/G**

L joint.
Internal polarity.

Colour	Code
○	**9012/W**
●	**9012/B**
◐	**9012/G**

L joint.
External polarity.

EUROSTANDARD PLUS

Colour	Code
○	**9013/W**
●	**9013/B**
◌	**9013/G**

T joint.
External polarity and on the left.

Colour	Code
○	**9014/W**
◑	**9014/B**
◌	**9014/G**

T joint.
External polarity and on the right.

Colour	Code
○	**9015/W**
●	**9015/B**
◌	**9015/G**

T joint.
Internal polarity and on the left.

Colour	Code
○	**9016/W**
◑	**9016/B**
◌	**9016/G**

T joint.
Internal polarity and on the right.

Colour	Code
○	**9017/W**
●	**9017/B**
◌	**9017/G**

X joint.

Mounting System



Colour	Code
○	**S-9000/M-W-KIT**
●	**S-9000/M-B-KIT**
◌	**S-9000/M-G-KIT**

Adapter for suspension installation.

Adapter

Colour	Code
○	**9009/W**
◑	**9009/B**
◌	**9009/G**

Adapter for power supply.
Allows for power supply from a Eurostandard Plus track.
EL/DALI.

EUROSTANDARD PLUS

Cover Panel

	Colour	Code
	○	**S-9001-R/6-W**
	●	**S-9001-R/6-B**
	◍	**S-9001-R/6-G**

False ceiling cover for lateral power supply.
Polycarbonate body.
For: 9001/...; 9002/...

	Colour	Code
	○	**S-9010-R/6-W**
	◑	**S-9010-R/6-B**
	◍	**S-9010-R/6-G**

False ceiling cover for central power supply.
Polycarbonate body.
For: 9010/...

	Colour	Code
	○	**S-9011-R/6-W**
	●	**S-9011-R/6-B**
	◍	**S-9011-R/6-G**

False ceiling cover for L connector.
Polycarbonate body.
For: 9011/...; 9012/...

	Colour	Code
	○	**S-9013-R/6-W**
	◑	**S-9013-R/6-B**
	◍	**S-9013-R/6-G**

False ceiling cover for T connector.
Polycarbonate body.
For: 9013/...; 9014/...; 9015/...; 9016/...



	Colour	Code
	○	**S-9017-R/6-W**
	●	**S-9017-R/6-B**
	◍	**S-9017-R/6-G**

False ceiling cover for X connector.
Polycarbonate body.
For: 9017.

	L	Colour	Code
	1000	○	**S-9000/GP-W**
	1000	◑	**S-9000/GP-B**
	1000	◍	**S-9000/GP-G**

Cover profile.
Can be cut to size.

EUROSTANDARD PLUS

Electrical scheme

During the wiring the electrical scheme of picture must be followed.



Load scheme



Installation

There is a polarity on the lighting track to guarantee the right connection of the multiple pieces of the track. Also end-feeds and connection joints have a polarity that must be taken into account in order to choose the right component. In the catalogue sketches of this articles, the position of the polarity is highlighted with a red line.



EUROSTANDARD PLUS

Lateral power supplies



9001/...



9002/...

Central power supplies

9010/...

“L” joint



9011/...



9012/...

“T” joint



9013/...



9014/...



9015/...



9016/...

“X” joint



9017/...

JEDI

Compact IP40

GENERAL INFO
Adjustable linear LEC projector.
41x37,5mm (exluded driver)
41x79mm (included driver)
Lengths 289mm – 570mm – 850mm – 1130mm

LED
Linear boards
From 1301lm to 6360lm
2700K – 3000K – 3500K – 4000K
Ra90

PRODUCT EFFICACY
Up to 100lm/W

OPTICS
SP, FL, Grazing,
Wall Washer

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Extruded anodised aluminium 15µ body.
1.8mm thick polycarbonate removable (to insert accessories) flat screen.
Removable driver box.
The body of the fixture is adjustable and can be installed away from the mounting surface using accessory brackets.

A compact, high performance linear LED fixture, suitable for installation in small grooves or on particularly thin frames. Depending on the optics chosen it is suitable for general lighting of walkways, vaulted ceilings or vertical surfaces. It is complete with a removable driver that can be positioned remotely if the installation space is small. The L. 300mm version is only available with a remote driver.

If equipped with special brackets the projector can be adjusted up to +/-145°.

Also available in an IP67 outdoor version.

Sala Zuccari, Palazzo Giustiniani
Rome, Italy

Plus



Grazing



Wall washer



Flood



Spot

Four different optical systems

The two different optical systems - hybrid and lenticular - make it possible to obtain four different lighting effects: grazing light thanks to the grazing optic, soft and uniform on high, wide surfaces with the wall washer optic and more concentrated effects with flood and spot optics. A special Louvre grill accessory makes it possible to equip the different versions of Jedi Compact IP40 with an anti-glare system with longitudinal blades to control lateral emission and reduce the risk of glare.

The Grazing optic versions

Is the most suitable solution for lighting vertical surfaces. Installed in continuous rows it makes it possible to obtain seamless uniform lighting.

Wide rotation

If equipped with special brackets the projector can be adjusted up to +/-145°.





JEDI COMPACT

IP40
Remote driver L. 289mm



LED / 12W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	14W	1	0.20	17993
Source Flux	1413lm	2	0.40	4498
Fixture Flux	1171lm	3	0.59	1999
Efficacy	84lm/W	4	0.79	1125
Imax	17993cd	5	0.99	720

TS1243 Imax=12734cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1T8920**	**1T8921**	**1T8922**	**1T8923**

LED / 12W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			85°	32°	
Fixture Power	14W	1	1.84	0.57	1049
Source Flux	1500lm	2	3.68	1.14	262
Fixture Flux	1121lm	3	5.52	1.70	117
Efficacy	80lm/W	4	7.36	2.27	66
Imax	1049cd	5	9.20	2.84	42

TS1078 Imax=700cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1T6747**	**1T6748**	**1T6749**	**1T6750**

LED / 12W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			76°	15°	
Fixture Power	14W	1	1.55	0.26	2403
Source Flux	1500lm	2	3.10	0.51	601
Fixture Flux	1247lm	3	4.65	0.77	267
Efficacy	89lm/W	4	6.21	1.02	150
Imax	2403cd	5	7.76	1.28	96

TS1080 Imax=1602cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1T6751**	**1T6752**	**1T6753**	**1T6754**

LED / 12W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			115°	59°	
Fixture Power	14W	1	3.12	1.34	1009
Source Flux	1500lm	2	6.23	2.67	252
Fixture Flux	1128lm	3	9.35	4.01	112
Efficacy	81lm/W	4	12.47	5.35	63
Imax	1161cd	5	15.59	6.69	40

TS1082 Imax=774cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1T6755**	**1T6756**	**1T6757**	**1T6758**

JEDI COMPACT

IP40
Integrated-removable driver
L. 570mm



LED / 23W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
	Fixture Power	26W	1	0.20	35986
	Source Flux	2826lm	2	0.40	8996
	Fixture Flux	2341lm	3	0.59	3998
	Efficacy	90lm/W	4	0.79	2249
TS1243	Imax	35986cd	5	0.99	1439

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T8924EL**	**1T8925EL**	**1T8926EL**	**1T8927EL**
DALI		**1T8924DA**	**1T8925DA**	**1T8926DA**	**1T8927DA**

LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			85°	32°	
	Fixture Power	28W	1	1.84	0.57	2099
	Source Flux	3000lm	2	3.68	1.14	525
	Fixture Flux	2242lm	3	5.52	1.70	233
	Efficacy	80lm/W	4	7.36	2.27	131
TS1078	Imax	2099cd	5	9.20	2.84	84

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6759EL**	**1T6760EL**	**1T6761EL**	**1T6762EL**
DALI		**1T6759DA**	**1T6760DA**	**1T6761DA**	**1T6762DA**

LED / 24W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			76°	15°	
	Fixture Power	28W	1	1.55	0.26	4805
	Source Flux	3000lm	2	3.10	0.51	1201
	Fixture Flux	2495lm	3	4.65	0.77	534
	Efficacy	89lm/W	4	6.21	1.02	300
TS1080	Imax	4805cd	5	7.76	1.28	192

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6763EL**	**1T6764EL**	**1T6765EL**	**1T6766EL**
DALI		**1T6763DA**	**1T6764DA**	**1T6765DA**	**1T6766DA**

LED / 24W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			115°	59°	
	Fixture Power	28W	1	3.12	1.34	2017
	Source Flux	3000lm	2	6.23	2.67	504
	Fixture Flux	2256lm	3	9.35	4.01	224
	Efficacy	81lm/W	4	12.47	5.35	126
TS1082	Imax	2321cd	5	15.59	6.69	81

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6767EL**	**1T6768EL**	**1T6769EL**	**1T6770EL**
DALI		**1T6767DA**	**1T6768DA**	**1T6769DA**	**1T6770DA**

JEDI COMPACT

IP40
Integrated-removable driver
L. 850mm



LED / 35W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	38W	1	0.20	53966
Source Flux	4238lm	2	0.40	13491
Fixture Flux	3511lm	3	0.59	5996
Efficacy	92lm/W	4	0.79	3373
TS1243 Imax=12734cd/klm	Imax	53966cd	5	0.99	2159

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T8928EL**	**1T8929EL**	**1T8930EL**	**1T8931EL**
DALI		**1T8928DA**	**1T8929DA**	**1T8930DA**	**1T8931DA**

LED / 36W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			85°	32°	
Fixture Power	40W	1	1.84	0.57	3146
Source Flux	4500lm	2	3.68	1.14	787
Fixture Flux	3361lm	3	5.52	1.70	350
Efficacy	84lm/W	4	7.36	2.27	197
TS1079 Imax=699cd/klm	Imax	3146cd	5	9.20	2.84	126

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6771EL**	**1T6772EL**	**1T6773EL**	**1T6774EL**
DALI		**1T6771DA**	**1T6772DA**	**1T6773DA**	**1T6774DA**

LED / 36W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			76°	15°	
Fixture Power	40W	1	1.55	0.26	7203
Source Flux	4500lm	2	3.10	0.51	1801
Fixture Flux	3740lm	3	4.65	0.77	800
Efficacy	94lm/W	4	6.21	1.02	450
TS1081 Imax=1601cd/klm	Imax	7203cd	5	7.76	1.28	288

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6775EL**	**1T6776EL**	**1T6777EL**	**1T6778EL**
DALI		**1T6775DA**	**1T6776DA**	**1T6777DA**	**1T6778DA**

LED / 36W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			115°	59°	
Fixture Power	40W	1	3.12	1.34	3026
Source Flux	4500lm	2	6.23	2.67	756
Fixture Flux	3384lm	3	9.35	4.01	336
Efficacy	85lm/W	4	12.47	5.35	189
TS1083 Imax=774cd/klm	Imax	3482cd	5	15.59	6.69	121

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6779EL**	**1T6780EL**	**1T6781EL**	**1T6782EL**
DALI		**1T6779DA**	**1T6780DA**	**1T6781DA**	**1T6782DA**

JEDI COMPACT

IP40
Integrated-removable driver
L. 1130mm



LED / 46W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
	Fixture Power	51W	1	0.20	71959
	Source Flux	5651lm	2	0.40	17990
	Fixture Flux	4682lm	3	0.59	7995
	Efficacy	92lm/W	4	0.79	4497
TS1243	Imax=12734cd/klm	Imax	5	0.99	2878

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T8932EL**	**1T8933EL**	**1T8934EL**	**1T8935EL**
DALI		**1T8932DA**	**1T8933DA**	**1T8934DA**	**1T8935DA**

LED / 48W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			85°	32°	
	Fixture Power	53W	1	1.84	0.57	4195
	Source Flux	6000lm	2	3.68	1.14	1049
	Fixture Flux	4482lm	3	5.52	1.70	466
	Efficacy	85lm/W	4	7.36	2.27	262
TS1079	Imax=699cd/klm	Imax	5	9.20	2.84	168

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6783EL**	**1T6784EL**	**1T6785EL**	**1T6786EL**
DALI		**1T6783DA**	**1T6784DA**	**1T6785DA**	**1T6786DA**

LED / 48W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			76°	15°	
	Fixture Power	53W	1	1.55	0.26	9605
	Source Flux	6000lm	2	3.10	0.51	2401
	Fixture Flux	4987lm	3	4.65	0.77	1067
	Efficacy	94lm/W	4	6.21	1.02	600
TS1081	Imax=1601cd/klm	Imax	5	7.76	1.28	384

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6787EL**	**1T6788EL**	**1T6789EL**	**1T6790EL**
DALI		**1T6787DA**	**1T6788DA**	**1T6789DA**	**1T6790DA**

LED / 48W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			115°	59°	
	Fixture Power	53W	1	3.12	1.34	4034
	Source Flux	6000lm	2	6.23	2.67	1009
	Fixture Flux	4512lm	3	9.35	4.01	448
	Efficacy	85lm/W	4	12.47	5.35	252
TS1083	Imax=774cd/klm	Imax	5	15.59	6.69	161

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T6791EL**	**1T6792EL**	**1T6793EL**	**1T6794EL**
DALI		**1T6791DA**	**1T6792DA**	**1T6793DA**	**1T6794DA**

Related codes

Bracket



Code
1T6940

Long bracket kit for surface installation (2 pieces).
Rotation +/-145°.



H	Code
52	**1T6800**

Medium bracket kit for surface installation (2 pieces).
Integrated driver version.
Rotation +/-90°.

JEDI COMPACT



	H	Code
	24	**1T6799**

Short bracket kit for surface installation (2 pieces).
Remote driver version.
Rotation +/-50°.

Power Supply



L	H	P	Output current	Driver	Code
404	47	41	500mA	EL.	**1T6797EL**
404	47	41	500mA	EL.	**1T6798EL**
404	47	41	500mA	DALI	**1T6797DA**
404	47	41	500mA	DALI	**1T6798DA**

Driver box.
L. 289mm version.
1T6797EL - n° 1 JEDI COMPACT
1T6798EL - n° 2-4 JEDI COMPACT
1T6797DA - n° 1 JEDI COMPACT
1T6798DA - n° 2-4 JEDI COMPACT

Accessories

Grid



	L	Code
	278	**1T6795**

Symmetrical anti-glare grill.
Installation inside the product.
For Spot, Flood and Grazing versions.
To be ordered in the following quantities for every fixture length: 1 for the 289mm version, 2 for the 570mm version, 3 for the 850mm version and 4 for the 1130mm version.



	L	Code
	278	**1T6796**

Asymmetrical anti-glare grill.
Installation inside the product.
For Wall Washer versions.
To be ordered in the following quantities for every fixture length: 1 for the 289mm version, 2 for the 570mm version, 3 for the 850mm version and 4 for the 1130mm version.

Bracket



	Code
	1T6806

Bracket kit for surface installation of the driver box (2 pieces).
Snap brackets.

JEDI COMPACT

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

ZENO

Wall mounted

GENERAL INFO
Asymmetric adjustable projector
Medium Ø134mm
Large Ø184mm

LED
Chip on Board
From 2602lm to 5121lm
3000K - 4000K
Ra97

PRODUCT EFFICACY
Up to 54lm/W

OPTICS
WW

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Die-cast painted aluminium optical unit and power supply box.

ON DEMAND

Easy Custom Colour

2700K-3500K

110-277Vac power supply

A range of professional projectors especially for museum lighting, given the quality of the LED sources, the cutting edge optics and installation flexibility.

The wall washer optics is particularly suitable for lighting vaulted ceilings.

The optical unit can be adjusted from 0 to -90° on the vertical plane; and 355° on the horizontal plane with aiming blocking system. Available in two different sizes.

Also available in the projector and recessed versions.

Palazzo Merendoni
Bologna, Italy

Photographer Ivan Rossi

ZENO



Applique Large



LED / 52W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra97			34°	81°	
Fixture Power	56W	1	0.98	1.99	1761
Source Flux	4995lm	2	1.96	3.98	440
Fixture Flux	2413lm	3	2.94	5.96	196
Efficacy	43lm/W	4	3.92	7.95	110
TS985 Imax=520cd/klm	Imax	2599cd	5	4.91	9.94	70

Driver	Colour	3000K	4000K
EL.	○	**1T6313EL**	**1T6314EL**
EL.	◐	**1T6315EL**	**1T6316EL**
DALI	○	**1T6313DA**	**1T6314DA**
DALI	◐	**1T6315DA**	**1T6316DA**

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

ZENO

Applique Medium



LED / 26W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra97			34°	54°	
Fixture Power	28W	1	1.06	1.18	1345
Source Flux	2602lm	2	2.11	2.35	336
Fixture Flux	1473lm	3	3.17	3.53	149
Efficacy	53lm/W	4	4.23	4.71	84
Imax	1939cd	5	5.28	5.89	54

Driver	Colour	3000K	4000K
EL.	○	**1T6309EL**	**1T6310EL**
EL.	◐	**1T6311EL**	**1T6312EL**
DALI	○	**1T6309DA**	**1T6310DA**
DALI	◐	**1T6311DA**	**1T6312DA**

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

VOLTA

GENERAL INFO
Professional adjustable LED projector for wall or cornice installation.
184mmx86,5mm

LED
Elliptical and asymmetrical optic:
LED Chip on board
NSP optic: LED Emitter
From 650lm to 4373lm
3000K
Ra80 – Ra84

PRODUCT EFFICACY
Up to 105lm/W

OPTICS
NSP – ASYM – ELLIPTICAL

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only with DALI driver).

MATERIAL
Body in extruded anodized aluminium, optic unit and terminal in die cast powder coated aluminium. Ultra flat protection screen in tempered glass. Bracket in stainless steel predisposed for surface installation.

ON DEMAND

Easy Custom Colour

110-277Vac
power supply

Professional adjustable LED projector for wall or cornice installation, particularly suitable for lighting historical buildings of great artistic value.

It can be installed on cornices for lighting vaulted ceilings or pedestrian areas.
Available in various colour variants that have been carefully studied to insert the fixture into historical architectural contexts.

All versions can be installed indoor as well as outdoor (IP66).

To be completed with an electronic or DALI remote power supply.



Loggia del Pesce
Firenze, Italia

Photographer Ivan Rossi

VOLTA



LED / 8W / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		12W	1	0.16	13011
Source Flux		650lm	2	0.32	3253
Fixture Flux		544lm	3	0.48	1446
Efficacy		47lm/W	4	0.64	813
TS880	Imax=20017cd/klm	Imax	13011cd	5	0.80	520

Power supply	Colour	3000K
900mA		**1T4632**
900mA		**1T4633**
900mA		**1E2565**
900mA		**1E2566**

LED / 21/33W / ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			61°	86°	
Fixture Power		24W	1	1.51	1.98	1356
Source Flux		3187lm	2	3.01	3.96	339
Fixture Flux		2304lm	3	4.52	5.94	151
Efficacy		96lm/W	4	6.02	7.92	85
TS881	Imax=464cd/klm	Imax	1480cd	5	7.53	9.89	54



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			61°	86°	
Fixture Power		37W	1	1.51	1.98	1860
Source Flux		4373lm	2	3.01	3.96	465
Fixture Flux		3162lm	3	4.52	5.94	207
Efficacy		85lm/W	4	6.02	7.92	116
TS881	Imax=464cd/klm	Imax	2031cd	5	7.53	9.89	74

Power supply	Colour	3000K
600/900mA		**1T4634**
600/900mA		**1T4635**
600/900mA		**1E2567**
600/900mA		**1E2568**

LED / 21/33W / ELLIPTICAL



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power		24W	1	0.76	1.66	2266
Source Flux		3187lm	2	1.52	3.31	567
Fixture Flux		2530lm	3	2.28	4.97	252
Efficacy		105lm/W	4	3.04	6.62	142
TS882	Imax=711cd/klm	Imax	2266cd	5	3.80	8.28	91



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power		37W	1	0.76	1.66	3110
Source Flux		4373lm	2	1.52	3.31	777
Fixture Flux		3471lm	3	2.28	4.97	346
Efficacy		94lm/W	4	3.04	6.62	194
TS882	Imax=711cd/klm	Imax	3110cd	5	3.80	8.28	124

Power supply	Colour	3000K
600/900mA		**1T4636**
600/900mA		**1T4637**
600/900mA		**1E2569**
600/900mA		**1E2570**

VOLTA

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
160x35x83	32W	110-240Vac	600mA	IP20	**1T3625**
150x40x148	max 43W	220-240Vac	600mA	IP68	**1E2571**
160x35x83	max 50W	220-240Vac	900mA	IP20	**1T2966**
150x40x148	max 50W	220-240Vac	900mA	IP68	**1E2573**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
160x35x83	32W	110-240Vac	600mA	IP20	**1T3627**
150x40x148	max 43W	220-240Vac	600mA	IP68	**1E2572**
160x35x83	max 50W	110-240Vac	900mA	IP20	**1T2968**
150x40x148	max 50W	220-240Vac	900mA	IP68	**1E2574**

DALI power supply.

Accessories

Filter

Colour	Code
	1T4638
	1T4639
	1E2575
	1E2576

Blade of light filter.
PMMA holographic filter for a blade of light effect, CNC machine anodised and powder coated aluminium frame.
To be used with NSP optics.

Colour	Code
	1T4640
	1T4641
	1E2577
	1E2578

Anti-glare.
PMMA holographic filter to reduce the beam angle, CNC machine anodised and powder coated aluminium frame.
To be used with NSP, ASYM and ELLIPTICAL optics.

Screen

Colour	Code
	1T4642
	1T4643
	1E2579
	1E2580

Asymmetric screen.
Powder coated stainless steel.
To be used with NSP, EFFECT and ELLIPTICAL optics.

Emergency Kit



Code
1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

Palazzo Merendoni
Bologna, Italy

Photographer Ivan Rossi

CORO

GENERAL INFO
Professional adjustable LED projector for wall or cornice installation.
Optic adjustability: +/-165° horizontally and +/-180° vertically with aiming blocking system.
Ø82mm – Ø119mm

LED
Chip on board
From 200lm to 7217lm
3000K-4000K
Ra80 (only NSP optic) – Ra84 – Ra97

PRODUCT EFFICACY
Up to 116lm/W

OPTICS
NSP (only Small version) – SP – FL
MWFL – WFL
DBS - Digital beam opening control (Coro Large)

POWER SUPPLY
Electronic – DALI - Casambi on board

MATERIAL
Coro Large: die-cast aluminium body and powder coated aluminium front ring and joints.
Coro Small: powder coated die-cast aluminium body, front ring and joints.

ON DEMAND
Easy Custom Colour

A range of cornice, capital and shelf projectors particularly suitable for installation in prestigious architectural environments where it is necessary to light the space without interfering with the architecture in any way.

Available in two different sizes - Large and Small - each with two different length arms and three different fixing systems that increase installation flexibility.

There is also a DBS - Dynamic Beam Shaper- version - for the Coro Large version only.

		CORO Large	CORO Small
		Ø 119mm	Ø 82mm
LED	Flux (lm)	2783-7217	200-2509
	Power	25W-47.6W	2.7W-18W
OPTICS			
NSP	Lens		•
SP	Lens		•
	Hybrid	•	
	Reflector	•	
FL	Lens		•
	Hybrid	•	
	Reflector	•	
MWFL	Reflector	•	•
WFL	Reflector		•
DBS	Variable	•	

Cattedrale di Santa Maria Assunta
Volterra, Pisa - Italy

Architect Giorgio Bascià

Lighting Design Arch. Massimo Iarussi

Plus

A **Coro available in two different sizes**
and two different finishes: sandstone grey and Florentine white, two colours that integrate perfectly in historical contexts.

B **The flexibility of the fixture is best represented by its fixing system.**
Three different solutions for as many types of installation.



Mounting rail for surfaces up to 900mm long. Great installation flexibility using a few fixing elements, the projectors can be fixed to any point on the rail which can also house all the electrical conduits of the system (remote driver)

Base for surface mounting (remote driver)

Base for surface mounting with integrated driver. Also available in a Casambi version to control fixtures using an App.

CORO

Large long arm



LED / 34W / HYBRID / SP / CRI84



3000K		H(m)	D(m)	Emax(lx)
Ra84			13°	
Fixture Power	37W	1	0.23	41198
Source Flux	4478lm	2	0.46	10299
Fixture Flux	2904lm	3	0.69	4578
Efficacy	78lm/W	4	0.92	2575
TS918 Imax=9200cd/klm	Imax	41198cd	5	1.14	1648

Power supply	Colour	3000K
900mA		**1T4785**
900mA		**1T4787**

LED / 34W / HYBRID / SP / CRI97



3000K		H(m)	D(m)	Emax(lx)
Ra97			13°	
Fixture Power	37W	1	0.23	30351
Source Flux	3299lm	2	0.46	7588
Fixture Flux	2139lm	3	0.69	3372
Efficacy	58lm/W	4	0.92	1897
TS918 Imax=9200cd/klm	Imax	30351cd	5	1.14	1214

Power supply	Colour	3000K
900mA		**1T5312**
900mA		**1T5314**

LED / 34W / HYBRID / FL / CRI84



3000K		H(m)	D(m)	Emax(lx)
Ra84			33°	
Fixture Power	37W	1	0.58	9994
Source Flux	4478lm	2	1.17	2499
Fixture Flux	2733lm	3	1.75	1110
Efficacy	73lm/W	4	2.33	625
TS919 Imax=2232cd/klm	Imax	9994cd	5	2.92	400

Power supply	Colour	3000K
900mA		**1T4786**
900mA		**1T4788**

LED / 34W / HYBRID / FL / CRI97



3000K		H(m)	D(m)	Emax(lx)
Ra97			33°	
Fixture Power	37W	1	0.58	7363
Source Flux	3299lm	2	1.17	1841
Fixture Flux	2014lm	3	1.75	818
Efficacy	54lm/W	4	2.33	460
TS919 Imax=2232cd/klm	Imax	7363cd	5	2.92	295

Power supply	Colour	3000K
900mA		**1T5313**
900mA		**1T5315**

LED / 25W / REFLECTOR / SP / CRI84



3000K		H(m)	D(m)	Emax(lx)
Ra84			15°	
Fixture Power	28W	1	0.26	24211
Source Flux	3617lm	2	0.52	6053
Fixture Flux	3074lm	3	0.78	2690
Efficacy	110lm/W	4	1.04	1513
TS860 Imax=6694cd/klm	Imax	24211cd	5	1.30	968

Power supply	Colour	3000K
700mA		**1T4560**
700mA		**1T4564**

CORO

LED / 25W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			15°	
Fixture Power		28W	1	0.26	18629
Source Flux		2783lm	2	0.52	4657
Fixture Flux		2366lm	3	0.78	2070
Efficacy		84lm/W	4	1.04	1164
TS860	Imax=6694cd/klm	Imax	18629cd	5	1.30	745

Power supply	Colour	3000K
700mA		**1T5302**
700mA		**1T5306**

LED / 25W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			31°	
Fixture Power		28W	1	0.55	9064
Source Flux		3617lm	2	1.09	2266
Fixture Flux		3062lm	3	1.64	1007
Efficacy		109lm/W	4	2.19	567
TS861	Imax=2506cd/klm	Imax	9064cd	5	2.73	363

Power supply	Colour	3000K
700mA		**1T4561**
700mA		**1T4565**

LED / 25W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			31°	
Fixture Power		28W	1	0.55	6974
Source Flux		2783lm	2	1.09	1744
Fixture Flux		2356lm	3	1.64	775
Efficacy		84lm/W	4	2.19	436
TS861	Imax=2506cd/klm	Imax	6974cd	5	2.73	279

Power supply	Colour	3000K
700mA		**1T5303**
700mA		**1T5307**

LED / 39W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			15°	
Fixture Power		42W	1	0.26	35380
Source Flux		4980lm	2	0.51	8845
Fixture Flux		4233lm	3	0.77	3931
Efficacy		100lm/W	4	1.02	2211
TS862	Imax=7104cd/klm	Imax	35380cd	5	1.28	1415

Power supply	Colour	3000K
1050mA		**1T4569**
1050mA		**1T4575**

LED / 39W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			15°	
Fixture Power		42W	1	0.26	27210
Source Flux		3830lm	2	0.51	6803
Fixture Flux		3255lm	3	0.77	3023
Efficacy		77lm/W	4	1.02	1701
TS862	Imax=7104cd/klm	Imax	27210cd	5	1.28	1088

Power supply	Colour	3000K
1050mA		**1T4581**
1050mA		**1T4587**

LED / 39W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			28°	
Fixture Power		42W	1	0.50	13841
Source Flux		4980lm	2	1.01	3460
Fixture Flux		4216lm	3	1.51	1538
Efficacy		99lm/W	4	2.02	865
TS863	Imax=2779cd/klm	Imax	13841cd	5	2.52	554

Power supply	Colour	3000K
1050mA		**1T4570**
1050mA		**1T4576**

CORO

LED / 39W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			28°	
Fixture Power		42W	1	0.50	10645
Source Flux		3830lm	2	1.01	2661
Fixture Flux		3242lm	3	1.51	1183
Efficacy		76lm/W	4	2.02	665
TS863	Imax=2779cd/klm	Imax	5	2.52	426

Power supply	Colour	3000K
1050mA		**1T4582**
1050mA		**1T4588**

LED / 39W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			43°	
Fixture Power		42W	1	0.79	8255
Source Flux		4980lm	2	1.59	2064
Fixture Flux		4328lm	3	2.38	917
Efficacy		102lm/W	4	3.18	516
TS864	Imax=1685cd/klm	Imax	5	3.97	330

Power supply	Colour	3000K
1050mA		**1T4571**
1050mA		**1T4577**

LED / 39W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			43°	
Fixture Power		42W	1	0.79	6349
Source Flux		3830lm	2	1.59	1587
Fixture Flux		3328lm	3	2.38	705
Efficacy		78lm/W	4	3.18	397
TS864	Imax=1685cd/klm	Imax	5	3.97	254

Power supply	Colour	3000K
1050mA		**1T4583**
1050mA		**1T4589**

LED / 47,6W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			34°	
Fixture Power		54W	1	0.62	15622
Source Flux		7217lm	2	1.23	3906
Fixture Flux		6109lm	3	1.85	1736
Efficacy		113lm/W	4	2.46	976
TS865-104	Imax=2165cd/klm	Imax	5	3.08	625

Power supply	Colour	3000K
1400mA		**1T4592**
1400mA		**1T4596**

LED / 47,6W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			34°	
Fixture Power		54W	1	0.62	11916
Source Flux		5505lm	2	1.23	2979
Fixture Flux		4660lm	3	1.85	1324
Efficacy		86lm/W	4	2.46	745
TS865-104	Imax=2165cd/klm	Imax	5	3.08	477

Power supply	Colour	3000K
1400mA		**1T4600**
1400mA		**1T4604**

LED / 47,6W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			47°	
Fixture Power		54W	1	0.87	10617
Source Flux		7217lm	2	1.75	2654
Fixture Flux		6272lm	3	2.62	1180
Efficacy		116lm/W	4	3.50	664
TS866-104	Imax=1472cd/klm	Imax	5	4.37	425

Power supply	Colour	3000K
1400mA		**1T4593**
1400mA		**1T4597**

CORO

LED / 47,6W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			47°	
Fixture Power		54W	1	0.87	8099
Source Flux		5505lm	2	1.75	2025
Fixture Flux		4784lm	3	2.62	900
Efficacy		89lm/W	4	3.50	506
TS866-104	Imax=1472cd/klm	Imax	5	4.37	324

Power supply	Colour	3000K
1400mA		**1T4601**
1400mA		**1T4605**

Large short arm



LED / 34W / HYBRID / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			13°	
Fixture Power		37W	1	0.23	41198
Source Flux		4478lm	2	0.46	10299
Fixture Flux		2904lm	3	0.69	4578
Efficacy		78lm/W	4	0.92	2575
TS918	Imax=9200cd/klm	Imax	5	1.14	1648

Power supply	Colour	3000K
900mA		**1T4781**
900mA		**1T4783**

LED / 34W / HYBRID / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			13°	
Fixture Power		37W	1	0.23	30351
Source Flux		3299lm	2	0.46	7588
Fixture Flux		2139lm	3	0.69	3372
Efficacy		58lm/W	4	0.92	1897
TS918	Imax=9200cd/klm	Imax	5	1.14	1214

Power supply	Colour	3000K
900mA		**1T5308**
900mA		**1T5310**

LED / 34W / HYBRID / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			33°	
Fixture Power		37W	1	0.58	9994
Source Flux		4478lm	2	1.17	2499
Fixture Flux		2733lm	3	1.75	1110
Efficacy		73lm/W	4	2.33	625
TS919	Imax=2232cd/klm	Imax	5	2.92	400

Power supply	Colour	3000K
900mA		**1T4782**
900mA		**1T4784**

LED / 34W / HYBRID / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			33°	
Fixture Power		37W	1	0.58	7363
Source Flux		3299lm	2	1.17	1841
Fixture Flux		2014lm	3	1.75	818
Efficacy		54lm/W	4	2.33	460
TS919	Imax=2232cd/klm	Imax	5	2.92	295

Power supply	Colour	3000K
900mA		**1T5309**
900mA		**1T5311**

CORO

LED / 25W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			15°	
Fixture Power		28W	1	0.26	24211
Source Flux		3617lm	2	0.52	6053
Fixture Flux		3074lm	3	0.78	2690
Efficacy		110lm/W	4	1.04	1513
TS860	Imax=6694cd/klm	Imax		1.30	968

Power supply	Colour	3000K
700mA		**1T4558**
700mA		**1T4562**

LED / 25W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			15°	
Fixture Power		28W	1	0.26	18629
Source Flux		2783lm	2	0.52	4657
Fixture Flux		2366lm	3	0.78	2070
Efficacy		84lm/W	4	1.04	1164
TS860	Imax=6694cd/klm	Imax		1.30	745

Power supply	Colour	3000K
700mA		**1T5300**
700mA		**1T5304**

LED / 25W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			31°	
Fixture Power		28W	1	0.55	9064
Source Flux		3617lm	2	1.09	2266
Fixture Flux		3062lm	3	1.64	1007
Efficacy		109lm/W	4	2.19	567
TS861	Imax=2506cd/klm	Imax		2.73	363

Power supply	Colour	3000K
700mA		**1T4559**
700mA		**1T4563**

LED / 25W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			31°	
Fixture Power		28W	1	0.55	6974
Source Flux		2783lm	2	1.09	1744
Fixture Flux		2356lm	3	1.64	775
Efficacy		84lm/W	4	2.19	436
TS861	Imax=2506cd/klm	Imax		2.73	279

Power supply	Colour	3000K
700mA		**1T5301**
700mA		**1T5305**

LED / 39W / REFLECTOR / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			15°	
Fixture Power		42W	1	0.26	35380
Source Flux		4980lm	2	0.51	8845
Fixture Flux		4233lm	3	0.77	3931
Efficacy		100lm/W	4	1.02	2211
TS862	Imax=7104cd/klm	Imax		1.28	1415

Power supply	Colour	3000K
1050mA		**1T4566**
1050mA		**1T4572**

LED / 39W / REFLECTOR / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			15°	
Fixture Power		42W	1	0.26	27210
Source Flux		3830lm	2	0.51	6803
Fixture Flux		3255lm	3	0.77	3023
Efficacy		77lm/W	4	1.02	1701
TS862	Imax=7104cd/klm	Imax		1.28	1088

Power supply	Colour	3000K
1050mA		**1T4578**
1050mA		**1T4584**

CORO

LED / 39W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			28°	
Fixture Power		42W	1	0.50	13841
Source Flux		4980lm	2	1.01	3460
Fixture Flux		4216lm	3	1.51	1538
Efficacy		99lm/W	4	2.02	865
TS863	Imax=2779cd/klm	Imax	13841cd	5	2.52	554

Power supply	Colour	3000K
1050mA		**1T4567**
1050mA		**1T4573**

LED / 39W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			28°	
Fixture Power		42W	1	0.50	10645
Source Flux		3830lm	2	1.01	2661
Fixture Flux		3242lm	3	1.51	1183
Efficacy		76lm/W	4	2.02	665
TS863	Imax=2779cd/klm	Imax	10645cd	5	2.52	426

Power supply	Colour	3000K
1050mA		**1T4579**
1050mA		**1T4585**

LED / 39W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			43°	
Fixture Power		42W	1	0.79	8255
Source Flux		4980lm	2	1.59	2064
Fixture Flux		4328lm	3	2.38	917
Efficacy		102lm/W	4	3.18	516
TS864	Imax=1685cd/klm	Imax	8390cd	5	3.97	330

Power supply	Colour	3000K
1050mA		**1T4568**
1050mA		**1T4574**

LED / 39W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			43°	
Fixture Power		42W	1	0.79	6349
Source Flux		3830lm	2	1.59	1587
Fixture Flux		3328lm	3	2.38	705
Efficacy		78lm/W	4	3.18	397
TS864	Imax=1685cd/klm	Imax	6453cd	5	3.97	254

Power supply	Colour	3000K
1050mA		**1T4580**
1050mA		**1T4586**

LED / 47,6W / REFLECTOR / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			34°	
Fixture Power		54W	1	0.62	15622
Source Flux		7217lm	2	1.23	3906
Fixture Flux		6109lm	3	1.85	1736
Efficacy		113lm/W	4	2.46	976
TS865-104	Imax=2165cd/klm	Imax	15622cd	5	3.08	625

Power supply	Colour	3000K
1400mA		**1T4590**
1400mA		**1T4594**

LED / 47,6W / REFLECTOR / FL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			34°	
Fixture Power		54W	1	0.62	11916
Source Flux		5505lm	2	1.23	2979
Fixture Flux		4660lm	3	1.85	1324
Efficacy		86lm/W	4	2.46	745
TS865-104	Imax=2165cd/klm	Imax	11916cd	5	3.08	477

Power supply	Colour	3000K
1400mA		**1T4598**
1400mA		**1T4602**

CORO

LED / 47,6W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			47°	
Fixture Power		54W	1	0.87	10617
Source Flux		7217lm	2	1.75	2654
Fixture Flux		6272lm	3	2.62	1180
Efficacy		116lm/W	4	3.50	664
TS866-104	Imax=1472cd/klm	Imax	5	4.37	425

Power supply	Colour	3000K
1400mA		**1T4591**
1400mA		**1T4595**

LED / 47,6W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			47°	
Fixture Power		54W	1	0.87	8099
Source Flux		5505lm	2	1.75	2025
Fixture Flux		4784lm	3	2.62	900
Efficacy		89lm/W	4	3.50	506
TS866-104	Imax=1472cd/klm	Imax	5	4.37	324

Power supply	Colour	3000K
1400mA		**1T4599**
1400mA		**1T4603**

Large DBS long arm



LED / 34W / DBS / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		37W	1	0.25	25176
Source Flux		4478lm	2	0.50	6294
Fixture Flux		2140lm	3	0.75	2797
Efficacy		58lm/W	4	1.00	1573
TS1110	Imax=5622cd/klm	Imax	5	1.26	1007

Driver	Colour	3000K
CASAMBI		**1T6945CA**
CASAMBI		**1T6946CA**



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			24°	
Fixture Power		37W	1	0.43	8931
Source Flux		4478lm	2	0.86	2233
Fixture Flux		2082lm	3	1.29	992
Efficacy		56lm/W	4	1.72	558
TS1111	Imax=1994cd/klm	Imax	5	2.15	357



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			31°	
Fixture Power		37W	1	0.56	5426
Source Flux		4478lm	2	1.13	1356
Fixture Flux		2016lm	3	1.69	603
Efficacy		54lm/W	4	2.25	339
TS1112	Imax=1212cd/klm	Imax	5	2.82	217



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
Fixture Power		37W	1	0.83	2585
Source Flux		4478lm	2	1.67	646
Fixture Flux		1769lm	3	2.50	287
Efficacy		48lm/W	4	3.34	162
TS1113	Imax=577cd/klm	Imax	5	4.17	103

CORO

LED / 34W / DBS / CRI97

Driver	Colour	4000K
CASAMBI		**1T6947CA**
CASAMBI		**1T6948CA**



3000K		H(m)	D(m)	Emax(lx)
Ra97			14°	
Fixture Power	37W	1	0.25	18547
Source Flux	3299lm	2	0.50	4637
Fixture Flux	1577lm	3	0.75	2061
Efficacy	42lm/W	4	1.00	1159
Imax	18547cd	5	1.26	742

TS1110 Imax=5622cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra97			24°	
Fixture Power	37W	1	0.43	6580
Source Flux	3299lm	2	0.86	1645
Fixture Flux	1534lm	3	1.29	731
Efficacy	41lm/W	4	1.72	411
Imax	6580cd	5	2.15	263

TS1111 Imax=1994cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra97			31°	
Fixture Power	37W	1	0.56	3997
Source Flux	3299lm	2	1.13	999
Fixture Flux	1485lm	3	1.69	444
Efficacy	40lm/W	4	2.25	250
Imax	3997cd	5	2.82	160

TS1112 Imax=1212cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra97			45°	
Fixture Power	37W	1	0.83	1904
Source Flux	3299lm	2	1.67	476
Fixture Flux	1303lm	3	2.50	212
Efficacy	35lm/W	4	3.34	119
Imax	1904cd	5	4.17	76

TS1113 Imax=577cd/klm

Related codes

Mounting System



Colour	Code
	1T4606
	1T4607

White surface mounting base.



Colour	Code
	1T4628
	1T4629

Surface mounting channel 900mm.
The channel can be cut to length at intervals of 10cm.
With three mounting bases for Coro “Small” and “Big”.

CORO



Power supply	Output current	Driver	Colour	Code
220-240Vac	700mA	EL.		**1T4612**
220-240Vac	700mA	DALI		**1T4613**
220-240Vac	700mA	DALI (CASAMBI)		**1T4613CA**
220-240Vac	900mA	EL.		**1T4614**
220-240Vac	900mA	DALI		**1T4615**
220-240Vac	900mA	DALI (CASAMBI)		**1T4615CA**
220-240Vac	1050mA max 60W	EL.		**1T4616**
220-240Vac	1050mA max 60W	DALI		**1T4617**
220-240Vac	1050mA max 60W	DALI (CASAMBI)		**1T4617CA**
220-240Vac	1400mA max 60W	EL.		**1T9512EL**
220-240Vac	1400mA max 60W	DALI		**1T9512DA**
220-240Vac	1400mA max 60W	DALI (CASAMBI)		**1T9512CA**
220-240Vac	700mA	EL.		**1T4622**
220-240Vac	700mA	DALI		**1T4623**
220-240Vac	700mA	DALI (CASAMBI)		**1T4623CA**
220-240Vac	900mA	EL.		**1T4624**
220-240Vac	900mA	DALI		**1T4625**
220-240Vac	900mA	DALI (CASAMBI)		**1T4625CA**
220-240Vac	1050mA max 60W	EL.		**1T4626**
220-240Vac	1050mA max 60W	DALI		**1T4627**
220-240Vac	1050mA max 60W	DALI (CASAMBI)		**1T4627CA**
220-240Vac	1400mA max 60W	EL.		**1T9514EL**
220-240Vac	1400mA max 60W	DALI		**1T9514DA**
220-240Vac	1400mA max 60W	DALI (CASAMBI)		**1T9514CA**

Surface mounting base with integrated driver.

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
160x35x83	29W	110-240Vac	700mA	IP20	**1T2963**
160x35x83	max 50W	220-240Vac	900mA	IP20	**1T2966**
160x35x83	max 42W	110-240Vac	1050mA	IP20	**1T3781**
130x30x43	60W	220-240Vac	1400mA	IP20	**1T9513EL**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
160x35x83	29W	110-240Vac	700mA	IP20	**1T2965**
160x35x83	max 50W	110-240Vac	900mA	IP20	**1T2968**
160x35x83	max 42W	110-240Vac	1050mA	IP20	**1T3783**
129x30x76	60W	220-240Vac	1400mA	IP20	**1T9513DA**

DALI power supply.

Accessories

Filter



Filter	Ø	Code
Red	80	**1T3424**
Green	80	**1T3425**
Blue	80	**1T3426**
Yellow	80	**1T3427**
Magenta	80	**1T3428**

Flat glass interference chromatic filter.



Ø	Code
80	**1T3141**

Flat glass, grooved refractive blade light filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.



Ø	Code
80	**1T3140**

Flat glass micro prismatic refractive diffusive filter.
This softens the luminous effect.



Filter	Ø	Code
Halogen +	80	**1T6382**
Vivid +	80	**1T6384**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Meat	80	**1T6386**
Fish	80	**1T6388**
Bread	80	**1T6390**
Vegetables	80	**1T6392**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
1T6386 - To be used only with 3000K and Ra84 fixtures.
1T6388 - To be used only with 4000K and Ra84 fixtures.
1T6390 - To be used only with 3000K and Ra84 fixtures.
1T6392 - To be used only with 3000K and Ra84 fixtures.



Filter	Ø	Code
Beauty	80	**1T6394**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.

Grid



Ø	Code
80	**1T3423**

Anti-glare louver.
Black painted metal honeycomb structure.

Zoom



Ø	Code
80	**1T3432**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It makes it possible to obtain a variable beam from 15° to 60°.
It can not be used with NSP and hybrid optics; no for DBS version.

CORO

Cut-off



Ø	Code
80	**1T3142**

Cut-off Tube.
Allows for the beam to be focused while removing the fall-off component.
No for DBS version.

Screen



Ø	Code
80	**1T3143**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Emergency Kit



Code
1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CORO

Small long arm



LED / 2,7W / LENS / NSP / CRI80



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		5W	1	0.15	4436
Source Flux		200lm	2	0.30	1109
Fixture Flux		163lm	3	0.45	493
Efficacy		31lm/W	4	0.60	277
TS890	Imax=22178cd/klm	Imax	4436cd	5	0.75	177

Power supply	Colour	3000K
900mA		**1T4724**
900mA		**1T4728**

LED / 11W / LENS / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			15°	
Fixture Power		14W	1	0.27	15975
Source Flux		1686lm	2	0.53	3994
Fixture Flux		1261lm	3	0.80	1775
Efficacy		93lm/W	4	1.07	998
TS855	Imax=9475cd/klm	Imax	15975cd	5	1.33	639

Power supply	Colour	3000K
350mA		**1T4528**
350mA		**1T4532**

LED / 12W / LENS / FL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			30°	
Fixture Power		14W	1	0.54	4873
Source Flux		1856lm	2	1.09	1218
Fixture Flux		1328lm	3	1.63	541
Efficacy		98lm/W	4	2.17	305
TS856	Imax=2625cd/klm	Imax	4873cd	5	2.72	195

Power supply	Colour	3000K
350mA		**1T4529**
350mA		**1T4533**

LED / 18W / LENS / SP / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			24°	
Fixture Power		20W	1	0.43	8958
Source Flux		2509lm	2	0.87	2239
Fixture Flux		1831lm	3	1.30	995
Efficacy		91lm/W	4	1.73	560
TS857	Imax=3570cd/klm	Imax	8958cd	5	2.17	358

Power supply	Colour	3000K
500mA		**1T4541**
500mA		**1T4547**

LED / 18W / LENS / SP / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			24°	
Fixture Power		20W	1	0.43	6869
Source Flux		1924lm	2	0.87	1717
Fixture Flux		1404lm	3	1.30	763
Efficacy		69lm/W	4	1.73	429
TS857	Imax=3570cd/klm	Imax	6869cd	5	2.17	275

Power supply	Colour	3000K
500mA		**1T5298**
500mA		**1T5299**

CORO

LED / 18W / REFLECTOR / MWFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		20W	1	0.90	3229
Source Flux		2509lm	2	1.80	807
Fixture Flux		1983lm	3	2.69	359
Efficacy		98lm/W	4	3.59	202
TS858	Imax=1310cd/klm	Imax	3287cd	5	4.49	129

Power supply	Colour	3000K
500mA		**1T4542**
500mA		**1T4548**

LED / 18W / REFLECTOR / MWFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			48°	
Fixture Power		20W	1	0.90	2476
Source Flux		1924lm	2	1.80	619
Fixture Flux		1520lm	3	2.69	275
Efficacy		75lm/W	4	3.59	155
TS858	Imax=1310cd/klm	Imax	2521cd	5	4.49	99

Power supply	Colour	3000K
500mA		**1T4552**
500mA		**1T4556**

LED / 18W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			60°	
Fixture Power		20W	1	1.16	2447
Source Flux		2509lm	2	2.32	612
Fixture Flux		2013lm	3	3.47	272
Efficacy		100lm/W	4	4.63	153
TS859	Imax=976cd/klm	Imax	2449cd	5	5.79	98

Power supply	Colour	3000K
500mA		**1T4543**
500mA		**1T4549**

LED / 18W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			60°	
Fixture Power		20W	1	1.16	1877
Source Flux		1924lm	2	2.32	469
Fixture Flux		1544lm	3	3.47	209
Efficacy		76lm/W	4	4.63	117
TS859	Imax=976cd/klm	Imax	1878cd	5	5.79	75

Power supply	Colour	3000K
500mA		**1T4553**
500mA		**1T4557**

Small short arm



LED / 2,7W / LENS / NSP / CRI80



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		5W	1	0.15	4436
Source Flux		200lm	2	0.30	1109
Fixture Flux		163lm	3	0.45	493
Efficacy		31lm/W	4	0.60	277
TS890	Imax=22178cd/klm	Imax	4436cd	5	0.75	177

Power supply	Colour	3000K
900mA		**1T4722**
900mA		**1T4726**

CORO

LED / 11W / LENS / SP / CRI84



3000K		H(m)	D(m)	Emax(lx)
Ra84			15°	
Fixture Power	14W	1	0.27	15975
Source Flux	1686lm	2	0.53	3994
Fixture Flux	1261lm	3	0.80	1775
Efficacy	93lm/W	4	1.07	998
TS855 Imax=9475cd/klm	Imax	15975cd	5	1.33	639

Power supply	Colour	3000K
350mA		**1T4526**
350mA		**1T4530**

LED / 12W / LENS / FL / CRI84



3000K		H(m)	D(m)	Emax(lx)
Ra84			30°	
Fixture Power	14W	1	0.54	4873
Source Flux	1856lm	2	1.09	1218
Fixture Flux	1328lm	3	1.63	541
Efficacy	98lm/W	4	2.17	305
TS856 Imax=2625cd/klm	Imax	4873cd	5	2.72	195

Power supply	Colour	3000K
350mA		**1T4527**
350mA		**1T4531**

LED / 18W / LENS / SP / CRI84



3000K		H(m)	D(m)	Emax(lx)
Ra84			24°	
Fixture Power	20W	1	0.43	8958
Source Flux	2509lm	2	0.87	2239
Fixture Flux	1831lm	3	1.30	995
Efficacy	91lm/W	4	1.73	560
TS857 Imax=3570cd/klm	Imax	8958cd	5	2.17	358

Power supply	Colour	3000K
500mA		**1T4538**
500mA		**1T4544**

LED / 18W / LENS / SP / CRI97



3000K		H(m)	D(m)	Emax(lx)
Ra97			24°	
Fixture Power	20W	1	0.43	6869
Source Flux	1924lm	2	0.87	1717
Fixture Flux	1404lm	3	1.30	763
Efficacy	69lm/W	4	1.73	429
TS857 Imax=3570cd/klm	Imax	6869cd	5	2.17	275

Power supply	Colour	3000K
500mA		**1T5296**
500mA		**1T5297**

LED / 18W / REFLECTOR / MWFL / CRI84



3000K		H(m)	D(m)	Emax(lx)
Ra84			48°	
Fixture Power	20W	1	0.90	3229
Source Flux	2509lm	2	1.80	807
Fixture Flux	1983lm	3	2.69	359
Efficacy	98lm/W	4	3.59	202
TS858 Imax=1310cd/klm	Imax	3287cd	5	4.49	129

Power supply	Colour	3000K
500mA		**1T4539**
500mA		**1T4545**

LED / 18W / REFLECTOR / MWFL / CRI97



3000K		H(m)	D(m)	Emax(lx)
Ra97			48°	
Fixture Power	20W	1	0.90	2476
Source Flux	1924lm	2	1.80	619
Fixture Flux	1520lm	3	2.69	275
Efficacy	75lm/W	4	3.59	155
TS858 Imax=1310cd/klm	Imax	2521cd	5	4.49	99

Power supply	Colour	3000K
500mA		**1T4550**
500mA		**1T4554**

CORO

LED / 18W / REFLECTOR / WFL / CRI84



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			60°	
Fixture Power		20W	1	1.16	2447
Source Flux		2509lm	2	2.32	612
Fixture Flux		2013lm	3	3.47	272
Efficacy		100lm/W	4	4.63	153
TS859	Imax=976cd/klm	Imax	2449cd	5	5.79	98

Power supply	Colour	3000K
500mA		**1T4540**
500mA		**1T4546**

LED / 18W / REFLECTOR / WFL / CRI97



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			60°	
Fixture Power		20W	1	1.16	1877
Source Flux		1924lm	2	2.32	469
Fixture Flux		1544lm	3	3.47	209
Efficacy		76lm/W	4	4.63	117
TS859	Imax=976cd/klm	Imax	1878cd	5	5.79	75

Power supply	Colour	3000K
500mA		**1T4551**
500mA		**1T4555**

Related codes

Mounting System



Colour	Code
	1T4606
	1T4607

White surface mounting base.



Colour	Code
	1T4628
	1T4629

Surface mounting channel 900mm.
The channel can be cut to length at intervals of 10cm.
With three mounting bases for Coro “Small” and “Big”.



Power supply	Output current	Driver	Colour	Code
220-240Vac	350mA	EL.		**1T4608**
220-240Vac	350mA	EL.		**1T4618**
220-240Vac	350mA	DALI		**1T4609**
220-240Vac	350mA	DALI		**1T4619**
220-240Vac	500mA	EL.		**1T4610**
220-240Vac	500mA	EL.		**1T4620**
220-240Vac	500mA	DALI		**1T4611**
220-240Vac	500mA	DALI		**1T4621**

Surface mounting base with integrated driver.



Power supply	Output current	Driver	Colour	Code
220-240Vac	900mA	EL.		**1T4614**
220-240Vac	900mA	DALI		**1T4615**
220-240Vac	900mA	DALI (CASAMBI)		**1T4615CA**
220-240Vac	900mA	EL.		**1T4624**
220-240Vac	900mA	DALI		**1T4625**
220-240Vac	900mA	DALI (CASAMBI)		**1T4625CA**
220-240Vac	350mA	DALI (CASAMBI)		**1T4609CA**
220-240Vac	350mA	DALI (CASAMBI)		**1T4619CA**
220-240Vac	500mA	DALI (CASAMBI)		**1T4611CA**
220-240Vac	500mA	DALI (CASAMBI)		**1T4621CA**

Surface mounting base with integrated driver.

CORO

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
119x22x52	15W	220-240Vac	350mA	IP20	**1T1757**
130x30x42	max 22W	220-240Vac	500mA	IP20	**1T3966**
160x35x83	max 50W	220-240Vac	900mA	IP20	**1T2966**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
119x22x52	max 15W	110-240Vac	350mA	IP20	**1T4630**
119x22x52	20/15W	220-240Vac/110-120Vac	500mA	IP20	**1T4631**
160x35x83	max 50W	110-240Vac	900mA	IP20	**1T2968**

DALI power supply.

Accessories

Filter

Filter	Ø	Code
Red	50	**49881**
Green	50	**49882**
Blue	50	**49886**
Yellow	50	**49887**
Magenta	50	**49959**

Flat glass interference chromatic filter.



Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Filter	Ø	Code
Halogen +	50	**1T6381**
Vivid +	50	**1T6383**

Art filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.

Filter	Ø	Code
Meat	50	**1T6385**
Fish	50	**1T6387**
Bread	50	**1T6389**
Vegetables	50	**1T6391**

Food filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
1T6385 - To be used only with 3000K and Ra84 fixtures.
1T6387 - To be used only with 4000K and Ra84 fixtures.
1T6389 - To be used only with 3000K and Ra84 fixtures.
1T6391 - To be used only with 3000K and Ra84 fixtures.

Filter	Ø	Code
Beauty	50	**1T6393**

Beauty filter.
Flat glass interference filter that can vary the colour parameters of the emission of the fixtures it is applied to.
To be used only with 3000K and Ra84 fixtures.

CORO

Screen



Ø	Code
50	**1T4325**

Black painted anodized diffusive aluminium asymmetric screen.
Complete with blade light filter.
Ideal for a Wall Washer effect.
To be combined with spot and flood optics.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Zoom



Ø	Code
50	**1T4324**

Zoom.
Optical system consists of an optical glass flat convex lens, an anodized aluminium specular reflector and a diffusive holographic filter.
To be used after removing the existing optic.
It can not be used with a narrow spot optic.
It makes it possible to obtain a variable beam from 15° to 60°.

Emergency Kit



Code
1T3144

Emergency kit.
Inverter + 3h battery pack.
LxHxP=165x25x46mm.
IP20.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

OTTO

GENERAL INFO
Pole mounted projector.
Adjustable spotlight body from 0°/-90° on the vertical plane and 0/+90°and 0/-90° on the horizontal plane.
Ø30mm

LED
LED Emitter
From 370lm to 397lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 30lm/W

OPTICS
ZOOM: from SP to FL

POWER SUPPLY
Remote electronic

MATERIAL
Painted or anodised aluminium body connected to a painted metal base.

ON DEMAND
110-277Vac power supply

A range of projectors with a minimal footprint with different installation types characterised by manual focus.

Availble with single or multi-optical configuration: 1x, 2x or 3x.

Also available in ceiling mounted versions with the following installations: semi-recessed, recessed extractable and ceiling mounted with a base.

Project 107
Moscow, Russia

Architect The Ply Architecture

Photographer Andrey Egorov

Plus



The pole version
Is suitable for lighting shop windows or showcases that require a controlled, modular and adjustable light.

Manual focus
It works exactly like a camera lens, rotating the optical unit extends it and the beam opening changes from 14° to 34°.

OTTO

Ceiling



LED / 3W / ZOOM / SP-FL



3000K		H(m)	D(m)	Emax(lx)
Ra84			14°	
Fixture Power	5W	1	0.24	2069
Source Flux	370lm	2	0.49	517
Fixture Flux	117lm	3	0.73	230
Efficacy	23lm/W	4	0.98	129
Imax	2069cd	5	1.22	83



3000K		H(m)	D(m)	Emax(lx)
Ra84			34°	
Fixture Power	5W	1	0.62	481
Source Flux	370lm	2	1.23	120
Fixture Flux	141lm	3	1.85	53
Efficacy	28lm/W	4	2.46	30
Imax	481cd	5	3.08	19

Power supply	Colour	3000K	4000K
1050mA	○	**1T6331**	**1T6332**
1050mA	◐	**1T6343**	**1T6344**
1050mA	◯	**1T6355**	**1T6356**

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
129x30x42	42W	220-240Vac	1050mA	IP20	**1T6524**

Electronic power supply.

Accessories

Canopy

Ø	H	Colour	Code
40	18	○	**1T6528**
40	18	●	**1T6529**
40	18	◯	**1T6530**

Canopy for electrical connection.

OTTO

Multi-Optic 1x



LED / 1x3W / ZOOM / SP-FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		5W	1	0.24	2069
Source Flux		370lm	2	0.49	517
Fixture Flux		117lm	3	0.73	230
Efficacy		23lm/W	4	0.98	129
TS1039	Imax=5593cd/klm	2069cd	5	1.22	83



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			34°	
Fixture Power		5W	1	0.62	481
Source Flux		370lm	2	1.23	120
Fixture Flux		141lm	3	1.85	53
Efficacy		28lm/W	4	2.46	30
TS1040	Imax=1301cd/klm	481cd	5	3.08	19

Power supply	Colour	3000K	4000K
1050mA	○	**1T6325**	**1T6326**
1050mA	◐	**1T6337**	**1T6338**
1050mA	●	**1T6349**	**1T6350**

Multi-Optic 2x



LED / 2x3W / ZOOM / SP-FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
Fixture Power		5W	1	0.24	2069
Source Flux		370lm	2	0.49	517
Fixture Flux		117lm	3	0.73	230
Efficacy		23lm/W	4	0.98	129
TS1039	Imax=5593cd/klm	2069cd	5	1.22	83



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			34°	
Fixture Power		5W	1	0.62	481
Source Flux		370lm	2	1.23	120
Fixture Flux		141lm	3	1.85	53
Efficacy		28lm/W	4	2.46	30
TS1040	Imax=1301cd/klm	481cd	5	3.08	19

Power supply	Colour	3000K	4000K
1050mA	○	**1T6327**	**1T6328**
1050mA	◐	**1T6339**	**1T6340**
1050mA	●	**1T6351**	**1T6352**

OTTO

Multi-Optic 3x



LED / 3x3W / ZOOM / SP-FL

	3000K		H(m)	D(m)	Emax(lx)
	Ra84			14°	
	Fixture Power	5W	1	0.24	2069
	Source Flux	370lm	2	0.49	517
	Fixture Flux	117lm	3	0.73	230
	Efficacy	23lm/W	4	0.98	129
	Imax	2069cd	5	1.22	83



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			34°	
	Fixture Power	5W	1	0.62	481
	Source Flux	370lm	2	1.23	120
	Fixture Flux	141lm	3	1.85	53
	Efficacy	28lm/W	4	2.46	30
	Imax	481cd	5	3.08	19

	Power supply	Colour	3000K	4000K
	1050mA	○	**1T6329**	**1T6330**
	1050mA	●	**1T6341**	**1T6342**
	1050mA	◌	**1T6353**	**1T6354**

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
129x30x42	42W	220-240Vac	1050mA	IP20	**1T6524**

Electronic power supply.

Accessories

Base



	Ø	H	Colour	Code
	40	18	○	**1T6525**
	40	18	●	**1T6526**
	40	18	◌	**1T6527**

Base for electrical connection.

Indoor

New Upgrade

Systems 48V



334
OZ
Power Track

334
OZ
Multiple Module
Small 5x

374
FORTYEIGHT
H section track Ceiling/ Suspension

374
FORTYEIGHT
Label 6
Ø59mm

334
OZ
Single module
Small Fixed

334
OZ
Multiple Module
Large 3x

374
FORTYEIGHT
Track Trimless Recessed

374
FORTYEIGHT
Label 4
Ø40mm

334
OZ
Single module
Small Adjustable

334
OZ
Module Linear



374
FORTYEIGHT
Track Trimless Deep Recessed

374
FORTYEIGHT
Label 2
Ø23mm



334
OZ
Single module
Large Fixed

334
OZ
Recessed profile Small/Large

374
FORTYEIGHT
Logico 30



334
OZ
Single module
Large Adjustable

334
OZ Ceiling/ Suspension installation profile Small/Large

374
FORTYEIGHT
Label 7
Ø74mm

Systems 230V

398
LOGICO System
Ceiling/Suspen-sion Continuous Light module

398
LOGICO System
Trimless Recessed Spot module

398
LOGICO System
Ceiling/Suspen-sion Projector modulee

398
LOGICO System
Recessed with flange Continuous Light module

398
LOGICO System
Ceiling/Suspen-sion Spot module Spot module



398
LOGICO System
Recessed with flange Projector module

398
LOGICO System
Trimless Recessed Continuous light module

398
LOGICO System
Recessed with flange Spot module

398
LOGICO System
Trimless Recessed Projector module

OZ SYSTEM 48V

INFO GENERALI

Power track
Lenghts: 1000mm – 2000mm – 3000mm
L, T and X linear electrical connections.
L orthogonal and adjustable connectors.

Magnetic LED light unit
Small fixed and adjustable
Large fixed and adjustable
5x Small fixed
3x Large fixed
Linear module

Profile
Profile for recessed, ceiling mounted and suspension installation with a double Large and Small section.
Lenghts: 1000mm – 2000mm – 3000mm

LED

Emitter for version Small.
Chip on Board for version Large.
Chip on Board for version Large.
LED Engine made of linear LED boards for linear modules.
From 135lm to 2418lm
2700K - 3000K - 3500K - 4000K
Ra90

PRODUCT EFFICACY

Up to 115lm/W

OPTICS

SP – FL – MWFL
Opal for linear modules
DBS - Digital beam opening control for single modules.

ALIMENTAZIONE

48V system with Electronic power supply - Casambi on board
DALI control system available using a dedicated accessory (only for Casambi version products).

MATERIAL

Power track
Black or white polycarbonate with 2 conductive stainless steel rails. Black or white polycarbonate cover.

Magnetic led light unit
Black or white painted die-cast aluminium.
Acrylic lens and black polycarbonate screen.

Linear modules
Black or white painted die-cast aluminium body with black polycarbonate frame. White highly reflective MCPET reflector and opaline polycarbonate louver screen.

Profile
black or white painted extruded aluminium.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

Oz is a system that designs space and lights it with extreme simplicity and lightness.
A clean, minimal design, an extremely thin 6mm track and a 48V power track. The real heart of the system the magnetic power track adapts freely to the space ready to welcome the light units available with different types, sizes and beam openings at any point along the track.

The systems can be left visible in surface installations where lightness and technology are highlighted, or housed in special profiles that allow for surface, suspension or recessed installation.

The system is available with a 1-10V (Digital Dimming) interface and a DALI-Casambi gateway.

Single light modules are available in DBS - Dynamic Beam Shaper versions.

OZ is also available in a ceiling and recessed stand alone 230V version.

New features to the world of OZ

A **New features to the world of OZ**
The world is not only made of right angles From today OZ is no longer a rigid and rigorous system where lines can only meet orthogonally. The new adjustable connector makes it possible to create new geometries extending the configuration and use possibilities of the OZ system. Thanks to the new connection system it is possible to create in space with greater freedom: every connector can connect from 2 to 8 powertracks to create free angles between “right” angles (minimum 45° angle).

B **DBS Module: a new record for OZ**
In the single version, both fixed and adjustable, Oz is the first miniature light unit that can be equipped with the innovative DBS – Dynamic Beam Shaper - optic that makes it possible to digitally regulate beam openings. Not only is it possible to add, remove and move light modules along the powertrack but now it is also possible to define the photometric distribution as well as the luminous emission of individual light points with extreme simplicity. A prime example of flexibility.

C **Linear light modules**
The OZ range has been extended with new linear light modules. Available in two different sizes - L=569mm e L=869mm - they are equipped with optical systems composed of a high reflectance reflector and an opal polycarbonate screen for a soft, diffused effect.

A connected system
Thanks to the new DALI-Casambi gateway it is possible to interface Casambi version OZ modules with a traditional DALI system. This makes it possible to manage individual light modules using Bluetooth directly from the DALI control unit.

D **A new L shaped support**
Thanks to the new L shaped support the system is even more flexible. In standard installation the light units appear perpendicular to the power track; the new L shaped support provides further possibilities to attach Small modules at 90° to allow for zenithal lighting for example, even when the power track is installed on the wall.







Light modules

Single

Fixed and adjustable Small

25x25mm



Fixed and adjustable Large

50x50mm

Multiple

Small

25x125mm



Large

50x150mm

Linear



Small

L=569mm e L=869mm

Electrical elements

Power track



L=1/2/3m • 48V DC
* To be completed with special end caps

Electrical connectors



Linear L, T, X connectors and orthogonal and adjustable L

Accessories



Cover

L=1/2/3m



An L shaped support

Power supply

see pages 348-349



Power supply for remote driver



Driver on board



Magnetic system

Installation solutions

Recessed for power track



L=1/2/3m

Recessed



Profiles for Small modules
Profiles for Large modules

L=1/2/3m
* To be completed with special end caps

Ceiling and suspension



Profiles for Small modules
Profiles for Large modules

L=1/2/3m
* To be completed with special end caps

Accessories



Cover for Small profile modules
and cover for Large modules

Recessed accessories



Linear and L
shaped connectors

Ceiling and suspension accessories



Linear mechanical L, T and X
shaped connectors

The power track is the heart of the system

The power track is available in three different lengths, black or white. For an effect of formal simplicity it is possible to accessorise the power-track with the cover that hides the two metal tracks. The cover can be easily cut to size on installation.

Innovative 48V magnetic system

Installing modules is really easy, just place them at any point on the system and the magnets will attach them without the need for accessories.

Individual lighting modules

Available in two different extremely compact sizes - 25x25x50 e 50x50x50 - both in fixed and adjustable versions. Now also available with a variable DBS - Dynamic Beam Shaper optic. They can have a body with a white finish and a black screen or be completely black.



Multiple lighting modules

New 3x multi-optical light modules for the Large version and 5x for the Small version, available both in an electronic and Casambi version for remote control of light points. This allows for independent autonomous management of light points on the same track to create different scenarios as needed.

Not only black and white

On request it is possible to have both the single and multiple lighting modules in the desired RAL colour.

Easy Custom Colour

Five different solutions for maximum application flexibility

OZ allows for maximum application flexibility. The power track can be installed directly on the wall and ceiling (A). Using a special “thin” recessed profile for power tracks, ideal for installation in existing suspended ceilings, it is possible to recess the power track leaving the light units visible (B). Alternatively, the profiles available allow to install the power track and luminous units completely hidden from view in suspended ceilings (C), on the ceiling (D) or suspension installation (E).

Thanks to the cover accessory, available in black or white, it is possible to cover the power track for a totally clean effect.
Thanks to a special cover accessory (F), available in black or white it is possible to cover the power track for a completely clean effect. A special cover accessory was also designed to complete the OZ system even with installations using profiles for ceiling or suspension applications (G).

The cover can be easily cut to size to leave only the part of the power track that is necessary to install the light modules on visible.




F
G
E

Zoya boutique
Bangalore, Karnataka - India

Architect Deepak Prem Architects
Lighting Design Mrs. Anusha Muthusubramanian, Lighting Spaces

Photographer GOJIS Lifestyle Pvt Ltd

A single profile for recessed installations with or without a flange

This recessed profile was specially developed to allow for both trimless installation and with a visible flange. This makes it possible to order a unique solution and decide the installation method after.

The rules of OZ

5

Is the maximum number of connectors that can be used n the same configuration



10

Metres is the maximum length of a configuration connected to the same power supply

1

Are the closed systems that can be created. Only closed systems with 4 L-joints are allowed.

3

There are 3 types of driver available

- On board driver box to be house directly on the power track - max 90W
- Driver box for ceiling installation - max 90W - and to be completed with a power head
- Remote driver to be completed with a power head - max 210W

100

Watt is the maximum power that can be installed per metre. The total power of the configuration varies according to the type of driver used.

∞

Possible solutions

▲ Power head ■ End cap

Connectors



System 1 System 2

Alimentation system 1 Alimentation system 1

System 1 Lx4

Different power supplies available

OZ is powered by a driver box installed directly on the power track or a remote driver, to be completed with a power head. The on board driver box can be positioned at the top of the system or at the centre of the power track.

For suspension applications it is possible to choose the solution with a ceiling driver box installed as a canopy and to be completed with a power head positioned directly on the power track.

1. Direct installation on the power track with an on board driver box
2. Direct installation on the power track with a remote driver and a power head
3. Direct installation on the power track with an on board driver box positioned in the centre between two power tracks
4. Installation on a recessed profile with an on board driver box
5. Installation on a recessed profile with a remote driver and a power head positioned on the power track
6. Installation on a ceiling profile with an on board driver box
7. Installation on a ceiling profile with a remote driver and a power head positioned on the power track
8. Installation on a suspension profile with an on board driver box
9. Installation on a suspension profile with a ceiling driver box and a power head positioned on the power track









How to configure Oz

A Standard Configuration



Power track

+

Standard product

+



On board or remote power supply

B DALI Configuration



Power track

+

Casambi product

+



On board or remote power supply

C DALI Configuration



Power track

+

Casambi product

+



On board or remote power supply

+



Bridge DALI-Casambi

D Digital Dimming Configuration



Power track

+

Digital Dimming product

+

Digital Dimming power head

+



Remote driver

+



Controller 1-10V



Power Track



POWER TRACK

Kg	L	Colour	Code
0.3	1000	○	**1T7431**
0.59	2000	○	**1T7432**
0.89	3000	○	**1T7433**
0.3	1000	●	**1T7434**
0.59	2000	●	**1T7435**
0.89	3000	●	**1T7436**

Related codes

End Caps





Colour	Code
○	**1T7026**
●	**1T7027**

Kit containing 2 profile end caps.

Power Supply



Dimensions LxHxP	Colour	Code
71x27x25	○	**1T7024**
71x27x25	●	**1T7025**

Power head.



Dimensions LxHxP	Version	Colour	Code
71x27x26	STANDARD	○	**1T9526DD**
71x27x26	DIMM ON BOARD	○	**1T9603DD**
71x27x26	STANDARD	●	**1T9604DD**
71x27x26	DIMM ON BOARD	●	**1T9605DD**

Digital dimming power head.



Driver	Colour	Code
EL.	○	**1T7028EL**
EL.	●	**1T7029EL**

48Vdc driver box with magnetic coupling.
LxHxP=240x54x26mm, 90W.





Driver	Colour	Code
EL.	○	**1T7030EL**
EL.	●	**1T7172EL**

48Vdc driver box for ceiling installation.
LxHxP=243x58x30mm, 90W.

OZ



Dimensions LxHxP	W	IP	Code
225x36x60	60W	IP20	**1T6917EL**
240x49x60	130W	IP20	**1T6916EL**
251x90x37	210W	IP20	**1T7403EL**

48Vdc electronic driver.
1T6917EL - Single power supply for Electronic, DALI and Casambi systems. Maximum distance 20m - cable 1.5mm^2.
1T6916EL - Single power supply for Electronic, DALI and Casambi systems. Maximum distance 10m - cable 1.5mm^2.
1T7403EL - Universal power supply (110-277V) for Electronic, DALI and Casambi systems. Maximum distance 5m - cable 1.5mm^2.

Accessories

Electrical Connector



Colour	Code
○	**1T7016**
●	**1T7020**

Linear electrical connector.
5 the maximum joints for each driver source.



Colour	Code
○	**1T7017**
●	**1T7021**

Electrical L connector.
5 the maximum joints for each driver source.





Colour	Code
○	**1T7018**
●	**1T7022**

Electrical T connector.
5 the maximum joints for each driver source.



Colour	Code
○	**1T7019**
●	**1T7023**

Electrical X connector.
5 the maximum joints for each driver source.



Colour	Code
○	**1T9524**
●	**1T9525**

Adjustable 2 way electric connector.
Using a special accessory element it is possible to connect up to 8 Power Tracks.



Colour	Code
○	**1T9579**
●	**1T9580**

Accessory element for adjustable electric connector.

OZ



Colour	Code
○	**1T7439**
●	**1T7440**

L-angle electrical coupling.
5 the maximum joints for each driver source.

Mounting System



Colour	Code
○	**1T9592**
●	**1T9593**

L shaped support that offers the possibility to attach modules to the Power Track at 90°.
The support allows for zenithal lighting for example when the power track is installed on the wall.
Only for single 25x25mm light modules.

Cover Panel

L	Colour	Code
1000	○	**1T7938**
1000	◐	**1T7941**
2000	○	**1T7939**
2000	◐	**1T7942**
3000	○	**1T7940**
3000	◐	**1T7943**

Cover for Power Track (5 pieces).

Mounting System



Code
1T7098

BI-ADHESIVE TAPE 10 meters for Power Track installation.

Code
1T9523

Bracket for ceiling installation of the Power Track in modular suspended ceilings.

Control systems



Code
1T9594D

1-10V (DIMM ON BOARD) controller for remote installation.

Code
1T8173CA

Bridge DALI/Casambi: a fixture that allows fixtures equipped with mesh Bluetooth Casambi to interface with a traditional DALI system and to be adjusted by a DALI control unit.
Inside the usual DALI circuit it is possible to have a maximum of 64 cabled DALI and Casambi wireless devices.
It only works with Casambi Evolution networks.
The DALI Bridge is transparent in the DALI system, and therefore does not require an address.
There is no need for a power supply given that it is supplied directly by the DALI bus.
LxHxP=40.4x14x36.3mm.

Lighting module - Single fixed 25x25mm



LED / 2,1W / LENS / SP / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	3W	1	0.20	2505
Source Flux	197lm	2	0.40	626
Fixture Flux	154lm	3	0.60	278
Efficacy	45lm/W	4	0.79	157
Imax	2505cd	5	0.99	100

TS1122 Imax=12713cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7506**	**1T7507**	**1T7508**	**1T7509**
●	**1T7518**	**1T7519**	**1T7520**	**1T7521**

LED / 2,1W / LENS / SP / FIXED CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	3W	1	0.20	2505
Source Flux	197lm	2	0.40	626
Fixture Flux	154lm	3	0.60	278
Efficacy	55lm/W	4	0.79	157
Imax	2505cd	5	0.99	100

TS 1122 Imax=12713cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7099CA**	**1T7100CA**	**1T7101CA**	**1T7102CA**
●	**1T7111CA**	**1T7112CA**	**1T7113CA**	**1T7114CA**

LED / 2,1W / LENS / SP / FIXED DIGITAL DIMMING



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	3W	1	0.20	2505
Source Flux	197lm	2	0.40	626
Fixture Flux	154lm	3	0.60	278
Efficacy	55lm/W	4	0.79	157
Imax	2505cd	5	0.99	100

TS 1122 Imax=12713cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7099DD**	**1T7100DD**	**1T7101DD**	**1T7102DD**
●	**1T7111DD**	**1T7112DD**	**1T7113DD**	**1T7114DD**

LED / 2,1W / LENS / FL / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			28°	
Fixture Power	3W	1	0.51	497
Source Flux	197lm	2	1.01	124
Fixture Flux	148lm	3	1.52	55
Efficacy	43lm/W	4	2.02	31
Imax	497cd	5	2.53	20

TS1123 Imax=2525cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7510**	**1T7511**	**1T7512**	**1T7513**
●	**1T7522**	**1T7523**	**1T7524**	**1T7525**

LED / 2,1W / LENS / FL / FIXED CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			28°	
Fixture Power	3W	1	0.51	497
Source Flux	197lm	2	1.01	124
Fixture Flux	148lm	3	1.52	55
Efficacy	53lm/W	4	2.02	31
Imax	497cd	5	2.53	20

TS 1123 Imax=2525cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7103CA**	**1T7104CA**	**1T7105CA**	**1T7106CA**
●	**1T7115CA**	**1T7116CA**	**1T7117CA**	**1T7118CA**

OZ

LED / 2,1W / LENS / FL / FIXED DIGITAL DIMMING



3000K		H(m)	D(m)	Emax(lx)
Ra90			28°	
Fixture Power	3W	1	0.51	497
Source Flux	197lm	2	1.01	124
Fixture Flux	148lm	3	1.52	55
Efficacy	53lm/W	4	2.02	31
TS 1123 Imax=2525cd/klm	Imax	497cd	5	2.53	20

Colour	2700K	3000K	3500K	4000K
○	**1T7103DD**	**1T7104DD**	**1T7105DD**	**1T7106DD**
●	**1T7115DD**	**1T7116DD**	**1T7117DD**	**1T7118DD**

LED / 2,1W / LENS / MWFL / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	3W	1	0.75	256
Source Flux	197lm	2	1.50	64
Fixture Flux	142lm	3	2.26	28
Efficacy	42lm/W	4	3.01	16
TS1124 Imax=1300cd/klm	Imax	256cd	5	3.76	10

Colour	2700K	3000K	3500K	4000K
○	**1T7514**	**1T7515**	**1T7516**	**1T7517**
●	**1T7526**	**1T7527**	**1T7528**	**1T7529**

LED / 2,1W / LENS / MWFL / FIXED CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	3W	1	0.75	256
Source Flux	197lm	2	1.50	64
Fixture Flux	142lm	3	2.26	28
Efficacy	51lm/W	4	3.01	16
TS 1124 Imax=1300cd/klm	Imax	256cd	5	3.76	10

Colour	2700K	3000K	3500K	4000K
○	**1T7107CA**	**1T7108CA**	**1T7109CA**	**1T7110CA**
●	**1T7119CA**	**1T7120CA**	**1T7121CA**	**1T7122CA**

LED / 2,1W / LENS / MWFL / FIXED DIGITAL DIMMING



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	3W	1	0.75	256
Source Flux	197lm	2	1.50	64
Fixture Flux	142lm	3	2.26	28
Efficacy	51lm/W	4	3.01	16
TS 1124 Imax=1300cd/klm	Imax	256cd	5	3.76	10

Colour	2700K	3000K	3500K	4000K
○	**1T7107DD**	**1T7108DD**	**1T7109DD**	**1T7110DD**
●	**1T7119DD**	**1T7120DD**	**1T7121DD**	**1T7122DD**

LED / 2,6W / LENS / SP / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	4W	1	0.20	3000
Source Flux	236lm	2	0.40	750
Fixture Flux	184lm	3	0.60	333
Efficacy	44lm/W	4	0.79	188
TS 1122 Imax=12713cd/klm	Imax	3000cd	5	0.99	120

Colour	2700K	3000K	3500K	4000K
○	**1T7099**	**1T7100**	**1T7101**	**1T7102**
●	**1T7111**	**1T7112**	**1T7113**	**1T7114**

LED / 2,6W / LENS / FL / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			28°	
Fixture Power	4W	1	0.51	596
Source Flux	236lm	2	1.01	149
Fixture Flux	177lm	3	1.52	66
Efficacy	42lm/W	4	2.02	37
TS 1123 Imax=2525cd/klm	Imax	596cd	5	2.53	24

Colour	2700K	3000K	3500K	4000K
○	**1T7103**	**1T7104**	**1T7105**	**1T7106**
●	**1T7115**	**1T7116**	**1T7117**	**1T7118**

OZ

LED / 2,6W / LENS / MWFL / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	4W	1	0.75	307
Source Flux	236lm	2	1.50	77
Fixture Flux	170lm	3	2.26	34
Efficacy	41lm/W	4	3.01	19
Imax	307cd	5	3.76	12

TS 1124 Imax=1300cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7107**	**1T7108**	**1T7109**	**1T7110**
●	**1T7119**	**1T7120**	**1T7121**	**1T7122**

LED / 2,1W / DBS / SP-MWFL / FIXED CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			16°	
Fixture Power	3W	1	0.28	1684
Source Flux	236lm	2	0.56	421
Fixture Flux	175lm	3	0.84	187
Efficacy	63lm/W	4	1.12	105
Imax	1684cd	5	1.40	67

TS1283 Imax=7134cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra90			35°	
Fixture Power	3W	1	0.62	283
Source Flux	236lm	2	1.24	71
Fixture Flux	156lm	3	1.86	31
Efficacy	56lm/W	4	2.49	18
Imax	283cd	5	3.11	11

TS1284 Imax=1198cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7965CA**	**1T7961CA**	**1T7969CA**	**1T7973CA**
●	**1T7949CA**	**1T7945CA**	**1T7953CA**	**1T7957CA**

Lighting module - Single adjustable 25x25mm



LED / 2,1W / LENS / SP / ADJUSTABLE



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	3W	1	0.20	2505
Source Flux	197lm	2	0.40	626
Fixture Flux	154lm	3	0.60	278
Efficacy	45lm/W	4	0.79	157
Imax	2505cd	5	0.99	100

TS1122 Imax=12713cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7530**	**1T7531**	**1T7532**	**1T7533**
●	**1T7542**	**1T7543**	**1T7544**	**1T7545**

LED / 2,1W / LENS / SP / ADJUSTABLE CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	3W	1	0.20	2505
Source Flux	197lm	2	0.40	626
Fixture Flux	154lm	3	0.60	278
Efficacy	55lm/W	4	0.79	157
Imax	2505cd	5	0.99	100

TS 1122 Imax=12713cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7123CA**	**1T7124CA**	**1T7125CA**	**1T7126CA**
●	**1T7135CA**	**1T7136CA**	**1T7137CA**	**1T7138CA**

LED / 2,1W / LENS / SP / ADJUSTABLE DIGITAL DIMMING



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	3W	1	0.20	2505
Source Flux	197lm	2	0.40	626
Fixture Flux	154lm	3	0.60	278
Efficacy	55lm/W	4	0.79	157
Imax	2505cd	5	0.99	100

TS 1122 Imax=12713cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7123DD**	**1T7124DD**	**1T7125DD**	**1T7126DD**
●	**1T7135DD**	**1T7136DD**	**1T7137DD**	**1T7138DD**

OZ

LED / 2,1W / LENS / FL / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			28°	
Fixture Power	3W	1		0.51	497
Source Flux	197lm	2		1.01	124
Fixture Flux	148lm	3		1.52	55
Efficacy	43lm/W	4		2.02	31
TS1123 Imax=2525cd/klm	Imax	497cd	5	2.53	20

Colour	2700K	3000K	3500K	4000K
○	**1T7534**	**1T7535**	**1T7536**	**1T7537**
●	**1T7546**	**1T7547**	**1T7548**	**1T7549**

LED / 2,1W / LENS / FL / ADJUSTABLE CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			28°	
Fixture Power	3W	1		0.51	497
Source Flux	197lm	2		1.01	124
Fixture Flux	148lm	3		1.52	55
Efficacy	53lm/W	4		2.02	31
TS 1123 Imax=2525cd/klm	Imax	497cd	5	2.53	20

Colour	2700K	3000K	3500K	4000K
○	**1T7127CA**	**1T7128CA**	**1T7129CA**	**1T7130CA**
●	**1T7139CA**	**1T7140CA**	**1T7141CA**	**1T7142CA**

LED / 2,1W / LENS / FL / ADJUSTABLE DIGITAL DIMMING



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			28°	
Fixture Power	3W	1		0.51	497
Source Flux	197lm	2		1.01	124
Fixture Flux	148lm	3		1.52	55
Efficacy	53lm/W	4		2.02	31
TS 1123 Imax=2525cd/klm	Imax	497cd	5	2.53	20

Colour	2700K	3000K	3500K	4000K
○	**1T7127DD**	**1T7128DD**	**1T7129DD**	**1T7130DD**
●	**1T7139DD**	**1T7140DD**	**1T7141DD**	**1T7142DD**

LED / 2,1W / LENS / MWFL / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power	3W	1		0.75	256
Source Flux	197lm	2		1.50	64
Fixture Flux	142lm	3		2.26	28
Efficacy	42lm/W	4		3.01	16
TS1124 Imax=1300cd/klm	Imax	256cd	5	3.76	10

Colour	2700K	3000K	3500K	4000K
○	**1T7538**	**1T7539**	**1T7540**	**1T7541**
●	**1T7550**	**1T7551**	**1T7552**	**1T7553**

LED / 2,1W / LENS / MWFL / ADJUSTABLE CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power	3W	1		0.75	256
Source Flux	197lm	2		1.50	64
Fixture Flux	142lm	3		2.26	28
Efficacy	51lm/W	4		3.01	16
TS 1124 Imax=1300cd/klm	Imax	256cd	5	3.76	10

Colour	2700K	3000K	3500K	4000K
○	**1T7131CA**	**1T7132CA**	**1T7133CA**	**1T7134CA**
●	**1T7143CA**	**1T7144CA**	**1T7145CA**	**1T7146CA**

LED / 2,1W / LENS / MWFL / ADJUSTABLE DIGITAL DIMMING



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power	3W	1		0.75	256
Source Flux	197lm	2		1.50	64
Fixture Flux	142lm	3		2.26	28
Efficacy	51lm/W	4		3.01	16
TS 1124 Imax=1300cd/klm	Imax	256cd	5	3.76	10

Colour	2700K	3000K	3500K	4000K
○	**1T7131DD**	**1T7132DD**	**1T7133DD**	**1T7134DD**
●	**1T7143DD**	**1T7144DD**	**1T7145DD**	**1T7146DD**

OZ

LED / 2,6W / LENS / SP / ADJUSTABLE



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	4W	1	0.20	3000
Source Flux	236lm	2	0.40	750
Fixture Flux	184lm	3	0.60	333
Efficacy	44lm/W	4	0.79	188
Imax	3000cd	5	0.99	120

TS 1122 Imax=12713cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7123**	**1T7124**	**1T7125**	**1T7126**
●	**1T7135**	**1T7136**	**1T7137**	**1T7138**

LED / 2,6W / LENS / FL / ADJUSTABLE



3000K		H(m)	D(m)	Emax(lx)
Ra90			28°	
Fixture Power	4W	1	0.51	596
Source Flux	236lm	2	1.01	149
Fixture Flux	177lm	3	1.52	66
Efficacy	42lm/W	4	2.02	37
Imax	596cd	5	2.53	24

TS 1123 Imax=2525cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7127**	**1T7128**	**1T7129**	**1T7130**
●	**1T7139**	**1T7140**	**1T7141**	**1T7142**

LED / 2,6W / LENS / MWFL / ADJUSTABLE



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	4W	1	0.75	307
Source Flux	236lm	2	1.50	77
Fixture Flux	170lm	3	2.26	34
Efficacy	41lm/W	4	3.01	19
Imax	307cd	5	3.76	12

TS 1124 Imax=1300cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7131**	**1T7132**	**1T7133**	**1T7134**
●	**1T7143**	**1T7144**	**1T7145**	**1T7146**

LED / 2,1W / DBS / SP-MWFL / ADJUSTABLE CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			16°	
Fixture Power	3W	1	0.28	1684
Source Flux	236lm	2	0.56	421
Fixture Flux	175lm	3	0.84	187
Efficacy	63lm/W	4	1.12	105
Imax	1684cd	5	1.40	67

TS1285 Imax=7134cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra90			35°	
Fixture Power	3W	1	0.62	283
Source Flux	236lm	2	1.24	71
Fixture Flux	156lm	3	1.86	31
Efficacy	56lm/W	4	2.49	18
Imax	283cd	5	3.11	11

TS1286 Imax=1198cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7967CA**	**1T7963CA**	**1T7971CA**	**1T7975CA**
●	**1T7951CA**	**1T7947CA**	**1T7955CA**	**1T7959CA**

Lighting module - Single fixed 50x50mm



LED / 6,8W / REFLECTOR / SP / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	8W	1	0.34	3911
Source Flux	846lm	2	0.68	978
Fixture Flux	691lm	3	1.02	435
Efficacy	87lm/W	4	1.36	244
Imax	3911cd	5	1.70	156

TS1125 Imax=4623cd/klm

Colour	2700K	3000K	3500K	4000K
○	**1T7554**	**1T7555**	**1T7556**	**1T7557**
●	**1T7566**	**1T7567**	**1T7568**	**1T7569**

OZ

LED / 6,8W / REFLECTOR / SP / FIXED CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		8W	1	0.34	3911
Source Flux		846lm	2	0.68	978
Fixture Flux		691lm	3	1.02	435
Efficacy		91lm/W	4	1.36	244
Imax		3911cd	5	1.70	156

Colour	2700K	3000K	3500K	4000K
○	**1T7147CA**	**1T7148CA**	**1T7149CA**	**1T7150CA**
●	**1T7159CA**	**1T7160CA**	**1T7161CA**	**1T7162CA**

LED / 6,8W / REFLECTOR / SP / FIXED DIGITAL DIMMING



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		8W	1	0.34	3911
Source Flux		846lm	2	0.68	978
Fixture Flux		691lm	3	1.02	435
Efficacy		91lm/W	4	1.36	244
Imax		3911cd	5	1.70	156

Colour	2700K	3000K	3500K	4000K
○	**1T7147DD**	**1T7148DD**	**1T7149DD**	**1T7150DD**
●	**1T7159DD**	**1T7160DD**	**1T7161DD**	**1T7162DD**

LED / 7,6W / REFLECTOR / FL / FIXED



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.49	2359
Source Flux		963lm	2	0.98	590
Fixture Flux		720lm	3	1.47	262
Efficacy		82lm/W	4	1.95	147
Imax		2359cd	5	2.44	94

Colour	2700K	3000K	3500K	4000K
○	**1T7558**	**1T7559**	**1T7560**	**1T7561**
●	**1T7570**	**1T7571**	**1T7572**	**1T7573**

LED / 7,6W / REFLECTOR / FL / FIXED CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.49	2359
Source Flux		963lm	2	0.98	590
Fixture Flux		720lm	3	1.47	262
Efficacy		85lm/W	4	1.95	147
Imax		2359cd	5	2.44	94

Colour	2700K	3000K	3500K	4000K
○	**1T7151CA**	**1T7152CA**	**1T7153CA**	**1T7154CA**
●	**1T7163CA**	**1T7164CA**	**1T7165CA**	**1T7166CA**

LED / 7,6W / REFLECTOR / FL / FIXED DIGITAL DIMMING



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.49	2359
Source Flux		963lm	2	0.98	590
Fixture Flux		720lm	3	1.47	262
Efficacy		85lm/W	4	1.95	147
Imax		2359cd	5	2.44	94

Colour	2700K	3000K	3500K	4000K
○	**1T7151DD**	**1T7152DD**	**1T7153DD**	**1T7154DD**
●	**1T7163DD**	**1T7164DD**	**1T7165DD**	**1T7166DD**

LED / 7,6W / REFLECTOR / MWFL / FIXED



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			37°	
Fixture Power		9W	1	0.66	1826
Source Flux		963lm	2	1.32	457
Fixture Flux		794lm	3	1.98	203
Efficacy		90lm/W	4	2.64	114
Imax		1826cd	5	3.31	73

Colour	2700K	3000K	3500K	4000K
○	**1T7562**	**1T7563**	**1T7564**	**1T7565**
●	**1T7574**	**1T7575**	**1T7576**	**1T7577**

OZ

LED / 7,6W / REFLECTOR / MWFL / FIXED CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			37°	
Fixture Power	9W	1	0.66	1826
Source Flux	963lm	2	1.32	457
Fixture Flux	794lm	3	1.98	203
Efficacy	93lm/W	4	2.64	114
TS 1127 Imax=1896cd/klm	Imax	1826cd	5	3.31	73

Colour	2700K	3000K	3500K	4000K
○	**1T7155CA**	**1T7156CA**	**1T7157CA**	**1T7158CA**
●	**1T7167CA**	**1T7168CA**	**1T7169CA**	**1T7170CA**

LED / 7,6W / REFLECTOR / MWFL / FIXED DIGITAL DIMMING



3000K		H(m)	D(m)	Emax(lx)
Ra90			37°	
Fixture Power	9W	1	0.66	1826
Source Flux	963lm	2	1.32	457
Fixture Flux	794lm	3	1.98	203
Efficacy	93lm/W	4	2.64	114
TS 1127 Imax=1896cd/klm	Imax	1826cd	5	3.31	73

Colour	2700K	3000K	3500K	4000K
○	**1T7155DD**	**1T7156DD**	**1T7157DD**	**1T7158DD**
●	**1T7167DD**	**1T7168DD**	**1T7169DD**	**1T7170DD**

LED / 7,5W / REFLECTOR / SP / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	9W	1	0.34	4752
Source Flux	1028lm	2	0.68	1188
Fixture Flux	840lm	3	1.02	528
Efficacy	97lm/W	4	1.36	297
TS 1125 Imax=4623cd/klm	Imax	4752cd	5	1.70	190

Colour	2700K	3000K	3500K	4000K
○	**1T7147**	**1T7148**	**1T7149**	**1T7150**
●	**1T7159**	**1T7160**	**1T7161**	**1T7162**

LED / 8,3W / REFLECTOR / FL / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			27°	
Fixture Power	10W	1	0.49	2896
Source Flux	1182lm	2	0.98	724
Fixture Flux	884lm	3	1.47	322
Efficacy	92lm/W	4	1.95	181
TS 1126 Imax=2450cd/klm	Imax	2896cd	5	2.44	116

Colour	2700K	3000K	3500K	4000K
○	**1T7151**	**1T7152**	**1T7153**	**1T7154**
●	**1T7163**	**1T7164**	**1T7165**	**1T7166**

LED / 8,3W / REFLECTOR / MWFL / FIXED



3000K		H(m)	D(m)	Emax(lx)
Ra90			37°	
Fixture Power	10W	1	0.66	2241
Source Flux	1182lm	2	1.32	560
Fixture Flux	974lm	3	1.98	249
Efficacy	101lm/W	4	2.64	140
TS 1127 Imax=1896cd/klm	Imax	2241cd	5	3.31	90

Colour	2700K	3000K	3500K	4000K
○	**1T7155**	**1T7156**	**1T7157**	**1T7158**
●	**1T7167**	**1T7168**	**1T7169**	**1T7170**

LED / 6,8W / DBS / SP-MWFL / FIXED CASAMBI



3000K		H(m)	D(m)	Emax(lx)
Ra90			22°	
Fixture Power	8W	1	0.39	2576
Source Flux	846lm	2	0.78	644
Fixture Flux	621lm	3	1.17	286
Efficacy	82lm/W	4	1.56	161
TS1287 Imax=3045cd/klm	Imax	2576cd	5	1.95	103



3000K		H(m)	D(m)	Emax(lx)
Ra90			46°	
Fixture Power	8W	1	0.84	770
Source Flux	846lm	2	1.69	193
Fixture Flux	591lm	3	2.53	86
Efficacy	78lm/W	4	3.37	48
TS1288 Imax=910cd/klm	Imax	770cd	5	4.21	31

Colour	2700K	3000K	3500K	4000K
○	**1T7966CA**	**1T7962CA**	**1T7970CA**	**1T7974CA**
●	**1T7950CA**	**1T7946CA**	**1T7954CA**	**1T7958CA**



Lighting module - Single adjustable 50x50mm



LED / 6,8W / REFLECTOR / SP / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		8W	1	0.34	3911
Source Flux		846lm	2	0.68	978
Fixture Flux		691lm	3	1.02	435
Efficacy		87lm/W	4	1.36	244
TS1125	Imax=4623cd/klm	Imax	3911cd	5	1.70	156

Colour	2700K	3000K	3500K	4000K
○	**1T7578**	**1T7579**	**1T7580**	**1T7581**
●	**1T7590**	**1T7591**	**1T7592**	**1T7593**

LED / 6,8W / REFLECTOR / SP / ADJUSTABLE CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		8W	1	0.34	3911
Source Flux		846lm	2	0.68	978
Fixture Flux		691lm	3	1.02	435
Efficacy		91lm/W	4	1.36	244
TS1171	Imax=4623cd/klm	Imax	3911cd	5	1.70	156

Colour	2700K	3000K	3500K	4000K
○	**1T7407CA**	**1T7408CA**	**1T7409CA**	**1T7410CA**
●	**1T7419CA**	**1T7420CA**	**1T7421CA**	**1T7422CA**

LED / 6,8W / REFLECTOR / SP / ADJUSTABLE DIGITAL DIMMING



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		8W	1	0.34	3911
Source Flux		846lm	2	0.68	978
Fixture Flux		691lm	3	1.02	435
Efficacy		91lm/W	4	1.36	244
TS1171	Imax=4623cd/klm	Imax	3911cd	5	1.70	156

Colour	2700K	3000K	3500K	4000K
○	**1T7407DD**	**1T7408DD**	**1T7409DD**	**1T7410DD**
●	**1T7419DD**	**1T7420DD**	**1T7421DD**	**1T7422DD**

LED / 7,6W / REFLECTOR / FL / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.49	2359
Source Flux		963lm	2	0.98	590
Fixture Flux		720lm	3	1.47	262
Efficacy		82lm/W	4	1.95	147
TS1126	Imax=2450cd/klm	Imax	2359cd	5	2.44	94

Colour	2700K	3000K	3500K	4000K
○	**1T7582**	**1T7583**	**1T7584**	**1T7585**
●	**1T7594**	**1T7595**	**1T7596**	**1T7597**

LED / 7,6W / REFLECTOR / FL / ADJUSTABLE CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.49	2359
Source Flux		963lm	2	0.98	590
Fixture Flux		720lm	3	1.47	262
Efficacy		85lm/W	4	1.95	147
TS1172	Imax=2450cd/klm	Imax	2359cd	5	2.44	94

Colour	2700K	3000K	3500K	4000K
○	**1T7411CA**	**1T7412CA**	**1T7413CA**	**1T7414CA**
●	**1T7423CA**	**1T7424CA**	**1T7425CA**	**1T7426CA**

OZ

LED / 7,6W / REFLECTOR / FL / ADJUSTABLE DIGITAL DIMMING



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power	9W	1		0.49	2359
Source Flux	963lm	2		0.98	590
Fixture Flux	720lm	3		1.47	262
Efficacy	85lm/W	4		1.95	147
TS1172 Imax=2450cd/klm	Imax	2359cd	5	2.44	94

Colour	2700K	3000K	3500K	4000K
○	**1T7411DD**	**1T7412DD**	**1T7413DD**	**1T7414DD**
●	**1T7423DD**	**1T7424DD**	**1T7425DD**	**1T7426DD**

LED / 7,6W / REFLECTOR / MWFL / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			37°	
Fixture Power	9W	1		0.66	1826
Source Flux	963lm	2		1.32	457
Fixture Flux	794lm	3		1.98	203
Efficacy	90lm/W	4		2.64	114
TS1127 Imax=1896cd/klm	Imax	1826cd	5	3.31	73

Colour	2700K	3000K	3500K	4000K
○	**1T7586**	**1T7587**	**1T7588**	**1T7589**
●	**1T7598**	**1T7599**	**1T7600**	**1T7601**

LED / 7,6W / REFLECTOR / MWFL / ADJUSTABLE CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			37°	
Fixture Power	9W	1		0.66	1826
Source Flux	963lm	2		1.32	457
Fixture Flux	794lm	3		1.98	203
Efficacy	93lm/W	4		2.64	114
TS1173 Imax=1896cd/klm	Imax	1826cd	5	3.31	73

Colour	2700K	3000K	3500K	4000K
○	**1T7415CA**	**1T7416CA**	**1T7417CA**	**1T7418CA**
●	**1T7427CA**	**1T7428CA**	**1T7429CA**	**1T7430CA**

LED / 7,6W / REFLECTOR / MWFL / ADJUSTABLE DIGITAL DIMMING



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			37°	
Fixture Power	9W	1		0.66	1826
Source Flux	963lm	2		1.32	457
Fixture Flux	794lm	3		1.98	203
Efficacy	93lm/W	4		2.64	114
TS1173 Imax=1896cd/klm	Imax	1826cd	5	3.31	73

Colour	2700K	3000K	3500K	4000K
○	**1T7415DD**	**1T7416DD**	**1T7417DD**	**1T7418DD**
●	**1T7427DD**	**1T7428DD**	**1T7429DD**	**1T7430DD**

LED / 7,5W / REFLECTOR / SP / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power	9W	1		0.34	4752
Source Flux	1028lm	2		0.68	1188
Fixture Flux	840lm	3		1.02	528
Efficacy	97lm/W	4		1.36	297
TS1171 Imax=4623cd/klm	Imax	4752cd	5	1.70	190

Colour	2700K	3000K	3500K	4000K
○	**1T7407**	**1T7408**	**1T7409**	**1T7410**
●	**1T7419**	**1T7420**	**1T7421**	**1T7422**

LED / 8,3W / REFLECTOR / FL / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power	10W	1		0.49	2896
Source Flux	1182lm	2		0.98	724
Fixture Flux	884lm	3		1.47	322
Efficacy	92lm/W	4		1.95	181
TS1172 Imax=2450cd/klm	Imax	2896cd	5	2.44	116

Colour	2700K	3000K	3500K	4000K
○	**1T7411**	**1T7412**	**1T7413**	**1T7414**
●	**1T7423**	**1T7424**	**1T7425**	**1T7426**

OZ

LED / 8,3W / REFLECTOR / MWFL / ADJUSTABLE



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			37°	
Fixture Power		10W	1	0.66	2241
Source Flux		1182lm	2	1.32	560
Fixture Flux		974lm	3	1.98	249
Efficacy		101lm/W	4	2.64	140
TS1173	Imax=1896cd/klm	Imax	2241cd	5	3.31	90

Colour	2700K	3000K	3500K	4000K
○	**1T7415**	**1T7416**	**1T7417**	**1T7418**
◐	**1T7427**	**1T7428**	**1T7429**	**1T7430**

LED / 6,8W / DBS / SP-MWFL / ADJUSTABLE CASAMBI



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			22°	
Fixture Power		8W	1	0.39	2576
Source Flux		846lm	2	0.78	644
Fixture Flux		621lm	3	1.17	286
Efficacy		82lm/W	4	1.56	161
TS1289	Imax=3045cd/klm	Imax	2576cd	5	1.95	103



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			46°	
Fixture Power		8W	1	0.84	770
Source Flux		846lm	2	1.69	193
Fixture Flux		591lm	3	2.53	86
Efficacy		78lm/W	4	3.37	48
TS1290	Imax=910cd/klm	Imax	770cd	5	4.21	31

Colour	2700K	3000K	3500K	4000K
○	**1T7968CA**	**1T7964CA**	**1T7972CA**	**1T7976CA**
◐	**1T7952CA**	**1T7948CA**	**1T7956CA**	**1T7960CA**

Lighting module - Multiple Small 5X (25x125mm)



LED / 8,7W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
Fixture Power		13W	1	0.20	10018
Source Flux		788lm	2	0.40	2505
Fixture Flux		615lm	3	0.60	1113
Efficacy		47lm/W	4	0.79	626
TS1122	Imax=12713cd/klm	Imax	10018cd	5	0.99	401

Version	Colour	2700K	3000K	3500K	4000K
5X	○	**1T7441**	**1T7442**	**1T7443**	**1T7444**
5X	●	**1T7453**	**1T7454**	**1T7455**	**1T7456**
5X CASAMBI	○	**1T7441CA**	**1T7442CA**	**1T7443CA**	**1T7444CA**
5X CASAMBI	●	**1T7453CA**	**1T7454CA**	**1T7455CA**	**1T7456CA**
5X DIGITAL DIMMING	○	**1T7441DD**	**1T7442DD**	**1T7443DD**	**1T7444DD**
5X DIGITAL DIMMING	●	**1T7453DD**	**1T7454DD**	**1T7455DD**	**1T7456DD**

LED / 8,7W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			28°	
Fixture Power		13W	1	0.51	1990
Source Flux		788lm	2	1.01	497
Fixture Flux		590lm	3	1.52	221
Efficacy		45lm/W	4	2.02	124
TS1123	Imax=2525cd/klm	Imax	1990cd	5	2.53	80

Version	Colour	2700K	3000K	3500K	4000K
5X	○	**1T7445**	**1T7446**	**1T7447**	**1T7448**
5X	●	**1T7457**	**1T7458**	**1T7459**	**1T7460**
5X CASAMBI	○	**1T7445CA**	**1T7446CA**	**1T7447CA**	**1T7448CA**
5X CASAMBI	●	**1T7457CA**	**1T7458CA**	**1T7459CA**	**1T7460CA**
5X DIGITAL DIMMING	○	**1T7445DD**	**1T7446DD**	**1T7447DD**	**1T7448DD**
5X DIGITAL DIMMING	●	**1T7457DD**	**1T7458DD**	**1T7459DD**	**1T7460DD**

LED / 8,7W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power		13W	1	0.75	1024
Source Flux		788lm	2	1.50	256
Fixture Flux		569lm	3	2.26	114
Efficacy		44lm/W	4	3.01	64
TS1124	Imax=1300cd/klm	Imax	1024cd	5	3.76	41

Version	Colour	2700K	3000K	3500K	4000K
5X	○	**1T7449**	**1T7450**	**1T7451**	**1T7452**
5X	●	**1T7461**	**1T7462**	**1T7463**	**1T7464**
5X CASAMBI	○	**1T7449CA**	**1T7450CA**	**1T7451CA**	**1T7452CA**
5X CASAMBI	●	**1T7461CA**	**1T7462CA**	**1T7463CA**	**1T7464CA**
5X DIGITAL DIMMING	○	**1T7449DD**	**1T7450DD**	**1T7451DD**	**1T7452DD**
5X DIGITAL DIMMING	●	**1T7461DD**	**1T7462DD**	**1T7463DD**	**1T7464DD**

Lighting module - Multiple Large 3X (50x150mm)



LED / 21W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power		24W	1	0.34	11732
Source Flux		2538lm	2	0.68	2933
Fixture Flux		2074lm	3	1.02	1304
Efficacy		86lm/W	4	1.36	733
TS1125	Imax=4623cd/klm	Imax	11732cd	5	1.70	469

Version	Colour	2700K	3000K	3500K	4000K
3X	○	**1T7465**	**1T7466**	**1T7467**	**1T7468**
3X	●	**1T7477**	**1T7478**	**1T7479**	**1T7480**
3X CASAMBI	○	**1T7465CA**	**1T7466CA**	**1T7467CA**	**1T7468CA**
3X CASAMBI	●	**1T7477CA**	**1T7478CA**	**1T7479CA**	**1T7480CA**
3X DIGITAL DIMMING	○	**1T7465DD**	**1T7466DD**	**1T7467DD**	**1T7468DD**
3X DIGITAL DIMMING	●	**1T7477DD**	**1T7478DD**	**1T7479DD**	**1T7480DD**

OZ

LED / 23W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		25W	1	0.49	7077
Source Flux		2889lm	2	0.98	1769
Fixture Flux		2161lm	3	1.47	786
Efficacy		86lm/W	4	1.95	442
TS1126	Imax=2450cd/klm	Imax	7077cd	5	2.44	283

Version	Colour	2700K	3000K	3500K	4000K
3X	○	**1T7469**	**1T7470**	**1T7471**	**1T7472**
3X	◐	**1T7481**	**1T7482**	**1T7483**	**1T7484**
3X CASAMBI	○	**1T7469CA**	**1T7470CA**	**1T7471CA**	**1T7472CA**
3X CASAMBI	◐	**1T7481CA**	**1T7482CA**	**1T7483CA**	**1T7484CA**
3X DIGITAL DIMMING	○	**1T7469DD**	**1T7470DD**	**1T7471DD**	**1T7472DD**
3X DIGITAL DIMMING	◐	**1T7481DD**	**1T7482DD**	**1T7483DD**	**1T7484DD**

LED / 23W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			37°	
Fixture Power		25W	1	0.66	5478
Source Flux		2889lm	2	1.32	1370
Fixture Flux		2381lm	3	1.98	609
Efficacy		95lm/W	4	2.64	342
TS1127	Imax=1896cd/klm	Imax	5478cd	5	3.31	219

Version	Colour	2700K	3000K	3500K	4000K
3X	○	**1T7473**	**1T7474**	**1T7475**	**1T7476**
3X	◐	**1T7485**	**1T7486**	**1T7487**	**1T7488**
3X CASAMBI	○	**1T7473CA**	**1T7474CA**	**1T7475CA**	**1T7476CA**
3X CASAMBI	◐	**1T7485CA**	**1T7486CA**	**1T7487CA**	**1T7488CA**
3X DIGITAL DIMMING	○	**1T7473DD**	**1T7474DD**	**1T7475DD**	**1T7476DD**
3X DIGITAL DIMMING	◐	**1T7485DD**	**1T7486DD**	**1T7487DD**	**1T7488DD**



Lighting module - Linear



LED / 12W / OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra90			108°	
Fixture Power	13W	1	2.74	350
Source Flux	1452lm	2	5.48	88
Fixture Flux	953lm	3	8.23	39
Efficacy	71lm/W	4	10.97	22
Imax	350cd	5	13.71	14

TS1264 Imax=241cd/klm

Power supply	Version	Colour	2700K	3000K	3500K	4000K
48Vdc	STANDARD	○	**1T8190**	**1T8191**	**1T8192**	**1T8193**
48Vdc	STANDARD	◐	**1T8194**	**1T8195**	**1T8196**	**1T8197**
48Vdc	CASAMBI	○	**1T8190CA**	**1T8191CA**	**1T8192CA**	**1T8193CA**
48Vdc	CASAMBI	◐	**1T8194CA**	**1T8195CA**	**1T8196CA**	**1T8197CA**



Lighting module - Linear



LED / 18W / OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra90			108°	
Fixture Power	20W	1	2.74	526
Source Flux	2178lm	2	5.48	131
Fixture Flux	1429lm	3	8.23	58
Efficacy	73lm/W	4	10.97	33
Imax	526cd	5	13.71	21

TS1263 Imax=241cd/klm

Power supply	Version	Colour	2700K	3000K	3500K	4000K
48Vdc	STANDARD	○	**1T8198**	**1T8199**	**1T8200**	**1T8201**
48Vdc	STANDARD	◐	**1T8202**	**1T8203**	**1T8204**	**1T8205**
48Vdc	CASAMBI	○	**1T8198CA**	**1T8199CA**	**1T8200CA**	**1T8201CA**
48Vdc	CASAMBI	◐	**1T8202CA**	**1T8203CA**	**1T8204CA**	**1T8205CA**

Recessed profile for Power Track



HEAD MODULE

Recessed profile for Power Track.
Extruded painted aluminium profile.
For trimless installation or with a flange.
To be completed with Power Track.

Kg	L	Colour	Code
0.4	1015	○	**1T7495**
0.8	2015	○	**1T7496**
1.2	3015	○	**1T7497**
0.4	1015	◐	**1T7498**
0.8	2015	◐	**1T7499**
1.2	3015	◐	**1T7500**

CENTRAL/END MODULE

Recessed profile for Power Track.
Extruded painted aluminium profile.
For trimless installation or with a flange.
To be completed with Power Track.

Kg	L	Colour	Code
0.4	1000	○	**1T7489**
0.8	2000	○	**1T7490**
1.2	3000	○	**1T7491**
0.4	1000	◐	**1T7492**
0.8	2000	◐	**1T7493**
1.2	3000	◐	**1T7494**

Related codes

Mounting System

Code	
1T7501	Steel bracket for Power Track built-in installation. 2 pieces to be ordered for 1m long modules, 3 pieces for 2m long modules and 4 pieces for 3m long modules.

Recessed profile Small



FOR 25x25mm LIGHT MODULES

Extruded painted aluminium profile.
For trimless installation or with a flange.
To be completed with Power Track.

Kg	L	Colour	Code
1.1	1000	○	**1T7031**
2.2	2000	○	**1T7032**
3.3	3000	○	**1T7033**
1.1	1000	●	**1T7034**
2.2	2000	●	**1T7035**
3.3	3000	●	**1T7036**

Recessed profile Large



FOR 50x50mm LIGHT MODULES

Extruded painted aluminium profile.
For trimless installation or with a flange.
To be completed with Power Track.

Kg	L	Colour	Code
1.2	1000	○	**1T7067**
2.5	2000	○	**1T7068**
3.7	3000	○	**1T7069**
1.2	1000	●	**1T7070**
2.5	2000	●	**1T7071**
3.7	3000	●	**1T7072**

Related codes

Mounting System

Code
1T7043

Steel bracket for recessed installation of the small profile.
2 pieces to be ordered for 1m long modules, 3 pieces for 2m long modules and 4 pieces for 3m long modules.

Code
1T7076

Steel bracket for recessed installation of the large profile.
2 pieces to be ordered for 1m long modules, 3 pieces for 2m long modules and 4 pieces for 3m long modules.

OZ

End Caps



Colour	Code
○	**1T7039**
●	**1T7040**

Kit containing 2 profile end caps.
For small recessed profiles.



Colour	Code
○	**1T7073**
◐	**1T7074**

Kit containing 2 profile end caps.
For large recessed profiles.

Accessories

Mechanical connector



Code
1T7041

Kit composed of 2 mechanical linear joints and 4 thrust screws.
For trimless installation profile.



Colour	Code
○	**1T7037**
◐	**1T7038**

Mechanical L connector.
For small recessed profiles.





Colour	Code
○	**1T7437**
●	**1T7438**

Mechanical L connector.
For large recessed profiles.

Ceiling/Suspension installation profile Small



FOR 25x25mm LIGHT MODULES - HEAD MODULE

Extruded painted aluminium profile.
For stand-alone installation only used head modules.
For system installation it is necessary to start the configuration with a head module.
For closed configurations it is necessary to order a minimum of two head modules or multiples of two to install back to back.
To be completed with Power Track.

Kg	L	Colour	Code
0.8	1015	○	**1T7050**
1.7	2015	○	**1T7051**
2.6	3015	○	**1T7052**
0.8	1015	●	**1T7053**
1.7	2015	●	**1T7054**
2.6	3015	●	**1T7055**

FOR 25x25mm LIGHT MODULES - CENTRAL/END MODULE

Extruded painted aluminium profile.
For stand-alone installation only used head modules.
For system installation it is necessary to start the configuration with a head module.
For closed configurations it is necessary to order a minimum of two head modules or multiples of two to install back to back.
To be completed with Power Track.

Kg	L	Colour	Code
0.8	1000	○	**1T7044**
1.7	2000	○	**1T7045**
2.6	3000	○	**1T7046**
0.8	1000	●	**1T7047**
1.7	2000	●	**1T7048**
2.6	3000	●	**1T7049**

Ceiling/Suspension installation profile Large



FOR 50x50mm LIGHT MODULES - HEAD MODULE

Extruded painted aluminium profile.
For stand-alone installation only used head modules.
For system installation it is necessary to start the configuration with a head module.
For closed configurations it is necessary to order a minimum of two head modules or multiples of two to install back to back.
To be completed with Power Track.

Kg	L	Colour	Code
1	1015	○	**1T7083**
2.1	2015	○	**1T7084**
3.1	3015	○	**1T7085**
1	1015	●	**1T7086**
2.1	2015	●	**1T7087**
3.1	3015	●	**1T7088**

OZ

FOR 50x50mm LIGHT MODULES - CENTRAL/END MODULE

Extruded painted aluminium profile.
For stand-alone installation only used head modules.
For system installation it is necessary to start the configuration with a head module.
For closed configurations it is necessary to order a minimum of two head modules or multiples of two to install back to back.
To be completed with Power Track.

	Kg	L	Colour	Code
	1	1000	○	**1T7077**
	2.1	2000	○	**1T7078**
	3.1	3000	○	**1T7079**
	1	1000	◐	**1T7080**
	2.1	2000	◐	**1T7081**
	3.1	3000	◐	**1T7082**

Related codes

End Caps

	Colour	Code
	○	**1T7062**
	◐	**1T7063**

Kit containing 2 profile end caps.
For small ceiling/suspension mounted profiles.

	Colour	Code
	○	**1T7095**
	◐	**1T7096**

Kit containing 2 profile end caps.
For large ceiling/suspension mounted profiles.

Mounting System

	Code
	1T7065

Ceiling installation kit.
2 pieces to be ordered for 1m long modules, 2 pieces for 2m long modules and 3 pieces for 3m long modules.

	Code
	1T7066

Suspension installation kit.
2 pieces to be ordered for 1m long modules, 2 pieces for 2m long modules and 3 pieces for 3m long modules.

Accessories

Mechanical connector





	Colour	Code
	○	**1T7056**
	◐	**1T7059**

Mechanical L connector.
For small ceiling/suspension mounted profiles.





	Colour	Code
	○	**1T7089**
	◐	**1T7092**

Mechanical L connector.
For large ceiling/suspension mounted profiles.

OZ



Colour	Code
○	**1T7057**
●	**1T7060**

Mechanical T connector.
For small ceiling/suspension mounted profiles.





Colour	Code
○	**1T7090**
◐	**1T7093**

Mechanical T connector.
For large ceiling/suspension mounted profiles.



Colour	Code
○	**1T7058**
●	**1T7061**

Mechanical X connector.
For small ceiling/suspension mounted profiles.





Colour	Code
○	**1T7091**
◐	**1T7094**

Mechanical X connector.
For large ceiling/suspension mounted profiles.



Colour	Code
○	**1T7064**
●	**1T7097**

Kit composed of 2 mechanical linear joints and 8 thrust screws.
For ceiling/suspension installation profile.

Cover Panel

L	Colour	Code
1000	○	**1T9595**
2000	○	**1T9596**
1000	●	**1T9597**
2000	●	**1T9598**

Cover for small profiles for ceiling/suspension installation.

L	Colour	Code
1000	○	**1T9599**
2000	○	**1T9600**
1000	◐	**1T9601**
2000	◐	**1T9602**

Cover for large profiles for ceiling/suspension installation.

OZ

Ceiling installation
Power track



Power Track
1T7431 / 1T7432 / 1T7433
1T7434 / 1T7435 / 1T7436

Recessed installation
Power Track + Profile

Recessed profile for Power Track





Power Track
1T7431 / 1T7432 / 1T7433
1T7434 / 1T7435 / 1T7436

Small Profile
1T7031 / 1T7032 / 1T7033
1T7034 / 1T7035 / 1T7036

Large Profile
1T7067 / 1T7068 / 1T7069
1T7070 / 1T7071 / 1T7072

Recessed profile





Power Track
1T7431 / 1T7432 / 1T7433
1T7434 / 1T7435 / 1T7436

1T7495 / 1T7496 / 1T7497
1T7498 / 1T7499 / 1T7500
1T7489 / 1T7490 / 1T7491
1T7492 / 1T7493 / 1T7494

OZ

Ceiling / Suspension installation
Power Track + Profile



Small Profile
1T7050 / 1T7051 / 1T7052
1T7053 / 1T7054 / 1T7055
1T7044 / 1T7045 / 1T7046
1T7047 / 1T7048 / 1T7049

Large Profile
1T7083 / 1T7084 / 1T7085
1T7086 / 1T7087 / 1T7088
1T7077 / 1T7078 / 1T7079
1T7080 / 1T7081 / 1T7082

Power Track
1T7431 / 1T7432 / 1T7433
1T7434 / 1T7435 / 1T7436



1T7065



1T7066

Installation constraints
OZ Lighting module – Single





OZ Lighting module – Multiple





OZ Lighting module – Linear





FORTYEIGHT

GENERAL INFO

Track
A modular system with variable lengths to be equipped with projectors and linear light fixtures. The geometry of the track varies on the type of installation (suspension, ceiling or recessed).

Label
Projectors for track installation available in a double version with a short and long bracket depending on the type of installation selected.
Ø23mm – Ø40mm – Ø59mm – Ø74mm

Logico 30
Low voltage linear LED fixture for track installation.
Lenghts: 294mm – 573mm – 1132mm – 1970mm
L Module: 310x310

LED

Label 4 and 6: Chip on board Ra90
Label 2: LED emitter Ra90
From 171lm to 2799lm
2700K – 3000K – 4000K
Logico 30: Linear boards Ra90
From 750lm to 5600lm
3000K – 4000K

PRODUCT EFFICACY

Label: up to 107lm/W
Logico 30: up to 77 lm/W

OPTICS

Label: SP – FL – MWFL
Logico 30: Opal

POWER SUPPLY

Electronic – DALI
Casambi control system as an accessory (only for DALI versions).

MATERIAL

Label: Painted extruded aluminium body.
Logico 30: Painted extruded aluminium body

ON DEMAND

Easy Custom Colour

110-277 vac power supply (Label 7)

3500K

2700K (Logico 30)

A 48V system that can be recessed or deep recessed both with a trimless finish, ceiling or wall and suspension mounted. It can be fitted at any point with linear lighting fixtures due to its simple mechanical fixing system.

The depth of the track is extremely compact: 25mm or 53mm. The new track with a H" section - has a depth of around 29mm.

The deep recessed version - trimless deep - must be equipped with Label projectors with long brackets.

		Label 2	Label 4	Label 6	Label 7	Logico 30
		Ø 23mm	Ø 40mm	Ø 59mm	Ø 74mm	
LED	Flux (lm)	171-195	912-1147	1404-1821	2490-2799	750-5600
	Power	2,6W	8W	14W-15W	21W	6W-42W
OPTICS						
SP	Lens	•		•	•	
	Reflector		•	•	•	
FL	Lens	•		•	•	
	Reflector		•	•	•	
MWFL	Lens	•		•	•	
	Reflector		•	•	•	
OPAL	Reflector + screen					•

Bally
Milan, Italy

Lighting design Ing. Angelo Iorio,
U&Me Consulting



Light units

Label



Label 7 – Ø74mm

- short arm
- long arm

Label 6 – Ø59mm

- short arm
- long arm

Label 4 – Ø40mm

- short arm
- long arm



Label 2 – Ø23mm

- short arm
- long arm

Logico 30



L=294mm/573mm/
1132mm/1970mm

310x310mm

Electrical elements

Electrical connectors

Throug joint

L shaped connector



Flexible connector

Power head

Remote driver

60W • 130W • 210W

Power head



Track

H section*

L=1/2/3m

* To be completed with special end caps

Trimless*



L=1/2/3m

Trimless deep*



L=1/2/3m

Installation solutions

H section track



Ceiling



Suspension

Trimless track



Recessed

Trimless deep track



Recessed

Plus

There are two recessed versions both with a trimless finish:

- Simple recessed with a flush system and protruding fixtures
- Deep recessed completely hidden in the ceiling with linear light elements. For this version the projectors have a longer bracket to allow for maximum extraction and adjustability.

Wall mounted installation
For effective easy lighting for example in retail spaces such as shop windows.



Logico 30

Linear modules complete with opaline screens
For a soft and diffused lighting effect equipped with LED 3000K and 4000K sources with Ra90.

The system can be configured in various ways
Thanks to the use of linear joints and the new corner joints that make it possible to create closed and open loops. Available a new corner light module for lines of seamless light.

Optic system with lense

Optic system with reflector

Label 48V

48V projectors available in four sizes

Carefully studied for professional applications in the museum, retail, interior and hotel sectors 48V Label projectors have a simple, essential shape and an extremely compact size. Available in four different sizes all versions have a remote power supply to reduce visual impact to the minimum. Label 2 (Ø23mm), Label 4 (Ø40mm) Label 6 (Ø59mm) and the new Label 7 Ø74mm) are equipped with Ra90 with 2700K, 3000K and 4000K colour temperatures.

Double optical systems

Label 6 and the new Label 7 can be equipped with two different optical systems: with a reflector for soft effects with low visual contrast or with lenses for more defined beams.

Label 2
Ø23mm

Label 4
Ø40mm

Label 6
Ø59mm

Label 7
Ø74mm

Label 2

The miniature projector in the Label range has a diameter of just 23mm and provides professional performance with an absorption of 4W. Available with three different optical systems equipped with lenses for the SP - FL - MWFL versions with both long and short arms.

FORTYEIGHT



Track H-shaped section ceiling/suspension



H-SHAPED SECTION

	Kg	L	Colour	Code
	0.7	1000	○	**9500-1/W2-ST6-E**
	1.4	2000	○	**9500-2/W2-ST6-E**
	2.1	3000	○	**9500-3/W2-ST6-E**
	0.7	1000	●	**9500-1/B-ST6-E**
	1.4	2000	●	**9500-2/B-ST6-E**
	2.1	3000	●	**9500-3/B-ST6-E**



Track trimless - recessed



TRIMLESS

	Kg	L	Colour	Code
	1.1	1000	○	**9500-1/W2-ST3-E**
	2.2	2000	○	**9500-2/W2-ST3-E**
	3.4	3000	○	**9500-3/W2-ST3-E**
	1.1	1000	●	**9500-1/B-ST3-E**
	2.2	2000	●	**9500-2/B-ST3-E**
	3.4	3000	●	**9500-3/B-ST3-E**



Track trimless deep - recessed



TRIMLESS DEEP

	Kg	L	Colour	Code
	1.6	1000	○	**9500-1/W2-TA1**
	3.2	2000	○	**9500-2/W2-TA1**
	4.8	3000	○	**9500-3/W2-TA1**
	1.6	1000	●	**9500-1/B-TA1**
	3.2	2000	●	**9500-2/B-TA1**
	4.8	3000	●	**9500-3/B-TA1**

Related codes

End Caps

Colour	Code
○	**9504/ST3-W2**
●	**9504/ST3-B**

End cap for Trimless track.
1X

Colour	Code
○	**1T7171**
◐	**1T6801**

End cap for Trimless Deep track.
2X

Colour	Code
○	**9504/ST6-W2**
●	**9504/ST6-B**

End cap for H section track.
1X

Colour	Code
○	**9504/ST6-W2-F**
◐	**9504/ST6-B-F**

End cap for H section track with a cable feed through hole.
1X

Mounting System



Colour	Code
◍	**1T9581**

Suspension installation kit with ABS adjustment on the fixture for H section track.



Colour	Code
◍	**1T9582**

Suspension kit with ceiling adjustment for H section track.

Code
1T9583

Kit composed of 4 lateral brackets and 2 stiffening brackets for the Trimless Deep track version.

Code
1T9584

Kit composed of 4 lateral brackets for the Trimless track version.

Colour	Code
○	**S-9500/114-W2**
●	**S-9500/114-B**

Clip for fixing to the ceiling.
For H section track.

FORTYEIGHT

Power Supply



Dimensions LxHxP	W	IP	Code
225x36x60	60W	IP20	**1T6917EL**
240x49x60	130W	IP20	**1T6916EL**
251x90x37	210W	IP20	**1T7403EL**

48Vdc electronic driver.
1T6917EL - Single power supply for Electronic, DALI and Casambi systems. Maximum distance 20m - cable 1.5mm².
1T6916EL - Single power supply for Electronic, DALI and Casambi systems. Maximum distance 10m - cable 1.5mm².
1T7403EL - Universal power supply (110-277V) for Electronic, DALI and Casambi systems. Maximum distance 5m - cable 1.5mm².



Colour	Code
○	**9501-S/W-E**
◐	**9501-S/B-E**

Power head unpolarised.

Accessories

Mechanical connector

Colour	Code
○	**S-9500/314-W2**
●	**S-9500/314-B**

Supporting bracket for direct connection for trimless and trimless deep applications.

Tool

Code
S-9000/T

Tool for shearing conductors, to be used if necessary to cut the track during installation.

Electrical Connector



Colour	Code
○	**9511/W-E**
●	**9511/B-E**

Unpolarised L joint for trimless and trimless deep versions and a H section.
For recessed installation the tracks must first be cut to 45°.



Colour	Code
○	**9503-S/W-E**
◐	**9503-S/B-E**

Unpolarised through joint.



Colour	Code
○	**9518-S/W-E**
●	**9518-S/B-E**

Non polarised flexible connector.

FORTYEIGHT

Mechanical connector



	Colour	Code
	○	**S-9511/W2-ST6**
	●	**S-9511/B-ST6**

Cover for L connector for H section track.

Control systems

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

FORTYEIGHT

Logico 30 L. 294mm



LED / 6W / OPAL



	Power supply	Version	Colour	3000K	4000K
	48Vdc	EL.	○	**1T6619EL**	**1T6620EL**
	48Vdc	EL.	●	**1T6621EL**	**1T6622EL**
	48Vdc	DALI	○	**1T6619DA**	**1T6620DA**
	48Vdc	DALI	●	**1T6621DA**	**1T6622DA**

Logico 30 L. 573mm



LED / 12W / OPAL



	Power supply	Version	Colour	3000K	4000K
	48Vdc	EL.	○	**1T6623EL**	**1T6624EL**
	48Vdc	EL.	●	**1T6625EL**	**1T6626EL**
	48Vdc	DALI	○	**1T6623DA**	**1T6624DA**
	48Vdc	DALI	●	**1T6625DA**	**1T6626DA**

Logico 30 L. 1132mm



LED / 24W / OPAL



	Power supply	Version	Colour	3000K	4000K
	48Vdc	EL.	○	**1T6627EL**	**1T6628EL**
	48Vdc	EL.	●	**1T6629EL**	**1T6630EL**
	48Vdc	DALI	○	**1T6627DA**	**1T6628DA**
	48Vdc	DALI	●	**1T6629DA**	**1T6630DA**

FORTYEIGHT

Logico 30 L. 1970mm



LED / 42W / OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra90			107°	
Fixture Power	46W	1	2.70	1242
Source Flux	5250lm	2	5.41	311
Fixture Flux	3269lm	3	8.11	138
Efficacy	71lm/W	4	10.81	78
TS1075 Imax=237cd/klm	Imax	1242cd	5	13.52	50

	Power supply	Version	Colour	3000K	4000K
	48Vdc	EL.	○	**1T6631EL**	**1T6632EL**
	48Vdc	EL.	◐	**1T6633EL**	**1T6634EL**
	48Vdc	DALI	○	**1T6631DA**	**1T6632DA**
	48Vdc	DALI	◐	**1T6633DA**	**1T6634DA**

Logico 30 L light module



LED / 12W / OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra90			107°	
Fixture Power	13W	1	2.70	355
Source Flux	1500lm	2	5.41	89
Fixture Flux	934lm	3	8.11	39
Efficacy	72lm/W	4	10.81	22
TS1075 Imax=237cd/klm	Imax	355cd	5	13.52	14

	Power supply	Version	Colour	3000K	4000K
	48Vdc	EL.	○	**1T6635EL**	**1T6636EL**
	48Vdc	EL.	◐	**1T6637EL**	**1T6638EL**
	48Vdc	DALI	○	**1T6635DA**	**1T6636DA**
	48Vdc	DALI	◐	**1T6637DA**	**1T6638DA**

FORTYEIGHT

Label 7 short arm



LED / 21W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			21°	
Fixture Power		23W	1	0.37	10611
Source Flux		2756lm	2	0.75	2653
Fixture Flux		1962lm	3	1.12	1179
Efficacy		85lm/W	4	1.50	663
TS1240	Imax=3850cd/klm	Imax	10611cd	5	1.87	424

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8049EL**	**1T8050EL**	**1T8051EL**
48Vdc	EL.	●	**1T8052EL**	**1T8053EL**	**1T8054EL**
48Vdc	DALI	○	**1T8049DA**	**1T8050DA**	**1T8051DA**
48Vdc	DALI	●	**1T8052DA**	**1T8053DA**	**1T8054DA**

LED / 21W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			33°	
Fixture Power		23W	1	0.59	5989
Source Flux		2756lm	2	1.18	1497
Fixture Flux		2031lm	3	1.77	665
Efficacy		88lm/W	4	2.36	374
TS1241	Imax=2173cd/klm	Imax	5989cd	5	2.95	240

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8055EL**	**1T8056EL**	**1T8057EL**
48Vdc	EL.	●	**1T8058EL**	**1T8059EL**	**1T8060EL**
48Vdc	DALI	○	**1T8055DA**	**1T8056DA**	**1T8057DA**
48Vdc	DALI	●	**1T8058DA**	**1T8059DA**	**1T8060DA**

LED / 21W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra97			46°	
Fixture Power		23W	1	0.85	3831
Source Flux		2756lm	2	1.69	958
Fixture Flux		2076lm	3	2.54	426
Efficacy		90lm/W	4	3.39	239
TS1242	Imax=1390cd/klm	Imax	3832cd	5	4.23	153

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8061EL**	**1T8062EL**	**1T8063EL**
48Vdc	EL.	●	**1T8064EL**	**1T8065EL**	**1T8066EL**
48Vdc	DALI	○	**1T8061DA**	**1T8062DA**	**1T8063DA**
48Vdc	DALI	●	**1T8064DA**	**1T8065DA**	**1T8066DA**

LED / 21W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			17°	
Fixture Power		23W	1	0.30	19631
Source Flux		2591lm	2	0.60	4908
Fixture Flux		2161lm	3	0.90	2181
Efficacy		94lm/W	4	1.19	1227
TS1260	Imax=7577cd/klm	Imax	19631cd	5	1.49	785

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8067EL**	**1T8068EL**	**1T8069EL**
48Vdc	EL.	●	**1T8070EL**	**1T8071EL**	**1T8072EL**
48Vdc	DALI	○	**1T8067DA**	**1T8068DA**	**1T8069DA**
48Vdc	DALI	●	**1T8070DA**	**1T8071DA**	**1T8072DA**

LED / 21W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		23W	1	0.47	8565
Source Flux		2591lm	2	0.94	2141
Fixture Flux		2112lm	3	1.41	952
Efficacy		92lm/W	4	1.88	535
TS1261	Imax=3306cd/klm	Imax	8565cd	5	2.35	343

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8073EL**	**1T8074EL**	**1T8075EL**
48Vdc	EL.	●	**1T8076EL**	**1T8077EL**	**1T8078EL**
48Vdc	DALI	○	**1T8073DA**	**1T8074DA**	**1T8075DA**
48Vdc	DALI	●	**1T8076DA**	**1T8077DA**	**1T8078DA**

FORTYEIGHT

LED / 21W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			41°	
Fixture Power	23W	1	0.75	4115
Source Flux	2591lm	2	1.49	1029
Fixture Flux	2016lm	3	2.24	457
Efficacy	88lm/W	4	2.99	257
Imax	4204cd	5	3.73	165

TS1262 Imax=1623cd/klm

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8079EL**	**1T8080EL**	**1T8081EL**
48Vdc	EL.	●	**1T8082EL**	**1T8083EL**	**1T8084EL**
48Vdc	DALI	○	**1T8079DA**	**1T8080DA**	**1T8081DA**
48Vdc	DALI	●	**1T8082DA**	**1T8083DA**	**1T8084DA**

Label 7 long arm



LED / 21W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			21°	
Fixture Power	23W	1	0.37	10611
Source Flux	2756lm	2	0.75	2653
Fixture Flux	1962lm	3	1.12	1179
Efficacy	85lm/W	4	1.50	663
Imax	10611cd	5	1.87	424

TS1240 Imax=3850cd/klm

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8100EL**	**1T8101EL**	**1T8102EL**
48Vdc	EL.	●	**1T8103EL**	**1T8104EL**	**1T8105EL**
48Vdc	DALI	○	**1T8100DA**	**1T8101DA**	**1T8102DA**
48Vdc	DALI	●	**1T8103DA**	**1T8104DA**	**1T8105DA**

LED / 21W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			33°	
Fixture Power	23W	1	0.59	5989
Source Flux	2756lm	2	1.18	1497
Fixture Flux	2031lm	3	1.77	665
Efficacy	88lm/W	4	2.36	374
Imax	5989cd	5	2.95	240

TS1241 Imax=2173cd/klm

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8106EL**	**1T8107EL**	**1T8108EL**
48Vdc	EL.	●	**1T8109EL**	**1T8110EL**	**1T8111EL**
48Vdc	DALI	○	**1T8106DA**	**1T8107DA**	**1T8108DA**
48Vdc	DALI	●	**1T8109DA**	**1T8110DA**	**1T8111DA**

LED / 21W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra97			46°	
Fixture Power	23W	1	0.85	3831
Source Flux	2756lm	2	1.69	958
Fixture Flux	2076lm	3	2.54	426
Efficacy	90lm/W	4	3.39	239
Imax	3832cd	5	4.23	153

TS1242 Imax=1390cd/klm

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8112EL**	**1T8113EL**	**1T8114EL**
48Vdc	EL.	●	**1T8115EL**	**1T8116EL**	**1T8117EL**
48Vdc	DALI	○	**1T8112DA**	**1T8113DA**	**1T8114DA**
48Vdc	DALI	●	**1T8115DA**	**1T8116DA**	**1T8117DA**

LED / 21W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			17°	
Fixture Power	23W	1	0.30	19631
Source Flux	2591lm	2	0.60	4908
Fixture Flux	2161lm	3	0.90	2181
Efficacy	94lm/W	4	1.19	1227
Imax	19631cd	5	1.49	785

TS1260 Imax=7577cd/klm

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8118EL**	**1T8119EL**	**1T8120EL**
48Vdc	EL.	●	**1T8121EL**	**1T8122EL**	**1T8123EL**
48Vdc	DALI	○	**1T8118DA**	**1T8119DA**	**1T8120DA**
48Vdc	DALI	●	**1T8121DA**	**1T8122DA**	**1T8123DA**

FORTYEIGHT

LED / 21W / LENS / FL



Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8124EL**	**1T8125EL**	**1T8126EL**
48Vdc	EL.	●	**1T8127EL**	**1T8128EL**	**1T8129EL**
48Vdc	DALI	○	**1T8124DA**	**1T8125DA**	**1T8126DA**
48Vdc	DALI	●	**1T8127DA**	**1T8128DA**	**1T8129DA**

LED / 21W / LENS / MWFL



Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T8130EL**	**1T8131EL**	**1T8132EL**
48Vdc	EL.	●	**1T8133EL**	**1T8134EL**	**1T8135EL**
48Vdc	DALI	○	**1T8130DA**	**1T8131DA**	**1T8132DA**
48Vdc	DALI	●	**1T8133DA**	**1T8134DA**	**1T8135DA**

Accessories

Grid



Ø	Code
63	**1T8093**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

Filter



Ø	Code
63	**1T8094**

Holographic PMMA filter with blade of light effect.
Allows the beam to be made oval; combined with spot and flood optics the effect appears more pronounced.

FORTYEIGHT

Label 6 short arm



LED / 14W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power		15W	1	0.28	10741
Source Flux		1793lm	2	0.55	2685
Fixture Flux		1316lm	3	0.83	1193
Efficacy		91lm/W	4	1.11	671
TS1068	Imax=5990cd/klm	Imax	10741cd	5	1.39	430

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6675EL**	**1T6676EL**	**1T6677EL**
48Vdc	EL.	●	**1T6678EL**	**1T6679EL**	**1T6680EL**
48Vdc	DALI	○	**1T6675DA**	**1T6676DA**	**1T6677DA**
48Vdc	DALI	●	**1T6678DA**	**1T6679DA**	**1T6680DA**

LED / 14W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power		15W	1	0.56	4410
Source Flux		1793lm	2	1.12	1102
Fixture Flux		1386lm	3	1.67	490
Efficacy		96lm/W	4	2.23	276
TS1069	Imax=2460cd/klm	Imax	4410cd	5	2.79	176

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6681EL**	**1T6682EL**	**1T6683EL**
48Vdc	EL.	●	**1T6684EL**	**1T6685EL**	**1T6686EL**
48Vdc	DALI	○	**1T6681DA**	**1T6682DA**	**1T6683DA**
48Vdc	DALI	●	**1T6684DA**	**1T6685DA**	**1T6686DA**

LED / 14W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power		15W	1	0.88	2457
Source Flux		1793lm	2	1.77	614
Fixture Flux		1373lm	3	2.65	273
Efficacy		95lm/W	4	3.53	154
TS1070	Imax=1378cd/klm	Imax	2471cd	5	4.41	98

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6687EL**	**1T6688EL**	**1T6689EL**
48Vdc	EL.	●	**1T6690EL**	**1T6691EL**	**1T6692EL**
48Vdc	DALI	○	**1T6687DA**	**1T6688DA**	**1T6689DA**
48Vdc	DALI	●	**1T6690DA**	**1T6691DA**	**1T6692DA**

LED / 15W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
Fixture Power		16W	1	0.25	15429
Source Flux		1512lm	2	0.49	3857
Fixture Flux		1244lm	3	0.74	1714
Efficacy		78lm/W	4	0.99	964
TS1293	Imax=10204cd/klm	Imax	15429cd	5	1.23	617

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T9046EL**	**1T9047EL**	**1T9048EL**
48Vdc	EL.	●	**1T9049EL**	**1T9050EL**	**1T9051EL**
48Vdc	DALI	○	**1T9046DA**	**1T9047DA**	**1T9048DA**
48Vdc	DALI	●	**1T9049DA**	**1T9050DA**	**1T9051DA**

LED / 14W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		15W	1	0.47	6254
Source Flux		1793lm	2	0.94	1563
Fixture Flux		1535lm	3	1.40	695
Efficacy		102lm/W	4	1.87	391
TS1291	Imax=3488cd/klm	Imax	6254cd	5	2.34	250

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T9052EL**	**1T9053EL**	**1T9054EL**
48Vdc	EL.	●	**1T9055EL**	**1T9056EL**	**1T9057EL**
48Vdc	DALI	○	**1T9052DA**	**1T9053DA**	**1T9054DA**
48Vdc	DALI	●	**1T9055DA**	**1T9056DA**	**1T9057DA**

FORTYEIGHT

LED / 14W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power	15W		1	0.75	3104
Source Flux	1793lm		2	1.50	776
Fixture Flux	1535lm		3	2.24	345
Efficacy	102lm/W		4	2.99	194
TS1292	Imax=1767cd/klm	Imax	5	3.74	124

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T9058EL**	**1T9059EL**	**1T9060EL**
48Vdc	EL.	●	**1T9061EL**	**1T9062EL**	**1T9063EL**
48Vdc	DALI	○	**1T9058DA**	**1T9059DA**	**1T9060DA**
48Vdc	DALI	●	**1T9061DA**	**1T9062DA**	**1T9063DA**

Label 6 long arm



LED / 14W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power	15W		1	0.28	10741
Source Flux	1793lm		2	0.55	2685
Fixture Flux	1316lm		3	0.83	1193
Efficacy	91lm/W		4	1.11	671
TS1068	Imax=5990cd/klm	Imax	5	1.39	430

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6729EL**	**1T6730EL**	**1T6731EL**
48Vdc	EL.	●	**1T6732EL**	**1T6733EL**	**1T6734EL**
48Vdc	DALI	○	**1T6729DA**	**1T6730DA**	**1T6731DA**
48Vdc	DALI	●	**1T6732DA**	**1T6733DA**	**1T6734DA**

LED / 14W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power	15W		1	0.56	4410
Source Flux	1793lm		2	1.12	1102
Fixture Flux	1386lm		3	1.67	490
Efficacy	96lm/W		4	2.23	276
TS1069	Imax=2460cd/klm	Imax	5	2.79	176

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6735EL**	**1T6736EL**	**1T6737EL**
48Vdc	EL.	●	**1T6738EL**	**1T6739EL**	**1T6740EL**
48Vdc	DALI	○	**1T6735DA**	**1T6736DA**	**1T6737DA**
48Vdc	DALI	●	**1T6738DA**	**1T6739DA**	**1T6740DA**

LED / 14W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power	15W		1	0.88	2457
Source Flux	1793lm		2	1.77	614
Fixture Flux	1373lm		3	2.65	273
Efficacy	95lm/W		4	3.53	154
TS1070	Imax=1378cd/klm	Imax	5	4.41	98

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6741EL**	**1T6742EL**	**1T6743EL**
48Vdc	EL.	●	**1T6744EL**	**1T6745EL**	**1T6746EL**
48Vdc	DALI	○	**1T6741DA**	**1T6742DA**	**1T6743DA**
48Vdc	DALI	●	**1T6744DA**	**1T6745DA**	**1T6746DA**

LED / 15W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			14°	
Fixture Power	16W		1	0.25	15429
Source Flux	1512lm		2	0.49	3857
Fixture Flux	1244lm		3	0.74	1714
Efficacy	78lm/W		4	0.99	964
TS1293	Imax=10204cd/klm	Imax	5	1.23	617

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T9064EL**	**1T9065EL**	**1T9066EL**
48Vdc	EL.	●	**1T9067EL**	**1T9068EL**	**1T9069EL**
48Vdc	DALI	○	**1T9064DA**	**1T9065DA**	**1T9066DA**
48Vdc	DALI	●	**1T9067DA**	**1T9068DA**	**1T9069DA**

FORTYEIGHT

LED / 14W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			26°	
Fixture Power		15W	1	0.47	6254
Source Flux		1793lm	2	0.94	1563
Fixture Flux		1535lm	3	1.40	695
Efficacy		102lm/W	4	1.87	391
Imax		6254cd	5	2.34	250

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T9070EL**	**1T9071EL**	**1T9072EL**
48Vdc	EL.	●	**1T9073EL**	**1T9074EL**	**1T9075EL**
48Vdc	DALI	○	**1T9070DA**	**1T9071DA**	**1T9072DA**
48Vdc	DALI	●	**1T9073DA**	**1T9074DA**	**1T9075DA**

LED / 14W / LENS / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			41°	
Fixture Power		15W	1	0.75	3104
Source Flux		1793lm	2	1.50	776
Fixture Flux		1535lm	3	2.24	345
Efficacy		102lm/W	4	2.99	194
Imax		3169cd	5	3.74	124

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T9076EL**	**1T9077EL**	**1T9078EL**
48Vdc	EL.	●	**1T9079EL**	**1T9080EL**	**1T9081EL**
48Vdc	DALI	○	**1T9076DA**	**1T9077DA**	**1T9078DA**
48Vdc	DALI	●	**1T9079DA**	**1T9080DA**	**1T9081DA**

Accessories

Filter



Ø	Code
50	**1T4721**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Grid



Ø	Code
50	**1T4322**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

FORTYEIGHT

Label 4 short arm



LED / 8W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power		9W	1	0.31	4214
Source Flux		982lm	2	0.62	1053
Fixture Flux		622lm	3	0.93	468
Efficacy		71lm/W	4	1.24	263
TS1072	Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6657EL**	**1T6658EL**	**1T6659EL**
48Vdc	EL.	●	**1T6660EL**	**1T6661EL**	**1T6662EL**
48Vdc	DALI	○	**1T6657DA**	**1T6658DA**	**1T6659DA**
48Vdc	DALI	●	**1T6660DA**	**1T6661DA**	**1T6662DA**

LED / 8W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.48	3199
Source Flux		1129lm	2	0.95	800
Fixture Flux		806lm	3	1.43	355
Efficacy		92lm/W	4	1.91	200
TS1073	Imax=2834cd/klm	Imax	3199cd	5	2.38	128

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6663EL**	**1T6664EL**	**1T6665EL**
48Vdc	EL.	●	**1T6666EL**	**1T6667EL**	**1T6668EL**
48Vdc	DALI	○	**1T6663DA**	**1T6664DA**	**1T6665DA**
48Vdc	DALI	●	**1T6666DA**	**1T6667DA**	**1T6668DA**

LED / 8W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power		9W	1	0.76	1831
Source Flux		1129lm	2	1.52	458
Fixture Flux		835lm	3	2.28	203
Efficacy		95lm/W	4	3.04	114
TS1074	Imax=1622cd/klm	Imax	1831cd	5	3.80	73

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6669EL**	**1T6670EL**	**1T6671EL**
48Vdc	EL.	●	**1T6672EL**	**1T6673EL**	**1T6674EL**
48Vdc	DALI	○	**1T6669DA**	**1T6670DA**	**1T6671DA**
48Vdc	DALI	●	**1T6672DA**	**1T6673DA**	**1T6674DA**

Label 4 long arm



LED / 8W / REFLECTOR / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power		9W	1	0.31	4214
Source Flux		982lm	2	0.62	1053
Fixture Flux		622lm	3	0.93	468
Efficacy		71lm/W	4	1.24	263
TS1072	Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6711EL**	**1T6712EL**	**1T6713EL**
48Vdc	EL.	●	**1T6714EL**	**1T6715EL**	**1T6716EL**
48Vdc	DALI	○	**1T6711DA**	**1T6712DA**	**1T6713DA**
48Vdc	DALI	●	**1T6714DA**	**1T6715DA**	**1T6716DA**

FORTYEIGHT

LED / 8W / REFLECTOR / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.48	3199
Source Flux		1129lm	2	0.95	800
Fixture Flux		806lm	3	1.43	355
Efficacy		92lm/W	4	1.91	200
Imax		3199cd	5	2.38	128

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6717EL**	**1T6718EL**	**1T6719EL**
48Vdc	EL.	●	**1T6720EL**	**1T6721EL**	**1T6722EL**
48Vdc	DALI	○	**1T6717DA**	**1T6718DA**	**1T6719DA**
48Vdc	DALI	●	**1T6720DA**	**1T6721DA**	**1T6722DA**

LED / 8W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power		9W	1	0.76	1831
Source Flux		1129lm	2	1.52	458
Fixture Flux		835lm	3	2.28	203
Efficacy		95lm/W	4	3.04	114
Imax		1831cd	5	3.80	73

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6723EL**	**1T6724EL**	**1T6725EL**
48Vdc	EL.	●	**1T6726EL**	**1T6727EL**	**1T6728EL**
48Vdc	DALI	○	**1T6723DA**	**1T6724DA**	**1T6725DA**
48Vdc	DALI	●	**1T6726DA**	**1T6727DA**	**1T6728DA**

Accessories

Filter



Ø	Code
34	**1T6931**

PMMA holographic filter with blade effect to ovalize the light beam; more evident when combined with spot and flood optics.

Grid



Ø	Code
34	**1T6930**

Anti-glare louver.
Black painted metal honeycomb structure.
Complete with holographic diffusion filter.

FORTYEIGHT

Label 2 short arm



LED / 2,6W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			13°	
Fixture Power	4W	1	0.23	1419
Source Flux	180lm	2	0.45	355
Fixture Flux	152lm	3	0.68	158
Efficacy	40lm/W	4	0.90	89
Imax	1419cd	5	1.13	57

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6639EL**	**1T6640EL**	**1T6641EL**
48Vdc	EL.	●	**1T6642EL**	**1T6643EL**	**1T6644EL**
48Vdc	DALI	○	**1T6639DA**	**1T6640DA**	**1T6641DA**
48Vdc	DALI	●	**1T6642DA**	**1T6643DA**	**1T6644DA**

LED / 2,6W / LENS / FL

3000K		H(m)	D(m)	Emax(lx)
Ra90			31°	
Fixture Power	4W	1	0.55	346
Source Flux	180lm	2	1.10	87
Fixture Flux	136lm	3	1.65	38
Efficacy	36lm/W	4	2.19	22
Imax	346cd	5	2.74	14

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6645EL**	**1T6646EL**	**1T6647EL**
48Vdc	EL.	●	**1T6648EL**	**1T6649EL**	**1T6650EL**
48Vdc	DALI	○	**1T6645DA**	**1T6646DA**	**1T6647DA**
48Vdc	DALI	●	**1T6648DA**	**1T6649DA**	**1T6650DA**

LED / 2,6W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	4W	1	0.90	177
Source Flux	180lm	2	1.81	44
Fixture Flux	131lm	3	2.71	20
Efficacy	34lm/W	4	3.62	11
Imax	177cd	5	4.52	7

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6651EL**	**1T6652EL**	**1T6653EL**
48Vdc	EL.	●	**1T6654EL**	**1T6655EL**	**1T6656EL**
48Vdc	DALI	○	**1T6651DA**	**1T6652DA**	**1T6653DA**
48Vdc	DALI	●	**1T6654DA**	**1T6655DA**	**1T6656DA**

Label 2 long arm



LED / 2,6W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			13°	
Fixture Power	4W	1	0.23	1419
Source Flux	180lm	2	0.45	355
Fixture Flux	152lm	3	0.68	158
Efficacy	40lm/W	4	0.90	89
Imax	1419cd	5	1.13	57

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6693EL**	**1T6694EL**	**1T6695EL**
48Vdc	EL.	●	**1T6696EL**	**1T6697EL**	**1T6698EL**
48Vdc	DALI	○	**1T6693DA**	**1T6694DA**	**1T6695DA**
48Vdc	DALI	●	**1T6696DA**	**1T6697DA**	**1T6698DA**

FORTYEIGHT

LED / 2,6W / LENS / FL

3000K		H(m)	D(m)	Emax(lx)
Ra90			31°	
Fixture Power	4W	1	0.55	346
Source Flux	180lm	2	1.10	87
Fixture Flux	136lm	3	1.65	38
Efficacy	36lm/W	4	2.19	22
TS1158 Imax=1920cd/klm	Imax	346cd	5	2.74	14

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6699EL**	**1T6700EL**	**1T6701EL**
48Vdc	EL.	●	**1T6702EL**	**1T6703EL**	**1T6704EL**
48Vdc	DALI	○	**1T6699DA**	**1T6700DA**	**1T6701DA**
48Vdc	DALI	●	**1T6702DA**	**1T6703DA**	**1T6704DA**

LED / 2,6W / LENS / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	4W	1	0.90	177
Source Flux	180lm	2	1.81	44
Fixture Flux	131lm	3	2.71	20
Efficacy	34lm/W	4	3.62	11
TS1159 Imax=983cd/klm	Imax	177cd	5	4.52	7

Power supply	Version	Colour	2700K	3000K	4000K
48Vdc	EL.	○	**1T6705EL**	**1T6706EL**	**1T6707EL**
48Vdc	EL.	●	**1T6708EL**	**1T6709EL**	**1T6710EL**
48Vdc	DALI	○	**1T6705DA**	**1T6706DA**	**1T6707DA**
48Vdc	DALI	●	**1T6708DA**	**1T6709DA**	**1T6710DA**

Accessories

Filter

	Ø	Code
	17	**1T6939**

Holographic PMMA filter with blade of light effect.
Allows the beam to be made oval; combined with spot and flood optics the effect appears more pronounced.

LOGICO

System

GENERAL INFO
Modules of variable lengths for ceiling, suspension, recessed and semi-recessed installations.
Recessed versions with a flange or trimless.
Lenghts:
281mm - 562mm – 1122mm – 1682mm – 3364mm

LED
Linear Board LED Engine for linear and SPOT versions
LED COB for LABEL versions
From 982lm to 28960lm
3000K – 4000K
OPAL, UGR, WW versions: Ra84 - Ra90

PRODUCT EFFICACY
Up to 109lm/W

OPTICS
OPAL – UGR – WW - SP - FL - MWFL

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Powder coated, extruded, calendered aluminium.

ON DEMAND

Tunable White (continuous light module)

110-277Vac power supply

Modular lighting system with which it is possible to create luminous shapes and numerous lighting scenes given the different lengths available and T, L, and X light connectors and high-power or low-power lumen on modules of the same length.

It is made up of many lighting units: diffused light, UGR<19 controlled light suitable for the workplace (EN-12464 - L65<3000 cd/m^2), wall washer and the new spotlight modules with Label 4 and Label 6 projectors.
The accessories allow it to be installed on the ceiling, walls, suspended, recessed, or semi-recessed (with or without flange).

Also available in a stand alone version.

Emergency versions available on request after checking feasibility.

Zonamerica
Montevideo, Uruguay

Architect Estudio Dovat Arquitectos
Lighting Design Estudio Hofstadter

Photographer Ferrés - Cánepa

Plus

Easy to assemble

Each module is already complete with the lighting unit. Modules with linear light snap together or use magnets, so no tools are needed. The new modules with spotlights already have built-in projectors or lighting elements.

Dimmer light

The Logico modules (opal, ugr, asy, Label) equipped with DALI driver can be dimmed from 10% to 100% with AM modulation amplitude. Dimming is done by modifying the piloting current and not by turning the LEDs on and off. This prevents flickering and makes it suitable for installation even where videos are recorded.

10% 100%



Opal



Ugr<19



Wall Washer



Spot Ugr<7

Four different optical systems

- Diffused light with an opal screen: a soft, wide light emission particularly suitable for receptions and communal areas, corridors, etc...
- Controlled light UGR<19 (EN-12464 - L65<3000 cd/m^2) with a prismatic screen (only for the direct component): ideal for open space offices, schools or meeting rooms where glare must be reduced to a minimum.
- Directed light with a Wall Washer optical system: ideal for lighting vertical surfaces like walls or works of art.
- Precise light where a system composed of micro lenses produces precise and focused SPOT effects with UGR<7, ideal for lighting commercial and hotel environments.



Plus



A **Logico trimless recessed**
It can be installed recessed or semi-recessed using the same recessing box that can be left with the flange visible or grouted for a trimless effect.

B **Logico recessed with flange**
It can be installed without an outer casing using the brackets supplied. Semi-recessed installation is not available

A





B



C **Ceiling installation**
The modules must be fixed to the ceiling with the special accessory brackets. The springs are attached to the modules in a “click” by applying pressure.

D **Suspended also on sloping ceilings**
The suspension kit allows installation even on tilted ceilings or on vertical elements.



C



D



Plus

New Label modules

New linear modules equipped with Label 4 or Label 6 projectors, available with spotlights, floodlights, and medium wide floodlights.

New Spot modules

As of today, Logico is also available with the new Spot modules with LED Lineare High Power card and optical system made up of TIR lenses in optical methacrylate, holographic filter and black polycarbonate frame (the profile finish also comes in white). The result is a highly concentrated and controlled light for scenic effects UGR<7 (EN 12464-1)

New blind modules

New blind modules to create a continuous system that connects the spaces between them without interruption. Joints without a light unit are also available to guarantee infinite compositional solutions.



LOGICO



System Ceiling/ Suspension - continuous light module L. 562mm



LED / 12W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	14W		1	2.66	451
Source Flux	1740lm		2	5.33	113
Fixture Flux	1185lm		3	7.99	50
Efficacy	85lm/W		4	10.65	28
TS991	Imax=259cd/klm	Imax	451cd	5	13.32	18

Driver	Colour	3000K	4000K
EL.	○	**1T6027EL**	**1T6028EL**
EL.	◐	**1T6031EL**	**1T6032EL**
EL.	●	**1T6035EL**	**1T6036EL**
DALI	○	**1T6027DA**	**1T6028DA**
DALI	◐	**1T6031DA**	**1T6032DA**
DALI	●	**1T6035DA**	**1T6036DA**

LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	27W		1	2.66	892
Source Flux	3440lm		2	5.33	223
Fixture Flux	2343lm		3	7.99	99
Efficacy	87lm/W		4	10.65	56
TS996	Imax=259cd/klm	Imax	892cd	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T6029EL**	**1T6030EL**
EL.	◐	**1T6033EL**	**1T6034EL**
EL.	●	**1T6037EL**	**1T6038EL**
DALI	○	**1T6029DA**	**1T6030DA**
DALI	◐	**1T6033DA**	**1T6034DA**
DALI	●	**1T6037DA**	**1T6038DA**

LED / 8W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	9W		1	1.51	556
Source Flux	1260lm		2	3.02	139
Fixture Flux	816lm		3	4.52	62
Efficacy	91lm/W		4	6.03	35
TS992	Imax=442cd/klm	Imax	556cd	5	7.54	22

Driver	Colour	3000K	4000K
EL.	○	**1T6825EL**	**1T6826EL**
EL.	◐	**1T6827EL**	**1T6828EL**
EL.	●	**1T6829EL**	**1T6830EL**
DALI	○	**1T6825DA**	**1T6826DA**
DALI	◐	**1T6827DA**	**1T6828DA**
DALI	●	**1T6829DA**	**1T6830DA**

LED / 12W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	14W		1	2.28	2.55	1400
Source Flux	1740lm		2	4.56	5.10	350
Fixture Flux	1369lm		3	6.84	7.64	156
Efficacy	98lm/W		4	9.12	10.19	88
TS993	Imax=1001cd/klm	Imax	1743cd	5	11.40	12.74	56

Driver	Colour	3000K	4000K
EL.	○	**1T6837EL**	**1T6838EL**
EL.	◐	**1T6839EL**	**1T6840EL**
EL.	●	**1T6841EL**	**1T6842EL**
DALI	○	**1T6837DA**	**1T6838DA**
DALI	◐	**1T6839DA**	**1T6840DA**
DALI	●	**1T6841DA**	**1T6842DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	27W		1	2.28	2.55	2768
Source Flux	3440lm		2	4.56	5.10	692
Fixture Flux	2707lm		3	6.84	7.64	308
Efficacy	100lm/W		4	9.12	10.19	173
TS997	Imax=1001cd/klm	Imax	3445cd	5	11.40	12.74	111

Driver	Colour	3000K	4000K
EL.	○	**1T6843EL**	**1T6844EL**
EL.	◐	**1T6845EL**	**1T6846EL**
EL.	●	**1T6847EL**	**1T6848EL**
DALI	○	**1T6843DA**	**1T6844DA**
DALI	◐	**1T6845DA**	**1T6846DA**
DALI	●	**1T6847DA**	**1T6848DA**

LOGICO

LED / 18W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		20W	1	2.66	387
Source Flux		2610lm	2	5.33	97
Fixture Flux		1773lm	3	7.99	43
Efficacy		89lm/W	4	10.65	24
TS994	Imax=148cd/klm	Imax	5	13.32	15

Driver	Colour	3000K	4000K
EL.	○	**1T6039EL**	**1T6040EL**
EL.	◐	**1T6043EL**	**1T6044EL**
EL.	◐	**1T6047EL**	**1T6048EL**
DALI	○	**1T6039DA**	**1T6040DA**
DALI	◐	**1T6043DA**	**1T6044DA**
DALI	◐	**1T6047DA**	**1T6048DA**

LED / 30W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		34W	1	2.66	810
Source Flux		4310lm	2	5.33	203
Fixture Flux		2930lm	3	7.99	90
Efficacy		86lm/W	4	10.65	51
TS998	Imax=188cd/klm	Imax	5	13.32	32

Driver	Colour	3000K	4000K
EL.	○	**1T6041EL**	**1T6042EL**
EL.	◐	**1T6045EL**	**1T6046EL**
EL.	◐	**1T6049EL**	**1T6050EL**
DALI	○	**1T6041DA**	**1T6042DA**
DALI	◐	**1T6045DA**	**1T6046DA**
DALI	◐	**1T6049DA**	**1T6050DA**

LED / 12W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		14W	1	1.51	477
Source Flux		1890lm	2	3.02	119
Fixture Flux		1248lm	3	4.52	53
Efficacy		89lm/W	4	6.03	30
TS995	Imax=252cd/klm	Imax	5	7.54	19

Driver	Colour	3000K	4000K
EL.	○	**1T6831EL**	**1T6832EL**
EL.	◐	**1T6833EL**	**1T6834EL**
EL.	◐	**1T6835EL**	**1T6836EL**
DALI	○	**1T6831DA**	**1T6832DA**
DALI	◐	**1T6833DA**	**1T6834DA**
DALI	◐	**1T6835DA**	**1T6836DA**

System Ceiling/ Suspension - continuous light module L. 1122mm



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		27W	1	2.66	903
Source Flux		3480lm	2	5.33	226
Fixture Flux		2370lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS991	Imax=259cd/klm	Imax	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T5635EL**	**1T5636EL**
EL.	◐	**1T5639EL**	**1T5640EL**
EL.	◐	**1T5637EL**	**1T5638EL**
DALI	○	**1T5635DA**	**1T5636DA**
DALI	◐	**1T5639DA**	**1T5640DA**
DALI	◐	**1T5637DA**	**1T5638DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		54W	1	2.66	1785
Source Flux		6880lm	2	5.33	446
Fixture Flux		4685lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS996	Imax=259cd/klm	Imax	5	13.32	71

Driver	Colour	3000K	4000K
EL.	○	**1T5641EL**	**1T5642EL**
EL.	◐	**1T5645EL**	**1T5646EL**
EL.	◐	**1T5643EL**	**1T5644EL**
DALI	○	**1T5641DA**	**1T5642DA**
DALI	◐	**1T5645DA**	**1T5646DA**
DALI	◐	**1T5643DA**	**1T5644DA**

LOGICO

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		18W	1	1.51	1113
Source Flux		2520lm	2	3.02	278
Fixture Flux		1631lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS992	Imax=442cd/klm	Imax	5	7.54	45

Driver	Colour	3000K	4000K
EL.	○	**1T5659EL**	**1T5660EL**
EL.	◐	**1T5663EL**	**1T5664EL**
EL.	◐	**1T5661EL**	**1T5662EL**
DALI	○	**1T5659DA**	**1T5660DA**
DALI	◐	**1T5663DA**	**1T5664DA**
DALI	◐	**1T5661DA**	**1T5662DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		27W	1	2.28	2.55	2801
Source Flux		3480lm	2	4.56	5.10	700
Fixture Flux		2739lm	3	6.84	7.64	311
Efficacy		101lm/W	4	9.12	10.19	175
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	112

Driver	Colour	3000K	4000K
EL.	○	**1T5671EL**	**1T5672EL**
EL.	◐	**1T5675EL**	**1T5676EL**
EL.	◐	**1T5673EL**	**1T5674EL**
DALI	○	**1T5671DA**	**1T5672DA**
DALI	◐	**1T5675DA**	**1T5676DA**
DALI	◐	**1T5673DA**	**1T5674DA**

LED / 48W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		54W	1	2.28	2.55	5537
Source Flux		6880lm	2	4.56	5.10	1384
Fixture Flux		5415lm	3	6.84	7.64	615
Efficacy		100lm/W	4	9.12	10.19	346
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	221

Driver	Colour	3000K	4000K
EL.	○	**1T5677EL**	**1T5678EL**
EL.	◐	**1T5681EL**	**1T5682EL**
EL.	◐	**1T5679EL**	**1T5680EL**
DALI	○	**1T5677DA**	**1T5678DA**
DALI	◐	**1T5681DA**	**1T5682DA**
DALI	◐	**1T5679DA**	**1T5680DA**

LED / 42W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		47W	1	2.66	903
Source Flux		6090lm	2	5.33	226
Fixture Flux		4136lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS994	Imax=148cd/klm	Imax	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T5647EL**	**1T5648EL**
EL.	◐	**1T5651EL**	**1T5652EL**
EL.	◐	**1T5649EL**	**1T5650EL**
DALI	○	**1T5647DA**	**1T5648DA**
DALI	◐	**1T5651DA**	**1T5652DA**
DALI	◐	**1T5649DA**	**1T5650DA**

LED / 66W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		74W	1	2.66	1785
Source Flux		9490lm	2	5.33	446
Fixture Flux		6452lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS998	Imax=188cd/klm	Imax	5	13.32	71

Driver	Colour	3000K	4000K
EL.	○	**1T5653EL**	**1T5654EL**
EL.	◐	**1T5657EL**	**1T5658EL**
EL.	◐	**1T5655EL**	**1T5656EL**
DALI	○	**1T5653DA**	**1T5654DA**
DALI	◐	**1T5657DA**	**1T5658DA**
DALI	◐	**1T5655DA**	**1T5656DA**

LED / 28W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		32W	1	1.51	1113
Source Flux		4410lm	2	3.02	278
Fixture Flux		2912lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS995	Imax=252cd/klm	Imax	5	7.54	45

Driver	Colour	3000K	4000K
EL.	○	**1T5665EL**	**1T5666EL**
EL.	◐	**1T5669EL**	**1T5670EL**
EL.	◐	**1T5667EL**	**1T5668EL**
DALI	○	**1T5665DA**	**1T5666DA**
DALI	◐	**1T5669DA**	**1T5670DA**
DALI	◐	**1T5667DA**	**1T5668DA**

LOGICO



System Ceiling/ Suspension - continuous light module L. 1682mm



LED / 36W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		40W	1	2.66	1354
Source Flux		5220lm	2	5.33	338
Fixture Flux		3555lm	3	7.99	150
Efficacy		89lm/W	4	10.65	85
TS991	Imax=259cd/klm	Imax	1354cd	5	13.32	54

Driver	Colour	3000K	4000K
EL.	○	**1T5683EL**	**1T5684EL**
EL.	◐	**1T5687EL**	**1T5688EL**
EL.	●	**1T5685EL**	**1T5686EL**
DALI	○	**1T5683DA**	**1T5684DA**
DALI	◐	**1T5687DA**	**1T5688DA**
DALI	●	**1T5685DA**	**1T5686DA**

LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2677
Source Flux		10320lm	2	5.33	669
Fixture Flux		7028lm	3	7.99	297
Efficacy		87lm/W	4	10.65	167
TS996	Imax=259cd/klm	Imax	2677cd	5	13.32	107

Driver	Colour	3000K	4000K
EL.	○	**1T5689EL**	**1T5690EL**
EL.	◐	**1T5693EL**	**1T5694EL**
EL.	●	**1T5691EL**	**1T5692EL**
DALI	○	**1T5689DA**	**1T5690DA**
DALI	◐	**1T5693DA**	**1T5694DA**
DALI	●	**1T5691DA**	**1T5692DA**

LED / 24W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		27W	1	1.51	1669
Source Flux		3780lm	2	3.02	417
Fixture Flux		2447lm	3	4.52	185
Efficacy		91lm/W	4	6.03	104
TS992	Imax=442cd/klm	Imax	1669cd	5	7.54	67

Driver	Colour	3000K	4000K
EL.	○	**1T5707EL**	**1T5708EL**
EL.	◐	**1T5711EL**	**1T5712EL**
EL.	●	**1T5709EL**	**1T5710EL**
DALI	○	**1T5707DA**	**1T5708DA**
DALI	◐	**1T5711DA**	**1T5712DA**
DALI	●	**1T5709DA**	**1T5710DA**

LED / 36W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		40W	1	2.28	2.55	4201
Source Flux		5220lm	2	4.56	5.10	1050
Fixture Flux		4108lm	3	6.84	7.64	467
Efficacy		103lm/W	4	9.12	10.19	263
TS993	Imax=1001cd/klm	Imax	5228cd	5	11.40	12.74	168

Driver	Colour	3000K	4000K
EL.	○	**1T5719EL**	**1T5720EL**
EL.	◐	**1T5723EL**	**1T5724EL**
EL.	●	**1T5721EL**	**1T5722EL**
DALI	○	**1T5719DA**	**1T5720DA**
DALI	◐	**1T5723DA**	**1T5724DA**
DALI	●	**1T5721DA**	**1T5722DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		81W	1	2.28	2.55	8305
Source Flux		10320lm	2	4.56	5.10	2076
Fixture Flux		8122lm	3	6.84	7.64	923
Efficacy		100lm/W	4	9.12	10.19	519
TS997	Imax=1001cd/klm	Imax	10335cd	5	11.40	12.74	332

Driver	Colour	3000K	4000K
EL.	○	**1T5725EL**	**1T5726EL**
EL.	◐	**1T5729EL**	**1T5730EL**
EL.	●	**1T5727EL**	**1T5728EL**
DALI	○	**1T5725DA**	**1T5726DA**
DALI	◐	**1T5729DA**	**1T5730DA**
DALI	●	**1T5727DA**	**1T5728DA**

LOGICO

LED / 60W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		68W	1	2.66	1290
Source Flux		8700lm	2	5.33	322
Fixture Flux		5909lm	3	7.99	143
Efficacy		87lm/W	4	10.65	81
TS994	Imax=148cd/klm	Imax	5	13.32	52

Driver	Colour	3000K	4000K
EL.	○	**1T5695EL**	**1T5696EL**
EL.	◐	**1T5699EL**	**1T5700EL**
EL.	◐	**1T5697EL**	**1T5698EL**
DALI	○	**1T5695DA**	**1T5696DA**
DALI	◐	**1T5699DA**	**1T5700DA**
DALI	◐	**1T5697DA**	**1T5698DA**

LED / 96W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		107W	1	2.66	2595
Source Flux		13800lm	2	5.33	649
Fixture Flux		9382lm	3	7.99	288
Efficacy		88lm/W	4	10.65	162
TS998	Imax=188cd/klm	Imax	5	13.32	104

Driver	Colour	3000K	4000K
EL.	○	**1T5701EL**	**1T5702EL**
EL.	◐	**1T5705EL**	**1T5706EL**
EL.	◐	**1T5703EL**	**1T5704EL**
DALI	○	**1T5701DA**	**1T5702DA**
DALI	◐	**1T5705DA**	**1T5706DA**
DALI	◐	**1T5703DA**	**1T5704DA**

LED / 40W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		45W	1	1.51	1590
Source Flux		6300lm	2	3.02	398
Fixture Flux		4160lm	3	4.52	177
Efficacy		92lm/W	4	6.03	99
TS995	Imax=252cd/klm	Imax	5	7.54	64

Driver	Colour	3000K	4000K
EL.	○	**1T5713EL**	**1T5714EL**
EL.	◐	**1T5717EL**	**1T5718EL**
EL.	◐	**1T5715EL**	**1T5716EL**
DALI	○	**1T5713DA**	**1T5714DA**
DALI	◐	**1T5717DA**	**1T5718DA**
DALI	◐	**1T5715DA**	**1T5716DA**

System Ceiling/ Suspension - continuous light module L. 3364mm



LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2708
Source Flux		10440lm	2	5.33	677
Fixture Flux		7110lm	3	7.99	301
Efficacy		88lm/W	4	10.65	169
TS991	Imax=259cd/klm	Imax	5	13.32	108

Driver	Colour	3000K	4000K
EL.	○	**1T5731EL**	**1T5732EL**
EL.	◐	**1T5735EL**	**1T5736EL**
EL.	◐	**1T5733EL**	**1T5734EL**
DALI	○	**1T5731DA**	**1T5732DA**
DALI	◐	**1T5735DA**	**1T5736DA**
DALI	◐	**1T5733DA**	**1T5734DA**

LED / 144W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		163W	1	2.66	5354
Source Flux		20640lm	2	5.33	1338
Fixture Flux		14056lm	3	7.99	595
Efficacy		86lm/W	4	10.65	335
TS996	Imax=259cd/klm	Imax	5	13.32	214

Driver	Colour	3000K	4000K
EL.	○	**1T5737EL**	**1T5738EL**
EL.	◐	**1T5741EL**	**1T5742EL**
EL.	◐	**1T5739EL**	**1T5740EL**
DALI	○	**1T5737DA**	**1T5738DA**
DALI	◐	**1T5741DA**	**1T5742DA**
DALI	◐	**1T5739DA**	**1T5740DA**

LOGICO

LED / 48W / DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	54W	1	1.51	3338
Source Flux	7560lm	2	3.02	834
Fixture Flux	4894lm	3	4.52	371
Efficacy	91lm/W	4	6.03	209
Imax	3338cd	5	7.54	134

TS992 Imax=442cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5755EL**	**1T5756EL**
EL.	◐	**1T5759EL**	**1T5760EL**
EL.	◐	**1T5757EL**	**1T5758EL**
DALI	○	**1T5755DA**	**1T5756DA**
DALI	◐	**1T5759DA**	**1T5760DA**
DALI	◐	**1T5757DA**	**1T5758DA**

LED / 72W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	81W	1	2.28	2.55	8402
Source Flux	10440lm	2	4.56	5.10	2101
Fixture Flux	8216lm	3	6.84	7.64	934
Efficacy	101lm/W	4	9.12	10.19	525
Imax	10455cd	5	11.40	12.74	336

TS993 Imax=1001cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5767EL**	**1T5768EL**
EL.	◐	**1T5771EL**	**1T5772EL**
EL.	◐	**1T5769EL**	**1T5770EL**
DALI	○	**1T5767DA**	**1T5768DA**
DALI	◐	**1T5771DA**	**1T5772DA**
DALI	◐	**1T5769DA**	**1T5770DA**

LED / 144W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	163W	1	2.28	2.55	16611
Source Flux	20640lm	2	4.56	5.10	4153
Fixture Flux	16244lm	3	6.84	7.64	1846
Efficacy	100lm/W	4	9.12	10.19	1038
Imax	20670cd	5	11.40	12.74	664

TS997 Imax=1001cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5773EL**	**1T5774EL**
EL.	◐	**1T5777EL**	**1T5778EL**
EL.	◐	**1T5775EL**	**1T5776EL**
DALI	○	**1T5773DA**	**1T5774DA**
DALI	◐	**1T5777DA**	**1T5778DA**
DALI	◐	**1T5775DA**	**1T5776DA**

LED / 120W / UP-DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	136W	1	2.66	2579
Source Flux	17400lm	2	5.33	645
Fixture Flux	11818lm	3	7.99	287
Efficacy	87lm/W	4	10.65	161
Imax	2579cd	5	13.32	103

TS994 Imax=148cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5743EL**	**1T5744EL**
EL.	◐	**1T5747EL**	**1T5748EL**
EL.	◐	**1T5745EL**	**1T5746EL**
DALI	○	**1T5743DA**	**1T5744DA**
DALI	◐	**1T5747DA**	**1T5748DA**
DALI	◐	**1T5745DA**	**1T5746DA**

LED / 192W / UP-DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	218W	1	2.66	5183
Source Flux	27560lm	2	5.33	1296
Fixture Flux	18736lm	3	7.99	576
Efficacy	86lm/W	4	10.65	324
Imax	5183cd	5	13.32	207

TS998 Imax=188cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5749EL**	**1T5750EL**
EL.	◐	**1T5753EL**	**1T5754EL**
EL.	◐	**1T5751EL**	**1T5752EL**
DALI	○	**1T5749DA**	**1T5750DA**
DALI	◐	**1T5753DA**	**1T5754DA**
DALI	◐	**1T5751DA**	**1T5752DA**

LED / 80W / UP-DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	91W	1	1.51	3181
Source Flux	12600lm	2	3.02	795
Fixture Flux	8320lm	3	4.52	353
Efficacy	91lm/W	4	6.03	199
Imax	3181cd	5	7.54	127

TS995 Imax=252cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5761EL**	**1T5762EL**
EL.	◐	**1T5765EL**	**1T5766EL**
EL.	◐	**1T5763EL**	**1T5764EL**
DALI	○	**1T5761DA**	**1T5762DA**
DALI	◐	**1T5765DA**	**1T5766DA**
DALI	◐	**1T5763DA**	**1T5764DA**

LOGICO

System Ceiling/ Suspension - continuous light module L connector



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		27W	1	2.66	903
Source Flux		3480lm	2	5.33	226
Fixture Flux		2370lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS991	Imax=259cd/klm	Imax	903cd	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T5976EL**	**1T5977EL**
EL.	◐	**1T5980EL**	**1T5981EL**
EL.	●	**1T5984EL**	**1T5985EL**
DALI	○	**1T5976DA**	**1T5977DA**
DALI	◐	**1T5980DA**	**1T5981DA**
DALI	●	**1T5984DA**	**1T5985DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		54W	1	2.66	1785
Source Flux		6880lm	2	5.33	445
Fixture Flux		4685lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS996	Imax=259cd/klm	Imax	1785cd	5	13.32	71

Driver	Colour	3000K	4000K
EL.	○	**1T5978EL**	**1T5979EL**
EL.	◐	**1T5982EL**	**1T5983EL**
EL.	●	**1T5986EL**	**1T5987EL**
DALI	○	**1T5978DA**	**1T5979DA**
DALI	◐	**1T5982DA**	**1T5983DA**
DALI	●	**1T5986DA**	**1T5987DA**

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		18W	1	1.51	1113
Source Flux		2520lm	2	3.02	278
Fixture Flux		1631lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS992	Imax=442cd/klm	Imax	1113cd	5	7.54	45

Driver	Colour	3000K	4000K
EL.	○	**1T6855EL**	**1T6856EL**
EL.	◐	**1T6857EL**	**1T6858EL**
EL.	●	**1T6859EL**	**1T6860EL**
DALI	○	**1T6855DA**	**1T6856DA**
DALI	◐	**1T6857DA**	**1T6858DA**
DALI	●	**1T6859DA**	**1T6860DA**

LED / 36W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		40W	1	2.66	774
Source Flux		5220lm	2	5.33	193
Fixture Flux		3545lm	3	7.99	86
Efficacy		89lm/W	4	10.65	48
TS994	Imax=148cd/klm	Imax	774cd	5	13.32	31

Driver	Colour	3000K	4000K
EL.	○	**1T6891EL**	**1T6892EL**
EL.	◐	**1T6893EL**	**1T6894EL**
EL.	●	**1T6895EL**	**1T6896EL**
DALI	○	**1T6891DA**	**1T6892DA**
DALI	◐	**1T6893DA**	**1T6894DA**
DALI	●	**1T6895DA**	**1T6896DA**

LED / 24W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		27W	1	1.51	954
Source Flux		3780lm	2	3.02	239
Fixture Flux		2496lm	3	4.52	106
Efficacy		92lm/W	4	6.03	60
TS995	Imax=252cd/klm	Imax	954cd	5	7.54	38

Driver	Colour	3000K	4000K
EL.	○	**1T6873EL**	**1T6874EL**
EL.	◐	**1T6875EL**	**1T6876EL**
EL.	●	**1T6877EL**	**1T6878EL**
DALI	○	**1T6873DA**	**1T6874DA**
DALI	◐	**1T6875DA**	**1T6876DA**
DALI	●	**1T6877DA**	**1T6878DA**

LOGICO



System Ceiling/ Suspension - continuous light module T connector



LED / 36W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	40W		1	2.66	1354
Source Flux	5220lm		2	5.33	338
Fixture Flux	3555lm		3	7.99	150
Efficacy	89lm/W		4	10.65	85
TS991	Imax=259cd/klm	Imax	1354cd	5	13.32	54

Driver	Colour	3000K	4000K
EL.	○	**1T5988EL**	**1T5989EL**
EL.	◐	**1T5992EL**	**1T5993EL**
EL.	●	**1T5996EL**	**1T5997EL**
DALI	○	**1T5988DA**	**1T5989DA**
DALI	◐	**1T5992DA**	**1T5993DA**
DALI	●	**1T5996DA**	**1T5997DA**

LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	81W		1	2.66	2677
Source Flux	10320lm		2	5.33	669
Fixture Flux	7028lm		3	7.99	297
Efficacy	87lm/W		4	10.65	167
TS996	Imax=259cd/klm	Imax	2677cd	5	13.32	107

Driver	Colour	3000K	4000K
EL.	○	**1T5990EL**	**1T5991EL**
EL.	◐	**1T5994EL**	**1T5995EL**
EL.	●	**1T5998EL**	**1T5999EL**
DALI	○	**1T5990DA**	**1T5991DA**
DALI	◐	**1T5994DA**	**1T5995DA**
DALI	●	**1T5998DA**	**1T5999DA**

LED / 24W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	27W		1	1.51	1669
Source Flux	3780lm		2	3.02	417
Fixture Flux	2447lm		3	4.52	185
Efficacy	91lm/W		4	6.03	104
TS992	Imax=442cd/klm	Imax	1669cd	5	7.54	67

Driver	Colour	3000K	4000K
EL.	○	**1T6861EL**	**1T6862EL**
EL.	◐	**1T6863EL**	**1T6864EL**
EL.	●	**1T6865EL**	**1T6866EL**
DALI	○	**1T6861DA**	**1T6862DA**
DALI	◐	**1T6863DA**	**1T6864DA**
DALI	●	**1T6865DA**	**1T6866DA**

LED / 54W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	60W		1	2.66	1161
Source Flux	7830lm		2	5.33	290
Fixture Flux	5318lm		3	7.99	129
Efficacy	89lm/W		4	10.65	73
TS994	Imax=148cd/klm	Imax	1161cd	5	13.32	46

Driver	Colour	3000K	4000K
EL.	○	**1T6897EL**	**1T6898EL**
EL.	◐	**1T6899EL**	**1T6900EL**
EL.	●	**1T6901EL**	**1T6902EL**
DALI	○	**1T6897DA**	**1T6898DA**
DALI	◐	**1T6899DA**	**1T6900DA**
DALI	●	**1T6901DA**	**1T6902DA**

LED / 36W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	40W		1	1.51	1431
Source Flux	5670lm		2	3.02	358
Fixture Flux	3744lm		3	4.52	159
Efficacy	94lm/W		4	6.03	89
TS995	Imax=252cd/klm	Imax	1431cd	5	7.54	57

Driver	Colour	3000K	4000K
EL.	○	**1T6879EL**	**1T6880EL**
EL.	◐	**1T6881EL**	**1T6882EL**
EL.	●	**1T6883EL**	**1T6884EL**
DALI	○	**1T6879DA**	**1T6880DA**
DALI	◐	**1T6881DA**	**1T6882DA**
DALI	●	**1T6883DA**	**1T6884DA**

LOGICO

System Ceiling/ Suspension - continuous light module X connector



LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	54W		1	2.66	1805
Source Flux	6960lm		2	5.33	451
Fixture Flux	4740lm		3	7.99	201
Efficacy	88lm/W		4	10.65	113
TS991	Imax=259cd/klm	Imax	5	13.32	72

Driver	Colour	3000K	4000K
EL.	○	**1T6000EL**	**1T6001EL**
EL.	◐	**1T6004EL**	**1T6005EL**
EL.	◐	**1T6008EL**	**1T6009EL**
DALI	○	**1T6000DA**	**1T6001DA**
DALI	◐	**1T6004DA**	**1T6005DA**
DALI	◐	**1T6008DA**	**1T6009DA**

LED / 96W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	108W		1	2.66	3569
Source Flux	13760lm		2	5.33	892
Fixture Flux	9371lm		3	7.99	397
Efficacy	87lm/W		4	10.65	223
TS996	Imax=259cd/klm	Imax	5	13.32	143

Driver	Colour	3000K	4000K
EL.	○	**1T6002EL**	**1T6003EL**
EL.	◐	**1T6006EL**	**1T6007EL**
EL.	◐	**1T6010EL**	**1T6011EL**
DALI	○	**1T6002DA**	**1T6003DA**
DALI	◐	**1T6006DA**	**1T6007DA**
DALI	◐	**1T6010DA**	**1T6011DA**

LED / 36W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	40W		1	1.51	2225
Source Flux	5040lm		2	3.02	556
Fixture Flux	3263lm		3	4.52	247
Efficacy	82lm/W		4	6.03	139
TS992	Imax=442cd/klm	Imax	5	7.54	89

Driver	Colour	3000K	4000K
EL.	○	**1T6867EL**	**1T6868EL**
EL.	◐	**1T6869EL**	**1T6870EL**
EL.	◐	**1T6871EL**	**1T6872EL**
DALI	○	**1T6867DA**	**1T6868DA**
DALI	◐	**1T6869DA**	**1T6870DA**
DALI	◐	**1T6871DA**	**1T6872DA**

LED / 72W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	81W		1	2.66	1547
Source Flux	10440lm		2	5.33	387
Fixture Flux	7091lm		3	7.99	172
Efficacy	88lm/W		4	10.65	97
TS994	Imax=148cd/klm	Imax	5	13.32	62

Driver	Colour	3000K	4000K
EL.	○	**1T6903EL**	**1T6904EL**
EL.	◐	**1T6905EL**	**1T6906EL**
EL.	◐	**1T6907EL**	**1T6908EL**
DALI	○	**1T6903DA**	**1T6904DA**
DALI	◐	**1T6905DA**	**1T6906DA**
DALI	◐	**1T6907DA**	**1T6908DA**

LED / 48W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	54W		1	1.51	1908
Source Flux	7560lm		2	3.02	477
Fixture Flux	4992lm		3	4.52	212
Efficacy	92lm/W		4	6.03	119
TS995	Imax=252cd/klm	Imax	5	7.54	76

Driver	Colour	3000K	4000K
EL.	○	**1T6885EL**	**1T6886EL**
EL.	◐	**1T6887EL**	**1T6888EL**
EL.	◐	**1T6889EL**	**1T6890EL**
DALI	○	**1T6885DA**	**1T6886DA**
DALI	◐	**1T6887DA**	**1T6888DA**
DALI	◐	**1T6889DA**	**1T6890DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Direct/indirect version: single switch.

System Ceiling/ Suspension - projector module Label 4



LED / 1x8W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power	9W	1		0.31	4214
Source Flux	982lm	2		0.62	1053
Fixture Flux	622lm	3		0.93	468
Efficacy	71lm/W	4		1.24	263
TS1165 Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Driver	Colour	3000K	4000K
EL.	○	**1T7221EL**	**1T7224EL**
EL.	◐	**1T7227EL**	**1T7230EL**
EL.	●	**1T7233EL**	**1T7236EL**
DALI	○	**1T7221DA**	**1T7224DA**
DALI	◐	**1T7227DA**	**1T7230DA**
DALI	●	**1T7233DA**	**1T7236DA**

LED / 1x8W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power	9W	1		0.48	3199
Source Flux	1129lm	2		0.95	800
Fixture Flux	806lm	3		1.43	355
Efficacy	92lm/W	4		1.91	200
TS1166 Imax=2834cd/klm	Imax	3199cd	5	2.38	128

Driver	Colour	3000K	4000K
EL.	○	**1T7222EL**	**1T7225EL**
EL.	◐	**1T7228EL**	**1T7231EL**
EL.	●	**1T7234EL**	**1T7237EL**
DALI	○	**1T7222DA**	**1T7225DA**
DALI	◐	**1T7228DA**	**1T7231DA**
DALI	●	**1T7234DA**	**1T7237DA**

LED / 1x8W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power	9W	1		0.76	1831
Source Flux	1129lm	2		1.52	458
Fixture Flux	835lm	3		2.28	203
Efficacy	95lm/W	4		3.04	114
TS1167 Imax=1622cd/klm	Imax	1831cd	5	3.80	73

Driver	Colour	3000K	4000K
EL.	○	**1T7223EL**	**1T7226EL**
EL.	◐	**1T7229EL**	**1T7232EL**
EL.	●	**1T7235EL**	**1T7238EL**
DALI	○	**1T7223DA**	**1T7226DA**
DALI	◐	**1T7229DA**	**1T7232DA**
DALI	●	**1T7235DA**	**1T7238DA**

System Ceiling/ Suspension - projector module Label 4



LED / 3x8W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power	9W	1		0.31	4214
Source Flux	982lm	2		0.62	1053
Fixture Flux	622lm	3		0.93	468
Efficacy	71lm/W	4		1.24	263
TS1165 Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Driver	Colour	3000K	4000K
EL.	○	**1T7239EL**	**1T7242EL**
EL.	◐	**1T7245EL**	**1T7248EL**
EL.	●	**1T7251EL**	**1T7254EL**
DALI	○	**1T7239DA**	**1T7242DA**
DALI	◐	**1T7245DA**	**1T7248DA**
DALI	●	**1T7251DA**	**1T7254DA**

LOGICO

LED / 3x8W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power	9W	1		0.48	3199
Source Flux	1129lm	2		0.95	800
Fixture Flux	806lm	3		1.43	355
Efficacy	92lm/W	4		1.91	200
Imax	3199cd	5		2.38	128

TS1166 Imax=2834cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7240EL**	**1T7243EL**
EL.	●	**1T7246EL**	**1T7249EL**
EL.	●	**1T7252EL**	**1T7255EL**
DALI	○	**1T7240DA**	**1T7243DA**
DALI	●	**1T7246DA**	**1T7249DA**
DALI	●	**1T7252DA**	**1T7255DA**

LED / 3x8W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power	9W	1		0.76	1831
Source Flux	1129lm	2		1.52	458
Fixture Flux	835lm	3		2.28	203
Efficacy	95lm/W	4		3.04	114
Imax	1831cd	5		3.80	73

TS1167 Imax=1622cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7241EL**	**1T7244EL**
EL.	●	**1T7247EL**	**1T7250EL**
EL.	●	**1T7253EL**	**1T7256EL**
DALI	○	**1T7241DA**	**1T7244DA**
DALI	●	**1T7247DA**	**1T7250DA**
DALI	●	**1T7253DA**	**1T7256DA**

System Ceiling/ Suspension - projector module Label 6



LED / 1x14W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power	15W	1		0.28	10741
Source Flux	1793lm	2		0.55	2685
Fixture Flux	1316lm	3		0.83	1193
Efficacy	91lm/W	4		1.11	671
Imax	10741cd	5		1.39	430

TS1168 Imax=5990cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7305EL**	**1T7308EL**
EL.	●	**1T7311EL**	**1T7314EL**
EL.	●	**1T7317EL**	**1T7320EL**
DALI	○	**1T7305DA**	**1T7308DA**
DALI	●	**1T7311DA**	**1T7314DA**
DALI	●	**1T7317DA**	**1T7320DA**

LED / 1x14W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power	15W	1		0.56	4410
Source Flux	1793lm	2		1.12	1102
Fixture Flux	1386lm	3		1.67	490
Efficacy	96lm/W	4		2.23	276
Imax	4410cd	5		2.79	176

TS813 Imax=2460cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7306EL**	**1T7309EL**
EL.	●	**1T7312EL**	**1T7315EL**
EL.	●	**1T7318EL**	**1T7321EL**
DALI	○	**1T7306DA**	**1T7309DA**
DALI	●	**1T7312DA**	**1T7315DA**
DALI	●	**1T7318DA**	**1T7321DA**

LED / 1x14W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power	15W	1		0.88	2457
Source Flux	1793lm	2		1.77	614
Fixture Flux	1373lm	3		2.65	273
Efficacy	95lm/W	4		3.53	154
Imax	2471cd	5		4.41	98

TS1170 Imax=1378cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7307EL**	**1T7310EL**
EL.	●	**1T7313EL**	**1T7316EL**
EL.	●	**1T7319EL**	**1T7322EL**
DALI	○	**1T7307DA**	**1T7310DA**
DALI	●	**1T7313DA**	**1T7316DA**
DALI	●	**1T7319DA**	**1T7322DA**

System Ceiling/ Suspension - projector module Label 6



LED / 3x14W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power		15W	1	0.28	10741
Source Flux		1793lm	2	0.55	2685
Fixture Flux		1316lm	3	0.83	1193
Efficacy		91lm/W	4	1.11	671
TS1168	Imax=5990cd/klm	Imax	10741cd	5	1.39	430

Driver	Colour	3000K	4000K
EL.	○	**1T7323EL**	**1T7326EL**
EL.	◐	**1T7329EL**	**1T7332EL**
EL.	●	**1T7335EL**	**1T7338EL**
DALI	○	**1T7323DA**	**1T7326DA**
DALI	◐	**1T7329DA**	**1T7332DA**
DALI	●	**1T7335DA**	**1T7338DA**

LED / 3x14W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power		15W	1	0.56	4410
Source Flux		1793lm	2	1.12	1102
Fixture Flux		1386lm	3	1.67	490
Efficacy		96lm/W	4	2.23	276
TS813	Imax=2460cd/klm	Imax	4410cd	5	2.79	176

Driver	Colour	3000K	4000K
EL.	○	**1T7324EL**	**1T7327EL**
EL.	◐	**1T7330EL**	**1T7333EL**
EL.	●	**1T7336EL**	**1T7339EL**
DALI	○	**1T7324DA**	**1T7327DA**
DALI	◐	**1T7330DA**	**1T7333DA**
DALI	●	**1T7336DA**	**1T7339DA**

LED / 3x14W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power		15W	1	0.88	2457
Source Flux		1793lm	2	1.77	614
Fixture Flux		1373lm	3	2.65	273
Efficacy		95lm/W	4	3.53	154
TS1170	Imax=1378cd/klm	Imax	2471cd	5	4.41	98

Driver	Colour	3000K	4000K
EL.	○	**1T7325EL**	**1T7328EL**
EL.	◐	**1T7331EL**	**1T7334EL**
EL.	●	**1T7337EL**	**1T7340EL**
DALI	○	**1T7325DA**	**1T7328DA**
DALI	◐	**1T7331DA**	**1T7334DA**
DALI	●	**1T7337DA**	**1T7340DA**

LOGICO



System Ceiling/ Suspension - spot module L. 281mm



LED / 11,5W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
	Fixture Power	13W	1	0.20	18466
	Source Flux	1487lm	2	0.40	4617
	Fixture Flux	1107lm	3	0.60	2052
	Efficacy	84lm/W	4	0.79	1154
	Imax	18466cd	5	0.99	739

	Driver	Colour	3000K	4000K
	EL.	○	**1T7349EL**	**1T7350EL**
	EL.	◐	**1T7351EL**	**1T7352EL**
	EL.	●	**1T7353EL**	**1T7354EL**
	DALI	○	**1T7349DA**	**1T7350DA**
	DALI	◐	**1T7351DA**	**1T7352DA**
	DALI	●	**1T7353DA**	**1T7354DA**



System Ceiling/ Suspension - spot module L. 562mm



LED / 23W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
	Fixture Power	26W	1	0.20	36933
	Source Flux	2973lm	2	0.40	9233
	Fixture Flux	2214lm	3	0.60	4104
	Efficacy	85lm/W	4	0.79	2308
	Imax	36933cd	5	0.99	1477

	Driver	Colour	3000K	4000K
	EL.	○	**1T7363EL**	**1T7364EL**
	EL.	◐	**1T7365EL**	**1T7366EL**
	EL.	●	**1T7367EL**	**1T7368EL**
	DALI	○	**1T7363DA**	**1T7364DA**
	DALI	◐	**1T7365DA**	**1T7366DA**
	DALI	●	**1T7367DA**	**1T7368DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

LOGICO

System Ceiling/ Suspension - blind module L. 281mm



LINEAR

Colour	Code
○	**1T7385**
◐	**1T7390**
◌	**1T7395**



System Ceiling/ Suspension - blind module L. 562mm



LINEAR

Colour	Code
○	**1T7386**
◐	**1T7391**
◌	**1T7396**



System Ceiling/ Suspension - blind module L connector



L CONNECTOR

Colour	Code
○	**1T7387**
◐	**1T7392**
◌	**1T7397**



System Ceiling/ Suspension - blind module T connector



T CONNECTOR

	Colour	Code
	○	**1T7388**
	◐	**1T7393**
	◐	**1T7398**



System Ceiling/ Suspension - blind module X connector



X CONNECTOR

	Colour	Code
	○	**1T7389**
	◐	**1T7394**
	◐	**1T7399**

Related codes

End Caps

Colour	Code
○	**1T5937**
●	**1T5938**
◍	**1T5939**

End caps for Ceiling Mounted, Suspension and Trimless versions.
2X

Mounting System



Colour	Code
○	**1T5912**
●	**1T5913**
◍	**1T5914**

Ceiling installation: polycarbonate bracket.
To be ordered in the following quantities for every fixture length:1 for 281mm version, 2 for the 562 / 1122 / 1135 / 1682 / 1695mm version, 3 for the 3364 / 3377mm version, 3 for the L/T version and 4 for the X version.



Colour	Code
○	**1T6919**
◑	**1T6920**
◍	**1T6921**

Wall installation: painted metal bracket.
To be ordered in the following quantities for every fixture length: 1 for the 281mm version, 2 for the 562 / 1122 / 1135 / 1682 / 1695mm version and 3 for the 3364 / 3377mm version.

Suspension

L	Colour	Code
2000	○	**1T5899**
2000	●	**1T5900**
2000	◍	**1T5901**
4000	○	**1T5902**
4000	●	**1T5903**
4000	◍	**1T5904**

Suspension cable.
To be ordered in the following quantities for every fixture length:1 for 281mm version, 2 for the 562 / 1122 / 1135 / 1682 / 1695mm version, 3 for the 3364 / 3377mm version, 3 for the L/T version and 4 for the X version.
Suspension cable compatible with ceiling or wall installations, even inclined.

Power Supply Kit



L	Driver	Colour	Code
4000	EL.	○	**1T5905EL**
4000	EL.	◑	**1T5906EL**
4000	EL.	◍	**1T5907EL**
4000	DALI	○	**1T5905DA**
4000	DALI	◑	**1T5906DA**
4000	DALI	◍	**1T5907DA**

Suspension installation kit: power cable complete with a painted polycarbonate rosette.
Max 0.6kW.

Accessories

Screen



	Code
	1T6502

Accessory designed to improve the visual comfort of the Wall Washer version.
To be installed on a standard reflector.
Made of matte black painted aluminium.
280mm in length; to be ordered in the following quantities for every fixture length: 2 for the 562mm version, 4 for the 1122/1135/1146mm versions, 6 for the 1682/1695/1706mm versions and 12 for the 3364/3377/3386mm versions.

Electrical Connector

	Code
	1T5911

Linear electrical connector.
EL/DALI.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.



System Trimless Recessed - continuous light module L. 562mm



LED / 12W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		14W	1	2.66	451
Source Flux		1740lm	2	5.33	113
Fixture Flux		1185lm	3	7.99	50
Efficacy		85lm/W	4	10.65	28
TS991	Imax=259cd/klm	Imax	451cd	13.32	18

Driver	Colour	3000K	4000K
EL.	○	**1T6019EL**	**1T6020EL**
EL.	●	**1T6023EL**	**1T6024EL**
DALI	○	**1T6019DA**	**1T6020DA**
DALI	●	**1T6023DA**	**1T6024DA**

LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		27W	1	2.66	892
Source Flux		3440lm	2	5.33	223
Fixture Flux		2343lm	3	7.99	99
Efficacy		87lm/W	4	10.65	56
TS996	Imax=259cd/klm	Imax	892cd	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T6021EL**	**1T6022EL**
EL.	●	**1T6025EL**	**1T6026EL**
DALI	○	**1T6021DA**	**1T6022DA**
DALI	●	**1T6025DA**	**1T6026DA**

LED / 8W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		9W	1	1.51	556
Source Flux		1260lm	2	3.02	139
Fixture Flux		816lm	3	4.52	62
Efficacy		91lm/W	4	6.03	35
TS992	Imax=442cd/klm	Imax	556cd	7.54	22

Driver	Colour	3000K	4000K
EL.	○	**1T6813EL**	**1T6814EL**
EL.	●	**1T6815EL**	**1T6816EL**
DALI	○	**1T6813DA**	**1T6814DA**
DALI	●	**1T6815DA**	**1T6816DA**

LED / 12W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		14W	1	2.28	2.55	1400
Source Flux		1740lm	2	4.56	5.10	350
Fixture Flux		1369lm	3	6.84	7.64	156
Efficacy		98lm/W	4	9.12	10.19	88
TS993	Imax=1001cd/klm	Imax	1743cd	11.40	12.74	56

Driver	Colour	3000K	4000K
EL.	○	**1T6817EL**	**1T6818EL**
EL.	●	**1T6819EL**	**1T6820EL**
DALI	○	**1T6817DA**	**1T6818DA**
DALI	●	**1T6819DA**	**1T6820DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		27W	1	2.28	2.55	2768
Source Flux		3440lm	2	4.56	5.10	692
Fixture Flux		2707lm	3	6.84	7.64	308
Efficacy		100lm/W	4	9.12	10.19	173
TS997	Imax=1001cd/klm	Imax	3445cd	11.40	12.74	111

Driver	Colour	3000K	4000K
EL.	○	**1T6821EL**	**1T6822EL**
EL.	●	**1T6823EL**	**1T6824EL**
DALI	○	**1T6821DA**	**1T6822DA**
DALI	●	**1T6823DA**	**1T6824DA**

LOGICO



System Trimless Recessed - continuous light module L. 1122mm



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		27W	1	2.66	903
Source Flux		3480lm	2	5.33	226
Fixture Flux		2370lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS991	Imax=259cd/klm	903cd	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T5839EL**	**1T5840EL**
EL.	●	**1T5841EL**	**1T5842EL**
DALI	○	**1T5839DA**	**1T5840DA**
DALI	●	**1T5841DA**	**1T5842DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		54W	1	2.66	1785
Source Flux		6880lm	2	5.33	446
Fixture Flux		4685lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS996	Imax=259cd/klm	1785cd	5	13.32	71

Driver	Colour	3000K	4000K
EL.	○	**1T5843EL**	**1T5844EL**
EL.	●	**1T5845EL**	**1T5846EL**
DALI	○	**1T5843DA**	**1T5844DA**
DALI	●	**1T5845DA**	**1T5846DA**

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		18W	1	1.51	1113
Source Flux		2520lm	2	3.02	278
Fixture Flux		1631lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS992	Imax=442cd/klm	1113cd	5	7.54	45

Driver	Colour	3000K	4000K
EL.	○	**1T5847EL**	**1T5848EL**
EL.	●	**1T5849EL**	**1T5850EL**
DALI	○	**1T5847DA**	**1T5848DA**
DALI	●	**1T5849DA**	**1T5850DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		27W	1	2.28	2.55	2801
Source Flux		3480lm	2	4.56	5.10	700
Fixture Flux		2739lm	3	6.84	7.64	311
Efficacy		101lm/W	4	9.12	10.19	175
TS993	Imax=1001cd/klm	3485cd	5	11.40	12.74	112

Driver	Colour	3000K	4000K
EL.	○	**1T5851EL**	**1T5852EL**
EL.	●	**1T5853EL**	**1T5854EL**
DALI	○	**1T5851DA**	**1T5852DA**
DALI	●	**1T5853DA**	**1T5854DA**

LED / 48W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		54W	1	2.28	2.55	5537
Source Flux		6880lm	2	4.56	5.10	1384
Fixture Flux		5415lm	3	6.84	7.64	615
Efficacy		100lm/W	4	9.12	10.19	346
TS997	Imax=1001cd/klm	6890cd	5	11.40	12.74	221

Driver	Colour	3000K	4000K
EL.	○	**1T5855EL**	**1T5856EL**
EL.	●	**1T5857EL**	**1T5858EL**
DALI	○	**1T5855DA**	**1T5856DA**
DALI	●	**1T5857DA**	**1T5858DA**



System Trimless Recessed - continuous light module L. 1682mm



LED / 36W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	40W	1	2.66	1354
Source Flux	5220lm	2	5.33	338
Fixture Flux	3555lm	3	7.99	150
Efficacy	89lm/W	4	10.65	85
Imax	1354cd	5	13.32	54

TS991 Imax=259cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5859EL**	**1T5860EL**
EL.	●	**1T5861EL**	**1T5862EL**
DALI	○	**1T5859DA**	**1T5860DA**
DALI	●	**1T5861DA**	**1T5862DA**

LED / 72W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	81W	1	2.66	2677
Source Flux	10320lm	2	5.33	669
Fixture Flux	7028lm	3	7.99	297
Efficacy	87lm/W	4	10.65	167
Imax	2677cd	5	13.32	107

TS996 Imax=259cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5863EL**	**1T5864EL**
EL.	●	**1T5865EL**	**1T5866EL**
DALI	○	**1T5863DA**	**1T5864DA**
DALI	●	**1T5865DA**	**1T5866DA**

LED / 24W / DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	27W	1	1.51	1669
Source Flux	3780lm	2	3.02	417
Fixture Flux	2447lm	3	4.52	185
Efficacy	91lm/W	4	6.03	104
Imax	1669cd	5	7.54	67

TS992 Imax=442cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5867EL**	**1T5868EL**
EL.	●	**1T5869EL**	**1T5870EL**
DALI	○	**1T5867DA**	**1T5868DA**
DALI	●	**1T5869DA**	**1T5870DA**

LED / 36W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	40W	1	2.28	2.55	4201
Source Flux	5220lm	2	4.56	5.10	1050
Fixture Flux	4108lm	3	6.84	7.64	467
Efficacy	103lm/W	4	9.12	10.19	263
Imax	5228cd	5	11.40	12.74	168

TS993 Imax=1001cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5871EL**	**1T5872EL**
EL.	●	**1T5873EL**	**1T5874EL**
DALI	○	**1T5871DA**	**1T5872DA**
DALI	●	**1T5873DA**	**1T5874DA**

LED / 72W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	81W	1	2.28	2.55	8305
Source Flux	10320lm	2	4.56	5.10	2076
Fixture Flux	8122lm	3	6.84	7.64	923
Efficacy	100lm/W	4	9.12	10.19	519
Imax	10335cd	5	11.40	12.74	332

TS997 Imax=1001cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5875EL**	**1T5876EL**
EL.	●	**1T5877EL**	**1T5878EL**
DALI	○	**1T5875DA**	**1T5876DA**
DALI	●	**1T5877DA**	**1T5878DA**

LOGICO



System Trimless Recessed - continuous light module L. 3364mm



LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2708
Source Flux		10440lm	2	5.33	677
Fixture Flux		7110lm	3	7.99	301
Efficacy		88lm/W	4	10.65	169
TS991	Imax=259cd/klm	Imax	5	13.32	108

Driver	Colour	3000K	4000K
EL.	○	**1T5879EL**	**1T5880EL**
EL.	●	**1T5881EL**	**1T5882EL**
DALI	○	**1T5879DA**	**1T5880DA**
DALI	●	**1T5881DA**	**1T5882DA**

LED / 144W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		163W	1	2.66	5354
Source Flux		20640lm	2	5.33	1338
Fixture Flux		14056lm	3	7.99	595
Efficacy		86lm/W	4	10.65	335
TS996	Imax=259cd/klm	Imax	5	13.32	214

Driver	Colour	3000K	4000K
EL.	○	**1T5883EL**	**1T5884EL**
EL.	●	**1T5885EL**	**1T5886EL**
DALI	○	**1T5883DA**	**1T5884DA**
DALI	●	**1T5885DA**	**1T5886DA**

LED / 48W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		54W	1	1.51	3338
Source Flux		7560lm	2	3.02	834
Fixture Flux		4894lm	3	4.52	371
Efficacy		91lm/W	4	6.03	209
TS992	Imax=442cd/klm	Imax	5	7.54	134

Driver	Colour	3000K	4000K
EL.	○	**1T5887EL**	**1T5888EL**
EL.	●	**1T5889EL**	**1T5890EL**
DALI	○	**1T5887DA**	**1T5888DA**
DALI	●	**1T5889DA**	**1T5890DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		81W	1	2.28	2.55	8402
Source Flux		10440lm	2	4.56	5.10	2101
Fixture Flux		8216lm	3	6.84	7.64	934
Efficacy		101lm/W	4	9.12	10.19	525
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	336

Driver	Colour	3000K	4000K
EL.	○	**1T5891EL**	**1T5892EL**
EL.	●	**1T5893EL**	**1T5894EL**
DALI	○	**1T5891DA**	**1T5892DA**
DALI	●	**1T5893DA**	**1T5894DA**

LED / 144W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		163W	1	2.28	2.55	16611
Source Flux		20640lm	2	4.56	5.10	4153
Fixture Flux		16244lm	3	6.84	7.64	1846
Efficacy		100lm/W	4	9.12	10.19	1038
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	664

Driver	Colour	3000K	4000K
EL.	○	**1T5895EL**	**1T5896EL**
EL.	●	**1T5897EL**	**1T5898EL**
DALI	○	**1T5895DA**	**1T5896DA**
DALI	●	**1T5897DA**	**1T5898DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

System Trimless Recessed - projector module Label 4



LED / 1x8W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power		9W	1	0.31	4214
Source Flux		982lm	2	0.62	1053
Fixture Flux		622lm	3	0.93	468
Efficacy		71lm/W	4	1.24	263
TS1165	Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Driver	Colour	3000K	4000K
EL.	○	**1T7197EL**	**1T7200EL**
EL.	●	**1T7203EL**	**1T7206EL**
DALI	○	**1T7197DA**	**1T7200DA**
DALI	●	**1T7203DA**	**1T7206DA**

LED / 1x8W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.48	3199
Source Flux		1129lm	2	0.95	800
Fixture Flux		806lm	3	1.43	355
Efficacy		92lm/W	4	1.91	200
TS1166	Imax=2834cd/klm	Imax	3199cd	5	2.38	128

Driver	Colour	3000K	4000K
EL.	○	**1T7198EL**	**1T7201EL**
EL.	●	**1T7204EL**	**1T7207EL**
DALI	○	**1T7198DA**	**1T7201DA**
DALI	●	**1T7204DA**	**1T7207DA**

LED / 1x8W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power		9W	1	0.76	1831
Source Flux		1129lm	2	1.52	458
Fixture Flux		835lm	3	2.28	203
Efficacy		95lm/W	4	3.04	114
TS1167	Imax=1622cd/klm	Imax	1831cd	5	3.80	73

Driver	Colour	3000K	4000K
EL.	○	**1T7199EL**	**1T7202EL**
EL.	●	**1T7205EL**	**1T7208EL**
DALI	○	**1T7199DA**	**1T7202DA**
DALI	●	**1T7205DA**	**1T7208DA**

System Trimless Recessed - projector module Label 4



LED / 3x8W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power		9W	1	0.31	4214
Source Flux		982lm	2	0.62	1053
Fixture Flux		622lm	3	0.93	468
Efficacy		71lm/W	4	1.24	263
TS1165	Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Driver	Colour	3000K	4000K
EL.	○	**1T7209EL**	**1T7212EL**
EL.	●	**1T7215EL**	**1T7218EL**
DALI	○	**1T7209DA**	**1T7212DA**
DALI	●	**1T7215DA**	**1T7218DA**

LOGICO

LED / 3x8W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power	9W	1		0.48	3199
Source Flux	1129lm	2		0.95	800
Fixture Flux	806lm	3		1.43	355
Efficacy	92lm/W	4		1.91	200
Imax	3199cd	5		2.38	128

TS1166 Imax=2834cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7210EL**	**1T7213EL**
EL.	●	**1T7216EL**	**1T7219EL**
DALI	○	**1T7210DA**	**1T7213DA**
DALI	●	**1T7216DA**	**1T7219DA**

LED / 3x8W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power	9W	1		0.76	1831
Source Flux	1129lm	2		1.52	458
Fixture Flux	835lm	3		2.28	203
Efficacy	95lm/W	4		3.04	114
Imax	1831cd	5		3.80	73

TS1167 Imax=1622cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7211EL**	**1T7214EL**
EL.	●	**1T7217EL**	**1T7220EL**
DALI	○	**1T7211DA**	**1T7214DA**
DALI	●	**1T7217DA**	**1T7220DA**

System Trimless Recessed - projector module Label 6



LED / 1x14W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power	15W	1		0.28	10741
Source Flux	1793lm	2		0.55	2685
Fixture Flux	1316lm	3		0.83	1193
Efficacy	91lm/W	4		1.11	671
Imax	10741cd	5		1.39	430

TS1168 Imax=5990cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7281EL**	**1T7284EL**
EL.	●	**1T7287EL**	**1T7290EL**
DALI	○	**1T7281DA**	**1T7284DA**
DALI	●	**1T7287DA**	**1T7290DA**

LED / 1x14W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power	15W	1		0.56	4410
Source Flux	1793lm	2		1.12	1102
Fixture Flux	1386lm	3		1.67	490
Efficacy	96lm/W	4		2.23	276
Imax	4410cd	5		2.79	176

TS813 Imax=2460cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7282EL**	**1T7285EL**
EL.	●	**1T7288EL**	**1T7291EL**
DALI	○	**1T7282DA**	**1T7285DA**
DALI	●	**1T7288DA**	**1T7291DA**

LED / 1x14W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power	15W	1		0.88	2457
Source Flux	1793lm	2		1.77	614
Fixture Flux	1373lm	3		2.65	273
Efficacy	95lm/W	4		3.53	154
Imax	2471cd	5		4.41	98

TS1170 Imax=1378cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T7283EL**	**1T7286EL**
EL.	●	**1T7289EL**	**1T7292EL**
DALI	○	**1T7283DA**	**1T7286DA**
DALI	●	**1T7289DA**	**1T7292DA**

System Trimless Recessed - projector module Label 6



LED / 3x14W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power		15W	1	0.28	10741
Source Flux		1793lm	2	0.55	2685
Fixture Flux		1316lm	3	0.83	1193
Efficacy		91lm/W	4	1.11	671
TS1168	Imax=5990cd/klm	Imax	10741cd	5	1.39	430

Driver	Colour	3000K	4000K
EL.	○	**1T7293EL**	**1T7296EL**
EL.	●	**1T7299EL**	**1T7302EL**
DALI	○	**1T7293DA**	**1T7296DA**
DALI	●	**1T7299DA**	**1T7302DA**

LED / 3x14W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power		15W	1	0.56	4410
Source Flux		1793lm	2	1.12	1102
Fixture Flux		1386lm	3	1.67	490
Efficacy		96lm/W	4	2.23	276
TS813	Imax=2460cd/klm	Imax	4410cd	5	2.79	176

Driver	Colour	3000K	4000K
EL.	○	**1T7294EL**	**1T7297EL**
EL.	●	**1T7300EL**	**1T7303EL**
DALI	○	**1T7294DA**	**1T7297DA**
DALI	●	**1T7300DA**	**1T7303DA**

LED / 3x14W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power		15W	1	0.88	2457
Source Flux		1793lm	2	1.77	614
Fixture Flux		1373lm	3	2.65	273
Efficacy		95lm/W	4	3.53	154
TS1170	Imax=1378cd/klm	Imax	2471cd	5	4.41	98

Driver	Colour	3000K	4000K
EL.	○	**1T7295EL**	**1T7298EL**
EL.	●	**1T7301EL**	**1T7304EL**
DALI	○	**1T7295DA**	**1T7298DA**
DALI	●	**1T7301DA**	**1T7304DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

The photometrics refer to individual projectors.



System Trimless Recessed - spot module L. 281mm



LED / 11,5W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
	Fixture Power	13W	1	0.20	18466
	Source Flux	1487lm	2	0.40	4617
	Fixture Flux	1107lm	3	0.60	2052
	Efficacy	84lm/W	4	0.79	1154
	Imax	18466cd	5	0.99	739

Driver	Colour	3000K	4000K
EL.	○	**1T7345EL**	**1T7346EL**
EL.	●	**1T7347EL**	**1T7348EL**
DALI	○	**1T7345DA**	**1T7346DA**
DALI	●	**1T7347DA**	**1T7348DA**

System Trimless Recessed - spot module L. 562mm



LED / 23W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
	Fixture Power	26W	1	0.20	36933
	Source Flux	2973lm	2	0.40	9233
	Fixture Flux	2214lm	3	0.60	4104
	Efficacy	85lm/W	4	0.79	2308
	Imax	36933cd	5	0.99	1477

Driver	Colour	3000K	4000K
EL.	○	**1T7359EL**	**1T7360EL**
EL.	●	**1T7361EL**	**1T7362EL**
DALI	○	**1T7359DA**	**1T7360DA**
DALI	●	**1T7361DA**	**1T7362DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

System Trimless Recessed - blind module L. 281mm



LINEAR

Colour	Code
○	**1T7381**
◐	**1T7383**



System Trimless Recessed - blind module L. 562mm



LINEAR

Colour	Code
○	**1T7382**
◐	**1T7384**

Related codes

Insertion Box



Kg	Cutout hole	L	Code
1.25	80x281	281	**1T7369**
1.8	80x562	562	**1T6051**
3.2	80x1122	1122	**1T5915**
3.8	80x1682	1682	**1T5916**

Outer casing for recessed and semi-recessed trimless installation.



Kg	Cutout hole	L	Code
1.3	80x291	306	**1T7370**
1.9	80x572	587	**1T6052**
3.2	80x1132	1147	**1T5917**
3.8	80x1692	1707	**1T5921**

Terminal outer casing for recessed and semi-recessed trimless installation.

End Caps

Colour	Code
○	**1T5937**
●	**1T5938**

End caps for Ceiling Mounted, Suspension and Trimless versions.
2X

Accessories

Screen



Code
1T6502

Accessory designed to improve the visual comfort of the Wall Washer version.
To be installed on a standard reflector.
Made of matte black painted aluminium.
280mm in length; to be ordered in the following quantities for every fixture length: 2 for the 562mm version, 4 for the 1122/1135/1146mm versions, 6 for the 1682/1695/1706mm versions and 12 for the 3364/3377/3386mm versions.

Electrical Connector

Code
1T5911

Linear electrical connector.
EL/DALI.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

LOGICO

System Recessed with flange - continuous light module L. 562mm



LED / 12W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	14W	1	2.66	451
Source Flux	1740lm	2	5.33	113
Fixture Flux	1185lm	3	7.99	50
Efficacy	85lm/W	4	10.65	28
TS991 Imax=259cd/klm	Imax 451cd	5	13.32	18

Driver	Colour	3000K	4000K
EL.	◯	**1T6015EL**	**1T6016EL**
DALI	◯	**1T6015DA**	**1T6016DA**

LED / 24W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	27W	1	2.66	892
Source Flux	3440lm	2	5.33	223
Fixture Flux	2343lm	3	7.99	99
Efficacy	87lm/W	4	10.65	56
TS996 Imax=259cd/klm	Imax 892cd	5	13.32	36

Driver	Colour	3000K	4000K
EL.	◯	**1T6017EL**	**1T6018EL**
DALI	◯	**1T6017DA**	**1T6018DA**

LED / 8W / DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	9W	1	1.51	556
Source Flux	1260lm	2	3.02	139
Fixture Flux	816lm	3	4.52	62
Efficacy	91lm/W	4	6.03	35
TS992 Imax=442cd/klm	Imax 556cd	5	7.54	22

Driver	Colour	3000K	4000K
EL.	◯	**1T6807EL**	**1T6808EL**
DALI	◯	**1T6807DA**	**1T6808DA**

LED / 12W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	14W	1	2.28	2.55	1400
Source Flux	1740lm	2	4.56	5.10	350
Fixture Flux	1369lm	3	6.84	7.64	156
Efficacy	98lm/W	4	9.12	10.19	88
TS993 Imax=1001cd/klm	Imax 1743cd	5	11.40	12.74	56

Driver	Colour	3000K	4000K
EL.	◯	**1T6809EL**	**1T6810EL**
DALI	◯	**1T6809DA**	**1T6810DA**

LED / 24W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	27W	1	2.28	2.55	2768
Source Flux	3440lm	2	4.56	5.10	692
Fixture Flux	2707lm	3	6.84	7.64	308
Efficacy	100lm/W	4	9.12	10.19	173
TS997 Imax=1001cd/klm	Imax 3445cd	5	11.40	12.74	111

Driver	Colour	3000K	4000K
EL.	◯	**1T6811EL**	**1T6812EL**
DALI	◯	**1T6811DA**	**1T6812DA**

LOGICO

System Recessed with flange - continuous light module L. 1122mm



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	27W		1	2.66	903
Source Flux	3480lm		2	5.33	226
Fixture Flux	2370lm		3	7.99	100
Efficacy	88lm/W		4	10.65	56
TS991	Imax=259cd/klm	Imax	5	13.32	36

Driver	Colour	3000K	4000K
EL.	◯	**1T5461EL**	**1T5462EL**
DALI	◯	**1T5461DA**	**1T5462DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	54W		1	2.66	1785
Source Flux	6880lm		2	5.33	446
Fixture Flux	4685lm		3	7.99	198
Efficacy	87lm/W		4	10.65	112
TS996	Imax=259cd/klm	Imax	5	13.32	71

Driver	Colour	3000K	4000K
EL.	◯	**1T5463EL**	**1T5464EL**
DALI	◯	**1T5463DA**	**1T5464DA**

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	18W		1	1.51	1113
Source Flux	2520lm		2	3.02	278
Fixture Flux	1631lm		3	4.52	124
Efficacy	91lm/W		4	6.03	70
TS992	Imax=442cd/klm	Imax	5	7.54	45

Driver	Colour	3000K	4000K
EL.	◯	**1T5465EL**	**1T5466EL**
DALI	◯	**1T5465DA**	**1T5466DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	27W		1	2.28	2.55	2801
Source Flux	3480lm		2	4.56	5.10	700
Fixture Flux	2739lm		3	6.84	7.64	311
Efficacy	101lm/W		4	9.12	10.19	175
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	112

Driver	Colour	3000K	4000K
EL.	◯	**1T5467EL**	**1T5468EL**
DALI	◯	**1T5467DA**	**1T5468DA**

LED / 48W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	54W		1	2.28	2.55	5537
Source Flux	6880lm		2	4.56	5.10	1384
Fixture Flux	5415lm		3	6.84	7.64	615
Efficacy	100lm/W		4	9.12	10.19	346
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	221

Driver	Colour	3000K	4000K
EL.	◯	**1T5469EL**	**1T5470EL**
DALI	◯	**1T5469DA**	**1T5470DA**

LOGICO

System Recessed with flange - continuous light module L. 1682mm



LED / 36W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	40W		1	2.66	1354
Source Flux	5220lm		2	5.33	338
Fixture Flux	3555lm		3	7.99	150
Efficacy	89lm/W		4	10.65	85
TS991	Imax=259cd/klm	Imax	5	13.32	54

Driver	Colour	3000K	4000K
EL.	◯	**1T5471EL**	**1T5472EL**
DALI	◯	**1T5471DA**	**1T5472DA**

LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	81W		1	2.66	2677
Source Flux	10320lm		2	5.33	669
Fixture Flux	7028lm		3	7.99	297
Efficacy	87lm/W		4	10.65	167
TS996	Imax=259cd/klm	Imax	5	13.32	107

Driver	Colour	3000K	4000K
EL.	◯	**1T5473EL**	**1T5474EL**
DALI	◯	**1T5473DA**	**1T5474DA**

LED / 24W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	27W		1	1.51	1669
Source Flux	3780lm		2	3.02	417
Fixture Flux	2447lm		3	4.52	185
Efficacy	91lm/W		4	6.03	104
TS992	Imax=442cd/klm	Imax	5	7.54	67

Driver	Colour	3000K	4000K
EL.	◯	**1T5475EL**	**1T5476EL**
DALI	◯	**1T5475DA**	**1T5476DA**

LED / 36W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	40W		1	2.28	2.55	4201
Source Flux	5220lm		2	4.56	5.10	1050
Fixture Flux	4108lm		3	6.84	7.64	467
Efficacy	103lm/W		4	9.12	10.19	263
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	168

Driver	Colour	3000K	4000K
EL.	◯	**1T5477EL**	**1T5478EL**
DALI	◯	**1T5477DA**	**1T5478DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	81W		1	2.28	2.55	8305
Source Flux	10320lm		2	4.56	5.10	2076
Fixture Flux	8122lm		3	6.84	7.64	923
Efficacy	100lm/W		4	9.12	10.19	519
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	332

Driver	Colour	3000K	4000K
EL.	◯	**1T5479EL**	**1T5480EL**
DALI	◯	**1T5479DA**	**1T5480DA**

LOGICO

System Recessed with flange - continuous light module L. 3364mm



LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	81W		1	2.66	2708
Source Flux	10440lm		2	5.33	677
Fixture Flux	7110lm		3	7.99	301
Efficacy	88lm/W		4	10.65	169
TS991	Imax=259cd/klm	Imax	5	13.32	108

Driver	Colour	3000K	4000K
EL.	◯	**1T5481EL**	**1T5482EL**
DALI	◯	**1T5481DA**	**1T5482DA**

LED / 144W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power	163W		1	2.66	5354
Source Flux	20640lm		2	5.33	1338
Fixture Flux	14056lm		3	7.99	595
Efficacy	86lm/W		4	10.65	335
TS996	Imax=259cd/klm	Imax	5	13.32	214

Driver	Colour	3000K	4000K
EL.	◯	**1T5483EL**	**1T5484EL**
DALI	◯	**1T5483DA**	**1T5484DA**

LED / 48W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power	54W		1	1.51	3338
Source Flux	7560lm		2	3.02	834
Fixture Flux	4894lm		3	4.52	371
Efficacy	91lm/W		4	6.03	209
TS992	Imax=442cd/klm	Imax	5	7.54	134

Driver	Colour	3000K	4000K
EL.	◯	**1T5485EL**	**1T5486EL**
DALI	◯	**1T5485DA**	**1T5486DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	81W		1	2.28	2.55	8402
Source Flux	10440lm		2	4.56	5.10	2101
Fixture Flux	8216lm		3	6.84	7.64	934
Efficacy	101lm/W		4	9.12	10.19	525
TS993	Imax=1001cd/klm	Imax	5	11.40	12.74	336

Driver	Colour	3000K	4000K
EL.	◯	**1T5487EL**	**1T5488EL**
DALI	◯	**1T5487DA**	**1T5488DA**

LED / 144W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power	163W		1	2.28	2.55	16611
Source Flux	20640lm		2	4.56	5.10	4153
Fixture Flux	16244lm		3	6.84	7.64	1846
Efficacy	100lm/W		4	9.12	10.19	1038
TS997	Imax=1001cd/klm	Imax	5	11.40	12.74	664

Driver	Colour	3000K	4000K
EL.	◯	**1T5489EL**	**1T5490EL**
DALI	◯	**1T5489DA**	**1T5490DA**

System Recessed with flange - continuous light module L connector



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		27W	1	2.66	903
Source Flux		3480lm	2	5.33	226
Fixture Flux		2370lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS991	Imax=259cd/klm	Imax	5	13.32	36

Driver	Colour	3000K	4000K
EL.	◯	**1T5940EL**	**1T5941EL**
DALI	◯	**1T5940DA**	**1T5941DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		54W	1	2.66	1785
Source Flux		6880lm	2	5.33	446
Fixture Flux		4685lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS996	Imax=259cd/klm	Imax	5	13.32	71

Driver	Colour	3000K	4000K
EL.	◯	**1T5942EL**	**1T5943EL**
DALI	◯	**1T5942DA**	**1T5943DA**

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		18W	1	1.51	1113
Source Flux		2520lm	2	3.02	278
Fixture Flux		1631lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS992	Imax=442cd/klm	Imax	5	7.54	45

Driver	Colour	3000K	4000K
EL.	◯	**1T6849EL**	**1T6850EL**
DALI	◯	**1T6849DA**	**1T6850DA**



System Recessed with flange - continuous light module T connector



LED / 36W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		40W	1	2.66	1354
Source Flux		5220lm	2	5.33	338
Fixture Flux		3555lm	3	7.99	150
Efficacy		89lm/W	4	10.65	85
TS991	Imax=259cd/klm	Imax	5	13.32	54

Driver	Colour	3000K	4000K
EL.	◯	**1T5944EL**	**1T5945EL**
DALI	◯	**1T5944DA**	**1T5945DA**

LOGICO

LED / 72W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	81W	1	2.66	2677
Source Flux	10320lm	2	5.33	669
Fixture Flux	7028lm	3	7.99	297
Efficacy	87lm/W	4	10.65	167
TS996 Imax=259cd/klm	Imax 2677cd	5	13.32	107

Driver	Colour	3000K	4000K
EL.	◯	**1T5946EL**	**1T5947EL**
DALI	◯	**1T5946DA**	**1T5947DA**

LED / 24W / DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	27W	1	1.51	1669
Source Flux	3780lm	2	3.02	417
Fixture Flux	2447lm	3	4.52	185
Efficacy	91lm/W	4	6.03	104
TS992 Imax=442cd/klm	Imax 1669cd	5	7.54	67

Driver	Colour	3000K	4000K
EL.	◯	**1T6851EL**	**1T6852EL**
DALI	◯	**1T6851DA**	**1T6852DA**



System Recessed with flange - continuous light module X connector



LED / 48W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	54W	1	2.66	1805
Source Flux	6960lm	2	5.33	451
Fixture Flux	4740lm	3	7.99	201
Efficacy	88lm/W	4	10.65	113
TS991 Imax=259cd/klm	Imax 1805cd	5	13.32	72

Driver	Colour	3000K	4000K
EL.	◯	**1T5948EL**	**1T5949EL**
DALI	◯	**1T5948DA**	**1T5949DA**

LED / 96W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	108W	1	2.66	3569
Source Flux	13760lm	2	5.33	892
Fixture Flux	9371lm	3	7.99	397
Efficacy	87lm/W	4	10.65	223
TS996 Imax=259cd/klm	Imax 3569cd	5	13.32	143

Driver	Colour	3000K	4000K
EL.	◯	**1T5950EL**	**1T5951EL**
DALI	◯	**1T5950DA**	**1T5951DA**

LED / 36W / DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	40W	1	1.51	2225
Source Flux	5040lm	2	3.02	556
Fixture Flux	3263lm	3	4.52	247
Efficacy	82lm/W	4	6.03	139
TS992 Imax=442cd/klm	Imax 2225cd	5	7.54	89

Driver	Colour	3000K	4000K
EL.	◯	**1T6853EL**	**1T6854EL**
DALI	◯	**1T6853DA**	**1T6854DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

System Recessed with flange - projector module Label 4



LED / 1x8W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power		9W	1	0.31	4214
Source Flux		982lm	2	0.62	1053
Fixture Flux		622lm	3	0.93	468
Efficacy		71lm/W	4	1.24	263
TS1165	Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Driver	Colour	3000K	4000K
EL.	◯	**1T7173EL**	**1T7176EL**
DALI	◯	**1T7173DA**	**1T7176DA**

LED / 1x8W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power		9W	1	0.48	3199
Source Flux		1129lm	2	0.95	800
Fixture Flux		806lm	3	1.43	355
Efficacy		92lm/W	4	1.91	200
TS1166	Imax=2834cd/klm	Imax	3199cd	5	2.38	128

Driver	Colour	3000K	4000K
EL.	◯	**1T7174EL**	**1T7177EL**
DALI	◯	**1T7174DA**	**1T7177DA**

LED / 1x8W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power		9W	1	0.76	1831
Source Flux		1129lm	2	1.52	458
Fixture Flux		835lm	3	2.28	203
Efficacy		95lm/W	4	3.04	114
TS1167	Imax=1622cd/klm	Imax	1831cd	5	3.80	73

Driver	Colour	3000K	4000K
EL.	◯	**1T7175EL**	**1T7178EL**
DALI	◯	**1T7175DA**	**1T7178DA**

System Recessed with flange - projector module Label 4



LED / 3x8W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power		9W	1	0.31	4214
Source Flux		982lm	2	0.62	1053
Fixture Flux		622lm	3	0.93	468
Efficacy		71lm/W	4	1.24	263
TS1165	Imax=4291cd/klm	Imax	4214cd	5	1.55	169

Driver	Colour	3000K	4000K
EL.	◯	**1T7185EL**	**1T7188EL**
DALI	◯	**1T7185DA**	**1T7188DA**

LOGICO

LED / 3x8W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			27°	
Fixture Power	9W		1	0.48	3199
Source Flux	1129lm		2	0.95	800
Fixture Flux	806lm		3	1.43	355
Efficacy	92lm/W		4	1.91	200
TS1166	Imax=2834cd/klm	Imax	3199cd	5	2.38	128

Driver	Colour	3000K	4000K
EL.	◯	**1T7186EL**	**1T7189EL**
DALI	◯	**1T7186DA**	**1T7189DA**

LED / 3x8W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			42°	
Fixture Power	9W		1	0.76	1831
Source Flux	1129lm		2	1.52	458
Fixture Flux	835lm		3	2.28	203
Efficacy	95lm/W		4	3.04	114
TS1167	Imax=1622cd/klm	Imax	1831cd	5	3.80	73

Driver	Colour	3000K	4000K
EL.	◯	**1T7187EL**	**1T7190EL**
DALI	◯	**1T7187DA**	**1T7190DA**

System Recessed with flange - projector module Label 6



LED / 1x14W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power	15W		1	0.28	10741
Source Flux	1793lm		2	0.55	2685
Fixture Flux	1316lm		3	0.83	1193
Efficacy	91lm/W		4	1.11	671
TS1168	Imax=5990cd/klm	Imax	10741cd	5	1.39	430

Driver	Colour	3000K	4000K
EL.	◯	**1T7257EL**	**1T7260EL**
DALI	◯	**1T7257DA**	**1T7260DA**

LED / 1x14W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power	15W		1	0.56	4410
Source Flux	1793lm		2	1.12	1102
Fixture Flux	1386lm		3	1.67	490
Efficacy	96lm/W		4	2.23	276
TS813	Imax=2460cd/klm	Imax	4410cd	5	2.79	176

Driver	Colour	3000K	4000K
EL.	◯	**1T7258EL**	**1T7261EL**
DALI	◯	**1T7258DA**	**1T7261DA**

LED / 1x14W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power	15W		1	0.88	2457
Source Flux	1793lm		2	1.77	614
Fixture Flux	1373lm		3	2.65	273
Efficacy	95lm/W		4	3.53	154
TS1170	Imax=1378cd/klm	Imax	2471cd	5	4.41	98

Driver	Colour	3000K	4000K
EL.	◯	**1T7259EL**	**1T7262EL**
DALI	◯	**1T7259DA**	**1T7262DA**

System Recessed with flange - projector module Label 6



LED / 3x14W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			16°	
Fixture Power		15W	1	0.28	10741
Source Flux		1793lm	2	0.55	2685
Fixture Flux		1316lm	3	0.83	1193
Efficacy		91lm/W	4	1.11	671
TS1168	Imax=5990cd/klm	Imax	10741cd	5	1.39	430

Driver	Colour	3000K	4000K
EL.	◯	**1T7269EL**	**1T7272EL**
DALI	◯	**1T7269DA**	**1T7272DA**

LED / 3x14W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			31°	
Fixture Power		15W	1	0.56	4410
Source Flux		1793lm	2	1.12	1102
Fixture Flux		1386lm	3	1.67	490
Efficacy		96lm/W	4	2.23	276
TS813	Imax=2460cd/klm	Imax	4410cd	5	2.79	176

Driver	Colour	3000K	4000K
EL.	◯	**1T7270EL**	**1T7273EL**
DALI	◯	**1T7270DA**	**1T7273DA**

LED / 3x14W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			48°	
Fixture Power		15W	1	0.88	2457
Source Flux		1793lm	2	1.77	614
Fixture Flux		1373lm	3	2.65	273
Efficacy		95lm/W	4	3.53	154
TS1170	Imax=1378cd/klm	Imax	2471cd	5	4.41	98

Driver	Colour	3000K	4000K
EL.	◯	**1T7271EL**	**1T7274EL**
DALI	◯	**1T7271DA**	**1T7274DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

The photometrics refer to individual projectors.

LOGICO

System Recessed with flange - spot module L. 281mm



LED / 11,5W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
Fixture Power		13W	1	0.20	18466
Source Flux		1487lm	2	0.40	4617
Fixture Flux		1107lm	3	0.60	2052
Efficacy		84lm/W	4	0.79	1154
TS1178	Imax=12421cd/klm	Imax	18466cd	5	0.99	739

Driver	Colour	3000K	4000K
EL.	◯	**1T7341EL**	**1T7342EL**
DALI	◯	**1T7341DA**	**1T7342DA**

System Recessed with flange - spot module L. 562mm



LED / 23W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			11°	
Fixture Power		26W	1	0.20	36933
Source Flux		2973lm	2	0.40	9233
Fixture Flux		2214lm	3	0.60	4104
Efficacy		85lm/W	4	0.79	2308
TS1178	Imax=12421cd/klm	Imax	36933cd	5	0.99	1477

Driver	Colour	3000K	4000K
EL.	◯	**1T7355EL**	**1T7356EL**
DALI	◯	**1T7355DA**	**1T7356DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

LOGICO



System Recessed with flange - blind module L. 281mm



LINEAR

Colour	Code
◯	**1T7371**



System Recessed with flange - blind module L. 562mm



LINEAR

Colour	Code
◯	**1T7372**



System Recessed with flange - blind module L connector



L CONNECTOR

Colour	Code
◯	**1T7373**



System Recessed with flange - blind module T connector



T CONNECTOR

Colour	Code
◯	**1T7374**

System Recessed with flange - blind module X connector



X CONNECTOR

Colour	Code
◯	**1T7375**

Related codes

End Caps



	Code
	1T5908

End caps for the recessed version with a flange.
White.
2X

Accessories

Screen



	Code
	1T6502

Accessory designed to improve the visual comfort of the Wall Washer version.
To be installed on a standard reflector.
Made of matte black painted aluminium.
280mm in length; to be ordered in the following quantities for every fixture length: 2 for the 562mm version, 4 for the 1122/1135/1146mm versions, 6 for the 1682/1695/1706mm versions and 12 for the 3364/3377/3386mm versions.

Electrical Connector

	Code
	1T5911

Linear electrical connector.
EL/DALI.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

Ceilingand Suspensions luminaires

Indoor

Linear
Ceiling/Suspension

448
ISO

454
OMEGA

460
LOGICO SA
Ceiling/ Suspension
Opal/UGR/WW

468
CARTESIO

472
DIVA

476
SLIM Line

476
SLIM Rectangle

Ceiling/Suspension

482
OZ Stand Alone
Ceiling Large 3x

482
OZ Stand Alone
Ceiling Large 5x

490
THREESIXTY
Ø384mm
Opal/UGR/Halo

490
THREESIXTY
Ø590mm
Opal/UGR/Halo

490
THREESIXTY
Ø870mm
Opal/UGR/Hal

490
THREESIXTY
Ø1150mm
Opal/UGR/Halo

502
CCTLED
Pendant

504
CCTLED
Tube Smart

504
CCTLED
Tube Tech

504
CCTLED
Tube Feel

504
CCTLED
Tube Deep

514
BEBOP
Ceiling/
Suspension

516
GLOBO

518
WASABI

522
DECANTER

ISO

GENERAL INFO
Stand-alone linear LED fixture for suspension installation.
2144x70x73mm

LED
LED Engine made of linear boards
From 3300 to 7129lm
2700K – 3000K – 3500K – 4000K
Ra90

PRODUCT EFFICACY
Up to 121lm/W

OPTICS
Diffused light with an opal screen - Highly reflective brushed aluminium reflector and an opaline polycarbonate screen. Controlled light UGR<19 (EN-12464) - Optical system composed of a highly reflective brushed aluminium reflector and a transparent polycarbonate screen coupled with a micro prismatic plate and a spreader lens.

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Painted extruded aluminium body and a painted aluminium optical unit and terminal. Opaline polycarbonate or UGR screen.

ON DEMAND

Easy Custom Colour

110-277Vac
power supply

New suspension fixture for office and hospitality environments designed in close collaboration with the American firm Gensler. Available with direct or direct/indirect emission with two different effects: diffused light and controlled light UGR<19 (EN-12464) L65<3000 cd/m^2.

L=840mm central indirect lighting.

Also available in a version for ceiling installation.



Plus

Design
The union between the interpenetration of two solids produce a fixture with a recognisable yet discrete design, perfect to characterise modern spaces

Two optical systems
The two different optical systems it can use – OPAL and UGR – make it suitable for installation in OFFICE applications which are increasingly becoming open spaces, and in Hospitality projects which require not only visual comfort, but also attention to design and detail.



UGR<19 optic

The UGR version is focused entirely on visual comfort. The colour rendering index of CRI 90 and the perfect UGR screening allows for a pleasant and measured light.
The sophisticated optical system, comprised of a mirrored reflector and a particular prismatic screen, reduces the shadows and reflections that can cause disturbance on work surfaces, allowing for an unrestricted distribution of desks without having to bear in mind the position of the lighting units.

Opal optic

The diffused effect of ISO OPAL is the result of a mirrored reflector with an opal screen. The light emitted appears soft and widespread, particularly suitable for reception areas in offices, hotels and spaces. In the direct/indirect light version, a line of light is present on the upper part, complete with diffusing screen to provide even light on the ceiling.

ISO



Suspension L. 2144mm



LED / 35W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra90			106°	
Fixture Power	40W	1	2.66	1192
Source Flux	4594lm	2	5.33	298
Fixture Flux	3129lm	3	7.99	132
Efficacy	78lm/W	4	10.65	74
TS1206 Imax=259cd/klm	Imax	1192cd	5	13.32	48

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T7179EL**	**1T7180EL**	**1T7181EL**	**1T7182EL**
DALI		**1T7179DA**	**1T7180DA**	**1T7181DA**	**1T7182DA**

LED / 16W / DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra90			74°	
Fixture Power	18W	1	1.51	1469
Source Flux	3326lm	2	3.02	367
Fixture Flux	2153lm	3	4.52	163
Efficacy	118lm/W	4	6.03	92
TS1208 Imax=442cd/klm	Imax	1469cd	5	7.54	59

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T7193EL**	**1T7194EL**	**1T7195EL**	**1T7196EL**
DALI		**1T7193DA**	**1T7194DA**	**1T7195DA**	**1T7196DA**

LED / 54W / UP-DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra90			106°	
Fixture Power	61W	1	2.66	1214
Source Flux	6951lm	2	5.33	304
Fixture Flux	4724lm	3	7.99	135
Efficacy	77lm/W	4	10.66	76
TS1207 Imax=175cd/klm	Imax	1214cd	5	13.32	49

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T7183EL**	**1T7184EL**	**1T7191EL**	**1T7192EL**
DALI		**1T7183DA**	**1T7184DA**	**1T7191DA**	**1T7192DA**

LED / 36W / UP-DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra90			72°	
Fixture Power	41W	1	1.45	1484
Source Flux	4995lm	2	2.90	371
Fixture Flux	3283lm	3	4.34	165
Efficacy	80lm/W	4	5.79	93
TS1209 Imax=297cd/klm	Imax	1484cd	5	7.24	59

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T7263EL**	**1T7264EL**	**1T7265EL**	**1T7266EL**
DALI		**1T7263DA**	**1T7264DA**	**1T7265DA**	**1T7266DA**

Note

Power supply kit and suspension kit L=4000mm supplied with the product.

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

OMEGA

GENERAL INFO
Stand-alone linear LED fixture for surface or suspension installations.
2112x50x80mm
792x50x80mm
472x50x80mm

LED
LED Engine made of linear boards
From 1041lm to 4459lm
2700K – 3000K – 3500K – 4000K
Ra90

PRODUCT EFFICACY
Up to 91lm/W

OPTICS
Direct emission Opal

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Anodized and painted extruded aluminium body.
Injection-moulded opal polycarbonate screen.

ON DEMAND

Easy Custom Colour

110-277 vac
power supply

The result of the collaboration with the architectural and design firm Gensler, Omega is a range of fixtures for coordinated lighting of work and hospitality environments in particular for reception areas and common areas. Available in different sizes and application types for ceiling, suspension and wall installation. For the wall version L=792mm it is now possible to choose between a Hi-Power and Low-Power solution.

Plus

Design
The union between two pure shapes led to the development of a discrete, yet recognisable lighting fixture. A new 270° light emission that takes advantage of geometries and shapes and the interpenetration of two solids for a soft light that lights up the three-dimensionality of a space.

Suspension versions
The suspension versions are 2114 mm in length with a single direct point of emission, supplied complete with suspension kit.

Wall-mounted version

Wall versions are available in two different lengths (472mm and 792mm) and can be installed vertically or horizontally. They are ideal for lighting common areas and stairwells coordinated with general lighting supplied by longer versions.

The L=792mm version is available with both Hi-Power and Low-Power solutions.



OMEGA



Suspension L. 2112mm



LED / 24W / DOWN OPAL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			102°	164°	
Fixture Power	27W	1	2.45	14.31	526
Source Flux	4347lm	2	4.90	28.63	132
Fixture Flux	2371lm	3	7.35	42.94	58
Efficacy	88lm/W	4	9.80	57.25	33
TS1199 Imax=121cd/klm	Imax 526cd	5	12.25	71.57	21

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T7267EL**	**1T7268EL**	**1T7275EL**	**1T7276EL**
DALI		**1T7267DA**	**1T7268DA**	**1T7275DA**	**1T7276DA**

Applique L. 472mm



LED / 7,8W / DOWN OPAL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			101°	163°	
Fixture Power	9W	1	2.44	13.57	131
Source Flux	1046lm	2	4.87	27.14	33
Fixture Flux	589lm	3	7.31	40.70	15
Efficacy	66lm/W	4	9.74	54.27	8
TS1197 Imax=126cd/klm	Imax 132cd	5	12.18	67.84	5

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T7277EL**	**1T7278EL**	**1T7279EL**	**1T7280EL**
DALI		**1T7277DA**	**1T7278DA**	**1T7279DA**	**1T7280DA**

Applique L. 792mm



LED / 16W / DOWN OPAL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			101°	163°	
Fixture Power	18W	1	2.44	13.57	263
Source Flux	2092lm	2	4.87	27.14	66
Fixture Flux	1178lm	3	7.31	40.70	29
Efficacy	67lm/W	4	9.74	54.27	16
TS1198 Imax=126cd/klm	Imax 263cd	5	12.18	67.84	11

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T7343EL**	**1T7344EL**	**1T7357EL**	**1T7358EL**
DALI		**1T7343DA**	**1T7344DA**	**1T7357DA**	**1T7358DA**

OMEGA

LED / 23W / DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra90			126°	
Fixture Power	28W	1	3.90	361
Source Flux	2876lm	2	7.80	90
Fixture Flux	1620lm	3	11.70	40
Efficacy	58lm/W	4	15.60	23
TS1379 Imax=126cd/klm	Imax 361cd	5	19.50	14

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1T9519EL**	**1T9520EL**	**1T9521EL**	**1T9522EL**
DALI		**1T9519DA**	**1T9520DA**	**1T9521DA**	**1T9522DA**

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

LOGICO

Stand Alone Ceiling and Suspension luminaire

A versatile fixture available in three different lengths, each with Low- Power and High-Power lumen and different finishes and installation types.

It can be ceiling, wall or suspension installation if equipped with special accessories; is it is available with direct or direct/indirect diffused light, UGR<19 (EN-12464) L65<3000 cd/m^2 controlled light ideal for lighting workplaces or wall-washer for lighting large vertical surfaces. There are also versions available for recessed installation. In addition there are custom made solutions that are available on request: modules with custom made lengths, emergency modules and Tunable technology.

Emergency versions available on request after checking feasibility.

GENERAL INFO
Modules of variable lengths for ceiling, suspension, recessed and semi-recessed installations.
Lengths: 1135mm – 1695mm – 3377mm

LED
Linear Board LED engine
From 2520lm to 28960lm
3000K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 109lm/W

OPTICS
OPAL – UGR – WW

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Powder coated, extruded, calendered aluminium.

ON DEMAND

Tunable White

110-277Vac power supply



Zonamerica
Montevideo, Uruguay

Architect Estudio Dovat Arquitectos
Lighting Design Estudio Hofstadter

Photographer Ferrés - Cánepa

LOGICO



Stand Alone Ceiling/ Suspension L. 1135mm



LED / 24W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		27W	1	2.66	903
Source Flux		3480lm	2	5.33	226
Fixture Flux		2370lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS991	Imax=259cd/klm	Imax	903cd	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T5491EL**	**1T5492EL**
EL.	●	**1T5495EL**	**1T5496EL**
EL.	◍	**1T5493EL**	**1T5494EL**
DALI	○	**1T5491DA**	**1T5492DA**
DALI	●	**1T5495DA**	**1T5496DA**
DALI	◍	**1T5493DA**	**1T5494DA**

LED / 48W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		54W	1	2.66	1785
Source Flux		6880lm	2	5.33	446
Fixture Flux		4685lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS996	Imax=259cd/klm	Imax	1785cd	5	13.32	71

Driver	Colour	3000K	4000K
EL.	○	**1T5497EL**	**1T5498EL**
EL.	●	**1T5501EL**	**1T5502EL**
EL.	◍	**1T5499EL**	**1T5500EL**
DALI	○	**1T5497DA**	**1T5498DA**
DALI	●	**1T5501DA**	**1T5502DA**
DALI	◍	**1T5499DA**	**1T5500DA**

LED / 16W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		18W	1	1.51	1113
Source Flux		2520lm	2	3.02	278
Fixture Flux		1631lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS992	Imax=442cd/klm	Imax	1113cd	5	7.54	45

Driver	Colour	3000K	4000K
EL.	○	**1T5515EL**	**1T5516EL**
EL.	●	**1T5519EL**	**1T5520EL**
EL.	◍	**1T5517EL**	**1T5518EL**
DALI	○	**1T5515DA**	**1T5516DA**
DALI	●	**1T5519DA**	**1T5520DA**
DALI	◍	**1T5517DA**	**1T5518DA**

LED / 24W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		27W	1	2.28	2.55	2801
Source Flux		3480lm	2	4.56	5.10	700
Fixture Flux		2739lm	3	6.84	7.64	311
Efficacy		101lm/W	4	9.12	10.19	175
TS993	Imax=1001cd/klm	Imax	3485cd	5	11.40	12.74	112

Driver	Colour	3000K	4000K
EL.	○	**1T5527EL**	**1T5528EL**
EL.	●	**1T5531EL**	**1T5532EL**
EL.	◍	**1T5529EL**	**1T5530EL**
DALI	○	**1T5527DA**	**1T5528DA**
DALI	●	**1T5531DA**	**1T5532DA**
DALI	◍	**1T5529DA**	**1T5530DA**

LED / 48W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		54W	1	2.28	2.55	5537
Source Flux		6880lm	2	4.56	5.10	1384
Fixture Flux		5415lm	3	6.84	7.64	615
Efficacy		100lm/W	4	9.12	10.19	346
TS997	Imax=1001cd/klm	Imax	6890cd	5	11.40	12.74	221

Driver	Colour	3000K	4000K
EL.	○	**1T5533EL**	**1T5534EL**
EL.	●	**1T5537EL**	**1T5538EL**
EL.	◍	**1T5535EL**	**1T5536EL**
DALI	○	**1T5533DA**	**1T5534DA**
DALI	●	**1T5537DA**	**1T5538DA**
DALI	◍	**1T5535DA**	**1T5536DA**

LOGICO

LED / 42W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		47W	1	2.66	903
Source Flux		6090lm	2	5.33	226
Fixture Flux		4136lm	3	7.99	100
Efficacy		88lm/W	4	10.65	56
TS994	Imax=148cd/klm	Imax	903cd	5	13.32	36

Driver	Colour	3000K	4000K
EL.	○	**1T5503EL**	**1T5504EL**
EL.	◐	**1T5507EL**	**1T5508EL**
EL.	◐	**1T5505EL**	**1T5506EL**
DALI	○	**1T5503DA**	**1T5504DA**
DALI	◐	**1T5507DA**	**1T5508DA**
DALI	◐	**1T5505DA**	**1T5506DA**

LED / 66W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		74W	1	2.66	1785
Source Flux		9490lm	2	5.33	446
Fixture Flux		6452lm	3	7.99	198
Efficacy		87lm/W	4	10.65	112
TS998	Imax=188cd/klm	Imax	1785cd	5	13.32	71

Driver	Colour	3000K	4000K
EL.	○	**1T5509EL**	**1T5510EL**
EL.	◐	**1T5513EL**	**1T5514EL**
EL.	◐	**1T5511EL**	**1T5512EL**
DALI	○	**1T5509DA**	**1T5510DA**
DALI	◐	**1T5513DA**	**1T5514DA**
DALI	◐	**1T5511DA**	**1T5512DA**

LED / 28W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		32W	1	1.51	1113
Source Flux		4410lm	2	3.02	278
Fixture Flux		2912lm	3	4.52	124
Efficacy		91lm/W	4	6.03	70
TS995	Imax=252cd/klm	Imax	1113cd	5	7.54	45

Driver	Colour	3000K	4000K
EL.	○	**1T5521EL**	**1T5522EL**
EL.	◐	**1T5525EL**	**1T5526EL**
EL.	◐	**1T5523EL**	**1T5524EL**
DALI	○	**1T5521DA**	**1T5522DA**
DALI	◐	**1T5525DA**	**1T5526DA**
DALI	◐	**1T5523DA**	**1T5524DA**



Stand Alone Ceiling/ Suspension L. 1695mm



LED / 36W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		40W	1	2.66	1354
Source Flux		5220lm	2	5.33	338
Fixture Flux		3555lm	3	7.99	150
Efficacy		89lm/W	4	10.65	85
TS991	Imax=259cd/klm	Imax	1354cd	5	13.32	54

Driver	Colour	3000K	4000K
EL.	○	**1T5539EL**	**1T5540EL**
EL.	◐	**1T5543EL**	**1T5544EL**
EL.	◐	**1T5541EL**	**1T5542EL**
DALI	○	**1T5539DA**	**1T5540DA**
DALI	◐	**1T5543DA**	**1T5544DA**
DALI	◐	**1T5541DA**	**1T5542DA**

LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2677
Source Flux		10320lm	2	5.33	669
Fixture Flux		7028lm	3	7.99	297
Efficacy		87lm/W	4	10.65	167
TS996	Imax=259cd/klm	Imax	2677cd	5	13.32	107

Driver	Colour	3000K	4000K
EL.	○	**1T5545EL**	**1T5546EL**
EL.	◐	**1T5549EL**	**1T5550EL**
EL.	◐	**1T5547EL**	**1T5548EL**
DALI	○	**1T5545DA**	**1T5546DA**
DALI	◐	**1T5549DA**	**1T5550DA**
DALI	◐	**1T5547DA**	**1T5548DA**

LOGICO

LED / 24W / DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	27W	1	1.51	1669
Source Flux	3780lm	2	3.02	417
Fixture Flux	2447lm	3	4.52	185
Efficacy	91lm/W	4	6.03	104
Imax	1669cd	5	7.54	67

TS992 Imax=442cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5563EL**	**1T5564EL**
EL.	◐	**1T5567EL**	**1T5568EL**
EL.	●	**1T5565EL**	**1T5566EL**
DALI	○	**1T5563DA**	**1T5564DA**
DALI	◐	**1T5567DA**	**1T5568DA**
DALI	●	**1T5565DA**	**1T5566DA**

LED / 36W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	40W	1	2.28	2.55	4201
Source Flux	5220lm	2	4.56	5.10	1050
Fixture Flux	4108lm	3	6.84	7.64	467
Efficacy	103lm/W	4	9.12	10.19	263
Imax	5228cd	5	11.40	12.74	168

TS993 Imax=1001cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5575EL**	**1T5576EL**
EL.	◐	**1T5579EL**	**1T5580EL**
EL.	●	**1T5577EL**	**1T5578EL**
DALI	○	**1T5575DA**	**1T5576DA**
DALI	◐	**1T5579DA**	**1T5580DA**
DALI	●	**1T5577DA**	**1T5578DA**

LED / 72W / DOWN WW



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			97°	101°	
Fixture Power	81W	1	2.28	2.55	8305
Source Flux	10320lm	2	4.56	5.10	2076
Fixture Flux	8122lm	3	6.84	7.64	923
Efficacy	100lm/W	4	9.12	10.19	519
Imax	10335cd	5	11.40	12.74	332

TS997 Imax=1001cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5581EL**	**1T5582EL**
EL.	◐	**1T5585EL**	**1T5586EL**
EL.	●	**1T5583EL**	**1T5584EL**
DALI	○	**1T5581DA**	**1T5582DA**
DALI	◐	**1T5585DA**	**1T5586DA**
DALI	●	**1T5583DA**	**1T5584DA**

LED / 60W / UP-DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	68W	1	2.66	1290
Source Flux	8700lm	2	5.33	322
Fixture Flux	5909lm	3	7.99	143
Efficacy	87lm/W	4	10.65	81
Imax	1290cd	5	13.32	52

TS994 Imax=148cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5551EL**	**1T5552EL**
EL.	◐	**1T5555EL**	**1T5556EL**
EL.	●	**1T5553EL**	**1T5554EL**
DALI	○	**1T5551DA**	**1T5552DA**
DALI	◐	**1T5555DA**	**1T5556DA**
DALI	●	**1T5553DA**	**1T5554DA**

LED / 96W / UP-DOWN OPAL



3000K		H(m)	D(m)	Emax(lx)
Ra84			106°	
Fixture Power	107W	1	2.66	2595
Source Flux	13800lm	2	5.33	649
Fixture Flux	9382lm	3	7.99	288
Efficacy	88lm/W	4	10.65	162
Imax	2595cd	5	13.32	104

TS998 Imax=188cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5557EL**	**1T5558EL**
EL.	◐	**1T5561EL**	**1T5562EL**
EL.	●	**1T5559EL**	**1T5560EL**
DALI	○	**1T5557DA**	**1T5558DA**
DALI	◐	**1T5561DA**	**1T5562DA**
DALI	●	**1T5559DA**	**1T5560DA**

LED / 40W / UP-DOWN UGR



3000K		H(m)	D(m)	Emax(lx)
Ra84			74°	
Fixture Power	45W	1	1.51	1590
Source Flux	6300lm	2	3.02	398
Fixture Flux	4160lm	3	4.52	177
Efficacy	92lm/W	4	6.03	99
Imax	1590cd	5	7.54	64

TS995 Imax=252cd/klm

Driver	Colour	3000K	4000K
EL.	○	**1T5569EL**	**1T5570EL**
EL.	◐	**1T5573EL**	**1T5574EL**
EL.	●	**1T5571EL**	**1T5572EL**
DALI	○	**1T5569DA**	**1T5570DA**
DALI	◐	**1T5573DA**	**1T5574DA**
DALI	●	**1T5571DA**	**1T5572DA**

LOGICO



Stand Alone Ceiling/ Suspension L. 3377mm



LED / 72W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		81W	1	2.66	2708
Source Flux		10440lm	2	5.33	677
Fixture Flux		7110lm	3	7.99	301
Efficacy		88lm/W	4	10.65	169
TS991	Imax=259cd/klm	Imax	2708cd	5	13.32	108

Driver	Colour	3000K	4000K
EL.	○	**1T5587EL**	**1T5588EL**
EL.	◐	**1T5591EL**	**1T5592EL**
EL.	●	**1T5589EL**	**1T5590EL**
DALI	○	**1T5587DA**	**1T5588DA**
DALI	◐	**1T5591DA**	**1T5592DA**
DALI	●	**1T5589DA**	**1T5590DA**

LED / 144W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		163W	1	2.66	5354
Source Flux		20640lm	2	5.33	1338
Fixture Flux		14056lm	3	7.99	595
Efficacy		86lm/W	4	10.65	335
TS996	Imax=259cd/klm	Imax	5354cd	5	13.32	214

Driver	Colour	3000K	4000K
EL.	○	**1T5593EL**	**1T5594EL**
EL.	◐	**1T5597EL**	**1T5598EL**
EL.	●	**1T5595EL**	**1T5596EL**
DALI	○	**1T5593DA**	**1T5594DA**
DALI	◐	**1T5597DA**	**1T5598DA**
DALI	●	**1T5595DA**	**1T5596DA**

LED / 48W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		54W	1	1.51	3338
Source Flux		7560lm	2	3.02	834
Fixture Flux		4894lm	3	4.52	371
Efficacy		91lm/W	4	6.03	209
TS992	Imax=442cd/klm	Imax	3338cd	5	7.54	134

Driver	Colour	3000K	4000K
EL.	○	**1T5611EL**	**1T5612EL**
EL.	◐	**1T5615EL**	**1T5616EL**
EL.	●	**1T5613EL**	**1T5614EL**
DALI	○	**1T5611DA**	**1T5612DA**
DALI	◐	**1T5615DA**	**1T5616DA**
DALI	●	**1T5613DA**	**1T5614DA**

LED / 72W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		81W	1	2.28	2.55	8402
Source Flux		10440lm	2	4.56	5.10	2101
Fixture Flux		8216lm	3	6.84	7.64	934
Efficacy		101lm/W	4	9.12	10.19	525
TS993	Imax=1001cd/klm	Imax	10455cd	5	11.40	12.74	336

Driver	Colour	3000K	4000K
EL.	○	**1T5623EL**	**1T5624EL**
EL.	◐	**1T5627EL**	**1T5628EL**
EL.	●	**1T5625EL**	**1T5626EL**
DALI	○	**1T5623DA**	**1T5624DA**
DALI	◐	**1T5627DA**	**1T5628DA**
DALI	●	**1T5625DA**	**1T5626DA**

LED / 144W / DOWN WW



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			97°	101°	
Fixture Power		163W	1	2.28	2.55	16611
Source Flux		20640lm	2	4.56	5.10	4153
Fixture Flux		16244lm	3	6.84	7.64	1846
Efficacy		100lm/W	4	9.12	10.19	1038
TS997	Imax=1001cd/klm	Imax	20670cd	5	11.40	12.74	664

Driver	Colour	3000K	4000K
EL.	○	**1T5629EL**	**1T5630EL**
EL.	◐	**1T5633EL**	**1T5634EL**
EL.	●	**1T5631EL**	**1T5632EL**
DALI	○	**1T5629DA**	**1T5630DA**
DALI	◐	**1T5633DA**	**1T5634DA**
DALI	●	**1T5631DA**	**1T5632DA**

LOGICO

LED / 120W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		136W	1	2.66	2579
Source Flux		17400lm	2	5.33	645
Fixture Flux		11818lm	3	7.99	287
Efficacy		87lm/W	4	10.65	161
TS994	Imax=148cd/klm	Imax	5	13.32	103

Driver	Colour	3000K	4000K
EL.	○	**1T5599EL**	**1T5600EL**
EL.	◐	**1T5603EL**	**1T5604EL**
EL.	◐	**1T5601EL**	**1T5602EL**
DALI	○	**1T5599DA**	**1T5600DA**
DALI	◐	**1T5603DA**	**1T5604DA**
DALI	◐	**1T5601DA**	**1T5602DA**

LED / 192W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			106°	
Fixture Power		218W	1	2.66	5183
Source Flux		27560lm	2	5.33	1296
Fixture Flux		18736lm	3	7.99	576
Efficacy		86lm/W	4	10.65	324
TS998	Imax=188cd/klm	Imax	5	13.32	207

Driver	Colour	3000K	4000K
EL.	○	**1T5605EL**	**1T5606EL**
EL.	◐	**1T5609EL**	**1T5610EL**
EL.	◐	**1T5607EL**	**1T5608EL**
DALI	○	**1T5605DA**	**1T5606DA**
DALI	◐	**1T5609DA**	**1T5610DA**
DALI	◐	**1T5607DA**	**1T5608DA**

LED / 80W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			74°	
Fixture Power		91W	1	1.51	3181
Source Flux		12600lm	2	3.02	795
Fixture Flux		8320lm	3	4.52	353
Efficacy		91lm/W	4	6.03	199
TS995	Imax=252cd/klm	Imax	5	7.54	127

Driver	Colour	3000K	4000K
EL.	○	**1T5617EL**	**1T5618EL**
EL.	◐	**1T5621EL**	**1T5622EL**
EL.	◐	**1T5619EL**	**1T5620EL**
DALI	○	**1T5617DA**	**1T5618DA**
DALI	◐	**1T5621DA**	**1T5622DA**
DALI	◐	**1T5619DA**	**1T5620DA**

Note

Check mounting instructions to verify the quantity of DALI drivers installed.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Direct/indirect version: single switch.

Related codes

Mounting System



Colour	Code
○	**1T5912**
●	**1T5913**
◐	**1T5914**

Ceiling installation: polycarbonate bracket.
To be ordered in the following quantities for every fixture length:1 for 281mm version, 2 for the 562 / 1122 / 1135 / 1682 / 1695mm version, 3 for the 3364 / 3377mm version, 3 for the L/T version and 4 for the X version.



Colour	Code
○	**1T6919**
◐	**1T6920**
◐	**1T6921**

Wall installation: painted metal bracket.
To be ordered in the following quantities for every fixture length: 1 for the 281mm version, 2 for the 562 / 1122 / 1135 / 1682 / 1695mm version and 3 for the 3364 / 3377mm version.

LOGICO

Suspension

	L	Colour	Code
	2000	○	**1T5899**
	2000	●	**1T5900**
	2000	◍	**1T5901**
	4000	○	**1T5902**
	4000	●	**1T5903**
	4000	◍	**1T5904**

Suspension cable.
To be ordered in the following quantities for every fixture length:1 for 281mm version, 2 for the 562 / 1122 / 1135 / 1682 / 1695mm version, 3 for the 3364 / 3377mm version, 3 for the L/T version and 4 for the X version.
Suspension cable compatible with ceiling or wall installations, even inclined.

Power Supply Kit



	L	Driver	Colour	Code
	4000	EL.	○	**1T5905EL**
	4000	EL.	◑	**1T5906EL**
	4000	EL.	◍	**1T5907EL**
	4000	DALI	○	**1T5905DA**
	4000	DALI	◑	**1T5906DA**
	4000	DALI	◍	**1T5907DA**

Suspension installation kit: power cable complete with a painted polycarbonate rosette.
Max 0.6kW.

Accessories

Screen



	Code
	1T6502

Accessory designed to improve the visual comfort of the Wall Washer version.
To be installed on a standard reflector.
Made of matte black painted aluminium.
280mm in length; to be ordered in the following quantities for every fixture length: 2 for the 562mm version, 4 for the 1122/1135/1146mm versions, 6 for the 1682/1695/1706mm versions and 12 for the 3364/3377/3386mm versions.

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CARTESIO

GENERAL INFO
Direct/indirect light suspension, ceiling mounted luminaire.
720x720x42mm
1147x420x42mm

LED
Direct lighting LED boards
Indirect lighting LED COB
From 2776lm to 6833lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 116lm/W

OPTICS
UGR

POWER SUPPLY
Electronic – DALI

MATERIAL
Extruded aluminium body with aluminium terminals.
Plaster white finish.

ON DEMAND
Easy Custom Colour

A range of fixtures dedicated to the work environment with soft lines and professional performance in rectangular and square versions for suspension ceiling and wall installations.

The suspension versions provide different light emissions: direct indirect and combined direct/indirect in a unique fixture. The rectangular UGR<19 (EN-12464) L65<3000 cd/m^2 suspension version can be installed in continuous rows using an accessory connector.

Direct and direct/indirect light suspension fixtures. Also available for ceiling and wall installation.

Plus



Lighting for the office

The rectangular Cartesio versions, fitted with the direct emission component guarantee more than 500lux on the work surface, in line with the requirements outlined in the EN12464-1 standard and have a UGR value of 16 which is considerably lower than the limits indicated in the standard (UGR<19), which ensures reliability and maximum freedom when designing spaces. In addition to this there is the indirect component that contributes to softly balancing the luminance to reduce user eyestrain and improve perception of the illuminated space.



CARTESIO

Rectangular Suspension UGR<19



LED / 48W / VWFL (UGR)



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			88°	92°	
Fixture Power	55W	1	1.95	2.08	1441
Source Flux	6402lm	2	3.90	4.15	360
Fixture Flux	6402lm	3	5.84	6.23	160
Efficacy	116lm/W	4	7.79	8.30	90
TS803 Imax=234cd/klm	Imax 1497cd	5	9.74	10.38	58

	Driver	Colour	3000K
	EL.	◯	**1T4063**
	DALI	◯	**1T4067**

LED / 52W / VWFL (UGR)



4000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	82°	
Fixture Power	59W	1	1.67	1.75	2068
Source Flux	6833lm	2	3.34	3.50	517
Fixture Flux	6833lm	3	5.01	5.25	230
Efficacy	116lm/W	4	6.67	7.00	129
TS840 Imax=321cd/klm	Imax 2190cd	5	8.34	8.75	83

	Driver	Colour	4000K
	EL.	◯	**1T4065**
	DALI	◯	**1T4069**

Square Suspension UGR<22



LED / 26W / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra80			119°	
Fixture Power	30W	1	3.37	891
Source Flux	2776lm	2	6.73	223
Fixture Flux	2776lm	3	10.10	99
Efficacy	94lm/W	4	13.47	56
TS843 Imax=321cd/klm	Imax 891cd	5	16.83	36

	Driver	Colour	3000K	4000K
	EL.	◯	**1T4241**	**1T4243**
	DALI	◯	**1T4242**	**1T4244**

Related codes

Canopy

	Driver	Colour	Code
	EL.	◯	**1T4071**
	DALI	◯	**1T4072**

Canopy.

Accessories

Mechanical connector



	Driver	Code
	EL.	**1T4075**
	DALI	**1T4240**

Linear connector.

CARTESIO

Square Wall/Ceiling UGR<22



LED / 26W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			119°	
	Fixture Power	30W	1	3.37	891
	Source Flux	2776lm	2	6.73	223
	Fixture Flux	2776lm	3	10.10	99
	Efficacy	94lm/W	4	13.47	56
	Imax	891cd	5	16.83	36

	Driver	Colour	3000K	4000K
	EL.	◯	**1T4245**	**1T4247**
	DALI	◯	**1T4246**	**1T4248**

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

DIVA

GENERAL INFO
Stand-alone direct or indirect light suspension lamp 1335x435x87mm

LED
Direct lighting LED boards
Indirect lighting LED COB
From 6402lm to 6833lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 116lm/W

OPTICS
UGR

POWER SUPPLY
Electronic – DALI

MATERIAL
White CRISTALPLANT© body.

A high end suspension light fixture for the office made of Cristalplant without the use of visible screws and joins, with soft lines ideal for the office environment; it interacts with the light using different light emissions: direct, indirect and combined direct/indirect in just one fixture.

Controlled low luminance direct light EN12464, UGR<19 and L65<3000 cd/m^2. Micrometric adjustment of the suspension cables using an ABS Auto Block System. Can be adjusted vertically by +/-15°.

Plus

It is made of Cristalplant®

Technologically advanced and unique composite material that is made up of a high percentage of natural extremely pure polyester polymers and acrylics; it is therefore an inert, hypoallergenic and non-toxic material.

Diva hides professional technology

Suitable for office lighting that meets all the regulations specified in the EN 12464-1 standard in terms of luminance, colour rendering and glare.

(A) Diva is able to create three different effects

Direct emission, indirect emission or mixed direct/indirect emission. The direct component is managed by a textured PMMA screen to control glare while the indirect component is managed by a highly efficient LED COB source that lights the ceiling with a Lambertian 'matte' reflectance to balance the luminance.



DIVA



UGR<19



LED / 48W / VWFL (UGR)



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			88°	92°	
Fixture Power	55W	1	1.95	2.08	1441
Source Flux	6402lm	2	3.90	4.15	360
Fixture Flux	6402lm	3	5.84	6.23	160
Efficacy	116lm/W	4	7.79	8.30	90
TS803 Imax=234cd/klm	Imax 1497cd	5	9.74	10.38	58

	Driver	Colour	3000K
	EL.	◯	**1T4522**
	DALI	◯	**1T4523**

LED / 52W / VWFL (UGR)



4000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	82°	
Fixture Power	59W	1	1.67	1.75	2068
Source Flux	6833lm	2	3.34	3.50	517
Fixture Flux	6833lm	3	5.01	5.25	230
Efficacy	116lm/W	4	6.67	7.00	129
TS840 Imax=321cd/klm	Imax 2190cd	5	8.34	8.75	83

	Driver	Colour	4000K
	EL.	◯	**1T4524**
	DALI	◯	**1T4525**

Accessories

Control systems

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

SLIM

Suspension

GENERAL INFO
Indirect or direct/indirect modular suspension for LED sources.

LED
Linear Board LED Low Power High Efficiency
From 2590lm to 13760lm
3000K
Ra80 - Ra84

PRODUCT EFFICACY
Up to 114lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic

MATERIAL
Body made of extruded anodised aluminium. Polycarbonate lateral end caps. Transparent polycarbonate upper safety screen. Lower diffusive screen made of ribbed, extruded opal polycarbonate.

ON DEMAND

Ra Ra90

Minimal modular suspension fixture with indirect or direct/indirect light emission with a compact size to disappear into the environment to leave space for just the architecture and the light.

There is also a linear version that can be configured in a system or stand alone, as well as a rectangular version that is particularly suitable for lighting open spaces.

Coordinable with the indirect or direct/indirect light wall solution.



SLIM

Line L. 1800mm



LED / 18W / INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			115°	
Fixture Power	21W	1	3.13	822
Source Flux	2590lm	2	6.26	206
Fixture Flux	2353lm	3	9.39	91
Efficacy	112lm/W	4	12.52	51
TS751 Imax=318cd/klm	Imax 824cd	5	15.65	33

Driver	Colour	3000K
EL.		**1T4186**

Line L. 3370mm

LED / 36W / INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			115°	
Fixture Power	42W	1	3.13	1645
Source Flux	5180lm	2	6.26	411
Fixture Flux	4705lm	3	9.39	183
Efficacy	112lm/W	4	12.52	103
TS751 Imax=318cd/klm	Imax 1648cd	5	15.65	66

Driver	Colour	3000K
EL.		**1T4188**

Line L. 1800mm



LED / 39W / DIRECT/INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			95°	
Fixture Power	44W	1	2.19	818
Source Flux	5620lm	2	4.37	205
Fixture Flux	4193lm	3	6.56	91
Efficacy	95lm/W	4	8.75	51
TS752 Imax=147cd/klm	Imax 824cd	5	10.93	33

Driver	Colour	3000K
EL.		**1T4187**

SLIM

Line L. 3370mm



LED / 78W / DIRECT/INDIRECT / VWFL



Driver	Colour	3000K
EL.		**1T4189**

Related codes

Power Supply Kit

Code
1V7213

Off-centre circular canopy complete with feeding cable L 2000mm.
Maximum power 2kW.
For single switching.

Code
1V7523

Off-centre square canopy complete with feeding cable L 2000mm.
Maximum power 2kW.
For single switching.

Accessories

Canopy

Code
1V7524

Canopy without feeding cable.
Square.

Code
1V7213AB

Canopy without feeding cable.
Circular.

Suspension

L	Code
10000	**1V7264**

Steel suspension cable.
Accessory to be ordered only for installations higher than 2000mm.

Cable

L	Code
5000	**1V7262**
10000	**1V7263**

Three pole feeding cable.
Accessory to be ordered only for installations higher than 2000mm.

SLIM

Mechanical connector

	Code
	1V7344

Joint for connecting two modules in a straight line. For the codes: 1T4186, 1T4187, 1T4188.

	Code
	1V7345

Joint for connecting two modules at 90°. For the codes: 1T4186, 1T4187, 1T4188.

SLIM

Rectangle L. 1800mm



LED / 48W / INDIRECT / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			115°	
Fixture Power		55W	1	3.13	2185
Source Flux		6880lm	2	6.26	546
Fixture Flux		6249lm	3	9.39	243
Efficacy		114lm/W	4	12.52	137
TS751	Imax=318cd/klm	Imax	2189cd	5	15.65	87

Driver	Colour	3000K
EL.		**1T4190**

LED / 96W / DIRECT/INDIRECT / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			95°	
Fixture Power		110W	1	2.19	2003
Source Flux		13760lm	2	4.37	501
Fixture Flux		10266lm	3	6.56	223
Efficacy		93lm/W	4	8.75	125
TS752	Imax=147cd/klm	Imax	2019cd	5	10.93	80

Driver	Colour	3000K
EL.		**1T4191**

Related codes

Power Supply Kit

Code
1V7213

Off-centre circular canopy complete with feeding cable L 2000mm.
Maximum power 2kW.
For single switching.

Code
1V7523

Off-centre square canopy complete with feeding cable L 2000mm.
Maximum power 2kW.
For single switching.

Accessories

Canopy

Code
1V7524

Canopy without feeding cable.
Square.

Code
1V7213AB

Canopy without feeding cable.
Circular.

SLIM

Suspension

	L	Code
	10000	**1V7264**

Steel suspension cable.
Accessory to be ordered only for installations higher than 2000mm.

Cable

	L	Code
	5000	**1V7262**
	10000	**1V7263**

Three pole feeding cable.
Accessory to be ordered only for installations higher than 2000mm.

Mechanical connector

	Code
	1V7343

Joint for connecting two modules in a line.

OZ Stand Alone

Ceiling

GENERAL INFO
Fixed multi-optic LED ceiling mounted fixture
Large version: 3x and 5x.
3x: 153x53mm h.100mm
5x: 253x53mm h.100mm

LED
High efficiency LED Chip on Board
From 1810lm to 4260lm
2700K – 3000K – 3500K – 4000K
Ra90

PRODUCT EFFICACY
Up to 101lm/W

OPTICS
SP – FL – MWFL
AM – ELT – ELL

POWER SUPPLY
Electronic and DALI driver integrated into the body of the fixture.
Casambi control system available with an accessory (only for DALI version products).

MATERIAL
Black or white painted die-cast aluminium body with black polycarbonate frame.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

New concept ceiling fixtures with miniature optics inspired by the 48V OZ. Available only in the Large version for ceiling installations.

The range is enriched with the addition of three new AM optical systems for soft and diffused general lighting, ELT and ELL - with a transversal elliptical (ELT) or longitudinal beam (ELL)- , ideal for controlled lighting in corridors and passage ways.

All the optical systems available make Oz Stand Alone suitable for installation in work environments (EN12464-1).

Large and Small versions also available for recessed installation with 1x, 3x and 5x modules.

		LARGE	
		3x	5x
Ambient Optics	AM	•	•
Roto-symmetric Optics	SP	•	•
	FL	•	•
	WFL	•	•
Elliptical Optics	ELL	•	•
	ELT	•	•

Plus

OZ 48V - the same family feeling

The same design, similar performance characteristics with a conceptually different installation philosophy.Small points of light provided by single or multiple elements that are self-sufficient, contrast with the concept of a system which is inspired on the other hand by a continuous line that develops in the space.



OZ System 48V

		SMALL		LARGE	
Ambient Optics	AM	UGR<14		UGR<14	
Roto-symmetric Optics	SP	UGR<13		UGR<17	
	FL	UGR<13		UGR<17	
	WFL	UGR<13		UGR<17	
Elliptical Optics	ELL	UGR<13	UGR<22	UGR<13	UGR<22
	ELT	UGR<22	UGR<13	UGR<22	UGR<13

New optical systems to interpret space

The new optical systems in the Oz Stand Alone range are designed to light space while enhancing flexibility. It is possible to select the desired optical system according to the conformation of the environment and furnishings to obtain comfortable and functional light distribution in compliance with regulations governing lighting in working environments.
The different optical systems available make it possible to interpret space in different ways to satisfy different requirements and tastes.



Stand Alone
Ceiling Luminaire
Large 3X (153x53mm)



LED / 18W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	20W	1	0.33	9415
Source Flux	1968lm	2	0.66	2354
Fixture Flux	1538lm	3	0.99	1046
Efficacy	77lm/W	4	1.32	588
TS1194 Imax=4784cd/klm	Imax	9415cd	5	1.65	377

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7890EL**	**1T7891EL**	**1T7892EL**	**1T7893EL**
EL.	●	**1T7902EL**	**1T7903EL**	**1T7904EL**	**1T7905EL**
DALI	○	**1T7890DA**	**1T7891DA**	**1T7892DA**	**1T7893DA**
DALI	●	**1T7902DA**	**1T7903DA**	**1T7904DA**	**1T7905DA**

LED / 18W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			34°	
Fixture Power	20W	1	0.61	5243
Source Flux	2517lm	2	1.22	1311
Fixture Flux	1797lm	3	1.83	583
Efficacy	90lm/W	4	2.43	328
TS1195 Imax=2083cd/klm	Imax	5243cd	5	3.04	210

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7894EL**	**1T7895EL**	**1T7896EL**	**1T7897EL**
EL.	●	**1T7906EL**	**1T7907EL**	**1T7908EL**	**1T7909EL**
DALI	○	**1T7894DA**	**1T7895DA**	**1T7896DA**	**1T7897DA**
DALI	●	**1T7906DA**	**1T7907DA**	**1T7908DA**	**1T7909DA**

LED / 18W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			50°	
Fixture Power	20W	1	0.93	3157
Source Flux	2517lm	2	1.85	789
Fixture Flux	1947lm	3	2.78	351
Efficacy	97lm/W	4	3.71	197
TS1196 Imax=1254cd/klm	Imax	3157cd	5	4.64	126

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7898EL**	**1T7899EL**	**1T7900EL**	**1T7901EL**
EL.	●	**1T7910EL**	**1T7911EL**	**1T7912EL**	**1T7913EL**
DALI	○	**1T7898DA**	**1T7899DA**	**1T7900DA**	**1T7901DA**
DALI	●	**1T7910DA**	**1T7911DA**	**1T7912DA**	**1T7913DA**

LED / 18W / REFLECTOR / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	20W	1	0.92	2902
Source Flux	2517lm	2	1.83	726
Fixture Flux	1804lm	3	2.75	322
Efficacy	90lm/W	4	3.67	181
TS1252 Imax=1153cd/klm	Imax	2902cd	5	4.59	116

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8898EL**	**1T8899EL**	**1T8900EL**	**1T8901EL**
EL.	●	**1T8910EL**	**1T8911EL**	**1T8912EL**	**1T8913EL**
DALI	○	**1T8898DA**	**1T8899DA**	**1T8900DA**	**1T8901DA**
DALI	●	**1T8910DA**	**1T8911DA**	**1T8912DA**	**1T8913DA**

LED / 18W / REFLECTOR / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			25°	58°	
Fixture Power	20W	1	0.44	1.11	3209
Source Flux	2280lm	2	0.88	2.21	802
Fixture Flux	1641lm	3	1.32	3.32	357
Efficacy	82lm/W	4	1.76	4.43	201
TS1254 Imax=1408cd/klm	Imax	3209cd	5	2.19	5.54	128

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8902EL**	**1T8903EL**	**1T8904EL**	**1T8905EL**
EL.	●	**1T8914EL**	**1T8915EL**	**1T8916EL**	**1T8917EL**
DALI	○	**1T8902DA**	**1T8903DA**	**1T8904DA**	**1T8905DA**
DALI	●	**1T8914DA**	**1T8915DA**	**1T8916DA**	**1T8917DA**

OZ

LED / 18W / REFLECTOR / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			58°	25°	
Fixture Power	20W	1	1.11	0.44	3209
Source Flux	2280lm	2	2.21	0.88	802
Fixture Flux	1641lm	3	3.32	1.32	357
Efficacy	82lm/W	4	4.43	1.76	201
TS1256 Imax=1408cd/klm	Imax	3209cd	5	5.54	2.19	128

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8906EL**	**1T8907EL**	**1T8908EL**	**1T8909EL**
EL.	●	**1T8918EL**	**1T8919EL**	**1T8936EL**	**1T8937EL**
DALI	○	**1T8906DA**	**1T8907DA**	**1T8908DA**	**1T8909DA**
DALI	●	**1T8918DA**	**1T8919DA**	**1T8936DA**	**1T8937DA**



Stand Alone Ceiling Luminaire Large 5X (253x53mm)



LED / 30W / REFLECTOR / SP



3000K		H(m)	D(m)	Emax(lx)
Ra90			19°	
Fixture Power	34W	1	0.33	15692
Source Flux	3280lm	2	0.66	3923
Fixture Flux	2563lm	3	0.99	1744
Efficacy	75lm/W	4	1.32	981
TS1194 Imax=4784cd/klm	Imax	15692cd	5	1.65	628

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7914EL**	**1T7915EL**	**1T7916EL**	**1T7917EL**
EL.	●	**1T7926EL**	**1T7927EL**	**1T7928EL**	**1T7929EL**
DALI	○	**1T7914DA**	**1T7915DA**	**1T7916DA**	**1T7917DA**
DALI	●	**1T7926DA**	**1T7927DA**	**1T7928DA**	**1T7929DA**

LED / 30W / REFLECTOR / FL



3000K		H(m)	D(m)	Emax(lx)
Ra90			34°	
Fixture Power	34W	1	0.61	8739
Source Flux	4195lm	2	1.22	2185
Fixture Flux	2996lm	3	1.83	971
Efficacy	88lm/W	4	2.43	546
TS1195 Imax=2083cd/klm	Imax	8739cd	5	3.04	350

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7918EL**	**1T7919EL**	**1T7920EL**	**1T7921EL**
EL.	●	**1T7930EL**	**1T7931EL**	**1T7932EL**	**1T7933EL**
DALI	○	**1T7918DA**	**1T7919DA**	**1T7920DA**	**1T7921DA**
DALI	●	**1T7930DA**	**1T7931DA**	**1T7932DA**	**1T7933DA**

LED / 30W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			50°	
Fixture Power	34W	1	0.93	5262
Source Flux	4195lm	2	1.85	1315
Fixture Flux	3246lm	3	2.78	585
Efficacy	95lm/W	4	3.71	329
TS1196 Imax=1254cd/klm	Imax	5262cd	5	4.64	210

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T7922EL**	**1T7923EL**	**1T7924EL**	**1T7925EL**
EL.	●	**1T7934EL**	**1T7935EL**	**1T7936EL**	**1T7937EL**
DALI	○	**1T7922DA**	**1T7923DA**	**1T7924DA**	**1T7925DA**
DALI	●	**1T7934DA**	**1T7935DA**	**1T7936DA**	**1T7937DA**

LED / 30W / REFLECTOR / AM



3000K		H(m)	D(m)	Emax(lx)
Ra90			49°	
Fixture Power	34W	1	0.92	4837
Source Flux	4195lm	2	1.83	1209
Fixture Flux	3007lm	3	2.75	537
Efficacy	88lm/W	4	3.67	302
TS1253 Imax=1153cd/klm	Imax	4837cd	5	4.59	193

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8938EL**	**1T8939EL**	**1T8940EL**	**1T8941EL**
EL.	●	**1T8950EL**	**1T8951EL**	**1T8952EL**	**1T8953EL**
DALI	○	**1T8938DA**	**1T8939DA**	**1T8940DA**	**1T8941DA**
DALI	●	**1T8950DA**	**1T8951DA**	**1T8952DA**	**1T8953DA**

OZ

LED / 30W / REFLECTOR / ELL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			25°	58°	
Fixture Power	34W	1	0.44	1.11	5349
Source Flux	3800lm	2	0.88	2.21	1337
Fixture Flux	2735lm	3	1.32	3.32	594
Efficacy	80lm/W	4	1.76	4.43	334
TS1255 Imax=1408cd/klm	Imax 5349cd	5	2.19	5.54	214

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8942EL**	**1T8943EL**	**1T8944EL**	**1T8945EL**
EL.	●	**1T8954EL**	**1T8955EL**	**1T8956EL**	**1T8957EL**
DALI	○	**1T8942DA**	**1T8943DA**	**1T8944DA**	**1T8945DA**
DALI	●	**1T8954DA**	**1T8955DA**	**1T8956DA**	**1T8957DA**

LED / 30W / REFLECTOR / ELT



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra90			58°	25°	
Fixture Power	34W	1	1.11	0.44	5349
Source Flux	3800lm	2	2.21	0.88	1337
Fixture Flux	2735lm	3	3.32	1.32	594
Efficacy	80lm/W	4	4.43	1.76	334
TS1257 Imax=1408cd/klm	Imax 5349cd	5	5.54	2.19	214

Driver	Colour	2700K	3000K	3500K	4000K
EL.	○	**1T8946EL**	**1T8947EL**	**1T8948EL**	**1T8949EL**
EL.	●	**1T8958EL**	**1T8959EL**	**1T8960EL**	**1T8961EL**
DALI	○	**1T8946DA**	**1T8947DA**	**1T8948DA**	**1T8949DA**
DALI	●	**1T8958DA**	**1T8959DA**	**1T8960DA**	**1T8961DA**

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

THREESIXTY

GENERAL INFO
Circular LED fixture for ceiling mounted, suspension and wall mounted installations.
Ø384mm - Ø590mm - Ø870mm - Ø1150mm

LED
Self-cooling circular boards.
From 2017lm to 44809lm
3000K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 121lm/W

OPTICS
OPALE – UGR – OPALE+HALO – UGR+HALO

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Powder coated, extruded, calendered aluminium.
High luminance transmission and light diffusion opaline polycarbonate lower diffusive screen. UGR Version: transparent micro prismatic PMMA lower diffusive screen and spreader lens.

ON DEMAND

Easy Custom Colour

Tunable White

110-277Vac power supply

A fixture with a pure and simple design in four different diameters and five different installation types: recessed, semi-recessed, ceiling mounted, suspension and wall mounted. Any light fixture can be configured in various ways when accessorised with different installation elements.

Available only with direct, direct/indirect light or in a direct light version combined with a slight indirect HALO component. a solution that is particularly suitable for the ceiling mounted, wall mounted or semi-recessed versions to create a soft frame of light. Also available in UGR<19 for the two smaller diameters (EN-12464 - L65<3000 cd/m^2).

The direct/indirect version is set up for three different effects: direct emission, indirect emission and mixed direct/indirect emission.

For recessed or semi-recessed installations it is necessary to order both the fixtures and the accessory outer casings.
The 384mm and 590mm versions can also be recessed wall installed using a special accessory outer casing.

Emergency versions available on request after checking feasibility.

Plus

Ø 1150mm
LP - HP
Opal

Ø 870mm
LP - HP
Opal

Ø 590mm
LP - HP
Opal, UGR

Ø 384mm
LP - HP
Opal, UGR

Four different diameters

To light spaces with different characteristics.
Compact solutions to light environments with limited heights and large size fixtures to light great heights and showrooms.

A wide range of direct or direct/indirect lighting effects

Diffused light, controlled light UGR<19 and a particular Halo effect

Dimmable light

The Threesixty DALI versions can be dimmed from 10% to 100% with amplitude modulation AM. Dimming is possible by modifying the drive current and not by turning the LED source on or off. This avoids flicker and makes the fixture suitable for installation even in environments where videos are recorded.

10% 100%



A **Suspension, Wall and ceiling mounted**
The fixture can be ceiling or wall mounted without the use of any accessories. For suspension installation a special suspension kit must be used.

B **Recessed - Semi Recessed**
For recessed or semi-recessed installations it must be completed with special outer casings.

- The 384 mm and 590 mm versions are compatible with an accessory standard or HALO version load bearing outer frame that attaches directly to the false ceiling.
- The 384 mm, 590 mm, 870 mm and 1150 mm versions are compatible with a recessed non load bearing frame that attaches to the main ceiling.

Different lumen packages
For every diameter to light spaces with the same design.



THREESIXTY

Ø 384mm



LED / 21W / DOWN OPAL



Driver	Colour	3000K	4000K
EL.	○	**1T6066EL**	**1T6067EL**
EL.	◐	**1T6070EL**	**1T6071EL**
EL.	●	**1T6068EL**	**1T6069EL**
DALI	○	**1T6066DA**	**1T6067DA**
DALI	◐	**1T6070DA**	**1T6071DA**
DALI	●	**1T6068DA**	**1T6069DA**

LED / 29W / DOWN OPAL



Driver	Colour	3000K	4000K
EL.	○	**1T6072EL**	**1T6073EL**
EL.	◐	**1T6076EL**	**1T6077EL**
EL.	●	**1T6074EL**	**1T6075EL**
DALI	○	**1T6072DA**	**1T6073DA**
DALI	◐	**1T6076DA**	**1T6077DA**
DALI	●	**1T6074DA**	**1T6075DA**

LED / 13W / DOWN UGR

Driver	Colour	3000K	4000K
EL.	○	**1T6102EL**	**1T6103EL**
EL.	◐	**1T6106EL**	**1T6107EL**
EL.	●	**1T6104EL**	**1T6105EL**
DALI	○	**1T6102DA**	**1T6103DA**
DALI	◐	**1T6106DA**	**1T6107DA**
DALI	●	**1T6104DA**	**1T6105DA**

LED / 29W / UP-DOWN OPAL



Driver	Colour	3000K	4000K
EL.	○	**1T6090EL**	**1T6091EL**
EL.	◐	**1T6094EL**	**1T6095EL**
EL.	●	**1T6092EL**	**1T6093EL**
DALI	○	**1T6090DA**	**1T6091DA**
DALI	◐	**1T6094DA**	**1T6095DA**
DALI	●	**1T6092DA**	**1T6093DA**

LED / 37W / UP-DOWN OPAL



Driver	Colour	3000K	4000K
EL.	○	**1T6096EL**	**1T6097EL**
EL.	◐	**1T6100EL**	**1T6101EL**
EL.	●	**1T6098EL**	**1T6099EL**
DALI	○	**1T6096DA**	**1T6097DA**
DALI	◐	**1T6100DA**	**1T6101DA**
DALI	●	**1T6098DA**	**1T6099DA**

THREESIXTY

LED / 21W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			92°	
Fixture Power		24W	1	2.07	711
Source Flux		3484lm	2	4.15	178
Fixture Flux		2783lm	3	6.22	79
Efficacy		116lm/W	4	8.29	44
TS1021	Imax=204cd/klm	Imax	5	10.36	28
		711cd			

Driver	Colour	3000K	4000K
EL.	○	**1T6126EL**	**1T6127EL**
EL.	◐	**1T6130EL**	**1T6131EL**
EL.	●	**1T6128EL**	**1T6129EL**
DALI	○	**1T6126DA**	**1T6127DA**
DALI	◐	**1T6130DA**	**1T6131DA**
DALI	●	**1T6128DA**	**1T6129DA**

LED / 35W (40,5W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		24W	1	3.09	636
Source Flux		3033lm	2	6.17	159
Fixture Flux		1836lm	3	9.26	71
Efficacy		76lm/W	4	12.35	40
TS1002	Imax=210cd/klm	Imax	5	15.43	25
		636cd			

Driver	Colour	3000K	4000K
EL.	○	**1T6078EL**	**1T6079EL**
EL.	◐	**1T6082EL**	**1T6083EL**
EL.	●	**1T6080EL**	**1T6081EL**
DALI	○	**1T6078DA**	**1T6079DA**
DALI	◐	**1T6082DA**	**1T6083DA**
DALI	●	**1T6080DA**	**1T6081DA**

LED / 43W (49,5W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		33W	1	3.09	848
Source Flux		4044lm	2	6.17	212
Fixture Flux		2448lm	3	9.26	94
Efficacy		74lm/W	4	12.35	53
TS1003	Imax=210cd/klm	Imax	5	15.43	34
		848cd			

Driver	Colour	3000K	4000K
EL.	○	**1T6084EL**	**1T6085EL**
EL.	◐	**1T6088EL**	**1T6089EL**
EL.	●	**1T6086EL**	**1T6087EL**
DALI	○	**1T6084DA**	**1T6085DA**
DALI	◐	**1T6088DA**	**1T6089DA**
DALI	●	**1T6086DA**	**1T6087DA**

LED / 27W (31,5W fixture power) / UGR + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			92°	
Fixture Power		15W	1	2.07	702
Source Flux		2017lm	2	4.15	176
Fixture Flux		1458lm	3	6.22	78
Efficacy		97lm/W	4	8.29	44
TS1018	Imax=348cd/klm	Imax	5	10.36	28
		702cd			

Driver	Colour	3000K	4000K
EL.	○	**1T6114EL**	**1T6115EL**
EL.	◐	**1T6118EL**	**1T6119EL**
EL.	●	**1T6116EL**	**1T6117EL**
DALI	○	**1T6114DA**	**1T6115DA**
DALI	◐	**1T6118DA**	**1T6119DA**
DALI	●	**1T6116DA**	**1T6117DA**

Ø 590mm



LED / 50W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		57W	1	3.09	1555
Source Flux		7418lm	2	6.17	389
Fixture Flux		4490lm	3	9.26	173
Efficacy		79lm/W	4	12.35	97
TS1002	Imax=210cd/klm	Imax	5	15.43	62
		1555cd			

Driver	Colour	3000K	4000K
EL.	○	**1T6138EL**	**1T6139EL**
EL.	◐	**1T6142EL**	**1T6143EL**
EL.	●	**1T6140EL**	**1T6141EL**
DALI	○	**1T6138DA**	**1T6139DA**
DALI	◐	**1T6142DA**	**1T6143DA**
DALI	●	**1T6140DA**	**1T6141DA**

THREESIXTY

LED / 67W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		75W	1	3.09	2079
Source Flux		9917lm	2	6.17	520
Fixture Flux		6003lm	3	9.26	231
Efficacy		80lm/W	4	12.35	130
TS1003	Imax=210cd/klm	Imax	5	15.43	83

Driver	Colour	3000K	4000K
EL.	○	**1T6144EL**	**1T6145EL**
EL.	◐	**1T6148EL**	**1T6149EL**
EL.	◍	**1T6146EL**	**1T6147EL**
DALI	○	**1T6144DA**	**1T6145DA**
DALI	◐	**1T6148DA**	**1T6149DA**
DALI	◍	**1T6146DA**	**1T6147DA**

LED / 31W / DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			92°	
Fixture Power		35W	1	2.07	1722
Source Flux		4944lm	2	4.15	430
Fixture Flux		3575lm	3	6.22	191
Efficacy		102lm/W	4	8.29	108
TS1019	Imax=348cd/klm	Imax	5	10.36	69

Driver	Colour	3000K	4000K
EL.	○	**1T6174EL**	**1T6175EL**
EL.	◐	**1T6178EL**	**1T6179EL**
EL.	◍	**1T6176EL**	**1T6177EL**
DALI	○	**1T6174DA**	**1T6175DA**
DALI	◐	**1T6178DA**	**1T6179DA**
DALI	◍	**1T6176DA**	**1T6177DA**

LED / 67W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		76W	1	3.09	1555
Source Flux		10112lm	2	6.17	389
Fixture Flux		6932lm	3	9.26	173
Efficacy		91lm/W	4	12.35	97
TS1005	Imax=154cd/klm	Imax	5	15.43	62

Driver	Colour	3000K	4000K
EL.	○	**1T6162EL**	**1T6163EL**
EL.	◐	**1T6166EL**	**1T6167EL**
EL.	◍	**1T6164EL**	**1T6165EL**
DALI	○	**1T6162DA**	**1T6163DA**
DALI	◐	**1T6166DA**	**1T6167DA**
DALI	◍	**1T6164DA**	**1T6165DA**

LED / 84W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		94W	1	3.09	2080
Source Flux		12611lm	2	6.17	520
Fixture Flux		8445lm	3	9.26	231
Efficacy		90lm/W	4	12.35	130
TS1015	Imax=165cd/klm	Imax	5	15.43	83

Driver	Colour	3000K	4000K
EL.	○	**1T6168EL**	**1T6169EL**
EL.	◐	**1T6172EL**	**1T6173EL**
EL.	◍	**1T6170EL**	**1T6171EL**
DALI	○	**1T6168DA**	**1T6169DA**
DALI	◐	**1T6172DA**	**1T6173DA**
DALI	◍	**1T6170DA**	**1T6171DA**

LED / 48W / UP-DOWN UGR



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			92°	
Fixture Power		54W	1	2.07	1740
Source Flux		7692lm	2	4.15	435
Fixture Flux		6055lm	3	6.22	193
Efficacy		112lm/W	4	8.29	109
TS1020	Imax=226cd/klm	Imax	5	10.36	70

Driver	Colour	3000K	4000K
EL.	○	**1T6198EL**	**1T6199EL**
EL.	◐	**1T6202EL**	**1T6203EL**
EL.	◍	**1T6200EL**	**1T6201EL**
DALI	○	**1T6198DA**	**1T6199DA**
DALI	◐	**1T6202DA**	**1T6203DA**
DALI	◍	**1T6200DA**	**1T6201DA**

LED / 70W (81W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		57W	1	3.09	1555
Source Flux		7418lm	2	6.17	389
Fixture Flux		4490lm	3	9.26	173
Efficacy		79lm/W	4	12.35	97
TS1002	Imax=210cd/klm	Imax	5	15.43	62

Driver	Colour	3000K	4000K
EL.	○	**1T6150EL**	**1T6151EL**
EL.	◐	**1T6154EL**	**1T6155EL**
EL.	◍	**1T6152EL**	**1T6153EL**
DALI	○	**1T6150DA**	**1T6151DA**
DALI	◐	**1T6154DA**	**1T6155DA**
DALI	◍	**1T6152DA**	**1T6153DA**

THREESIXTY

LED / 87W (99W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		75W	1	3.09	2079
Source Flux		9917lm	2	6.17	520
Fixture Flux		6003lm	3	9.26	231
Efficacy		80lm/W	4	12.35	130
TS1003	Imax=210cd/klm	Imax	5	15.43	83

Driver	Colour	3000K	4000K
EL.	○	**1T6156EL**	**1T6157EL**
EL.	●	**1T6160EL**	**1T6161EL**
EL.	◍	**1T6158EL**	**1T6159EL**
DALI	○	**1T6156DA**	**1T6157DA**
DALI	●	**1T6160DA**	**1T6161DA**
DALI	◍	**1T6158DA**	**1T6159DA**

LED / 51W (59W fixture power) / UGR + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			92°	
Fixture Power		35W	1	2.07	1722
Source Flux		4944lm	2	4.15	430
Fixture Flux		3575lm	3	6.22	191
Efficacy		102lm/W	4	8.29	108
TS1019	Imax=348cd/klm	Imax	5	10.36	69

Driver	Colour	3000K	4000K
EL.	○	**1T6186EL**	**1T6187EL**
EL.	●	**1T6190EL**	**1T6191EL**
EL.	◍	**1T6188EL**	**1T6189EL**
DALI	○	**1T6186DA**	**1T6187DA**
DALI	●	**1T6190DA**	**1T6191DA**
DALI	◍	**1T6188DA**	**1T6189DA**

Ø 870mm



LED / 113W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		127W	1	3.09	3404
Source Flux		16238lm	2	6.17	851
Fixture Flux		9829lm	3	9.26	378
Efficacy		77lm/W	4	12.35	213
TS1002	Imax=210cd/klm	Imax	5	15.43	136

Driver	Colour	3000K	4000K
EL.	○	**1T6210EL**	**1T6211EL**
EL.	●	**1T6214EL**	**1T6215EL**
EL.	◍	**1T6212EL**	**1T6213EL**
DALI	○	**1T6210DA**	**1T6211DA**
DALI	●	**1T6214DA**	**1T6215DA**
DALI	◍	**1T6212DA**	**1T6213DA**

LED / 144W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		162W	1	3.09	4548
Source Flux		21693lm	2	6.17	1137
Fixture Flux		13131lm	3	9.26	505
Efficacy		81lm/W	4	12.35	284
TS1003	Imax=210cd/klm	Imax	5	15.43	182

Driver	Colour	3000K	4000K
EL.	○	**1T6216EL**	**1T6217EL**
EL.	●	**1T6220EL**	**1T6221EL**
EL.	◍	**1T6218EL**	**1T6219EL**
DALI	○	**1T6216DA**	**1T6217DA**
DALI	●	**1T6220DA**	**1T6221DA**
DALI	◍	**1T6218DA**	**1T6219DA**

LED / 146W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		164W	1	3.09	3406
Source Flux		20629lm	2	6.17	852
Fixture Flux		13813lm	3	9.26	378
Efficacy		84lm/W	4	12.35	213
TS1006	Imax=165cd/klm	Imax	5	15.43	136

Driver	Colour	3000K	4000K
EL.	○	**1T6234EL**	**1T6235EL**
EL.	●	**1T6238EL**	**1T6239EL**
EL.	◍	**1T6236EL**	**1T6237EL**
DALI	○	**1T6234DA**	**1T6235DA**
DALI	●	**1T6238DA**	**1T6239DA**
DALI	◍	**1T6236DA**	**1T6237DA**

THREESIXTY

LED / 177W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		199W	1	3.09	4548
Source Flux		26084lm	2	6.17	1137
Fixture Flux		17111lm	3	9.26	505
Efficacy		86lm/W	4	12.35	284
TS1016	Imax=174cd/klm	Imax	4548cd	5	15.43	182

Driver	Colour	3000K	4000K
EL.	○	**1T6240EL**	**1T6241EL**
EL.	◐	**1T6244EL**	**1T6245EL**
EL.	◍	**1T6242EL**	**1T6243EL**
DALI	○	**1T6240DA**	**1T6241DA**
DALI	◐	**1T6244DA**	**1T6245DA**
DALI	◍	**1T6242DA**	**1T6243DA**

LED / 138W (160W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		127W	1	3.09	3404
Source Flux		16238lm	2	6.17	851
Fixture Flux		9829lm	3	9.26	378
Efficacy		77lm/W	4	12.35	213
TS1002	Imax=210cd/klm	Imax	3404cd	5	15.43	136

Driver	Colour	3000K	4000K
EL.	○	**1T6222EL**	**1T6223EL**
EL.	◐	**1T6226EL**	**1T6227EL**
EL.	◍	**1T6224EL**	**1T6225EL**
DALI	○	**1T6222DA**	**1T6223DA**
DALI	◐	**1T6226DA**	**1T6227DA**
DALI	◍	**1T6224DA**	**1T6225DA**

LED / 174W (201W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		162W	1	3.09	4548
Source Flux		21693lm	2	6.17	1137
Fixture Flux		13131lm	3	9.26	505
Efficacy		81lm/W	4	12.35	284
TS1003	Imax=210cd/klm	Imax	4548cd	5	15.43	182

Driver	Colour	3000K	4000K
EL.	○	**1T6228EL**	**1T6229EL**
EL.	◐	**1T6232EL**	**1T6233EL**
EL.	◍	**1T6230EL**	**1T6231EL**
DALI	○	**1T6228DA**	**1T6229DA**
DALI	◐	**1T6232DA**	**1T6233DA**
DALI	◍	**1T6230DA**	**1T6231DA**

Ø 1150mm



LED / 182W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		204W	1	3.09	5760
Source Flux		27475lm	2	6.17	1440
Fixture Flux		16631lm	3	9.26	640
Efficacy		82lm/W	4	12.35	360
TS1002	Imax=210cd/klm	Imax	5760cd	5	15.43	230

Driver	Colour	3000K	4000K
EL.	○	**1T6246EL**	**1T6247EL**
EL.	◐	**1T6250EL**	**1T6251EL**
EL.	◍	**1T6248EL**	**1T6249EL**
DALI	○	**1T6246DA**	**1T6247DA**
DALI	◐	**1T6250DA**	**1T6251DA**
DALI	◍	**1T6248DA**	**1T6249DA**

LED / 243W / DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		273W	1	3.09	7695
Source Flux		36705lm	2	6.17	1924
Fixture Flux		22218lm	3	9.26	855
Efficacy		81lm/W	4	12.35	481
TS1003	Imax=210cd/klm	Imax	7695cd	5	15.43	308

Driver	Colour	3000K	4000K
EL.	○	**1T6252EL**	**1T6253EL**
EL.	◐	**1T6256EL**	**1T6257EL**
EL.	◍	**1T6254EL**	**1T6255EL**
DALI	○	**1T6252DA**	**1T6253DA**
DALI	◐	**1T6256DA**	**1T6257DA**
DALI	◍	**1T6254DA**	**1T6255DA**

THREESIXTY

LED / 233W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		261W	1	3.09	5761
Source Flux		33649lm	2	6.17	1440
Fixture Flux		22227lm	3	9.26	640
Efficacy		85lm/W	4	12.35	360
TS1007	Imax=171cd/klm	Imax	5	15.43	230

Driver	Colour	3000K	4000K
EL.	○	**1T6270EL**	**1T6271EL**
EL.	◐	**1T6274EL**	**1T6275EL**
EL.	●	**1T6272EL**	**1T6273EL**
DALI	○	**1T6270DA**	**1T6271DA**
DALI	◐	**1T6274DA**	**1T6275DA**
DALI	●	**1T6272DA**	**1T6273DA**

LED / 294W / UP-DOWN OPAL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		330W	1	3.09	7696
Source Flux		42879lm	2	6.17	1924
Fixture Flux		27815lm	3	9.26	855
Efficacy		84lm/W	4	12.35	481
TS1017	Imax=179cd/klm	Imax	5	15.43	308

Driver	Colour	3000K	4000K
EL.	○	**1T6276EL**	**1T6277EL**
EL.	◐	**1T6280EL**	**1T6281EL**
EL.	●	**1T6278EL**	**1T6279EL**
DALI	○	**1T6276DA**	**1T6277DA**
DALI	◐	**1T6280DA**	**1T6281DA**
DALI	●	**1T6278DA**	**1T6279DA**

LED / 226W (258W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		204W	1	3.09	5760
Source Flux		27475lm	2	6.17	1440
Fixture Flux		16631lm	3	9.26	640
Efficacy		82lm/W	4	12.35	360
TS1002	Imax=210cd/klm	Imax	5	15.43	230

Driver	Colour	3000K	4000K
EL.	○	**1T6258EL**	**1T6259EL**
EL.	◐	**1T6262EL**	**1T6263EL**
EL.	●	**1T6260EL**	**1T6261EL**
DALI	○	**1T6258DA**	**1T6259DA**
DALI	◐	**1T6262DA**	**1T6263DA**
DALI	●	**1T6260DA**	**1T6261DA**

LED / 286W (325W fixture power) / OPAL + HALO



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			114°	
Fixture Power		273W	1	3.09	7695
Source Flux		36705lm	2	6.17	1924
Fixture Flux		22218lm	3	9.26	855
Efficacy		81lm/W	4	12.35	481
TS1003	Imax=210cd/klm	Imax	5	15.43	308

Driver	Colour	3000K	4000K
EL.	○	**1T6264EL**	**1T6265EL**
EL.	◐	**1T6268EL**	**1T6269EL**
EL.	●	**1T6266EL**	**1T6267EL**
DALI	○	**1T6264DA**	**1T6265DA**
DALI	◐	**1T6268DA**	**1T6269DA**
DALI	●	**1T6266DA**	**1T6267DA**

Note

HALO Version: for the photometric curve please see the direct version. Indirect emission with the HALO effect is purely decorative and its effect depends on the type of installation.

DIRECT/INDIRECT VERSION: Fitted with separate switches. Three different light effects available: direct light, indirect light and mixed direct/indirect light.

Check mounting instructions to verify the quantity of DALI drivers installed.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

THREESIXTY

Related codes

Insertion Box



Cutout hole	Ø	Colour	Code
Ø410	421	○	**1T6291**
Ø410	421	●	**1T6292**
Ø410	421	◍	**1T6293**
Ø615	627	○	**1T6294**
Ø615	627	●	**1T6295**
Ø615	627	◍	**1T6296**
Ø895	907	○	**1T6297**
Ø895	907	●	**1T6298**
Ø895	907	◍	**1T6299**
Ø1175	1187	○	**1T6300**
Ø1175	1187	●	**1T6301**
Ø1175	1187	◍	**1T6302**

Adjustable frame for semi or completely recessed installation.
Non load bearing frame compatible with all sizes.
Powder coated, extruded, calendered aluminium body.
The outer casing attaches to the ceiling with pre-galvanised steel brackets.
The fixture must then be fixed to the ceiling using a suspension cable with an ABS control system installed in the outer casing.
H=99mm.
Minimum ceiling height 230mm.





Cutout hole	Ø	Colour	Code
Ø450	460	○	**1T6401**
Ø450	460	◐	**1T6402**
Ø450	460	◍	**1T6403**
Ø660	670	○	**1T6404**
Ø660	670	◐	**1T6405**
Ø660	670	◍	**1T6406**

Casing for semi or completely recessed installation.
Load bearing outer casing measuring 384mm and 590mm.
Powder coated, spun aluminium body.
The outer casing attaches to the ceiling with pre-galvanised steel brackets.
Halo Version.
H=165mm.





Cutout hole	Ø	Colour	Code
Ø410	421	○	**1T6303**
Ø410	421	●	**1T6304**
Ø410	421	◍	**1T6305**
Ø615	627	○	**1T6306**
Ø615	627	●	**1T6307**
Ø615	627	◍	**1T6308**

Frame for semi or completely recessed installation.
Load bearing outer frame measuring 384mm and 590mm.
Powder coated, extruded, calendered aluminium body.
The outer frame attaches to the ceiling with pre-galvanised steel brackets.
Standard Version.
H=130mm.

THREESIXTY

Suspension

	L	Colour	Code
	2000		**1T6282**
	4000		**1T6285**

Suspension kit composed of 3 steel cables with an ABS control system.
Suspension kit compatible with ceiling or wall installations, even inclined.

Power Supply Kit

	Driver	Colour	Code
	EL.		**1T6288EL**
	EL.		**1T6289EL**
	EL.		**1T6290EL**
	DALI		**1T6288DA**
	DALI		**1T6289DA**
	DALI		**1T6290DA**

Accessory for suspension installation composed of a canopy and 3 or 5 poles complete with a 4000mm power cable.

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTLED PENDANT

GENERAL INFO
Suspension with diffused downlight for high output LED lamps.
Ø317mm

LED
Chip on Board
From 2756lm to 3755lm
3000K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 84lm/W

OPTICS
FL

POWER SUPPLY
Electronic – DALI - Emergency - DALI Emergency
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Black painted metal canopy and black painted die-cast aluminium heat sink. Microprismatic trasparent polycarbonate dome refractor optic.

ON DEMAND

Easy Custom Colour

Ra97

2700K - 3500K

A professional suspension fixture from the CCTLED range. Available with a faceted transparent polycarbonate optic for diffused lighting, complete with micro prismatic dome refractor to screen the source and to distribute the light softly.

CCTLED PENDANT

Ambient



LED / 18W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			39°	
	Fixture Power	20W	1	0.71	2757
	Source Flux	2756lm	2	1.42	689
	Fixture Flux	1663lm	3	2.12	306
	Efficacy	82lm/W	4	2.83	172
	Imax	2757cd	5	3.54	110

Kg	Driver	3000K	4000K
2	EL.	**1T3274**	**1T3275**
2	DALI	**1T3298**	**1T3299**
2.7	EL. EM.	**1T3322**	**1T3323**
2.7	DALI EM.	**1T3346**	**1T3347**

LED / 25W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			39°	
	Fixture Power	29W	1	0.71	3662
	Source Flux	3663lm	2	1.42	916
	Fixture Flux	2210lm	3	2.12	407
	Efficacy	76lm/W	4	2.83	229
	Imax	3662cd	5	3.54	146

Kg	Driver	3000K	4000K
2	EL.	**1T3272**	**1T3273**
2	DALI	**1T3296**	**1T3297**
2.7	EL. EM.	**1T3320**	**1T3321**
2.7	DALI EM.	**1T3344**	**1T3345**

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Accessories

Decorative Ring

Colour	Code
●	**1T4061**
○	**1T4062**

Dissipator cover.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTLED TUBE

GENERAL INFO
Ceiling-mounted, pendant, wall-mounted or track-mounted luminaire for high output LED sources.
Ø180mm

LED
Chip on board
From 2269lm to 4462lm
3000K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 123lm/W

OPTICS
SMART HE – TECH – FEEL – DEEP

POWER SUPPLY
Casambi control system available using a dedicated accessory (only for DALI version products)

MATERIAL
Painted aluminium body.
Painted polycarbonate decorative squared ring.
Black painted die-cast aluminium internal frame and heat sink

ON DEMAND

Easy Custom Colour

Ra97

2700K-3500K

Belongs to the CCTLED range with different installation solutions: ceiling, suspension, wall and track. It also comes in the same power supply and optics in order to use the same fixture in an entire project. The same uniform quality effect with different installation solutions.

SMART, TECH, FEEL optics for a variety of environments, from retail, to hospitality, up to office spaces (SMART UGR<22, TECH UGR<19, FEEL UGR>19 - EN 12464-1).

CCTLED TUBE

Smart Facetted



LED / 18W / FACETTED / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			82°	
Fixture Power	21W	1	1.73	1466
Source Flux	2756lm	2	3.45	367
Fixture Flux	2360lm	3	5.18	163
Efficacy	111lm/W	4	6.90	92
Imax	1632cd	5	8.63	59

TS658 Imax=592cd/klm

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	○	**1T3162**	**1T3163**
2	ENEC	DALI	○	**1T3182**	**1T3183**
2.5		EL. EM.	○	**1T3202**	**1T3203**
2.5		DALI EM.	○	**1T3222**	**1T3223**

LED / 25W / FACETTED / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			82°	
Fixture Power	29W	1	1.73	1963
Source Flux	3663lm	2	3.45	491
Fixture Flux	3160lm	3	5.18	218
Efficacy	109lm/W	4	6.90	123
Imax	2185cd	5	8.63	79

TS653 Imax=597cd/klm

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	○	**1T3174**	**1T3175**
2	ENEC	DALI	○	**1T3194**	**1T3195**

Smart Matt



LED / 18W / MATT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			72°	
Fixture Power	21W	1	1.46	1904
Source Flux	2756lm	2	2.91	476
Fixture Flux	2337lm	3	4.37	212
Efficacy	110lm/W	4	5.82	119
Imax	1904cd	5	7.28	76

TS657 Imax=691cd/klm

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	○	**1T3164**	**1T3165**
2	ENEC	EL.	○	**1T4455**	
2	ENEC	DALI	○	**1T3184**	**1T3185**
2	ENEC	DALI	○	**1T4457**	
2.5		EL. EM.	○	**1T3204**	**1T3205**
2.5		DALI EM.	○	**1T3224**	**1T3225**

LED / 25W / MATT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			72°	
Fixture Power	29W	1	1.46	2527
Source Flux	3663lm	2	2.92	632
Fixture Flux	3106lm	3	4.37	281
Efficacy	107lm/W	4	5.83	158
Imax	2527cd	5	7.29	101

TS654 Imax=690cd/klm

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	○	**1T3176**	**1T3177**
2	ENEC	EL.	○	**1T4456**	
2	ENEC	DALI	○	**1T3196**	**1T3197**
2	ENEC	DALI	○	**1T4458**	

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

CCTLED TUBE

Related codes

Mounting System

Driver	Colour	Code
EL.	○	**1T0130**
DALI	○	**1T0130DA**
EL.	◐	**1T4465**

Eurostandard Plus track kit.

Driver	Colour	Code
EL./EL. EM.	●	**1T0123**
DALI	●	**1T0123DA**
EL./EL. EM.	◐	**1T4466**
DALI	◐	**1T4467**
DALI EM.	●	**1T3243**

Ceiling mounting kit.

L	Driver	Colour	Code
1000	EL./EL. EM.	○	**1T0124**
1000	DALI	○	**1T0124DA**
6000	EL./EL. EM.	◐	**1T4469**
6000	DALI	◐	**1T4470**
1000	DALI EM.	○	**1T3244**

Suspension kit.

L	Driver	Colour	Code
2000	EL./EL. EM.	○	**1T3245**
2000	DALI	○	**1T3246**
6000	EL./EL. EM.	◐	**1T4472**
6000	DALI	◐	**1T4473**
2000	DALI EM.	○	**1T3247**

Double suspension kit.



Driver	Colour	Code
EL.	○	**1T7402**

Eurostandard Plus track suspension kit.



Driver	Colour	Code
DALI	○	**1T3242DA**

Eurostandard Plus track suspension kit.

Driver	Colour	Code
EL./EL. EM.	○	**1T3449**
DALI	○	**1T3450**
EL./EL. EM.	◐	**1T4475**
DALI	◐	**1T4476**
DALI EM.	○	**1T3451**

Wall mounting kit.

Driver	Colour	Code
EL./EL. EM.	○	**1T3452**
DALI	○	**1T3453**
EL./EL. EM.	◐	**1T4478**
DALI	◐	**1T4479**
DALI EM.	○	**1T3454**

Wall mounting kit for double emission.

CCTLED TUBE

Accessories

Decorative Ring



Ø	Colour	Code
180	◯	**1T3248**

Round ring.



Ø	Colour	Code
180	◯	**1T3249**

Square ring with micro prismatic diffusive screen.



Ø	Colour	Code
180	◯	**1T3250**

Square ring with external silk screen printed screen.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTLED TUBE

Tech Secondary facetted



LED / 15W / FACETTED / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			70°	
Fixture Power	17W	1	1.39	1689
Source Flux	2520lm	2	2.78	422
Fixture Flux	2070lm	3	4.16	188
Efficacy	120lm/W	4	5.55	106
Imax	1817cd	5	6.94	68

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	◯	**1T3166**	**1T3167**
2	ENEC	DALI	◯	**1T3186**	**1T3187**
2.5		EL. EM.	◯	**1T3206**	**1T3207**
2.5		DALI EM.	◯	**1T3226**	**1T3227**

LED / 21W / FACETTED / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			70°	
Fixture Power	24W	1	1.39	2172
Source Flux	3240lm	2	2.78	543
Fixture Flux	2662lm	3	4.16	241
Efficacy	111lm/W	4	5.55	136
Imax	2336cd	5	6.94	87

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	◯	**1T3178**	**1T3179**
2	ENEC	DALI	◯	**1T3198**	**1T3199**
2.5		EL. EM.	◯	**1T3218**	**1T3219**
2.5		DALI EM.	◯	**1T3238**	**1T3239**

Tech Secondary matt



LED / 15W / MATT / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			69°	
Fixture Power	17W	1	1.38	1679
Source Flux	2520lm	2	2.77	420
Fixture Flux	2070lm	3	4.15	187
Efficacy	120lm/W	4	5.54	105
Imax	1847cd	5	6.92	67

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	◯	**1T3168**	**1T3169**
2	ENEC	EL.	◯	**1T4459**	
2	ENEC	DALI	◯	**1T3188**	**1T3189**
2	ENEC	DALI	◯	**1T4461**	
2.5		EL. EM.	◯	**1T3208**	**1T3209**
2.5		DALI EM.	◯	**1T3228**	**1T3229**

LED / 21W / MATT / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			69°	
Fixture Power	24W	1	1.38	2159
Source Flux	3240lm	2	2.77	540
Fixture Flux	2662lm	3	4.15	240
Efficacy	111lm/W	4	5.54	135
Imax	2375cd	5	6.92	86

Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	◯	**1T3180**	**1T3181**
2	ENEC	EL.	◯	**1T4460**	
2	ENEC	DALI	◯	**1T3200**	**1T3201**
2	ENEC	DALI	◯	**1T4462**	
2.5		EL. EM.	◯	**1T3220**	**1T3221**
2.5		DALI EM.	◯	**1T3240**	**1T3241**

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

CCTLED TUBE

Related codes

Mounting System

	Driver	Colour	Code
	EL.	○	**1T0130**
	DALI	○	**1T0130DA**
	EL.	◐	**1T4465**

Eurostandard Plus track kit.

	Driver	Colour	Code
	EL./EL. EM.	●	**1T0123**
	DALI	●	**1T0123DA**
	EL./EL. EM.	◐	**1T4466**
	DALI	◐	**1T4467**
	DALI EM.	●	**1T3243**

Ceiling mounting kit.

	L	Driver	Colour	Code
	1000	EL./EL. EM.	○	**1T0124**
	1000	DALI	○	**1T0124DA**
	6000	EL./EL. EM.	◐	**1T4469**
	6000	DALI	◐	**1T4470**
	1000	DALI EM.	○	**1T3244**

Suspension kit.

	L	Driver	Colour	Code
	2000	EL./EL. EM.	○	**1T3245**
	2000	DALI	○	**1T3246**
	6000	EL./EL. EM.	◐	**1T4472**
	6000	DALI	◐	**1T4473**
	2000	DALI EM.	○	**1T3247**

Double suspension kit.

	Driver	Colour	Code
	EL.	○	**1T7402**

Eurostandard Plus track suspension kit.

	Driver	Colour	Code
	DALI	○	**1T3242DA**

Eurostandard Plus track suspension kit.

	Driver	Colour	Code
	EL./EL. EM.	○	**1T3449**
	DALI	○	**1T3450**
	EL./EL. EM.	◐	**1T4475**
	DALI	◐	**1T4476**
	DALI EM.	○	**1T3451**

Wall mounting kit.

	Driver	Colour	Code
	EL./EL. EM.	○	**1T3452**
	DALI	○	**1T3453**
	EL./EL. EM.	◐	**1T4478**
	DALI	◐	**1T4479**
	DALI EM.	○	**1T3454**

Wall mounting kit for double emission.

CCTLED TUBE

Accessories

Decorative Ring



Ø	Colour	Code
180	◯	**1T3248**

Round ring.



Ø	Colour	Code
180	◯	**1T3249**

Square ring with micro prismatic diffusive screen.



Ø	Colour	Code
180	◯	**1T3250**

Square ring with external silk screen printed screen.



Ø	Colour	Code
180	◯	**1T3251**

XL ring.
For the TECH version.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

CCTLED TUBE

Feel Facetted



LED / 14W / FACETTED / VWFL



Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	○	**1T3170**	**1T3171**
2	ENEC	DALI	○	**1T3190**	**1T3191**
2.5		EL. EM.	○	**1T3210**	**1T3211**
2.5		DALI EM.	○	**1T3230**	**1T3231**

Feel Matt



LED / 14W / MATT / WFL



Kg	Certificate	Driver	Colour	3000K	4000K
2	ENEC	EL.	○	**1T3172**	**1T3173**
2	ENEC	EL.	◐	**1T4463**	
2	ENEC	DALI	○	**1T3192**	**1T3193**
2	ENEC	DALI	◐	**1T4464**	
2.5		EL. EM.	○	**1T3212**	**1T3213**
2.5		DALI EM.	○	**1T3232**	**1T3233**

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Related codes

Mounting System

Driver	Colour	Code
EL.	○	**1T0130**
DALI	○	**1T0130DA**
EL.	◐	**1T4465**

Eurostandard Plus track kit.

Driver	Colour	Code
EL./EL. EM.	●	**1T0123**
DALI	●	**1T0123DA**
EL./EL. EM.	◐	**1T4466**
DALI	◐	**1T4467**
DALI EM.	●	**1T3243**

Ceiling mounting kit.

CCTLED TUBE

	L	Driver	Colour	Code
	1000	EL./EL. EM.	○	**1T0124**
	1000	DALI	○	**1T0124DA**
	6000	EL./EL. EM.	○	**1T4469**
	6000	DALI	○	**1T4470**
	1000	DALI EM.	○	**1T3244**

Suspension kit.

	L	Driver	Colour	Code
	2000	EL./EL. EM.	○	**1T3245**
	2000	DALI	○	**1T3246**
	6000	EL./EL. EM.	○	**1T4472**
	6000	DALI	○	**1T4473**
	2000	DALI EM.	○	**1T3247**

Double suspension kit.



	Driver	Colour	Code
	EL.	○	**1T7402**

Eurostandard Plus track suspension kit.



	Driver	Colour	Code
	DALI	○	**1T3242DA**

Eurostandard Plus track suspension kit.

	Driver	Colour	Code
	EL./EL. EM.	○	**1T3449**
	DALI	○	**1T3450**
	EL./EL. EM.	○	**1T4475**
	DALI	○	**1T4476**
	DALI EM.	○	**1T3451**

Wall mounting kit.

	Driver	Colour	Code
	EL./EL. EM.	○	**1T3452**
	DALI	○	**1T3453**
	EL./EL. EM.	○	**1T4478**
	DALI	○	**1T4479**
	DALI EM.	○	**1T3454**

Wall mounting kit for double emission.

Accessories

Decorative Ring



	Ø	Colour	Code
	180	○	**1T3248**

Round ring.



	Ø	Colour	Code
	180	○	**1T3249**

Square ring with micro prismatic diffusive screen.



	Ø	Colour	Code
	180	○	**1T3250**

Square ring with external silk screen printed screen.

CCTLED TUBE

Adapter



Ø	H	Driver	Colour	Code
100	32	EL.	○	**1T2221**
100	32	EL.	●	**1T2220**
100	32	EL.	◍	**1T2219**

Base for ceiling installation of projectors with an adapter for electrified track.



Ø	H	Driver	Colour	Code
118	38	DALI	○	**9000/BPU-D-W**
118	38	DALI	◍	**9000/BPU-D-B**
118	38	DALI	◍	**9000/BPU-D-G**

Base for ceiling installation of projectors with an adapter for electrified track.



Cutout hole	Ø	H	Driver	Colour	Code
Ø105/125	130	60	EL.	○	**1T2223**
Ø105/125	130	60	EL.	●	**1T2222**
Ø105/125	130	60	EL.	◍	**1T2224**

Adapter for recessed installation of the base.
1T2222 - To be completed with 1T2220.
1T2223 - To be completed with 1T2221.
1T2224 - To be completed with 1T2219.



Cutout hole	Ø	H	Driver	Colour	Code
Ø125/130	144	67	DALI	○	**9000/BRU-W**
Ø125/130	144	67	DALI	◍	**9000/BRU-B**
Ø125/130	144	67	DALI	◍	**9000/BRU-G**

Adapter for recessed installation of the base.
9000/BRU-G - To be completed with 9000/BPU-D-G.
9000/BRU-W - To be completed with 9000/BPU-D-W.
9000/BRU-B - To be completed with 9000/BPU-D-B.

Control systems

Code
1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

Code
1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

BEBOP

Ceiling / Suspension

GENERAL INFO
LED pendant and ceiling mounted for direct diffuse lighting.
Ø90mm

LED
Chip on board
From 1706lm to 1750lm
3000K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 91lm/W

OPTICS
MWFL - WFL

POWER SUPPLY
Electronic

MATERIAL
Painted aluminium body. Painted polycarbonate front element. Die-cast aluminium finned internal heat sink.

ON DEMAND
Easy Custom Colour
2700K-3500K

A range of high performance products characterised by simple, soft and rounded lines. Available in three different versions for ceiling mounted, suspension and recessed installation.

Also available in a recessed installation version.

In all versions the LED lamps are retracted and hidden from view to ensure optimum visual comfort. The flexible installation makes it possible to use the same type of light in environments with different architectural characteristics.

BEBOP

Suspension



LED / 13W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		15W	1	0.90	1823
Source Flux		1706lm	2	1.79	456
Fixture Flux		1310lm	3	2.69	203
Efficacy		90lm/W	4	3.59	114
Imax		1840cd	5	4.48	73

Driver	Colour	3000K	4000K
EL.	○	**1T4764EL**	**1T4765EL**
EL.	◐	**1T5418EL**	**1T5419EL**

LED / 13W / WFL

	3000K		H(m)	D(m)	Emax(lx)
	Ra84			64°	
Fixture Power		15W	1	1.24	1087
Source Flux		1706lm	2	2.49	272
Fixture Flux		1285lm	3	3.73	121
Efficacy		89lm/W	4	4.98	68
Imax		1174cd	5	6.22	43

Driver	Colour	3000K	4000K
EL.	○	**1T4762EL**	**1T4763EL**
EL.	◐	**1T5420EL**	**1T5421EL**

Note

Complete with 2000mm long steel suspension cable with micrometric adjustment system.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Ceiling



LED / 13W / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		15W	1	0.90	1823
Source Flux		1706lm	2	1.79	456
Fixture Flux		1310lm	3	2.69	203
Efficacy		90lm/W	4	3.59	114
Imax		1840cd	5	4.48	73

Driver	Colour	3000K	4000K
EL.	○	**1T4768EL**	**1T4769EL**
EL.	◐	**1T5414EL**	**1T5415EL**

LED / 13W / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			64°	
Fixture Power		15W	1	1.24	1087
Source Flux		1706lm	2	2.49	272
Fixture Flux		1285lm	3	3.73	121
Efficacy		89lm/W	4	4.98	68
Imax		1174cd	5	6.22	43

Driver	Colour	3000K	4000K
EL.	○	**1T4766EL**	**1T4767EL**
EL.	◐	**1T5416EL**	**1T5417EL**

GLOBO

GENERAL INFO
Diffused emission suspension fixture for halogen, LED lamp or compact fluorescent lamps with E27 lamp holder.
Ø350mm

LED
Lamp not included

MATERIAL
Metal frame and opaline glass diffuser.

Diffused emission suspension fixture. The high quality opaline glass diffuser ensure maximum light diffusion and perfect distribution over surfaces

It can be fitted with any type of lamp with an E27 adapter including LED.

GLOBO



FLUO/HAL / max 42W/max 100W / E27



2600K	
-	
Fixture Power	100W
Source Flux	1160lm
Fixture Flux	666lm
Efficacy	71m/W
Imax	62cd

	Power supply	Colour	Code
	220-240Vac		**344540**

Accessories

Control systems

	Code
	1T5351

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology.
It works with LED 230V-AC modules, dimmable LED sources and halogen lamps.
It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies.
It can manage systems with a maximum absorption of 150W.
The module is wireless controlled using a Casambi app for smartphones and tablets or traditional wall switches.
IP20.
LxHxP=40.4x14x36.3mm.

WASABI

GENERAL INFO
Diffused LED light suspension fixture.
Ø103mm – Ø125mm – Ø163mm

LED
Dimmable 230V LED module
From 806lm to 825lm
3000K
Ra80

PRODUCT EFFICACY
Up to 60lm/W

OPTICS
MWFL

POWER SUPPLY
Electronic
Casambi control system available by using a dedicated accessory (230Vac LED module max 150W).

MATERIAL
Satin polished and painted heat dissipator.
Diffuser in glazed opal glass.

ON DEMAND
Easy Custom Color

A suspension fixture with soft lines inspired by the orient that combines the lightness of glass with the technology in the LED module as well as the particular heatsink with a shape inspired by nature.

No driver necessary thanks to the 230V LED module for maximum installation flexibility. Available in three different sizes.

WASABI

Ø 163mm



LED / 13W

3000K		H(m)	D(m)	Emax(lx)
Ra80			21°	
Fixture Power	14W	1	0.38	376
Source Flux	808lm	2	0.75	94
Fixture Flux	808lm	3	1.13	42
Efficacy	59lm/W	4	1.50	24
Imax	376cd	5	1.88	15

Power supply	Colour	3000K
220-240Vac	○	**1T3979**
220-240Vac	◐	**1T3980**

Ø 125mm



LED / 13W

3000K		H(m)	D(m)	Emax(lx)
Ra80			9°	
Fixture Power	14W	1	0.17	202
Source Flux	806lm	2	0.33	50
Fixture Flux	806lm	3	0.50	22
Efficacy	59lm/W	4	0.66	13
Imax	202cd	5	0.83	8

Power supply	Colour	3000K
220-240Vac	○	**1T3991**
220-240Vac	◐	**1T3992**

Ø 103mm



LED / 13W

3000K		H(m)	D(m)	Emax(lx)
Ra80			14°	
Fixture Power	14W	1	0.25	319
Source Flux	825lm	2	0.49	80
Fixture Flux	825lm	3	0.74	35
Efficacy	60lm/W	4	0.99	20
Imax	319cd	5	1.23	13

Power supply	Colour	3000K
220-240Vac	○	**1T3985**
220-240Vac	◐	**1T3986**

WASABI

Accessories

Canopy



	Colour	Code
	○	**1T3978**
	●	**1T5430**

Canopy.

Control systems

	Code
	1T5351

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology.
It works with LED 230V-AC modules, dimmable LED sources and halogen lamps.
It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies.
It can manage systems with a maximum absorption of 150W.
The module is wireless controlled using a Casambi app for smartphones and tablets or traditional wall switches.
IP20.
LxHxP=40.4x14x36.3mm.

DECANTER

GENERAL INFO
LED suspension for direct diffuse lighting.
Ø170mm – Ø320mm – Ø480mm

LED
Circular LED board
From 264lm to 1553lm
3000K
Ra84

PRODUCT EFFICACY
Up to 104lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic

MATERIAL
Disc made of Baydur® (large and medium models) or aluminium (small version). Aluminium stem and decorative canopy matt painted. Microprismatic diffuser in transparent PMMA. Painted decorative canopy.

ON DEMAND
Easy Custom Colour

Its sinuous shape is the result of research into innovative materials and moulding techniques that make it possible to obtain extremely thin thicknesses; the result is a light suspension fixture with excellent mechanical resistance.

The special micro prismatic screen ensures perfect, particularly homogeneous light diffusion that is comfortable to the eye. Available in three different sizes, from extremely small for decorative light up to an excellent light on work surfaces.

DECANTER

Ø 170mm



LED / 4W / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			83°	
Fixture Power	6W	1	1.78	140
Source Flux	264lm	2	3.56	35
Fixture Flux	264lm	3	5.34	16
Efficacy	44lm/W	4	7.12	9
Imax	140cd	5	8.90	6

TS626 Imax=532cd/klm

Driver	Colour	3000K
EL.	○	**1T4076**
EL.	◐	**1T4077**

Ø 320mm



LED / 9W / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			83°	
Fixture Power	10W	1	1.76	295
Source Flux	528lm	2	3.53	74
Fixture Flux	528lm	3	5.29	33
Efficacy	53lm/W	4	7.06	18
Imax	295cd	5	8.82	12

TS627 Imax=558cd/klm

Driver	Colour	3000K
EL.	○	**1T4082**
EL.	◐	**1T4083**

Ø 480mm



LED / 13W / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			84°	
Fixture Power	15W	1	1.80	851
Source Flux	1553lm	2	3.60	213
Fixture Flux	1553lm	3	5.40	95
Efficacy	104lm/W	4	7.21	53
Imax	853cd	5	9.01	34

TS628 Imax=549cd/klm

Driver	Colour	3000K
EL.	○	**1T4088**
EL.	◐	**1T4089**

Wall mounted luminaires

Indoor

Upgrade


454

526


528

530

532

534

536

536

536

536

536

540

540

540

540

FLOOD

GENERAL INFO
Wall mounted fixture with indirect light emission for LED sources.
224x330mm
224x700mm

LED
Linear boards
From 2610lm to 5220lm
3000K
Ra80 - Ra90

PRODUCT EFFICACY
Up to 119lm/W

OPTICS
VWFL

POWER SUPPLY
DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Painted metal body.
Transparent protective screen.

ON DEMAND
Easy Custom Colour

Wall mounted fixture with indirect light available in two different lengths with two different power supplies for soft and comfortable indirect light. It is suitable for lighting small and large spaces.



Design Daniel Bernard

FLOOD



L. 330mm



LED / 18W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			117°	
	Fixture Power	22W	1	3.29	875
	Source Flux	2610lm	2	6.57	219
	Fixture Flux	2432lm	3	9.86	97
	Efficacy	111lm/W	4	13.14	55
	Imax	875cd	5	16.43	35

	Driver	Colour	3000K
	DALI	○	**1T4512**
	DALI	●	**1T4514**

L. 700mm



LED / 36W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			117°	
	Fixture Power	41W	1	3.29	1751
	Source Flux	5220lm	2	6.57	438
	Fixture Flux	4865lm	3	9.86	195
	Efficacy	119lm/W	4	13.14	109
	Imax	1751cd	5	16.43	70

	Driver	Colour	3000K
	DALI	○	**1T4513**
	DALI	●	**1T4515**

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra80).

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

HALL

GENERAL INFO
Wall mounted fixture with indirect light emission for LED sources.
297x330x112mm

LED
LED Low Power High Efficiency Linear boards
5160lm
3000K
Ra80 - Ra90

PRODUCT EFFICACY
111lm/W

OPTICS
ASYM

POWER SUPPLY
DALI - Casambi on board

MATERIAL
Painted metal body.
Diffuse protective screen.

ON DEMAND
Easy Custom Colour

Professional applique with indirect light emission with an asymmetrical optic.
The strongly asymmetric emission allows for deep indirect lighting of large spaces.

Used on its own it is capable of producing soft and comfortable light: combined with direct lighting on the other hand it balances and improves visual comfort throughout the space.



Design Daniel Bernard

HALL





LED / 36W / ASYMMETRICAL



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra80			121°	89°	
Fixture Power	40W	1	3.52	4.23	1670
Source Flux	5160lm	2	7.03	8.46	418
Fixture Flux	4453lm	3	10.55	12.69	186
Efficacy	111lm/W	4	14.07	16.93	104
TS892 Imax=487cd/klm	Imax	2511cd	5	17.59	21.16	67

	Driver	Colour	3000K
	DALI		**1T4499**
	DALI		**1T4506**
	DALI		**1T4507**
	CASAMBI		**1T4499CA**

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra80).

Accessories

Control systems

	Code
	1T5349

Wireless control unit for DALI fixtures.
It generates a local DALI bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.
LxHxP=56.5x22.3x35.8mm.

	Code
	1T5352

IP20 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.
LxHxP=129x30x42mm.

SLIM

Wall mounted

GENERAL INFO
Indirect or direct/indirect modular wall mounted luminaire for LED sources.
638x26x80
1238x26x80

LED
Linear LED boards Low Power High efficiency
From 1720lm to 6880lm
3000K
Ra80 - Ra84

PRODUCT EFFICACY
Up to 112lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic

MATERIAL
Body made of extruded anodised aluminium. Polycarbonate lateral end caps. Lower diffusive screen made of ribbed, extruded opal polycarbonate. Transparent polycarbonate upper safety screen.

Compact size minimal modular applique with indirect/direct light emission that disappears into its surroundings leaving space for the architecture and light only.

Also available in a modular system suspension version or stand-alone, as well as a rectangular version that is particularly suitable for lighting open spaces in the office environment. Coordinates with the indirect or direct/indirect light emission wall mounted solution.

Design Daniel Bernard

SLIM

Wall L. 638mm



LED / 12W / INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			115°	
Fixture Power	14W	1	3.13	546
Source Flux	1720lm	2	6.26	137
Fixture Flux	1562lm	3	9.39	61
Efficacy	112lm/W	4	12.52	34
TS751 Imax=318cd/klm	Imax 547cd	5	15.65	22

Driver	Colour	3000K
EL.		**1T4192**

LED / 24W / DIRECT/INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			95°	
Fixture Power	28W	1	2.19	501
Source Flux	3440lm	2	4.37	125
Fixture Flux	2567lm	3	6.56	56
Efficacy	92lm/W	4	8.75	31
TS752 Imax=147cd/klm	Imax 505cd	5	10.93	20

Driver	Colour	3000K
EL.		**1T4193**

Wall L. 1238mm



LED / 24W / INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			115°	
Fixture Power	28W	1	3.13	1092
Source Flux	3440lm	2	6.26	273
Fixture Flux	3125lm	3	9.39	121
Efficacy	112lm/W	4	12.52	68
TS751 Imax=318cd/klm	Imax 1095cd	5	15.65	44

Driver	Colour	3000K
EL.		**1T4194**

LED / 48W / DIRECT/INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			95°	
Fixture Power	56W	1	2.19	1002
Source Flux	6880lm	2	4.37	250
Fixture Flux	5133lm	3	6.56	111
Efficacy	92lm/W	4	8.75	63
TS752 Imax=147cd/klm	Imax 1009cd	5	10.93	40

Driver	Colour	3000K
EL.		**1T4195**

MINIMINIMA

Wall mounted

GENERAL INFO
Wall mounted fixture for LED sources with indirect or direct/indirect light emission.
600x50x32mm

LED
Linear Board LED Low Power High Efficiency
1720lm
3000K
Ra80 - Ra90

PRODUCT EFFICACY
Up to 60lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic

MATERIAL
Body made of chromed or painted aluminium with opal polycarbonate diffuser.

ON DEMAND
Easy Custom Colour

A unique, thin linear element designed to remove sharp edges without connecting elements and any visible fastening system.

Available in different types to meet different needs: only indirect or combined direct/ indirect light emission.



MINIMINIMA

Wall



LED / 12W / INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra80			111°	
Fixture Power	14W	1	2.89	321
Source Flux	1720lm	2	5.79	80
Fixture Flux	842lm	3	8.68	36
Efficacy	60lm/W	4	11.58	20
TS749 Imax=187cd/klm	Imax 321cd	5	14.47	13

	Driver	Colour	3000K
	EL.		**1T4170**
	EL.		**1T4171**
	EL.		**1T4172**
	EL.		**1T4173**

LED / 12W / DIRECT/INDIRECT / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra80			114°	
Fixture Power	14W	1	3.08	185
Source Flux	1720lm	2	6.15	46
Fixture Flux	1071lm	3	9.23	21
Efficacy	76lm/W	4	12.31	12
TS750 Imax=112cd/klm	Imax 192cd	5	15.38	7

	Driver	Colour	3000K
	EL.		**1T4174**
	EL.		**1T4175**
	EL.		**1T4176**
	EL.		**1T4177**

Note

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra80).

BRAQUE

GENERAL INFO
Indirect emission wall mounted LED fixture.
200x79x29mm
65x200x29mm

LED
LED module 230V
893lm
3000K
Ra80

PRODUCT EFFICACY
65lm/W

OPTICS
VWFL

POWER SUPPLY
No driver necessary
Casambi control system available by using a dedicated accessory (230Vac LED module max 150W).

MATERIAL
Matt painted aluminium body. Transparent polycarbonate screen.

ON DEMAND
Easy Custom Colour

Metal applique with sharp edges with mains voltage LED lamps. The special type of machining of the piece hollowed out from a solid provides perfect edges without visible joints or screws.

Available in two different sizes and two different installation types.

It doesn’t need to the driver.



BRAQUE

Pependicular



LED / 13W / VWFL



		3000K		H(m)	D1(m)	D2(m)	Emax(lx)
		Ra80			110°	108°	
	Fixture Power		14W	1	2.86	2.73	348
	Source Flux		893lm	2	5.72	5.46	87
	Fixture Flux		893lm	3	8.58	8.18	39
	Efficacy		65lm/W	4	11.44	10.91	22
TS770	Imax=389cd/klm	Imax	348cd	5	14.29	13.64	14

Colour	3000K
○	**1T3762**
◐	**1T3763**



Parallel



LED / 13W / VWFL



		3000K		H(m)	D1(m)	D2(m)	Emax(lx)
		Ra80			110°	108°	
	Fixture Power		14W	1	2.86	2.73	348
	Source Flux		893lm	2	5.72	5.46	87
	Fixture Flux		893lm	3	8.58	8.18	39
	Efficacy		65lm/W	4	11.44	10.91	22
TS770	Imax=389cd/klm	Imax	348cd	5	14.29	13.64	14

Colour	3000K
○	**1T3759**
◐	**1T3760**

Accessories

Control systems

	Code
	1T5351

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology.
It works with LED 230V-AC modules, dimmable LED sources and halogen lamps.
It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies.
It can manage systems with a maximum absorption of 150W.
The module is wireless controlled using a Casambi app for smartphones and tablets or traditional wall switches.
IP20.
LxHxP=40.4x14x36.3mm.

OSIRIDE

GENERAL INFO
Wall or ceiling mounted fixture for halogen or compact fluorescent lamps or LED version.
Ø200mm – Ø260mm
Ø320mm – Ø400mm – Ø500mm

LED
LED Version
Ø260mm
230V LED module

Ø320MM – Ø400MM
Circular boards
From 619lm to 993m
3000K
Ra84

PRODUCT EFFICACY
LED Version
Up to 99lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic
Casambi control system available by using a dedicated accessory (230Vac LED module max 150W).

MATERIAL
White painted metal body and satin opaline white glass diffuser.

ON DEMAND
(Osiride LED Ø320mm and Ø400mm)

Dimmable version

A range of glass ceiling/wall fixtures satin opaline white glass and a painted white metal frame.

Five different sizes that can be equipped with halogen lamps, compact fluorescent lamps or LED lamps with E27 adapters not included or a 230V LED version with the LED lamp included.



OSIRIDE



Ø 200mm



FLUO/HAL / max 1x42W/max 1x60W / E27

1,1 IP44

Power supply	Colour	Code
220-240Vac		**323494IP**

Ø 260mm



FLUO/HAL / max 1x42W/max 1x60W / E27

1,5 IP44

Power supply	Colour	Code
220-240Vac		**323404IP**

Ø 320mm



FLUO/HAL / max 2x42W/max 2x60W / E27

2,5 IP44

Power supply	Colour	Code
220-240Vac		**323414IP**

OSIRIDE

Ø 400mm



FLUO/HAL / max 2x42W/max 2x60W / E27

3,7 IP44

	Power supply	Colour	Code
	220-240Vac		**323424IP**

Ø 500mm



FLUO/HAL / max 2x42W/max 2x60W / E27

4,6 IP44

	Power supply	Colour	Code
	220-240Vac		**323434IP**

LED Ø 260mm



LED / 14W / VWFL

1,5 IP44



3000K		H(m)	D(m)	Emax(lx)
Ra84			121°	
Fixture Power	14W	1	3.56	164
Source Flux	619lm	2	7.12	41
Fixture Flux	619lm	3	10.68	18
Efficacy	45lm/W	4	14.25	10
Imax	164cd	5	17.81	7

	Power supply	Driver	Colour	3000K
	220-240Vac			**1T4002**

OSIRIDE

LED Ø 320mm



LED / 8W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			121°	
Fixture Power		10W	1	3.56	263
Source Flux		993lm	2	7.12	66
Fixture Flux		993lm	3	10.68	29
Efficacy		99lm/W	4	14.25	16
Imax		263cd	5	17.81	11

Power supply	Driver	Colour	3000K
220-240Vac	EL.		**1T4003**

LED Ø 400mm



LED / 8W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			121°	
Fixture Power		10W	1	3.56	236
Source Flux		892lm	2	7.12	59
Fixture Flux		892lm	3	10.68	26
Efficacy		89lm/W	4	14.25	15
Imax		236cd	5	17.81	9

Power supply	Driver	Colour	3000K
220-240Vac	EL.		**1T4004**

Accessories

Mounting System

Code
323900

Support for semi-recessed installation.
D=200mm cutout hole 147mm.
D=260mm cutout hole 193mm.
D=320mm cutout hole 244mm.
D=400mm cutout hole 322mm.
D=500mm cutout hole 368mm.

Control systems

Code
1T5351

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology.
It works with LED 230V-AC modules, dimmable LED sources and halogen lamps.
It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies.
It can manage systems with a maximum absorption of 150W.
The module is wireless controlled using a Casambi app for smartphones and tablets or traditional wall switches.
IP20.
LxHxP=40.4x14x36.3mm.

PROFESSIONAL

GENERAL INFO
Wall or ceiling mounted fixture for LED, halogen or compact fluorescent lamps or LED 230V integrated version.
120x220mm
235x235mm
275x275mm
350x350mm

LED
LED VERSION 235x235
230V Module
LED VERSION 275x275mm
Circular boards
From 722lm to 936lm
3000K
Ra84

LAMPS
HAL – FLUO – LED
2xmax42W
TC-DEL 2x18W
Not included

PRODUCT EFFICACY
94lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic
Casambi control system available by using a dedicated accessory (Professional LED 14W)

MATERIAL
White painted metal body and satin opaline white glass diffuser.
White painted metal fixing plate.

ON DEMAND
(Professional LED 8W)

Dimmable version

A wall or ceiling mounted fixture with a glazed glass diffuser for soft general lighting.

Available in four different sizes fitted with traditional LED lamps with E27 adapters or compact fluorescent lamps not included.

Available also in a LED 230V version.

PROFESSIONAL

120x220mm



FLUO/HAL / max 1x42W/max 1x60W / E27

Power supply	Driver	Colour	Code
220-240Vac			**374604IP**

235x235mm



FLUO/HAL / max 1x42W/max 1x60W / E27

Power supply	Driver	Colour	Code
220-240Vac			**374404IP**

TC-TEL / 1x26W / GX24q-3

Power supply	Driver	Colour	Code
220-240Vac	EL.		**374404E**

PROFESSIONAL

275x275mm



FLUO/HAL / max 2x42W/max 2x60W / E27

2,2 IP44

	Power supply	Driver	Colour	Code
	220-240Vac			**374414IP**

TC-DEL / 2x18W / G24q-2

2,8 IP44

	Power supply	Driver	Colour	Code
	220-240Vac	EL.		**374414E**

350x350mm



FLUO/HAL / max 3x42W/max 3x60W / E27

4,8 IP44

	Power supply	Driver	Colour	Code
	220-240Vac			**374424IP**

TC-TEL / 2x42W / GX24q-4

5 IP44

	Power supply	Driver	Colour	Code
	220-240Vac	EL.		**374424E**

PROFESSIONAL

LED 235x235mm



LED / 14W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			135°	
Fixture Power		14W	1	4.86	142
Source Flux		722lm	2	9.72	36
Fixture Flux		722lm	3	14.58	16
Efficacy		52lm/W	4	19.44	9
TS802	Imax=197cd/klm	Imax	143cd	5	24.30	6

Power supply	Driver	Colour	3000K
220-240Vac			**1T4005**

LED 275x275mm



LED / 8W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			135°	
Fixture Power		10W	1	4.86	184
Source Flux		936lm	2	9.72	46
Fixture Flux		936lm	3	14.58	20
Efficacy		94lm/W	4	19.44	12
TS802	Imax=197cd/klm	Imax	185cd	5	24.30	7

Power supply	Driver	Colour	3000K
220-240Vac	EL.		**1T4006**

Accessories

Control systems

Code
1T5351

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology.
It works with LED 230V-AC modules, dimmable LED sources and halogen lamps.
It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies.
It can manage systems with a maximum absorption of 150W.
The module is wireless controlled using a Casambi app for smartphones and tablets or traditional wall switches.
IP20.
LxHxP=40.4x14x36.3mm.

Inground recessed

Outdoor

New Upgrade

Linear inground recessed



546
JEDI

546
JEDI RGBW



558
JEDI Compact

574
MERCURE
Light-line

574
MINIMERCURE
LED - RGB

574
MICROMERCURE

Inground recessed



582
KEPLERO
Zoom



582
KEPLERO
Zoom RGBW



582
KEPLERO
Gimbal

582
KEPLERO
Gimbal HP



582
KEPLERO
WW



582
KEPLERO
WW RGBW

582
KEPLERO
Mini Zoom

582
KEPLERO
Mini Gimbal

582
KEPLERO
Mini HE

582
KEPLERO
Mini HE RGBW



582
KEPLERO
Mini WW

622
JUPITER
Ø 80mm



622
JUPITER
Mini
Ø 50mm

632
SATURN
Ø 60mm



632
SATURN
Mini
Ø 35mm



638
LED.Y
Multiled
Ø60mm Ø68mm



638
LED.Y
Monoled
Ø 63mm



638
LED.Y
Monoled RGB
Ø 63mm

644
TITANO

JEDI

Recessed

GENERAL INFO
Recessed linear projector.
Lenghts 616mm – 916mm – 1216mm

LED
Optics FL, GR, WW - Linear boards
Optic SP - Led Emitter
RGBW version - Led Emitter
From 632lm to 7180lm
3000K – 4000K
Ra84
RGBW

PRODUCT EFFICACY
Up to 113lm/W

OPTICS
SP – FL – GRAZING – WALL WASHER

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Extruded anodised aluminium 15µ body. Extra clear 10mm thick glass flat screen. Brushed stainless steel (AISI 316) frame. The body of the fixture can resist a static load up to 20kN and vandalism (IK10). Anti-slip glass available on request.

ON DEMAND

110-277Vac power supply (Jedi Recessed RGBW)

2700K - 3500K

A coordinated range of linear projectors for lighting large surfaces.

The multiplicity of effects, three different lengths with lumen packages proportioned to each one, maximum load and vandal resistance make it a flexible tool that can always provide solutions to various project needs in the public or private sector.

Completely sealed housing complete with external electrical connection through IP68 connectors.
Continuous line installation using accessories.

Available also in projector and RGBW versions.

Anti-theft Torx screws.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

5300 McConnell
Los Angeles, USA

Architect Shubin+Donaldson Architects
Lighting Design Oculus Light Studio

Photographer ©Henri Khodaverdi

JEDI



Recessed L. 616mm



LED / 23W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		28W	1	0.18	32201
Source Flux		1947lm	2	0.37	8050
Fixture Flux		1560lm	3	0.55	3578
Efficacy		56lm/W	4	0.73	2013
TS889	Imax=16539cd/klm	Imax	5	0.92	1288

Driver	Colour	3000K	4000K
EL.		**1E2737**	**1E2738**
DALI		**1E2739**	**1E2740**

LED / 12W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		15W	1	0.57	1.84	1203
Source Flux		1720lm	2	1.14	3.68	301
Fixture Flux		1285lm	3	1.70	5.53	134
Efficacy		86lm/W	4	2.27	7.37	75
TS886	Imax=699cd/klm	Imax	5	2.84	9.21	48

Driver	Colour	3000K	4000K
EL.		**1E2689**	**1E2690**
DALI		**1E2691**	**1E2692**

LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		28W	1	0.57	1.84	2392
Source Flux		3420lm	2	1.14	3.68	598
Fixture Flux		2555lm	3	1.70	5.53	266
Efficacy		91lm/W	4	2.27	7.37	149
TS885	Imax=699cd/klm	Imax	5	2.84	9.21	96

Driver	Colour	3000K	4000K
EL.		**1E2693**	**1E2694**
DALI		**1E2695**	**1E2696**

LED / 12W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		15W	1	0.26	1.55	2753
Source Flux		1720lm	2	0.51	3.10	688
Fixture Flux		1481lm	3	0.77	4.65	306
Efficacy		99lm/W	4	1.02	6.20	172
TS888	Imax=1601cd/klm	Imax	5	1.28	7.76	110

Driver	Colour	3000K	4000K
EL.		**1E2665**	**1E2666**
DALI		**1E2667**	**1E2668**

LED / 24W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		28W	1	0.26	1.55	5474
Source Flux		3420lm	2	0.51	3.10	1368
Fixture Flux		2961lm	3	0.77	4.65	608
Efficacy		106lm/W	4	1.02	6.21	342
TS887	Imax=1601cd/klm	Imax	5	1.28	7.76	219

Driver	Colour	3000K	4000K
EL.		**1E2669**	**1E2670**
DALI		**1E2671**	**1E2672**

JEDI

LED / 12W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			28°	78°	
Fixture Power	15W	1	0.55	1.70	1155
Source Flux	1720lm	2	1.11	3.40	289
Fixture Flux	1293lm	3	1.66	5.10	128
Efficacy	86lm/W	4	2.22	6.79	72
Imax	1331cd	5	2.77	8.49	46

TS884 Imax=774cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2713**	**1E2714**
DALI		**1E2715**	**1E2716**

LED / 24W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			28°	78°	
Fixture Power	28W	1	0.55	1.70	2297
Source Flux	3420lm	2	1.11	3.40	574
Fixture Flux	2572lm	3	1.66	5.10	255
Efficacy	92lm/W	4	2.22	6.79	144
Imax	2646cd	5	2.77	8.49	92

TS883 Imax=774cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2717**	**1E2718**
DALI		**1E2719**	**1E2720**



Recessed L. 916mm



LED / 34W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			10°	
Fixture Power	40W	1	0.18	48326
Source Flux	2922lm	2	0.37	12081
Fixture Flux	2341lm	3	0.55	5370
Efficacy	59lm/W	4	0.73	3020
Imax	48326cd	5	0.92	1933

TS889 Imax=16539cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2741**	**1E2742**
DALI		**1E2743**	**1E2744**

LED / 18W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			32°	85°	
Fixture Power	22W	1	0.57	1.84	1804
Source Flux	2580lm	2	1.14	3.68	451
Fixture Flux	1927lm	3	1.70	5.53	200
Efficacy	88lm/W	4	2.27	7.37	113
Imax	1804cd	5	2.84	9.21	72

TS886 Imax=699cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2697**	**1E2698**
DALI		**1E2699**	**1E2700**

LED / 36W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			32°	85°	
Fixture Power	40W	1	0.57	1.84	3588
Source Flux	5130lm	2	1.14	3.68	897
Fixture Flux	3833lm	3	1.70	5.53	399
Efficacy	96lm/W	4	2.27	7.37	224
Imax	3588cd	5	2.84	9.21	144

TS885 Imax=699cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2701**	**1E2702**
DALI		**1E2703**	**1E2704**

JEDI

LED / 18W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		22W	1	0.26	1.55	4130
Source Flux		2580lm	2	0.51	3.10	1032
Fixture Flux		2222lm	3	0.77	4.65	459
Efficacy		101lm/W	4	1.02	6.20	258
TS888	Imax=1601cd/klm	Imax 4130cd	5	1.28	7.76	165

Driver	Colour	3000K	4000K
EL.		**1E2673**	**1E2674**
DALI		**1E2675**	**1E2676**

LED / 36W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		40W	1	0.26	1.55	8211
Source Flux		5130lm	2	0.51	3.10	2053
Fixture Flux		4441lm	3	0.77	4.65	912
Efficacy		111lm/W	4	1.02	6.21	513
TS887	Imax=1601cd/klm	Imax 8211cd	5	1.28	7.76	328

Driver	Colour	3000K	4000K
EL.		**1E2677**	**1E2678**
DALI		**1E2679**	**1E2680**

LED / 18W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		22W	1	0.55	1.70	1733
Source Flux		2580lm	2	1.11	3.40	433
Fixture Flux		1940lm	3	1.66	5.10	193
Efficacy		88lm/W	4	2.22	6.79	108
TS884	Imax=774cd/klm	Imax 1996cd	5	2.77	8.49	69

Driver	Colour	3000K	4000K
EL.		**1E2721**	**1E2722**
DALI		**1E2723**	**1E2724**

LED / 36W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		40W	1	0.55	1.70	3445
Source Flux		5130lm	2	1.11	3.40	861
Fixture Flux		3858lm	3	1.66	5.10	383
Efficacy		96lm/W	4	2.22	6.79	215
TS883	Imax=774cd/klm	Imax 3969cd	5	2.77	8.49	138

Driver	Colour	3000K	4000K
EL.		**1E2725**	**1E2726**
DALI		**1E2727**	**1E2728**



Recessed L. 1216mm



LED / 46W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		51W	1	0.18	64401
Source Flux		3894lm	2	0.37	16100
Fixture Flux		3120lm	3	0.55	7156
Efficacy		61lm/W	4	0.73	4025
TS889	Imax=16539cd/klm	Imax 64401cd	5	0.92	2576

Driver	Colour	3000K	4000K
EL.		**1E2745**	**1E2746**
DALI		**1E2747**	**1E2748**

JEDI

LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		28W	1	0.57	1.84	2405
Source Flux		3440lm	2	1.14	3.68	601
Fixture Flux		2570lm	3	1.70	5.53	267
Efficacy		92lm/W	4	2.27	7.37	150
TS886	Imax=699cd/klm	Imax	5	2.84	9.21	96

Driver	Colour	3000K	4000K
EL.		**1E2705**	**1E2706**
DALI		**1E2707**	**1E2708**

LED / 48W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		53W	1	0.57	1.84	4784
Source Flux		6840lm	2	1.14	3.68	1196
Fixture Flux		5111lm	3	1.70	5.53	532
Efficacy		96lm/W	4	2.27	7.37	299
TS885	Imax=699cd/klm	Imax	5	2.84	9.21	191

Driver	Colour	3000K	4000K
EL.		**1E2709**	**1E2710**
DALI		**1E2711**	**1E2712**

LED / 24W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		28W	1	0.26	1.55	5506
Source Flux		3440lm	2	0.51	3.10	1377
Fixture Flux		2963lm	3	0.77	4.65	612
Efficacy		106lm/W	4	1.02	6.20	344
TS888	Imax=1601cd/klm	Imax	5	1.28	7.76	220

Driver	Colour	3000K	4000K
EL.		**1E2681**	**1E2682**
DALI		**1E2683**	**1E2684**

LED / 48W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		53W	1	0.26	1.55	10948
Source Flux		6840lm	2	0.51	3.10	2737
Fixture Flux		5922lm	3	0.77	4.65	1216
Efficacy		112lm/W	4	1.02	6.21	684
TS887	Imax=1601cd/klm	Imax	5	1.28	7.76	438

Driver	Colour	3000K	4000K
EL.		**1E2685**	**1E2686**
DALI		**1E2687**	**1E2688**

LED / 24W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		28W	1	0.55	1.70	2310
Source Flux		3440lm	2	1.11	3.40	578
Fixture Flux		2587lm	3	1.66	5.10	257
Efficacy		92lm/W	4	2.22	6.79	144
TS884	Imax=774cd/klm	Imax	5	2.77	8.49	92

Driver	Colour	3000K	4000K
EL.		**1E2729**	**1E2730**
DALI		**1E2731**	**1E2732**

LED / 48W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		53W	1	0.55	1.70	4594
Source Flux		6840lm	2	1.11	3.40	1148
Fixture Flux		5143lm	3	1.66	5.10	510
Efficacy		97lm/W	4	2.22	6.79	287
TS883	Imax=774cd/klm	Imax	5	2.77	8.49	184

Driver	Colour	3000K	4000K
EL.		**1E2733**	**1E2734**
DALI		**1E2735**	**1E2736**

JEDI

Related codes

Insertion Box



L	Code
618	**1E3507**
918	**1E3508**
1218	**1E3509**

Extruded anodized aluminium insertion box.

Accessories

Tool

Code
1E2495

Features TORX HEAD, TX 30.

Cable

L	Code
320	**1E2762**
470	**1E2763**
620	**1E2764**
770	**1E2765**

Connection cable.
Complete with 5 pole connectors.
For the electronic and DALI version.
1E2762 - For in line adjacent connection of one 600mm projector with one 900mm projector.
1E2763 - For in line adjacent connection of one 600mm projector with one 1200mm projector or two 900mm projectors.
1E2764 - For in line adjacent connection of one 900mm projector with one 1200mm projector.
1E2765 - For in line adjacent connection of two 1200mm projectors.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Control systems

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

JEDI



Recessed RGBW
L. 616mm



LED RGBW / 17W 4Ch / SPOT



-		H(m)	D(m)	Emax(lx)
-			11°	
Fixture Power	20W	1	0.19	14937
Source Flux	860lm	2	0.38	3734
Fixture Flux	860lm	3	0.56	1660
Efficacy	43lm/W	4	0.75	934
TS1030 Imax=17366cd/klm	Imax	14937cd	5	0.94	597

Driver	Colour	Code
EL. DMX		**1E3100**

LED RGBW / 17W 4Ch / FLOOD



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			85°	29°	
Fixture Power	20W	1	1.82	0.52	656
Source Flux	632lm	2	3.65	1.04	164
Fixture Flux	632lm	3	5.47	1.56	73
Efficacy	32lm/W	4	7.29	2.08	41
TS1033 Imax=1038cd/klm	Imax	656cd	5	9.11	2.60	26

Driver	Colour	Code
EL. DMX		**1E3101**

LED RGBW / 17W 4Ch / GRAZING



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			73°	11°	
Fixture Power	20W	1	1.48	0.19	1665
Source Flux	740lm	2	2.97	0.38	416
Fixture Flux	740lm	3	4.45	0.57	185
Efficacy	37lm/W	4	5.94	0.76	104
TS1029 Imax=2250cd/klm	Imax	1665cd	5	7.42	0.96	67

Driver	Colour	Code
EL. DMX		**1E3099**

LED RGBW / 17W 4Ch / WALL WASHER



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			115°	55°	
Fixture Power	20W	1	3.17	1.18	669
Source Flux	675lm	2	6.33	2.36	167
Fixture Flux	675lm	3	9.50	3.55	74
Efficacy	34lm/W	4	12.67	4.73	42
TS1036 Imax=1163cd/klm	Imax	786cd	5	15.83	5.91	27

Driver	Colour	Code
EL. DMX		**1E3102**

JEDI



Recessed RGBW
L. 916mm



LED RGBW / 26W 4Ch / SPOT



-		H(m)	D(m)	Emax(lx)
-			11°	
Fixture Power	31W	1	0.19	22404
Source Flux	1290lm	2	0.38	5601
Fixture Flux	1290lm	3	0.56	2489
Efficacy	42lm/W	4	0.75	1400
TS1031 Imax=17366cd/klm	Imax 22404cd	5	0.94	896

Driver	Colour	Code
EL. DMX		**1E3104**

LED RGBW / 26W 4Ch / FLOOD



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			85°	29°	
Fixture Power	31W	1	1.82	0.52	984
Source Flux	949lm	2	3.65	1.04	246
Fixture Flux	949lm	3	5.47	1.56	109
Efficacy	31lm/W	4	7.29	2.08	62
TS1034 Imax=1038cd/klm	Imax 984cd	5	9.11	2.60	39

Driver	Colour	Code
EL. DMX		**1E3105**

LED RGBW / 26W 4Ch / GRAZING



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			73°	11°	
Fixture Power	31W	1	1.48	0.19	2498
Source Flux	1110lm	2	2.97	0.38	624
Fixture Flux	1110lm	3	4.45	0.57	278
Efficacy	36lm/W	4	5.94	0.76	156
TS1028 Imax=2250cd/klm	Imax 2498cd	5	7.42	0.96	100

Driver	Colour	Code
EL. DMX		**1E3103**

LED RGBW / 26W 4Ch / WALL WASHER



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			115°	55°	
Fixture Power	31W	1	3.17	1.18	1004
Source Flux	1013lm	2	6.33	2.36	251
Fixture Flux	1013lm	3	9.50	3.55	112
Efficacy	33lm/W	4	12.67	4.73	63
TS1037 Imax=1163cd/klm	Imax 1179cd	5	15.83	5.91	40

Driver	Colour	Code
EL. DMX		**1E3106**

JEDI



Recessed RGBW
L. 1216mm



LED RGBW / 34W 4Ch / SPOT



		H(m)	D(m)	Emax(lx)
-			11°	
Fixture Power	41W	1	0.19	29872
Source Flux	1720lm	2	0.38	7468
Fixture Flux	1720lm	3	0.56	3319
Efficacy	42lm/W	4	0.75	1867
TS1032 Imax=17366cd/klm	Imax 29872cd	5	0.94	1195

Driver	Colour	Code
EL. DMX		**1E3108**

LED RGBW / 34W 4Ch / FLOOD



		H(m)	D1(m)	D2(m)	Emax(lx)
-			85°	29°	
Fixture Power	41W	1	1.82	0.52	1313
Source Flux	1265lm	2	3.65	1.04	328
Fixture Flux	1265lm	3	5.47	1.56	146
Efficacy	31lm/W	4	7.29	2.08	82
TS1035 Imax=1038cd/klm	Imax 1313cd	5	9.11	2.60	53

Driver	Colour	Code
EL. DMX		**1E3109**

LED RGBW / 34W 4Ch / GRAZING



		H(m)	D1(m)	D2(m)	Emax(lx)
-			73°	11°	
Fixture Power	41W	1	1.48	0.19	3330
Source Flux	1480lm	2	2.97	0.38	833
Fixture Flux	1480lm	3	4.45	0.57	370
Efficacy	36lm/W	4	5.94	0.76	208
TS1027 Imax=2250cd/klm	Imax 3330cd	5	7.42	0.96	133

Driver	Colour	Code
EL. DMX		**1E3107**

LED RGBW / 34W 4Ch / WALL WASHER



		H(m)	D1(m)	D2(m)	Emax(lx)
-			115°	55°	
Fixture Power	41W	1	3.17	1.18	1338
Source Flux	1351lm	2	6.33	2.36	335
Fixture Flux	1351lm	3	9.50	3.55	149
Efficacy	33lm/W	4	12.67	4.73	84
TS1038 Imax=1163cd/klm	Imax 1572cd	5	15.83	5.91	54

Driver	Colour	Code
EL. DMX		**1E3110**

Note

Photometrics show the maximum emission values of fixtures.

JEDI

Related codes

Insertion Box



L	Code
618	**1E3507**
918	**1E3508**
1218	**1E3509**

Extruded anodized aluminium insertion box.

Accessories

Control systems

Code
1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the “RDM Targetti” software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.

Code
1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

Control systems

Code
1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

Tool

Code
1E2495

Features TORX HEAD, TX 30.

Università LUMSA
Rome, Italy

Architect Giuseppe Manara & Partners
Photographer Ivan Rossi

Engineer Maurizio Russo, Mario Di Paola
Electrical Engineer SIEC Srl

JEDI

Compact Recessed IP67

GENERAL INFO
Ground recessed linear projector
53x43mm (remote driver)
53x80mm (integrated driver)
Length 344mm – 625mm – 905mm – 1185mm

LED
Linear boards
From 1431 to 7200lm
2700K – 3000K – 3500K – 4000K
Ra84

PRODUCT EFFICACY
Up to 113lm/W

OPTICS
SP, FL, Grazing, Wall Washer

with Louvre
FL, Grazing, Wall Washer

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Extruded anodised aluminium 15µ body. Extra clear 5mm thick glass flat screen.

ON DEMAND

Ra Ra90

110-277Vac power supply

Compact, high performance, recessed linear LED fixture.
The 34mm version is only available with a remote driver.
To be completed with a special outer casing.
Four different optics available: Spot, Flood, Grazing and Wall Washer.

The Flood, Grazing and Wall Washer optic versions can be ordered already equipped with an integrated Louvre grill with longitudinal blades to control lateral emission and reduce the risk of glare.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Also available in a projector version both for indoor and outdoor installations.

Torre Huaycho
Espinar, Perù

Lighting Design Gerardo Sanchez Sucsa
Pepe Sanchez Sucsa

Photographer James Aragón Carrasco

JEDI COMPACT

Recessed IP67
Remote driver L. 344mm



LED / 12W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			11°	
Fixture Power		12W	1	0.20	19792
Source Flux		1554lm	2	0.40	4948
Fixture Flux		1288lm	3	0.59	2199
Efficacy		107lm/W	4	0.79	1237
TS1339	Imax=12736cd/klm	Imax	19792cd	5	0.99	792

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3835**	**1E3836**	**1E3837**	**1E3838**

LED / 12W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			85°	32°	
Fixture Power		14W	1	1.84	0.57	1203
Source Flux		1720lm	2	3.68	1.14	301
Fixture Flux		1285lm	3	5.52	1.70	134
Efficacy		92lm/W	4	7.36	2.27	75
TS1084	Imax=699cd/klm	Imax	1203cd	5	9.20	2.84	48

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3561**	**1E3562**	**1E3563**	**1E3564**

LED / 12W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	15°	
Fixture Power		14W	1	1.55	0.26	2752
Source Flux		1720lm	2	3.10	0.51	688
Fixture Flux		1429lm	3	4.65	0.77	306
Efficacy		102lm/W	4	6.21	1.02	172
TS1088	Imax=1600cd/klm	Imax	2752cd	5	7.76	1.28	110

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3565**	**1E3566**	**1E3567**	**1E3568**

LED / 12W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			115°	59°	
Fixture Power		14W	1	3.12	1.34	1156
Source Flux		1720lm	2	6.23	2.67	289
Fixture Flux		1293lm	3	9.35	4.01	128
Efficacy		92lm/W	4	12.47	5.35	72
TS1092	Imax=774cd/klm	Imax	1331cd	5	15.59	6.69	46

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3569**	**1E3570**	**1E3571**	**1E3572**

JEDI COMPACT

Recessed IP67
Remote driver L. 625mm



LED / 23W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	23W	1	0.20	39584
Source Flux	3108lm	2	0.40	9896
Fixture Flux	2575lm	3	0.59	4398
Efficacy	112lm/W	4	0.79	2474
TS1339 Imax=12736cd/klm	Imax	39584cd	5	0.99	1583

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3839**	**1E3840**	**1E3841**	**1E3842**

LED / 24W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	28W	1	1.84	0.57	2406
Source Flux	3440lm	2	3.68	1.14	601
Fixture Flux	2570lm	3	5.52	1.70	267
Efficacy	92lm/W	4	7.36	2.27	150
TS1084 Imax=699cd/klm	Imax	2406cd	5	9.20	2.84	96

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3585**	**1E3586**	**1E3587**	**1E3588**

LED / 24W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	28W	1	1.55	0.26	5505
Source Flux	3440lm	2	3.10	0.51	1376
Fixture Flux	2858lm	3	4.65	0.77	612
Efficacy	102lm/W	4	6.21	1.02	344
TS1088 Imax=1600cd/klm	Imax	5505cd	5	7.76	1.28	220

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3589**	**1E3590**	**1E3591**	**1E3592**

LED / 24W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	28W	1	3.12	1.34	2312
Source Flux	3440lm	2	6.23	2.67	578
Fixture Flux	2586lm	3	9.35	4.01	257
Efficacy	92lm/W	4	12.47	5.35	145
TS1092 Imax=774cd/klm	Imax	2661cd	5	15.59	6.69	92

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3593**	**1E3594**	**1E3595**	**1E3596**

JEDI COMPACT

Recessed IP67
Remote driver L. 905mm



LED / 35W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	35W	1	0.20	59376
Source Flux	4662lm	2	0.40	14844
Fixture Flux	3863lm	3	0.59	6597
Efficacy	110lm/W	4	0.79	3711
Imax	59376cd	5	0.99	2375

TS1339 Imax=12736cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3843**	**1E3844**	**1E3845**	**1E3846**

LED / 36W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	40W	1	1.84	0.57	3609
Source Flux	5160lm	2	3.68	1.14	902
Fixture Flux	3856lm	3	5.52	1.70	401
Efficacy	96lm/W	4	7.36	2.27	226
Imax	3609cd	5	9.20	2.84	144

TS1085 Imax=699cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3609**	**1E3610**	**1E3611**	**1E3612**

LED / 36W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	40W	1	1.55	0.26	8259
Source Flux	5160lm	2	3.10	0.51	2065
Fixture Flux	4288lm	3	4.65	0.77	918
Efficacy	107lm/W	4	6.21	1.02	516
Imax	8259cd	5	7.76	1.28	330

TS1089 Imax=1601cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3613**	**1E3614**	**1E3615**	**1E3616**

LED / 36W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	40W	1	3.12	1.34	3469
Source Flux	5160lm	2	6.23	2.67	867
Fixture Flux	3880lm	3	9.35	4.01	385
Efficacy	97lm/W	4	12.47	5.35	217
Imax	3992cd	5	15.59	6.69	139

TS1093 Imax=774cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3617**	**1E3618**	**1E3619**	**1E3620**

JEDI COMPACT

Recessed IP67
Remote driver L. 1185mm



LED / 46W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	46W	1	0.20	79167
Source Flux	6216lm	2	0.40	19792
Fixture Flux	5151lm	3	0.59	8796
Efficacy	112lm/W	4	0.79	4948
Imax	79167cd	5	0.99	3167

TS1339 Imax=12736cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3847**	**1E3848**	**1E3849**	**1E3850**

LED / 48W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	53W	1	1.84	0.57	4812
Source Flux	6880lm	2	3.68	1.14	1203
Fixture Flux	5141lm	3	5.52	1.70	535
Efficacy	97lm/W	4	7.36	2.27	301
Imax	4812cd	5	9.20	2.84	192

TS1085 Imax=699cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3633**	**1E3634**	**1E3635**	**1E3636**

LED / 48W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	53W	1	1.55	0.26	11012
Source Flux	6880lm	2	3.10	0.51	2753
Fixture Flux	5717lm	3	4.65	0.77	1224
Efficacy	108lm/W	4	6.21	1.02	688
Imax	11012cd	5	7.76	1.28	440

TS1089 Imax=1601cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3637**	**1E3638**	**1E3639**	**1E3640**

LED / 48W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	53W	1	3.12	1.34	4625
Source Flux	6880lm	2	6.23	2.67	1156
Fixture Flux	5173lm	3	9.35	4.01	514
Efficacy	98lm/W	4	12.47	5.35	289
Imax	5323cd	5	15.59	6.69	185

TS1093 Imax=774cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3641**	**1E3642**	**1E3643**	**1E3644**

JEDI COMPACT

Recessed IP67 Louvre
Remote driver L. 344mm



LED / 12W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			86°	29°	
Fixture Power		14W	1	1.86	0.52	873
Source Flux		1720lm	2	3.71	1.05	218
Fixture Flux		752lm	3	5.57	1.57	97
Efficacy		54lm/W	4	7.42	2.09	55
TS1086	Imax=508cd/klm	Imax	873cd	5	9.28	2.62	35

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3573**	**1E3574**	**1E3575**	**1E3576**

LED / 12W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			80°	13°	
Fixture Power		14W	1	1.68	0.23	1903
Source Flux		1720lm	2	3.36	0.46	476
Fixture Flux		912lm	3	5.04	0.68	211
Efficacy		65lm/W	4	6.72	0.91	119
TS1090	Imax=1106cd/klm	Imax	1903cd	5	8.40	1.14	76

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3577**	**1E3578**	**1E3579**	**1E3580**

LED / 12W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			116°	62°	
Fixture Power		14W	1	3.17	1.49	960
Source Flux		1720lm	2	6.35	2.97	240
Fixture Flux		975lm	3	9.52	4.46	107
Efficacy		70lm/W	4	12.70	5.95	60
TS1094	Imax=671cd/klm	Imax	1153cd	5	15.87	7.43	38

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3581**	**1E3582**	**1E3583**	**1E3584**

Recessed IP67 Louvre
Remote driver L. 625mm



LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			86°	29°	
Fixture Power		28W	1	1.86	0.52	1747
Source Flux		3440lm	2	3.71	1.05	437
Fixture Flux		1503lm	3	5.57	1.57	194
Efficacy		54lm/W	4	7.42	2.09	109
TS1086	Imax=508cd/klm	Imax	1747cd	5	9.28	2.62	70

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3597**	**1E3598**	**1E3599**	**1E3600**

JEDI COMPACT

LED / 24W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	28W	1	1.68	0.23	3805
Source Flux	3440lm	2	3.36	0.46	951
Fixture Flux	1824lm	3	5.04	0.68	423
Efficacy	65lm/W	4	6.72	0.91	238
TS1090 Imax=1106cd/klm	Imax 3805cd	5	8.40	1.14	152

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3601**	**1E3602**	**1E3603**	**1E3604**

LED / 24W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	28W	1	3.17	1.49	1919
Source Flux	3440lm	2	6.35	2.97	480
Fixture Flux	1950lm	3	9.52	4.46	213
Efficacy	70lm/W	4	12.70	5.95	120
TS1094 Imax=671cd/klm	Imax 2307cd	5	15.87	7.43	77

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3605**	**1E3606**	**1E3607**	**1E3608**

Recessed IP67 Louvre
Remote driver L. 905mm



LED / 36W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	40W	1	1.86	0.52	2620
Source Flux	5160lm	2	3.71	1.05	655
Fixture Flux	2255lm	3	5.57	1.57	291
Efficacy	56lm/W	4	7.42	2.09	164
TS1087 Imax=508cd/klm	Imax 2620cd	5	9.28	2.62	105

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3621**	**1E3622**	**1E3623**	**1E3624**

LED / 36W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	40W	1	1.68	0.23	5707
Source Flux	5160lm	2	3.36	0.46	1427
Fixture Flux	2735lm	3	5.04	0.68	634
Efficacy	68lm/W	4	6.72	0.91	357
TS1091 Imax=1106cd/klm	Imax 5707cd	5	8.40	1.14	228

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3625**	**1E3626**	**1E3627**	**1E3628**

LED / 36W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	40W	1	3.17	1.49	2879
Source Flux	5160lm	2	6.35	2.97	720
Fixture Flux	2926lm	3	9.52	4.46	320
Efficacy	73lm/W	4	12.70	5.95	180
TS1095 Imax=671cd/klm	Imax 3460cd	5	15.87	7.43	115

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3629**	**1E3630**	**1E3631**	**1E3632**

JEDI COMPACT

Recessed IP67 Louvre
Remote driver L. 1185mm



LED / 48W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	53W	1	1.86	0.52	3494
Source Flux	6880lm	2	3.71	1.05	873
Fixture Flux	3007lm	3	5.57	1.57	388
Efficacy	57lm/W	4	7.42	2.09	218
TS1087 Imax=508cd/klm	Imax 3494cd	5	9.28	2.62	140

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3645**	**1E3646**	**1E3647**	**1E3648**

LED / 48W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	53W	1	1.68	0.23	7609
Source Flux	6880lm	2	3.36	0.46	1902
Fixture Flux	3646lm	3	5.04	0.68	845
Efficacy	69lm/W	4	6.72	0.91	476
TS1091 Imax=1106cd/klm	Imax 7609cd	5	8.40	1.14	304

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3649**	**1E3650**	**1E3651**	**1E3652**

LED / 48W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	53W	1	3.17	1.49	3838
Source Flux	6880lm	2	6.35	2.97	960
Fixture Flux	3901lm	3	9.52	4.46	426
Efficacy	74lm/W	4	12.70	5.95	240
TS1095 Imax=671cd/klm	Imax 4613cd	5	15.87	7.43	154

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3653**	**1E3654**	**1E3655**	**1E3656**

Recessed IP67
Integrated driver
L. 625mm



LED / 23W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	26W	1	0.20	39584
Source Flux	3108lm	2	0.40	9896
Fixture Flux	2575lm	3	0.59	4398
Efficacy	99lm/W	4	0.79	2474
TS1339 Imax=12736cd/klm	Imax 39584cd	5	0.99	1583

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3851EL**	**1E3852EL**	**1E3853EL**	**1E3854EL**
DALI		**1E3851DA**	**1E3852DA**	**1E3853DA**	**1E3854DA**

JEDI COMPACT

LED / 24W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	28W	1	1.84	0.57	2406
Source Flux	3440lm	2	3.68	1.14	601
Fixture Flux	2570lm	3	5.52	1.70	267
Efficacy	92lm/W	4	7.36	2.27	150
TS1084 Imax=699cd/klm	Imax 2406cd	5	9.20	2.84	96

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3657EL**	**1E3658EL**	**1E3659EL**	**1E3660EL**
DALI		**1E3657DA**	**1E3658DA**	**1E3659DA**	**1E3660DA**

LED / 24W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	28W	1	1.55	0.26	5505
Source Flux	3440lm	2	3.10	0.51	1376
Fixture Flux	2858lm	3	4.65	0.77	612
Efficacy	102lm/W	4	6.21	1.02	344
TS1088 Imax=1600cd/klm	Imax 5505cd	5	7.76	1.28	220

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3661EL**	**1E3662EL**	**1E3663EL**	**1E3664EL**
DALI		**1E3661DA**	**1E3662DA**	**1E3663DA**	**1E3664DA**

LED / 24W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	28W	1	3.12	1.34	2312
Source Flux	3440lm	2	6.23	2.67	578
Fixture Flux	2586lm	3	9.35	4.01	257
Efficacy	92lm/W	4	12.47	5.35	145
TS1092 Imax=774cd/klm	Imax 2661cd	5	15.59	6.69	92

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3665EL**	**1E3666EL**	**1E3667EL**	**1E3668EL**
DALI		**1E3665DA**	**1E3666DA**	**1E3667DA**	**1E3668DA**

Recessed IP67
Integrated driver
L. 905mm



LED / 35W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	37W	1	0.20	59376
Source Flux	4662lm	2	0.40	14844
Fixture Flux	3863lm	3	0.59	6597
Efficacy	104lm/W	4	0.79	3711
TS1339 Imax=12736cd/klm	Imax 59376cd	5	0.99	2375

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3855EL**	**1E3856EL**	**1E3857EL**	**1E3858EL**
DALI		**1E3855DA**	**1E3856DA**	**1E3857DA**	**1E3858DA**

LED / 36W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	40W	1	1.84	0.57	3609
Source Flux	5160lm	2	3.68	1.14	902
Fixture Flux	3856lm	3	5.52	1.70	401
Efficacy	96lm/W	4	7.36	2.27	226
TS1085 Imax=699cd/klm	Imax 3609cd	5	9.20	2.84	144

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3681EL**	**1E3682EL**	**1E3683EL**	**1E3684EL**
DALI		**1E3681DA**	**1E3682DA**	**1E3683DA**	**1E3684DA**

JEDI COMPACT

LED / 36W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	40W	1	1.55	0.26	8259
Source Flux	5160lm	2	3.10	0.51	2065
Fixture Flux	4288lm	3	4.65	0.77	918
Efficacy	107lm/W	4	6.21	1.02	516
TS1089 Imax=1601cd/klm	Imax 8259cd	5	7.76	1.28	330

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3685EL**	**1E3686EL**	**1E3687EL**	**1E3688EL**
DALI		**1E3685DA**	**1E3686DA**	**1E3687DA**	**1E3688DA**

LED / 36W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	40W	1	3.12	1.34	3469
Source Flux	5160lm	2	6.23	2.67	867
Fixture Flux	3880lm	3	9.35	4.01	385
Efficacy	97lm/W	4	12.47	5.35	217
TS1093 Imax=774cd/klm	Imax 3992cd	5	15.59	6.69	139

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3689EL**	**1E3690EL**	**1E3691EL**	**1E3692EL**
DALI		**1E3689DA**	**1E3690DA**	**1E3691DA**	**1E3692DA**

Recessed IP67
Integrated driver
L. 1185mm



LED / 46W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	49W	1	0.20	79167
Source Flux	6216lm	2	0.40	19792
Fixture Flux	5151lm	3	0.59	8796
Efficacy	105lm/W	4	0.79	4948
TS1339 Imax=12736cd/klm	Imax 79167cd	5	0.99	3167

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3859EL**	**1E3860EL**	**1E3861EL**	**1E3862EL**
DALI		**1E3859DA**	**1E3860DA**	**1E3861DA**	**1E3862DA**

LED / 48W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	53W	1	1.84	0.57	4812
Source Flux	6880lm	2	3.68	1.14	1203
Fixture Flux	5141lm	3	5.52	1.70	535
Efficacy	97lm/W	4	7.36	2.27	301
TS1085 Imax=699cd/klm	Imax 4812cd	5	9.20	2.84	192

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3705EL**	**1E3706EL**	**1E3707EL**	**1E3708EL**
DALI		**1E3705DA**	**1E3706DA**	**1E3707DA**	**1E3708DA**

LED / 48W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	53W	1	1.55	0.26	11012
Source Flux	6880lm	2	3.10	0.51	2753
Fixture Flux	5717lm	3	4.65	0.77	1224
Efficacy	108lm/W	4	6.21	1.02	688
TS1089 Imax=1601cd/klm	Imax 11012cd	5	7.76	1.28	440

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3709EL**	**1E3710EL**	**1E3711EL**	**1E3712EL**
DALI		**1E3709DA**	**1E3710DA**	**1E3711DA**	**1E3712DA**

JEDI COMPACT

LED / 48W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			115°	59°	
Fixture Power	53W		1	3.12	1.34	4625
Source Flux	6880lm		2	6.23	2.67	1156
Fixture Flux	5173lm		3	9.35	4.01	514
Efficacy	98lm/W		4	12.47	5.35	289
TS1093	Imax=774cd/klm	Imax	5	15.59	6.69	185

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3713EL**	**1E3714EL**	**1E3715EL**	**1E3716EL**
DALI		**1E3713DA**	**1E3714DA**	**1E3715DA**	**1E3716DA**

Recessed IP67 Louvre
Integrated driver
L. 625mm



LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			86°	29°	
Fixture Power	28W		1	1.86	0.52	1747
Source Flux	3440lm		2	3.71	1.05	437
Fixture Flux	1503lm		3	5.57	1.57	194
Efficacy	54lm/W		4	7.42	2.09	109
TS1086	Imax=508cd/klm	Imax	5	9.28	2.62	70

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3669EL**	**1E3670EL**	**1E3671EL**	**1E3672EL**
DALI		**1E3669DA**	**1E3670DA**	**1E3671DA**	**1E3672DA**

LED / 24W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			80°	13°	
Fixture Power	28W		1	1.68	0.23	3805
Source Flux	3440lm		2	3.36	0.46	951
Fixture Flux	1824lm		3	5.04	0.68	423
Efficacy	65lm/W		4	6.72	0.91	238
TS1090	Imax=1106cd/klm	Imax	5	8.40	1.14	152

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3673EL**	**1E3674EL**	**1E3675EL**	**1E3676EL**
DALI		**1E3673DA**	**1E3674DA**	**1E3675DA**	**1E3676DA**

LED / 24W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			116°	62°	
Fixture Power	28W		1	3.17	1.49	1919
Source Flux	3440lm		2	6.35	2.97	480
Fixture Flux	1950lm		3	9.52	4.46	213
Efficacy	70lm/W		4	12.70	5.95	120
TS1094	Imax=671cd/klm	Imax	5	15.87	7.43	77

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3677EL**	**1E3678EL**	**1E3679EL**	**1E3680EL**
DALI		**1E3677DA**	**1E3678DA**	**1E3679DA**	**1E3680DA**

JEDI COMPACT

Recessed IP67 Louvre
Integrated driver
L. 905mm



LED / 36W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			86°	29°	
Fixture Power		40W	1	1.86	0.52	2620
Source Flux		5160lm	2	3.71	1.05	655
Fixture Flux		2255lm	3	5.57	1.57	291
Efficacy		56lm/W	4	7.42	2.09	164
TS1087	Imax=508cd/klm	Imax 2620cd	5	9.28	2.62	105

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3693EL**	**1E3694EL**	**1E3695EL**	**1E3696EL**
DALI		**1E3693DA**	**1E3694DA**	**1E3695DA**	**1E3696DA**

LED / 36W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			80°	13°	
Fixture Power		40W	1	1.68	0.23	5707
Source Flux		5160lm	2	3.36	0.46	1427
Fixture Flux		2735lm	3	5.04	0.68	634
Efficacy		68lm/W	4	6.72	0.91	357
TS1091	Imax=1106cd/klm	Imax 5707cd	5	8.40	1.14	228

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3697EL**	**1E3698EL**	**1E3699EL**	**1E3700EL**
DALI		**1E3697DA**	**1E3698DA**	**1E3699DA**	**1E3700DA**

LED / 36W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			116°	62°	
Fixture Power		40W	1	3.17	1.49	2879
Source Flux		5160lm	2	6.35	2.97	720
Fixture Flux		2926lm	3	9.52	4.46	320
Efficacy		73lm/W	4	12.70	5.95	180
TS1095	Imax=671cd/klm	Imax 3460cd	5	15.87	7.43	115

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3701EL**	**1E3702EL**	**1E3703EL**	**1E3704EL**
DALI		**1E3701DA**	**1E3702DA**	**1E3703DA**	**1E3704DA**

Recessed IP67 Louvre
Integrated driver
L. 1185mm



LED / 48W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			86°	29°	
Fixture Power		53W	1	1.86	0.52	3494
Source Flux		6880lm	2	3.71	1.05	873
Fixture Flux		3007lm	3	5.57	1.57	388
Efficacy		57lm/W	4	7.42	2.09	218
TS1087	Imax=508cd/klm	Imax 3494cd	5	9.28	2.62	140

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3717EL**	**1E3718EL**	**1E3719EL**	**1E3720EL**
DALI		**1E3717DA**	**1E3718DA**	**1E3719DA**	**1E3720DA**

JEDI COMPACT

LED / 48W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	53W	1	1.68	0.23	7609
Source Flux	6880lm	2	3.36	0.46	1902
Fixture Flux	3646lm	3	5.04	0.68	845
Efficacy	69lm/W	4	6.72	0.91	476
TS1091 Imax=1106cd/klm	Imax 7609cd	5	8.40	1.14	304

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3721EL**	**1E3722EL**	**1E3723EL**	**1E3724EL**
DALI		**1E3721DA**	**1E3722DA**	**1E3723DA**	**1E3724DA**

LED / 48W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	53W	1	3.17	1.49	3838
Source Flux	6880lm	2	6.35	2.97	960
Fixture Flux	3901lm	3	9.52	4.46	426
Efficacy	74lm/W	4	12.70	5.95	240
TS1095 Imax=671cd/klm	Imax 4613cd	5	15.87	7.43	154

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3725EL**	**1E3726EL**	**1E3727EL**	**1E3728EL**
DALI		**1E3725DA**	**1E3726DA**	**1E3727DA**	**1E3728DA**

Note

To be completed with an anodised aluminium outer casing suitable for in-line installation and external looping.

Related codes

Insertion Box



L	H	P	Code
348	58	94	**1E3729**
629	58	94	**1E3730**
909	58	94	**1E3731**
1189	58	94	**1E3732**

Aluminium outer casing for Jedi Compact with remote driver.



L	H	P	Code
629	88	96	**1E3733**
909	88	96	**1E3734**
1189	88	96	**1E3735**

Aluminium outer casing for Jedi Compact with integrated driver.

Power Supply

Code
1E3557

EL power supply version kit composed of an aluminium watertight box (LxHxP=270x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 3G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 312.5/344mm versions.

Code
1E3558

EL power supply version kit composed of an aluminium watertight box (LxHxP=486x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 3G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 593.5/625/873.5/905/1153.5/1185mm versions.

JEDI COMPACT

Code
1E3559

DALI power supply version kit composed of an aluminium watertight box (LxHxP=486x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 5G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 312.5/344/593.5/625mm versions.

Code
1E3560

DALI power supply version kit composed of an aluminium watertight box (LxHxP=486x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 5G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 873.5/905/1153.5/1185mm versions.

Accessories

Tool

Code
1E3305

(Tightening) wrench for the connector kit.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Code
1E3184

IP68 4-way cable connector (5 pole).

Control systems

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

MERCURE

GENERAL INFO
Inground linear fixture.
Lenghts: 300mm - 600mm

LED
Linear boards
From 74lm to 1800lm
3000K – 4000K
Ra84 – Ra80
RGB

PRODUCT EFFICACY
Up to 59lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic - 24V
Casambi control system available using a dedicated accessory.

MATERIAL
Die-cast aluminium housing.
Anti slip, flush, tempered safety glass.

ON DEMAND
Ra Ra90

A range of compact inground recessed linear light fixtures with and a flush “all glass” finish” for particularly striking and elegant installation in continuous rows. Mercure comes in three different sizes to light shapes with monochromatic or RGB light.

The larger versions combine elegance and high performance; the smaller version combines a compact size, elegant design and resistance in a unique linear glass fixture that can meet walk-over requirements.

Mercure and Minimercure are subject to Cataphoresis treatment and are therefore suitable to be installed near the sea (up to 5 metres) or in hostile environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.



Private Residence
Huntinton Beach, USA

Photographer ©SAC Design

MERCURE

Light-line

LED / 12W / VWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			116°	
Fixture Power	15W	1	3.21	278
Source Flux	1720lm	2	6.43	69
Fixture Flux	849lm	3	9.64	31
Efficacy	57lm/W	4	12.85	17
Imax	278cd	5	16.07	11

	Driver	Colour	3000K	4000K
	EL.		**1E2274**	**1E2275**

Note

Supplied with an IP67 coaxial connection kit.

Related codes

Insertion Box



Code
1E2264

Anodized aluminium insertion box available in three different heights to satisfy any installation need.
Complete with removable end caps for in-line installation.
Low.
L=600mm.



Code
1E2265

Anodized aluminium insertion box available in three different heights to satisfy any installation need.
Complete with removable end caps for in-line installation.
Medium.
L=600mm.

Related codes

Insertion Box



Code
1E2266

Anodized aluminium insertion box available in three different heights to satisfy any installation need.
Complete with removable end caps for in-line installation.
High.
L=600mm.

Accessories

Tool

Code
1E0388

Sucker tool to raise the glass.

MERCURE

MINIMERCURE LED



LED / 8W / VWFL



Insulation	Power supply	Driver	Colour	3000K	4000K
CLASS 3	24Vdc			**1E3406**	**1E3407**
CLASS 2	220-240Vac	EL.		**1E3404**	**1E3405**

Related codes

Insertion Box



Code
1E2382

Aluminium insertion boxes with horizontal or vertical development pre-set with removable end caps for installations in continuous rows.
Complete with internal supports for installations in concrete.
Vertical.
L=601mm.



Code
1E2383

Aluminium insertion boxes with horizontal or vertical development pre-set with removable end caps for installations in continuous rows.
Complete with internal supports for installations in concrete.
Horizontal
L=601mm.

Power Supply



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**

Electronic power supply.

MERCURE

MINIMERCURE RGB



LED RGB / 8W / VWFL



		H(m)	D1(m)	D2(m)	Emax(lx)
-			117°	129°	
Fixture Power	9W	1	3.27	4.16	25
Source Flux	83lm	2	6.55	8.31	6
Fixture Flux	82lm	3	9.82	12.47	3
Efficacy	10lm/W	4	13.09	16.63	2
Imax	25cd	5	16.37	20.79	1

Power supply	Colour	RGB
24Vdc		**1E2381**

Note

Photometrics show the maximum emission values of fixtures.

Related codes

Insertion Box



Code
1E2382

Aluminium insertion boxes with horizontal or vertical development pre-set with removable end caps for installations in continuous rows.
Complete with internal supports for installations in concrete.
Vertical.
L=601mm.



Code
1E2383

Aluminium insertion boxes with horizontal or vertical development pre-set with removable end caps for installations in continuous rows.
Complete with internal supports for installations in concrete.
Horizontal
L=601mm.

Control systems

Code
1E1401

SECS 75.
IP67
Power supply and Control System SECS Scene Effect Control System.
SECS 75 drivers combine the following 3 functions in a single unit,: power supply to RGB LED devices, playback of pre-set colour sequences and a DMX interface for external control devices.
The SECS “Easy-Run-Menu” function is able to playback colour-changing light scenarios that are pre-stored into the driver without the use of an external driver: - 8 static colour scenarios; - 8 dynamic colour sequences; - 5 different playback speed values; - Start/Stop the selected scenario using a remote switch.
SECS 75 drivers can also be controlled through DMX 512; in this case: - DMX address (from 1 to 511) can be configured by using dip-switches; - 3 channel mode: all R-G-B outputs are controlled simultaneously by 3 DMX channels only; - 6 channel mode: the outputs are divided into 2 R-G-B groups, each one controlled by 3 different DMX channels; - DMX line termination: SECS drivers contain a 120Ohm resistance which can be activated using a dip-switch; - DMX output is available for connection to other DMX devices.
75W output.

Code
1T2245

SECS 36.
IP20
Power supply and Control System SECS Scene Effect Control System.
SECS 36 drivers combine the following 3 functions in a single unit,: power supply to RGB LED devices, playback of pre-set colour sequences and a DMX interface for external control devices.
The SECS “Easy-Run-Menu” function is able to playback colour-changing light scenarios that are pre-stored into the driver without the use of an external driver: - 8 static colour scenarios; - 8 dynamic colour sequences; - 5 different playback speed values; - Start/Stop the selected scenario using a remote switch.
SECS 75 drivers can also be controlled through DMX 512; in this case: - DMX address (from 1 to 511) can be configured by using dip-switches; - 3 channel mode: all R-G-B outputs are controlled simultaneously by 3 DMX channels only; - 6 channel mode: the outputs are divided into 2 R-G-B groups, each one controlled by 3 different DMX channels; - DMX line termination: SECS drivers contain a 120Ohm resistance which can be activated using a dip-switch; - DMX output is available for connection to other DMX devices.
35W output.

MERCURE

Accessories

Cable

	Code
	1T1932

Standard DMX cable (1 twisted pair + shield, 120 Ohm).

Control systems

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

	Code
	1T7944

Wireless Bluetooth Dimmer capable of handling constant voltage loads of 12V or 24V subdivided into 4 channels with PWM output.
This dimmer must be connected between the 12V or 24V power supply and the constant voltage LED module.
The maximum total current that can be supplied by the control unit is 6A (equivalent to a total of 144W) that can be divided between the 4 outputs.
LxHxP=72.6x18x30mm.
IP20

MERCURE

MICROMERCURE



LED / 3W / VWFL



	Power supply	Colour	3000K	4000K
	12Vdc		**1E2267**	**1E2268**

Related codes

Insertion Box



	Code
	1E2269

Galvanized metal insertion box.
Complete with removable end caps for in-line installation.
L=300mm.

Power Supply



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
145x19x55	10/20W	110-240Vac/220-240Vac	12Vdc	IP20	**T1585**
225x51x65	70W	220-240Vac	12Vdc	IP67	**T1586**

Non-dimmable electronic power supply.

Accessories

Control systems

	Code
	1T7944

Wireless Bluetooth Dimmer capable of handling constant voltage loads of 12V or 24V subdivided into 4 channels with PWM output.
This dimmer must be connected between the 12V or 24V power supply and the constant voltage LED module.
The maximum total current that can be supplied by the control unit is 6A (equivalent to a total of 144W) that can be divided between the 4 outputs.
LxHxP=72.6x18x30mm.
IP20

KEPLERO

GENERAL INFO
Recessed professional projector.
ø280mm - ø161mm

LED
Chip on board for Zoom – Wall Washer versions
Emitter for RGBW – Gimbal versions
From 768lm to 4665lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 106lm/W

OPTICS
NSP – SP – FL – FL RECT
MWFL – WFL – WW

POWER SUPPLY
Electronic – DALI – DMX

MATERIAL
Anodized and black painted die-cast aluminium body. Brushed stainless steel ultra flat decorative ring with bevelled edge.

ON DEMAND
110-277 vac power supply
2700K-3500K

A complete range of recessed LED up-lights for outdoor lighting. The two different sizes with a wide range of optics with white LED or RGBW lamps with different lumens are the expression of versatility and performance. The entire range has been subject to “Cataphoresis” treatment and is therefore suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

Keplero uses the “Waterblock Plus” technical solution that involves resin coating the connection cables and completely resin coating the integrated driver.
The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

The large versions of Keplero are available with an integrated electronic 220-240V driver, while the Keplero Mini has a range with both an integrated 110-240V driver and a remote 48V driver making it easier to connect several fixtures to the same driver that is available as an accessory. Cabling is simply through IP68 connectors that are equipped for In and Out looping.

The Pools
Irvine, USA

Architect Studio K1

Photographer ©Brad Nelson

Plus

Zoom
Spot, Flood, Medium wide Flood, Wide flood

Zoom RGBW
Spot, Flood, Medium wide Flood, Wide flood

Wall Washer



Wall Washer RGBW

Gimbal
Narrow spot, Flood, Flood rectangle

Gimbal Hp
Narrow spot, Spot, Flood

Keplero

A powerful solution

And an ideal and flexible choice for lighting large and small public spaces, building facades and trees given its size and high performance.

Keplero Mini

A compact version

With only 166mm in diameter and has a maximum installation depth of just 200mm. It takes its technology and flexibility from the large version but given its dimensions and high performance it is also suitable for external lighting such as building facades and small trees.

Zoom
Spot, Flood, Medium wide flood, Wide flood

Wall Washer

Gimbal
Spot, Flood

Hi-Efficacy
Spot, Flood, Medium wide flood

Hi- Efficacy RGBW
Spot, Flood, Medium wide flood

Plus



Keplero Zoom



Keplero Mini Zoom

The dynamism of the optical system produces numerous luminous effects

Perfect solidity and stillness of an inground recessed fixture contrast with the dynamism of a unique optical system that gives life to countless luminous effects. The light emitted by Keplero Zoom and Keplero Mini Zoom can change at any time thanks to the innovative patented optical system that makes it possible to vary the beam opening by manually moving the optical unit. Thanks to a few simple steps it is possible to modify the emission of the fixture from spot to wide flood and adjust the beam up to 20°. Grade rings help to identify orientation and make replication simple.





Keplero Gimbal

Keplero Mini Gimbal

Gimbal optic

For precision lighting. A real projector given its high performance and the adjustability of the optical unit up to 40°.

Wall washer

Optical system to light vertical surfaces uniformly

An optical system composed of a reflector and a lens that can not only guarantee complete uniformity on vertical surfaces but also excellent light diffusion from very close to the floor.
Now available even in a Mini version (Ø 161mm)

Keplero Wall Washer

Keplero Mini Wall Washer

Plus



Brushed stainless steel ring finish

Installed flush or protruding by simply removing the frame from the nylon installation sleeve available as an accessory. Special stainless steel inserts - with silicone o-ring - house the fixing screws of the ring thus preventing corrosion deriving from galvanic interactions

Extremely resistant to corrosion

The aluminium “primary alloy” with a low copper level used for die-casting makes Keplero highly resistant to corrosive phenomenon. In addition 8µm of anodisation, 15/40µm of cataphoresis treatment and 100µm of black polyester paint on the top ensure protection to all exposed surfaces, making it suitable to be installed up to 5 mt from the sea (no submersion).

Anti-slip glass

Keplero and Keplero Mini can be equipped with anti-slip glass, ideal for public pedestrian areas.

Easy pointing

Graduated rings help to define aim adjustment and replicate it easily.

KEPLERO

Zoom



LED / 33W / SP, FL, MWFL, WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			19°	
Fixture Power	36W	1	0.34	11460
Source Flux	4550lm	2	0.67	2865
Fixture Flux	1666lm	3	1.01	1273
Efficacy	47lm/W	4	1.34	716
Imax	11460cd	5	1.68	458

TS782 Imax=2519cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra84			26°	
Fixture Power	36W	1	0.46	7939
Source Flux	4550lm	2	0.93	1985
Fixture Flux	2205lm	3	1.39	882
Efficacy	62lm/W	4	1.85	496
Imax	7939cd	5	2.31	318

TS781 Imax=1745cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra84			43°	
Fixture Power	36W	1	0.79	4579
Source Flux	4550lm	2	1.57	1145
Fixture Flux	2756lm	3	2.36	509
Efficacy	77lm/W	4	3.14	286
Imax	4579cd	5	3.93	183

TS780 Imax=1006cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra84			64°	
Fixture Power	36W	1	1.25	2724
Source Flux	4550lm	2	2.50	681
Fixture Flux	2889lm	3	3.75	303
Efficacy	81lm/W	4	5.00	170
Imax	2724cd	5	6.25	109

TS779 Imax=599cd/klm

Certificate	Driver	Version	Colour	3000K	4000K
ENEC	EL.	STANDARD		**1E2386**	**1E2387**
	DALI	STANDARD		**1E2386DA**	**1E2387DA**
	EL.	ANTI-SLIP GLASS		**1E2386AS**	**1E2387AS**
	DALI	ANTI-SLIP GLASS		**1E2386DAAS**	**1E2387DAAS**

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation. IP69K complies with Standard DIN 40050-9.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve



	Code
	1E2394

Grey nylon installation sleeve.
The sleeve is pre-set for both flush or straight edge installation.
Complete with dedicated cover cap for installations in concrete.
Flush ring Ø 286 H.225.
Straight edge ring Ø 271 H. 223.

KEPLERO

Accessories

Filter



Filter	Ø	Code
Red	101	**1T1700**
Green	101	**1T1701**
Blue	101	**1T1702**
Yellow	101	**1T1703**
Magenta	101	**1T1704**

Flat glass interference chromatic filter.



Ø	Code
101	**1T1696**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.

Grid



Ø	Code
101	**1T1699**

Anti-glare louver.
Black painted metal honeycomb structure.

Shutter

Colour	Code
●	**1E2402**

Half-moon shutter.

Tool

Code
1E2496

Metal handle for fixture removal

Code
1E2495

Features TORX HEAD, TX 30.

Code
1E0388

Sucker tool to raise the glass.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

KEPLERO

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

KEPLERO

Zoom RGBW



LED RGBW / 49W / SP, FL, MWFL, WFL

	Driver	Version	Colour	Code
	EL. DMX	STANDARD		**1E2768**
	EL. DMX	ANTI-SLIP GLASS		**1E2768AS**



-		H(m)	D(m)	Emax(lx)
-			23°	
Fixture Power	56W	1	0.42	4266
Source Flux	826lm	2	0.83	1067
Fixture Flux	826lm	3	1.25	474
Efficacy	15lm/W	4	1.66	267
Imax	4266cd	5	2.08	171

TS904 Imax=5165cd/klm



-		H(m)	D(m)	Emax(lx)
-			32°	
Fixture Power	56W	1	0.57	3161
Source Flux	1082lm	2	1.14	790
Fixture Flux	1082lm	3	1.71	351
Efficacy	19lm/W	4	2.27	198
Imax	3161cd	5	2.84	126

TS905 Imax=2921cd/klm



-		H(m)	D(m)	Emax(lx)
-			51°	
Fixture Power	56W	1	0.95	1877
Source Flux	1359lm	2	1.90	469
Fixture Flux	1359lm	3	2.85	209
Efficacy	24lm/W	4	3.80	117
Imax	1877cd	5	4.75	75

TS906 Imax=1380cd/klm



-		H(m)	D(m)	Emax(lx)
-			72°	
Fixture Power	56W	1	1.45	1076
Source Flux	1402lm	2	2.90	269
Fixture Flux	1402lm	3	4.35	120
Efficacy	25lm/W	4	5.80	67
Imax	1076cd	5	7.25	43

TS907 Imax=768cd/klm

Note

Photometrics show the maximum emission values of fixtures.

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation. IP69K complies with Standard DIN 40050-9.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve



	Code
	1E2394

Grey nylon installation sleeve.
The sleeve is pre-set for both flush or straight edge installation.
Complete with dedicated cover cap for installations in concrete.
Flush ring Ø 286 H.225.
Straight edge ring Ø 271 H. 223.

KEPLERO

Accessories

Filter



	Ø	Code
	101	**1T1696**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.

Grid



	Ø	Code
	101	**1T1699**

Anti-glare louver.
Black painted metal honeycomb structure.

Shutter

	Colour	Code
	●	**1E2402**

Half-moon shutter.

Tool

	Code
	1E2496

Metal handle for fixture removal

	Code
	1E2495

Features TORX HEAD, TX 30.

	Code
	1E0388

Sucker tool to raise the glass.

Connector

	Code
	1E3184

IP68 4-way cable connector (5 pole).

KEPLERO

Control systems

	Code
	1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the “RDM Targetti” software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

KEPLERO

Gimbal



LED / 11W / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra80			9°	
Fixture Power	15W	1	0.15	20172
Source Flux	878lm	2	0.31	5043
Fixture Flux	718lm	3	0.46	2241
Efficacy	50lm/W	4	0.61	1261
Imax	20172cd	5	0.76	807

Certificate	Driver	Version	Colour	3000K	4000K
ENEC	EL.	STANDARD		**1E2388**	**1E2389**
	DALI	STANDARD		**1E2388DA**	**1E2389DA**
	EL.	ANTI-SLIP GLASS		**1E2388AS**	**1E2389AS**
	DALI	ANTI-SLIP GLASS		**1E2388DAAS**	**1E2389DAAS**

LED / 11W / FL



3000K		H(m)	D(m)	Emax(lx)
Ra80			28°	
Fixture Power	15W	1	0.51	2508
Source Flux	878lm	2	1.01	627
Fixture Flux	636lm	3	1.52	279
Efficacy	44lm/W	4	2.02	157
Imax	2508cd	5	2.53	100

Certificate	Driver	Version	Colour	3000K	4000K
ENEC	EL.	STANDARD		**1E2390**	**1E2391**
	DALI	STANDARD		**1E2390DA**	**1E2391DA**
	EL.	ANTI-SLIP GLASS		**1E2390AS**	**1E2391AS**
	DALI	ANTI-SLIP GLASS		**1E2390DAAS**	**1E2391DAAS**

LED / 11W / FL RECTANGLE



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra80			43°	30°	
Fixture Power	15W	1	0.79	0.54	1228
Source Flux	878lm	2	1.58	1.08	307
Fixture Flux	582lm	3	2.36	1.62	136
Efficacy	40lm/W	4	3.15	2.15	77
Imax	1228cd	5	3.94	2.69	49

Certificate	Driver	Version	Colour	3000K	4000K
ENEC	EL.	STANDARD		**1E2392**	**1E2393**
	DALI	STANDARD		**1E2392DA**	**1E2393DA**
	EL.	ANTI-SLIP GLASS		**1E2392AS**	**1E2393AS**
	DALI	ANTI-SLIP GLASS		**1E2392DAAS**	**1E2393DAAS**

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation. IP69K complies with Standard DIN 40050-9.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve



	Code
	1E2394

Grey nylon installation sleeve.
The sleeve is pre-set for both flush or straight edge installation.
Complete with dedicated cover cap for installations in concrete.
Flush ring Ø 286 H.225.
Straight edge ring Ø 271 H. 223.

KEPLERO

Accessories

Filter

Filter	Ø	Code
Red	101	**1T1700**
Green	101	**1T1701**
Blue	101	**1T1702**
Yellow	101	**1T1703**
Magenta	101	**1T1704**

Flat glass interference chromatic filter.



Ø	Code
101	**1T1696**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.

Grid



Ø	Code
101	**1T1699**

Anti-glare louver.
Black painted metal honeycomb structure.

Shutter

Colour	Code
●	**1E2402**

Half-moon shutter.

Tool

Code
1E2496

Metal handle for fixture removal

Code
1E2495

Features TORX HEAD, TX 30.

Code
1E0388

Sucker tool to raise the glass.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

KEPLERO

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

KEPLERO

Gimbal HP



LED / 33W / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			8°	
Fixture Power		37W	1	0.14	78598
Source Flux		2791lm	2	0.29	19650
Fixture Flux		2373lm	3	0.43	8733
Efficacy		64lm/W	4	0.57	4912
TS986	Imax=28161cd/klm	Imax	78598cd	5	0.72	3144

Driver	Version	Colour	3000K	4000K
EL.	STANDARD		**1E3050**	**1E3053**
DALI	STANDARD		**1E3050DA**	**1E3053DA**
EL.	ANTI-SLIP GLASS		**1E3050AS**	**1E3053AS**
DALI	ANTI-SLIP GLASS		**1E3050DAAS**	**1E3053DAAS**

LED / 33W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			18°	
Fixture Power		37W	1	0.32	18947
Source Flux		2791lm	2	0.63	4737
Fixture Flux		2205lm	3	0.95	2105
Efficacy		60lm/W	4	1.27	1184
TS987	Imax=6789cd/klm	Imax	18947cd	5	1.58	758

Driver	Version	Colour	3000K	4000K
EL.	STANDARD		**1E3051**	**1E3054**
DALI	STANDARD		**1E3051DA**	**1E3054DA**
EL.	ANTI-SLIP GLASS		**1E3051AS**	**1E3054AS**
DALI	ANTI-SLIP GLASS		**1E3051DAAS**	**1E3054DAAS**

LED / 33W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			30°	
Fixture Power		37W	1	0.53	8160
Source Flux		2791lm	2	1.06	2040
Fixture Flux		2149lm	3	1.59	907
Efficacy		58lm/W	4	2.12	510
TS988	Imax=2924cd/klm	Imax	8160cd	5	2.65	326

Driver	Version	Colour	3000K	4000K
EL.	STANDARD		**1E3052**	**1E3055**
DALI	STANDARD		**1E3052DA**	**1E3055DA**
EL.	ANTI-SLIP GLASS		**1E3052AS**	**1E3055AS**
DALI	ANTI-SLIP GLASS		**1E3052DAAS**	**1E3055DAAS**

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation. IP69K complies with Standard DIN 40050-9.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve



Flush ring
Ø286 H225

Straight edge ring
Ø271 H223

	Code
	1E2394

Grey nylon installation sleeve.
The sleeve is pre-set for both flush or straight edge installation.
Complete with dedicated cover cap for installations in concrete.
Flush ring Ø 286 H.225.
Straight edge ring Ø 271 H. 223.

Accessories

Tool

Code
1E2496

Metal handle for fixture removal

Code
1E2495

Features TORX HEAD, TX 30.

Code
1E0388

Sucker tool to raise the glass.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

KEPLERO



Wall Washer



LED / 33W



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			106°	65°	
	Fixture Power	36W	1	2.68	1.61	1355
	Source Flux	4550lm	2	5.36	3.22	339
	Fixture Flux	2318lm	3	8.04	4.84	151
	Efficacy	65lm/W	4	10.71	6.45	85
TS853	Imax=393cd/klm	Imax 1790cd	5	13.39	8.06	54

Certificate	Driver	Version	Colour	3000K	4000K
ENEC	EL.	STANDARD		**1E2561**	**1E2562**
	DALI	STANDARD		**1E2561DA**	**1E2562DA**
	EL.	ANTI-SLIP GLASS		**1E2561AS**	**1E2562AS**
	DALI	ANTI-SLIP GLASS		**1E2561DAAS**	**1E2562DAAS**

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation. IP69K complies with Standard DIN 40050-9.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve



Code
1E2394

Grey nylon installation sleeve.
The sleeve is pre-set for both flush or straight edge installation.
Complete with dedicated cover cap for installations in concrete.
Flush ring Ø 286 H.225.
Straight edge ring Ø 271 H. 223.

Accessories

Tool

Code
1E2495

Features TORX HEAD, TX 30.

Code
1E2496

Metal handle for fixture removal

KEPLERO

	Code
	1E0388
Sucker tool to raise the glass.	

Connector

	Code
	1E2769
Linear connection box IP66/IP68. 5 poles max. wire section 1.5mm^2. Cable diameter range from 7 to 12mm.	

	Code
	1E2494
Multiple connection box IP68. 1 IN - 3 OUT 4 poles max. wire section 2.5mm^2. Cable diameter range from 6 to 12mm.	

Control systems

	Code
	1E3048
A IP67 Module for individual control of external devices equipped with DALI drivers. The module needs to be positioned in order to receive radio signals. The distance to the lighting fixtures can reach up to 50m. Wireless control via the Casambi application. LxHxP=56.5x22.3x35.8mm.	

	Code
	1E3049
IP67 Extender for wireless control of DALI fixtures. It generates a local DALI bus with the capacity to drive up to 64 fixtures. Can control DALI fixtures in outdoor applications via the Casambi application. LxHxP=150x40x148mm.	

KEPLERO



Wall Washer RGBW



LED RGBW / 49W



-		H(m)	D1(m)	D2(m)	Emax(lx)
-			114°	75°	
Fixture Power	56W	1	3.10	2.07	452
Source Flux	1091lm	2	6.19	4.14	113
Fixture Flux	1091lm	3	9.29	6.21	50
Efficacy	19lm/W	4	12.39	8.29	28
Imax	600cd	5	15.48	10.36	18

Driver	Version	Colour	Code
EL. DMX	STANDARD		**1E3123**
EL. DMX	ANTI-SLIP GLASS		**1E3123AS**

Note

Photometrics show the maximum emission values of fixtures.

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation. IP69K complies with Standard DIN 40050-9.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve



	Code
	1E2394

Grey nylon installation sleeve.
The sleeve is pre-set for both flush or straight edge installation.
Complete with dedicated cover cap for installations in concrete.
Flush ring Ø 286 H.225.
Straight edge ring Ø 271 H. 223.

Accessories

Tool

	Code
	1E2496
Metal handle for fixture removal	

	Code
	1E2495
Features TORX HEAD, TX 30.	

KEPLERO

	Code
	1E0388

Sucker tool to raise the glass.

Connector

	Code
	1E3184

IP68 4-way cable connector (5 pole).

Control systems

	Code
	1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the “RDM Targetti” software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

KEPLERO

Mini Zoom



LED / 12W / ZOOM / SP, FL, MWFL, WFL / 220-240Vac

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.		**1E2497**	**1E2498**
	DALI		**1E2497DA**	**1E2498DA**



3000K		H(m)	D(m)	Emax(lx)
Ra84			15°	
Fixture Power	14W	1	0.27	5715
Source Flux	1775lm	2	0.54	1429
Fixture Flux	610lm	3	0.82	635
Efficacy	45lm/W	4	1.09	357
TS815 Imax=3220cd/klm	Imax	5715cd	1.36	229



3000K		H(m)	D(m)	Emax(lx)
Ra84			32°	
Fixture Power	14W	1	0.58	2608
Source Flux	1775lm	2	1.15	652
Fixture Flux	809lm	3	1.73	290
Efficacy	60lm/W	4	2.30	163
TS816 Imax=1469cd/klm	Imax	2608cd	2.88	104



3000K		H(m)	D(m)	Emax(lx)
Ra84			53°	
Fixture Power	14W	1	0.99	1536
Source Flux	1775lm	2	1.98	384
Fixture Flux	1045lm	3	2.97	171
Efficacy	77lm/W	4	3.95	96
TS817 Imax=866cd/klm	Imax	1536cd	4.94	61



3000K		H(m)	D(m)	Emax(lx)
Ra84			61°	
Fixture Power	14W	1	1.18	1102
Source Flux	1775lm	2	2.37	276
Fixture Flux	1127lm	3	3.55	122
Efficacy	83lm/W	4	4.74	69
TS818 Imax=621cd/klm	Imax	1102cd	5.92	44

LED / 12W / ZOOM / SP, FL, MWFL, WFL / 48Vdc

Certificate	Driver	Colour	3000K	4000K
ENEC			**1E2499**	**1E2500**



3000K		H(m)	D(m)	Emax(lx)
Ra84			16°	
Fixture Power	13W	1	0.28	5715
Source Flux	1775lm	2	0.55	1429
Fixture Flux	615lm	3	0.83	635
Efficacy	49lm/W	4	1.10	357
TS815 Imax=3220cd/klm	Imax	5715cd	1.38	229



3000K		H(m)	D(m)	Emax(lx)
Ra84			33°	
Fixture Power	13W	1	0.58	2608
Source Flux	1775lm	2	1.17	652
Fixture Flux	809lm	3	1.75	290
Efficacy	65lm/W	4	2.33	163
TS816 Imax=1469cd/klm	Imax	2608cd	2.92	104



3000K		H(m)	D(m)	Emax(lx)
Ra84			53°	
Fixture Power	13W	1	0.99	1536
Source Flux	1775lm	2	1.98	384
Fixture Flux	1045lm	3	2.97	171
Efficacy	84lm/W	4	3.95	96
TS817 Imax=866cd/klm	Imax	1536cd	4.94	61



3000K		H(m)	D(m)	Emax(lx)
Ra84			61°	
Fixture Power	13W	1	1.18	1102
Source Flux	1775lm	2	2.37	276
Fixture Flux	1127lm	3	3.55	122
Efficacy	90lm/W	4	4.74	69
TS818 Imax=621cd/klm	Imax	1102cd	5.92	44

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

KEPLERO

Related codes

Sleeve

Ø	H	Code
166	200	**1E2521**

Installation sleeve.
Grey Nylon casing.
Round and square ring for semi-flush installation. Only round ring for flush installation.

L	H	Code
168	200	**1E2522**

Installation sleeve.
Grey Nylon casing and stainless steel profile.
Square ring for flush installation.

Decorative Ring



Code
1E2525

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2526

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2525AS

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2526AS

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.

Power Supply



Code
1E2320

Electronic driver 70W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).



Code
1E2321

Electronic driver 150W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).

KEPLERO



Code
1E2533

Electronic driver 240W, LxHxP=125x100x125mm, input voltage: 220V-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply.
DIN RAIL power supply.



Code
1E2323

Electronic driver 480W, LxHxP=227x100x125mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply - DIN RAIL power supply.

Accessories

Filter

Filter	Ø	Code
Red	70	**1T1712**
Green	70	**1T1713**
Blue	70	**1T1714**
Yellow	70	**1T1715**
Magenta	70	**1T1716**

Flat glass interference chromatic filter.
To be completed with an additional holder ring for Cloud, Ray Mini, Store and Keplero Mini HE.

Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Shutter

Colour	Code
◐	**1E2523**

Black half-moon shutter.

Tool

Code
1E0388

Sucker tool to raise the glass.

Code
1E2495

Features TORX HEAD, TX 30.

KEPLERO

	Code
	1E2524
Metal handle for fixture removal	

Connector

	Code
	1E2769
Linear connection box IP66/IP68. 5 poles max. wire section 1.5mm^2. Cable diameter range from 7 to 12mm.	

	Code
	1E2494
Multiple connection box IP68. 1 IN - 3 OUT 4 poles max. wire section 2.5mm^2. Cable diameter range from 6 to 12mm.	

Control systems

	Code
	1E3048
A IP67 Module for individual control of external devices equipped with DALI drivers. The module needs to be positioned in order to receive radio signals. The distance to the lighting fixtures can reach up to 50m. Wireless control via the Casambi application. LxHxP=56.5x22.3x35.8mm.	

	Code
	1E3049
IP67 Extender for wireless control of DALI fixtures. It generates a local DALI bus with the capacity to drive up to 64 fixtures. Can control DALI fixtures in outdoor applications via the Casambi application. LxHxP=150x40x148mm.	

KEPLERO

Mini Gimbal



LED / 8,4W / GIMBAL / SP / 220-240Vac



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			11°	
Fixture Power		11W	1	0.19	11401
Source Flux		768lm	2	0.38	2850
Fixture Flux		592lm	3	0.57	1267
Efficacy		56lm/W	4	0.77	713
TS819 Imax=14845cd/klm	Imax	11401cd	5	0.96	456

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.		**1E2501**	**1E2502**
	DALI		**1E2501DA**	**1E2502DA**

LED / 8,4W / GIMBAL / SP / 48Vdc



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			11°	
Fixture Power		10W	1	0.19	11401
Source Flux		768lm	2	0.38	2850
Fixture Flux		592lm	3	0.57	1267
Efficacy		61lm/W	4	0.77	713
TS819 Imax=14845cd/klm	Imax	11401cd	5	0.96	456

Certificate	Driver	Colour	3000K	4000K
ENEC			**1E2505**	**1E2506**

LED / 8,4W / GIMBAL / FL / 220-240Vac



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra80			32°	30°	
Fixture Power		11W	1	0.57	0.54	2112
Source Flux		768lm	2	1.15	1.09	528
Fixture Flux		568lm	3	1.72	1.63	235
Efficacy		54lm/W	4	2.29	2.17	132
TS820 Imax=2750cd/klm	Imax	2112cd	5	2.87	2.72	84

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.		**1E2503**	**1E2504**
	DALI		**1E2503DA**	**1E2504DA**

LED / 8,4W / GIMBAL / FL / 48Vdc



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra80			32°	30°	
Fixture Power		10W	1	0.57	0.54	2112
Source Flux		768lm	2	1.15	1.09	528
Fixture Flux		568lm	3	1.72	1.63	235
Efficacy		59lm/W	4	2.29	2.17	132
TS820 Imax=2750cd/klm	Imax	2112cd	5	2.87	2.72	84

Certificate	Driver	Colour	3000K	4000K
ENEC			**1E2507**	**1E2508**

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

KEPLERO

Related codes

Sleeve

Ø	H	Code
166	200	**1E2521**

Installation sleeve.
Grey Nylon casing.
Round and square ring for semi-flush installation. Only round ring for flush installation.

L	H	Code
168	200	**1E2522**

Installation sleeve.
Grey Nylon casing and stainless steel profile.
Square ring for flush installation.

Decorative Ring



Code
1E2525

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2526

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2525AS

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2526AS

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.

Power Supply



Code
1E2320

Electronic driver 70W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).



Code
1E2321

Electronic driver 150W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).

KEPLERO



Code
1E2533

Electronic driver 240W, LxHxP=125x100x125mm, input voltage: 220V-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply.
DIN RAIL power supply.



Code
1E2323

Electronic driver 480W, LxHxP=227x100x125mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply - DIN RAIL power supply.

Accessories

Filter

Filter	Ø	Code
Red	70	**1T1712**
Green	70	**1T1713**
Blue	70	**1T1714**
Yellow	70	**1T1715**
Magenta	70	**1T1716**

Flat glass interference chromatic filter.
To be completed with an additional holder ring for Cloud, Ray Mini, Store and Keplero Mini HE.

Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Shutter

Colour	Code
◐	**1E2523**

Black half-moon shutter.

Tool

Code
1E0388

Sucker tool to raise the glass.

Code
1E2495

Features TORX HEAD, TX 30.

KEPLERO

	Code
	1E2524
Metal handle for fixture removal	

Connector

	Code
	1E2769
Linear connection box IP66/IP68. 5 poles max. wire section 1.5mm^2. Cable diameter range from 7 to 12mm.	

	Code
	1E2494
Multiple connection box IP68. 1 IN - 3 OUT 4 poles max. wire section 2.5mm^2. Cable diameter range from 6 to 12mm.	

Control systems

	Code
	1E3048
A IP67 Module for individual control of external devices equipped with DALI drivers. The module needs to be positioned in order to receive radio signals. The distance to the lighting fixtures can reach up to 50m. Wireless control via the Casambi application. LxHxP=56.5x22.3x35.8mm.	

	Code
	1E3049
IP67 Extender for wireless control of DALI fixtures. It generates a local DALI bus with the capacity to drive up to 64 fixtures. Can control DALI fixtures in outdoor applications via the Casambi application. LxHxP=150x40x148mm.	

KEPLERO

Mini High Efficacy



LED / 12W / SP / 220-240Vac



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	14W	1	0.20	17736
Source Flux	1775lm	2	0.39	4434
Fixture Flux	1387lm	3	0.59	1971
Efficacy	103lm/W	4	0.79	1109
Imax	17736cd	5	0.99	709

TS821 Imax=9992cd/klm

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.		**1E2509**	**1E2510**
	DALI		**1E2509DA**	**1E2510DA**

LED / 12W / SP / 48Vdc



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	13W	1	0.20	17736
Source Flux	1775lm	2	0.39	4434
Fixture Flux	1403lm	3	0.59	1971
Efficacy	112lm/W	4	0.79	1109
Imax	17736cd	5	0.99	709

TS821 Imax=9992cd/klm

Certificate	Driver	Colour	3000K	4000K
ENEC			**1E2515**	**1E2516**

LED / 12W / FL / 220-240Vac



3000K		H(m)	D(m)	Emax(lx)
Ra84			18°	
Fixture Power	14W	1	0.31	7969
Source Flux	1775lm	2	0.63	1992
Fixture Flux	1397lm	3	0.94	885
Efficacy	104lm/W	4	1.25	498
Imax	7969cd	5	1.57	319

TS822 Imax=4490cd/klm

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.		**1E2511**	**1E2512**
	DALI		**1E2511DA**	**1E2512DA**

LED / 12W / FL / 48Vdc



3000K		H(m)	D(m)	Emax(lx)
Ra84			18°	
Fixture Power	13W	1	0.31	7969
Source Flux	1775lm	2	0.63	1992
Fixture Flux	1397lm	3	0.94	885
Efficacy	112lm/W	4	1.25	498
Imax	7969cd	5	1.57	319

TS822 Imax=4490cd/klm

Certificate	Driver	Colour	3000K	4000K
ENEC			**1E2517**	**1E2518**

LED / 12W / MWFL / 220-240Vac



3000K		H(m)	D(m)	Emax(lx)
Ra84			40°	
Fixture Power	14W	1	0.73	2861
Source Flux	1775lm	2	1.47	715
Fixture Flux	1384lm	3	2.20	318
Efficacy	102lm/W	4	2.93	179
Imax	2882cd	5	3.67	114

TS823 Imax=1624cd/klm

Certificate	Driver	Colour	3000K	4000K
ENEC	EL.		**1E2513**	**1E2514**
	DALI		**1E2513DA**	**1E2514DA**

KEPLERO

LED / 12W / MWFL / 48Vdc



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			40°	
	Fixture Power	13W	1	0.73	2861
	Source Flux	1775lm	2	1.47	715
	Fixture Flux	1384lm	3	2.20	318
	Efficacy	111lm/W	4	2.93	179
	Imax	2882cd	5	3.67	114

Certificate	Driver	Colour	3000K	4000K
ENEC			**1E2519**	**1E2520**

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve

Ø	H	Code
166	200	**1E2521**

Installation sleeve.
Grey Nylon casing.
Round and square ring for semi-flush installation. Only round ring for flush installation.

L	H	Code
168	200	**1E2522**

Installation sleeve.
Grey Nylon casing and stainless steel profile.
Square ring for flush installation.

Decorative Ring



Code
1E2525

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2526

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2525AS

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.



Code
1E2526AS

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.

KEPLERO

Power Supply



Code
1E2320

Electronic driver 70W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).



Code
1E2321

Electronic driver 150W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).



Code
1E2533

Electronic driver 240W, LxHxP=125x100x125mm, input voltage: 220V-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply.
DIN RAIL power supply.



Code
1E2323

Electronic driver 480W, LxHxP=227x100x125mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply - DIN RAIL power supply.

Accessories

Filter



Filter	Ø	Code
Red	70	**1T1712**
Green	70	**1T1713**
Blue	70	**1T1714**
Yellow	70	**1T1715**
Magenta	70	**1T1716**

Flat glass interference chromatic filter.
To be completed with an additional holder ring for Cloud, Ray Mini, Store and Keplero Mini HE.



Ø	Code
70	**1T1708**

Flat striped glass blade light refractive filter.
This makes the beam take on an oval shape and when combined with spotlights, the light blade appears more prominent.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Grid



Ø	Code
70	**1T1711**

Anti-glare louver.
Black painted metal honeycomb structure.
To be completed with an additional holder ring for Cloud, Ray Mini, Store, Label 9, CCTEvo Extractable 162 and Keplero Mini HE.

Shutter

Colour	Code
◐	**1E2523**

Black half-moon shutter.

KEPLERO

Holder Ring

Code
1T3727

Transparent polycarbonate accessory holder ring.

Tool

Code
1E0388

Sucker tool to raise the glass.

Code
1E2495

Features TORX HEAD, TX 30.

Code
1E2524

Metal handle for fixture removal

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

KEPLERO

Mini High Efficacy RGBW



LED RGBW / 15W / SP



			H(m)	D(m)	Emax(lx)
	-			18°	
	Fixture Power	15W	1	0.32	3858
	Source Flux	875lm	2	0.63	965
	Fixture Flux	656lm	3	0.95	429
	Efficacy	43lm/W	4	1.27	241
TS1412	Imax=4407cd/klm	Imax	3858cd	5	1.58	154

Power supply	Colour	Code
450mA		**1E3867**

LED RGBW / 15W / FL



			H(m)	D(m)	Emax(lx)
	-			33°	
	Fixture Power	15W	1	0.60	1617
	Source Flux	875lm	2	1.20	404
	Fixture Flux	657lm	3	1.80	180
	Efficacy	43lm/W	4	2.40	101
TS1413	Imax=1847cd/klm	Imax	1617cd	5	3.00	65

Power supply	Colour	Code
450mA		**1E3868**

LED RGBW / 15W / MWFL



			H(m)	D(m)	Emax(lx)
	-			49°	
	Fixture Power	15W	1	0.91	963
	Source Flux	875lm	2	1.82	241
	Fixture Flux	647lm	3	2.73	107
	Efficacy	42lm/W	4	3.64	60
TS1414	Imax=1100cd/klm	Imax	963cd	5	4.56	39

Power supply	Colour	Code
450mA		**1E3869**

Note

Photometrics show the maximum emission values of fixtures.

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve



Ø	H	Code
166	200	**1E2521**

Installation sleeve.
Grey Nylon casing.
Round and square ring for semi-flush installation. Only round ring for flush installation.



L	H	Code
168	200	**1E2522**

Installation sleeve.
Grey Nylon casing and stainless steel profile.
Square ring for flush installation.

KEPLERO

Decorative Ring



Code

1E2525

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code

1E2526

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code

1E2525AS

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.



Code

1E2526AS

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.

Power Supply



Code

1E3871

DMX 4 channel driver.
LxHxP=220x80x120mm, IP66, 110-277Vac.



Code

1E3881

DMX 4 channel driver.
LxHxP=220x80x120mm, IP68, 110-277Vac.

Accessories

Tool

Code

1E0388

Sucker tool to raise the glass.

Code

1E2495

Features TORX HEAD, TX 30.

Code

1E2524

Metal handle for fixture removal

KEPLERO

Control systems

	Code
	1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the “RDM Targetti” software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

KEPLERO



Mini Wall Washer



LED / 12W / WALL WASHER / 220-240Vac



		3000K	H(m)	D1(m)	D2(m)	Emax(lx)
		Ra84		34°	84°	
Fixture Power	14W		1	0.70	1.87	877
Source Flux	1852lm		2	1.40	3.75	219
Fixture Flux	933lm		3	2.10	5.62	97
Efficacy	67lm/W		4	2.81	7.49	55
TS1152 Imax=537cd/klm	Imax	994cd	5	3.51	9.36	35

Driver	Colour	3000K	4000K
EL.		**1E3517**	**1E3518**
DALI		**1E3517DA**	**1E3518DA**

LED / 12W / WALL WASHER / 48Vdc



		3000K	H(m)	D1(m)	D2(m)	Emax(lx)
		Ra84		34°	84°	
Fixture Power	13W		1	0.70	1.87	877
Source Flux	1852lm		2	1.40	3.75	219
Fixture Flux	933lm		3	2.10	5.62	97
Efficacy	75lm/W		4	2.81	7.49	55
TS1152 Imax=537cd/klm	Imax	994cd	5	3.51	9.36	35

Driver	Colour	3000K	4000K
		1E3519	**1E3520**

Note

All lighting fixtures have to be completed with installation sleeves.

The projector can withstand temporary accidental immersion to a depth of 1.3 metres (max.1h) but is unsuitable for permanent underwater installation.

All versions of the KEPLERO family meet all the requirements of EN 60598-2-13 standard regarding drive-over and walk-over performances. Low temperatures on the glass which characterises the LED range of fixtures make them suitable even for installation in “special areas”, such as spaces for children.

Related codes

Sleeve

Ø	H	Code
166	200	**1E2521**

Installation sleeve.
Grey Nylon casing.
Round and square ring for semi-flush installation. Only round ring for flush installation.



L	H	Code
168	200	**1E2522**

Installation sleeve.
Grey Nylon casing and stainless steel profile.
Square ring for flush installation.

KEPLERO

Decorative Ring



Code

1E2525

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code

1E2526

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
10mm thick extra clear protective glass.
Silicone gasket.
Anti-theft Torx screws.



Code

1E2525AS

Brushed stainless steel (AISI316L), ultra flat, bevelled edge decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.



Code

1E2526AS

Brushed stainless steel (AISI316L), ultra flat square decorative ring.
Special 10mm thick anti-slip glass for public pedestrian areas.
Silicone gasket.
Anti-theft Torx screws.

Power Supply



Code

1E2320

Electronic driver 70W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).



Code

1E2321

Electronic driver 150W, LxHxP=225x51x65mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP67.
Cable length 1 meter (IN-OUT).



Code

1E2533

Electronic driver 240W, LxHxP=125x100x125mm, input voltage: 220V-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply.
DIN RAIL power supply.



Code

1E2323

Electronic driver 480W, LxHxP=227x100x125mm, input voltage: 220-240V 50/60Hz, 48V-DC, IP20.
Without cable.
Complete with connector.
Electrical panel power supply - DIN RAIL power supply.

KEPLERO

Accessories

Tool

	Code
	1E0388

Sucker tool to raise the glass.

	Code
	1E2495

Features TORX HEAD, TX 30.

	Code
	1E2524

Metal handle for fixture removal

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

JUPITER

GENERAL INFO
Miniaturised recessed fixture
ø80mm - ø50mm

LED
Chip on board
From 157lm to 779lm
2700K - 3000K - 4000K
Ra90

PRODUCT EFFICACY
Up to 85lm/W

OPTICS
SP – FL – WFL

POWER SUPPLY
24V
Casambi control system available using a dedicated accessory (only with DALI dimmer).

MATERIAL
Anodised polished aluminium body. Polished stainless steel front ring.

ON DEMAND
110-277 vac power supply

High performance fixture with a lenticular optic. The absence of visible screws and the raised ring avoid treacherous steps on the ground. The 24V power supply makes it possible to install Jupiter in environments like SPAs or near swimming pools. It is easy to install and has an extremely compact recess depth.

All Jupiter fixtures are drive-over and can also be supplied complete with an anti-glare grill or an asymmetric screen.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Also available in a projector version.



Studio Ceri
Prato, Italy

Architect Studio Ceri

Photographer Officine Fotografiche

JUPITER

Drive-over



LED / 6,1W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			21°	
Fixture Power		7W	1	0.38	2336
Source Flux		756lm	2	0.75	584
Fixture Flux		532lm	3	1.13	260
Efficacy		79lm/W	4	1.50	146
TS1424	Imax=3090cd/klm	Imax	2336cd	5	1.88	93

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E345190**	**1E345490**	**1E345790**

LED / 6,1W / FL (39°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			39°	
Fixture Power		7W	1	0.71	1020
Source Flux		756lm	2	1.41	255
Fixture Flux		550lm	3	2.12	113
Efficacy		82lm/W	4	2.83	64
TS1425	Imax=1349cd/klm	Imax	1020cd	5	3.53	41

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E345290**	**1E345590**	**1E345890**

LED / 6,1W / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			53°	
Fixture Power		7W	1	0.99	642
Source Flux		756lm	2	1.99	161
Fixture Flux		526lm	3	2.98	71
Efficacy		79lm/W	4	3.98	40
TS1426	Imax=849cd/klm	Imax	642cd	5	4.97	26

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E345390**	**1E345690**	**1E345990**



Drive-over with grid



LED / 6,1W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			18°	
Fixture Power		7W	1	0.32	2150
Source Flux		756lm	2	0.63	537
Fixture Flux		334lm	3	0.95	239
Efficacy		50lm/W	4	1.27	134
TS1427	Imax=2844cd/klm	Imax	2150cd	5	1.59	86

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E347190**	**1E347490**	**1E347790**

JUPITER

LED / 6,1W / FL (29°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			29°	
Fixture Power	7W	1		0.52	938
Source Flux	756lm	2		1.05	235
Fixture Flux	299lm	3		1.57	104
Efficacy	45lm/W	4		2.09	59
TS1428 Imax=1241cd/klm	Imax	938cd	5	2.61	38

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E347290**	**1E347590**	**1E347890**

LED / 6,1W / FL (38°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			38°	
Fixture Power	7W	1		0.68	577
Source Flux	756lm	2		1.37	144
Fixture Flux	259lm	3		2.05	64
Efficacy	39lm/W	4		2.73	36
TS1429 Imax=763cd/klm	Imax	577cd	5	3.41	23

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E347390**	**1E347690**	**1E347990**



Drive-over with asymmetric screen



LED / 6,1W / SP - ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			26°	26°	
Fixture Power	7W	1		0.56	0.50	381
Source Flux	756lm	2		1.11	1.00	95
Fixture Flux	161lm	3		1.67	1.51	42
Efficacy	24lm/W	4		2.22	2.01	24
TS1430 Imax=628cd/klm	Imax	475cd	5	2.78	2.51	15

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E348990**	**1E349290**	**1E349590**

LED / 6,1W / FL - ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			36°	41°	
Fixture Power	7W	1		0.82	0.82	218
Source Flux	756lm	2		1.64	1.64	55
Fixture Flux	154lm	3		2.46	2.46	24
Efficacy	23lm/W	4		3.29	3.29	14
TS1431 Imax=377cd/klm	Imax	285cd	5	4.11	4.11	9

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E349090**	**1E349390**	**1E349690**

LED / 6,1W / WFL - ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			42°	49°	
Fixture Power	7W	1		1.01	1.05	151
Source Flux	756lm	2		2.01	2.11	38
Fixture Flux	143lm	3		3.02	3.16	17
Efficacy	21lm/W	4		4.03	4.22	9
TS1432 Imax=270cd/klm	Imax	204cd	5	5.03	5.27	6

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E349190**	**1E349490**	**1E349790**

JUPITER

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Sleeve

	Ø	H	Code
	75	80	**1E3460**

Installation sleeve.
For the drive-over version.

JUPITER

Accessories

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems



	Code
	1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

JUPITER



Mini Drive-over



LED / 1,9W / SP (19°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			19°	
Fixture Power	3W		1	0.33	675
Source Flux	170lm		2	0.65	169
Fixture Flux	101lm		3	0.98	75
Efficacy	37lm/W		4	1.31	42
TS1415	Imax=3977cd/klm	Imax	675cd	5	1.63	27

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E346190**	**1E346490**	**1E346790**

LED / 1,9W / SP (24°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			24°	
Fixture Power	3W		1	0.42	417
Source Flux	170lm		2	0.85	104
Fixture Flux	95lm		3	1.27	46
Efficacy	35lm/W		4	1.69	26
TS1416	Imax=2457cd/klm	Imax	417cd	5	2.11	17

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E346290**	**1E346590**	**1E346890**

LED / 1,9W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			32°	
Fixture Power	3W		1	0.57	241
Source Flux	170lm		2	1.15	60
Fixture Flux	93lm		3	1.72	27
Efficacy	34lm/W		4	2.30	15
TS1417	Imax=1421cd/klm	Imax	241cd	5	2.87	10

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E346390**	**1E346690**	**1E346990**



Mini Drive-over with grid



LED / 1,9W / SP (17°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			17°	
Fixture Power	3W		1	0.29	559
Source Flux	170lm		2	0.58	140
Fixture Flux	64lm		3	0.88	62
Efficacy	24lm/W		4	1.17	35
TS1418	Imax=3296cd/klm	Imax	559cd	5	1.46	22

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E348090**	**1E348390**	**1E348690**

JUPITER

LED / 1,9W / SP (20°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			20°	
Fixture Power	3W	1		0.36	374
Source Flux	170lm	2		0.72	93
Fixture Flux	60lm	3		1.07	42
Efficacy	22lm/W	4		1.43	23
TS1419 Imax=2203cd/klm	Imax	374cd	5	1.79	15

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E348190**	**1E348490**	**1E348790**

LED / 1,9W / SP (25°)



	3000K		H(m)	D(m)	Emax(lx)
	Ra90			25°	
Fixture Power	3W	1		0.44	216
Source Flux	170lm	2		0.88	54
Fixture Flux	52lm	3		1.32	24
Efficacy	19lm/W	4		1.75	13
TS1420 Imax=1273cd/klm	Imax	216cd	5	2.19	9

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E348290**	**1E348590**	**1E348890**

Mini Drive-over with asymmetric screen



LED / 1,9W / SP - ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			18°	18°	
Fixture Power	3W	1		0.36	0.33	91
Source Flux	170lm	2		0.72	0.66	23
Fixture Flux	20lm	3		1.09	0.99	10
Efficacy	7lm/W	4		1.45	1.32	6
TS1421 Imax=645cd/klm	Imax	109cd	5	1.81	1.65	4

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E349890**	**1E350190**	**1E350490**

LED / 1,9W / FL - ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			21°	24°	
Fixture Power	3W	1		0.42	0.46	64
Source Flux	170lm	2		0.84	0.91	16
Fixture Flux	18lm	3		1.26	1.37	7
Efficacy	7lm/W	4		1.68	1.82	4
TS1422 Imax=443cd/klm	Imax	75cd	5	2.10	2.28	3

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E349990**	**1E350290**	**1E350590**

LED / 1,9W / WFL - ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra90			31°	32°	
Fixture Power	3W	1		0.65	0.60	40
Source Flux	170lm	2		1.29	1.20	10
Fixture Flux	18lm	3		1.94	1.81	4
Efficacy	7lm/W	4		2.59	2.41	2
TS1423 Imax=278cd/klm	Imax	47cd	5	3.23	3.01	2

Power supply	Colour	2700K	3000K	4000K
24Vdc		**1E350090**	**1E350390**	**1E350690**

JUPITER

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Sleeve

Ø	H	Code
44	60	**1E3470**

Installation sleeve.
For the drive-over version.

JUPITER

Accessories

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems



	Code
	1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

SATURN

GENERAL INFO
Miniaturised recessed fixture.
ø35mm – ø60mm

LED
LED Emitter
From 353lm to 682lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 10lm/W

OPTICS
WFL

POWER SUPPLY
Electronic – DALI – 1-10V
Casambi control system available using a dedicated accessory (only with DALI dimmer).

MATERIAL
Anodised polished aluminium body. Front made entirely of screen-printed, opal white glass.

ON DEMAND

110-277Vac power supply

Ra Ra90

A range of miniature 24V inground fixtures with a glass finishing ring for an elegant glass only effect. It is available in two different sizes, both extremely compact and flush opal glass that screens the lamp to produce a soft light.

The 24V voltage, the absence of visible screws and the “glass only” effect make it particularly suitable for indoor installations in hospitality, SPAs or homes.
The glass only finish for Saturn goes perfectly with the same aesthetic solution in the Mercure range, to light environments in different ways using the same family feeling.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.



Park Hyatt
Wien, Austria

Photographer Gregor Titze

SATURN





LED / 4W / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			115°	
Fixture Power		5W	1	3.13	16
Source Flux		638lm	2	6.27	4
Fixture Flux		48lm	3	9.40	2
Efficacy		10lm/W	4	12.53	1
Imax		16cd	5	15.67	1

Power supply	3000K	4000K
24Vdc	**1E3144**	**1E3145**

Related codes

Power Supply



Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.

Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Sleeve



	Code
	1E3177

Installation sleeve.
Flush installation h 70, Ø 65mm.
Straight installation h 60, Ø 57mm.

SATURN

Accessories

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems



	Code
	1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

SATURN



Mini



LED / 2,6W / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			122°	
Fixture Power		3W	1	3.59	4
Source Flux		353lm	2	7.18	1
Fixture Flux		11lm	3	10.77	0
Efficacy		4lm/W	4	14.36	0
Imax		4cd	5	17.95	0

	Power supply	3000K	4000K
	24Vdc	**1E3146**	**1E3147**

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Sleeve

	Code
	1E3178

Installation sleeve.
Flush installation h 70, Ø 40mm.
Straight installation h 60, Ø 34mm.

SATURN

Accessories

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems



	Code
	1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

LED.Y

GENERAL INFO
Recessed fixture
Multiled
ø60mm – ø68mm
Monoled-RGB
ø63mm

LED
Monoled: LED emitter
3000K – 6000K
From 99lm to 121lm
Ra80
Multiled: LED Board
6000K – Blue – Amber
From 5lm to 7lm
Ra80
RGB: RGB LED Multichip
From 40lm to 48lm

PRODUCT EFFICACY
Up to 48lm/W

OPTICS
Monoled
SP - FL
Multiled/RGB
VWFL

POWER SUPPLY
Electronic

MATERIAL
Anodised aluminium body and ring.

ON DEMAND
110-277Vac power supply

A series of miniature LED fixtures available in recessed or projector versions with monochromatic LED and RGB technology. The monochromatic versions are both mono and multi-LED.

The recessed version has a flat, flared edge and domed glass for a choreographic effect.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Multiled
flush ring - flat screen



LED / 1W / VWFL



6000K		H(m)	D(m)	Emax(lx)
-			102°	
Fixture Power	2W	1	2.47	2
Source Flux	5lm	2	4.94	0
Fixture Flux	5lm	3	7.41	0
Efficacy	3lm/W	4	9.87	0
Imax	2cd	5	12.34	0

Power supply	Colour	6000K	AMBER	BLUE
24Vdc		**1E1022**	**1E1021**	**1E1028**

Multiled
raised ring - flat screen



LED / 1W / VWFL



6000K		H(m)	D(m)	Emax(lx)
Ra80			102°	
Fixture Power	2W	1	2.47	2
Source Flux	5lm	2	4.94	0
Fixture Flux	5lm	3	7.41	0
Efficacy	3lm/W	4	9.87	0
Imax	2cd	5	12.34	0

Power supply	Colour	6000K	AMBER	BLUE
24Vdc		**1E1012**	**1E1011**	**1E1018**

Multiled raised ring
curved screen



LED / 1W / VWFL



6000K		H(m)	D(m)	Emax(lx)
Ra80			102°	
Fixture Power	2W	1	2.47	2
Source Flux	5lm	2	4.94	0
Fixture Flux	5lm	3	7.41	0
Efficacy	3lm/W	4	9.87	0
Imax	2cd	5	12.34	0

Power supply	Colour	6000K	AMBER	BLUE
24Vdc		**1E1002**	**1E1001**	**1E1008**

Note

All LED.Y fixtures meet all the requirements of EN 60598-2-13 standard regarding pedestrian use and are therefore ideal for lighting all the areas provided for by the regulations, such as pedestrian zones and other designated areas.

LED.Y

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.

Accessories

Mounting System

Code
1E0994

Installation kit.
Extension for the PVC casing.
A wider space facilitates electrical connections.
Water tight electrical connection system is not included.



Code
1E0996

Steel spring. For ceiling and wall installation.

Tool

Code
1E0990

Mounting key.

LED.Y

Monoled



LED / 2W / SP

	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
	Fixture Power	3W	1	0.16	2012
	Source Flux	117lm	2	0.32	503
	Fixture Flux	116lm	3	0.48	224
	Efficacy	39lm/W	4	0.64	126
	Imax	2012cd	5	0.80	80

Power supply	Colour	3000K	6000K
700mA		**1E2367**	**1E2368**

LED / 2W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			34°	
	Fixture Power	3W	1	0.60	223
	Source Flux	99lm	2	1.21	56
	Fixture Flux	99lm	3	1.81	25
	Efficacy	33lm/W	4	2.42	14
	Imax	223cd	5	3.02	9

Power supply	Colour	3000K	6000K
700mA		**1E2369**	**1E2370**

Note

All LED.Y fixtures meet all the requirements of EN 60598-2-13 standard regarding pedestrian use and are therefore ideal for lighting all the areas provided for by the regulations, such as pedestrian zones and other designated areas.

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output current	IP	Code
105x74	17/12W	220-240Vac/110-120Vac	700mA	IP68	**1E1385**

Electronic power supply.

Accessories

Tool

Code
1E0990

Mounting key.

Accessories

Mounting System

Code
1E0994

Installation kit.
Extension for the PVC casing.
A wider space facilitates electrical connections.
Water tight electrical connection system is not included.



Code
1E0996

Steel spring. For ceiling and wall installation.

LED.Y

Monoled RGB



LED RGB / 3,5W / SP



Power supply	Colour	RGB
3x350mA		**1E1854**

LED RGB / 3,5W / FL



Power supply	Colour	RGB
3x350mA		**1E1409**

Note

Photometrics show the maximum emission values of fixtures.

All LED.Y fixtures meet all the requirements of EN 60598-2-13 standard regarding pedestrian use and are therefore ideal for lighting all the areas provided for by the regulations, such as pedestrian zones and other designated areas.

Related codes

Control systems

Code
1E1401

SECS 75.
IP67
Power supply and Control System SECS Scene Effect Control System.
SECS 75 drivers combine the following 3 functions in a single unit,: power supply to RGB LED devices, playback of pre-set colour sequences and a DMX interface for external control devices.
The SECS “Easy-Run-Menu” function is able to playback colour-changing light scenarios that are pre-stored into the driver without the use of an external driver: - 8 static colour scenarios; - 8 dynamic colour sequences; - 5 different playback speed values; - Start/Stop the selected scenario using a remote switch.
SECS 75 drivers can also be controlled through DMX 512; in this case: - DMX address (from 1 to 511) can be configured by using dip-switches; - 3 channel mode: all R-G-B outputs are controlled simultaneously by 3 DMX channels only; - 6 channel mode: the outputs are divided into 2 R-G-B groups, each one controlled by 3 different DMX channels; - DMX line termination: SECS drivers contain a 120Ohm resistance which can be activated using a dip-switch; - DMX output is available for connection to other DMX devices.
75W output.

Code
1T2245

SECS 36.
IP20
Power supply and Control System SECS Scene Effect Control System.
SECS 36 drivers combine the following 3 functions in a single unit,: power supply to RGB LED devices, playback of pre-set colour sequences and a DMX interface for external control devices.
The SECS “Easy-Run-Menu” function is able to playback colour-changing light scenarios that are pre-stored into the driver without the use of an external driver: - 8 static colour scenarios; - 8 dynamic colour sequences; - 5 different playback speed values; - Start/Stop the selected scenario using a remote switch.
SECS 75 drivers can also be controlled through DMX 512; in this case: - DMX address (from 1 to 511) can be configured by using dip-switches; - 3 channel mode: all R-G-B outputs are controlled simultaneously by 3 DMX channels only; - 6 channel mode: the outputs are divided into 2 R-G-B groups, each one controlled by 3 different DMX channels; - DMX line termination: SECS drivers contain a 120Ohm resistance which can be activated using a dip-switch; - DMX output is available for connection to other DMX devices.
35W output.

Accessories

Mounting System





	Code
	1E0994

Installation kit.
Extension for the PVC casing.
A wider space facilitates electrical connections.
Water tight electrical connection system is not included.

	Code
	1E0996

Steel spring. For ceiling and wall installation.

Tool

	Code
	1E0990

Mounting key.

Cable

	Code
	1E1713

6-pole cable for driver output connection to Constant Current LED sources.

Control systems

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

TITANO

GENERAL INFO
Semi-recessed fixture for grazing light effect.
ø169mm

LED
LED Emitter multichip
From 47lm to 181lm
3000K Ra83
4000K Ra80

PRODUCT EFFICACY
Unitil 31lm/W

OPTICS
One-emission 106°
Double-emission 106°+106°
Pluri-emission 4x62°

POWER SUPPLY
Electronic

MATERIAL
Stainless steel body.
Painted anodised aluminium ring and cover.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

Cataphoresis treatment

Grazing light effect inground fixture with a light that can be projected in one, two or more directions. The vertical angle is controlled by the lens to produce a glare-free effect which is highly effective on horizontal surfaces.

They meet all the requirements of standard EN 60598-2-13 regarding vehicle and pedestrian use and are therefore ideal for lighting all the areas provided for by the regulations, such as car parks, pedestrian zones and other designated areas.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

TITANO

LED



LED / 5W / MONO-DIRECTIONAL EMISSION



3000K	
Ra83	
Fixture Power	6W
Source Flux	47lm
Fixture Flux	47lm
Efficacy	8lm/W
EV331 Imax=3651cd/klm	Imax 172cd

Driver	Colour	3000K	4000K
EL.		**1E2770**	**1E2771**

LED / 5W / BI-DIRECTIONAL EMISSION



3000K	
Ra83	
Fixture Power	6W
Source Flux	93lm
Fixture Flux	93lm
Efficacy	16lm/W
EV332 Imax=1846cd/klm	Imax 172cd

Driver	Colour	3000K	4000K
EL.		**1E2772**	**1E2773**

LED / 5W / MULTIDIRECTIONAL



3000K	
Ra83	
Fixture Power	6W
Source Flux	158lm
Fixture Flux	158lm
Efficacy	27lm/W
EV333 Imax=1020cd/klm	Imax 162cd

Driver	Colour	3000K	4000K
EL.		**1E2774**	**1E2775**

Accessories

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Projectors

Outdoor

Upgrade

Linear projectors

648
JEDI

648
JEDI RGBW

662
JEDI Compact

Projectors



678
DART Maxi
214x214mm

678
DART Medium
134x134mm

678
DART Small
76x76mm

678
DART Small
Remote driver
76x76mm

696
PYROS
Ø 186mm

696
PYROS
RGBW
Ø 186mm

696
NANO PYROS
Ø 107mm

696
NANO PYROS
RGB
Ø 107mm

696
PICO PYROS
Ø 45mm

708
JUPITER PRO
Ø 50mm

708
JUPITER PRO
Small
Ø 40mm

708
JUPITER Mini
Ø 38mm

722
LED.Y
Ø50mm

722
LED.Y
RGB
Ø 50mm

JEDI

Projector

GENERAL INFO
Adjustable linear projector.
Lengths 616mm – 916mm – 1216mm

LED
Optics FL, GR, WW - Linear boards
Optic SP - LED Emitter
Version RGBW - LED Emitter
From 632lm to 7180m
3000K – 4000K
Ra84
RGBW

PRODUCT EFFICACY
Unitil 113lm/W

OTTICHE
SP – FL – Grazing – Wall Washer

POWER SUPPLY
Electronic – DALI

MATERIAL
Extruded anodised aluminium body.
Extra clear glass flat screen.
Black polycarbonate driver box.

ON DEMAND

110-277Vac power supply (Jedi RGBW)

2700K - 3500K

A coordinated range of linear projectors for lighting large surfaces.

A coordinated range of linear projectors for lighting wide surfaces. The multiplicity of effects, installation flexibility, three different lengths and the possibility to camouflage them into the architecture make them fundamental tools for lighting large surfaces.

The accessory fixing system allows the projector to be adjusted with aim locking.

Completely sealed housing complete - external electrical connection through IP68 connectors.

Also available Inground and RGB versions.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.



Plus





Four different effects

Spot and Flood optics to obtein more concentrated, precise lighting.
Grazing Optic for a grazing, uniform light effect for installation near to the wall to be illuminated.
Wall Washer Optic for a completely homogeneous effect on the wall, thus avoiding any bright stripes or separate beams that are typical of linear fixtures that are fitted with visible LED strips.

The different lengths have proportioned lumen packets to suit each one

The different lengths have proportioned lumen packets to suit each one. The same quantity of light per linear metre makes it possible to light every surface in a uniform way irrespective of the length of the fixture used.

JEDI

Projector L. 616mm



LED / 23W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		28W	1	0.18	32201
Source Flux		1947lm	2	0.37	8050
Fixture Flux		1560lm	3	0.55	3578
Efficacy		56lm/W	4	0.73	2013
TS889	Imax=16539cd/klm	Imax 32201cd	5	0.92	1288

Driver	Colour	3000K	4000K
EL.		**1E2653**	**1E2654**
DALI		**1E2655**	**1E2656**

LED / 12W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		15W	1	0.57	1.84	1203
Source Flux		1720lm	2	1.14	3.68	301
Fixture Flux		1285lm	3	1.70	5.53	134
Efficacy		86lm/W	4	2.27	7.37	75
TS886	Imax=699cd/klm	Imax 1203cd	5	2.84	9.21	48

Driver	Colour	3000K	4000K
EL.		**1E2605**	**1E2606**
DALI		**1E2607**	**1E2608**

LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		28W	1	0.57	1.84	2392
Source Flux		3420lm	2	1.14	3.68	598
Fixture Flux		2555lm	3	1.70	5.53	266
Efficacy		91lm/W	4	2.27	7.37	149
TS885	Imax=699cd/klm	Imax 2392cd	5	2.84	9.21	96

Driver	Colour	3000K	4000K
EL.		**1E2609**	**1E2610**
DALI		**1E2611**	**1E2612**

LED / 12W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		15W	1	0.55	1.70	1155
Source Flux		1720lm	2	1.11	3.40	289
Fixture Flux		1293lm	3	1.66	5.10	128
Efficacy		86lm/W	4	2.22	6.79	72
TS884	Imax=774cd/klm	Imax 1331cd	5	2.77	8.49	46

Driver	Colour	3000K	4000K
EL.		**1E2629**	**1E2630**
DALI		**1E2631**	**1E2632**

LED / 24W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		28W	1	0.55	1.70	2297
Source Flux		3420lm	2	1.11	3.40	574
Fixture Flux		2572lm	3	1.66	5.10	255
Efficacy		92lm/W	4	2.22	6.79	144
TS883	Imax=774cd/klm	Imax 2646cd	5	2.77	8.49	92

Driver	Colour	3000K	4000K
EL.		**1E2633**	**1E2634**
DALI		**1E2635**	**1E2636**

JEDI

LED / 12W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			15°	76°	
Fixture Power	15W	1	0.26	1.55	2753
Source Flux	1720lm	2	0.51	3.10	688
Fixture Flux	1481lm	3	0.77	4.65	306
Efficacy	99lm/W	4	1.02	6.20	172
Imax	2753cd	5	1.28	7.76	110

TS888 Imax=1601cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2581**	**1E2582**
DALI		**1E2583**	**1E2584**

LED / 24W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			15°	76°	
Fixture Power	28W	1	0.26	1.55	5474
Source Flux	3420lm	2	0.51	3.10	1368
Fixture Flux	2961lm	3	0.77	4.65	608
Efficacy	106lm/W	4	1.02	6.21	342
Imax	5474cd	5	1.28	7.76	219

TS887 Imax=1601cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2585**	**1E2586**
DALI		**1E2587**	**1E2588**

Projector L. 916mm



LED / 34W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			10°	
Fixture Power	40W	1	0.18	48326
Source Flux	2922lm	2	0.37	12081
Fixture Flux	2341lm	3	0.55	5370
Efficacy	59lm/W	4	0.73	3020
Imax	48326cd	5	0.92	1933

TS889 Imax=16539cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2657**	**1E2658**
DALI		**1E2659**	**1E2660**

LED / 18W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			32°	85°	
Fixture Power	22W	1	0.57	1.84	1804
Source Flux	2580lm	2	1.14	3.68	451
Fixture Flux	1927lm	3	1.70	5.53	200
Efficacy	88lm/W	4	2.27	7.37	113
Imax	1804cd	5	2.84	9.21	72

TS886 Imax=699cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2613**	**1E2614**
DALI		**1E2615**	**1E2616**

LED / 36W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			32°	85°	
Fixture Power	40W	1	0.57	1.84	3588
Source Flux	5130lm	2	1.14	3.68	897
Fixture Flux	3833lm	3	1.70	5.53	399
Efficacy	96lm/W	4	2.27	7.37	224
Imax	3588cd	5	2.84	9.21	144

TS885 Imax=699cd/klm

Driver	Colour	3000K	4000K
EL.		**1E2617**	**1E2618**
DALI		**1E2619**	**1E2620**

JEDI

LED / 18W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		22W	1	0.55	1.70	1733
Source Flux		2580lm	2	1.11	3.40	433
Fixture Flux		1940lm	3	1.66	5.10	193
Efficacy		88lm/W	4	2.22	6.79	108
TS884	Imax=774cd/klm	Imax 1996cd	5	2.77	8.49	69

Driver	Colour	3000K	4000K
EL.		**1E2637**	**1E2638**
DALI		**1E2639**	**1E2640**

LED / 36W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		40W	1	0.55	1.70	3445
Source Flux		5130lm	2	1.11	3.40	861
Fixture Flux		3858lm	3	1.66	5.10	383
Efficacy		96lm/W	4	2.22	6.79	215
TS883	Imax=774cd/klm	Imax 3969cd	5	2.77	8.49	138

Driver	Colour	3000K	4000K
EL.		**1E2641**	**1E2642**
DALI		**1E2643**	**1E2644**

LED / 18W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		22W	1	0.26	1.55	4130
Source Flux		2580lm	2	0.51	3.10	1032
Fixture Flux		2222lm	3	0.77	4.65	459
Efficacy		101lm/W	4	1.02	6.20	258
TS888	Imax=1601cd/klm	Imax 4130cd	5	1.28	7.76	165

Driver	Colour	3000K	4000K
EL.		**1E2589**	**1E2590**
DALI		**1E2591**	**1E2592**

LED / 36W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		40W	1	0.26	1.55	8211
Source Flux		5130lm	2	0.51	3.10	2053
Fixture Flux		4441lm	3	0.77	4.65	912
Efficacy		111lm/W	4	1.02	6.21	513
TS887	Imax=1601cd/klm	Imax 8211cd	5	1.28	7.76	328

Driver	Colour	3000K	4000K
EL.		**1E2593**	**1E2594**
DALI		**1E2595**	**1E2596**

Projector L. 1216mm



LED / 46W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		51W	1	0.18	64401
Source Flux		3894lm	2	0.37	16100
Fixture Flux		3120lm	3	0.55	7156
Efficacy		61lm/W	4	0.73	4025
TS889	Imax=16539cd/klm	Imax 64401cd	5	0.92	2576

Driver	Colour	3000K	4000K
EL.		**1E2661**	**1E2662**
DALI		**1E2663**	**1E2664**

JEDI

LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		28W	1	0.57	1.84	2405
Source Flux		3440lm	2	1.14	3.68	601
Fixture Flux		2570lm	3	1.70	5.53	267
Efficacy		92lm/W	4	2.27	7.37	150
TS886	Imax=699cd/klm	Imax	5	2.84	9.21	96

Driver	Colour	3000K	4000K
EL.		**1E2621**	**1E2622**
DALI		**1E2623**	**1E2624**

LED / 48W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			32°	85°	
Fixture Power		53W	1	0.57	1.84	4784
Source Flux		6840lm	2	1.14	3.68	1196
Fixture Flux		5111lm	3	1.70	5.53	532
Efficacy		96lm/W	4	2.27	7.37	299
TS885	Imax=699cd/klm	Imax	5	2.84	9.21	191

Driver	Colour	3000K	4000K
EL.		**1E2625**	**1E2626**
DALI		**1E2627**	**1E2628**

LED / 24W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		28W	1	0.55	1.70	2310
Source Flux		3440lm	2	1.11	3.40	578
Fixture Flux		2587lm	3	1.66	5.10	257
Efficacy		92lm/W	4	2.22	6.79	144
TS884	Imax=774cd/klm	Imax	5	2.77	8.49	92

Driver	Colour	3000K	4000K
EL.		**1E2645**	**1E2646**
DALI		**1E2647**	**1E2648**

LED / 48W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			28°	78°	
Fixture Power		53W	1	0.55	1.70	4594
Source Flux		6840lm	2	1.11	3.40	1148
Fixture Flux		5143lm	3	1.66	5.10	510
Efficacy		97lm/W	4	2.22	6.79	287
TS883	Imax=774cd/klm	Imax	5	2.77	8.49	184

Driver	Colour	3000K	4000K
EL.		**1E2649**	**1E2650**
DALI		**1E2651**	**1E2652**

LED / 24W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		28W	1	0.26	1.55	5506
Source Flux		3440lm	2	0.51	3.10	1377
Fixture Flux		2963lm	3	0.77	4.65	612
Efficacy		106lm/W	4	1.02	6.20	344
TS888	Imax=1601cd/klm	Imax	5	1.28	7.76	220

Driver	Colour	3000K	4000K
EL.		**1E2597**	**1E2598**
DALI		**1E2599**	**1E2600**

LED / 48W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			15°	76°	
Fixture Power		53W	1	0.26	1.55	10948
Source Flux		6840lm	2	0.51	3.10	2737
Fixture Flux		5922lm	3	0.77	4.65	1216
Efficacy		112lm/W	4	1.02	6.21	684
TS887	Imax=1601cd/klm	Imax	5	1.28	7.76	438

Driver	Colour	3000K	4000K
EL.		**1E2601**	**1E2602**
DALI		**1E2603**	**1E2604**

JEDI

Related codes

Mounting System



Code
1E2752

Short bracket for wall installation (2 pieces).



Code
1E2753

Long bracket for wall installation (2 pieces).



Code
1E2754

Bracket for ceiling installation (2 pieces).

Accessories

End Caps

Code
1E2761

End cap.

Cover Panel



L	Code
616	**1E3045**
916	**1E3046**
1216	**1E3047**

Side cover for ceiling installation.



L	Code
616	**1E2755**
916	**1E2756**
1216	**1E2757**

Side cover for wall/cornice installation.



L	Code
616	**1E2758**
916	**1E2759**
1216	**1E2760**

Anti-glare side cover.

JEDI

Cable

L	Code
320	**1E2762**
470	**1E2763**
620	**1E2764**
770	**1E2765**

Connection cable.
Complete with 5 pole connectors.
For the electronic and DALI version.
1E2762 - For in line adjacent connection of one 600mm projector with one 900mm projector.
1E2763 - For in line adjacent connection of one 600mm projector with one 1200mm projector or two 900mm projectors.
1E2764 - For in line adjacent connection of one 900mm projector with one 1200mm projector.
1E2765 - For in line adjacent connection of two 1200mm projectors.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Control systems

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

JEDI

Projector RGBW
L. 616mm



LED RGBW / 17W 4Ch / SPOT



		H(m)	D(m)	Emax(lx)
-			11°	
Fixture Power	20W	1	0.19	14937
Source Flux	860lm	2	0.38	3734
Fixture Flux	860lm	3	0.56	1660
Efficacy	43lm/W	4	0.75	934
TS1030 Imax=17366cd/klm	Imax 14937cd	5	0.94	597

Driver	Colour	Code
EL. DMX		**1E3112**

LED RGBW / 17W 4Ch / FLOOD



		H(m)	D1(m)	D2(m)	Emax(lx)
-			85°	29°	
Fixture Power	20W	1	1.82	0.52	656
Source Flux	632lm	2	3.65	1.04	164
Fixture Flux	632lm	3	5.47	1.56	73
Efficacy	32lm/W	4	7.29	2.08	41
TS1033 Imax=1038cd/klm	Imax 656cd	5	9.11	2.60	26

Driver	Colour	Code
EL. DMX		**1E3113**

LED RGBW / 17W 4Ch / WALL WASHER



		H(m)	D1(m)	D2(m)	Emax(lx)
-			115°	55°	
Fixture Power	20W	1	3.17	1.18	669
Source Flux	675lm	2	6.33	2.36	167
Fixture Flux	675lm	3	9.50	3.55	74
Efficacy	34lm/W	4	12.67	4.73	42
TS1036 Imax=1163cd/klm	Imax 786cd	5	15.83	5.91	27

Driver	Colour	Code
EL. DMX		**1E3114**

LED RGBW / 17W 4Ch / GRAZING



		H(m)	D1(m)	D2(m)	Emax(lx)
-			73°	11°	
Fixture Power	20W	1	1.48	0.19	1665
Source Flux	740lm	2	2.97	0.38	416
Fixture Flux	740lm	3	4.45	0.57	185
Efficacy	37lm/W	4	5.94	0.76	104
TS1029 Imax=2250cd/klm	Imax 1665cd	5	7.42	0.96	67

Driver	Colour	Code
EL. DMX		**1E3111**

JEDI

Projector RGBW
L. 916mm



LED RGBW / 26W 4Ch / SPOT



		H(m)	D(m)	Emax(lx)
-			11°	
Fixture Power	31W	1	0.19	22404
Source Flux	1290lm	2	0.38	5601
Fixture Flux	1290lm	3	0.56	2489
Efficacy	42lm/W	4	0.75	1400
TS1031 Imax=17366cd/klm	Imax 22404cd	5	0.94	896

Driver	Colour	Code
EL. DMX		**1E3116**

LED RGBW / 26W 4Ch / FLOOD



		H(m)	D1(m)	D2(m)	Emax(lx)
-			85°	29°	
Fixture Power	31W	1	1.82	0.52	984
Source Flux	949lm	2	3.65	1.04	246
Fixture Flux	949lm	3	5.47	1.56	109
Efficacy	31lm/W	4	7.29	2.08	62
TS1034 Imax=1038cd/klm	Imax 984cd	5	9.11	2.60	39

Driver	Colour	Code
EL. DMX		**1E3117**

LED RGBW / 26W 4Ch / WALL WASHER



		H(m)	D1(m)	D2(m)	Emax(lx)
-			115°	55°	
Fixture Power	31W	1	3.17	1.18	1004
Source Flux	1013lm	2	6.33	2.36	251
Fixture Flux	1013lm	3	9.50	3.55	112
Efficacy	33lm/W	4	12.67	4.73	63
TS1037 Imax=1163cd/klm	Imax 1179cd	5	15.83	5.91	40

Driver	Colour	Code
EL. DMX		**1E3118**

LED RGBW / 26W 4Ch / GRAZING



		H(m)	D1(m)	D2(m)	Emax(lx)
-			73°	11°	
Fixture Power	31W	1	1.48	0.19	2498
Source Flux	1110lm	2	2.97	0.38	624
Fixture Flux	1110lm	3	4.45	0.57	278
Efficacy	36lm/W	4	5.94	0.76	156
TS1028 Imax=2250cd/klm	Imax 2498cd	5	7.42	0.96	100

Driver	Colour	Code
EL. DMX		**1E3115**

JEDI

Projector RGBW
L. 1216mm



LED RGBW / 34W 4Ch / SPOT



		H(m)	D(m)	Emax(lx)
-			11°	
Fixture Power	41W	1	0.19	29872
Source Flux	1720lm	2	0.38	7468
Fixture Flux	1720lm	3	0.56	3319
Efficacy	42lm/W	4	0.75	1867
TS1032 Imax=17366cd/klm	Imax 29872cd	5	0.94	1195

Driver	Colour	Code
EL. DMX		**1E3120**

LED RGBW / 34W 4Ch / FLOOD



		H(m)	D1(m)	D2(m)	Emax(lx)
-			85°	29°	
Fixture Power	41W	1	1.82	0.52	1313
Source Flux	1265lm	2	3.65	1.04	328
Fixture Flux	1265lm	3	5.47	1.56	146
Efficacy	31lm/W	4	7.29	2.08	82
TS1035 Imax=1038cd/klm	Imax 1313cd	5	9.11	2.60	53

Driver	Colour	Code
EL. DMX		**1E3121**

LED RGBW / 34W 4Ch / WALL WASHER



		H(m)	D1(m)	D2(m)	Emax(lx)
-			115°	55°	
Fixture Power	41W	1	3.17	1.18	1338
Source Flux	1351lm	2	6.33	2.36	335
Fixture Flux	1351lm	3	9.50	3.55	149
Efficacy	33lm/W	4	12.67	4.73	84
TS1038 Imax=1163cd/klm	Imax 1572cd	5	15.83	5.91	54

Driver	Colour	Code
EL. DMX		**1E3122**

LED RGBW / 34W 4Ch / GRAZING



		H(m)	D1(m)	D2(m)	Emax(lx)
-			73°	11°	
Fixture Power	41W	1	1.48	0.19	3330
Source Flux	1480lm	2	2.97	0.38	833
Fixture Flux	1480lm	3	4.45	0.57	370
Efficacy	36lm/W	4	5.94	0.76	208
TS1027 Imax=2250cd/klm	Imax 3330cd	5	7.42	0.96	133

Driver	Colour	Code
EL. DMX		**1E3119**

Note

Photometrics show the maximum emission values of fixtures.

JEDI

Related codes

Mounting System



Code
1E2752

Short bracket for wall installation (2 pieces).



Code
1E2753

Long bracket for wall installation (2 pieces).



Code
1E2754

Bracket for ceiling installation (2 pieces).

Accessories

End Caps

Code
1E2761

End cap.

Cover Panel



L	Code
616	**1E3045**
916	**1E3046**
1216	**1E3047**

Side cover for ceiling installation.



L	Code
616	**1E2755**
916	**1E2756**
1216	**1E2757**

Side cover for wall/cornice installation.



L	Code
616	**1E2758**
916	**1E2759**
1216	**1E2760**

Anti-glare side cover.

JEDI

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E3184

IP68 4-way cable connector (5 pole).

Control systems

	Code
	1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the “RDM Targetti” software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

Università LUMSA
Rome, Italy

Architect Giuseppe Manara & Partners
Photographer Ivan Rossi

Engineer Maurizio Russo, Mario Di Paola
Electrical Engineer SIEC Srl

JEDI

Compact IP67

GENERAL INFO
Adjustable linear projector.
Lengths (remote driver):
312.5mm – 593.5mm –
873.5mm – 1153.5mm
Lengths (integrated driver):
576mm – 856mm –
1136mm

LED
Linear boards
Da 1431lm a 7200lm
2700K – 3000K – 3500K
– 4000K
Ra84

PRODUCT EFFICACY
Until 113lm/W

OPTICS
SP – FL – Grazing –
Wall Washer

With Louvre
FL - Grazing - Wall Washer

POWER SUPPLY
Electronic – DALI
Casambi control system
available as an accessory
(only for DALI versions).

MATERIAL
Extruded anodised
aluminium 15µ body. Extra
clear 5mm thick glass flat
screen.

ON DEMAND

Ra Ra90

110-277Vac
power supply

A compact, high performance linear LED fixture suitable for installation in small grooves or on particularly thin frames. Depending on the chosen optic it is suitable for general lighting in pedestrian areas, vaulted ceilings and vertical surfaces. Available also in a double version with an integrated or remote driver with an extremely thin profile of just 5x4 cm.

If equipped with special brackets the projector can be adjusted up to +/-90°.

The L. 300mm version is only available with a remote driver.

The versions with Flood, Grazing and Wall Washer optics can be ordered already equipped with an integrated Louvre grill.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Also available recessed version.

Catedral de Valledupar
Valledupar, Colombia

Architect Gustavo Vasquez

Photographer Sebastian Franco

Plus



A Compact size and adjustability

There are two profiles to choose from depending on the characteristics of the installation surface: with a remote driver where it is necessary to have a compact profile, or with an integrated driver when space permits and priority is given to connection speed. Furthermore, thanks to the special brackets that are available in two different lengths, the projector can be rotated from -90° to +90° with aim locking using an Allen key for maximum reliability in the installation phase.

B Anti-glare multiple effects

The two optical systems - hybrid and lenticular - make it possible to obtain four different luminous effects: grazing light with the grazing optic, soft and uniform light on high and wide surfaces with the wall washer optic and more concentrated effects with flood and spot optics.
The versions with Flood, Grazing and Wall Washer optics can be ordered already equipped with an integrated Louvre grill and longitudinal blades to control lateral emission and reduce the risk of glare.



JEDI COMPACT

IP67
Remote driver L. 312.5mm



LED / 12W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			11°	
Fixture Power		14W	1	0.20	19792
Source Flux		1554lm	2	0.40	4948
Fixture Flux		1288lm	3	0.59	2199
Efficacy		92lm/W	4	0.79	1237
TS1340	Imax=12736cd/klm	Imax	19792cd	5	0.99	792

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3807**	**1E3808**	**1E3809**	**1E3810**

LED / 12W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			85°	32°	
Fixture Power		14W	1	1.84	0.57	1203
Source Flux		1720lm	2	3.68	1.14	301
Fixture Flux		1285lm	3	5.52	1.70	134
Efficacy		92lm/W	4	7.36	2.27	75
TS1084	Imax=699cd/klm	Imax	1203cd	5	9.20	2.84	48

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3220**	**1E3221**	**1E3222**	**1E3223**

LED / 12W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	15°	
Fixture Power		14W	1	1.55	0.26	2752
Source Flux		1720lm	2	3.10	0.51	688
Fixture Flux		1429lm	3	4.65	0.77	306
Efficacy		102lm/W	4	6.21	1.02	172
TS1088	Imax=1600cd/klm	Imax	2752cd	5	7.76	1.28	110

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3224**	**1E3225**	**1E3226**	**1E3227**

LED / 12W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			115°	59°	
Fixture Power		14W	1	3.12	1.34	1156
Source Flux		1720lm	2	6.23	2.67	289
Fixture Flux		1293lm	3	9.35	4.01	128
Efficacy		92lm/W	4	12.47	5.35	72
TS1092	Imax=774cd/klm	Imax	1331cd	5	15.59	6.69	46

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3228**	**1E3229**	**1E3230**	**1E3231**

JEDI COMPACT

IP67
Remote driver L. 593.5mm



LED / 23W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	26W	1	0.20	39584
Source Flux	3108lm	2	0.40	9896
Fixture Flux	2575lm	3	0.59	4398
Efficacy	99lm/W	4	0.79	2474
TS1340 Imax=12736cd/klm	Imax	39584cd	5	0.99	1583

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3811**	**1E3812**	**1E3813**	**1E3814**

LED / 24W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	28W	1	1.84	0.57	2406
Source Flux	3440lm	2	3.68	1.14	601
Fixture Flux	2570lm	3	5.52	1.70	267
Efficacy	92lm/W	4	7.36	2.27	150
TS1084 Imax=699cd/klm	Imax	2406cd	5	9.20	2.84	96

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3232**	**1E3233**	**1E3234**	**1E3235**

LED / 24W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	28W	1	1.55	0.26	5505
Source Flux	3440lm	2	3.10	0.51	1376
Fixture Flux	2858lm	3	4.65	0.77	612
Efficacy	102lm/W	4	6.21	1.02	344
TS1088 Imax=1600cd/klm	Imax	5505cd	5	7.76	1.28	220

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3236**	**1E3237**	**1E3238**	**1E3239**

LED / 24W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	28W	1	3.12	1.34	2312
Source Flux	3440lm	2	6.23	2.67	578
Fixture Flux	2586lm	3	9.35	4.01	257
Efficacy	92lm/W	4	12.47	5.35	145
TS1092 Imax=774cd/klm	Imax	2661cd	5	15.59	6.69	92

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3240**	**1E3241**	**1E3242**	**1E3243**

JEDI COMPACT

IP67
Remote driver L. 873.5mm



LED / 35W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			11°	
Fixture Power		38W	1	0.20	59376
Source Flux		4662lm	2	0.40	14844
Fixture Flux		3863lm	3	0.59	6597
Efficacy		102lm/W	4	0.79	3711
TS1340	Imax=12736cd/klm	Imax	59376cd	5	0.99	2375

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3815**	**1E3816**	**1E3817**	**1E3818**

LED / 36W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			85°	32°	
Fixture Power		40W	1	1.84	0.57	3609
Source Flux		5160lm	2	3.68	1.14	902
Fixture Flux		3856lm	3	5.52	1.70	401
Efficacy		96lm/W	4	7.36	2.27	226
TS1085	Imax=699cd/klm	Imax	3609cd	5	9.20	2.84	144

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3244**	**1E3245**	**1E3246**	**1E3247**

LED / 36W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	15°	
Fixture Power		40W	1	1.55	0.26	8259
Source Flux		5160lm	2	3.10	0.51	2065
Fixture Flux		4288lm	3	4.65	0.77	918
Efficacy		107lm/W	4	6.21	1.02	516
TS1089	Imax=1601cd/klm	Imax	8259cd	5	7.76	1.28	330

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3248**	**1E3249**	**1E3250**	**1E3251**

LED / 36W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			115°	59°	
Fixture Power		40W	1	3.12	1.34	3469
Source Flux		5160lm	2	6.23	2.67	867
Fixture Flux		3880lm	3	9.35	4.01	385
Efficacy		97lm/W	4	12.47	5.35	217
TS1093	Imax=774cd/klm	Imax	3992cd	5	15.59	6.69	139

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3252**	**1E3253**	**1E3254**	**1E3255**

JEDI COMPACT

IP67
Remote driver L. 1153.5mm



LED / 46W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			11°	
Fixture Power		51W	1	0.20	79167
Source Flux		6216lm	2	0.40	19792
Fixture Flux		5151lm	3	0.59	8796
Efficacy		101lm/W	4	0.79	4948
TS1340	Imax=12736cd/klm	Imax	79167cd	5	0.99	3167

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3819**	**1E3820**	**1E3821**	**1E3822**

LED / 48W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			85°	32°	
Fixture Power		53W	1	1.84	0.57	4812
Source Flux		6880lm	2	3.68	1.14	1203
Fixture Flux		5141lm	3	5.52	1.70	535
Efficacy		97lm/W	4	7.36	2.27	301
TS1085	Imax=699cd/klm	Imax	4812cd	5	9.20	2.84	192

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3256**	**1E3257**	**1E3258**	**1E3259**

LED / 48W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	15°	
Fixture Power		53W	1	1.55	0.26	11012
Source Flux		6880lm	2	3.10	0.51	2753
Fixture Flux		5717lm	3	4.65	0.77	1224
Efficacy		108lm/W	4	6.21	1.02	688
TS1089	Imax=1601cd/klm	Imax	11012cd	5	7.76	1.28	440

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3260**	**1E3261**	**1E3262**	**1E3263**

LED / 48W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			115°	59°	
Fixture Power		53W	1	3.12	1.34	4625
Source Flux		6880lm	2	6.23	2.67	1156
Fixture Flux		5173lm	3	9.35	4.01	514
Efficacy		98lm/W	4	12.47	5.35	289
TS1093	Imax=774cd/klm	Imax	5323cd	5	15.59	6.69	185

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3264**	**1E3265**	**1E3266**	**1E3267**

JEDI COMPACT

IP67 Louvre
Remote driver L. 312.5mm



LED / 12W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	14W	1	1.86	0.52	873
Source Flux	1720lm	2	3.71	1.05	218
Fixture Flux	752lm	3	5.57	1.57	97
Efficacy	54lm/W	4	7.42	2.09	55
TS1086 Imax=508cd/klm	Imax 873cd	5	9.28	2.62	35

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3307**	**1E3308**	**1E3309**	**1E3310**

LED / 12W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	14W	1	1.68	0.23	1903
Source Flux	1720lm	2	3.36	0.46	476
Fixture Flux	912lm	3	5.04	0.68	211
Efficacy	65lm/W	4	6.72	0.91	119
TS1090 Imax=1106cd/klm	Imax 1903cd	5	8.40	1.14	76

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3311**	**1E3312**	**1E3313**	**1E3314**

LED / 12W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	14W	1	3.17	1.49	960
Source Flux	1720lm	2	6.35	2.97	240
Fixture Flux	975lm	3	9.52	4.46	107
Efficacy	70lm/W	4	12.70	5.95	60
TS1094 Imax=671cd/klm	Imax 1153cd	5	15.87	7.43	38

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3315**	**1E3316**	**1E3317**	**1E3318**

IP67 Louvre
Remote driver L. 593.5mm



LED / 24W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	28W	1	1.86	0.52	1747
Source Flux	3440lm	2	3.71	1.05	437
Fixture Flux	1503lm	3	5.57	1.57	194
Efficacy	54lm/W	4	7.42	2.09	109
TS1086 Imax=508cd/klm	Imax 1747cd	5	9.28	2.62	70

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3319**	**1E3320**	**1E3321**	**1E3322**

JEDI COMPACT

LED / 24W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			80°	13°	
Fixture Power	28W		1	1.68	0.23	3805
Source Flux	3440lm		2	3.36	0.46	951
Fixture Flux	1824lm		3	5.04	0.68	423
Efficacy	65lm/W		4	6.72	0.91	238
TS1090	Imax=1106cd/klm	Imax	5	8.40	1.14	152

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3323**	**1E3324**	**1E3325**	**1E3326**

LED / 24W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			116°	62°	
Fixture Power	28W		1	3.17	1.49	1919
Source Flux	3440lm		2	6.35	2.97	480
Fixture Flux	1950lm		3	9.52	4.46	213
Efficacy	70lm/W		4	12.70	5.95	120
TS1094	Imax=671cd/klm	Imax	5	15.87	7.43	77

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3327**	**1E3328**	**1E3329**	**1E3330**

IP67 Louvre
Remote driver L. 873.5mm



LED / 36W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			86°	29°	
Fixture Power	40W		1	1.86	0.52	2620
Source Flux	5160lm		2	3.71	1.05	655
Fixture Flux	2255lm		3	5.57	1.57	291
Efficacy	56lm/W		4	7.42	2.09	164
TS1087	Imax=508cd/klm	Imax	5	9.28	2.62	105

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3331**	**1E3332**	**1E3333**	**1E3334**

LED / 36W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			80°	13°	
Fixture Power	40W		1	1.68	0.23	5707
Source Flux	5160lm		2	3.36	0.46	1427
Fixture Flux	2735lm		3	5.04	0.68	634
Efficacy	68lm/W		4	6.72	0.91	357
TS1091	Imax=1106cd/klm	Imax	5	8.40	1.14	228

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3335**	**1E3336**	**1E3337**	**1E3338**

LED / 36W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			116°	62°	
Fixture Power	40W		1	3.17	1.49	2879
Source Flux	5160lm		2	6.35	2.97	720
Fixture Flux	2926lm		3	9.52	4.46	320
Efficacy	73lm/W		4	12.70	5.95	180
TS1095	Imax=671cd/klm	Imax	5	15.87	7.43	115

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3339**	**1E3340**	**1E3341**	**1E3342**

JEDI COMPACT

IP67 Louvre
Remote driver L. 1153.5mm



LED / 48W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	53W	1	1.86	0.52	3494
Source Flux	6880lm	2	3.71	1.05	873
Fixture Flux	3007lm	3	5.57	1.57	388
Efficacy	57lm/W	4	7.42	2.09	218
TS1087 Imax=508cd/klm	Imax 3494cd	5	9.28	2.62	140

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3343**	**1E3344**	**1E3345**	**1E3346**

LED / 48W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	53W	1	1.68	0.23	7609
Source Flux	6880lm	2	3.36	0.46	1902
Fixture Flux	3646lm	3	5.04	0.68	845
Efficacy	69lm/W	4	6.72	0.91	476
TS1091 Imax=1106cd/klm	Imax 7609cd	5	8.40	1.14	304

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3347**	**1E3348**	**1E3349**	**1E3350**

LED / 48W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	53W	1	3.17	1.49	3838
Source Flux	6880lm	2	6.35	2.97	960
Fixture Flux	3901lm	3	9.52	4.46	426
Efficacy	74lm/W	4	12.70	5.95	240
TS1095 Imax=671cd/klm	Imax 4613cd	5	15.87	7.43	154

Power supply	Colour	2700K	3000K	3500K	4000K
500mA		**1E3351**	**1E3352**	**1E3353**	**1E3354**

IP67
Integrated driver L. 576mm



LED / 23W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	26W	1	0.20	39584
Source Flux	3108lm	2	0.40	9896
Fixture Flux	2575lm	3	0.59	4398
Efficacy	99lm/W	4	0.79	2474
TS1340 Imax=12736cd/klm	Imax 39584cd	5	0.99	1583

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3823EL**	**1E3824EL**	**1E3825EL**	**1E3826EL**
DALI		**1E3823DA**	**1E3824DA**	**1E3825DA**	**1E3826DA**

JEDI COMPACT

LED / 24W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			85°	32°	
Fixture Power	28W	1	1.84	0.57	2406	
Source Flux	3440lm	2	3.68	1.14	601	
Fixture Flux	2570lm	3	5.52	1.70	267	
Efficacy	92lm/W	4	7.36	2.27	150	
TS1084 Imax=699cd/klm	Imax	2406cd	5	9.20	2.84	96

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3268EL**	**1E3269EL**	**1E3270EL**	**1E3271EL**
DALI		**1E3268DA**	**1E3269DA**	**1E3270DA**	**1E3271DA**

LED / 24W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	15°	
Fixture Power	28W	1	1.55	0.26	5505	
Source Flux	3440lm	2	3.10	0.51	1376	
Fixture Flux	2858lm	3	4.65	0.77	612	
Efficacy	102lm/W	4	6.21	1.02	344	
TS1088 Imax=1600cd/klm	Imax	5505cd	5	7.76	1.28	220

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3272EL**	**1E3273EL**	**1E3274EL**	**1E3275EL**
DALI		**1E3272DA**	**1E3273DA**	**1E3274DA**	**1E3275DA**

LED / 24W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			115°	59°	
Fixture Power	28W	1	3.12	1.34	2312	
Source Flux	3440lm	2	6.23	2.67	578	
Fixture Flux	2586lm	3	9.35	4.01	257	
Efficacy	92lm/W	4	12.47	5.35	145	
TS1092 Imax=774cd/klm	Imax	2661cd	5	15.59	6.69	92

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3276EL**	**1E3277EL**	**1E3278EL**	**1E3279EL**
DALI		**1E3276DA**	**1E3277DA**	**1E3278DA**	**1E3279DA**

IP67
Integrated driver L. 856mm



LED / 35W / SPOT



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			11°	
Fixture Power	38W	1	0.20	59376	
Source Flux	4662lm	2	0.40	14844	
Fixture Flux	3863lm	3	0.59	6597	
Efficacy	102lm/W	4	0.79	3711	
TS1340 Imax=12736cd/klm	Imax	59376cd	5	0.99	2375

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3827EL**	**1E3828EL**	**1E3829EL**	**1E3830EL**
DALI		**1E3827DA**	**1E3828DA**	**1E3829DA**	**1E3830DA**

LED / 36W / FLOOD



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			85°	32°	
Fixture Power	40W	1	1.84	0.57	3609	
Source Flux	5160lm	2	3.68	1.14	902	
Fixture Flux	3856lm	3	5.52	1.70	401	
Efficacy	96lm/W	4	7.36	2.27	226	
TS1085 Imax=699cd/klm	Imax	3609cd	5	9.20	2.84	144

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3280EL**	**1E3281EL**	**1E3282EL**	**1E3283EL**
DALI		**1E3280DA**	**1E3281DA**	**1E3282DA**	**1E3283DA**

JEDI COMPACT

LED / 36W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	40W	1	1.55	0.26	8259
Source Flux	5160lm	2	3.10	0.51	2065
Fixture Flux	4288lm	3	4.65	0.77	918
Efficacy	107lm/W	4	6.21	1.02	516
TS1089 Imax=1601cd/klm	Imax 8259cd	5	7.76	1.28	330

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3284EL**	**1E3285EL**	**1E3286EL**	**1E3287EL**
DALI		**1E3284DA**	**1E3285DA**	**1E3286DA**	**1E3287DA**

LED / 36W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	40W	1	3.12	1.34	3469
Source Flux	5160lm	2	6.23	2.67	867
Fixture Flux	3880lm	3	9.35	4.01	385
Efficacy	97lm/W	4	12.47	5.35	217
TS1093 Imax=774cd/klm	Imax 3992cd	5	15.59	6.69	139

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3288EL**	**1E3289EL**	**1E3290EL**	**1E3291EL**
DALI		**1E3288DA**	**1E3289DA**	**1E3290DA**	**1E3291DA**

IP67
Integrated driver L. 1136mm



LED / 46W / SPOT



3000K		H(m)	D(m)	Emax(lx)
Ra84			11°	
Fixture Power	51W	1	0.20	79167
Source Flux	6216lm	2	0.40	19792
Fixture Flux	5151lm	3	0.59	8796
Efficacy	101lm/W	4	0.79	4948
TS1340 Imax=12736cd/klm	Imax 79167cd	5	0.99	3167

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3831EL**	**1E3832EL**	**1E3833EL**	**1E3834EL**
DALI		**1E3831DA**	**1E3832DA**	**1E3833DA**	**1E3834DA**

LED / 48W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			85°	32°	
Fixture Power	53W	1	1.84	0.57	4812
Source Flux	6880lm	2	3.68	1.14	1203
Fixture Flux	5141lm	3	5.52	1.70	535
Efficacy	97lm/W	4	7.36	2.27	301
TS1085 Imax=699cd/klm	Imax 4812cd	5	9.20	2.84	192

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3292EL**	**1E3293EL**	**1E3294EL**	**1E3295EL**
DALI		**1E3292DA**	**1E3293DA**	**1E3294DA**	**1E3295DA**

LED / 48W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			76°	15°	
Fixture Power	53W	1	1.55	0.26	11012
Source Flux	6880lm	2	3.10	0.51	2753
Fixture Flux	5717lm	3	4.65	0.77	1224
Efficacy	108lm/W	4	6.21	1.02	688
TS1089 Imax=1601cd/klm	Imax 11012cd	5	7.76	1.28	440

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3296EL**	**1E3297EL**	**1E3298EL**	**1E3299EL**
DALI		**1E3296DA**	**1E3297DA**	**1E3298DA**	**1E3299DA**

JEDI COMPACT

LED / 48W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			115°	59°	
Fixture Power	53W	1	3.12	1.34	4625
Source Flux	6880lm	2	6.23	2.67	1156
Fixture Flux	5173lm	3	9.35	4.01	514
Efficacy	98lm/W	4	12.47	5.35	289
Imax	5323cd	5	15.59	6.69	185

TS1093 Imax=774cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3300EL**	**1E3301EL**	**1E3302EL**	**1E3303EL**
DALI		**1E3300DA**	**1E3301DA**	**1E3302DA**	**1E3303DA**

IP67 Louvre
Integrated driver L. 576mm



LED / 24W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	28W	1	1.86	0.52	1747
Source Flux	3440lm	2	3.71	1.05	437
Fixture Flux	1503lm	3	5.57	1.57	194
Efficacy	54lm/W	4	7.42	2.09	109
Imax	1747cd	5	9.28	2.62	70

TS1086 Imax=508cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3355EL**	**1E3356EL**	**1E3357EL**	**1E3358EL**
DALI		**1E3355DA**	**1E3356DA**	**1E3357DA**	**1E3358DA**

LED / 24W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	28W	1	1.68	0.23	3805
Source Flux	3440lm	2	3.36	0.46	951
Fixture Flux	1824lm	3	5.04	0.68	423
Efficacy	65lm/W	4	6.72	0.91	238
Imax	3805cd	5	8.40	1.14	152

TS1090 Imax=1106cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3359EL**	**1E3360EL**	**1E3361EL**	**1E3362EL**
DALI		**1E3359DA**	**1E3360DA**	**1E3361DA**	**1E3362DA**

LED / 24W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	28W	1	3.17	1.49	1919
Source Flux	3440lm	2	6.35	2.97	480
Fixture Flux	1950lm	3	9.52	4.46	213
Efficacy	70lm/W	4	12.70	5.95	120
Imax	2307cd	5	15.87	7.43	77

TS1094 Imax=671cd/klm

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3363EL**	**1E3364EL**	**1E3365EL**	**1E3366EL**
DALI		**1E3363DA**	**1E3364DA**	**1E3365DA**	**1E3366DA**

JEDI COMPACT

IP67 Louvre
Integrated driver L. 856mm



LED / 36W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	40W	1	1.86	0.52	2620
Source Flux	5160lm	2	3.71	1.05	655
Fixture Flux	2255lm	3	5.57	1.57	291
Efficacy	56lm/W	4	7.42	2.09	164
TS1087 Imax=508cd/klm	Imax 2620cd	5	9.28	2.62	105

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3367EL**	**1E3368EL**	**1E3369EL**	**1E3370EL**
DALI		**1E3367DA**	**1E3368DA**	**1E3369DA**	**1E3370DA**

LED / 36W / GRAZING



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			80°	13°	
Fixture Power	40W	1	1.68	0.23	5707
Source Flux	5160lm	2	3.36	0.46	1427
Fixture Flux	2735lm	3	5.04	0.68	634
Efficacy	68lm/W	4	6.72	0.91	357
TS1091 Imax=1106cd/klm	Imax 5707cd	5	8.40	1.14	228

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3371EL**	**1E3372EL**	**1E3373EL**	**1E3374EL**
DALI		**1E3371DA**	**1E3372DA**	**1E3373DA**	**1E3374DA**

LED / 36W / WALL WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			116°	62°	
Fixture Power	40W	1	3.17	1.49	2879
Source Flux	5160lm	2	6.35	2.97	720
Fixture Flux	2926lm	3	9.52	4.46	320
Efficacy	73lm/W	4	12.70	5.95	180
TS1095 Imax=671cd/klm	Imax 3460cd	5	15.87	7.43	115

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3375EL**	**1E3376EL**	**1E3377EL**	**1E3378EL**
DALI		**1E3375DA**	**1E3376DA**	**1E3377DA**	**1E3378DA**

IP67 Louvre
Integrated driver L. 1136mm



LED / 48W / FLOOD



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			86°	29°	
Fixture Power	53W	1	1.86	0.52	3494
Source Flux	6880lm	2	3.71	1.05	873
Fixture Flux	3007lm	3	5.57	1.57	388
Efficacy	57lm/W	4	7.42	2.09	218
TS1087 Imax=508cd/klm	Imax 3494cd	5	9.28	2.62	140

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3379EL**	**1E3380EL**	**1E3381EL**	**1E3382EL**
DALI		**1E3379DA**	**1E3380DA**	**1E3381DA**	**1E3382DA**

JEDI COMPACT

LED / 48W / GRAZING



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			80°	13°	
Fixture Power		53W	1	1.68	0.23	7609
Source Flux		6880lm	2	3.36	0.46	1902
Fixture Flux		3646lm	3	5.04	0.68	845
Efficacy		69lm/W	4	6.72	0.91	476
TS1091	Imax=1106cd/klm	Imax 7609cd	5	8.40	1.14	304

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3383EL**	**1E3384EL**	**1E3385EL**	**1E3386EL**
DALI		**1E3383DA**	**1E3384DA**	**1E3385DA**	**1E3386DA**

LED / 48W / WALL WASHER



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			116°	62°	
Fixture Power		53W	1	3.17	1.49	3838
Source Flux		6880lm	2	6.35	2.97	960
Fixture Flux		3901lm	3	9.52	4.46	426
Efficacy		74lm/W	4	12.70	5.95	240
TS1095	Imax=671cd/klm	Imax 4613cd	5	15.87	7.43	154

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3387EL**	**1E3388EL**	**1E3389EL**	**1E3390EL**
DALI		**1E3387DA**	**1E3388DA**	**1E3389DA**	**1E3390DA**

Related codes

Bracket



Code
1E3304

Stainless steel short bracket kit for surface installation (2 pieces).
Rotation +/-90°.



Code
1E3306

Stainless steel long bracket kit for surface installation (2 pieces).
Rotation +/-90°.

Power Supply

Code
1E3557

EL power supply version kit composed of an aluminium watertight box (LxHxP=270x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 3G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 312.5/344mm versions.

Code
1E3558

EL power supply version kit composed of an aluminium watertight box (LxHxP=486x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 3G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 593.5/625/873.5/905/1153.5/1185mm versions.

Code
1E3559

DALI power supply version kit composed of an aluminium watertight box (LxHxP=486x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 5G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 312.5/344/593.5/625mm versions.

Code
1E3560

DALI power supply version kit composed of an aluminium watertight box (LxHxP=486x49,5x44mm) complete with power supply input cable (1 metre, type H07RN8-F, 5G1mm^2) and an output cable to the fixture (1 metre, type H07RN8-F, 3G1mm^2).
For the L 873.5/905/1153.5/1185mm versions.

JEDI COMPACT

Accessories

Tool

	Code
	1E3305

(Tightening) wrench for the connector kit.

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

	Code
	1E3184

IP68 4-way cable connector (5 pole).

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

DART

GENERAL INFO
Professional adjustable projector
76x76 - 134x134 - 214x214

LED
Chip on board
Emitter for versions NSP Small e Medium
From 200lm to 8978lm
3000K – 4000K
Ra80 – Ra84

PRODUCT EFFICACY
Up to 110lm/W

OPTICS
NSP – SP – FL – MWFL for all versions.
WFL – ASYM for versions Medium e Maxi
NARROW ASYM for versions Medium

POWER SUPPLY
Electronic – DALI – 1-10V
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Painted die-cast anodised aluminium body and painted stainless steel mounting bracket.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

Cataphoresis treatment

A range of professional al projectors for outdoor architectural lighting, available in three different sizes-Small, Medium and Maxi; it has a compact and essential design that integrates into every architectural context.

Dart is extremely versatile thanks to the possibility to choose from different versions with different lumens and optics for accent lighting or uniform lighting of large surfaces. Also available with an asymmetrical optic.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

		SMALL	MEDIUM	MAXI
		76x76mm	134x134mm	214x214mm
LED	Flux (lm)	200-2087	1332-4628	3273-8978
	Power	3W - 14W	16W - 34W	26W - 80W
OPTICS				
NSP	Lens	•	•	
	Indirect			•
SP	Lens	•		
	Hybrid		•	•
FL	Lens	•		
	Hybrid		•	•
MWFL	Reflector	•	•	•
WFL	Reflector		•	•
ASYM	Reflector		•	•
NASYM	Reflector		•	

Abbaye de Maubuisson
Saint-Ouen l'Aumone, France

Architect YCA Yves Chemineau Architecte
Photographer Bruno Singer

Architect for the heritage
Valari Architecte Aristide Bravaccio

Plus

The large version in the Dart range

Is designed for architectural lighting of large surfaces and where it is essential to install fixtures at a distance.
Dart MAXI has the NSP optic to have clean, precise 6° beams. It works by reflection which means the lamp is hidden from sight and aimed towards the parabolic reflector which collimates the beam and emits a particularly defined, precise cone of light.

Dart medium is available with two asymmetrical optics

A more open version on the horizontal axis that makes it possible to widen the pitch between fixtures and a new version defined as Narrow Asymmetric that is more comfortable and controlled.

The MINI version is available with a remote power
Supply for installation in extremely confined spaces and with an integrated driver to simplify installation and accommodate cables on building facades.

Off-centre rotation to zoom
The body of the fixture towards and away from the support surface. Fitted with a graduated scale for precise aiming.



Ponte di Rialto
Venice, Italy

Photographer Ivan Rossi

DART



Maxi



LED / 26W / INDIRECT / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			6°	
	Fixture Power	28W	1	0.11	152341
	Source Flux	3273lm	2	0.22	38085
	Fixture Flux	2170lm	3	0.33	16927
	Efficacy	77lm/W	4	0.45	9521
TS1008	Imax=46545cd/klm	Imax	152341cd	5	0.56	6094

Driver	Colour	3000K	4000K
EL.		**1E3064EL**	**1E3070EL**
1-10V		**1E3064D**	**1E3070D**
DALI		**1E3064DA**	**1E3070DA**

LED / 34W / INDIRECT / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			6°	
	Fixture Power	37W	1	0.11	196977
	Source Flux	4232lm	2	0.22	49244
	Fixture Flux	2806lm	3	0.33	21886
	Efficacy	75lm/W	4	0.45	12311
TS1008	Imax=46545cd/klm	Imax	196977cd	5	0.56	7879

Driver	Colour	3000K	4000K
EL.		**1E3076EL**	**1E3082EL**
1-10V		**1E3076D**	**1E3082D**
DALI		**1E3076DA**	**1E3082DA**

LED / 51W / HYBRID / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			17°	
	Fixture Power	54W	1	0.30	34252
	Source Flux	6780lm	2	0.60	8563
	Fixture Flux	3634lm	3	0.89	3806
	Efficacy	67lm/W	4	1.19	2141
TS1009	Imax=5052cd/klm	Imax	34252cd	5	1.49	1370

Driver	Colour	3000K	4000K
EL.		**1E3065EL**	**1E3071EL**
1-10V		**1E3065D**	**1E3071D**
DALI		**1E3065DA**	**1E3071DA**

LED / 80W / HYBRID / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			17°	
	Fixture Power	88W	1	0.30	43451
	Source Flux	8601lm	2	0.60	10863
	Fixture Flux	4609lm	3	0.89	4828
	Efficacy	52lm/W	4	1.19	2716
TS1009	Imax=5052cd/klm	Imax	43451cd	5	1.49	1738

Driver	Colour	3000K	4000K
EL.		**1E3077EL**	**1E3083EL**
1-10V		**1E3077D**	**1E3083D**
DALI		**1E3077DA**	**1E3083DA**

LED / 51W / HYBRID / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			27°	
	Fixture Power	54W	1	0.47	19248
	Source Flux	6780lm	2	0.94	4812
	Fixture Flux	4081lm	3	1.42	2139
	Efficacy	75lm/W	4	1.89	1203
TS1010	Imax=2839cd/klm	Imax	19248cd	5	2.36	770

Driver	Colour	3000K	4000K
EL.		**1E3066EL**	**1E3072EL**
1-10V		**1E3066D**	**1E3072D**
DALI		**1E3066DA**	**1E3072DA**

DART

LED / 80W / HYBRID / FL



3000K		H(m)	D(m)	Emax(lx)
Ra84			27°	
Fixture Power	88W	1	0.47	24418
Source Flux	8601lm	2	0.94	6104
Fixture Flux	5177lm	3	1.42	2713
Efficacy	59lm/W	4	1.89	1526
TS1010 Imax=2839cd/klm	Imax	5	2.36	977

Driver	Colour	3000K	4000K
EL.		**1E3078EL**	**1E3084EL**
1-10V		**1E3078D**	**1E3084D**
DALI		**1E3078DA**	**1E3084DA**

LED / 51W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			38°	
Fixture Power	54W	1	0.69	8952
Source Flux	6780lm	2	1.38	2238
Fixture Flux	5227lm	3	2.07	995
Efficacy	96lm/W	4	2.76	560
TS1011 Imax=1333cd/klm	Imax	5	3.44	358

Driver	Colour	3000K	4000K
EL.		**1E3067EL**	**1E3073EL**
1-10V		**1E3067D**	**1E3073D**
DALI		**1E3067DA**	**1E3073DA**

LED / 80W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			38°	
Fixture Power	88W	1	0.69	11357
Source Flux	8601lm	2	1.38	2839
Fixture Flux	6631lm	3	2.07	1262
Efficacy	75lm/W	4	2.76	710
TS1011 Imax=1333cd/klm	Imax	5	3.44	454

Driver	Colour	3000K	4000K
EL.		**1E3079EL**	**1E3085EL**
1-10V		**1E3079D**	**1E3085D**
DALI		**1E3079DA**	**1E3085DA**

LED / 51W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			52°	
Fixture Power	54W	1	0.97	6549
Source Flux	6780lm	2	1.94	1637
Fixture Flux	5213lm	3	2.91	728
Efficacy	96lm/W	4	3.88	409
TS1012 Imax=966cd/klm	Imax	5	4.85	262

Driver	Colour	3000K	4000K
EL.		**1E3068EL**	**1E3074EL**
1-10V		**1E3068D**	**1E3074D**
DALI		**1E3068DA**	**1E3074DA**

LED / 80W / REFLECTOR / WFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			52°	
Fixture Power	88W	1	0.97	8308
Source Flux	8601lm	2	1.94	2077
Fixture Flux	6614lm	3	2.91	923
Efficacy	75lm/W	4	3.88	519
TS1012 Imax=966cd/klm	Imax	5	4.85	332

Driver	Colour	3000K	4000K
EL.		**1E3080EL**	**1E3086EL**
1-10V		**1E3080D**	**1E3086D**
DALI		**1E3080DA**	**1E3086DA**

LED / 51W / ASYM



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			89°	76°	
Fixture Power	54W	1	1.96	3.41	2831
Source Flux	6780lm	2	3.93	6.83	708
Fixture Flux	5827lm	3	5.89	10.24	315
Efficacy	107lm/W	4	7.86	13.66	177
TS1013 Imax=895cd/klm	Imax	5	9.82	17.07	113

Driver	Colour	3000K	4000K
EL.		**1E3069EL**	**1E3075EL**
1-10V		**1E3069D**	**1E3075D**
DALI		**1E3069DA**	**1E3075DA**

DART

LED / 80W / ASYM



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			89°	76°	
Fixture Power	88W	1	1.96	3.41	3591
Source Flux	8601lm	2	3.93	6.83	898
Fixture Flux	7391lm	3	5.89	10.24	399
Efficacy	84lm/W	4	7.86	13.66	224
TS1013 Imax=895cd/klm	Imax 7700cd	5	9.82	17.07	144

Driver	Colour	3000K	4000K
EL.		**1E3081EL**	**1E3087EL**
1-10V		**1E3081D**	**1E3087D**
DALI		**1E3081DA**	**1E3087DA**

Note

1 (1E2769) connector necessary for electronic and DALI versions. 2 (1E2769) connectors necessary for the 1-10V version.

Accessories

Filter



Code
1E3094

Blade of light filter.
PMMA holographic filter for a blade of light effect.
To be completed with a dedicated holder ring.
Diameter 168mm.

Grid



Code
1E3096

Anti-glare louver.
The central elements may be removed to obtain two different levels of glare control.
Powder coated stainless steel.
Ferrite/matte black.

Screen



Code
1E3095

Asymmetric screen.
Powder coated stainless steel.
Ferrite.

Mounting System



Code
1E3026

Plate for fixture rotation.
Powder coated stainless steel.
Ferrite.

Ø	H	Code
96	182	**1E3028**
150	352	**1E3188**

Earthspike.
Powder coated stainless steel.
Ferrite.

DART



Code

1E2825

Pole bracket.
Anodised and powder coated aluminium.
Pole Ø 60mm (+/-2mm).



Code

1E3097

Pole multiple mounting system.
Powder coated stainless steel.
To be completed with 1E2825.
Max 4 projectors.





Code

1E3187

Pole with base.
Powder coated stainless steel.

Holder Ring



Code

1E3093

Holder ring.
Powder coated stainless steel.
AxB 195x195mm.

Tool

Code

1E3098

Laser pointing system.
Installed by friction on the projector's body.
Powder coated stainless steel.
Laser included.

Connector

Code

1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code

1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems

Code

1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code

1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

DART

Medium



LED / 16W / LENS / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			10°	
Fixture Power		19W	1	0.17	24179
Source Flux		1332lm	2	0.34	6045
Fixture Flux		1008lm	3	0.51	2687
Efficacy		53lm/W	4	0.68	1511
TS941	Imax=18153cd/klm	Imax	5	0.86	967

Driver	Colour	3000K	4000K
EL.		**1E2994EL**	**1E2995EL**
1-10V		**1E2994D**	**1E2995D**
DALI		**1E2994DA**	**1E2995DA**

LED / 34W / HYBRID / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			13°	
Fixture Power		37W	1	0.23	38850
Source Flux		4428lm	2	0.46	9712
Fixture Flux		2738lm	3	0.69	4317
Efficacy		74lm/W	4	0.92	2428
TS942	Imax=8774cd/klm	Imax	5	1.14	1554

Driver	Colour	3000K	4000K
EL.		**1E2996EL**	**1E2997EL**
1-10V		**1E2996D**	**1E2997D**
DALI		**1E2996DA**	**1E2997DA**

LED / 34W / HYBRID / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			33°	
Fixture Power		37W	1	0.58	9385
Source Flux		4428lm	2	1.17	2346
Fixture Flux		2570lm	3	1.75	1043
Efficacy		69lm/W	4	2.33	587
TS943	Imax=2119cd/klm	Imax	5	2.92	375

Driver	Colour	3000K	4000K
EL.		**1E2998EL**	**1E2999EL**
1-10V		**1E2998D**	**1E2999D**
DALI		**1E2998DA**	**1E2999DA**

LED / 33W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			48°	
Fixture Power		36W	1	0.89	5843
Source Flux		4434lm	2	1.78	1461
Fixture Flux		3703lm	3	2.68	649
Efficacy		104lm/W	4	3.57	365
TS944	Imax=1366cd/klm	Imax	5	4.46	234

Driver	Colour	3000K	4000K
EL.		**1E3000EL**	**1E3001EL**
1-10V		**1E3000D**	**1E3001D**
DALI		**1E3000DA**	**1E3001DA**

LED / 33W / REFLECTOR / WFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			62°	
Fixture Power		36W	1	1.20	4420
Source Flux		4434lm	2	2.40	1105
Fixture Flux		3725lm	3	3.60	491
Efficacy		104lm/W	4	4.80	276
TS945	Imax=997cd/klm	Imax	5	5.99	177

Driver	Colour	3000K	4000K
EL.		**1E3002EL**	**1E3003EL**
1-10V		**1E3002D**	**1E3003D**
DALI		**1E3002DA**	**1E3003DA**

DART

LED / 33W / ASYM



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			113°	91°	
Fixture Power	36W	1	3.02	4.08	1190
Source Flux	4434lm	2	6.04	8.15	298
Fixture Flux	3151lm	3	9.06	12.23	132
Efficacy	88lm/W	4	12.08	16.30	74
TS946 Imax=504cd/klm	Imax 2236cd	5	15.10	20.38	48

Driver	Colour	3000K	4000K
EL.		**1E3004EL**	**1E3005EL**
1-10V		**1E3004D**	**1E3005D**
DALI		**1E3004DA**	**1E3005DA**

LED / 33W / NARROW ASYM



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			41°	52°	
Fixture Power	36W	1	1.20	1.25	2760
Source Flux	4514lm	2	2.41	2.49	690
Fixture Flux	3497lm	3	3.61	3.74	307
Efficacy	98lm/W	4	4.81	4.99	172
TS1054 Imax=1098cd/klm	Imax 4956cd	5	6.02	6.24	110

Driver	Colour	3000K	4000K
EL.		**1E3126EL**	**1E3127EL**
1-10V		**1E3126D**	**1E3127D**
DALI		**1E3126DA**	**1E3127DA**

Note

1 (1E2769) connector necessary for electronic and DALI versions. 2 (1E2769) connectors necessary for the 1-10V version.

Accessories

Filter



Filter	Ø	Code
Red	101	**1E3017**
Green	101	**1E3018**
Blue	101	**1E3019**
Yellow	101	**1E3020**
Magenta	101	**1E3021**

Chromatic filter.
Glass with dichroic treatment.
Non suitable for the asymmetric reflector nor for grazing lighting.
To be completed with a dedicated holder ring.



Code
1E3023

Blade of light filter.
PMMA holographic filter for a blade of light effect.
To be completed with a dedicated holder ring.
Diameter 101mm.

Grid



Code
1E3025

Anti-glare louver.
The central elements may be removed to obtain two different levels of glare control.
Powder coated stainless steel.
Ferrite/matte black.

Screen



Code
1E3024

Asymmetric screen.
Powder coated stainless steel.
Ferrite.

DART

Mounting System



Code
1E3026

Plate for fixture rotation.
Powder coated stainless steel.
Ferrite.

Ø	H	Code
96	182	**1E3028**

Earthspike.
Powder coated stainless steel.
Ferrite.



Code
1E2825

Pole bracket.
Anodised and powder coated aluminium.
Pole Ø 60mm (+/-2mm).



Code
1E3027

Pole multiple mounting system.
Powder coated stainless steel.
To be completed with 1E2825.
Max 4 projectors.

Holder Ring



Code
1E3022

Holder ring.
Powder coated stainless steel.
AxB 120x120mm.

Tool

Code
1E3029

Laser pointing system.
Installed by friction on the projector's body.
Powder coated stainless steel.
Laser included.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

DART

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

DART

Small Integrated driver



LED / 2,7W / LENS / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra80			9°	
Fixture Power	5W	1	0.15	4041
Source Flux	200lm	2	0.30	1010
Fixture Flux	151lm	3	0.46	449
Efficacy	29lm/W	4	0.61	253
Imax	4041cd	5	0.76	162

TS937 Imax=20203cd/klm

Driver	Colour	3000K	4000K
EL.		**1E3056EL**	**1E3057EL**

LED / 11W / LENS / SP



3000K		H(m)	D(m)	Emax(lx)
Ra84			17°	
Fixture Power	15W	1	0.30	10469
Source Flux	1786lm	2	0.61	2617
Fixture Flux	1258lm	3	0.91	1163
Efficacy	85lm/W	4	1.21	654
Imax	10469cd	5	1.52	419

TS938 Imax=5862cd/klm

Driver	Colour	3000K	4000K
EL.		**1E3058EL**	**1E3059EL**

LED / 12W / LENS / FL



3000K		H(m)	D(m)	Emax(lx)
Ra84			32°	
Fixture Power	14W	1	0.58	3645
Source Flux	1821lm	2	1.15	911
Fixture Flux	1231lm	3	1.73	405
Efficacy	91lm/W	4	2.31	228
Imax	3645cd	5	2.88	146

TS939 Imax=2002cd/klm

Driver	Colour	3000K	4000K
EL.		**1E3060EL**	**1E3061EL**

LED / 12W / REFLECTOR / MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra84			46°	
Fixture Power	14W	1	0.85	2586
Source Flux	1821lm	2	1.70	647
Fixture Flux	1435lm	3	2.54	287
Efficacy	106lm/W	4	3.39	162
Imax	2588cd	5	4.24	103

TS940 Imax=1421cd/klm

Driver	Colour	3000K	4000K
EL.		**1E3062EL**	**1E3063EL**

DART

Small Remote driver



LED / 2,7W / LENS / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		5W	1	0.15	4041
Source Flux		200lm	2	0.30	1010
Fixture Flux		151lm	3	0.46	449
Efficacy		29lm/W	4	0.61	253
TS937	Imax=20203cd/klm	Imax	4041cd	5	0.76	162

Power supply	Colour	3000K	4000K
900mA		**1E2986**	**1E2987**

LED / 13W / LENS / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			17°	
Fixture Power		17W	1	0.30	10569
Source Flux		1803lm	2	0.61	2642
Fixture Flux		1270lm	3	0.91	1174
Efficacy		75lm/W	4	1.21	661
TS938	Imax=5862cd/klm	Imax	10569cd	5	1.52	423

Power supply	Colour	3000K	4000K
400mA		**1E2988**	**1E2989**

LED / 14W / LENS / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			32°	
Fixture Power		15W	1	0.58	4071
Source Flux		2034lm	2	1.15	1018
Fixture Flux		1375lm	3	1.73	452
Efficacy		89lm/W	4	2.31	254
TS939	Imax=2002cd/klm	Imax	4071cd	5	2.88	163

Power supply	Colour	3000K	4000K
400mA		**1E2990**	**1E2991**

LED / 14W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			46°	
Fixture Power		15W	1	0.85	2889
Source Flux		2034lm	2	1.70	722
Fixture Flux		1603lm	3	2.54	321
Efficacy		104lm/W	4	3.39	181
TS940	Imax=1421cd/klm	Imax	2891cd	5	4.24	116

Power supply	Colour	3000K	4000K
400mA		**1E2992**	**1E2993**

Note

Remote driver version: to be completed with an electronic or DALI driver.

DART

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output current	IP	Code
118x22x52	20W	220-240Vac	400mA	IP20	**1T4215EL**
110x22x52	20W	110-240Vac	900mA	IP20	**1T5295EL**
150x40x148	20W	220-240Vac	400mA	IP68	**1E3033EL**
150x40x148	20W	110-240Vac	900mA	IP68	**1E3034EL**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
118x22x52	20W	110-240Vac	400mA	IP20	**1T4215D**
118x22x52	20W	110-240Vac	900mA	IP20	**1T5295D**
150x40x148	20W	110-240Vac	400mA	IP68	**1E3033D**
150x40x148	20W	110-240Vac	900mA	IP68	**1E3034D**

1-10V power supply.



Dimensions LxHxP	W	Power supply	Output current	IP	Code
118x22x52	20W	110-240Vac	400mA	IP20	**1T4215DA**
120x30x50	20W	110-240Vac	400mA	IP68	**1E3033DA**
150x40x148	max 50W	220-240Vac	900mA	IP68	**1E2574**

DALI power supply.

Accessories

Filter



	Filter	Ø	Code
	Red	53	**1E3006**
	Green	53	**1E3007**
	Blue	53	**1E3008**
	Yellow	53	**1E3009**
	Magenta	53	**1E3010**

Chromatic filter.
Glass with dichroic treatment.
Non suitable for the asymmetric reflector nor for grazing lighting.
To be completed with a dedicated holder ring.



	Ø	Code
	53	**1E3012**

Blade of light filter.
PMMA holographic filter for a blade of light effect.
To be completed with a dedicated holder ring.

Grid



	Code
	1E3014

Anti-glare louver.
The central elements may be removed to obtain two different levels of glare control.
Powder coated stainless steel.
Ferrite/matte black.

Screen



	Code
	1E3013

Asymmetric screen.
Powder coated stainless steel.
Ferrite.

DART

Mounting System



Code
1E3015

Plate for fixture rotation.
Powder coated stainless steel.
Ferrite.

Ø	H	Code
70	182	**1E3016**

Earthspike.
Powder coated stainless steel.
Ferrite.

Holder Ring



L	Code
66	**1E3011**

Holder ring.
Powder coated stainless steel.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

PYROS

GENERAL INFO
Professional projector.
Pyros
ø186mm
Nano Pyros
ø107mm
Pico Pyros
ø50mm

LED
Chip on board
LED Emitter for version
Pico Pyros e RGBW
From 216lm to 9402lm
3000K – 4000K
Ra80 – Ra84

PRODUCT EFFICACY
Unitil 110lm/W

OPTICS
SP – FL – MWFL

POWER SUPPLY
Electronic

MATERIAL
Painted die-cast anodised aluminium body, brackets and joints.

ON DEMAND

Easy Custom Colour

110-277Vac power supply (Pyros Pyros RGBW Nano Pyros)

Cataphoresis treatment

A range that was designed for lighting building facades, accentuating trees and green elements and in all those contexts where precision must be combined with excellent performance.

The larger version is high performance making it suitable for lighting from long distances and large architectural structures. Where on the other hand it is required to light details the Nano and Pico versions provide optical solutions and different powers. Pyros shows the extent of its flexibility with its installation system that makes it possible to extend or contract it depending on requirements.

The Pyros and Nano Pyros versions are also available in RGBW and RGB versions.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Piazza Gae Aulenti
Milano, Italia

PYROS

L. 237mm



LED / 25W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		28W	1	0.17	48565
Source Flux		3655lm	2	0.35	12141
Fixture Flux		2938lm	3	0.52	5396
Efficacy		105lm/W	4	0.69	3035
TS640	Imax=13287cd/klm	Imax	5	0.87	1943

Driver	Colour	3000K	4000K
EL.		**1E2779**	**1E2780**

LED / 25W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			25°	
Fixture Power		28W	1	0.45	11885
Source Flux		3655lm	2	0.89	2971
Fixture Flux		2869lm	3	1.34	1321
Efficacy		102lm/W	4	1.79	743
TS641	Imax=3252cd/klm	Imax	5	2.23	475

Driver	Colour	3000K	4000K
EL.		**1E2781**	**1E2782**

LED / 39W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		42W	1	0.17	67087
Source Flux		5049lm	2	0.35	16772
Fixture Flux		4059lm	3	0.52	7454
Efficacy		98lm/W	4	0.69	4193
TS640	Imax=13287cd/klm	Imax	5	0.87	2683

Driver	Colour	3000K	4000K
EL.		**1E2783**	**1E2784**

LED / 39W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			25°	
Fixture Power		42W	1	0.45	16417
Source Flux		5049lm	2	0.89	4104
Fixture Flux		3963lm	3	1.34	1824
Efficacy		95lm/W	4	1.79	1026
TS641	Imax=3252cd/klm	Imax	5	2.23	657

Driver	Colour	3000K	4000K
EL.		**1E2785**	**1E2786**

LED / 50W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		55W	1	0.17	91495
Source Flux		6672lm	2	0.35	22874
Fixture Flux		5364lm	3	0.52	10166
Efficacy		98lm/W	4	0.70	5718
TS972	Imax=13713cd/klm	Imax	5	0.87	3660

Driver	Colour	3000K	4000K
EL.		**1E2978**	**1E2979**

PYROS

LED / 50W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			24°	
Fixture Power		55W	1	0.43	22191
Source Flux		6672lm	2	0.86	5548
Fixture Flux		5237lm	3	1.28	2466
Efficacy		95lm/W	4	1.71	1387
TS973	Imax=3326cd/klm	Imax	22191cd	5	2.14	888

Driver	Colour	3000K	4000K
EL.		**1E2980**	**1E2981**

L. 307mm



LED / 80W / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			10°	
Fixture Power		88W	1	0.17	123310
Source Flux		8992lm	2	0.35	30827
Fixture Flux		7230lm	3	0.52	13701
Efficacy		82lm/W	4	0.70	7707
TS972	Imax=13713cd/klm	Imax	123310cd	5	0.87	4932

Driver	Colour	3000K	4000K
EL.		**1E2982**	**1E2983**

LED / 80W / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			24°	
Fixture Power		88W	1	0.43	29908
Source Flux		8992lm	2	0.86	7477
Fixture Flux		7059lm	3	1.28	3323
Efficacy		80lm/W	4	1.71	1869
TS973	Imax=3326cd/klm	Imax	29908cd	5	2.14	1196

Driver	Colour	3000K	4000K
EL.		**1E2984**	**1E2985**

Note

All projector bodies must be completed with dedicated mounting brackets equipped with graduated metal rings on the bracket allowing 360° rotation on the horizontal axis and 180° on the vertical axis. Mechanical locking system to ensure aiming stability.

Related codes

Mounting System



Kg	Colour	Code
0.6		**1E2806**

Die-cast aluminium bracket with double joint to allow 180° rotation on the vertical plane.
Graduated metal ring located at the base of the bracket to allow 360° rotation on the horizontal plane. Mechanical locking system to ensure aiming stability.
Short version.



Kg	Colour	Code
1.3		**1E2807**

Die-cast aluminium bracket with double joint to allow 180° rotation on the vertical plane.
Graduated metal ring located at the base of the bracket to allow 360° rotation on the horizontal plane. Mechanical locking system to ensure aiming stability.
Complete with a connection joint.
Long version.

PYROS



Code
1E2825

Pole bracket.
Anodised and powder coated aluminium.
Pole Ø 60mm (+/-2mm).

Code
1E2826

Pole head for pole with external diameter 60mm (+/-2mm) and internal diameter > 40mm.

Accessories

Filter

Ø	Code
187	**1E2821**

"Blade of light" effect refractive filter.
The special linear incisions modify the light beam, enlarging it in a perpendicular direction to the incisions.
With very narrow beams it is possible to obtain precise "blades" of light for special effects.
Complete with ring.



Ø	Code
187	**1E2822**

"Soft beam" effect refractive filter.
The special linear incisions reduce the variance between the primary and secondary light beam, making it more uniform.
Complete with ring.

Ø	Code
187	**1E2820**

Frosted glass. Complete with ring.

Screen



Code
1E2823

Adjustable stainless steel asymmetric screen with 8 positions and 2 mounting screws.
Permits the shielding of the light beam with wide beam optics.

Ray Shade



Code
1E2824

Stainless steel barn door with fixed flaps, adjustable to 4 positions with 2 mounting screws.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

PYROS

RGBW short arm



LED RGBW / 35W / SP



			H(m)	D(m)	Emax(lx)
	-			19°	
	Fixture Power	43W	1	0.34	5855
	Source Flux	972lm	2	0.67	1464
	Fixture Flux	972lm	3	1.01	651
	Efficacy	23lm/W	4	1.34	366
TS1055	Imax=6025cd/klm	Imax	5	1.68	234

Driver	Colour	Code
EL. DMX		**1E3124**

LED RGBW / 35W / FL



			H(m)	D(m)	Emax(lx)
	-			37°	
	Fixture Power	43W	1	0.67	2353
	Source Flux	960lm	2	1.34	588
	Fixture Flux	960lm	3	2.00	261
	Efficacy	22lm/W	4	2.67	147
TS1056	Imax=2456cd/klm	Imax	5	3.34	94

Driver	Colour	Code
EL. DMX		**1E3173**

RGBW long arm



LED RGBW / 35W / SP



			H(m)	D(m)	Emax(lx)
	-			19°	
	Fixture Power	43W	1	0.34	5855
	Source Flux	972lm	2	0.67	1464
	Fixture Flux	972lm	3	1.01	651
	Efficacy	23lm/W	4	1.34	366
TS1055	Imax=6025cd/klm	Imax	5	1.68	234

Driver	Colour	Code
EL. DMX		**1E3125**

LED RGBW / 35W / FL



			H(m)	D(m)	Emax(lx)
	-			37°	
	Fixture Power	43W	1	0.67	2353
	Source Flux	960lm	2	1.34	588
	Fixture Flux	960lm	3	2.00	261
	Efficacy	22lm/W	4	2.67	147
TS1056	Imax=2456cd/klm	Imax	5	3.34	94

Driver	Colour	Code
EL. DMX		**1E3174**

Note

Photometrics show the maximum emission values of fixtures.

PYROS

Accessories

Screen



Code
1E2823

Adjustable stainless steel asymmetric screen with 8 positions and 2 mounting screws.
Permits the shielding of the light beam with wide beam optics.

Ray Shade



Code
1E2824

Stainless steel barn door with fixed flaps, adjustable to 4 positions with 2 mounting screws.

Mounting System



Code
1E2825

Pole bracket.
Anodised and powder coated aluminium.
Pole Ø 60mm (+/-2mm).

Code
1E2826

Pole head for pole with external diameter 60mm (+/-2mm) and internal diameter > 40mm.

Control systems

Code
1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the “RDM Targetti” software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.

Code
1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

Code
1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

PYROS

NANO PYROS



LED / 21W / HYBRID / SP



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			13°	
	Fixture Power	24W	1	0.23	25082
	Source Flux	2954lm	2	0.46	6271
	Fixture Flux	1768lm	3	0.69	2787
	Efficacy	73lm/W	4	0.92	1568
	Imax	25082cd	5	1.14	1003

	Driver	Colour	3000K	4000K
	EL.		**1E2827**	**1E2828**

LED / 21W / HYBRID / FL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			32°	
	Fixture Power	24W	1	0.58	6061
	Source Flux	2954lm	2	1.17	1515
	Fixture Flux	1656lm	3	1.75	673
	Efficacy	69lm/W	4	2.33	379
	Imax	6061cd	5	2.91	242

	Driver	Colour	3000K	4000K
	EL.		**1E2829**	**1E2830**

LED / 21W / REFLECTOR / MWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			45°	
	Fixture Power	24W	1	0.82	4830
	Source Flux	3153lm	2	1.64	1207
	Fixture Flux	2582lm	3	2.46	537
	Efficacy	107lm/W	4	3.28	302
	Imax	4917cd	5	4.10	193

	Driver	Colour	3000K	4000K
	EL.		**1E2831**	**1E2832**

Accessories

Filter

	Kg	Filter	Ø	Code
	0.4	Red	107	**1E2849**
	0.4	Green	107	**1E2850**
	0.4	Blue	107	**1E2851**
	0.4	Yellow	107	**1E2852**

Chromatic filter. Complete with ring.



	Kg	Ø	Code
	0.2	107	**1E2853**

"Blade of light" effect refractive filter.
The special linear incisions modify the light beam, enlarging it in a perpendicular direction to the incisions.
With very narrow beams it is possible to obtain precise "blades" of light.
Complete with ring.

PYROS



	Kg	Ø	Code
	0.2	107	**1E2854**

"Soft beam" effect refractive filter.
The special linear incisions reduce the variance between the primary and secondary light beam, making it more uniform.
Complete with ring.

Grid

	Code
	1E2766

Anti-glare louver.
Black painted metal honeycomb structure.
Designed to be housed inside the fixture.

Screen



	Code
	1E2855

Adjustable stainless steel asymmetric screen with 8 positions and 2 mounting screws.
Permits the shielding of the light beam with wide beam optics.
0.7Kg.

Ray Shade



	Code
	1E2856

Stainless steel barn door with fixed flaps, adjustable to 4 positions with 2 mounting screws.
0.4Kg.

Mounting System

	Kg	L	Code
	0.5	200	**1E2845**
	1.8	800	**1E2846**

Earthspike.

	Kg	L	Code
	0.7	232	**1E2847**
	2	832	**1E2848**

Spike with base for surface installation.
1E2847 - Short peg with base for surface mounting.
1E2848 - Long peg with base for surface mounting.

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

PYROS

NANO PYROS RGB



LED RGB / 20W / SP



-		H(m)	D(m)	Emax(lx)
-			15°	
Fixture Power	25W	1	0.26	1396
Source Flux	216lm	2	0.53	349
Fixture Flux	173lm	3	0.79	155
Efficacy	71lm/W	4	1.06	87
Imax	1396cd	5	1.32	56

Driver	Colour	Code
EL. DMX		**1E2833**

LED RGB / 20W / FL



-		H(m)	D(m)	Emax(lx)
-			24°	
Fixture Power	24W	1	0.42	800
Source Flux	239lm	2	0.84	200
Fixture Flux	187lm	3	1.26	89
Efficacy	8lm/W	4	1.68	50
Imax	800cd	5	2.10	32

Driver	Colour	Code
EL. DMX		**1E2834**

Note

Photometrics show the maximum emission values of fixtures.

Accessories

Grid

Code
1E2766

Anti-glare louver.
Black painted metal honeycomb structure.
Designed to be housed inside the fixture.

Screen



Code
1E2855

Adjustable stainless steel asymmetric screen with 8 positions and 2 mounting screws.
Permits the shielding of the light beam with wide beam optics.
0.7Kg.

Ray Shade



Code
1E2856

Stainless steel barn door with fixed flaps, adjustable to 4 positions with 2 mounting screws.
0.4Kg.

PYROS

Mounting System

	Kg	L	Code
	0.5	200	**1E2845**
	1.8	800	**1E2846**

Earthspike.

	Kg	L	Code
	0.7	232	**1E2847**
	2	832	**1E2848**

Spike with base for surface installation.
1E2847 - Short peg with base for surface mounting.
1E2848 - Long peg with base for surface mounting.

Cable

	Code
	1T1932

Standard DMX cable (1 twisted pair + shield, 120 Ohm).

Control systems

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

PYROS

PICO PYROS



LED / 8W / SP



	3000K	H(m)	D(m)	Emax(lx)
	Ra80		18°	
Fixture Power	11W	1	0.32	2253
Source Flux	501lm	2	0.65	563
Fixture Flux	408lm	3	0.97	250
Efficacy	39lm/W	4	1.29	141
Imax	2253cd	5	1.62	90

Driver	Colour	3000K	4000K
EL.		**1E2857**	**1E2859**

LED / 8W / FL



	3000K	H(m)	D(m)	Emax(lx)
	Ra80		36°	
Fixture Power	11W	1	0.65	656
Source Flux	501lm	2	1.30	164
Fixture Flux	361lm	3	1.95	73
Efficacy	34lm/W	4	2.60	41
Imax	656cd	5	3.25	26

Driver	Colour	3000K	4000K
EL.		**1E2858**	**1E2860**

Accessories

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

JUPITER

GENERAL INFO
Jupiter
Ultra compact adjustable projector
Ø38mm
Jupiter Pro
Professional adjustable LED projector
Ø40mm - Ø50mm

LED
Jupiter
Chip on board
From 157lm to 182lm
3000K – 4000K
Ra 90
Jupiter Pro
Jupiter Pro
LED Emitter
From 479lm to 1228lm
2700K – 3000K – 3500K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 77lm/W

OPTICS
Jupiter
SP – FL – WFL
Jupiter Pro
NSP (fixed optic)
SP15 - SP24 - FL - MWFL (multi-optic)

POWER SUPPLY
Jupiter
24V
Jupiter Pro
24V
Casambi control system available using a dedicated accessory (only with DALI dimmer).

MATERIAL
Jupiter
Anodised polished aluminium body. Aluminium front ring. Bevelled extra-clear front glass. Stainless steel bracket fixed to the body for adjustability.
Jupiter Pro
Frame and joint in aluminium with CNC machining, anodised and painted.

ON DEMAND
110-277Vac power supply (Jupiter)

Range of professional projectors. Ultra-compact and adjustable Jupiter projectors are equipped with a lenticular type optical system for precise and defined beams. Made completely of ferrite painted anodised aluminium they are characterised by an aluminium bracket which allows them to be adjusted on the both the vertical and horizontal planes.

Jupiter Pro projectors, available in two different sizes ø40mm and ø50mm, are equipped with a joint that allows them to be adjusted by ±360°on the horizontal plane and 180°on the vertical plane. The multi-optic system of Jupiter Pro projectors makes it possible to vary the width of the beam opening easily – from SP15 to SP24, FL, MWFL – according to needs, without affecting the IP protection rating of the fixtures.

The 24V power supply of Jupiter and Jupiter Pro means that it can even be used in humid environments like SPAs or near swimming pools. The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture. The Jupiter range is available in a recessed version.

Toyekunov Family Palace
Moscow, Russia

Lighting designer Tatyana Shkolnikova **Photographer** Ilya Kouzov

Jupiter

Jupiter is the most simple and compact version in the family, with a fixed, lenticular-type optic system for precise and defined beams.
It is entirely made of anodized aluminium painted ferrite complete with a steel bracket that allows it to be adjusted in respect to both the vertical and horizontal plane.

Jupiter Pro

Jupiter Pro is the most professional projector of the JUPITER range and is available in two different diameters Ø40 and Ø50 with fixed or multiple optics.

Now available with Ra90 LED.

Varied and flexible installation

Jupiter Pro is equipped with a universal mounting system and can be installed using any support equipped with a G ½ shank hole (Ø22mm). In the Targetti collection there are two different installation systems available as accessories: a spike for in-ground installation and a plate for wall or inground installation.

Plus



Maximum flexibility

The joint Jupiter Pro is equipped with makes it possible to adjust the projector ±360° on the horizontal plane and 180° on the vertical plane.

Three elements in a single projector

Jupiter Pro is made up of three elements:

- the base that can be attached to the floor or wall and then completed with the actual projector body;
- The central body, which is the heart of the system and physically isolated from the other elements with resin coating;
- The optical compartment that allows to vary the beam angle by replacing the different holographic filters.



Multi-optic versions

One of the primary features of Jupiter Pro is the ability to change the beam angle of the Multi-optic version. Without changing the IP rating, the holographic filter can be changed inside the optical compartment to obtain different beam angles. The product comes with additional holographic filters so they can be changed based on the project needs.

JUPITER

PRO



LED / 5,7W / LENS / NSP



3000K		H(m)	D(m)	Emax(lx)
Ra90			8°	
Fixture Power	8W	1	0.15	12587
Source Flux	520lm	2	0.30	3147
Fixture Flux	394lm	3	0.44	1399
Efficacy	51lm/W	4	0.59	787
Imax	12587cd	5	0.74	503

TS1404 Imax=24196cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
24Vdc		**1E377390**	**1E377490**	**1E377590**	**1E387790**
24Vdc		**1E377690**	**1E377790**	**1E377890**	**1E387890**

LED / 10,3W / LENS / SP (15°), SP (24°), FL, MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			15°	
Fixture Power	12W	1	0.27	7200
Source Flux	987lm	2	0.54	1800
Fixture Flux	738lm	3	0.81	800
Efficacy	62lm/W	4	1.08	450
Imax	7200cd	5	1.35	288

TS1405 Imax=7292cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra90			24°	
Fixture Power	12W	1	0.43	2846
Source Flux	987lm	2	0.85	712
Fixture Flux	698lm	3	1.28	316
Efficacy	58lm/W	4	1.71	178
Imax	2846cd	5	2.14	114

TS1406 Imax=2883cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra90			31°	
Fixture Power	12W	1	0.55	1892
Source Flux	987lm	2	1.09	473
Fixture Flux	704lm	3	1.64	210
Efficacy	59lm/W	4	2.18	118
Imax	1892cd	5	2.73	76

TS1407 Imax=1916cd/klm



3000K		H(m)	D(m)	Emax(lx)
Ra90			44°	
Fixture Power	12W	1	0.82	996
Source Flux	987lm	2	1.63	249
Fixture Flux	689lm	3	2.45	111
Efficacy	57lm/W	4	3.27	62
Imax	996cd	5	4.08	40

TS1408 Imax=1009cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
24Vdc		**1E377990**	**1E378090**	**1E378190**	**1E387990**
24Vdc		**1E378290**	**1E378390**	**1E378490**	**1E388090**

Note

Ra84: to order this version it is necessary to remove the suffix “90” at the end of the standard code.

Related codes

Mounting System

Ø	H	Colour	Code
50	182		**1E3785**
50	182		**1E3803**

Earthspike.
Powder coated stainless steel.



Colour	Code
	1E3786
	1E3804

Plate for fixture rotation (surface installation).
Powder coated stainless steel.

JUPITER

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Accessories

Filter

Filter	Ø	Code
Red	36	**1E3798**
Green	36	**1E3799**
Blue	36	**1E3800**
Yellow	36	**1E3801**
Magenta	36	**1E3802**

Chromatic filter.
Glass with dichroic treatment.

Code
1E3790

Blade of light filter.
PMMA holographic filter for a blade of light effect.
Diameter 36mm.

Grid

Code
1E3792

Anti-glare louver.
Black painted metal honeycomb structure.
Ready to be housed inside the optical compartment.
Diameter 36mm.

Screen

Colour	Code
	1E3788
	1E3806

Asymmetric screen.
Powder coated stainless steel.
Diameter 36mm.

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

JUPITER

Tool

	Code
(Tightening) wrench for the connector kit.	**1E3305**

Control systems



	Code
Dimmer for 12-24Vdc constant voltage LED driver. 1-10V/DALI control input. IP20	**1T6581**

	Code
A IP67 Module for individual control of external devices equipped with DALI drivers. The module needs to be positioned in order to receive radio signals. The distance to the lighting fixtures can reach up to 50m. Wireless control via the Casambi application. LxHxP=56.5x22.3x35.8mm.	**1E3048**

	Code
IP67 Extender for wireless control of DALI fixtures. It generates a local DALI bus with the capacity to drive up to 64 fixtures. Can control DALI fixtures in outdoor applications via the Casambi application. LxHxP=150x40x148mm.	**1E3049**

JUPITER

PRO Small



LED / 5,7W / LENS / SP, FL, MWFL



3000K		H(m)	D(m)	Emax(lx)
Ra90			11°	
Fixture Power	8W	1	0.19	7545
Source Flux	520lm	2	0.38	1886
Fixture Flux	380lm	3	0.57	838
Efficacy	49lm/W	4	0.75	472
Imax	7545cd	5	0.94	302



3000K		H(m)	D(m)	Emax(lx)
Ra90			20°	
Fixture Power	8W	1	0.36	1869
Source Flux	520lm	2	0.72	467
Fixture Flux	332lm	3	1.08	208
Efficacy	43lm/W	4	1.44	117
Imax	1869cd	5	1.80	75



3000K		H(m)	D(m)	Emax(lx)
Ra90			37°	
Fixture Power	8W	1	0.68	614
Source Flux	520lm	2	1.36	153
Fixture Flux	300lm	3	2.04	68
Efficacy	39lm/W	4	2.71	38
Imax	614cd	5	3.39	25

Power supply	Colour	2700K	3000K	3500K	4000K
24Vdc		**1E376790**	**1E376890**	**1E376990**	**1E387590**
24Vdc		**1E377090**	**1E377190**	**1E377290**	**1E387690**

Note

Ra84: to order this version it is necessary to remove the suffix “90” at the end of the standard code.

Related codes

Mounting System

Ø	H	Colour	Code
50	182		**1E3785**
50	182		**1E3803**

Earthspike.
Powder coated stainless steel.



Colour	Code
	1E3786
	1E3804

Plate for fixture rotation (surface installation).
Powder coated stainless steel.

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

JUPITER

Accessories

Filter

	Filter	Ø	Code
	Red	26	**1E3793**
	Green	26	**1E3794**
	Blue	26	**1E3795**
	Yellow	26	**1E3796**
	Magenta	26	**1E3797**

Chromatic filter.
Glass with dichroic treatment.

	Code
	1E3789

Blade of light filter.
PMMA holographic filter for a blade of light effect.
Diameter 26mm.

Grid

	Code
	1E3791

Anti-glare louver.
Black painted metal honeycomb structure.
Ready to be housed inside the optical compartment.
Diameter 26mm.

Screen

	Colour	Code
		1E3787
		1E3805

Asymmetric screen.
Powder coated stainless steel.
Diameter 26mm.

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Tool

	Code
	1E3305

(Tightening) wrench for the connector kit.

JUPITER

Control systems



Code
1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

JUPITER

Mini Projector



LED / 1,9W / SP (19°)



		3000K	H(m)	D(m)	Emax(lx)
		Ra90		19°	
	Fixture Power	3W	1	0.33	675
	Source Flux	170lm	2	0.65	169
	Fixture Flux	101lm	3	0.98	75
	Efficacy	37lm/W	4	1.31	42
TS1415	Imax=3977cd/klm	Imax	675cd	5	1.63	27

Power supply	Colour	3000K	4000K
24Vdc		**1E316790**	**1E316890**

LED / 1,9W / SP (24°)



		3000K	H(m)	D(m)	Emax(lx)
		Ra90		24°	
	Fixture Power	3W	1	0.42	417
	Source Flux	170lm	2	0.85	104
	Fixture Flux	95lm	3	1.27	46
	Efficacy	35lm/W	4	1.69	26
TS1416	Imax=2457cd/klm	Imax	417cd	5	2.11	17

Power supply	Colour	3000K	4000K
24Vdc		**1E316990**	**1E317090**

LED / 1,9W / FL



		3000K	H(m)	D(m)	Emax(lx)
		Ra90		32°	
	Fixture Power	3W	1	0.57	241
	Source Flux	170lm	2	1.15	60
	Fixture Flux	93lm	3	1.72	27
	Efficacy	34lm/W	4	2.30	15
TS1417	Imax=1421cd/klm	Imax	241cd	5	2.87	10

Power supply	Colour	3000K	4000K
24Vdc		**1E317190**	**1E317290**

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

JUPITER

Accessories

Mounting System

	L	Code
	110	**1E0995FE**

Ferrite painted stainless steel peg for ground anchorage.

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Control systems



	Code
	1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

LED.Y

GENERAL INFO
Adjustable on bracket projector
ø50mm

LED
Mono-led
LED emitter
3000K – 6000K
From 99lm to 143lm
Ra80
RGB: RGB LED Multichip
From 40lm to 48lm

PRODUCT EFFICACY
Until 47lm/W

OPTICS
Versions Mono-led
SP - FL

POWER SUPPLY
Electronic

MATERIAL
Anodised aluminium body and bracket. Vandalproof clear polycarbonate 40 joule shock resistant screen.

ON DEMAND
110-277Vac power supply

A series of miniature fixtures available in recessed or projector versions with monochromatic LED and RGB technology.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.



LED.Y



Projector



LED / 2W / SP



	3000K	H(m)	D(m)	Emax(lx)
	Ra80		9°	
Fixture Power	3W	1	0.16	2012
Source Flux	117lm	2	0.32	503
Fixture Flux	116lm	3	0.48	224
Efficacy	39lm/W	4	0.64	126
Imax	2012cd	5	0.80	80

Power supply	Colour	3000K	6000K
700mA		**1E2371**	**1E2372**

LED / 2W / FL



	3000K	H(m)	D(m)	Emax(lx)
	Ra80		34°	
Fixture Power	3W	1	0.60	223
Source Flux	99lm	2	1.21	56
Fixture Flux	99lm	3	1.81	25
Efficacy	33lm/W	4	2.42	14
Imax	223cd	5	3.02	9

Power supply	Colour	3000K	6000K
700mA		**1E2373**	**1E2374**

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output current	IP	Code
105x74	17/12W	220-240Vac/110-120Vac	700mA	IP68	**1E1385**

Electronic power supply.

Accessories

Mounting System

	L	Code
	110	**1E0995**

Peg for ground anchorage.
Stainless steel.

Accessories

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.



Projector RGB



LED RGB / 3,5W / SP



Power supply	Colour	RGB
3x350mA		**1E1855**

LED RGB / 3,5W / FL



Power supply	Colour	RGB
3x350mA		**1E1410**

Note

Photometrics show the maximum emission values of fixtures.

Related codes

Control systems

Code
1E1401

SECS 75.
IP67
Power supply and Control System SECS Scene Effect Control System.
SECS 75 drivers combine the following 3 functions in a single unit,: power supply to RGB LED devices, playback of pre-set colour sequences and a DMX interface for external control devices.
The SECS “Easy-Run-Menu” function is able to playback colour-changing light scenarios that are pre-stored into the driver without the use of an external driver: - 8 static colour scenarios; - 8 dynamic colour sequences; - 5 different playback speed values; - Start/Stop the selected scenario using a remote switch.
SECS 75 drivers can also be controlled through DMX 512; in this case: - DMX address (from 1 to 511) can be configured by using dip-switches; - 3 channel mode: all R-G-B outputs are controlled simultaneously by 3 DMX channels only; - 6 channel mode: the outputs are divided into 2 R-G-B groups, each one controlled by 3 different DMX channels; - DMX line termination: SECS drivers contain a 120Ohm resistance which can be activated using a dip-switch; - DMX output is available for connection to other DMX devices.
75W output.

Code
1T2245

SECS 36.
IP20
Power supply and Control System SECS Scene Effect Control System.
SECS 36 drivers combine the following 3 functions in a single unit,: power supply to RGB LED devices, playback of pre-set colour sequences and a DMX interface for external control devices.
The SECS “Easy-Run-Menu” function is able to playback colour-changing light scenarios that are pre-stored into the driver without the use of an external driver: - 8 static colour scenarios; - 8 dynamic colour sequences; - 5 different playback speed values; - Start/Stop the selected scenario using a remote switch.
SECS 75 drivers can also be controlled through DMX 512; in this case: - DMX address (from 1 to 511) can be configured by using dip-switches; - 3 channel mode: all R-G-B outputs are controlled simultaneously by 3 DMX channels only; - 6 channel mode: the outputs are divided into 2 R-G-B groups, each one controlled by 3 different DMX channels; - DMX line termination: SECS drivers contain a 120Ohm resistance which can be activated using a dip-switch; - DMX output is available for connection to other DMX devices.
35W output.

Accessories

Mounting System

	L	Code
	110	**1E0995**

Peg for ground anchorage.
Stainless steel.

Cable

	Code
	1E1713

6-pole cable for driver output connection to Constant Current LED sources.

Control systems

	Code
	1T1898

my-SCENARIO Show Store.
Digital devices designed to control dynamic lighting fixtures and programme dynamic light scenarios and sequences.
The system consists of intuitive software, compatible with Windows operating systems, able to control different hardware devices with the following functions: - record colour-changing scenarios set by the operator; - allow selection among the multiple scenarios already recorded; - transmit the control signals to the lighting system.
The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.
The software provides a graphic simulation of the operating keys of a lighting controller; the patching function allows the DMX control channels to be assigned to fixtures by using the internal library.
The Colour Manager function allows for quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times.
The built-in calendar allows full time scheduling of show playback (month, day, hour, minutes, recurring events).
The programmed light shows can be transferred to different control interfaces.

	Code
	1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
Power supply adapter and USB cable included.
To be used with all RGB and RGBW products.

Wall recessed

Outdoor

728
ZEDGE PRO

736
ZEDGE
Line



736
ZEDGE
Line Opal

742
ZEDGE

ZEDGE

Family

The result of the collaboration with the architectural and design firm Gensler, the Zedge range is designed to light passage ways, stairwells and corridors with solutions with the same minimal and refined design characterised by a perfect play of proportions, inclined planes, and sharp and defined edges.

The range is available in three different sizes and with 24V and 220V integrated drivers. In addition to the first Zedge version - the extremely compact step-marker, - the range includes Zedge Line and Zedge Line Opal linear fixtures, the Zedge Pro floor washer - and the compact Zedge Bollard suitable for lighting small passage ways.



ZEDGE PRO

GENERAL INFO
Recessed wall mounted fixture, surface mounted and bollard.
Zedge PRO 200x200mm

LED
2 Chip on board
From 2022lm to2179lm
2700K - 3000K - 3500K - 4000K
Ra84

PRODUCT EFFICACY
Up to 50lm/W

OPTICS
Floor Washer deep
Floor Washer wide
Floor Washer adjustable

POWER SUPPLY
Electronic - DALI - 24V
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
The body of the fixture and the external frame are made of powder coated die-cast anodised aluminium.

ON DEMAND

Easy Custom Colour

Cataphoresis treatment

Ra90

110-277Vac power supply

The larger and high-performance fixture it is a real floor-washer with an innovative optical system and a design based on a perfect play of proportions, inclined planes, defined corners and sharp edges.
The finishing screen can be installed on the surface or flush with the wall for maximum formal simplicity.

Optical systems is made of two independent beams that can be configured in different ways to produce multiple effects: deep, wide plus all the effects in between with the innovative adjustable version.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Bollard and
Wall mounted versions

Thanks to the special accessories it is now possible to install Zedge Pro even in a Wall mounted and Bollard versions, available in three different heights 400 - 800 - 1000mm.



Adjustable Version

An innovative solution that makes it possible to obtain different light effects with the same fixture by calibrating the light beam to suit different project needs. Using an Allen key, it is possible to rotate the optical system changing from a DEEP effect to a WIDE effect fluidly, choosing the most suitable position for the project from among the myriad of intermediary positions.

Deep Version

For deep lighting of horizontal surfaces where the priority is to light large open spaces or very wide pathways.

Wide Version

For lighting that favours illuminance uniformity on the longitudinal axis such as long public or private pedestrian walkways.



ZEDGE

Pro



LED / 13W / DEEP



Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3192EL**	**1E3195EL**	**1E3760EL**	**1E3198EL**
DALI		**1E3192DA**	**1E3195DA**	**1E3760DA**	**1E3198DA**

LED / 13W / WIDE



Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3201EL**	**1E3204EL**	**1E3761EL**	**1E3207EL**
DALI		**1E3201DA**	**1E3204DA**	**1E3761DA**	**1E3207DA**

LED / 13W / ADJUSTABLE





Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3210EL**	**1E3213EL**	**1E3762EL**	**1E3216EL**
DALI		**1E3210DA**	**1E3213DA**	**1E3762DA**	**1E3216DA**

Related codes

Insertion Box





Code
1E3219

Nylon outer casing fitted for parallel connection with feed through-wiring.
AxBxH=207x207x114.5mm.
For flush or overlay installation.

Carter



Colour	Code
	1E3440

Plate accessory for wall mounted installation.
Powder coated anodised aluminium.
AxBxH=201x201x107mm.

ZEDGE

Bollard



	Kg	H	Colour	Code
	2.7	400		**1E3437**
	5.1	800		**1E3438**
	6.2	1000		**1E3439**

Powder coated anodised aluminium bollard.

Mounting System



	Code
	1E3450

Fixing rods for installation in concrete.
AISI 316 stainless steel.
For Zedge Pro Bollard installation (+1E3437, 1E3438, 1E3439).
For Zedge Bollard installation (+1E3741).
H=143mm.

Accessories

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Tool

	Code
	1E3305

(Tightening) wrench for the connector kit.

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

ZEDGE LINE AND ZEDGE LINE OPAL

GENERAL INFO
Recessed wall mounted fixture and surface mounted.
Zedge Line
63x304mm
Zedge Line Opal
63x304mm

LED
Linear boards
From 815lm to 1310lm
2700K - 3000K - 3500K - 4000K
Ra84

PRODUCT EFFICACY
Zedge Line
Up to 29lm/W
Zedge Line Opal
Up to 78lm/W

OPTICS
Zedge Line
Floor Washer
Zedge Line Opal
Opal

POWER SUPPLY
Electronic - DALI - 24V
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Zedge Line: Die-cast anodised aluminium body and external frame; powder coated frame.
Screen-printed extra-clear tempered glass screen.
Zedge Line Opal:
Die-cast anodised aluminium body and external frame; powder coated frame.
Polycarbonate screen.

ON DEMAND

Easy Custom Colour

Cataphoresis treatment

Ra90

110-277Vac power supply

The slender and slim rectangular version of the range is available with both a floor washer reflector for discrete and controlled lighting of floors as well as in a new Opal version for a softer and more diffused effect.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.



Plus



Surface installation

Thanks to the special accessory Zedge Line and Zedge Line Opal can also be surface installed.

One solution for two recessed possibilities.

The special outer casing makes it possible to install Zedge Line and Zedge Line Opal both flush (A) and surface with a protrusion of just 4.5mm (B).



Flush installation Surface installation

ZEDGE



Line



LED / 6W / FLOOR WASHER / 24Vdc



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			48°	88°	
Fixture Power	7W	1	1.90	2.12	115
Source Flux	870lm	2	3.80	4.25	29
Fixture Flux	171lm	3	5.70	6.37	13
Efficacy	24lm/W	4	7.60	8.49	7
Imax	151cd	5	9.50	10.61	5

Driver	Colour	2700K	3000K	3500K	4000K
		1E3441	**1E3445**	**1E3763**	**1E3446**

LED / 8W / FLOOR WASHER / 220-240Vac



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			48°	88°	
Fixture Power	9W	1	1.90	2.12	165
Source Flux	1250lm	2	3.80	4.25	41
Fixture Flux	245lm	3	5.70	6.37	18
Efficacy	27lm/W	4	7.60	8.49	10
Imax	217cd	5	9.50	10.61	7

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3442EL**	**1E3443EL**	**1E3764EL**	**1E3444EL**
DALI		**1E3442DA**	**1E3443DA**	**1E3764DA**	**1E3444DA**

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Insertion Box



Code
1E3447

Nylon outer casing fitted for parallel connection with feed through-wiring.
Cutout hole for flush installation AxBxP=308x68x80mm.
Cutout hole for overlay installation AxBxP=298x57x73mm.

Mounting System

Code
1T7003

Stainless steel spring kit for installation without insertion box.

ZEDGE

Carter





Colour	Code
	1E3872

Carter for surface installation.
Can contain 1E2769 and 1E2494 connectors inside.
Powder coated stainless steel.
AxBxH=62x304x76.5mm.





Colour	Code
	1E3873

Carter for surface installation.
To be completed with an external junction box.
Powder coated stainless steel.
AxBxH=62x304x63.5mm.

Accessories

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Code
1E3184

IP68 4-way cable connector (5 pole).

Control systems



Code
1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

Line Opal



LED / 6W / VWFL / 24Vdc



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			116°	
	Fixture Power	7W	1	3.21	175
	Source Flux	898lm	2	6.42	44
	Fixture Flux	515lm	3	9.63	19
	Efficacy	74lm/W	4	12.84	11
TS1181	Imax=195cd/klm	Imax	5	16.06	7

Driver	Colour	2700K	3000K	3500K	4000K
		1E3511	**1E3513**	**1E3765**	**1E3515**

LED / 6W / VWFL / 220-240Vac



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			116°	
	Fixture Power	7W	1	3.19	177
	Source Flux	876lm	2	6.38	44
	Fixture Flux	517lm	3	9.57	20
	Efficacy	74lm/W	4	12.76	11
TS1182	Imax=202cd/klm	Imax	5	15.95	7

Driver	Colour	2700K	3000K	3500K	4000K
EL.		**1E3512EL**	**1E3514EL**	**1E3766EL**	**1E3516EL**
DALI		**1E3512DA**	**1E3514DA**	**1E3766DA**	**1E3516DA**

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Insertion Box



Code
1E3447

Nylon outer casing fitted for parallel connection with feed through-wiring.
Cutout hole for flush installation AxBxP=308x68x80mm.
Cutout hole for overlay installation AxBxP=298x57x73mm.

Mounting System

Code
1T7003

Stainless steel spring kit for installation without insertion box.

ZEDGE

Carter





Colour	Code
	1E3872

Carter for surface installation.
Can contain 1E2769 and 1E2494 connectors inside.
Powder coated stainless steel.
AxBxH=62x304x76.5mm.





Colour	Code
	1E3873

Carter for surface installation.
To be completed with an external junction box.
Powder coated stainless steel.
AxBxH=62x304x63.5mm.

Accessories

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Code
1E3184

IP68 4-way cable connector (5 pole).

Control systems



Code
1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

ZEDGE

GENERAL INFO
Recessed wall mounted fixture
Zedge 63.5x63.5mm

LED
Linear boards
From 537lm to 598lm
2700K - 3000K - 3500K - 4000K
Ra84

PRODUCT EFFICACY
Up to 9lm/W

OPTICS
Floor washer
Floor washer + Halo Louvre

POWER SUPPLY
Electronic - DALI - 24V
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Die-cast anodised aluminium body fitted with a spring fixing system.
Powder coated die-cast anodised aluminium external frame.

ON DEMAND

Easy Custom Colour

Cataphoresis treatment

Ra90

110-277Vac power supply

Zedge, the first and smallest version in the range is an extremely compact step-marker - 63.5mm x 63.5 mm – with a minimal and well proportioned design that characterises the entire family.

Designed to light outdoor environments it is a functional yet decorative fixture at the same time, ideal even for indoor environments thanks to its compact size and the possibility to choose from different colour finishes in the RAL range.
Installation requires the use of an accessory outer casing or directly on the plasterboard.

The decorative front screen, available in three different versions and just 5mm thick simplifies and finishes any installation to ensure three different lighting effects.

Zedge uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Catedral Santo Eccehomo
Valledupar, Colombia

Architect Gustavo Vasquez
Photographer Sebastian Franco

Eletrical Engineer Schaller Tech



ZEDGE



Floor Washer



LED / 4W



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			55°	86°	
Fixture Power		5W	1	2.62	2.11	23
Source Flux		570lm	2	5.25	4.22	6
Fixture Flux		40lm	3	7.87	6.33	3
Efficacy		7lm/W	4	10.50	8.44	1
TS999	Imax=53cd/klm	Imax	30cd	5	13.12	10.55	1

Power supply	Colour	2700K	3000K	3500K	4000K
24Vdc	○	**1E3742**	**1E3154**	**1E3745**	**1E3157**
24Vdc	◐	**1E3743**	**1E3160**	**1E3746**	**1E3163**
24Vdc	◐	**1E3744**	**1E3148**	**1E3747**	**1E3151**



Floor Washer + Halo



LED / 4W



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			56°	90°	
Fixture Power		5W	1	2.82	2.30	23
Source Flux		570lm	2	5.65	4.60	6
Fixture Flux		46lm	3	8.47	6.90	3
Efficacy		9lm/W	4	11.30	9.19	1
TS1000	Imax=54cd/klm	Imax	31cd	5	14.12	11.49	1

Power supply	Colour	2700K	3000K	3500K	4000K
24Vdc	○	**1E3748**	**1E3155**	**1E3751**	**1E3158**
24Vdc	◐	**1E3749**	**1E3161**	**1E3752**	**1E3164**
24Vdc	◐	**1E3750**	**1E3149**	**1E3753**	**1E3152**

Louvre



LED / 4W



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			49°	94°	
Fixture Power		5W	1	14.87	3.25	8
Source Flux		570lm	2	29.74	6.50	2
Fixture Flux		33lm	3	44.60	9.75	1
Efficacy		6lm/W	4	59.47	13.00	0
TS1001	Imax=46cd/klm	Imax	26cd	5	74.34	16.25	0

Power supply	Colour	2700K	3000K	3500K	4000K
24Vdc	○	**1E3754**	**1E3156**	**1E3757**	**1E3159**
24Vdc	◐	**1E3755**	**1E3162**	**1E3758**	**1E3165**
24Vdc	◐	**1E3756**	**1E3150**	**1E3759**	**1E3153**

ZEDGE

Related codes

Power Supply



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.

Accessories

Insertion Box



Code

1E3166

Outer casing in plastic material fitted for parallel connection with feed through-wiring.
For the fixture.
Cutout hole AxBxP=87x59x72.5mm.





Code

1E3180

Stainless steel outer casing fitted for parallel connection with feed through-wiring.
For fixture + driver (1E3179).
Cutout hole AxBxP=166x72x87mm.

Control systems



Code

1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Terminal Box

Code

1E3181

Terminal box with gel.

Control systems

Code

1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code

1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

Surface luminaires

Outdoor

Upgrade



748
MR SMITH

748
MRS SMITH

756
FEBO EVO



760
Q-BO

762
STILO
Wall/Ceiling

774
HOCKEY
Wall/Ceiling

728
ZEDGE PRO



736
ZEDGE
Line

736
ZEDGE
Line Opal

Mr & Mrs SMITH

GENERAL INFO
Wall mounted LED fixtures.
Mr Smith
130x130x51.5mm
Mrs Smith
305x63.6x51.5mm

LED
LED Chip on board high efficacy
From 835lm to 1957lm
2700K – 3000K – 4000K
Ra84 - Ra90

PRODUCT EFFICACY
Up to 97lm/W

OPTICS
Opal version: Direct - Indirect - Direct/indirect

POWER SUPPLY
Electronic – DALI - 24V

MATERIAL
Anodised and painted die-cast aluminium body.
Injection moulded opal polycarbonate screen.

ON DEMAND

Easy Custom Colour

3500K

Cataphoresis treatment

110-277Vac power supply

New applique for outdoor installation. Available in two different versions: Square shaped Mr Smith and rectangular shaped Mrs Smith for wall mounted installations with direct fixing on the back of the product. Both versions are available with different emissions: indirect, direct and direct/indirect.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.



Plus







Three light skimming effects

Direct, indirect, and direct/indirect emission.
The direct light version has an inclined plane at the bottom that, together with the opal polycarbonate screen, softly accompanies the light recalling the design of the ZEDGE Series.
In the version with only indirect or direct/indirect emission the polycarbonate screen at the top softly diffuses the light.

Double geometry and easy installation

130x130 square solution and 63x300 rectangular solution, both made up of two elements for quick mounting without visible screws and an overall clean effect. The base is attached to the installation surface and the body of the device, which has different sections based on the type of emission, is attached to it.

MR & MRS SMITH



MR SMITH



LED / 6W / OPAL / DIRECT / 24Vdc



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			102°	64°	
Fixture Power	7W	1	2.46	1.26	296
Source Flux	896lm	2	4.91	2.51	74
Fixture Flux	490lm	3	7.37	3.77	33
Efficacy	70lm/W	4	9.82	5.03	18
Imax	296cd	5	12.28	6.29	12

TS1198 Imax=330cd/klm

Driver	Colour	2700K	3000K	4000K
		1E3528	**1E3530**	**1E3532**

LED / 5,85W / OPAL / DIRECT / 220-240Vac



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			102°	64°	
Fixture Power	7W	1	2.46	1.26	315
Source Flux	954lm	2	4.91	2.51	79
Fixture Flux	522lm	3	7.37	3.77	35
Efficacy	75lm/W	4	9.82	5.03	20
Imax	315cd	5	12.28	6.29	13

TS1198 Imax=330cd/klm

Driver	Colour	2700K	3000K	4000K
EL.		**1E3527EL**	**1E3529EL**	**1E3531EL**
DALI		**1E3527DA**	**1E3529DA**	**1E3531DA**

LED / 6W / OPAL / INDIRECT / 24Vdc



3000K	
Ra84	
Fixture Power	7W
Source Flux	896lm
Fixture Flux	624lm
Efficacy	89lm/W
Imax	340cd

TS1197 Imax=379cd/klm

Driver	Colour	2700K	3000K	4000K
		1E3522	**1E3524**	**1E3526**

LED / 5,85W / OPAL / INDIRECT / 220-240Vac



3000K	
Ra84	
Fixture Power	7W
Source Flux	954lm
Fixture Flux	664lm
Efficacy	95lm/W
Imax	361cd

TS1197 Imax=379cd/klm

Driver	Colour	2700K	3000K	4000K
EL.		**1E3521EL**	**1E3523EL**	**1E3525EL**
DALI		**1E3521DA**	**1E3523DA**	**1E3525DA**

LED / 12W / OPAL / DIRECT/INDIRECT / 24Vdc



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			102°	64°	
Fixture Power	14W	1	2.46	1.26	296
Source Flux	1793lm	2	4.91	2.51	74
Fixture Flux	1115lm	3	7.37	3.77	33
Efficacy	80lm/W	4	9.82	5.03	18
Imax	330cd	5	12.28	6.29	12

TS1199 Imax=184cd/klm

Driver	Colour	2700K	3000K	4000K
		1E3534	**1E3536**	**1E3538**

MR & MRS SMITH

LED / 11,7W / OPAL / DIRECT/INDIRECT / 220-240Vac



Driver	Colour	2700K	3000K	4000K
EL.		**1E3533EL**	**1E3535EL**	**1E3537EL**
DALI		**1E3533DA**	**1E3535DA**	**1E3537DA**

Note

24V version to be powered with an electronic 230V/24Vdc transformer available as an accessory and dimmable with the special accessory kit.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Accessories

Control systems



Code
1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

MR & MRS SMITH



MRS SMITH



LED / 6,1W / OPAL / DIRECT / 24Vdc



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	93°	
Fixture Power		7W	1	1.60	2.12	302
Source Flux		870lm	2	3.21	4.25	75
Fixture Flux		494lm	3	4.81	6.37	34
Efficacy		72lm/W	4	6.41	8.50	19
TS1202	Imax=348cd/klm	Imax	302cd	5	8.02	10.62	12

Driver	Colour	2700K	3000K	4000K
	●	**1E3546**	**1E3548**	**1E3550**

LED / 6,1W / OPAL / DIRECT / 220-240Vac



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	93°	
Fixture Power		7W	1	1.60	2.12	302
Source Flux		870lm	2	3.21	4.25	75
Fixture Flux		494lm	3	4.81	6.37	34
Efficacy		72lm/W	4	6.41	8.50	19
TS1202	Imax=348cd/klm	Imax	302cd	5	8.02	10.62	12

Driver	Colour	2700K	3000K	4000K
EL.	●	**1E3545EL**	**1E3547EL**	**1E3549EL**
DALI	●	**1E3545DA**	**1E3547DA**	**1E3549DA**

LED / 6,1W / OPAL / INDIRECT / 24Vdc



	3000K	
	Ra84	
Fixture Power		7W
Source Flux		870lm
Fixture Flux		554lm
Efficacy		80lm/W
TS1200	Imax=342cd/klm	Imax	298cd

Driver	Colour	2700K	3000K	4000K
	●	**1E3540**	**1E3542**	**1E3544**

LED / 6,1W / OPAL / INDIRECT / 220-240Vac



	3000K	
	Ra84	
Fixture Power		7W
Source Flux		870lm
Fixture Flux		554lm
Efficacy		80lm/W
TS1200	Imax=342cd/klm	Imax	298cd

Driver	Colour	2700K	3000K	4000K
EL.	●	**1E3539EL**	**1E3541EL**	**1E3543EL**
DALI	●	**1E3539DA**	**1E3541DA**	**1E3543DA**

LED / 12W / OPAL / DIRECT/INDIRECT / 24Vdc



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			76°	93°	
Fixture Power		14W	1	1.60	2.12	289
Source Flux		1740lm	2	3.21	4.24	72
Fixture Flux		1050lm	3	4.81	6.37	32
Efficacy		76lm/W	4	6.41	8.49	18
TS1204	Imax=177cd/klm	Imax	308cd	5	8.01	10.61	12

Driver	Colour	2700K	3000K	4000K
	●	**1E3552**	**1E3554**	**1E3556**

MR & MRS SMITH

LED / 12W / OPAL / DIRECT/INDIRECT / 220-240Vac



Driver	Colour	2700K	3000K	4000K
EL.		**1E3551EL**	**1E3553EL**	**1E3555EL**
DALI		**1E3551DA**	**1E3553DA**	**1E3555DA**

Note

24V version to be powered with an electronic 230V/24Vdc transformer available as an accessory and dimmable with the special accessory kit.

Ra90: to order this version it is necessary to add the suffix “90” at the end of the standard code (Ra84).

Related codes

Power Supply

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
185x22x64	50W	220-240Vac	24Vdc	IP20	**1T3726**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Accessories

Control systems



Code
1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

FEBO EVO

GENERAL INFO
Inground or wall fixture with grazing light effect.
ø160mm – H 150mm

LED
Multiple sources circuit, mid-power
LED
From 4452lm to 5038lm
2700K – 3000K – 4000K
Ra84

PRODUCT EFFICACY
Unitil 76m/W

OPTICS
Grazing

POWER SUPPLY
Available with an integrated electronic or DALI power supply. Watertight connection system inside the fixture included.
Casambi control system available using a dedicated accessory (only for DALI version products). 220-240Vac 50/60Hz

MATERIAL
Extruded aluminium body, die-cast aluminium optical head with black radial blades.

ON DEMAND

Easy Custom Colour

3500K

Cataphoresis treatment

Inground or wall mounted LED fixture with grazing lighting effect with unbroken radial 360° emission that can be controlled using accessories to modulate the light as if it were a second skin.
The light emitted is capable of adhering perfectly to architectural surfaces and to emphasize textures and the consistency of different materials. Its compact design integrates harmoniously with the architecture making it a discrete element even during the daytime.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Plus” technical solution that involves resin coating the connection cables and completely resin coating the integrated driver limiting the risk of humidity reaching the fixture.

Volkstheater
Vienna, Austria

Lighting design Podpod design
Architects Ferdinand Fellner and Hermann Helmer

Restauration Dietrich Untertrifaller Architekten, Alexander van der Donk
Photographer Podpod design

Plus



Installed on the floor Febo Evo

Is a reliable tool with minimal visual impact capable of lighting paths in depth and breadth, or separating different areas using light. It is installed on the ground with a simple support base that is supplied.

It is in wall installations that Febo Evo shows its potential the most

This sophisticated fixture emits a 360° blade of light without any interruptions that is capable of adhering to every surface like a second skin.

With the use of accessories

The light from Febo Evo can be shaped according to needs. Simple rubber elements, combined, coordinated or cut can be positioned at any point so that they “design” the light that best suits the project needs..









FEBO

EVO



LED / 32W / WFL



	Driver	2700K	3000K	4000K
	EL.	**1E3189EL**	**1E3190EL**	**1E3191EL**
	DALI	**1E3189DA**	**1E3190DA**	**1E3191DA**

Accessories

Shutter



	Code
	1E3399

120° shutter kit (with 4 cut zones that allow to shutter even 105°/90°/75°/60° angles).
Max. no. of kits per product: 2.

Tool

	Code
	1E3305

(Tightening) wrench for the connector kit.

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

Q-BO

IP67

GENERAL INFO
Wall and ceiling mounted fixture for grazing light effect.
Side 160mm

LED
Chip on board
From 4122lm to 4228lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Unitil 86lm/W

OPTICS
Reflector Optics
Bi-emission – pluri-emission

POWER SUPPLY
Electronic

MATERIAL
Painted die-cast anodised aluminium body.

ON DEMAND

Easy Custom Colour

Ra90

Cataphoresis treatment

A ceiling or wall mounted fixture for grazing light effect available in two versions, bi-emission direct/indirect or pluri-emission.

The range of accessories the fixture can be completed with make it possible to create scenographic lighting effects on the surface to be illuminated and to tailor the light beam according to specific project requirements.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.



Q-BO IP67



LED / 29W / BI-DIRECTIONAL EMISSION / VWFL



	Driver	Colour	3000K	4000K
	EL.		**1E2956**	**1E2957**

LED / 29W / MULTIDIRECTIONAL / VWFL



	Driver	Colour	3000K	4000K
	EL.		**1E2958**	**1E2959**

Accessories

Shaper

	Code
	1E2953

Blade of light (4/6°).
Equipped with micrometric adjustability to obtain perfect light beam direction.

	Code
	1E2954

Narrow blade of light (10/12°).
Equipped with micrometric adjustability to obtain perfect light beam direction.

	Code
	1E2960

Louvre.
Beam width 50°.

	Code
	1E2961

Louvre.
Beam width 30°.

Shutter

	Code
	1E2955

Shutter.
To be mounted outside the fixture.

STILO

Wall mounted
Ceiling mounted

GENERAL INFO
Wall-mounted fixture.
282x80x184mm

LED
ASY and ELL optic: LED Chip on board
NSP optic: LED Emitter
Effect optic: LED Multichip Emitter
From 600lm to 6536lm
3000K – 4000K
Ra80 – Ra84

PRODUCT EFFICACY
Unitil 112lm/W

OPTICS
NSP – Effect – Asym – Elliptical

POWER SUPPLY
Electronic

MATERIAL
Anodized and painted extruded aluminium body and anodized and powder coated die-cast aluminium optical unit and terminal. Tempered glass protective screen.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

Cataphoresis treatment

A range of products with the same design but with different installation characteristics: from architectural lighting of building facades and porticos right up to pedestrian walkways. Different needs and effects with a unique family feeling; wall mounted versions, ceiling mounted and bollards that produce a myriad of lighting effects, from purely graphic and defined effects to wider beams that fill large spaces.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Arma
Moscow, Russian Federation

Architect SKiP Architectural Bureau

Photographer Ilya Melikhov

Plus

Available in two installation types

FLAT (parallel to the wall) and STRAIGHT (perpendicular to the wall), both available in mono and bi-emission versions.

The ceiling mounted version

Are ideal to light porticos, the different optics make it possible to light pedestrian areas or vertical walls.





Stilo is available with four different optical solutions

A Elliptical emission
Using it like a grazing lighting is ideal to illuminate the building facades.
The ceiling mounted versions allows to light pedestrian areas in a particularly uniform way.

B Asymmetric emission
Installed for indirect emission to light arches and direct emission for pedestrian areas.
The ceiling mounted version can also be used to light walls.

C Superspot emission
Has a particularly concentrated and defined effect that is suitable for lighting a facade.

D Defined effects
Real light patterns on the wall from a blade light beam as thin as a pin, to wider, yet defined effects with beam angles of 30° and 90°.

STILO

Wall Flat



LED / 1x9W / NSP / MONO-EMISSION



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		12W	1	0.16	13011
Source Flux		650lm	2	0.32	3253
Fixture Flux		544lm	3	0.48	1446
Efficacy		47lm/W	4	0.64	813
TS791	Imax=20017cd/klm	Imax 13011cd	5	0.80	520

Driver	Colour	3000K	4000K
EL.		**1E2547**	
EL.		**1E2556**	**1E2881**

LED / 1x11W / EFFECT / MONO-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra80			68°	95°	
Fixture Power		15W	1	1.36	2.19	189
Source Flux		600lm	2	2.72	4.39	47
Fixture Flux		292lm	3	4.08	6.58	21
Efficacy		20lm/W	4	5.44	8.78	12
TS788	Imax=315cd/klm	Imax 189cd	5	6.80	10.97	8

Driver	Colour	3000K	4000K
EL.		**1E2882**	**1E2883**

LED / 2x9W / NSP-NSP / BI-EMISSION



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		20W	1	0.16	13011
Source Flux		1300lm	2	0.32	3253
Fixture Flux		1087lm	3	0.48	1446
Efficacy		54lm/W	4	0.64	813
TS824	Imax=10009cd/klm	Imax 13011cd	5	0.80	520

Driver	Colour	3000K	4000K
EL.		**1E2551**	
EL.		**1E2560**	**1E2887**

LED / 2x11W / EFFECT-EFFECT / BI-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra80			68°	95°	
Fixture Power		27W	1	1.36	2.19	189
Source Flux		1200lm	2	2.72	4.39	47
Fixture Flux		584lm	3	4.08	6.58	21
Efficacy		22lm/W	4	5.44	8.78	12
TS814	Imax=157cd/klm	Imax 189cd	5	6.80	10.97	8

Driver	Colour	3000K	4000K
EL.		**1E2888**	**1E2889**

LED / 1x21W / ASYM / MONO-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			61°	86°	
Fixture Power		23W	1	1.51	1.98	1356
Source Flux		3187lm	2	3.01	3.96	339
Fixture Flux		2304lm	3	4.52	5.94	151
Efficacy		100lm/W	4	6.02	7.92	85
TS787	Imax=464cd/klm	Imax 1480cd	5	7.53	9.89	54

Driver	Colour	3000K	4000K
EL.		**1E2543**	
EL.		**1E2552**	**1E2877**

STILO

LED / 1x21W / ELLIPTICAL / MONO-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power	23W		1	0.76	1.66	2266
Source Flux	3187lm		2	1.52	3.31	567
Fixture Flux	2530lm		3	2.28	4.97	252
Efficacy	110lm/W		4	3.04	6.62	142
TS786	Imax=711cd/klm	Imax	5	3.80	8.28	91

Driver	Colour	3000K	4000K
EL.		**1E2545**	
EL.		**1E2554**	**1E2879**

LED / 1x33W / ASYM / MONO-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			61°	85°	
Fixture Power	36W		1	1.51	1.98	1860
Source Flux	4373lm		2	3.01	3.96	465
Fixture Flux	3162lm		3	4.52	5.94	207
Efficacy	89lm/W		4	6.02	7.92	116
TS787	Imax=464cd/klm	Imax	5	7.53	9.89	74

Driver	Colour	3000K	4000K
EL.		**1E2544**	
EL.		**1E2553**	**1E2878**

LED / 1x33W / ELLIPTICAL / MONO-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power	36W		1	0.76	1.66	3110
Source Flux	4373lm		2	1.52	3.31	777
Fixture Flux	3471lm		3	2.28	4.97	346
Efficacy	97lm/W		4	3.04	6.62	194
TS786	Imax=711cd/klm	Imax	5	3.80	8.28	124

Driver	Colour	3000K	4000K
EL.		**1E2546**	
EL.		**1E2555**	**1E2880**

LED / 2x21W / ASYM-ASYM / BI-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			61°	85°	
Fixture Power	46W		1	1.51	1.98	1356
Source Flux	6375lm		2	3.01	3.96	339
Fixture Flux	4609lm		3	4.52	5.94	151
Efficacy	100lm/W		4	6.02	7.92	85
TS830	Imax=232cd/klm	Imax	5	7.53	9.89	54

Driver	Colour	3000K	4000K
EL.		**1E2548**	
EL.		**1E2557**	**1E2884**

LED / 2x21W / ELLIPTICAL-ELLIPTICAL / BI-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power	46W		1	0.76	1.66	2267
Source Flux	6375lm		2	1.52	3.31	567
Fixture Flux	5060lm		3	2.28	4.97	252
Efficacy	109lm/W		4	3.04	6.62	142
TS829	Imax=356cd/klm	Imax	5	3.80	8.28	91

Driver	Colour	3000K	4000K
EL.		**1E2549**	
EL.		**1E2558**	**1E2885**

LED / 2x21W / ELLIPTICAL-ASYM / BI-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power	46W		1	0.76	1.66	2267
Source Flux	6375lm		2	1.52	3.31	567
Fixture Flux	4835lm		3	2.28	4.97	252
Efficacy	104lm/W		4	3.04	6.62	142
TS831	Imax=356cd/klm	Imax	5	3.80	8.28	91

Driver	Colour	3000K	4000K
EL.		**1E2550**	
EL.		**1E2559**	**1E2886**

Note

EFFECT Version: the fixture comes equipped with a 90° beam aperture. The beam can be shaped using shutter accessories.

STILO

Accessories

Filter

Filter	Code
Red	**1E3035**
Green	**1E3036**
Blue	**1E3037**
Yellow	**1E3038**
Magenta	**1E3039**

Chromatic coloured PMMA filter, anodised powder coated frame (ferrite).
NSP, EFFECT, ASYM, ELLIPTICAL

Colour	Code
	1E2575
	1E2576

Blade of light filter.
PMMA holographic filter for a blade of light effect, CNC machine anodised and powder coated aluminium frame.
To be used with NSP optics.

Colour	Code
	1E2577
	1E2578

Anti-glare.
PMMA holographic filter to reduce the beam angle, CNC machine anodised and powder coated aluminium frame.
To be used with NSP, ASYM and ELLIPTICAL optics.

Shaper

Code
1E2901

30° shutter.
Powder coated stainless steel plate (ferrite).
EFFECT

Code
1E2902

Blade effect shutter.
PMMA plano convex cylindrical lens and powder coated stainless steel plate (ferrite).
EFFECT

Screen

Colour	Code
	1E2579
	1E2580

Asymmetric screen.
Powder coated stainless steel.
To be used with NSP, EFFECT and ELLIPTICAL optics.

Mounting System





Code
1E2906

Pole (Ø60mm) installation bracket.
Powder coated stainless steel.
NSP, ASYM, ELLIPTICAL

STILO



Wall Straight



LED / 1x9W / NSP / MONO-EMISSION



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		12W	1	0.16	13011
Source Flux		650lm	2	0.32	3253
Fixture Flux		544lm	3	0.48	1446
Efficacy		47lm/W	4	0.64	813
TS791	Imax=20017cd/klm	Imax 13011cd	5	0.80	520

Driver	Colour	3000K	4000K
EL.		**1E2894**	**1E2895**

LED / 1x21W / ELLIPTICAL / MONO-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power		23W	1	0.76	1.66	2266
Source Flux		3187lm	2	1.52	3.31	567
Fixture Flux		2530lm	3	2.28	4.97	252
Efficacy		110lm/W	4	3.04	6.62	142
TS786	Imax=711cd/klm	Imax 2266cd	5	3.80	8.28	91

Driver	Colour	3000K	4000K
EL.		**1E2890**	**1E2891**

LED / 1x33W / ELLIPTICAL / MONO-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power		36W	1	0.76	1.66	3110
Source Flux		4373lm	2	1.52	3.31	777
Fixture Flux		3471lm	3	2.28	4.97	346
Efficacy		97lm/W	4	3.04	6.62	194
TS786	Imax=711cd/klm	Imax 3110cd	5	3.80	8.28	124

Driver	Colour	3000K	4000K
EL.		**1E2892**	**1E2893**

LED / 2x9W / NSP-NSP / BI-EMISSION



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		20W	1	0.16	13011
Source Flux		1300lm	2	0.32	3253
Fixture Flux		1087lm	3	0.48	1446
Efficacy		54lm/W	4	0.64	813
TS824	Imax=10009cd/klm	Imax 13011cd	5	0.80	520

Driver	Colour	3000K	4000K
EL.		**1E2898**	**1E2899**

LED / 2x21W / ELLIPTICAL-ELLIPTICAL / BI-EMISSION



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power		46W	1	0.76	1.66	2267
Source Flux		6375lm	2	1.52	3.31	567
Fixture Flux		5060lm	3	2.28	4.97	252
Efficacy		109lm/W	4	3.04	6.62	142
TS829	Imax=356cd/klm	Imax 2267cd	5	3.80	8.28	91

Driver	Colour	3000K	4000K
EL.		**1E2896**	**1E2897**

STILO

Accessories

Filter

Filter	Code
Red	**1E3035**
Green	**1E3036**
Blue	**1E3037**
Yellow	**1E3038**
Magenta	**1E3039**

Chromatic coloured PMMA filter, anodised powder coated frame (ferrite).
NSP, EFFECT, ASYM, ELLIPTICAL

Colour	Code
	1E2576

Blade of light filter.
PMMA holographic filter for a blade of light effect, CNC machine anodised and powder coated aluminium frame.
To be used with NSP optics.

Colour	Code
	1E2578

Anti-glare.
PMMA holographic filter to reduce the beam angle, CNC machine anodised and powder coated aluminium frame.
To be used with NSP, ASYM and ELLIPTICAL optics.

Mounting System





Code
1E2906

Pole (Ø60mm) installation bracket.
Powder coated stainless steel.
NSP, ASYM, ELLIPTICAL



Code
1E2907

Bracket for corner installation.
Powder coated stainless steel.
NSP, ELLIPTICAL



Code
1E2900

Bracket for edge installation.
Powder coated stainless steel.
NSP, ELLIPTICAL

STILO

Ceiling



LED / 9W / NSP



	3000K		H(m)	D(m)	Emax(lx)
	Ra80			9°	
Fixture Power		12W	1	0.16	13011
Source Flux		650lm	2	0.32	3253
Fixture Flux		544lm	3	0.48	1446
Efficacy		47lm/W	4	0.64	813
TS791	Imax=20017cd/klm	Imax 13011cd	5	0.80	520

Driver	Colour	3000K	4000K
EL.		**1E2875**	**1E2876**

LED / 21W / ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			61°	85°	
Fixture Power		23W	1	1.51	1.98	1356
Source Flux		3187lm	2	3.01	3.96	339
Fixture Flux		2304lm	3	4.52	5.94	151
Efficacy		100lm/W	4	6.02	7.92	85
TS787	Imax=464cd/klm	Imax 1480cd	5	7.53	9.89	54

Driver	Colour	3000K	4000K
EL.		**1E2871**	**1E2872**

LED / 21W / ELLIPTICAL



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power		23W	1	0.76	1.66	2266
Source Flux		3187lm	2	1.52	3.31	567
Fixture Flux		2530lm	3	2.28	4.97	252
Efficacy		110lm/W	4	3.04	6.62	142
TS786	Imax=711cd/klm	Imax 2266cd	5	3.80	8.28	91

Driver	Colour	3000K	4000K
EL.		**1E2867**	**1E2868**

LED / 33W / ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			61°	85°	
Fixture Power		36W	1	1.51	1.98	1860
Source Flux		4373lm	2	3.01	3.96	465
Fixture Flux		3162lm	3	4.52	5.94	207
Efficacy		89lm/W	4	6.02	7.92	116
TS787	Imax=464cd/klm	Imax 2031cd	5	7.53	9.89	74

Driver	Colour	3000K	4000K
EL.		**1E2873**	**1E2874**

LED / 33W / ELLIPTICAL



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			42°	79°	
Fixture Power		36W	1	0.76	1.66	3110
Source Flux		4373lm	2	1.52	3.31	777
Fixture Flux		3471lm	3	2.28	4.97	346
Efficacy		97lm/W	4	3.04	6.62	194
TS786	Imax=711cd/klm	Imax 3110cd	5	3.80	8.28	124

Driver	Colour	3000K	4000K
EL.		**1E2869**	**1E2870**

STILO

Accessories

Filter

Filter	Code
Red	**1E3035**
Green	**1E3036**
Blue	**1E3037**
Yellow	**1E3038**
Magenta	**1E3039**

Chromatic coloured PMMA filter, anodised powder coated frame (ferrite).
NSP, EFFECT, ASYM, ELLIPTICAL

Colour	Code
	1E2578

Anti-glare.
PMMA holographic filter to reduce the beam angle, CNC machine anodised and powder coated aluminium frame.
To be used with NSP, ASYM and ELLIPTICAL optics.

Colour	Code
	1E2576

Blade of light filter.
PMMA holographic filter for a blade of light effect, CNC machine anodised and powder coated aluminium frame.
To be used with NSP optics.

Screen

Colour	Code
	1E2580

Asymmetric screen.
Powder coated stainless steel.
To be used with NSP, EFFECT and ELLIPTICAL optics.

Private Residence
Bogotà, Colombia

Architect Helmer Junco
Photographer Sebastián Franco

Engineer Schaller Tech Team
Lighting Design Gregory Schaller, Jeins Tinoco

HOCKEY

GENERAL INFO
Applique, ceiling mounted
ø179mm

LED
LED board.
From 1533lm to 1632lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Unitil 109lm/W

OPTICS
VWFL

POWER SUPPLY
Electronic

MATERIAL
Die-cast ferrite colour anodised aluminium body. LED plate with micro-prismatic diffuser in transparent PMMA.

ON DEMAND

Easy Custom Colour

Cataphoresis treatment

A compact fixture with a simple design with two different installation types- ceiling and wall mounted for direct light- that makes this a flexible tool in the hands of lighting designers.

In the wall mounted version the cast aluminium bracket echoes the fixture's rounded shape becoming part of its design.

On request it is possible to subject the product to "Cataphoresis" treatment making it suitable to be installed near the sea (up to 5 metres) or in "hostile" environments.

The entire range uses the "Waterblock Smart" technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

HOCKEY

Ceiling

LED / 13W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			84°	
Fixture Power		15W	1	1.80	839
Source Flux		1533lm	2	3.60	210
Fixture Flux		1533lm	3	5.40	93
Efficacy		102lm/W	4	7.20	52
EV328	Imax=548cd/klm	Imax	840cd	5	9.00	34

Driver	Colour	3000K	4000K
EL.		**1E2911**	**1E2912**

Wall



LED / 13W / VWFL



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			84°	
Fixture Power		15W	1	1.80	839
Source Flux		1533lm	2	3.60	210
Fixture Flux		1533lm	3	5.40	93
Efficacy		102lm/W	4	7.20	52
EV328	Imax=548cd/klm	Imax	840cd	5	9.00	34

Driver	Colour	3000K	4000K
EL.		**1E2909**	**1E2910**

Bollards

Outdoor

778
MR. BO
H 400mm

778
MR. BO
H 800mm

778
MR. BO
H 1000mm

786
CHIODINO
H 890

790
STILO
Bollard Path
H 800mm

790
STILO
Bollard Path
H 1100mm

790
STILO
Bollard Raised
H 864mm

794
ZEDGE
Bollard
H 400mm

794
ZEDGE PRO
Bollard
H 400mm

794
ZEDGE PRO
Bollard
H 800mm

794
ZEDGE PRO
Bollard
H 1000mm

MR.BO

GENERAL INFO
Radial-emission bollard.
ø160mm
H 400mm – 800mm – 1000mm

LED
Chip on board
From 1427lm to 3817lm
2700K – 3000K – 4000K
Ra84

PRODUCT EFFICACY
Up to 51lm/W

OPTICS
90° - 90° + 90° - 180° - 360°

POWER SUPPLY
Electronic – DALI
Casambi control system available using a dedicated accessory (only for DALI version products).

MATERIAL
Powdered coated anodised die-cast aluminium body. Die-cast aluminium optical head. Ferrite finish.

ON DEMAND

- Easy Custom Colour
- 110-277Vac power supply
- Ra90
- 3500K
- Cataphoresis treatment

LED bollard specifically designed to light large open spaces.
Its mechanical characteristics (IK10) and performance make it possible to use it in every space.
The highly controlled radial emission avoids any risk of glare while still ensuring deep lighting in pedestrian areas.

All versions have been designed to maintain the same level of lighting on the floor regardless of the combination of different versions used in the same project.

On request it is possible to subject the product to cataphoresis treatment making it suitable to be installed near the sea (up to 5 metres) or in hostile environments.

The entire range uses the “Waterblock Plus” technical solution that involves resin coating the connection cables and completely resin coating the integrated driver limiting the risk of humidity reaching the fixture.

Plus

360°



180°



90°



90°+90°



The fixture is made of three different elements

The fixture is composed of different elements that, combined together create various solutions. Four different optical units for four different radial emissions - from 90° to 360° - to be combined with poles available in three different heights 334mm, 734mm and 934mm and two different fixing systems.



400mm 800mm 1000mm

A







A Fixing system

There are 3 different installation systems available

- plate for installation with fixing rods for installation in concrete
- a small plate for surface installation. The plate is not visible when it is installed in the ground
- a large plate for surface installation. The plate remains visible even when the product is installed.

B Excellent lighting performance

The high quality optical system developed for Mr Bo makes it possible to obtain an average lighting of 40 lux even with a distance of 8mt between fixtures.

B



MR.BO

Optic head for bollard
H. 334mm



LED / 8W / 90°



3000K	
Ra84	
Fixture Power	9W
Source Flux	1488lm
Fixture Flux	223lm
Efficacy	26lm/W
TS1120 Imax=165cd/klm	Imax 246cd

Driver	Colour	2700K	3000K	4000K
EL.		**1E3428EL**	**1E3429EL**	**1E3430EL**
DALI		**1E3428DA**	**1E3429DA**	**1E3430DA**

LED / 12W / 90°+90°



3000K	
Ra84	
Fixture Power	14W
Source Flux	2034lm
Fixture Flux	456lm
Efficacy	34lm/W
TS1121 Imax=122cd/klm	Imax 247cd

Driver	Colour	2700K	3000K	4000K
EL.		**1E3431EL**	**1E3432EL**	**1E3433EL**
DALI		**1E3431DA**	**1E3432DA**	**1E3433DA**

LED / 12W / 180°



		H(m)	D1(m)	D2(m)	Emax(lx)
3000K			43°	90°	
Ra84					
Fixture Power	14W	1	3.07	13.22	76
Source Flux	2034lm	2	6.14	26.45	19
Fixture Flux	454lm	3	9.21	39.67	8
Efficacy	34lm/W	4	12.28	52.89	5
TS1119 Imax=146cd/klm	Imax 297cd	5	15.35	66.11	3

Driver	Colour	2700K	3000K	4000K
EL.		**1E3425EL**	**1E3426EL**	**1E3427EL**
DALI		**1E3425DA**	**1E3426DA**	**1E3427DA**

LED / 17W / 360°



		H(m)	D(m)	Emax(lx)
3000K			41°	
Ra84				
Fixture Power	18W	1	2.98	79
Source Flux	2783lm	2	5.95	20
Fixture Flux	910lm	3	8.93	9
Efficacy	50lm/W	4	11.91	5
TS1118 Imax=100cd/klm	Imax 278cd	5	14.88	3

Driver	Colour	2700K	3000K	4000K
EL.		**1E3422EL**	**1E3423EL**	**1E3424EL**
DALI		**1E3422DA**	**1E3423DA**	**1E3424DA**

MR.BO



Optic head for bollard
H. 734/934mm



LED / 12W / 90°



3000K	
Ra84	
Fixture Power	14W
Source Flux	2034lm
Fixture Flux	305lm
Efficacy	23lm/W
TS1120 Imax=165cd/klm	Imax 336cd

Driver	Colour	2700K	3000K	4000K
EL.	●	**1E3416EL**	**1E3417EL**	**1E3418EL**
DALI	●	**1E3416DA**	**1E3417DA**	**1E3418DA**

LED / 17W / 90°+90°



3000K	
Ra84	
Fixture Power	18W
Source Flux	2783lm
Fixture Flux	623lm
Efficacy	34lm/W
TS1121 Imax=122cd/klm	Imax 338cd

Driver	Colour	2700K	3000K	4000K
EL.	●	**1E3419EL**	**1E3420EL**	**1E3421EL**
DALI	●	**1E3419DA**	**1E3420DA**	**1E3421DA**

LED / 17W / 180°



		H(m)	D1(m)	D2(m)	Emax(lx)
3000K			43°	90°	
Ra84					
Fixture Power	18W	1	3.07	13.22	104
Source Flux	2783lm	2	6.14	26.45	26
Fixture Flux	621lm	3	9.21	39.67	12
Efficacy	34lm/W	4	12.28	52.89	6
TS1119 Imax=146cd/klm	Imax 407cd	5	15.35	66.11	4

Driver	Colour	2700K	3000K	4000K
EL.	●	**1E3413EL**	**1E3414EL**	**1E3415EL**
DALI	●	**1E3413DA**	**1E3414DA**	**1E3415DA**

LED / 24W / 360°



		H(m)	D(m)	Emax(lx)
3000K			41°	
Ra84				
Fixture Power	26W	1	2.98	106
Source Flux	3723lm	2	5.95	26
Fixture Flux	1217lm	3	8.93	12
Efficacy	47lm/W	4	11.91	7
TS1118 Imax=100cd/klm	Imax 372cd	5	14.88	4

Driver	Colour	2700K	3000K	4000K
EL.	●	**1E3410EL**	**1E3411EL**	**1E3412EL**
DALI	●	**1E3410DA**	**1E3411DA**	**1E3412DA**

Note

Available with three different height poles - 334, 734 and 934mm - to be combined with the relative head available in four different versions - 360°, 180°, 90°, 90°+90° (the same code for the 800 and 1000mm, specific code for the 400mm). To be completed with a stainless steel anchoring system, available for the double version with a plate for installation with dowels or with fixing rods for installation in concrete.

MR.BO

Related codes

Bollard

	Kg	H	Colour	Code
	1.34	334		**1E3434**
	2.95	734		**1E3435**
	3.8	934		**1E3436**

Powder coated anodised aluminium pole.

Mounting System





Code
1E3448

Plate with fixing rods for installation in concrete.
AISI 316 stainless steel.
0.34Kg.

Code
1E3449

Plate for surface installation (inside the pole).
AISI 316 stainless steel compatible with dowels to be inserted into holes with 8.5mm diameter.
0.68Kg.



Code
1E3510

Plate for surface installation (outside the pole).
AISI 316 stainless steel compatible with dowels to be inserted into 4 holes with 22mm diameter.
1.10Kg.

Accessories

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

MR.BO

Tool

	Code
	1E3305

(Tightening) wrench for the connector kit.

Control systems

	Code
	1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

	Code
	1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

CHIODINO

GENERAL INFO
Radial-emission bollard.
ø196mm
H 890mm

LED
Chip on board
From 2551lm to 2615lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Unitil 70lm/W

OPTICS
360°

POWER SUPPLY
Electronic

MATERIAL
Tapered, anodized aluminium body and die-cast anodized head, both powder painted with a ferrite finish. Ultra flat transparent polycarbonate protective screen.

ON DEMAND

Easy Custom Colour

Ra90

Cataphoresis treatment

High performance bollard with sophisticated LED technology and an original design, ideal for public use thanks to its resistant sturdy construction, it is also a popular private option given its appealing design.

Complies with regulations on light pollution.

Already complete with stainless steel fixing rod.
Plate for surface installation available as an accessory.

On request it is possible to subject the product to "Cataphoresis" treatment making it suitable to be installed near the sea (up to 5 metres) or in "hostile" environments.

The entire range uses the "Waterblock Smart" technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Plus



Thanks to its special, perfectly flat emission sceen

Chiodino takes above horizon emissions to 0cd/klm in compliance with all national and international light pollution laws. This makes it the ideal bollard for public-urban contexts where antipollution regulations are particularly strict.

Excellent uniformity

With an interval of three metres between one fixtues and the next, the light never drops below 70lux to assure a perfectly uniform effect. With an interval of four metres between one fixtues and the next, the light never drops below 30lux.



CHIODINO

H. 890mm



LED / 17W



	3000K		H(m)	D(m)	Emax(lx)
	Ra84			66°	
	Fixture Power	19W	1	2.70	210
	Source Flux	2551lm	2	5.40	52
	Fixture Flux	1310lm	3	8.11	23
	Efficacy	68lm/W	4	10.81	13
	Imax	367cd	5	13.51	8

	Driver	Colour	3000K	4000K
	EL.		**1E2967**	**1E2968**

Note

Complete with an AISI 316L stainless steel fixing rod and A2 stainless steel vandal-proof screws (key accessory 1E2495).

Accessories

Shutter

	Code
	1E2970

Shutter 90°.
Emission 2x90° or 270°

	Code
	1E2971

Shutter 180°.
Emission 180°

	Code
	1E2972

Shutter 270°.
Emission 90°

Mounting System



	Code
	1E2969

Plate for surface installation.
Powder coated ferrite finish 316L grade stainless steel. Compatible with 10mm up to 23mm fixing rods.
2Kg.

Tool

	Code
	1E2495

Features TORX HEAD, TX 30.

CHIODINO

Connector

	Code
	1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

	Code
	1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Tool

	Code
	1E3305

(Tightening) wrench for the connector kit.

STILO

Bollard

GENERAL INFO
Direct or asymmetric emission bollard.
Raised Version H. 864mm
Path Version H. 800/1100mm

LED
Chip on board
From 1960lm to 4351lm
3000K – 4000K
Ra84

PRODUCT EFFICACY
Unitil 90lm/W

OPTICS
ASYM – FLOOR WASHER – WALL WASHER

POWER SUPPLY
Electronic

MATERIAL
Powder coated in ferrite finish anodized extruded aluminium body and die-cast aluminium optical unit. Transparent methacrylate protective screen or extra clear tempered safety glass.

ON DEMAND

Easy Custom Colour

110-277Vac power supply

Ra90

Cataphoresis treatment

A range of products with the same design but with different installation characteristics: from architectural lighting of building facades and porticos right up to pedestrian walkways. Different needs and effects with a unique family feeling; wall mounted versions, ceiling mounted and bollards that produce a myriad of lighting effects, from purely graphic and defined to wider beams that fill large spaces. The Bollard version comes in two different types, Path and Raised.
Comes with AISI 316 stainless steel fixing pegs and type A2 stainless steel anti-theft screws.

On request it is possible to subject the product to cataphoresis treatment making it suitable to be installed near the sea (up to 5 metres) or in hostile environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Plus

The bollard versions are available in two different types

- The Path version is ideal for lighting paths with its particular “size” that hides the optical system, shielding the source to obtain a well, distributed effect on pedestrian paths without the risk of glare.

- The Raised version is designed for architectural lighting and is available with different optical systems. A Floor Washer optic makes it possible to light horizontal surfaces in great depth to cover wide surfaces up to 6 metres; it is ideal to light parks, gardens and forecourts. There is also a Wall Washer optic that is ideal for lighting vertical surfaces in an extraordinary uniform way, such as facades, perimeter walls and vertical gardens.

Cantine Briziarelli - **Photographer** Antonino Ciddio

STILO

Bollard Path H. 800mm



LED / 12W / ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			93°	53°	
Fixture Power		14W	1	2.10	1.17	754
Source Flux		1960lm	2	4.20	2.33	188
Fixture Flux		1108lm	3	6.30	3.50	84
Efficacy		82lm/W	4	8.40	4.66	47
Imax		776cd	5	10.50	5.83	30

Driver	Colour	3000K	4000K
EL.		**1E2863**	**1E2864**

Bollard Path H. 1100mm



LED / 21W / ASYM



	3000K		H(m)	D1(m)	D2(m)	Emax(lx)
	Ra84			93°	53°	
Fixture Power		23W	1	2.10	1.17	1225
Source Flux		3187lm	2	4.20	2.33	306
Fixture Flux		1802lm	3	6.30	3.50	136
Efficacy		78lm/W	4	8.40	4.66	77
Imax		1261cd	5	10.50	5.83	49

Driver	Colour	3000K	4000K
EL.		**1E2861**	**1E2862**

Note

Comes with AISI 316 stainless steel fixing pegs and type A2 stainless steel anti-theft screws.

Accessories

Mounting System





	Colour	Code
		1E2564

Plate for surface installation.
0.8Kg.

Tool

	Code
	1E3185

T20 Torx insert.

STILO

Bollard Raised



LED / 21W / FLOOR WASHER



	Driver	Colour	3000K	4000K
	EL.		**1E2539**	
	EL.		**1E2540**	**1E2865**

LED / 33W / WALL WASHER



	Driver	Colour	3000K	4000K
	EL.		**1E2541**	
	EL.		**1E2542**	**1E2866**

Note

Comes with AISI 316 stainless steel fixing pegs and type A2 stainless steel anti-theft screws.

Accessories

Filter

	Filter	Code
	Red	**1E3040**
	Green	**1E3041**
	Blue	**1E3042**
	Yellow	**1E3043**
	Magenta	**1E3044**

Chromatic coloured PMMA filter, anodised powder coated frame (ferrite).

Mounting System





	Colour	Code
		1E2564
		1E2563

Plate for surface installation.
0.8Kg.

Tool

	Code
	1E3185

T20 Torx insert.

ZEDGE BOLLARD

GENERAL INFO
Pathlight bollard
64x64mm H.400mm

LED
Linear boards
From 537lm to 598lm
2700K - 3000K - 3500K - 4000K
Ra84

PRODUCT EFFICACY
Up to 8lm/W

OPTICS
Floor Washer

POWER SUPPLY

24V version to be powered with an electronic 230V/24Vdc transformer available as an accessory and dimmable with the special accessory kit. Casambi control system available using a dedicated accessory (only with DALI dimmer).

MATERIAL
The body of the fixture are made of powder coated die-cast anodised aluminium.

ON DEMAND

Easy Custom Colour

Cataphoresis treatment

Ra90

110-277Vac power supply

Suitable for lighting small walkways Zedge Bollard is the most compact bollard in the Zedge range developed in collaboration with the Gensler architecture and design firm. The floor washer optic makes it possible to light distances with maximum visual comfort.

On request it is possible to subject the product to “Cataphoresis” treatment making it suitable to be installed near the sea (up to 5 metres) or in “hostile” environments.

The entire range uses the “Waterblock Smart” technical solution that involves resin coating the connection cables limiting the risk of humidity reaching the driver or the fixture.

Zedge Bollard is available in a 24V version to be powered by a 230V/24Vdc electronic transformer accessory and can be dimmed using a special kit. It must be completed with a special fixing system.

Thanks to the special accessories even Zedge Pro can be installed in a bollard version for a high performance solution capable of adapting to different needs.

ZEDGE



BOLLARD



LED / 4W / FLOOR WASHER



3000K		H(m)	D1(m)	D2(m)	Emax(lx)
Ra84			55°	86°	
Fixture Power	5W	1	2.62	2.11	23
Source Flux	570lm	2	5.25	4.22	6
Fixture Flux	40lm	3	7.87	6.33	3
Efficacy	7lm/W	4	10.50	8.44	1
Imax	30cd	5	13.12	10.55	1

TS1177 Imax=53cd/klm

Power supply	Colour	2700K	3000K	3500K	4000K
24Vdc		**1E3736**	**1E3737**	**1E3738**	**1E3739**

Related codes

Mounting System



Code
1E3740

AISI 316 stainless steel plate with fixing rods for installation in concrete.





Code
1E3741

AISI 316 stainless steel plate for surface installation.
Can be used with 1E3450 fixing rods.



Code
1E3450

Fixing rods for installation in concrete.
AISI 316 stainless steel.
For Zedge Pro Bollard installation (+1E3437, 1E3438, 1E3439).
For Zedge Bollard installation (+1E3741).
H=143mm.

Power Supply



Dimensions LxHxP	W	Power supply	Output voltage	IP	Code
79x25x38	10W	220-240Vac	24Vdc	IP67	**1E3179**
130x32x80	75W	220-240Vac	24Vdc	IP67	**1T3586**
230x87x43	100W	220-240Vac	24Vdc	IP67	**1T3587**
238x42x67	200W	220-240Vac	24Vdc	IP67	**1T3588**

Electronic power supply.

Dimensions ØxH	W	Power supply	Output voltage	IP	Code
98x78	max 20W	220-240Vac	24Vdc	IP68	**1E0993**

Electronic power supply.

Accessories

Connector

Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm^2.
Cable diameter range from 7 to 12mm.

Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm^2.
Cable diameter range from 6 to 12mm.

Connector

Code
1E2493

Linear connection box IP68.
4 poles max. wire section 2.5mm^2.
Cable diameter range from 7 to 12mm.

Tool

Code
1E3305

(Tightening) wrench for the connector kit.

Control systems



Code
1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Code
1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers.
The module needs to be positioned in order to receive radio signals.
The distance to the lighting fixtures can reach up to 50m.
Wireless control via the Casambi application.
LxHxP=56.5x22.3x35.8mm.

Code
1E3049

IP67 Extender for wireless control of DALI fixtures.
It generates a local DALI bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in outdoor applications via the Casambi application.
LxHxP=150x40x148mm.

Light Management System

798

798

Light Management System

How we control our fixtures

Dali

The fixture is equipped with a driver that provides a connection to a BUS DALI system for overall management of the system.

DALI is the acronym for “Digital Addressable Lighting Interface”, an international standard protocol compliant with IEC EN 62386 that guarantees the interchangeability of dimmable electronic power supplies from different manufacturers. It is used in building automation. It can be used for medium-sized and large projects and entails a preventive design with special cable routing.
Many fixtures in the Targetti collection have DALI drivers and are therefore compatible with home automation systems that integrate lighting into building automation.

Targetti Control powered by Casambi

Fixtures are controlled via wireless or Bluetooth by a smartphone or a tablet without the need for any other hardware. For Casambi on board fixtures or those equipped with DALI drivers.

LMS is the Targetti home automation lighting control system that makes it possible to manage lighting systems in wireless mode. Designed for both the consumer and professional markets LMS is the result of a combination of components from Casambi, a leading company producing wireless lighting control solutions, and Targetti light fixtures. As one of the first to apply this type of control system along with Casambi we later developed ad hoc components (Extender) that make it possible to control several DALI fixtures in wireless mode.

Dimm on board

The fixture is dimmed using a commutator located inside it.

The simplest system for dimming light fixtures. A commutator inside the fixtures makes it possible to intervene manually and regulate the intensity of the light emission to modulate the light according to actual project needs.

DMX

RGB and RGBW fixtures are controlled using a DMX protocol. Software and touch screen interfaces are available to manage and create static and dynamic lighting scenes.

Targetti Control

Powered by Casambi

LMS is the Targetti wireless home automation system that can manage even the most complex lighting systems. Designed for the consumer and the professional market, LMS is the result of the combination of components from Casambi - a leading company producing wireless lighting control solutions - and Targetti light fixtures.

iOS and Android apps

Thanks to the intuitive simplicity of the app developed by Casambi for iOS and Android, LMS ensures system operational readiness. You just need a phone or another mobile device and anyone can create and manage a lighting network singlehandedly by controlling every fixture individually or in groups depending on the needs and the functions required. Managing the system using a standard handset is also made possible with the use of specific accessories.

Extreme usability

the ease of use and programming of the system makes it easy to manage without the use of special control units or assistance from specialised technicians. The application recognises and associates the Targetti fixtures that are installed in the space automatically by using the BLE (Casambi Bluetooth Low Energy) proprietary protocol to communicate with the various fixtures. No Internet connection is necessary except for synchronisation functions or remote access.

Mesh self-healing network

LMS allows the final user to generate adaptive and multipoint networks: “adaptive” because every fixture can work as a buffer for all the others, adapting automatically to various contexts to optimise control signal propagation; “multipoint” because you can connect up to 127 fixtures on each network without any limit on the number of networks. The result is strong, reliable and affordable networks that manage the system, the profiles of individual fixtures and access rights.



Installation sequence

1

Choose Targetti fixtures by opting for the Targetti Casambi Ready package or Casambi accessory components

2

Download the Casambi iOS or Android App depending on the device used

3

Launch the App: the fixtures in operation will be detected automatically

4

Create one or two networks depending on the characteristics of the environment

5

Create groups of devices as needed

6

Program scenes and/or sequences.

7

Set the level of network sharing

TC — Functions

Control Type

Casambi control can be done using:
- Buttons and switches (manual control)
- App (manual digital control)
- Sensors and timers (automatic digital control)

Grouping

Different fixtures can be grouped together to be managed all together or individually. Grouping is easy and the same as grouping apps on smart devices.

Scene

It is possible to:
- create lighting scenes for different occasions;
- manage several fixtures with just one touch to create the perfect atmosphere for specific needs;
- Use the same fixture in different scenes.

Tunable control

Casambi provides complete colour temperature control for those permitted in the range for LED sources. Just swipe your finger over the icon for the source to change the colour temperature.

Animazioni

It is possible to create dynamic scenes with fades from scene to scene. Animated scenes can be recalled again or repeated as required. It is possible to set both the duration of each scene and fade times between scenes.

Gallery

The exclusive gallery function makes control intuitive. Taking a photo of an environment or uploading a floor plan on the app it is possible to mark the fixtures and then recall them. Images are saved in a special gallery on the app with the fixtures displayed. Users only have to touch the ones they want to manage.

Gateway

With the gateway function it is possible to access a Casambi network remotely. Casambi enabled fixtures can be managed and network settings (administration rights required) can be changed. To enable the remote access feature, an iOS or Android device must act as a gateway on the Casambi network.

Adattabilità

The Casambi system is adaptable to both simple as well as more complex projects. It is based on the possibility to create an unlimited number of networks that can be turned on and off.

Calendario

With the calendar and timer function it is possible to activate and deactivate scenes and animated scenes based on parameters such as: timetables, weekly scheduling, seasonality etc. This makes it possible to meet the needs of different users and the environments to be lit. All Casambi units keep track of time.

Casambi Accessories

External accessories with simple electric cables make it possible to control Targetti fixtures in wireless mode. For a clear and easy choice for the correct accessories, please refer to the explanatory table on page 808 that shows:

- An alphabetical list of the Targetti fixtures that are compatible with Casambi accessories
- Product variants that are compatible with Casambi accessories (only some variants of the same product can be controlled by the LMS system)
- Compatible accessories (descriptions and technical characteristics are listed below)
- Wiring diagram

Gateway DALI/Casambi available that allows fixtures fitted with mesh Bluetooth Casambi technology to interface with a traditional DALI system and to be adjusted by a DALI control unit. For further information seethe website.

Control module IP20 — 1T5349

A wireless control module with a DALI interface. It generates a local DALI bus which makes it possible to connect a LED driver directly to a DALI interface. The module can only be used in a closed system and cannot be connected to an existing DALI network. The module is wireless controlled using a CASAMBI app for smartphones and tablets using Bluetooth 4.0 technology. The devices create an adaptive, secure and reliable wireless mesh network that can control a large number of fixtures in a simple and efficient way. IP20.

Power supply	220-240 VAC
Power	1,1W - PF 0,6
Max current	0,6 Amp AC
Max n. DALI driver	1
Max n. 1-10v driver	1
Dimensions	37x41x14mm
Exit	

Dimmer wireless Bluetooth — 1T5344

Wireless Bluetooth Dimmer capable of handling constant voltage loads of 12V or 24V subdivided into 4 channels with PWM output. This dimmer must be connected between the 12V or 24V power supply and the constant voltage LED module. The maximum total current that can be supplied by the control unit is 6A (equivalent to a total of 144W) that can be divided between the 4 outputs. Compatible with Minimercure RGB and Micromercure.

Power supply	12/24 VDC
Power	144W (24V)
Max current	72W (12V)
Max n. DALI driver	
Max n. 1-10v driver	
Dimensions	72,6x18x30mm
Exit	PWM

Xpress — 1T5350

Xpress is a wall mounted wireless user interface; it can be installed wherever the user chooses thanks to battery power with autonomy of 2-3 years providing direct access to all the most important CASAMBI system control functions. As well as switching the fixtures on and off, Xpress controls dimming, colour temperature change in fixtures equipped with this technology, and control of individual fixtures and lighting scene or sequence management.

Bridge DALI/Casambi — 1T8173CA

A fixture that allows fixtures equipped with mesh Bluetooth Casambi to interface with a traditional DALI system and to be adjusted by a DALI control unit. Inside the usual DALI circuit it is possible to have a maximum of 64 cabled DALI and Casambi wireless devices. It only works with Casambi Evolution networks. The DALI Bridge is transparent in the DALI system, and therefore does not require an address. There is no need for a power supply given that it is supplied directly by the DALI bus.

Dimensions	40,4x14x36,3mm

Trailing Edge dimmer IP20

1T5351

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology. It works with LED 230 V-AC modules, dimmable LED sources and halogen lamps. It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies. It can manage systems with a maximum absorption of 150W. The module is wireless controlled using a CASAMBI app for smartphones and tablets or traditional wall switches. IP20

Power supply	85-240 VAC
Power	0,3W - PF 0,35
PMax power fixtures*	
Dimensions	37x41x14mm

*Consultare le istruzioni di montaggio

Extender IP20

1T5352

Extender IP20 allows for wireless control with a DALI interface.
It generates a local DALI bus with the capacity to drive up to 64 fixtures and can control groups of fixtures in indoor applications. It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A. It prevents any change to the management features provided by the CASAMBI system.

Power supply	100-240 VAC
Power	2,7W - PF 0,6
Max current	6 Amp AC
Max n. DALI driver	64
Max n. 1-10v driver	30
Dimensions	100x42x30mm

Control module IP67

1E3048

A IP67 Module for individual control of external devices equipped with DALI drivers. The module needs to be positioned in order to receive radio signals. The distance to the lighting fixtures can reach up to 50m.

Power supply	220-240 VAC
Power	1,1W - PF 0,6
Max current	0,6 Amp AC
Max n. DALI driver	1
Max n. 1-10v driver	1
Dimensions	120x65x30mm

Extender IP67

1E3049

A IP67 Extender allows for wireless control with DALI interfaces.
It generates a local DALI bus with the capacity to drive up to 64 fixtures and can control groups of fixtures in outdoor applications. It prevents any change to the management features provided by the CASAMBI system.

Power supply	100-240 VAC
Power	2,7W - PF 0,6
Max current	6 Amp AC
Max n. DALI driver	64
Max n. 1-10v driver	30
Dimensions	150x150x40mm

Unità di controllo IP20

1T5349DA8

Wireless control unit for DALI8 fixtures.
It generates a local DALI8 bus that can control individual fixtures.
The module can be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 4.0 technology.
The devices create a wireless mesh network that can control up to 128 fixtures.
IP20.

Dimensions	56,5x22,3x35,8mm

Extender IP20

1T5352DA8

IP20 Extender for wireless control of DALI8 fixtures.
It generates a local DALI8 bus with the capacity to drive up to 64 fixtures.
Can control DALI fixtures in indoor applications via the Casambi application.
It is also equipped with a relay that can control non-dimmable fixtures up to a maximum of 6A.

Dimensions	129x30x42mm

Synoptic table of Casambi accessories

PRODUCT		VARIANT	1T5349 Control module IP20	1T5351 Trailing edge dimmer IP20	1T5352 Extender IP20	1E3048 Control module IP67	1E3049 Extender IP67	DIAGRAMS Pag. 812/813
BEBOP RECESSED		DALI Version	●		●			**01 - 04**
BRAQUE		Modulo LED 230Vac max 150W		●				**03**
CARTESIO	Rectangular suspension	DALI Version			●			**04**
	Square suspension		●		●			**01 - 04**
	Square ceiling mounted		●		●			**01 - 04**
CCTEVO ARCHITECTURAL		DALI Version	●		●			**01 - 04**
CCTEVO DOWNLIGHT		With DALI driver	●		●			**01 - 04**
CCTEVO GIMBAL		DALI Version	●		●			**01 - 04**
CCTEVO ESTRAIBILE		DALI Version	●		●			**01 - 04**
CCTEVO WW		With DALI driver	●		●			**01 - 04**
CCTLED PENDANT		DALI Version	●		●			**01 - 04**
CCTLED TUBE		DALI Version	●		●			**01 - 04**
CORO		With DALI driver	●		●			**01 - 04**
COZY		DALI Version	●		●			**01 - 04**
DART MAXI		DALI Version				●	●	**05 - 06**
DART MEDIUM		DALI Version				●	●	**05 - 06**

PRODUCT	VARIANT	1T5349 Control module IP20	1T5351 Trailing edge dimmer IP20	1T5352 Extender IP20	1E3048 Control module IP67	1E3049 Extender IP67	DIAGRAMS Pag. 812/813
DART SMALL	DALI Version				●	●	**05 - 06**
DIVA	DALI Version			●			**04**
FEBO EVO	DALI Version				●	●	**05 - 06**
FLOOD	DALI Version	●		●			**01 - 04**
FORTYEIGHT LABEL 48V	DALI Version	●		●			**01 - 04**
FORTYEIGHT LOGICO 30	DALI Version	●		●			**01 - 04**
GLOBO	Halogen max 150W		●				**03**
HALL	DALI Version	●		●			**01 - 04**
ISO		●		●			**01 - 04**
JEDI	DALI Version				●	●	**05 - 06**
JEDI INCASSO					●	●	**05 - 06**
JEDI COMPACT IP40	DALI Version	●		●			**01 - 04**
JEDI COMPACT IP67	DALI Version				●	●	**05 - 06**
JEDI COMPACT IP67 INCASSO	DALI Version				●	●	**05 - 06**
JUPITER	With DALI controller				●	●	**05 - 06**
JUPITER PRO					●	●	**05 - 06**

Synoptic table of Casambi accessories

PRODUCT	VARIANT	1T5349 Control module IP20	1T5351 Trailing edge dimmer IP20	1T5352 Extender IP20	1E3048 Control module IP67	1E3049 Extender IP67	DIAGRAMS Pag. 812/813
KEPLERO	DALI Version				●	●	**05 - 06**
LABEL 230V	DALI Version	●		●			**01 - 04**
LOGICO	DALI Version For fixture with 1 driver	●		●			**01 - 04**
MR. BO	DALI Version				●	●	**05 - 06**
MR. SMITH					●	●	**05 - 06**
MRS. SMITH					●	●	**05 - 06**
OMEGA		●		●			**01 - 04**
OSIRIDE LED	Version with LED module 230Vac max 150W		●				**03**
OZ STAND ALONE 230V		●		●			**01 - 04**
PANTHEON	LED module 230Vac max 150W		●				**03**
PROFESSIONAL LED	Version with LED module 230Vac max 150W		●				**03**
QUICKLED	DALI Version	●		●			**01 - 04**
SATURN	With DALI controller				●	●	**05 - 06**
STORE GIMBAL	DALI Version	●		●			**01 - 04**
STORE MINI GIMBAL	DALI Version	●		●			**01 - 04**
THREESIXTY	DALI Version For fixture with 1 driver	●		●			**01 - 04**

PRODUCT		VARIANT	1T5349 Control module IP20	1T5351 Trailing edge dimmer IP20	1T5352 Extender IP20	1E3048 Control module IP67	1E3049 Extender IP67	DIAGRAMS Pag. 812/813
	VOLTA IP66	With DALI driver				●	●	**05 - 06**
	WASABI	LED module 230Vac max 150W		●				**03**
	ZEDGE	With DALI controller				●	●	**05 - 06**
	ZEDGE LINE	DALI Version				●	●	**05 - 06**
	ZEDGE PRO	DALI Version				●	●	**05 - 06**
	ZENO APPLIQUE	DALI Version	●		●			**01 - 04**
	ZENO SMALL	DALI Version	●		●			**01 - 04**

Wiring diagrams

01

1T5349

Single DALI control IP20



02

1T7944

CASAMBI control, 1-4 channels IP20



03

1T5351

Single Trailing Edge control for LED 230 V-AC Modules, dimmable LED sources and halogen lamps - 12V and mains voltage (IP20)



04

1T5352

DALI multiple control IP20



04

1T5352

DALI multiple control with relay IP20



05

1E3048

DALI single control IP67



06

1E3049

DALI multiple control IP67



07

1T5351

Diagram for use with wall mounted push button

normally closed

normally open



DMX

Control system for DMX, Tunable White RGB and RGBW fixtures

For programming and control RGB and RGBW fixtures use the DMX 512 digital protocol, the most widespread and proven standard for smart light control. This allows for complete compatibility with other fixtures on the market and makes a wide variety of accessories available at a reasonable cost.

Fixture power supply

LED RGB and RGBW fixtures need special power supplies with PWM (Pulse Width Modulation) technology that makes it possible to regulate the light intensity separately of primary colours.
In larger RGB and RGBW products the electronic power supply is always combined with the one used for dynamic control (DMX); in this case the fixtures are self-sufficient and defined as "smart"; smaller fixtures on the other hand require an external device called a SECS BOX that can power and control several fixtures at the same time.
RGB fixtures and drivers are compatible with the DMX control protocol and are fitted with a dip-switch for address programming and operating modes. RGBW fixtures are compatible with the DMX – RDM protocol that allows for remote programming via the data line.

Automatic operation

to programme colour-changing light scenarios an external device is usually needed.
Thanks to the "Easy-Run-Menu" function the so called "intelligent" RGB fixtures and the SECS drivers can operate automatically performing dynamic colour sequences without any external controller. Through internal dip-switches it is possible to select among 16 different chromatic sequences:
- 8 static colour scenarios
- 8 dynamic colour sequences
- 5 different playback speed values (30sec, 80sec, 160sec, 320sec, 740sec).

"Master/slave" - Configuration

RGB Fixtures can be configured in a master/slave configuration where a virtually unlimited number of fixtures is controlled by a main one. In case of "non intelligent" fixture the master/slave configuration is achieved through a SECS BOX.

SECS 75/36

Power supply and Control System SECS Scene Effect Control System

SECS 75 and SECS 36 drivers combine, in a single unit, the following 3 functions: power supply of RGB LED devices, playback of pre-set colour sequences and DMX interface for external control devices. The SECS “Easy-Run-Menu” function allows to playback of colour-changing light scenarios that are pre-stored into the driver, without the use of any external driver:

- 8 static colour scenarios;
- 8 dynamic colour sequences;
- 5 different playback speed values;
- Start/Stop of the selected scenario through a remote switch.

SECS 75 and SECS 36 drivers can also be controlled through DMX 512; in this case:

- DMX address (from 1 to 511) can be configured by using dip-switches;
- 3 channels mode: all R-G-B outputs are controlled simultaneously by 3 DMX channels only;
- 6 channels mode: the outputs are divided in 2 R-G-B groups, each one controlled by 3 different DMX channels;
- DMX line termination: SECS drivers contain a 120Ohm resistance which can be activated using a dip-switch;
- a DMX output is available for connection to other DMX devices.

SECS 75 **1E1401**

1,5 IP67



Output 75W

Power supply: 100-240 VAC, 50-60 Hz with automatic adjustment and short circuit protection

Max. output power: 75W

Output voltage: maximum 24 VDC

Driving current can be selected using dip-switches: 350 mA (for 1W leds) or 700 mA (for 3W leds)

Controllable led devices: RGB led with common anode (+24 VDC, 4 wires) and power RGB led (1-3W, 6 wires)

Led control mode: Pulse Width Modulation (PWM)

Resolution: 8 bytes with 256 levels equal to 16.770 million colours

Digital interface: RS485 with opto-isolator and integrated buffer, compatible with USITT DMX 512 (1990) protocol

Input: socket for DMX signal, over-voltage protection

Outputs (modular terminal boards) that can be used simultaneously:
- 2 outputs for constant voltage led devices
- 2 outputs for constant current
- 1 DMX output (over-voltage protection)

Operating configuration: through dip-switches

Internal diagnostics: led signalling correct or erroneous DMX connection

Firmware updates: by PC using DMX input

Operating temperature: -20° +50°C

SECS 36 — 1T2245

1,25 | IP20



Output 35W

Power supply: 90-240 VAC, 50-60 Hz with automatic adjustment and short circuit protection

Max. output power: 35W

Power factor 0.9 (PFC)

Led control mode: Pulse Width Modulation (PWM)

Output voltage: maximum 30 VDC, SELV

Driving current 350 mA

Controllable devices: power RGB led (1-3W, 6 wires), 9 LED for colour max

Resolution: 8 bytes with 256 levels equal to 16.770 million colours

Digital interface: RS485 with opto-isolator and integrated buffer, compatible with USITT DMX 512 (1990) protocol

Input: socket for DMX signal, over-voltage protection

Outputs:
- 2 outputs for constant current LED devices
- 1 DMX output with over-voltage protection

Operating configuration: through dip-switches

Internal diagnostics: led signalling correct or erratic DMX connection

Operating temperature: -20° +50°C

Optosplitter — 1T2266

0,85 | IP66



4 ch

Device that has to be used for splitting a DMX 512 line to create up to four new branches, each fully optoisolated from the others. Optical isolation of each line increases transmission reliability, since it eliminates any possibility of ground looping.
OptoSplitter 4ch also amplifies the DMX signals in output; this permits extending the transmission length to the maximum recommended by the DMX standards; each of the new DMX lines may be used as an independent line and each can handle up to 32 devices (not buffered). The fixture is not RDM compatible.

Power supply: 100-240 V AC, 50-60 Hz input (built-in)

Power consumption: 5W

Main switch for switching the device ON/OFF

Input: 1 input for DMX 512 - USITT 1990 signal

Outputs: 4 optoisolated, amplified DMX 512 outputs (3 kV), 1 amplified output for daisy-chain connection

Connectors: modular terminal blocks inside the housing

DIP switch: for inserting terminal resistor at end DMX line

Protection classification: IP66

Housing: Plastic material with input and output cable glands, Complete with 1.5-meter power cord

Ambient temperature for operation: -20°C to +50°C

Dimensions: 250 x 200 x 75 mm

Feeding cable

6-pole cable for driver output connection to Constant Current LEDs	**1E1713**
Multifunction cable for outdoor use (DMX + power supply)	**1E1715**
Standard DMX cable (1 twisted pair + shield, 120Ohm)	**1T1932**



Schema tipico di collegamento

Dmx 512 Wireless technology

DMX Wireless technology can be transmitted the control signal to the lighting fixtures, without cables. Transmission is handled by a radio transmitter operating on a reserved frequency that is license-free worldwide.

It is able to transmit a signal:
- from one building to another;
- from a central control room to multiple installations in different positions, distant the ones from the others;
- from the inside of a building to the exterior, the facade, the roof, or a surrounding;
- in archaeological contexts in which digging trenches for laying.

A DMX 512 Wireless system requires that the control unit be equipped with a radio transmitter (external or built-in) and that a radio receiver is available in proximity to each DMX device or group of fixtures.

The product range includes a series of devices/fixture incorporating DMX 512 Wireless technology, having the following characteristics in common:

- the signal is transmitted via radio, using a protocol and components derived from the GSM mobile telephony standard;
- the frequency used is FCC approved and is license-free throughout the world, including Japan and the USA;
- the devices apply FHSS (Frequency Hopping Spread Spectrum) technology;
- installation is the “plug-and-play” type; that is, there is no need to attribute IP addresses to the fixtures, which automatically recognize the transmitter by which they are controlled;
- the radio signal can be transmitted in a range up to 500 meters (1700 feet) in free space and through material such as walls, glass, and metals;
- multiple transmitters may be used in the same area because they can be individually to control a single group of fixtures without creating reciprocal interference;
- the fixtures are not RDM compatible.

Wireless optosplitter — 1E1906

IP66

4 ch with Wireless receiver

A device that operates as a radio receiver with up to 4 wired DMX lines in output.

Technical feature of this unit are identical to the ones of the normal Optosplitter with the following additional features:
Built-in radio receiver module
Built-in antenna
RLS (Radio Link Status) monitoring system and LOG command (for transmitter linkage)
Built-in power supply for all components, including radio section
Protection grade: IP65
Not RDM compatible

Wireless dmx - Transmitter — 1E1929

0,2 IP66

Transm. with 1 DMX input

This device receives a DMX-IN signal via cable. It can be installed at any point in a DMX line and from that point on it transmits the signal via radio. For example, connecting the device directly to the output of any DMX512 controller transforms it into a wireless controller. Not RDM compatible.

Built-in radio module transmitting on the 2.45 GHz license-free radio frequency
One radio output with external antenna
Capability to control a DMX universe and to address individually 512 radio receivers
RLS (Radio Link Status) LED system for monitoring quality of DMX transmission
LOG key for secure receiver linkage
Transmission range: 50S0 meters in open air
Built-in power supply: 90-250V AC, 50/60 Hz
Housing in plastic material, for outdoor use (IP65)
Dimensions: 175 x 125 x 76 mm.

mySCENARIO

Systems of digital devices designed to control dynamic lighting fixtures and to programme dynamic light scenarios and sequences.

The system consists of an intuitive software, compatible with Windows operating systems, able to control different hardware devices having the following functions:

- recording colour-changing scenarios set by the operator;
- rallowing the selection among the multiple scenarios recorded;
- rtransmitting the control signals to the lighting system.

The software is interfaced to the PC through a USB port; the interface with lighting fixtures is featured through a DMX 512 output.

The software provides a graphic simulation of the operating keys of lighting controller; the patching function allows to assign the DMX control channels to the fixtures by using the internal library.

The Colour Manager function allows a quick and intuitive programming of a RGB light show, consisting of several steps with assigned duration and fading times. The built-in calendar allows a full time scheduling of show playback (month, day, hour, minutes, recurring events). The programmed light shows can be transferred to the different control interfaces.

mySCENARIO show store **1T1898**

Software + USB interface
Storage, via USB, of light-shows created through mySCENARIO software
Automatic stand-alone operation with non need of a PC or any other external driver
Keys for scrolling through programmed sequences
Digital display to show the number (1-99) of active scene
Led indicators for ON/OFF status
Three poles XLR output – DMX signal to lighting fixtures
XLR input for daisy chain connection to other identical unit
Management of 512 DMX channels (512 parameters to be programmed separately)
Memory dedicated to light shows proportional to number of connected

Typial wiring layout



mySCENARIO Wall

DMX controller with a glass touch sensitive screen for architectural applications.

- It can control two different DMX universes (2x 512 channels).
- Stand alone function or connected to a computer using a USB port.
- Software for creating scenarios (that can be downloaded from the Targetti website) is included.
- It can manage 10 different lighting zones and 50 scenarios per zone.
- The touch keys on the front make it possible to modify and recall programmed scenarios.
- Power supply adapter and USB cable included.
- To be used with all RGB and RGBW products.

mySCENARIO Wall **1T6499**



Power supply	6 Vdc
Output	4W
Memory	SD card
DMX Channels	2 x 511
Operating system	Windows 32/64bit
Dimensions	146 x 106 x 11 mm

USB-RDM Programmer code

DMX-RDM (Remote Device Management) address planner.

Used with the “RDM Targetti” software that can be downloaded for free from the Targetti website download section.

To be used with all RGBW products.

USB – RDM **1E2767**

Technical data

Flicker

We spend the majority of our time exposed to artificial lighting. The quality of the effect, even in terms of stability of the light is therefore an indispensable requirement for a light fixture. Flicker is defined as “rapid variations in intensity over time of a light source”; in particular, those belonging to the frequency range of between 0-80Hz.

However, when fluctuations belong to the frequency range of between 80Hz-2KHz these are called “Stroboscopic effects” in which fluctuations in brightness produce a misperception of the movement of lit objects by a static observer.

This phenomenon has become increasingly important following the introduction of LED sources for general lighting due to a combination of the following factors:
These fluctuations in light intensity, according to the frequency, intensity, viewing angle, level of light in the environment, age of the observer and their sensitivity level, can be perceptible on a conscious and/or unconscious level and generate a series of side effects depending on the sensitivity level such as headaches, visual fatigue, distraction etc.

In order to mitigate the risks on health in lighting contexts using LED sources on a European level Technical Reports IEC TR 61547-1 and IEC TR 63158 have been developed.

1. **LED sources are characterised by a high speed response to fluctuations in the power supply which result in variations of the light emitted.**
2. **Unwanted residual fluctuations of the driving current generated by the electronic power supplies used.**
3. **Modulation of the driving current of LED sources for example PWM (Pulse Width Modulation), necessary to adjust the emission level.**
4. **Any instability in the operation of dimmers connected externally to the LED source power supplies.**

The Targetti approach to the Flicker phenomenon

Fixtures with the Safe Flicker logo in the catalogue and on data sheets have parameters below the minimum visibility threshold PstLM=1 and SVM≤0,4 (IEC TR 61547-1 and IEC TR 63158).

1

PstLM
(Short-Term flicker)

Quantifies visible Flicker that is harmful to human health caused by the modulation of light in the frequency range of between 0.3Hz and 80Hz.

The recommended threshold is P st LM =1.

Note - This value was determined based on a representative test group of people and identifies the average perception threshold of visible flicker.

2

SVM
(Stroboscopic Visibility Measure)

Quantifies stroboscopic effects that can occur in situations relating to objects in movement in the presence of modulation of light in the frequency range of between 80Hz and 20KHz.

SVM=1 represents the visibility threshold in a test group of people that quantifies the stroboscopic effect in defined laboratory conditions.

Fixtures that do not have the Safe Flicker logo on the data sheet on the other hand show the flicker value declared by the driver manufacturer which is not determined according to IEC criteria. Constant renewal of drivers will bring about the introduction of new models in line with IEC requirements.

For more details and/or specific needs please contact our technical department.


100
10
1
0.1
Modulation (%)
Magnetically Ballasted HPS
SVM=1
Magnetically Ballasted Fluorescent
CA title 24 proposed limit
Incandescent
IEEE 1789 Low Risk
IEEE 1789 No Effect
Electronically Ballasted Fluorescent
P st =1
Flicker
Stroboscopic Effect
1
10
100
1000
Frequency (Hz)

Photobiological Safety Risk Groups

This is an extremely important parameter because it identifies the danger to the eyes and skin of prolonged exposure to artificial sources. Legislative Decree 81/2008 (Consolidated Law) and supplementary and corrective measures Legislative Decree 06/2009, puts risk assessment and management obligations for workers' health and safety in the hands of the company and more precisely employers.

Among the risks employers have to evaluate there are also any possible photobiological risks deriving from exposure to artificial optical radiation (AoR), chapter V of Legislative Decree 81/08. The technical reference standard IEC/EN 62471:2010 defines a classification of sources in 3 Photobiological Safety Risk Groups on the basis of the quantity of radiation emitted by the sources in the range of wavelengths from 200 nm to 3000 nm, therefore well beyond the range of the visible, providing a clear indication of the limits of maximum exposure for each group. In accordance with Paragraph 6.1 of EN 62471: 2010 the risk groups (for blue light) are defined as follows:

1

RG0
(Risk Exempt)

The source does not cause any photo-biological risk. Requirement met by any lamp that does not cause a blue light (BL) retinal risk with an exposure time of up to 10,000 s (about 2.8 h).

2

RG1
(Low Risk)

The source does not cause risk due to normal operating limitations on exposure. Requirement met by any source that exceeds the limits of the Exempt Group but does not cause a blue light (BL) retinal risk with an exposure time of up to 100 s.

3

RG2
(Moderate Risk)

The source does not cause a risk due to an instinctive reaction when looking at very bright light sources (or due to a sensation of thermal discomfort.) Requirement met by any source that exceeds the limits of Risk 1 Group but does not cause a blue light (BL) retinal risk with an exposure time of up to 0.25 s.

4

RG3
(High Risk)

The source can constitute a risk even due to momentary or brief exposure.

We choose LED sources with the lowest Photobiological Safety Risk Group available on the market so that our fixtures are in the Risk 0 or Risk 1 groups.

The current standard EN 60598-1 concerning indoor light fixtures indicates that RG0 or RG1 risk groups are acceptable for safety purposes albeit technically not equivalent. Exposure to fixtures with RG1 is not to be considered dangerous in ordinary use because exposure times of more than 100 seconds are considered to be "unlikely", although not impossible because this would mean looking in the direction of a light fixture for 100 consecutive seconds. Risk group RG0, on the other hand, has a period of exposure greater than 2.8 h and as such, it can be stated with greater confidence that fixtures would not be viewed for such a long time.

Power supply



Electronic ballast/power supply for LED source

Power	LxHxP	Power supply	Output current	Output voltage	Dimming	Protection	
max 20W	Ø 98 H 78	220-240V		24V-DC		IP68	**1E0993**
17W	Ø 105 H 74	220-240V	700 mA				**1E1385**
12W	Ø 105 H 74	110-120V	700 mA				**1E1385**
70W	225x51x65	220-240V		48V-DC		IP67	**1E2320**
150W	225x51x65	220-240V		48V-DC		IP67	**1E2321**
480W	227x100x125	220-240V		48V-DC		IP20	**1E2323**
240W	125x100x125	220-240V		48V-DC		IP20	**1E2533**
max 43W	150x40x150	220-240V	600mA			IP68	**1E2571**
max 43W	150x40x148	220-240V	600mA		DALI	IP68	**1E2572**
max 50W	150x40x148	220-240V	900mA			IP68	**1E2573**
max 50W	150x40x148	220-240V	900mA		DALI	IP68	**1E2574**
20W	150x40x148	110-240V	400mA		1-10V	IP68	**1E3033D**
20W	150x40x148	110-240V	400mA		DALI	IP68	**1E3033DA**
20W	150x40x148	220-240V	400mA			IP68	**1E3033EL**
20W	150x40x148	110-240V	900mA		1-10V	IP68	**1E3034D**
20W	150x40x148	110-240V	700mA		DALI	IP68	**1E3034DA**
20W	150x40x148	110-240V	900mA			IP68	**1E3034EL**
10W	69x33x38	220-240V		24V-DC		IP67	**1E3179**
15W	119x22x52	220-240V	350mA			IP20	**1T1757**
29W	160x35x83	110-240V	700mA			IP20	**1T2963**
29W	160x35x83	110-240V	700mA		DALI	IP20	**1T2965**
max 50W	160x35x83	220-240V	900mA			IP20	**1T2966**
max 50W	160x35x83	110-240V	900mA		DALI	IP20	**1T2968**
75W	130x32x80	220-240V		24V-DC		IP67	**1T3586**
100W	230x87x43	220-240V		24V-DC		IP67	**1T3587**
200W	238x42x67	220-240V		24V-DC		IP67	**1T3588**
32W	160x35x83	110-240V	600mA			IP20	**1T3625**
32W	160x35x83	110-240V	600mA		DALI	IP20	**1T3627**
50W	185x22x63,5	220-240V		24V-DC		IP20	**1T3726**
42W	160x35x83	110-240V	1050mA			IP20	**1T3781**
42W	160x35x83	110-240V	1050mA		DALI	IP20	**1T3783**
max 22W	130x30x42	220-240V	500mA			IP20	**1T3966**
20W	118x22x52	110-240V	400mA		1-10V	IP20	**1T4215D**
20W	118x22x52	110-240V	400mA		DALI	IP20	**1T4215DA**
20W	118x22x52	220-240V	400mA			IP20	**1T4215EL**
max 15W	119x22x52	110-240V	350mA		DALI	IP20	**1T4630**
20W	119x22x52	220-240V	500mA		DALI	IP20	**1T4631**
15W	119x22x52	110-120V	500mA		DALI	IP20	**1T4631**
max 60W	129x30x76	220-240V	1050mA			IP20	**1T4723**
max 60W	129x30x76	220-240V	1050mA		DALI	IP20	**1T4725**
20W	118x22x52	110-240V	900mA		1-10V	IP20	**1T5295D**
20W	118x22x52	110-240V	700mA		DALI	IP20	**1T5295DA**
20W	118x22x52	110-240V	900mA			IP20	**1T5295EL**
12W	101,5x29,5x51	220-240V	350mA			IP20	**1T6503**
12W	67x103x21	220-240V	350mA		DALI	IP20	**1T6504**
12W	158x19x22	220-240V	350mA			IP20	**1T6505**
42W	129x30x42	220-240V	1050mA			IP20	**1T6524**
10W/20W	145x19x55	110-240V/220-240V		12V-DC		IP20	**T1585**
70W	225x51x65	220-240V		12V-DC		IP65	**T1586**

DC MINI JOLLY DALI IP67

LED

Characteristics of the LED lamps Targetti fixtures are fitted with

1

Colour tolerance

The Targetti collection uses different LED lamps depending on the type of fixture. Nevertheless the hue of the light emitted is always the same from one fixture to another because only LED lamps produced by leading companies in the sector are used, with the same chromaticity identified by the methodology of MacAdam ellipse or SDCM (Standard Color Deviation Matching).

Light chromaticity is identified using a two-dimensional value within an ellipse that defines the maximum displacement of chromaticity from the point of reference (the centre of the ellipse).

A 3 SDCM value is generally considered the maximum value before an average observer perceives chromaticity differences.

The colour tolerance values used in Targetti are as follows:

- **1.5 SDCM** (1 on request) for fixtures that use COB LED lamps
- **3 SDCM** (2 on request) for fixtures that use LED COB Hight density and LED Mid-Power lamps

It is also important to consider colour tolerance throughout the life span lamps (long term color consistency). Targetti LED lamps ensure the declared colour tolerance for the entire life of all fixtures.









2

Colour rendering

The colour rendering index is the quantitative measure of the ability of a light source to reproduce colours faithfully. The method approved and currently used is the CIE CRI (Color Rendering Index) also known as CIE Ra. To determine it a comparison is carried out between the lamps to be evaluated and a reference light source with the same colour temperature.

It is based on a comparison of 15 “patches” of colour. The Ra index is the average of the 15 Patches, R9 is the rendering of the red patch.
A colour rendering index between 90 and 100 is considered excellent and a value between 80 and 90 is good. Among specialists in the field the CRI method is often contested given that it provides values that are sometimes inadequate especially for some LED sources.

At meetings between the regulatory and standardisation committees various alternative methods have been put forward.
The one that is more popular and considered more reliable today is the TM 30-15 method from the IES (Illuminating Engineering Society).

Most importantly is the IES TM-30-15 IES – the acronym for the Illuminating Engineering Society – the organisation that developed the scale as a new method for evaluating the colour rendering of a light source. It appears to be more reliable than the previous Ra because it is based on the colour rendering comparison of 99 “colour patches" rather than 8+6 like the CRI. In addition, where the CRI provides a single score, therefore it does not significantly express the narrow but broad relationship between light and colour, the TM-30 appears to be more complete because it is identified using three different parameters: an Rf Fidelity index, an Rg Gamut index and a colour vector graphic. These combine to provide a more accurate image of the colour fidelity of a light source and a better explanation of the exceptional colour rendering capabilities of LED sources.



3

Rf (Fidelity)

The TM-30 Fidelity index uses 99 colours, rather than 8+4 of the CRI, chosen from real world objects. Like the CRI the points of the Fidelity index go from 0 to 100. A score of less than 60 is too poor for indoor use and a 90+ score is ideal for an effect that is similar to daylight.

The TM-30, 99 “colour patches" are classified into seven groups (nature, skin tones, textiles, paints, plastics, printed material and colour systems). This categorisation helps because the light source can be tested on specific application areas.

Rg (Gamut)

Evaluates the intensity of colours under a certain light, therefore it provides indications of the source’s ability to reproduce colour saturation (breadth of colour range). A score range equal to 100 indicates that the light source does not change the hue or colour saturation that are reproduced in the same way as the sample source.

R>100 indicates an increase in colour saturation, therefore they appear more intense.

R<100 indicates a decrease in saturation.

4

TM-30 colour vector graphic

Indicates which colours appear to be saturated and which desaturated.

In the TM- 30 colour vector graphic the white circle represents the sample light, while the circle with the colored background is the light being tested. If the circles overlap perfectly the tested light corresponds to sunlight.
The areas that extend beyond the black circle indicate that the colours are more intense compared to the sample, however those that remain inside represent colours that appear desaturated.
Unlike the Fidelity and Gamut indexes which are numerical scores, the colour vector graphic is a visual representation that makes it possible to understand which colours are more and less intense. This is particular useful when it is necessary to highlight a particular colour, for example in retail applications.



5

Life expectancy of LED sources and lumen maintenance

LED lamps emit light for an extremely long length of time with an almost insignificant failure rate. The life expectancy of a LED lamp is based on the decreasing lumen rate and the percentage of fixtures are subject to this decrease in a certain period of time.

For example a LED source with a life expectancy of 80000 hours is identified with the code L80 B10 when lots of this type of source once they reach 80000 hours will have at least 90% (100% - B=10) of the LED with lumen of over 80% of the original (L=80).

The lifetime of LED lamps is measured using tests carried out according to the IES LM80 standard. A certain number of LED lamps are left working at different temperatures for at least 6000 hours. Every 1000 hours various parameters are measured: lumen, chromaticity, power etc. The results are then processed using the IES TM 21 procedure that makes it possible to extract the data and produce the lumen maintenance values in hours, L and B depending on the operating temperature.

6

Life span of LED fixtures

The life span of LED light fixtures depends mainly on two components: the LED lamp and the LED driver.
The life span of LED sources and LED drivers are heavily dependent on the temperature these components operate inside the fixture. Targetti fixtures are designed to have very low operating temperatures for LED sources and drivers compared to the limits indicated by producers to ensure excellent performance in terms of duration and lumen maintenance.

7

Targetti fixture data

Since LED technology was applied to light fixtures we have always wanted to be completely transparent in publishing data relating to the performance of our fixtures. For every fixture we have always indicated:

- The power of the LED source (Watt)
- The lumen of the LED source (lm)
- The power of the fixture (Watt)
- The lumen of the fixture (lm)
- Maximum intensity (cd)
- Typical colour rendering CIE Ra - TM30 Rf, Rg

8

Warnings on LED fixtures

Given the production process of LED lamps, typical values indicated by parameters only represent statistical magnitude. These values are affected by the manufacturing tolerances of producers of LED lamps, drivers (LED power feed) and also the operating temperature of the fixtures (LED voltage varies with temperature).

Targetti fixtures are designed, built and tested in compliance with current standard regulations and technical requirements. As required by regulation IEC 60598, technical checks are carried out at a room temperature of 25°C.
Even lumen output and lighting data are based on a room temperature of 25°C. At different temperatures deviations from the values indicated in the catalogue are possible.

Manufacturing tolerance on data relating to declared output and performance is ± 10%
Then laboratory measurement uncertainties are then added:

- Lumen 5%
- Intensity 1%
- Power 0.5%
- Temperature 3%

Photometric data

Photometric measurements were taken at the “Photometric Laboratory Targetti. These measurements are performed at a room temperature equal to 25±1 °C as required by UNI EN 13032-1 - Light and lighting - Measurement and presentation of photometric data of lamps and luminaries - Part 1.

Polar dyagram



Luminous intensity

Photometric curve

TS947 Imax=7844cd/km — Imax

Photometric code

3000K Ra84		**Kelvin - Irc**
Fixture Power	23W	**Fixture power**
Source Flux	2886lm	**Led flux**
Fixture Flux	2453lm	**Fixture flux**
Efficacy	107lm/W	**Efficacy**
Imax	22638cd	**Imax**

H(m)	D(m)	Emax(lx)	
	14°		**Beam angle**
1	0.24	22638	**Distance from the plan (m)**
2	0.48	5659	
3	0.72	2515	**Ø luminous cone (m)**
4	0.96	1415	
5	1.20	906	**Max illumination (lx)**



Reference “C-γ”

Transverse plane
Piano C0° - C180
Beam angles α α

Longitudinal plane
Piano C90° - C270°
Beam angles α β

The photometric values quoted are dependent on the optical system to which they relate, and from the light source used. In order to improve its production, the Company reserves the right to change these optical systems and consequently relative photometric data without notice.

This catalog shows the only photometries for the 3000K color temperature version, to consult the photometric data of the other versions, please refer to the website www.targetti.com.
For ease of use, the photometric curve present within this catalogue is shown and explained below.

Photometric data are available in the “download” section of www.targetti.com, in digital format.

The photometric curves shown in this catalogue are compiled according to the “C-γ” international reference system, where the C0-C180 plane is perpendicular to the fixtues and the C90-C270 plane is parallel to the fixtues, as depicted in the figue. For symmetrical and rotationally symmetric fixtues therefore, a single curve is used.

Cie flux code

Commission Internationale de l'Eclairage (CIE) provides a classification of luminaires according to the distribution of the flux delivered within certain limits of solid angle. The first three numbers indicate the fluxes contained in the cones identified by solid angles equal to π/2, π, 3/2π. The fourth number gives the percentage of direct light compared to total emission. The fifth is the ratio between the total emission of the fixtures and total emission of the lamps (efficiency of the fixtures). The 5 codes are expressed in percentages.

Fixture performance

In accordance with EN 13032-2 - Light and lighting - Measurement and presentation of photometric data of lamps and luminaries - Part 2: Presentation of data for indoor and outdoor work places - the performance of lighting fixtures is indicated by the acronym "LOR" (Light Output Ratio) defined as the ratio of the luminous flux emitted by a fixture and the total flux of the sources used. For direct/ indirect light fixtures appliances, the regulation introduces the components "DLOR" (Down Light Output Ratio) and "ULOR" (Up Light Output Ratio). These components show the distribution of luminous flux of the fixtures in the lower and upper half-space. The 3 parameters are expressed as percentages.

UGR values

The UGR (Unified Glare Rating) method was introduced by the CIE (Commission Internationale de l'Eclairage) with the CIE 117 – 1995 publication "Glare Discomfort in Interior Lighting" in order to have a unified method for evaluating glare. Unlike the previous method (Diagram of light or Söllner), the index of glare depends on both the characteristics of the fixtures, and the characteristics of the environment in which it is installed, taking into account the relative position of observer- fixtures.
The UGR glare index is calculated from the size of the room, the type of light fixtures, its size and the surface reflection properties of the environment.
It is expressed by the formula:

$$UGR = 8 \log \left(\frac{0{,}25}{L_b} \sum \frac{L^2 \pi}{\rho^2} \right)$$

UGR: A value that defines the class of the annoying glare (or glare that causes disruption without affecting the view of objects) directly produced by the fixtures of an indoor lighting system.
Background luminance Lb: luminance of the visual field, in cd/ sqm, with the exclusion of glaring sources.
Fixtures luminance L: luminance of the luminous parts, in cd/sqm, of each appliance in the direction of observation.
Solid angle π: solid angle, in steradian, of the luminous parts of each illumination fixture in the direction of the eye of the observer.
Guth's position index ρ: a value that defines the offset angle to the axis of vision for each individual luminary.

UGR glare index values are between 10 and 30, from minimum to maximum probability of distress.

- **UGR C 0:** refers to the transversal direction of observation of the fixtures
- **UGR C 90:** refers to the longitudinal direction of observation of the fixtures.

Glare ratio reported in polar diagrams are calculated in relation to a local standard, as provided for by regulation CIE 117, having the following characteristics (Figure 1).

The size of the room as well as the distance between fixtures in both directions are specified in relation to the distance
H between the fixture plane and the observer plane (usually assumed to be equal to 1.2 m)
S Distance between fixtures in both directions equal to 0.25H
X longitudinal dimension of the room equal to 4H
Y transverse dimension of the room equal to 8H
Reflectance index of the ceiling, walls and floor, respectively, equal to 0.7, 0.5, 0.2

To aid better understanding, the UGR values reported in the polar diagram of the lighting fixtures have been grouped into the following illustrative classes by type of application, as specified in UNI EN 12464-1:

- <16 maximum viewing comfort
- <19 comfort required in offices
- <22 comfort required in other work places
- <25 need for reduced visual comfort
- <28 extremely low visual comfort

Luminance values

The UNI EN 12464-1 - Light and lighting - Lighting of workplaces - Part 1: internal workplaces - prescribes the boundary values of average luminance of the lighting equipment at elevation angles of 65° and above from the downward vertical, radially around the luminaires, for work stations where display screens which are vertical or inclined up to 15° tilt angle are used.



Figure 1

Case A
Flat screens operating at positive polarity with normal requirements concerning colour and details of the shown information, as used in office, education, etc.

Case B
To flat screens operating at negative polarity and/or with higher requirements concerning colour and details of the shown information, as used for CAD colour inspection, etc.



Screen high state luminance	High luminance screen > 200 cd/mq	Medium luminance screen ≤ 200 cd/mq
Case A	≤ 3000 cd/mq	≤ 1500 cd/mq
Case B	≤ 1500 cd/mq	≤ 1000 cd/mq

Index for code

COD.	PAG.
1E0388	576, 590, 593, 596, 599, 601, 603, 606, 610, 615, 617, 621
1E0990	640, 641, 643
1E0993	626, 630, 634, 636, 640, 715, 717, 720, 738, 740, 745, 753, 755, 796
1E0994	640, 641, 643
1E0995	723, 725
1E0995FE	721
1E0996	640, 641, 643
1E1001	639
1E1002	639
1E1008	639
1E1011	639
1E1012	639
1E1018	639
1E1021	639
1E1022	639
1E1028	639
1E1385	641, 723
1E1401	579, 642, 724, 816
1E1409	642
1E1410	724
1E1713	643, 725, 817
1E1715	817
1E1854	642
1E1855	724
1E1906	818
1E1929	818
1E2264	576
1E2265	576
1E2266	576
1E2267	581
1E2268	581
1E2269	581
1E2274	576
1E2275	576
1E2320	605, 609, 614, 620
1E2321	605, 609, 614, 620
1E2323	606, 610, 614, 620
1E2367	641
1E2368	641
1E2369	641
1E2370	641
1E2371	723
1E2372	723
1E2373	723
1E2374	723
1E2381	579
1E2382	578, 579
1E2383	578, 579
1E2386	589
1E2386AS	589
1E2386DA	589
1E2386DAAS	589
1E2387	589
1E2387AS	589
1E2387DA	589
1E2387DAAS	589
1E2388	595
1E2388AS	595
1E2388DA	595
1E2388DAAS	595

COD.	PAG.
1E2389	595
1E2389AS	595
1E2389DA	595
1E2389DAAS	595
1E2390	595
1E2390AS	595
1E2390DA	595
1E2390DAAS	595
1E2391	595
1E2391AS	595
1E2391DA	595
1E2391DAAS	595
1E2392	595
1E2392AS	595
1E2392DA	595
1E2392DAAS	595
1E2393	595
1E2393AS	595
1E2393DA	595
1E2393DAAS	595
1E2394	589, 592, 595, 598, 600, 602
1E2402	590, 593, 596
1E2493	797
1E2494	572, 590, 596, 599, 601, 607, 611, 615, 621, 627, 631, 635, 637, 645, 677, 687, 690, 695, 700, 704, 707, 715, 718, 721, 723, 735, 739, 741, 784, 789, 797
1E2495	552, 556, 590, 593, 596, 599, 600, 602, 606, 610, 615, 617, 621, 788
1E2496	590, 593, 596, 599, 600, 602
1E2497	604
1E2497DA	604
1E2498	604
1E2498DA	604
1E2499	604
1E2500	604
1E2501	608
1E2501DA	608
1E2502	608
1E2502DA	608
1E2503	608
1E2503DA	608
1E2504	608
1E2504DA	608
1E2505	608
1E2506	608
1E2507	608
1E2508	608
1E2509	612
1E2509DA	612
1E2510	612
1E2510DA	612
1E2511	612
1E2511DA	612
1E2512	612
1E2512DA	612
1E2513	612
1E2513DA	612
1E2514	612
1E2514DA	612
1E2515	612
1E2516	612
1E2517	612
1E2518	612
1E2519	613
1E2520	613
1E2521	605, 609, 613, 616, 619
1E2522	605, 609, 613, 616, 619
1E2523	606, 610, 614
1E2524	607, 611, 615, 617, 621

COD.	PAG.
1E2525	605, 609, 613, 617, 620
1E2525AS	605, 609, 613, 617, 620
1E2526	605, 609, 613, 617, 620
1E2526AS	605, 609, 613, 617, 620
1E2533	606, 610, 614, 620
1E2539	793
1E2540	793
1E2541	793
1E2542	793
1E2543	766
1E2544	767
1E2545	767
1E2546	767
1E2547	766
1E2548	767
1E2549	767
1E2550	767
1E2551	766
1E2552	766
1E2553	767
1E2554	767
1E2555	767
1E2556	766
1E2557	767
1E2558	767
1E2559	767
1E2560	766
1E2561	600
1E2561AS	600
1E2561DA	600
1E2561DAAS	600
1E2562	600
1E2562AS	600
1E2562DA	600
1E2562DAAS	600
1E2563	793
1E2564	792, 793
1E2565	302
1E2566	302
1E2567	302
1E2568	302
1E2569	302
1E2570	302
1E2571	303
1E2572	303
1E2573	303
1E2574	303, 694
1E2575	303, 768
1E2576	303, 768, 770, 772
1E2577	303, 768
1E2578	303, 768, 770, 772
1E2579	303, 768
1E2580	303, 768, 772
1E2581	651
1E2582	651
1E2583	651
1E2584	651
1E2585	651
1E2586	651
1E2587	651
1E2588	651
1E2589	652
1E2590	652
1E2591	652
1E2592	652
1E2593	652
1E2594	652
1E2595	652
1E2596	652
1E2597	653
1E2598	653
1E2599	653
1E2600	653
1E2601	653
1E2602	653
1E2603	653
1E2604	653

COD.	PAG.
1E2605	650
1E2606	650
1E2607	650
1E2608	650
1E2609	650
1E2610	650
1E2611	650
1E2612	650
1E2613	651
1E2614	651
1E2615	651
1E2616	651
1E2617	651
1E2618	651
1E2619	651
1E2620	651
1E2621	653
1E2622	653
1E2623	653
1E2624	653
1E2625	653
1E2626	653
1E2627	653
1E2628	653
1E2629	650
1E2630	650
1E2631	650
1E2632	650
1E2633	650
1E2634	650
1E2635	650
1E2636	650
1E2637	652
1E2638	652
1E2639	652
1E2640	652
1E2641	652
1E2642	652
1E2643	652
1E2644	652
1E2645	653
1E2646	653
1E2647	653
1E2648	653
1E2649	653
1E2650	653
1E2651	653
1E2652	653
1E2653	650
1E2654	650
1E2655	650
1E2656	650
1E2657	651
1E2658	651
1E2659	651
1E2660	651
1E2661	652
1E2662	652
1E2663	652
1E2664	652
1E2665	548
1E2666	548
1E2667	548
1E2668	548
1E2669	548
1E2670	548
1E2671	548
1E2672	548
1E2673	550
1E2674	550
1E2675	550
1E2676	550
1E2677	550
1E2678	550
1E2679	550
1E2680	550
1E2681	551
1E2682	551
1E2683	551
1E2684	551
1E2685	551
1E2686	551
1E2687	551
1E2688	551
1E2689	548
1E2690	548
1E2691	548
1E2692	548
1E2693	548
1E2694	548
1E2695	548
1E2696	548
1E2697	549
1E2698	549
1E2699	549
1E2700	549
1E2701	549
1E2702	549
1E2703	549
1E2704	549
1E2705	551
1E2706	551
1E2707	551
1E2708	551
1E2709	551
1E2710	551
1E2711	551
1E2712	551
1E2713	549
1E2714	549
1E2715	549
1E2716	549
1E2717	549
1E2718	549
1E2719	549
1E2720	549
1E2721	550
1E2722	550
1E2723	550
1E2724	550
1E2725	550
1E2726	550
1E2727	550
1E2728	550
1E2729	551
1E2730	551
1E2731	551
1E2732	551
1E2733	551
1E2734	551
1E2735	551
1E2736	551
1E2737	548
1E2738	548
1E2739	548
1E2740	548
1E2741	549
1E2742	549
1E2743	549
1E2744	549
1E2745	550
1E2746	550
1E2747	550
1E2748	550
1E2752	654, 659
1E2753	654, 659
1E2754	654, 659
1E2755	654, 659
1E2756	654, 659
1E2757	654, 659
1E2758	654, 659
1E2759	654, 659
1E2760	654, 659
1E2761	654, 659
1E2762	552, 655
1E2763	552, 655
1E2764	552, 655
1E2765	552, 655
1E2766	704, 705
1E2767	556, 594, 603, 618, 660, 702, 820
1E2768	592
1E2768AS	592
1E2769	552, 572, 590, 596, 599, 601, 607, 611, 615, 621, 627, 631, 635, 637, 645, 655, 660, 677, 687, 690, 695, 700, 704, 707, 715, 718, 721, 723, 735, 739, 741, 784, 789, 797
1E2770	645
1E2771	645
1E2772	645
1E2773	645
1E2774	645
1E2775	645
1E2779	698
1E2780	698
1E2781	698
1E2782	698
1E2783	698
1E2784	698
1E2785	698
1E2786	698
1E2806	699
1E2807	699
1E2820	700
1E2821	700
1E2822	700
1E2823	700, 702
1E2824	700, 702
1E2825	687, 690, 700, 702
1E2826	700, 702
1E2827	703
1E2828	703
1E2829	703
1E2830	703
1E2831	703
1E2832	703
1E2833	705
1E2834	705
1E2845	704, 706
1E2846	704, 706
1E2847	704, 706
1E2848	704, 706
1E2849	703
1E2850	703
1E2851	703
1E2852	703
1E2853	703
1E2854	704
1E2855	704, 705
1E2856	704, 705
1E2857	707
1E2858	707
1E2859	707
1E2860	707
1E2861	792
1E2862	792
1E2863	792
1E2864	792
1E2865	793
1E2866	793
1E2867	771
1E2868	771
1E2869	771
1E2870	771
1E2871	771
1E2872	771
1E2873	771
1E2874	771
1E2875	771
1E2876	771
1E2877	766
1E2878	767
1E2879	767
1E2880	767
1E2881	766
1E2882	766
1E2883	766
1E2884	767

COD.	PAG.
1E2885	767
1E2886	767
1E2887	766
1E2888	766
1E2889	766
1E2890	769
1E2891	769
1E2892	769
1E2893	769
1E2894	769
1E2895	769
1E2896	769
1E2897	769
1E2898	769
1E2899	769
1E2900	770
1E2901	768
1E2902	768
1E2906	768, 770
1E2907	770
1E2909	775
1E2910	775
1E2911	775
1E2912	775
1E2953	761
1E2954	761
1E2955	761
1E2956	761
1E2957	761
1E2958	761
1E2959	761
1E2960	761
1E2961	761
1E2967	788
1E2968	788
1E2969	788
1E2970	788
1E2971	788
1E2972	788
1E2978	698
1E2979	698
1E2980	699
1E2981	699
1E2982	699
1E2983	699
1E2984	699
1E2985	699
1E2986	693
1E2987	693
1E2988	693
1E2989	693
1E2990	693
1E2991	693
1E2992	693
1E2993	693
1E2994D	688
1E2994DA	688
1E2994EL	688
1E2995D	688
1E2995DA	688
1E2995EL	688
1E2996D	688
1E2996DA	688
1E2996EL	688
1E2997D	688
1E2997DA	688
1E2997EL	688
1E2998D	688
1E2998DA	688
1E2998EL	688
1E2999D	688
1E2999DA	688
1E2999EL	688
1E3000D	688
1E3000DA	688
1E3000EL	688
1E3001D	688
1E3001DA	688
1E3001EL	688
1E3002D	688
1E3002DA	688
1E3002EL	688
1E3003D	688
1E3003DA	688
1E3003EL	688
1E3004D	689
1E3004DA	689
1E3004EL	689
1E3005D	689
1E3005DA	689
1E3005EL	689
1E3006	694
1E3007	694
1E3008	694
1E3009	694
1E3010	694
1E3011	695
1E3012	694
1E3013	694
1E3014	694
1E3015	695
1E3016	695
1E3017	689
1E3018	689
1E3019	689
1E3020	689
1E3021	689
1E3022	690
1E3023	689
1E3024	689
1E3025	689
1E3026	686, 690
1E3027	690
1E3028	686, 690
1E3029	690
1E3033D	694
1E3033DA	694
1E3033EL	694
1E3034D	694
1E3034EL	694
1E3035	768, 770, 772
1E3036	768, 770, 772
1E3037	768, 770, 772
1E3038	768, 770, 772
1E3039	768, 770, 772
1E3040	793
1E3041	793
1E3042	793
1E3043	793
1E3044	793
1E3045	654, 659
1E3046	654, 659
1E3047	654, 659
1E3048	304, 552, 572, 591, 597, 599, 601, 607, 611, 615, 621, 627, 631, 635, 637, 655, 677, 687, 691, 695, 716, 719, 721, 735, 739, 741, 745, 753, 755, 759, 785, 797, 807, 813
1E3049	304, 552, 572, 591, 597, 599, 601, 607, 611, 615, 621, 627, 631, 635, 637, 655, 677, 687, 691, 695, 716, 719, 721, 735, 739, 741, 745, 753, 755, 759, 785, 797, 807, 813
1E3050	598
1E3050AS	598
1E3050DA	598
1E3050DAAS	598
1E3051	598
1E3051AS	598
1E3051DA	598
1E3051DAAS	598
1E3052	598
1E3052AS	598
1E3052DA	598
1E3052DAAS	598
1E3053	598
1E3053AS	598
1E3053DA	598
1E3053DAAS	598
1E3054	598
1E3054AS	598
1E3054DA	598
1E3054DAAS	598
1E3055	598
1E3055AS	598
1E3055DA	598
1E3055DAAS	598
1E3056EL	692
1E3057EL	692
1E3058EL	692
1E3059EL	692
1E3060EL	692
1E3061EL	692
1E3062EL	692
1E3063EL	692
1E3064D	684
1E3064DA	684
1E3064EL	684
1E3065D	684
1E3065DA	684
1E3065EL	684
1E3066D	684
1E3066DA	684
1E3066EL	684
1E3067D	685
1E3067DA	685
1E3067EL	685
1E3068D	685
1E3068DA	685
1E3068EL	685
1E3069D	685
1E3069DA	685
1E3069EL	685
1E3070D	684
1E3070DA	684
1E3070EL	684
1E3071D	684
1E3071DA	684
1E3071EL	684
1E3072D	684
1E3072DA	684
1E3072EL	684
1E3073D	685
1E3073DA	685
1E3073EL	685
1E3074D	685
1E3074DA	685
1E3074EL	685
1E3075D	685
1E3075DA	685
1E3075EL	685
1E3076D	684
1E3076DA	684
1E3076EL	684
1E3077D	684
1E3077DA	684
1E3077EL	684
1E3078D	685
1E3078DA	685
1E3078EL	685
1E3079D	685
1E3079DA	685
1E3079EL	685
1E3080D	685
1E3080DA	685
1E3080EL	685
1E3081D	686
1E3081DA	686
1E3081EL	686
1E3082D	684
1E3082DA	684
1E3082EL	684
1E3083D	684
1E3083DA	684
1E3083EL	684

COD.	PAG.
1E3084D	685
1E3084DA	685
1E3084EL	685
1E3085D	685
1E3085DA	685
1E3085EL	685
1E3086D	685
1E3086DA	685
1E3086EL	685
1E3087D	686
1E3087DA	686
1E3087EL	686
1E3093	687
1E3094	686
1E3095	686
1E3096	686
1E3097	687
1E3098	687
1E3099	553
1E3100	553
1E3101	553
1E3102	553
1E3103	554
1E3104	554
1E3105	554
1E3106	554
1E3107	555
1E3108	555
1E3109	555
1E3110	555
1E3111	656
1E3112	656
1E3113	656
1E3114	656
1E3115	657
1E3116	657
1E3117	657
1E3118	657
1E3119	658
1E3120	658
1E3121	658
1E3122	658
1E3123	602
1E3123AS	602
1E3124	701
1E3125	701
1E3126D	689
1E3126DA	689
1E3126EL	689
1E3127D	689
1E3127DA	689
1E3127EL	689
1E3144	634
1E3145	634
1E3146	636
1E3147	636
1E3148	744
1E3149	744
1E3150	744
1E3151	744
1E3152	744
1E3153	744
1E3154	744
1E3155	744
1E3156	744
1E3157	744
1E3158	744
1E3159	744
1E3160	744
1E3161	744
1E3162	744
1E3163	744
1E3164	744
1E3165	744
1E3166	745
1E316790	720
1E316890	720
1E316990	720
1E317090	720
1E317190	720
1E317290	720

COD.	PAG.
1E3173	701
1E3174	701
1E3177	634
1E3178	636
1E3179	626, 630, 634, 636, 715, 717, 720, 738, 740, 745, 753, 755, 796
1E3180	745
1E3181	745
1E3184	572, 593, 603, 660, 677, 739, 741
1E3185	792, 793
1E3187	687
1E3188	686
1E3189DA	759
1E3189EL	759
1E3190DA	759
1E3190EL	759
1E3191DA	759
1E3191EL	759
1E3192DA	734
1E3192EL	734
1E3195DA	734
1E3195EL	734
1E3198DA	734
1E3198EL	734
1E3201DA	734
1E3201EL	734
1E3204DA	734
1E3204EL	734
1E3207DA	734
1E3207EL	734
1E3210DA	734
1E3210EL	734
1E3213DA	734
1E3213EL	734
1E3216DA	734
1E3216EL	734
1E3219	734
1E3220	665
1E3221	665
1E3222	665
1E3223	665
1E3224	665
1E3225	665
1E3226	665
1E3227	665
1E3228	665
1E3229	665
1E3230	665
1E3231	665
1E3232	666
1E3233	666
1E3234	666
1E3235	666
1E3236	666
1E3237	666
1E3238	666
1E3239	666
1E3240	666
1E3241	666
1E3242	666
1E3243	666
1E3244	667
1E3245	667
1E3246	667
1E3247	667
1E3248	667
1E3249	667
1E3250	667
1E3251	667
1E3252	667
1E3253	667
1E3254	667
1E3255	667
1E3256	668
1E3257	668
1E3258	668
1E3259	668
1E3260	668

COD.	PAG.
1E3261	668
1E3262	668
1E3263	668
1E3264	668
1E3265	668
1E3266	668
1E3267	668
1E3268DA	672
1E3268EL	672
1E3269DA	672
1E3269EL	672
1E3270DA	672
1E3270EL	672
1E3271DA	672
1E3271EL	672
1E3272DA	672
1E3272EL	672
1E3273DA	672
1E3273EL	672
1E3274DA	672
1E3274EL	672
1E3275DA	672
1E3275EL	672
1E3276DA	672
1E3276EL	672
1E3277DA	672
1E3277EL	672
1E3278DA	672
1E3278EL	672
1E3279DA	672
1E3279EL	672
1E3280DA	672
1E3280EL	672
1E3281DA	672
1E3281EL	672
1E3282DA	672
1E3282EL	672
1E3283DA	672
1E3283EL	672
1E3284DA	673
1E3284EL	673
1E3285DA	673
1E3285EL	673
1E3286DA	673
1E3286EL	673
1E3287DA	673
1E3287EL	673
1E3288DA	673
1E3288EL	673
1E3289DA	673
1E3289EL	673
1E3290DA	673
1E3290EL	673
1E3291DA	673
1E3291EL	673
1E3292DA	673
1E3292EL	673
1E3293DA	673
1E3293EL	673
1E3294DA	673
1E3294EL	673
1E3295DA	673
1E3295EL	673
1E3296DA	673
1E3296EL	673
1E3297DA	673
1E3297EL	673
1E3298DA	673
1E3298EL	673
1E3299DA	673
1E3299EL	673
1E3300DA	674
1E3300EL	674
1E3301DA	674
1E3301EL	674
1E3302DA	674
1E3302EL	674
1E3303DA	674
1E3303EL	674
1E3304	676

COD.	PAG.
1E3305	572, 677, 716, 718, 735, 759, 785, 789
1E3306	676
1E3307	669
1E3308	669
1E3309	669
1E3310	669
1E3311	669
1E3312	669
1E3313	669
1E3314	669
1E3315	669
1E3316	669
1E3317	669
1E3318	669
1E3319	669
1E3320	669
1E3321	669
1E3322	669
1E3323	670
1E3324	670
1E3325	670
1E3326	670
1E3327	670
1E3328	670
1E3329	670
1E3330	670
1E3331	670
1E3332	670
1E3333	670
1E3334	670
1E3335	670
1E3336	670
1E3337	670
1E3338	670
1E3339	670
1E3340	670
1E3341	670
1E3342	670
1E3343	671
1E3344	671
1E3345	671
1E3346	671
1E3347	671
1E3348	671
1E3349	671
1E3350	671
1E3351	671
1E3352	671
1E3353	671
1E3354	671
1E3355DA	674
1E3355EL	674
1E3356DA	674
1E3356EL	674
1E3357DA	674
1E3357EL	674
1E3358DA	674
1E3358EL	674
1E3359DA	674
1E3359EL	674
1E3360DA	674
1E3360EL	674
1E3361DA	674
1E3361EL	674
1E3362DA	674
1E3362EL	674
1E3363DA	674
1E3363EL	674
1E3364DA	674
1E3364EL	674
1E3365DA	674
1E3365EL	674
1E3366DA	674
1E3366EL	674
1E3367DA	675
1E3367EL	675
1E3368DA	675
1E3368EL	675
1E3369DA	675
1E3369EL	675
1E3370DA	675
1E3370EL	675
1E3371DA	675
1E3371EL	675
1E3372DA	675
1E3372EL	675
1E3373DA	675
1E3373EL	675
1E3374DA	675
1E3374EL	675
1E3375DA	675
1E3375EL	675
1E3376DA	675
1E3376EL	675
1E3377DA	675
1E3377EL	675
1E3378DA	675
1E3378EL	675
1E3379DA	675
1E3379EL	675
1E3380DA	675
1E3380EL	675
1E3381DA	675
1E3381EL	675
1E3382DA	675
1E3382EL	675
1E3383DA	676
1E3383EL	676
1E3384DA	676
1E3384EL	676
1E3385DA	676
1E3385EL	676
1E3386DA	676
1E3386EL	676
1E3387DA	676
1E3387EL	676
1E3388DA	676
1E3388EL	676
1E3389DA	676
1E3389EL	676
1E3390DA	676
1E3390EL	676
1E3399	759
1E3404	578
1E3405	578
1E3406	578
1E3407	578
1E3410DA	783
1E3410EL	783
1E3411DA	783
1E3411EL	783
1E3412DA	783
1E3412EL	783
1E3413DA	783
1E3413EL	783
1E3414DA	783
1E3414EL	783
1E3415DA	783
1E3415EL	783
1E3416DA	783
1E3416EL	783
1E3417DA	783
1E3417EL	783
1E3418DA	783
1E3418EL	783
1E3419DA	783
1E3419EL	783
1E3420DA	783
1E3420EL	783
1E3421DA	783
1E3421EL	783
1E3422DA	782
1E3422EL	782
1E3423DA	782
1E3423EL	782
1E3424DA	782
1E3424EL	782
1E3425DA	782
1E3425EL	782
1E3426DA	782
1E3426EL	782
1E3427DA	782
1E3427EL	782
1E3428DA	782
1E3428EL	782
1E3429DA	782
1E3429EL	782
1E3430DA	782
1E3430EL	782
1E3431DA	782
1E3431EL	782
1E3432DA	782
1E3432EL	782
1E3433DA	782
1E3433EL	782
1E3434	784
1E3435	784
1E3436	784
1E3437	735
1E3438	735
1E3439	735
1E3440	734
1E3441	738
1E3442DA	738
1E3442EL	738
1E3443DA	738
1E3443EL	738
1E3444DA	738
1E3444EL	738
1E3445	738
1E3446	738
1E3447	738, 740
1E3448	784
1E3449	784
1E3450	735, 796
1E345190	624
1E345290	624
1E345390	624
1E345490	624
1E345590	624
1E345690	624
1E345790	624
1E345890	624
1E345990	624
1E3460	626
1E346190	628
1E346290	628
1E346390	628
1E346490	628
1E346590	628
1E346690	628
1E346790	628
1E346890	628
1E346990	628
1E3470	630
1E347190	624
1E347290	625
1E347390	625
1E347490	624
1E347590	625
1E347690	625
1E347790	624
1E347890	625
1E347990	625
1E348090	628
1E348190	629
1E348290	629
1E348390	628
1E348490	629
1E348590	629
1E348690	628
1E348790	629
1E348890	629
1E348990	625
1E349090	625
1E349190	625
1E349290	625
1E349390	625
1E349490	625
1E349590	625
1E349690	625
1E349790	625

COD.	PAG.
1E349890	629
1E349990	629
1E350090	629
1E350190	629
1E350290	629
1E350390	629
1E350490	629
1E350590	629
1E350690	629
1E3507	552, 556
1E3508	552, 556
1E3509	552, 556
1E3510	784
1E3511	740
1E3512DA	740
1E3512EL	740
1E3513	740
1E3514DA	740
1E3514EL	740
1E3515	740
1E3516DA	740
1E3516EL	740
1E3517	619
1E3517DA	619
1E3518	619
1E3518DA	619
1E3519	619
1E3520	619
1E3521DA	752
1E3521EL	752
1E3522	752
1E3523DA	752
1E3523EL	752
1E3524	752
1E3525DA	752
1E3525EL	752
1E3526	752
1E3527DA	752
1E3527EL	752
1E3528	752
1E3529DA	752
1E3529EL	752
1E3530	752
1E3531DA	752
1E3531EL	752
1E3532	752
1E3533DA	753
1E3533EL	753
1E3534	752
1E3535DA	753
1E3535EL	753
1E3536	752
1E3537DA	753
1E3537EL	753
1E3538	752
1E3539DA	754
1E3539EL	754
1E3540	754
1E3541DA	754
1E3541EL	754
1E3542	754
1E3543DA	754
1E3543EL	754
1E3544	754
1E3545DA	754
1E3545EL	754
1E3546	754
1E3547DA	754
1E3547EL	754
1E3548	754
1E3549DA	754
1E3549EL	754
1E3550	754
1E3551DA	755
1E3551EL	755
1E3552	754
1E3553DA	755
1E3553EL	755
1E3554	754
1E3555DA	755
1E3555EL	755
1E3556	754
1E3557	571, 676
1E3558	571, 676
1E3559	572, 676
1E3560	572, 676
1E3561	560
1E3562	560
1E3563	560
1E3564	560
1E3565	560
1E3566	560
1E3567	560
1E3568	560
1E3569	560
1E3570	560
1E3571	560
1E3572	560
1E3573	564
1E3574	564
1E3575	564
1E3576	564
1E3577	564
1E3578	564
1E3579	564
1E3580	564
1E3581	564
1E3582	564
1E3583	564
1E3584	564
1E3585	561
1E3586	561
1E3587	561
1E3588	561
1E3589	561
1E3590	561
1E3591	561
1E3592	561
1E3593	561
1E3594	561
1E3595	561
1E3596	561
1E3597	564
1E3598	564
1E3599	564
1E3600	564
1E3601	565
1E3602	565
1E3603	565
1E3604	565
1E3605	565
1E3606	565
1E3607	565
1E3608	565
1E3609	562
1E3610	562
1E3611	562
1E3612	562
1E3613	562
1E3614	562
1E3615	562
1E3616	562
1E3617	562
1E3618	562
1E3619	562
1E3620	562
1E3621	565
1E3622	565
1E3623	565
1E3624	565
1E3625	565
1E3626	565
1E3627	565
1E3628	565
1E3629	565
1E3630	565
1E3631	565
1E3632	565
1E3633	563
1E3634	563
1E3635	563
1E3636	563
1E3637	563
1E3638	563
1E3639	563
1E3640	563
1E3641	563
1E3642	563
1E3643	563
1E3644	563
1E3645	566
1E3646	566
1E3647	566
1E3648	566
1E3649	566
1E3650	566
1E3651	566
1E3652	566
1E3653	566
1E3654	566
1E3655	566
1E3656	566
1E3657DA	567
1E3657EL	567
1E3658DA	567
1E3658EL	567
1E3659DA	567
1E3659EL	567
1E3660DA	567
1E3660EL	567
1E3661DA	567
1E3661EL	567
1E3662DA	567
1E3662EL	567
1E3663DA	567
1E3663EL	567
1E3664DA	567
1E3664EL	567
1E3665DA	567
1E3665EL	567
1E3666DA	567
1E3666EL	567
1E3667DA	567
1E3667EL	567
1E3668DA	567
1E3668EL	567
1E3669DA	569
1E3669EL	569
1E3670DA	569
1E3670EL	569
1E3671DA	569
1E3671EL	569
1E3672DA	569
1E3672EL	569
1E3673DA	569
1E3673EL	569
1E3674DA	569
1E3674EL	569
1E3675DA	569
1E3675EL	569
1E3676DA	569
1E3676EL	569
1E3677DA	569
1E3677EL	569
1E3678DA	569
1E3678EL	569
1E3679DA	569
1E3679EL	569
1E3680DA	569
1E3680EL	569
1E3681DA	567
1E3681EL	567
1E3682DA	567
1E3682EL	567
1E3683DA	567
1E3683EL	567
1E3684DA	567
1E3684EL	567
1E3685DA	568
1E3685EL	568
1E3686DA	568
1E3686EL	568
1E3687DA	568

COD.	PAG.
1E3687EL	568
1E3688DA	568
1E3688EL	568
1E3689DA	568
1E3689EL	568
1E3690DA	568
1E3690EL	568
1E3691DA	568
1E3691EL	568
1E3692DA	568
1E3692EL	568
1E3693DA	570
1E3693EL	570
1E3694DA	570
1E3694EL	570
1E3695DA	570
1E3695EL	570
1E3696DA	570
1E3696EL	570
1E3697DA	570
1E3697EL	570
1E3698DA	570
1E3698EL	570
1E3699DA	570
1E3699EL	570
1E3700DA	570
1E3700EL	570
1E3701DA	570
1E3701EL	570
1E3702DA	570
1E3702EL	570
1E3703DA	570
1E3703EL	570
1E3704DA	570
1E3704EL	570
1E3705DA	568
1E3705EL	568
1E3706DA	568
1E3706EL	568
1E3707DA	568
1E3707EL	568
1E3708DA	568
1E3708EL	568
1E3709DA	568
1E3709EL	568
1E3710DA	568
1E3710EL	568
1E3711DA	568
1E3711EL	568
1E3712DA	568
1E3712EL	568
1E3713DA	569
1E3713EL	569
1E3714DA	569
1E3714EL	569
1E3715DA	569
1E3715EL	569
1E3716DA	569
1E3716EL	569
1E3717DA	570
1E3717EL	570
1E3718DA	570
1E3718EL	570
1E3719DA	570
1E3719EL	570
1E3720DA	570
1E3720EL	570
1E3721DA	571
1E3721EL	571
1E3722DA	571
1E3722EL	571
1E3723DA	571
1E3723EL	571
1E3724DA	571
1E3724EL	571
1E3725DA	571
1E3725EL	571
1E3726DA	571
1E3726EL	571
1E3727DA	571
1E3727EL	571
1E3728DA	571
1E3728EL	571
1E3729	571
1E3730	571
1E3731	571
1E3732	571
1E3733	571
1E3734	571
1E3735	571
1E3736	796
1E3737	796
1E3738	796
1E3739	796
1E3740	796
1E3741	796
1E3742	744
1E3743	744
1E3744	744
1E3745	744
1E3746	744
1E3747	744
1E3748	744
1E3749	744
1E3750	744
1E3751	744
1E3752	744
1E3753	744
1E3754	744
1E3755	744
1E3756	744
1E3757	744
1E3758	744
1E3759	744
1E3760DA	734
1E3760EL	734
1E3761DA	734
1E3761EL	734
1E3762DA	734
1E3762EL	734
1E3763	738
1E3764DA	738
1E3764EL	738
1E3765	740
1E3766DA	740
1E3766EL	740
1E376790	717
1E376890	717
1E376990	717
1E377090	717
1E377190	717
1E377290	717
1E377390	714
1E377490	714
1E377590	714
1E377690	714
1E377790	714
1E377890	714
1E377990	714
1E378090	714
1E378190	714
1E378290	714
1E378390	714
1E378490	714
1E3785	714, 717
1E3786	714, 717
1E3787	718
1E3788	715
1E3789	718
1E3790	715
1E3791	718
1E3792	715
1E3793	718
1E3794	718
1E3795	718
1E3796	718
1E3797	718
1E3798	715
1E3799	715
1E3800	715
1E3801	715
1E3802	715
1E3803	714, 717
1E3804	714, 717
1E3805	718
1E3806	715
1E3807	665
1E3808	665
1E3809	665
1E3810	665
1E3811	666
1E3812	666
1E3813	666
1E3814	666
1E3815	667
1E3816	667
1E3817	667
1E3818	667
1E3819	668
1E3820	668
1E3821	668
1E3822	668
1E3823DA	671
1E3823EL	671
1E3824DA	671
1E3824EL	671
1E3825DA	671
1E3825EL	671
1E3826DA	671
1E3826EL	671
1E3827DA	672
1E3827EL	672
1E3828DA	672
1E3828EL	672
1E3829DA	672
1E3829EL	672
1E3830DA	672
1E3830EL	672
1E3831DA	673
1E3831EL	673
1E3832DA	673
1E3832EL	673
1E3833DA	673
1E3833EL	673
1E3834DA	673
1E3834EL	673
1E3835	560
1E3836	560
1E3837	560
1E3838	560
1E3839	561
1E3840	561
1E3841	561
1E3842	561
1E3843	562
1E3844	562
1E3845	562
1E3846	562
1E3847	563
1E3848	563
1E3849	563
1E3850	563
1E3851DA	566
1E3851EL	566
1E3852DA	566
1E3852EL	566
1E3853DA	566
1E3853EL	566
1E3854DA	566
1E3854EL	566
1E3855DA	567
1E3855EL	567
1E3856DA	567
1E3856EL	567
1E3857DA	567
1E3857EL	567
1E3858DA	567
1E3858EL	567
1E3859DA	568
1E3859EL	568
1E3860DA	568
1E3860EL	568
1E3861DA	568

COD.	PAG.
1E3861EL	568
1E3862DA	568
1E3862EL	568
1E3867	616
1E3868	616
1E3869	616
1E3871	617
1E3872	739, 741
1E3873	739, 741
1E387590	717
1E387690	717
1E387790	714
1E387890	714
1E387990	714
1E388090	714
1E3881	617
1T0123	506, 509, 511
1T0123DA	506, 509, 511
1T0124	506, 509, 512
1T0124DA	506, 509, 512
1T0130	506, 509, 511
1T0130DA	506, 509, 511
1T1696	590, 593, 596
1T1699	590, 593, 596
1T1700	590, 596
1T1701	590, 596
1T1702	590, 596
1T1703	590, 596
1T1704	590, 596
1T1708	134, 178, 235, 251, 273, 606, 610, 614
1T1709	134, 178, 235, 251, 273
1T1711	134, 179, 235, 252, 274, 606, 610, 614
1T1712	178, 251, 273, 606, 610, 614
1T1713	178, 251, 273, 606, 610, 614
1T1714	178, 251, 273, 606, 610, 614
1T1715	178, 251, 273, 606, 610, 614
1T1716	178, 251, 273, 606, 610, 614
1T1757	324
1T1898	556, 580, 594, 603, 618, 643, 660, 702, 706, 725, 819
1T1932	580, 706, 817
1T2219	252, 263, 266, 277, 513
1T2220	252, 263, 266, 277, 513
1T2221	252, 263, 266, 277, 513
1T2222	253, 264, 266, 277, 513
1T2223	253, 264, 266, 277, 513
1T2224	253, 264, 266, 277, 513
1T2245	579, 642, 724, 817
1T2266	817
1T2963	317
1T2965	317
1T2966	303, 317, 324
1T2968	303, 317, 324
1T3140	262, 265, 318
1T3141	262, 265, 318
1T3142	134, 179, 235, 252, 263, 266, 274, 319
1T3143	179, 252, 263, 266, 274, 319
1T3144	94, 97, 99, 101, 102, 108, 110, 111, 180, 185, 194, 198, 201, 303, 319, 325
1T3162	505
1T3163	505
1T3164	505
1T3165	505
1T3166	508
1T3167	508
1T3168	508
1T3169	508
1T3170	511
1T3171	511
1T3172	511
1T3173	511
1T3174	505
1T3175	505
1T3176	505
1T3177	505
1T3178	508
1T3179	508
1T3180	508
1T3181	508
1T3182	505
1T3183	505
1T3184	505
1T3185	505
1T3186	508
1T3187	508
1T3188	508
1T3189	508
1T3190	511
1T3191	511
1T3192	511
1T3193	511
1T3194	505
1T3195	505
1T3196	505
1T3197	505
1T3198	508
1T3199	508
1T3200	508
1T3201	508
1T3202	505
1T3203	505
1T3204	505
1T3205	505
1T3206	508
1T3207	508
1T3208	508
1T3209	508
1T3210	511
1T3211	511
1T3212	511
1T3213	511
1T3218	508
1T3219	508
1T3220	508
1T3221	508
1T3222	505
1T3223	505
1T3224	505
1T3225	505
1T3226	508
1T3227	508
1T3228	508
1T3229	508
1T3230	511
1T3231	511
1T3232	511
1T3233	511
1T3238	508
1T3239	508
1T3240	508
1T3241	508
1T3242DA	506, 509, 512
1T3243	506, 509, 511
1T3244	506, 509, 512
1T3245	506, 509, 512
1T3246	506, 509, 512
1T3247	506, 509, 512
1T3248	507, 510, 512
1T3249	507, 510, 512
1T3250	507, 510, 512
1T3251	510
1T3272	503
1T3273	503
1T3274	503
1T3275	503
1T3296	503
1T3297	503
1T3298	503
1T3299	503
1T3320	503
1T3321	503
1T3322	503
1T3323	503
1T3344	503
1T3345	503
1T3346	503
1T3347	503
1T3423	263, 266, 318
1T3424	262, 318
1T3425	262, 318
1T3426	262, 318
1T3427	262, 318
1T3428	262, 318
1T3432	179, 252, 263, 266, 274, 318
1T3449	506, 509, 512
1T3450	506, 509, 512
1T3451	506, 509, 512
1T3452	506, 509, 512
1T3453	506, 509, 512
1T3454	506, 509, 512
1T3483	260
1T3484	260
1T3485	260
1T3486	260
1T3491	260
1T3492	260
1T3493	260
1T3494	260
1T3499	260
1T3500	260
1T3501	260
1T3502	260
1T3586	578, 626, 630, 634, 636, 715, 717, 720, 738, 740, 745, 753, 755, 796
1T3587	626, 630, 634, 636, 715, 717, 720, 738, 740, 745, 753, 755, 796
1T3588	626, 630, 634, 636, 715, 717, 720, 738, 740, 745, 753, 755, 796
1T3625	303
1T3627	303
1T3684	270
1T3684DA	270
1T3685	270
1T3685DA	270
1T3686	270
1T3686DA	270
1T3687	270
1T3687DA	270
1T3692	270
1T3692DA	270
1T3693	270
1T3693DA	270
1T3694	271
1T3694DA	271
1T3695	271
1T3695DA	271
1T3696	271
1T3726	626, 630, 634, 636, 715, 717, 720, 738, 740, 745, 753, 755
1T3727	134, 179, 235, 252, 274, 615
1T3759	535
1T3760	535
1T3762	535
1T3763	535
1T3781	317

COD.	PAG.
1T3783	317
1T3966	324
1T3978	521
1T3979	520
1T3980	520
1T3985	520
1T3986	520
1T3991	520
1T3992	520
1T4002	538
1T4003	539
1T4004	539
1T4005	543
1T4006	543
1T4061	503
1T4062	503
1T4063	470
1T4065	470
1T4067	470
1T4069	470
1T4071	470
1T4072	470
1T4075	470
1T4076	523
1T4077	523
1T4082	523
1T4083	523
1T4088	523
1T4089	523
1T4170	533
1T4171	533
1T4172	533
1T4173	533
1T4174	533
1T4175	533
1T4176	533
1T4177	533
1T4186	477
1T4187	477
1T4188	477
1T4189	478
1T4190	480
1T4191	480
1T4192	531
1T4193	531
1T4194	531
1T4195	531
1T4197	272
1T4197DA	272
1T4198	272
1T4198DA	272
1T4199	272
1T4199DA	272
1T4201	272
1T4201DA	272
1T4202	272
1T4202DA	272
1T4203	272
1T4203DA	272
1T4215D	694
1T4215DA	694
1T4215EL	694
1T4240	470
1T4241	470
1T4242	470
1T4243	470
1T4244	470
1T4245	471
1T4246	471
1T4247	471
1T4248	471
1T4249	270
1T4249DA	270
1T4250	270
1T4250DA	270
1T4251	270
1T4251DA	270
1T4252	270
1T4252DA	270
1T4253	271
1T4253DA	271
1T4254	271
1T4254DA	271
1T4255	271
1T4255DA	271
1T4256	271
1T4256DA	271
1T4257	272
1T4257DA	272
1T4258	272
1T4258DA	272
1T4259	273
1T4259DA	273
1T4260	272
1T4260DA	272
1T4261	272
1T4261DA	272
1T4262	273
1T4262DA	273
1T4322	124, 137, 145, 185, 241, 257, 276, 325, 393
1T4324	185, 257, 276, 325
1T4325	185, 257, 276, 325
1T4369	260
1T4370	260
1T4373	260
1T4374	260
1T4377	260
1T4378	260
1T4381	260
1T4381CA	261
1T4382	260
1T4382CA	261
1T4385	260
1T4385CA	261
1T4386	260
1T4386CA	261
1T4389	260
1T4389CA	261
1T4390	260
1T4390CA	261
1T4439CA	265
1T4440CA	265
1T4441CA	265
1T4442CA	265
1T4443CA	265
1T4444CA	265
1T4445CA	265
1T4446CA	265
1T4447CA	265
1T4448CA	265
1T4449CA	265
1T4450CA	265
1T4455	505
1T4456	505
1T4457	505
1T4458	505
1T4459	508
1T4460	508
1T4461	508
1T4462	508
1T4463	511
1T4464	511
1T4465	506, 509, 511
1T4466	506, 509, 511
1T4467	506, 509, 511
1T4469	506, 509, 512
1T4470	506, 509, 512
1T4472	506, 509, 512
1T4473	506, 509, 512
1T4475	506, 509, 512
1T4476	506, 509, 512
1T4478	506, 509, 512
1T4479	506, 509, 512
1T4499	529
1T4499CA	529
1T4506	529
1T4507	529
1T4512	527
1T4513	527
1T4514	527
1T4515	527
1T4522	474
1T4523	474
1T4524	474
1T4525	474
1T4526	322
1T4527	322
1T4528	320
1T4529	320
1T4530	322
1T4531	322
1T4532	320
1T4533	320
1T4538	322
1T4539	322
1T4540	323
1T4541	320
1T4542	321
1T4543	321
1T4544	322
1T4545	322
1T4546	323
1T4547	320
1T4548	321
1T4549	321
1T4550	322
1T4551	323
1T4552	321
1T4553	321
1T4554	322
1T4555	323
1T4556	321
1T4557	321
1T4558	313
1T4559	313
1T4560	309
1T4561	310
1T4562	313
1T4563	313
1T4564	309
1T4565	310
1T4566	313
1T4567	314
1T4568	314
1T4569	310
1T4570	310
1T4571	311
1T4572	313
1T4573	314
1T4574	314
1T4575	310
1T4576	310
1T4577	311
1T4578	313
1T4579	314
1T4580	314
1T4581	310
1T4582	311
1T4583	311
1T4584	313
1T4585	314
1T4586	314
1T4587	310
1T4588	311
1T4589	311
1T4590	314
1T4591	315
1T4592	311
1T4593	311
1T4594	314
1T4595	315
1T4596	311
1T4597	311
1T4598	314
1T4599	315
1T4600	311
1T4601	312
1T4602	314
1T4603	315
1T4604	311
1T4605	312

COD.	PAG.
1T4606	316, 323
1T4607	316, 323
1T4608	323
1T4609	323
1T4609CA	323
1T4610	323
1T4611	323
1T4611CA	323
1T4612	317
1T4613	317
1T4613CA	317
1T4614	317, 323
1T4615	317, 323
1T4615CA	317, 323
1T4616	317
1T4617	317
1T4617CA	317
1T4618	323
1T4619	323
1T4619CA	323
1T4620	323
1T4621	323
1T4621CA	323
1T4622	317
1T4623	317
1T4623CA	317
1T4624	317, 323
1T4625	317, 323
1T4625CA	317, 323
1T4626	317
1T4627	317
1T4627CA	317
1T4628	316, 323
1T4629	316, 323
1T4630	324
1T4631	324
1T4632	302
1T4633	302
1T4634	302
1T4635	302
1T4636	302
1T4637	302
1T4638	303
1T4639	303
1T4640	303
1T4641	303
1T4642	303
1T4643	303
1T4721	124, 137, 145, 184, 241, 256, 275, 324, 393
1T4722	321
1T4724	320
1T4726	321
1T4728	320
1T4754DA	197
1T4754EL	197
1T4755DA	197
1T4755EL	197
1T4756DA	197
1T4756EL	197
1T4757DA	197
1T4757EL	197
1T4758DA	197
1T4758EL	197
1T4759DA	197
1T4759EL	197
1T4760DA	197
1T4760EL	197
1T4761DA	197
1T4761EL	197
1T4762EL	515
1T4763EL	515
1T4764EL	515
1T4765EL	515
1T4766EL	515
1T4767EL	515
1T4768EL	515
1T4769EL	515
1T4770DA	201
1T4770EL	201
1T4771DA	201
1T4771EL	201
1T4772DA	201
1T4772EL	201
1T4773DA	201
1T4773EL	201
1T4774DA	201
1T4774EL	201
1T4775DA	201
1T4775EL	201
1T4776DA	201
1T4776EL	201
1T4777DA	201
1T4777EL	201
1T4781	312
1T4782	312
1T4783	312
1T4784	312
1T4785	309
1T4786	309
1T4787	309
1T4788	309
1T4878	260
1T4879	260
1T4880	260
1T4881	260
1T4882	260
1T4883	260
1T4884	260
1T4885	260
1T4886	260
1T4887	260
1T4888	260
1T4889	260
1T4890	260
1T4891	260
1T4892	260
1T4893	260
1T4894	260
1T4895	260
1T4896	260
1T4896CA	261
1T4897	260
1T4897CA	261
1T4898	260
1T4898CA	261
1T4899	260
1T4899CA	261
1T4900	260
1T4900CA	261
1T4901	260
1T4901CA	261
1T4926DA	181
1T4926EL	181
1T4927DA	181
1T4927EL	181
1T4928DA	181
1T4928EL	181
1T4929DA	181
1T4929EL	181
1T4930DA	181
1T4930EL	181
1T4931DA	181
1T4931EL	181
1T4932DA	181
1T4932EL	181
1T4933DA	181
1T4933EL	181
1T4934DA	181
1T4934EL	181
1T4935DA	181
1T4935EL	181
1T4936DA	181
1T4936EL	181
1T4937DA	181
1T4937EL	181
1T4938DA	181
1T4938EL	181
1T4939DA	181
1T4939EL	181
1T4940DA	181
1T4940EL	181
1T4941DA	181
1T4941EL	181
1T4942DA	181
1T4942EL	181
1T4943DA	181
1T4943EL	181
1T4944DA	182
1T4944EL	182
1T4945DA	182
1T4945EL	182
1T4946DA	182
1T4946EL	182
1T4947DA	182
1T4947EL	182
1T4948DA	181
1T4948EL	181
1T4949DA	181
1T4949EL	181
1T4950DA	182
1T4950EL	182
1T4951DA	182
1T4951EL	182
1T4952DA	182
1T4952EL	182
1T4953DA	182
1T4953EL	182
1T5010DA	255
1T5010EL	254
1T5011DA	255
1T5011EL	254
1T5012DA	255
1T5012EL	254
1T5013DA	255
1T5013EL	254
1T5014DA	255
1T5014EL	254
1T5015DA	255
1T5015EL	254
1T5016DA	255
1T5016EL	254
1T5017DA	255
1T5017EL	254
1T5018DA	255
1T5018EL	254
1T5019DA	255
1T5019EL	254
1T5020DA	255
1T5020EL	254
1T5021DA	255
1T5021EL	254
1T5022DA	255
1T5022EL	254
1T5023DA	255
1T5023EL	254
1T5024DA	256
1T5024EL	254
1T5025DA	256
1T5025EL	254
1T5026DA	256
1T5026EL	255
1T5027DA	256
1T5027EL	255
1T5028DA	255
1T5028EL	254
1T5029DA	255
1T5029EL	254
1T5030DA	256
1T5030EL	254
1T5031DA	256
1T5031EL	254
1T5032DA	256
1T5032EL	255
1T5033DA	256
1T5033EL	255
1T5034DA	248
1T5034EL	248
1T5035DA	248
1T5035EL	248
1T5036DA	248
1T5036EL	248

COD.	PAG.
1T5037DA	248
1T5037EL	248
1T5038DA	248
1T5038EL	248
1T5039DA	248
1T5039EL	248
1T5040DA	248
1T5040EL	248
1T5041DA	248
1T5041EL	248
1T5042DA	248
1T5042EL	248
1T5043DA	249
1T5043EL	249
1T5044DA	248
1T5044EL	248
1T5045DA	249
1T5045EL	249
1T5046DA	249
1T5046EL	249
1T5047DA	249
1T5047EL	249
1T5048DA	249
1T5048EL	249
1T5049DA	249
1T5049EL	249
1T5050DA	248
1T5050EL	248
1T5051DA	248
1T5051EL	248
1T5052DA	248
1T5052EL	248
1T5053DA	248
1T5053EL	248
1T5054DA	248
1T5054EL	248
1T5055DA	248
1T5055EL	248
1T5056DA	248
1T5056EL	248
1T5057DA	248
1T5057EL	248
1T5058DA	248
1T5058EL	248
1T5059DA	249
1T5059EL	249
1T5060DA	248
1T5060EL	248
1T5061DA	249
1T5061EL	249
1T5062DA	249
1T5062EL	249
1T5063DA	249
1T5063EL	249
1T5064DA	249
1T5064EL	249
1T5065DA	249
1T5065EL	249
1T5066DA	249
1T5066EL	249
1T5067DA	249
1T5067EL	249
1T5068DA	249
1T5068EL	249
1T5069DA	249
1T5069EL	249
1T5070DA	249
1T5070EL	249
1T5071DA	250
1T5071EL	250
1T5072DA	249
1T5072EL	249
1T5073DA	250
1T5073EL	250
1T5074DA	250
1T5074EL	250
1T5075DA	250
1T5075EL	250
1T5076DA	250
1T5076EL	250
1T5077DA	250
1T5077EL	250
1T5078DA	250
1T5078EL	250
1T5079DA	250
1T5079EL	250
1T5080DA	250
1T5080EL	250
1T5081DA	250
1T5081EL	250
1T5082DA	249
1T5082EL	249
1T5083DA	249
1T5083EL	249
1T5084DA	249
1T5084EL	249
1T5085DA	249
1T5085EL	249
1T5086DA	249
1T5086EL	249
1T5087DA	250
1T5087EL	250
1T5088DA	249
1T5088EL	249
1T5089DA	250
1T5089EL	250
1T5090DA	250
1T5090EL	250
1T5091DA	250
1T5091EL	250
1T5092DA	250
1T5092EL	250
1T5093DA	250
1T5093EL	250
1T5094DA	250
1T5094EL	250
1T5095DA	250
1T5095EL	250
1T5096DA	250
1T5096EL	250
1T5097DA	250
1T5097EL	250
1T5098DA	172
1T5098EL	172
1T5099DA	172
1T5099EL	172
1T5100DA	172
1T5100EL	172
1T5101DA	172
1T5101EL	172
1T5102DA	172
1T5102EL	172
1T5103DA	172
1T5103EL	172
1T5104DA	172
1T5104EL	172
1T5105DA	172
1T5105EL	172
1T5106DA	172
1T5106EL	172
1T5107DA	173
1T5107EL	173
1T5108DA	172
1T5108EL	172
1T5109DA	173
1T5109EL	173
1T5110DA	173
1T5110EL	173
1T5111DA	173
1T5111EL	173
1T5112DA	173
1T5112EL	173
1T5113DA	173
1T5113EL	173
1T5114DA	172
1T5114EL	172
1T5115DA	172
1T5115EL	172
1T5116DA	172
1T5116EL	172
1T5117DA	172
1T5117EL	172
1T5118DA	172
1T5118EL	172
1T5119DA	172
1T5119EL	172
1T5120DA	172
1T5120EL	172
1T5121DA	172
1T5121EL	172
1T5122DA	172
1T5122EL	172
1T5123DA	173
1T5123EL	173
1T5124DA	172
1T5124EL	172
1T5125DA	173
1T5125EL	173
1T5126DA	173
1T5126EL	173
1T5127DA	173
1T5127EL	173
1T5128DA	173
1T5128EL	173
1T5129DA	173
1T5129EL	173
1T5130DA	173
1T5130EL	173
1T5131DA	173
1T5131EL	173
1T5132DA	173
1T5132EL	173
1T5133DA	173
1T5133EL	173
1T5134DA	173
1T5134EL	173
1T5135DA	174
1T5135EL	174
1T5136DA	173
1T5136EL	173
1T5137DA	174
1T5137EL	174
1T5138DA	174
1T5138EL	174
1T5139DA	174
1T5139EL	174
1T5140DA	174
1T5140EL	174
1T5141DA	174
1T5141EL	174
1T5142DA	174
1T5142EL	174
1T5143DA	174
1T5143EL	174
1T5144DA	174
1T5144EL	174
1T5145DA	174
1T5145EL	174
1T5146DA	173
1T5146EL	173
1T5147DA	173
1T5147EL	173
1T5148DA	173
1T5148EL	173
1T5149DA	173
1T5149EL	173
1T5150DA	173
1T5150EL	173
1T5151DA	174
1T5151EL	174
1T5152DA	173
1T5152EL	173
1T5153DA	174
1T5153EL	174
1T5154DA	174
1T5154EL	174
1T5155DA	174
1T5155EL	174
1T5156DA	174
1T5156EL	174
1T5157DA	174
1T5157EL	174
1T5158DA	174

COD.	PAG.
1T5158EL	174
1T5159DA	174
1T5159EL	174
1T5160DA	174
1T5160EL	174
1T5161DA	174
1T5161EL	174
1T5295D	694
1T5295EL	158, 165, 694
1T5296	322
1T5297	322
1T5298	320
1T5299	320
1T5300	313
1T5301	313
1T5302	310
1T5303	310
1T5304	313
1T5305	313
1T5306	310
1T5307	310
1T5308	312
1T5309	312
1T5310	312
1T5311	312
1T5312	309
1T5313	309
1T5314	309
1T5315	309
1T5321	270
1T5321DA	270
1T5322	270
1T5322DA	270
1T5323	270
1T5323DA	270
1T5324	270
1T5324DA	270
1T5325	270
1T5325DA	270
1T5326	270
1T5326DA	270
1T5327	271
1T5327DA	271
1T5328	271
1T5328DA	271
1T5329	270
1T5329DA	270
1T5330	270
1T5330DA	270
1T5331	270
1T5331DA	270
1T5332	270
1T5332DA	270
1T5333	271
1T5333DA	271
1T5334	271
1T5334DA	271
1T5335	271
1T5335DA	271
1T5336	271
1T5336DA	271
1T5337	272
1T5337DA	272
1T5338	272
1T5338DA	272
1T5339	272
1T5339DA	272
1T5340	272
1T5340DA	272
1T5341	272
1T5341DA	272
1T5342	272
1T5342DA	272
1T5343	272
1T5343DA	272
1T5344	272, 806
1T5344DA	272
1T5345	273
1T5345DA	273
1T5346	272
1T5346DA	272
1T5347	272
1T5347DA	272
1T5348	273
1T5348DA	273
1T5349	79, 83, 94, 97, 99, 101, 103, 109, 110, 111, 121, 124, 126, 127, 134, 137, 142, 145, 158, 165, 169, 180, 185, 190, 194, 198, 201, 295, 298, 299, 304, 319, 325, 422, 432, 445, 453, 459, 467, 471, 488, 501, 503, 507, 510, 513, 527, 529, 806, 812
1T5349DA8	97, 100, 807
1T5350	806
1T5351	517, 521, 535, 539, 543, 807, 812
1T5352	79, 83, 94, 97, 99, 101, 103, 109, 110, 111, 121, 124, 126, 127, 134, 137, 142, 145, 158, 165, 180, 185, 190, 194, 198, 201, 235, 238, 241, 295, 298, 299, 304, 319, 325, 385, 422, 432, 445, 453, 459, 467, 471, 474, 488, 501, 503, 507, 510, 513, 527, 529, 807, 812, 813
1T5352DA8	97, 100, 807
1T5406DA	197
1T5406EL	197
1T5407DA	197
1T5407EL	197
1T5408DA	197
1T5408EL	197
1T5409DA	197
1T5409EL	197
1T5410DA	197
1T5410EL	197
1T5411DA	197
1T5411EL	197
1T5412DA	197
1T5412EL	197
1T5413DA	197
1T5413EL	197
1T5414EL	515
1T5415EL	515
1T5416EL	515
1T5417EL	515
1T5418EL	515
1T5419EL	515
1T5420EL	515
1T5421EL	515
1T5430	521
1T5431DA	80
1T5431EL	80
1T5432DA	80
1T5432EL	80
1T5433DA	80
1T5433EL	80
1T5434DA	80
1T5434EL	80
1T5435DA	80
1T5435EL	80
1T5436DA	80
1T5436EL	80
1T5437DA	80
1T5437EL	80
1T5438DA	80
1T5438EL	80
1T5439DA	80
1T5439EL	80
1T5440DA	80
1T5440EL	80
1T5441DA	81
1T5441EL	81
1T5442DA	81
1T5442EL	81
1T5443DA	81
1T5443EL	81
1T5444DA	81
1T5444EL	81
1T5445DA	81
1T5445EL	81
1T5446DA	81
1T5446EL	81
1T5447DA	81
1T5447EL	81
1T5448DA	81
1T5448EL	81
1T5449DA	81
1T5449EL	81
1T5450DA	81
1T5450EL	81
1T5451DA	82
1T5451EL	82
1T5452DA	82
1T5452EL	82
1T5453DA	82
1T5453EL	82
1T5454DA	82
1T5454EL	82
1T5455DA	82
1T5455EL	82
1T5456DA	82
1T5456EL	82
1T5457DA	82
1T5457EL	82
1T5458DA	82
1T5458EL	82
1T5459DA	82
1T5459EL	82
1T5460DA	82
1T5460EL	82
1T5461DA	434
1T5461EL	434
1T5462DA	434
1T5462EL	434
1T5463DA	434
1T5463EL	434
1T5464DA	434
1T5464EL	434
1T5465DA	434
1T5465EL	434
1T5466DA	434
1T5466EL	434
1T5467DA	434
1T5467EL	434
1T5468DA	434
1T5468EL	434
1T5469DA	434
1T5469EL	434
1T5470DA	434
1T5470EL	434
1T5471DA	435
1T5471EL	435
1T5472DA	435
1T5472EL	435
1T5473DA	435
1T5473EL	435
1T5474DA	435
1T5474EL	435
1T5475DA	435
1T5475EL	435
1T5476DA	435
1T5476EL	435
1T5477DA	435
1T5477EL	435
1T5478DA	435
1T5478EL	435
1T5479DA	435
1T5479EL	435
1T5480DA	435
1T5480EL	435
1T5481DA	436
1T5481EL	436
1T5482DA	436

COD.	PAG.
1T5482EL	436
1T5483DA	436
1T5483EL	436
1T5484DA	436
1T5484EL	436
1T5485DA	436
1T5485EL	436
1T5486DA	436
1T5486EL	436
1T5487DA	436
1T5487EL	436
1T5488DA	436
1T5488EL	436
1T5489DA	436
1T5489EL	436
1T5490DA	436
1T5490EL	436
1T5491DA	462
1T5491EL	462
1T5492DA	462
1T5492EL	462
1T5493DA	462
1T5493EL	462
1T5494DA	462
1T5494EL	462
1T5495DA	462
1T5495EL	462
1T5496DA	462
1T5496EL	462
1T5497DA	462
1T5497EL	462
1T5498DA	462
1T5498EL	462
1T5499DA	462
1T5499EL	462
1T5500DA	462
1T5500EL	462
1T5501DA	462
1T5501EL	462
1T5502DA	462
1T5502EL	462
1T5503DA	463
1T5503EL	463
1T5504DA	463
1T5504EL	463
1T5505DA	463
1T5505EL	463
1T5506DA	463
1T5506EL	463
1T5507DA	463
1T5507EL	463
1T5508DA	463
1T5508EL	463
1T5509DA	463
1T5509EL	463
1T5510DA	463
1T5510EL	463
1T5511DA	463
1T5511EL	463
1T5512DA	463
1T5512EL	463
1T5513DA	463
1T5513EL	463
1T5514DA	463
1T5514EL	463
1T5515DA	462
1T5515EL	462
1T5516DA	462
1T5516EL	462
1T5517DA	462
1T5517EL	462
1T5518DA	462
1T5518EL	462
1T5519DA	462
1T5519EL	462
1T5520DA	462
1T5520EL	462
1T5521DA	463
1T5521EL	463
1T5522DA	463
1T5522EL	463

COD.	PAG.
1T5523DA	463
1T5523EL	463
1T5524DA	463
1T5524EL	463
1T5525DA	463
1T5525EL	463
1T5526DA	463
1T5526EL	463
1T5527DA	462
1T5527EL	462
1T5528DA	462
1T5528EL	462
1T5529DA	462
1T5529EL	462
1T5530DA	462
1T5530EL	462
1T5531DA	462
1T5531EL	462
1T5532DA	462
1T5532EL	462
1T5533DA	462
1T5533EL	462
1T5534DA	462
1T5534EL	462
1T5535DA	462
1T5535EL	462
1T5536DA	462
1T5536EL	462
1T5537DA	462
1T5537EL	462
1T5538DA	462
1T5538EL	462
1T5539DA	463
1T5539EL	463
1T5540DA	463
1T5540EL	463
1T5541DA	463
1T5541EL	463
1T5542DA	463
1T5542EL	463
1T5543DA	463
1T5543EL	463
1T5544DA	463
1T5544EL	463
1T5545DA	463
1T5545EL	463
1T5546DA	463
1T5546EL	463
1T5547DA	463
1T5547EL	463
1T5548DA	463
1T5548EL	463
1T5549DA	463
1T5549EL	463
1T5550DA	463
1T5550EL	463
1T5551DA	464
1T5551EL	464
1T5552DA	464
1T5552EL	464
1T5553DA	464
1T5553EL	464
1T5554DA	464
1T5554EL	464
1T5555DA	464
1T5555EL	464
1T5556DA	464
1T5556EL	464
1T5557DA	464
1T5557EL	464
1T5558DA	464
1T5558EL	464
1T5559DA	464
1T5559EL	464
1T5560DA	464
1T5560EL	464
1T5561DA	464
1T5561EL	464
1T5562DA	464
1T5562EL	464
1T5563DA	464

COD.	PAG.
1T5563EL	464
1T5564DA	464
1T5564EL	464
1T5565DA	464
1T5565EL	464
1T5566DA	464
1T5566EL	464
1T5567DA	464
1T5567EL	464
1T5568DA	464
1T5568EL	464
1T5569DA	464
1T5569EL	464
1T5570DA	464
1T5570EL	464
1T5571DA	464
1T5571EL	464
1T5572DA	464
1T5572EL	464
1T5573DA	464
1T5573EL	464
1T5574DA	464
1T5574EL	464
1T5575DA	464
1T5575EL	464
1T5576DA	464
1T5576EL	464
1T5577DA	464
1T5577EL	464
1T5578DA	464
1T5578EL	464
1T5579DA	464
1T5579EL	464
1T5580DA	464
1T5580EL	464
1T5581DA	464
1T5581EL	464
1T5582DA	464
1T5582EL	464
1T5583DA	464
1T5583EL	464
1T5584DA	464
1T5584EL	464
1T5585DA	464
1T5585EL	464
1T5586DA	464
1T5586EL	464
1T5587DA	465
1T5587EL	465
1T5588DA	465
1T5588EL	465
1T5589DA	465
1T5589EL	465
1T5590DA	465
1T5590EL	465
1T5591DA	465
1T5591EL	465
1T5592DA	465
1T5592EL	465
1T5593DA	465
1T5593EL	465
1T5594DA	465
1T5594EL	465
1T5595DA	465
1T5595EL	465
1T5596DA	465
1T5596EL	465
1T5597DA	465
1T5597EL	465
1T5598DA	465
1T5598EL	465
1T5599DA	466
1T5599EL	466
1T5600DA	466
1T5600EL	466
1T5601DA	466
1T5601EL	466
1T5602DA	466
1T5602EL	466
1T5603DA	466
1T5603EL	466

COD.	PAG.
1T5604DA	466
1T5604EL	466
1T5605DA	466
1T5605EL	466
1T5606DA	466
1T5606EL	466
1T5607DA	466
1T5607EL	466
1T5608DA	466
1T5608EL	466
1T5609DA	466
1T5609EL	466
1T5610DA	466
1T5610EL	466
1T5611DA	465
1T5611EL	465
1T5612DA	465
1T5612EL	465
1T5613DA	465
1T5613EL	465
1T5614DA	465
1T5614EL	465
1T5615DA	465
1T5615EL	465
1T5616DA	465
1T5616EL	465
1T5617DA	466
1T5617EL	466
1T5618DA	466
1T5618EL	466
1T5619DA	466
1T5619EL	466
1T5620DA	466
1T5620EL	466
1T5621DA	466
1T5621EL	466
1T5622DA	466
1T5622EL	466
1T5623DA	465
1T5623EL	465
1T5624DA	465
1T5624EL	465
1T5625DA	465
1T5625EL	465
1T5626DA	465
1T5626EL	465
1T5627DA	465
1T5627EL	465
1T5628DA	465
1T5628EL	465
1T5629DA	465
1T5629EL	465
1T5630DA	465
1T5630EL	465
1T5631DA	465
1T5631EL	465
1T5632DA	465
1T5632EL	465
1T5633DA	465
1T5633EL	465
1T5634DA	465
1T5634EL	465
1T5635DA	407
1T5635EL	407
1T5636DA	407
1T5636EL	407
1T5637DA	407
1T5637EL	407
1T5638DA	407
1T5638EL	407
1T5639DA	407
1T5639EL	407
1T5640DA	407
1T5640EL	407
1T5641DA	407
1T5641EL	407
1T5642DA	407
1T5642EL	407
1T5643DA	407
1T5643EL	407
1T5644DA	407

COD.	PAG.
1T5644EL	407
1T5645DA	407
1T5645EL	407
1T5646DA	407
1T5646EL	407
1T5647DA	408
1T5647EL	408
1T5648DA	408
1T5648EL	408
1T5649DA	408
1T5649EL	408
1T5650DA	408
1T5650EL	408
1T5651DA	408
1T5651EL	408
1T5652DA	408
1T5652EL	408
1T5653DA	408
1T5653EL	408
1T5654DA	408
1T5654EL	408
1T5655DA	408
1T5655EL	408
1T5656DA	408
1T5656EL	408
1T5657DA	408
1T5657EL	408
1T5658DA	408
1T5658EL	408
1T5659DA	408
1T5659EL	408
1T5660DA	408
1T5660EL	408
1T5661DA	408
1T5661EL	408
1T5662DA	408
1T5662EL	408
1T5663DA	408
1T5663EL	408
1T5664DA	408
1T5664EL	408
1T5665DA	408
1T5665EL	408
1T5666DA	408
1T5666EL	408
1T5667DA	408
1T5667EL	408
1T5668DA	408
1T5668EL	408
1T5669DA	408
1T5669EL	408
1T5670DA	408
1T5670EL	408
1T5671DA	408
1T5671EL	408
1T5672DA	408
1T5672EL	408
1T5673DA	408
1T5673EL	408
1T5674DA	408
1T5674EL	408
1T5675DA	408
1T5675EL	408
1T5676DA	408
1T5676EL	408
1T5677DA	408
1T5677EL	408
1T5678DA	408
1T5678EL	408
1T5679DA	408
1T5679EL	408
1T5680DA	408
1T5680EL	408
1T5681DA	408
1T5681EL	408
1T5682DA	408
1T5682EL	408
1T5683DA	409
1T5683EL	409
1T5684DA	409
1T5684EL	409

COD.	PAG.
1T5685DA	409
1T5685EL	409
1T5686DA	409
1T5686EL	409
1T5687DA	409
1T5687EL	409
1T5688DA	409
1T5688EL	409
1T5689DA	409
1T5689EL	409
1T5690DA	409
1T5690EL	409
1T5691DA	409
1T5691EL	409
1T5692DA	409
1T5692EL	409
1T5693DA	409
1T5693EL	409
1T5694DA	409
1T5694EL	409
1T5695DA	410
1T5695EL	410
1T5696DA	410
1T5696EL	410
1T5697DA	410
1T5697EL	410
1T5698DA	410
1T5698EL	410
1T5699DA	410
1T5699EL	410
1T5700DA	410
1T5700EL	410
1T5701DA	410
1T5701EL	410
1T5702DA	410
1T5702EL	410
1T5703DA	410
1T5703EL	410
1T5704DA	410
1T5704EL	410
1T5705DA	410
1T5705EL	410
1T5706DA	410
1T5706EL	410
1T5707DA	409
1T5707EL	409
1T5708DA	409
1T5708EL	409
1T5709DA	409
1T5709EL	409
1T5710DA	409
1T5710EL	409
1T5711DA	409
1T5711EL	409
1T5712DA	409
1T5712EL	409
1T5713DA	410
1T5713EL	410
1T5714DA	410
1T5714EL	410
1T5715DA	410
1T5715EL	410
1T5716DA	410
1T5716EL	410
1T5717DA	410
1T5717EL	410
1T5718DA	410
1T5718EL	410
1T5719DA	409
1T5719EL	409
1T5720DA	409
1T5720EL	409
1T5721DA	409
1T5721EL	409
1T5722DA	409
1T5722EL	409
1T5723DA	409
1T5723EL	409
1T5724DA	409
1T5724EL	409
1T5725DA	409

COD.	PAG.
1T5725EL	409
1T5726DA	409
1T5726EL	409
1T5727DA	409
1T5727EL	409
1T5728DA	409
1T5728EL	409
1T5729DA	409
1T5729EL	409
1T5730DA	409
1T5730EL	409
1T5731DA	410
1T5731EL	410
1T5732DA	410
1T5732EL	410
1T5733DA	410
1T5733EL	410
1T5734DA	410
1T5734EL	410
1T5735DA	410
1T5735EL	410
1T5736DA	410
1T5736EL	410
1T5737DA	410
1T5737EL	410
1T5738DA	410
1T5738EL	410
1T5739DA	410
1T5739EL	410
1T5740DA	410
1T5740EL	410
1T5741DA	410
1T5741EL	410
1T5742DA	410
1T5742EL	410
1T5743DA	411
1T5743EL	411
1T5744DA	411
1T5744EL	411
1T5745DA	411
1T5745EL	411
1T5746DA	411
1T5746EL	411
1T5747DA	411
1T5747EL	411
1T5748DA	411
1T5748EL	411
1T5749DA	411
1T5749EL	411
1T5750DA	411
1T5750EL	411
1T5751DA	411
1T5751EL	411
1T5752DA	411
1T5752EL	411
1T5753DA	411
1T5753EL	411
1T5754DA	411
1T5754EL	411
1T5755DA	411
1T5755EL	411
1T5756DA	411
1T5756EL	411
1T5757DA	411
1T5757EL	411
1T5758DA	411
1T5758EL	411
1T5759DA	411
1T5759EL	411
1T5760DA	411
1T5760EL	411
1T5761DA	411
1T5761EL	411
1T5762DA	411
1T5762EL	411
1T5763DA	411
1T5763EL	411
1T5764DA	411
1T5764EL	411
1T5765DA	411
1T5765EL	411
1T5766DA	411
1T5766EL	411
1T5767DA	411
1T5767EL	411
1T5768DA	411
1T5768EL	411
1T5769DA	411
1T5769EL	411
1T5770DA	411
1T5770EL	411
1T5771DA	411
1T5771EL	411
1T5772DA	411
1T5772EL	411
1T5773DA	411
1T5773EL	411
1T5774DA	411
1T5774EL	411
1T5775DA	411
1T5775EL	411
1T5776DA	411
1T5776EL	411
1T5777DA	411
1T5777EL	411
1T5778DA	411
1T5778EL	411
1T5779DA	76
1T5779EL	76
1T5780DA	76
1T5780EL	76
1T5781DA	76
1T5781EL	76
1T5782DA	76
1T5782EL	76
1T5783DA	76
1T5783EL	76
1T5784DA	76
1T5784EL	76
1T5785DA	76
1T5785EL	76
1T5786DA	76
1T5786EL	76
1T5787DA	76
1T5787EL	76
1T5788DA	76
1T5788EL	76
1T5789DA	76
1T5789EL	76
1T5790DA	76
1T5790EL	76
1T5791DA	76
1T5791EL	76
1T5792DA	76
1T5792EL	76
1T5793DA	76
1T5793EL	76
1T5794DA	76
1T5794EL	76
1T5795DA	76
1T5795EL	76
1T5796DA	76
1T5796EL	76
1T5797DA	76
1T5797EL	76
1T5798DA	76
1T5798EL	76
1T5799DA	77
1T5799EL	77
1T5800DA	77
1T5800EL	77
1T5801DA	77
1T5801EL	77
1T5802DA	77
1T5802EL	77
1T5803DA	77
1T5803EL	77
1T5804DA	77
1T5804EL	77
1T5805DA	77
1T5805EL	77
1T5806DA	77
1T5806EL	77
1T5807DA	77
1T5807EL	77
1T5808DA	77
1T5808EL	77
1T5809DA	77
1T5809EL	77
1T5810DA	77
1T5810EL	77
1T5811DA	77
1T5811EL	77
1T5812DA	77
1T5812EL	77
1T5813DA	77
1T5813EL	77
1T5814DA	77
1T5814EL	77
1T5815DA	77
1T5815EL	77
1T5816DA	77
1T5816EL	77
1T5817DA	77
1T5817EL	77
1T5818DA	77
1T5818EL	77
1T5819DA	78
1T5819EL	78
1T5820DA	78
1T5820EL	78
1T5821DA	78
1T5821EL	78
1T5822DA	78
1T5822EL	78
1T5823DA	78
1T5823EL	78
1T5824DA	78
1T5824EL	78
1T5825DA	78
1T5825EL	78
1T5826DA	78
1T5826EL	78
1T5827DA	78
1T5827EL	78
1T5828DA	78
1T5828EL	78
1T5829DA	78
1T5829EL	78
1T5830DA	78
1T5830EL	78
1T5831DA	78
1T5831EL	78
1T5832DA	78
1T5832EL	78
1T5833DA	78
1T5833EL	78
1T5834DA	78
1T5834EL	78
1T5835DA	78
1T5835EL	78
1T5836DA	78
1T5836EL	78
1T5837DA	78
1T5837EL	78
1T5838DA	78
1T5838EL	78
1T5839DA	424
1T5839EL	424
1T5840DA	424
1T5840EL	424
1T5841DA	424
1T5841EL	424
1T5842DA	424
1T5842EL	424
1T5843DA	424
1T5843EL	424
1T5844DA	424
1T5844EL	424
1T5845DA	424
1T5845EL	424
1T5846DA	424
1T5846EL	424

COD.	PAG.
1T5847DA	424
1T5847EL	424
1T5848DA	424
1T5848EL	424
1T5849DA	424
1T5849EL	424
1T5850DA	424
1T5850EL	424
1T5851DA	424
1T5851EL	424
1T5852DA	424
1T5852EL	424
1T5853DA	424
1T5853EL	424
1T5854DA	424
1T5854EL	424
1T5855DA	424
1T5855EL	424
1T5856DA	424
1T5856EL	424
1T5857DA	424
1T5857EL	424
1T5858DA	424
1T5858EL	424
1T5859DA	425
1T5859EL	425
1T5860DA	425
1T5860EL	425
1T5861DA	425
1T5861EL	425
1T5862DA	425
1T5862EL	425
1T5863DA	425
1T5863EL	425
1T5864DA	425
1T5864EL	425
1T5865DA	425
1T5865EL	425
1T5866DA	425
1T5866EL	425
1T5867DA	425
1T5867EL	425
1T5868DA	425
1T5868EL	425
1T5869DA	425
1T5869EL	425
1T5870DA	425
1T5870EL	425
1T5871DA	425
1T5871EL	425
1T5872DA	425
1T5872EL	425
1T5873DA	425
1T5873EL	425
1T5874DA	425
1T5874EL	425
1T5875DA	425
1T5875EL	425
1T5876DA	425
1T5876EL	425
1T5877DA	425
1T5877EL	425
1T5878DA	425
1T5878EL	425
1T5879DA	426
1T5879EL	426
1T5880DA	426
1T5880EL	426
1T5881DA	426
1T5881EL	426
1T5882DA	426
1T5882EL	426
1T5883DA	426
1T5883EL	426
1T5884DA	426
1T5884EL	426
1T5885DA	426
1T5885EL	426
1T5886DA	426
1T5886EL	426
1T5887DA	426
1T5887EL	426
1T5888DA	426
1T5888EL	426
1T5889DA	426
1T5889EL	426
1T5890DA	426
1T5890EL	426
1T5891DA	426
1T5891EL	426
1T5892DA	426
1T5892EL	426
1T5893DA	426
1T5893EL	426
1T5894DA	426
1T5894EL	426
1T5895DA	426
1T5895EL	426
1T5896DA	426
1T5896EL	426
1T5897DA	426
1T5897EL	426
1T5898DA	426
1T5898EL	426
1T5899	421, 467
1T5900	421, 467
1T5901	421, 467
1T5902	421, 467
1T5903	421, 467
1T5904	421, 467
1T5905DA	169, 421, 467
1T5905EL	421, 467
1T5906DA	421, 467
1T5906EL	421, 467
1T5907DA	421, 467
1T5907EL	421, 467
1T5908	445
1T5911	422, 432, 445
1T5912	421, 466
1T5913	421, 466
1T5914	421, 466
1T5915	432
1T5916	432
1T5917	432
1T5918	79
1T5919	79
1T5920	79
1T5921	432
1T5937	421, 432
1T5938	421, 432
1T5939	421
1T5940DA	437
1T5940EL	437
1T5941DA	437
1T5941EL	437
1T5942DA	437
1T5942EL	437
1T5943DA	437
1T5943EL	437
1T5944DA	437
1T5944EL	437
1T5945DA	437
1T5945EL	437
1T5946DA	438
1T5946EL	438
1T5947DA	438
1T5947EL	438
1T5948DA	438
1T5948EL	438
1T5949DA	438
1T5949EL	438
1T5950DA	438
1T5950EL	438
1T5951DA	438
1T5951EL	438
1T5952DA	182
1T5952EL	182
1T5953DA	182
1T5953EL	182
1T5954DA	182
1T5954EL	182
1T5955DA	182
1T5955EL	182
1T5956DA	183
1T5956EL	183
1T5957DA	183
1T5957EL	183
1T5958DA	183
1T5958EL	183
1T5959DA	183
1T5959EL	183
1T5960DA	182
1T5960EL	182
1T5961DA	182
1T5961EL	182
1T5962DA	182
1T5962EL	182
1T5963DA	182
1T5963EL	182
1T5964DA	183
1T5964EL	183
1T5965DA	183
1T5965EL	183
1T5966DA	183
1T5966EL	183
1T5967DA	183
1T5967EL	183
1T5968DA	182
1T5968EL	182
1T5969DA	182
1T5969EL	182
1T5970DA	183
1T5970EL	183
1T5971DA	183
1T5971EL	183
1T5972DA	183
1T5972EL	183
1T5973DA	183
1T5973EL	183
1T5974DA	182
1T5974EL	182
1T5975DA	182
1T5975EL	182
1T5976DA	412
1T5976EL	412
1T5977DA	412
1T5977EL	412
1T5978DA	412
1T5978EL	412
1T5979DA	412
1T5979EL	412
1T5980DA	412
1T5980EL	412
1T5981DA	412
1T5981EL	412
1T5982DA	412
1T5982EL	412
1T5983DA	412
1T5983EL	412
1T5984DA	412
1T5984EL	412
1T5985DA	412
1T5985EL	412
1T5986DA	412
1T5986EL	412
1T5987DA	412
1T5987EL	412
1T5988DA	413
1T5988EL	413
1T5989DA	413
1T5989EL	413
1T5990DA	413
1T5990EL	413
1T5991DA	413
1T5991EL	413
1T5992DA	413
1T5992EL	413
1T5993DA	413
1T5993EL	413
1T5994DA	413
1T5994EL	413
1T5995DA	413
1T5995EL	413

COD.	PAG.
1T5996DA	413
1T5996EL	413
1T5997DA	413
1T5997EL	413
1T5998DA	413
1T5998EL	413
1T5999DA	413
1T5999EL	413
1T6000DA	414
1T6000EL	414
1T6001DA	414
1T6001EL	414
1T6002DA	414
1T6002EL	414
1T6003DA	414
1T6003EL	414
1T6004DA	414
1T6004EL	414
1T6005DA	414
1T6005EL	414
1T6006DA	414
1T6006EL	414
1T6007DA	414
1T6007EL	414
1T6008DA	414
1T6008EL	414
1T6009DA	414
1T6009EL	414
1T6010DA	414
1T6010EL	414
1T6011DA	414
1T6011EL	414
1T6012	79
1T6013	79
1T6014	79
1T6015DA	433
1T6015EL	433
1T6016DA	433
1T6016EL	433
1T6017DA	433
1T6017EL	433
1T6018DA	433
1T6018EL	433
1T6019DA	423
1T6019EL	423
1T6020DA	423
1T6020EL	423
1T6021DA	423
1T6021EL	423
1T6022DA	423
1T6022EL	423
1T6023DA	423
1T6023EL	423
1T6024DA	423
1T6024EL	423
1T6025DA	423
1T6025EL	423
1T6026DA	423
1T6026EL	423
1T6027DA	406
1T6027EL	406
1T6028DA	406
1T6028EL	406
1T6029DA	406
1T6029EL	406
1T6030DA	406
1T6030EL	406
1T6031DA	406
1T6031EL	406
1T6032DA	406
1T6032EL	406
1T6033DA	406
1T6033EL	406
1T6034DA	406
1T6034EL	406
1T6035DA	406
1T6035EL	406
1T6036DA	406
1T6036EL	406
1T6037DA	406
1T6037EL	406

COD.	PAG.
1T6038DA	406
1T6038EL	406
1T6039DA	407
1T6039EL	407
1T6040DA	407
1T6040EL	407
1T6041DA	407
1T6041EL	407
1T6042DA	407
1T6042EL	407
1T6043DA	407
1T6043EL	407
1T6044DA	407
1T6044EL	407
1T6045DA	407
1T6045EL	407
1T6046DA	407
1T6046EL	407
1T6047DA	407
1T6047EL	407
1T6048DA	407
1T6048EL	407
1T6049DA	407
1T6049EL	407
1T6050DA	407
1T6050EL	407
1T6051	432
1T6052	432
1T6053	218
1T6054	218
1T6055	218
1T6056	218
1T6057	218
1T6058	218
1T6059	224
1T6060	224
1T6061	224
1T6062	224
1T6063	224
1T6064	224
1T6066DA	494
1T6066EL	494
1T6067DA	494
1T6067EL	494
1T6068DA	494
1T6068EL	494
1T6069DA	494
1T6069EL	494
1T6070DA	494
1T6070EL	494
1T6071DA	494
1T6071EL	494
1T6072DA	494
1T6072EL	494
1T6073DA	494
1T6073EL	494
1T6074DA	494
1T6074EL	494
1T6075DA	494
1T6075EL	494
1T6076DA	494
1T6076EL	494
1T6077DA	494
1T6077EL	494
1T6078DA	495
1T6078EL	495
1T6079DA	495
1T6079EL	495
1T6080DA	495
1T6080EL	495
1T6081DA	495
1T6081EL	495
1T6082DA	495
1T6082EL	495
1T6083DA	495
1T6083EL	495
1T6084DA	495
1T6084EL	495
1T6085DA	495
1T6085EL	495
1T6086DA	495

COD.	PAG.
1T6086EL	495
1T6087DA	495
1T6087EL	495
1T6088DA	495
1T6088EL	495
1T6089DA	495
1T6089EL	495
1T6090DA	494
1T6090EL	494
1T6091DA	494
1T6091EL	494
1T6092DA	494
1T6092EL	494
1T6093DA	494
1T6093EL	494
1T6094DA	494
1T6094EL	494
1T6095DA	494
1T6095EL	494
1T6096DA	494
1T6096EL	494
1T6097DA	494
1T6097EL	494
1T6098DA	494
1T6098EL	494
1T6099DA	494
1T6099EL	494
1T6100DA	494
1T6100EL	494
1T6101DA	494
1T6101EL	494
1T6102DA	494
1T6102EL	494
1T6103DA	494
1T6103EL	494
1T6104DA	494
1T6104EL	494
1T6105DA	494
1T6105EL	494
1T6106DA	494
1T6106EL	494
1T6107DA	494
1T6107EL	494
1T6114DA	495
1T6114EL	495
1T6115DA	495
1T6115EL	495
1T6116DA	495
1T6116EL	495
1T6117DA	495
1T6117EL	495
1T6118DA	495
1T6118EL	495
1T6119DA	495
1T6119EL	495
1T6126DA	495
1T6126EL	495
1T6127DA	495
1T6127EL	495
1T6128DA	495
1T6128EL	495
1T6129DA	495
1T6129EL	495
1T6130DA	495
1T6130EL	495
1T6131DA	495
1T6131EL	495
1T6138DA	495
1T6138EL	495
1T6139DA	495
1T6139EL	495
1T6140DA	495
1T6140EL	495
1T6141DA	495
1T6141EL	495
1T6142DA	495
1T6142EL	495
1T6143DA	495
1T6143EL	495
1T6144DA	496
1T6144EL	496

COD.	PAG.
1T6145DA	496
1T6145DA	496
1T6146DA	496
1T6146EL	496
1T6147DA	496
1T6147EL	496
1T6148DA	496
1T6148EL	496
1T6149DA	496
1T6149EL	496
1T6150DA	496
1T6150EL	496
1T6151DA	496
1T6151EL	496
1T6152DA	496
1T6152EL	496
1T6153DA	496
1T6153EL	496
1T6154DA	496
1T6154EL	496
1T6155DA	496
1T6155EL	496
1T6156DA	497
1T6156EL	497
1T6157DA	497
1T6157EL	497
1T6158DA	497
1T6158EL	497
1T6159DA	497
1T6159EL	497
1T6160DA	497
1T6160EL	497
1T6161DA	497
1T6161EL	497
1T6162DA	496
1T6162EL	496
1T6163DA	496
1T6163EL	496
1T6164DA	496
1T6164EL	496
1T6165DA	496
1T6165EL	496
1T6166DA	496
1T6166EL	496
1T6167DA	496
1T6167EL	496
1T6168DA	496
1T6168EL	496
1T6169DA	496
1T6169EL	496
1T6170DA	496
1T6170EL	496
1T6171DA	496
1T6171EL	496
1T6172DA	496
1T6172EL	496
1T6173DA	496
1T6173EL	496
1T6174DA	496
1T6174EL	496
1T6175DA	496
1T6175EL	496
1T6176DA	496
1T6176EL	496
1T6177DA	496
1T6177EL	496
1T6178DA	496
1T6178EL	496
1T6179DA	496
1T6179EL	496
1T6186DA	497
1T6186EL	497
1T6187DA	497
1T6187EL	497
1T6188DA	497
1T6188EL	497
1T6189DA	497
1T6189EL	497
1T6190DA	497
1T6190EL	497
1T6191DA	497
1T6191EL	497
1T6198DA	496
1T6198EL	496
1T6199DA	496
1T6199EL	496
1T6200DA	496
1T6200EL	496
1T6201DA	496
1T6201EL	496
1T6202DA	496
1T6202EL	496
1T6203DA	496
1T6203EL	496
1T6210DA	497
1T6210EL	497
1T6211DA	497
1T6211EL	497
1T6212DA	497
1T6212EL	497
1T6213DA	497
1T6213EL	497
1T6214DA	497
1T6214EL	497
1T6215DA	497
1T6215EL	497
1T6216DA	497
1T6216EL	497
1T6217DA	497
1T6217EL	497
1T6218DA	497
1T6218EL	497
1T6219DA	497
1T6219EL	497
1T6220DA	497
1T6220EL	497
1T6221DA	497
1T6221EL	497
1T6222DA	498
1T6222EL	498
1T6223DA	498
1T6223EL	498
1T6224DA	498
1T6224EL	498
1T6225DA	498
1T6225EL	498
1T6226DA	498
1T6226EL	498
1T6227DA	498
1T6227EL	498
1T6228DA	498
1T6228EL	498
1T6229DA	498
1T6229EL	498
1T6230DA	498
1T6230EL	498
1T6231DA	498
1T6231EL	498
1T6232DA	498
1T6232EL	498
1T6233DA	498
1T6233EL	498
1T6234DA	497
1T6234EL	497
1T6235DA	497
1T6235EL	497
1T6236DA	497
1T6236EL	497
1T6237DA	497
1T6237EL	497
1T6238DA	497
1T6238EL	497
1T6239DA	497
1T6239EL	497
1T6240DA	498
1T6240EL	498
1T6241DA	498
1T6241EL	498
1T6242DA	498
1T6242EL	498
1T6243DA	498
1T6243EL	498
1T6244DA	498
1T6244EL	498
1T6245DA	498
1T6245EL	498
1T6246DA	498
1T6246EL	498
1T6247DA	498
1T6247EL	498
1T6248DA	498
1T6248EL	498
1T6249DA	498
1T6249EL	498
1T6250DA	498
1T6250EL	498
1T6251DA	498
1T6251EL	498
1T6252DA	498
1T6252EL	498
1T6253DA	498
1T6253EL	498
1T6254DA	498
1T6254EL	498
1T6255DA	498
1T6255EL	498
1T6256DA	498
1T6256EL	498
1T6257DA	498
1T6257EL	498
1T6258DA	499
1T6258EL	499
1T6259DA	499
1T6259EL	499
1T6260DA	499
1T6260EL	499
1T6261DA	499
1T6261EL	499
1T6262DA	499
1T6262EL	499
1T6263DA	499
1T6263EL	499
1T6264DA	499
1T6264EL	499
1T6265DA	499
1T6265EL	499
1T6266DA	499
1T6266EL	499
1T6267DA	499
1T6267EL	499
1T6268DA	499
1T6268EL	499
1T6269DA	499
1T6269EL	499
1T6270DA	499
1T6270EL	499
1T6271DA	499
1T6271EL	499
1T6272DA	499
1T6272EL	499
1T6273DA	499
1T6273EL	499
1T6274DA	499
1T6274EL	499
1T6275DA	499
1T6275EL	499
1T6276DA	499
1T6276EL	499
1T6277DA	499
1T6277EL	499
1T6278DA	499
1T6278EL	499
1T6279DA	499
1T6279EL	499
1T6280DA	499
1T6280EL	499
1T6281DA	499
1T6281EL	499
1T6282	501
1T6285	501
1T6288DA	501
1T6288EL	501
1T6289DA	501

COD.	PAG.
1T6289EL	501
1T6290DA	501
1T6290EL	501
1T6291	500
1T6292	500
1T6293	500
1T6294	500
1T6295	500
1T6296	500
1T6297	500
1T6298	500
1T6299	500
1T6300	500
1T6301	500
1T6302	500
1T6303	500
1T6304	500
1T6305	500
1T6306	500
1T6307	500
1T6308	500
1T6309DA	299
1T6309EL	299
1T6310DA	299
1T6310EL	299
1T6311DA	299
1T6311EL	299
1T6312DA	299
1T6312EL	299
1T6313DA	298
1T6313EL	298
1T6314DA	298
1T6314EL	298
1T6315DA	298
1T6315EL	298
1T6316DA	298
1T6316EL	298
1T6317	275
1T6318	275
1T6319	275
1T6320	275
1T6321	275
1T6322	275
1T6323	275
1T6324	275
1T6325	330
1T6326	330
1T6327	330
1T6328	330
1T6329	331
1T6330	331
1T6331	329
1T6332	329
1T6333	205
1T6334	205
1T6335	204
1T6336	204
1T6337	330
1T6338	330
1T6339	330
1T6340	330
1T6341	331
1T6342	331
1T6343	329
1T6344	329
1T6345	205
1T6346	205
1T6347	204
1T6348	204
1T6349	330
1T6350	330
1T6351	330
1T6352	330
1T6353	331
1T6354	331
1T6355	329
1T6356	329
1T6357	205
1T6358	205
1T6359	204
1T6360	204
1T6377	193
1T6378	193
1T6379	193
1T6380	193
1T6381	184, 256, 276, 324
1T6382	318
1T6383	184, 256, 276, 324
1T6384	318
1T6385	184, 256, 276, 324
1T6386	318
1T6387	184, 256, 276, 324
1T6388	318
1T6389	184, 256, 276, 324
1T6390	318
1T6391	184, 256, 276, 324
1T6392	318
1T6393	185, 257, 276, 324
1T6394	318
1T6401	500
1T6402	500
1T6403	500
1T6404	500
1T6405	500
1T6406	500
1T6419DA	183
1T6419EL	183
1T6420DA	183
1T6420EL	183
1T6421DA	183
1T6421EL	183
1T6422DA	183
1T6422EL	183
1T6423	183
1T6424	183
1T6425	184
1T6426	183
1T6427	183
1T6428	184
1T6429DA	175
1T6429EL	175
1T6430DA	175
1T6430EL	175
1T6431DA	175
1T6431EL	175
1T6432DA	175
1T6432EL	175
1T6433DA	175
1T6433EL	175
1T6434DA	175
1T6434EL	175
1T6435DA	175
1T6435EL	175
1T6436DA	175
1T6436EL	175
1T6437DA	175
1T6437EL	175
1T6438DA	176
1T6438EL	176
1T6439DA	175
1T6439EL	175
1T6440DA	176
1T6440EL	176
1T6441DA	176
1T6441EL	176
1T6442DA	176
1T6442EL	176
1T6443DA	176
1T6443EL	176
1T6444DA	176
1T6444EL	176
1T6445DA	175
1T6445EL	175
1T6446DA	175
1T6446EL	175
1T6447DA	175
1T6447EL	175
1T6448DA	175
1T6448EL	175
1T6449DA	175
1T6449EL	175
1T6450DA	175
1T6450EL	175
1T6451DA	175
1T6451EL	175
1T6452DA	175
1T6452EL	175
1T6453DA	175
1T6453EL	175
1T6454DA	176
1T6454EL	176
1T6455DA	175
1T6455EL	175
1T6456DA	176
1T6456EL	176
1T6457DA	176
1T6457EL	176
1T6458DA	176
1T6458EL	176
1T6459DA	176
1T6459EL	176
1T6460DA	176
1T6460EL	176
1T6461DA	176
1T6461EL	176
1T6462DA	176
1T6462EL	176
1T6463DA	176
1T6463EL	176
1T6464DA	176
1T6464EL	176
1T6465DA	176
1T6465EL	176
1T6466DA	177
1T6466EL	177
1T6467DA	176
1T6467EL	176
1T6468DA	177
1T6468EL	177
1T6469DA	177
1T6469EL	177
1T6470DA	177
1T6470EL	177
1T6471DA	177
1T6471EL	177
1T6472DA	177
1T6472EL	177
1T6473DA	177
1T6473EL	177
1T6474DA	177
1T6474EL	177
1T6475DA	177
1T6475EL	177
1T6476DA	177
1T6476EL	177
1T6477DA	176
1T6477EL	176
1T6478DA	176
1T6478EL	176
1T6479DA	176
1T6479EL	176
1T6480DA	176
1T6480EL	176
1T6481DA	176
1T6481EL	176
1T6482DA	177
1T6482EL	177
1T6483DA	176
1T6483EL	176
1T6484DA	177
1T6484EL	177
1T6485DA	177
1T6485EL	177
1T6486DA	177
1T6486EL	177
1T6487DA	177
1T6487EL	177
1T6488DA	177
1T6488EL	177
1T6489DA	177
1T6489EL	177
1T6490DA	177
1T6490EL	177

COD.	PAG.
1T6491DA	177
1T6491EL	177
1T6492DA	177
1T6492EL	177
1T6493	178
1T6494	178
1T6495	178
1T6496	178
1T6497	178
1T6498	178
1T6499	556, 580, 594, 603, 618, 643, 660, 702, 706, 725, 820
1T6500	218
1T6501	224
1T6502	79, 83, 422, 432, 445, 467
1T6504	193
1T6505	193
1T6506	178, 251, 273
1T6507	178, 251, 273
1T6508	179, 251, 273
1T6509	179, 251, 273
1T6510	179, 251, 273
1T6511	179, 251, 273
1T6512	179, 251, 273
1T6521	185, 257, 276
1T6522	179, 252, 263, 266, 274
1T6523	271
1T6524	204, 205, 329, 331
1T6525	331
1T6526	331
1T6527	331
1T6528	329
1T6529	329
1T6530	329
1T6543D	228
1T6543DA	229
1T6543EL	227
1T6544D	228
1T6544DA	229
1T6544EL	227
1T6545D	228
1T6545DA	229
1T6545EL	227
1T6546D	228
1T6546DA	229
1T6546EL	227
1T6547D	228
1T6547DA	229
1T6547EL	227
1T6548D	228
1T6548DA	229
1T6548EL	227
1T6549D	228
1T6549DA	229
1T6549EL	227
1T6550D	228
1T6550DA	229
1T6550EL	227
1T6563DA	188
1T6563EL	188
1T6564DA	188
1T6564EL	188
1T6565DA	188
1T6565EL	188
1T6566DA	188
1T6566EL	188
1T6567DA	188
1T6567EL	188
1T6568DA	188
1T6568EL	188
1T6569DA	188
1T6569EL	188
1T6570DA	188
1T6570EL	188
1T6571	189, 231
1T6572	189, 231
1T6573	189, 231
1T6574	189, 231
1T6575	189, 231
1T6576	189, 231
1T6579	189
1T6580	189
1T6581	627, 631, 635, 637, 716, 719, 721, 739, 741, 745, 753, 755, 797
1T6582DA	240
1T6582EL	239
1T6583DA	240
1T6583EL	239
1T6584DA	240
1T6584EL	239
1T6585DA	240
1T6585EL	239
1T6586DA	240
1T6586EL	239
1T6587DA	240
1T6587EL	239
1T6588DA	240
1T6588EL	239
1T6589DA	240
1T6589EL	239
1T6590DA	240
1T6590EL	239
1T6591DA	240
1T6591EL	239
1T6592DA	240
1T6592EL	239
1T6593DA	240
1T6593EL	239
1T6594DA	240
1T6594EL	239
1T6595DA	240
1T6595EL	239
1T6596DA	240
1T6596EL	239
1T6597DA	240
1T6597EL	239
1T6598DA	240
1T6598EL	239
1T6599DA	240
1T6599EL	239
1T6600DA	234
1T6600EL	234
1T6601DA	234
1T6601EL	234
1T6602DA	234
1T6602EL	234
1T6603DA	234
1T6603EL	234
1T6604DA	234
1T6604EL	234
1T6605DA	234
1T6605EL	234
1T6606DA	235
1T6606EL	234
1T6607DA	235
1T6607EL	234
1T6608DA	235
1T6608EL	234
1T6609DA	235
1T6609EL	234
1T6610DA	235
1T6610EL	234
1T6611DA	235
1T6611EL	234
1T6612DA	235
1T6612EL	234
1T6613DA	235
1T6613EL	234
1T6614DA	235
1T6614EL	234
1T6615DA	235
1T6615EL	234
1T6616DA	235
1T6616EL	234
1T6617DA	235
1T6617EL	234
1T6619DA	386
1T6619EL	386
1T6620DA	386
1T6620EL	386
1T6621DA	386
1T6621EL	386
1T6622DA	386
1T6622EL	386
1T6623DA	386
1T6623EL	386
1T6624DA	386
1T6624EL	386
1T6625DA	386
1T6625EL	386
1T6626DA	386
1T6626EL	386
1T6627DA	386
1T6627EL	386
1T6628DA	386
1T6628EL	386
1T6629DA	386
1T6629EL	386
1T6630DA	386
1T6630EL	386
1T6631DA	387
1T6631EL	387
1T6632DA	387
1T6632EL	387
1T6633DA	387
1T6633EL	387
1T6634DA	387
1T6634EL	387
1T6635DA	387
1T6635EL	387
1T6636DA	387
1T6636EL	387
1T6637DA	387
1T6637EL	387
1T6638DA	387
1T6638EL	387
1T6639DA	396
1T6639EL	396
1T6640DA	396
1T6640EL	396
1T6641DA	396
1T6641EL	396
1T6642DA	396
1T6642EL	396
1T6643DA	396
1T6643EL	396
1T6644DA	396
1T6644EL	396
1T6645DA	396
1T6645EL	396
1T6646DA	396
1T6646EL	396
1T6647DA	396
1T6647EL	396
1T6648DA	396
1T6648EL	396
1T6649DA	396
1T6649EL	396
1T6650DA	396
1T6650EL	396
1T6651DA	396
1T6651EL	396
1T6652DA	396
1T6652EL	396
1T6653DA	396
1T6653EL	396
1T6654DA	396
1T6654EL	396
1T6655DA	396
1T6655EL	396
1T6656DA	396
1T6656EL	396
1T6657DA	394
1T6657EL	394
1T6658DA	394
1T6658EL	394
1T6659DA	394
1T6659EL	394

COD.	PAG.
1T6660DA	394
1T6660EL	394
1T6661DA	394
1T6661EL	394
1T6662DA	394
1T6662EL	394
1T6663DA	394
1T6663EL	394
1T6664DA	394
1T6664EL	394
1T6665DA	394
1T6665EL	394
1T6666DA	394
1T6666EL	394
1T6667DA	394
1T6667EL	394
1T6668DA	394
1T6668EL	394
1T6669DA	394
1T6669EL	394
1T6670DA	394
1T6670EL	394
1T6671DA	394
1T6671EL	394
1T6672DA	394
1T6672EL	394
1T6673DA	394
1T6673EL	394
1T6674DA	394
1T6674EL	394
1T6675DA	391
1T6675EL	391
1T6676DA	391
1T6676EL	391
1T6677DA	391
1T6677EL	391
1T6678DA	391
1T6678EL	391
1T6679DA	391
1T6679EL	391
1T6680DA	391
1T6680EL	391
1T6681DA	391
1T6681EL	391
1T6682DA	391
1T6682EL	391
1T6683DA	391
1T6683EL	391
1T6684DA	391
1T6684EL	391
1T6685DA	391
1T6685EL	391
1T6686DA	391
1T6686EL	391
1T6687DA	391
1T6687EL	391
1T6688DA	391
1T6688EL	391
1T6689DA	391
1T6689EL	391
1T6690DA	391
1T6690EL	391
1T6691DA	391
1T6691EL	391
1T6692DA	391
1T6692EL	391
1T6693DA	396
1T6693EL	396
1T6694DA	396
1T6694EL	396
1T6695DA	396
1T6695EL	396
1T6696DA	396
1T6696EL	396
1T6697DA	396
1T6697EL	396
1T6698DA	396
1T6698EL	396
1T6699DA	397
1T6699EL	397
1T6700DA	397
1T6700EL	397
1T6701DA	397
1T6701EL	397
1T6702DA	397
1T6702EL	397
1T6703DA	397
1T6703EL	397
1T6704DA	397
1T6704EL	397
1T6705DA	397
1T6705EL	397
1T6706DA	397
1T6706EL	397
1T6707DA	397
1T6707EL	397
1T6708DA	397
1T6708EL	397
1T6709DA	397
1T6709EL	397
1T6710DA	397
1T6710EL	397
1T6711DA	394
1T6711EL	394
1T6712DA	394
1T6712EL	394
1T6713DA	394
1T6713EL	394
1T6714DA	394
1T6714EL	394
1T6715DA	394
1T6715EL	394
1T6716DA	394
1T6716EL	394
1T6717DA	395
1T6717EL	395
1T6718DA	395
1T6718EL	395
1T6719DA	395
1T6719EL	395
1T6720DA	395
1T6720EL	395
1T6721DA	395
1T6721EL	395
1T6722DA	395
1T6722EL	395
1T6723DA	395
1T6723EL	395
1T6724DA	395
1T6724EL	395
1T6725DA	395
1T6725EL	395
1T6726DA	395
1T6726EL	395
1T6727DA	395
1T6727EL	395
1T6728DA	395
1T6728EL	395
1T6729DA	392
1T6729EL	392
1T6730DA	392
1T6730EL	392
1T6731DA	392
1T6731EL	392
1T6732DA	392
1T6732EL	392
1T6733DA	392
1T6733EL	392
1T6734DA	392
1T6734EL	392
1T6735DA	392
1T6735EL	392
1T6736DA	392
1T6736EL	392
1T6737DA	392
1T6737EL	392
1T6738DA	392
1T6738EL	392
1T6739DA	392
1T6739EL	392
1T6740DA	392
1T6740EL	392
1T6741DA	392
1T6741EL	392
1T6742DA	392
1T6742EL	392
1T6743DA	392
1T6743EL	392
1T6744DA	392
1T6744EL	392
1T6745DA	392
1T6745EL	392
1T6746DA	392
1T6746EL	392
1T6747	290
1T6748	290
1T6749	290
1T6750	290
1T6751	290
1T6752	290
1T6753	290
1T6754	290
1T6755	290
1T6756	290
1T6757	290
1T6758	290
1T6759DA	291
1T6759EL	291
1T6760DA	291
1T6760EL	291
1T6761DA	291
1T6761EL	291
1T6762DA	291
1T6762EL	291
1T6763DA	291
1T6763EL	291
1T6764DA	291
1T6764EL	291
1T6765DA	291
1T6765EL	291
1T6766DA	291
1T6766EL	291
1T6767DA	291
1T6767EL	291
1T6768DA	291
1T6768EL	291
1T6769DA	291
1T6769EL	291
1T6770DA	291
1T6770EL	291
1T6771DA	292
1T6771EL	292
1T6772DA	292
1T6772EL	292
1T6773DA	292
1T6773EL	292
1T6774DA	292
1T6774EL	292
1T6775DA	292
1T6775EL	292
1T6776DA	292
1T6776EL	292
1T6777DA	292
1T6777EL	292
1T6778DA	292
1T6778EL	292
1T6779DA	292
1T6779EL	292
1T6780DA	292
1T6780EL	292
1T6781DA	292
1T6781EL	292
1T6782DA	292
1T6782EL	292
1T6783DA	293
1T6783EL	293
1T6784DA	293
1T6784EL	293
1T6785DA	293
1T6785EL	293
1T6786DA	293
1T6786EL	293
1T6787DA	293

COD.	PAG.
1T6787EL	293
1T6788DA	293
1T6788EL	293
1T6789DA	293
1T6789EL	293
1T6790DA	293
1T6790EL	293
1T6791DA	293
1T6791EL	293
1T6792DA	293
1T6792EL	293
1T6793DA	293
1T6793EL	293
1T6794DA	293
1T6794EL	293
1T6795	294
1T6796	294
1T6797DA	294
1T6797EL	294
1T6798DA	294
1T6798EL	294
1T6799	294
1T6800	293
1T6801	383
1T6806	294
1T6807DA	433
1T6807EL	433
1T6808DA	433
1T6808EL	433
1T6809DA	433
1T6809EL	433
1T6810DA	433
1T6810EL	433
1T6811DA	433
1T6811EL	433
1T6812DA	433
1T6812EL	433
1T6813DA	423
1T6813EL	423
1T6814DA	423
1T6814EL	423
1T6815DA	423
1T6815EL	423
1T6816DA	423
1T6816EL	423
1T6817DA	423
1T6817EL	423
1T6818DA	423
1T6818EL	423
1T6819DA	423
1T6819EL	423
1T6820DA	423
1T6820EL	423
1T6821DA	423
1T6821EL	423
1T6822DA	423
1T6822EL	423
1T6823DA	423
1T6823EL	423
1T6824DA	423
1T6824EL	423
1T6825DA	406
1T6825EL	406
1T6826DA	406
1T6826EL	406
1T6827DA	406
1T6827EL	406
1T6828DA	406
1T6828EL	406
1T6829DA	406
1T6829EL	406
1T6830DA	406
1T6830EL	406
1T6831DA	407
1T6831EL	407
1T6832DA	407
1T6832EL	407
1T6833DA	407
1T6833EL	407
1T6834DA	407
1T6834EL	407

COD.	PAG.
1T6835DA	407
1T6835EL	407
1T6836DA	407
1T6836EL	407
1T6837DA	406
1T6837EL	406
1T6838DA	406
1T6838EL	406
1T6839DA	406
1T6839EL	406
1T6840DA	406
1T6840EL	406
1T6841DA	406
1T6841EL	406
1T6842DA	406
1T6842EL	406
1T6843DA	406
1T6843EL	406
1T6844DA	406
1T6844EL	406
1T6845DA	406
1T6845EL	406
1T6846DA	406
1T6846EL	406
1T6847DA	406
1T6847EL	406
1T6848DA	406
1T6848EL	406
1T6849DA	437
1T6849EL	437
1T6850DA	437
1T6850EL	437
1T6851DA	438
1T6851EL	438
1T6852DA	438
1T6852EL	438
1T6853DA	438
1T6853EL	438
1T6854DA	438
1T6854EL	438
1T6855DA	412
1T6855EL	412
1T6856DA	412
1T6856EL	412
1T6857DA	412
1T6857EL	412
1T6858DA	412
1T6858EL	412
1T6859DA	412
1T6859EL	412
1T6860DA	412
1T6860EL	412
1T6861DA	413
1T6861EL	413
1T6862DA	413
1T6862EL	413
1T6863DA	413
1T6863EL	413
1T6864DA	413
1T6864EL	413
1T6865DA	413
1T6865EL	413
1T6866DA	413
1T6866EL	413
1T6867DA	414
1T6867EL	414
1T6868DA	414
1T6868EL	414
1T6869DA	414
1T6869EL	414
1T6870DA	414
1T6870EL	414
1T6871DA	414
1T6871EL	414
1T6872DA	414
1T6872EL	414
1T6873DA	412
1T6873EL	412
1T6874DA	412
1T6874EL	412
1T6875DA	412

COD.	PAG.
1T6875EL	412
1T6876DA	412
1T6876EL	412
1T6877DA	412
1T6877EL	412
1T6878DA	412
1T6878EL	412
1T6879DA	413
1T6879EL	413
1T6880DA	413
1T6880EL	413
1T6881DA	413
1T6881EL	413
1T6882DA	413
1T6882EL	413
1T6883DA	413
1T6883EL	413
1T6884DA	413
1T6884EL	413
1T6885DA	414
1T6885EL	414
1T6886DA	414
1T6886EL	414
1T6887DA	414
1T6887EL	414
1T6888DA	414
1T6888EL	414
1T6889DA	414
1T6889EL	414
1T6890DA	414
1T6890EL	414
1T6891DA	412
1T6891EL	412
1T6892DA	412
1T6892EL	412
1T6893DA	412
1T6893EL	412
1T6894DA	412
1T6894EL	412
1T6895DA	412
1T6895EL	412
1T6896DA	412
1T6896EL	412
1T6897DA	413
1T6897EL	413
1T6898DA	413
1T6898EL	413
1T6899DA	413
1T6899EL	413
1T6900DA	413
1T6900EL	413
1T6901DA	413
1T6901EL	413
1T6902DA	413
1T6902EL	413
1T6903DA	414
1T6903EL	414
1T6904DA	414
1T6904EL	414
1T6905DA	414
1T6905EL	414
1T6906DA	414
1T6906EL	414
1T6907DA	414
1T6907EL	414
1T6908DA	414
1T6908EL	414
1T6916EL	351, 384
1T6917EL	351, 384
1T6918	271
1T6919	421, 466
1T6920	421, 466
1T6921	421, 466
1T6930	125, 395
1T6931	125, 395
1T6939	397
1T6940	293
1T6945CA	315
1T6946CA	315
1T6947CA	316
1T6948CA	316

COD.	PAG.
1T6955CA	262
1T6956CA	262
1T6957CA	262
1T6958CA	262
1T6959CA	262
1T6960CA	262
1T6961CA	262
1T6962CA	262
1T7003	738, 740
1T7004	281
1T7005	281
1T7006	281
1T7007	281
1T7008	281
1T7009	281
1T7016	351
1T7017	351
1T7018	351
1T7019	351
1T7020	351
1T7021	351
1T7022	351
1T7023	351
1T7024	350
1T7025	350
1T7026	350
1T7027	350
1T7028EL	350
1T7029EL	350
1T7030EL	350
1T7031	367
1T7032	367
1T7033	367
1T7034	367
1T7035	367
1T7036	367
1T7037	368
1T7038	368
1T7039	368
1T7040	368
1T7041	368
1T7043	367
1T7044	369
1T7045	369
1T7046	369
1T7047	369
1T7048	369
1T7049	369
1T7050	369
1T7051	369
1T7052	369
1T7053	369
1T7054	369
1T7055	369
1T7056	370
1T7057	371
1T7058	371
1T7059	370
1T7060	371
1T7061	371
1T7062	370
1T7063	370
1T7064	371
1T7065	370
1T7066	370
1T7067	367
1T7068	367
1T7069	367
1T7070	367
1T7071	367
1T7072	367
1T7073	368
1T7074	368
1T7076	367
1T7077	370
1T7078	370
1T7079	370
1T7080	370
1T7081	370
1T7082	370
1T7083	369
1T7084	369
1T7085	369
1T7086	369
1T7087	369
1T7088	369
1T7089	370
1T7090	371
1T7091	371
1T7092	370
1T7093	371
1T7094	371
1T7095	370
1T7096	370
1T7097	371
1T7098	352
1T7099	354
1T7099CA	353
1T7099DD	353
1T7100	354
1T7100CA	353
1T7100DD	353
1T7101	354
1T7101CA	353
1T7101DD	353
1T7102	354
1T7102CA	353
1T7102DD	353
1T7103	354
1T7103CA	353
1T7103DD	354
1T7104	354
1T7104CA	353
1T7104DD	354
1T7105	354
1T7105CA	353
1T7105DD	354
1T7106	354
1T7106CA	353
1T7106DD	354
1T7107	355
1T7107CA	354
1T7107DD	354
1T7108	355
1T7108CA	354
1T7108DD	354
1T7109	355
1T7109CA	354
1T7109DD	354
1T7110	355
1T7110CA	354
1T7110DD	354
1T7111	354
1T7111CA	353
1T7111DD	353
1T7112	354
1T7112CA	353
1T7112DD	353
1T7113	354
1T7113CA	353
1T7113DD	353
1T7114	354
1T7114CA	353
1T7114DD	353
1T7115	354
1T7115CA	353
1T7115DD	354
1T7116	354
1T7116CA	353
1T7116DD	354
1T7117	354
1T7117CA	353
1T7117DD	354
1T7118	354
1T7118CA	353
1T7118DD	354
1T7119	355
1T7119CA	354
1T7119DD	354
1T7120	355
1T7120CA	354
1T7120DD	354
1T7121	355
1T7121CA	354
1T7121DD	354
1T7122	355
1T7122CA	354
1T7122DD	354
1T7123	357
1T7123CA	355
1T7123DD	355
1T7124	357
1T7124CA	355
1T7124DD	355
1T7125	357
1T7125CA	355
1T7125DD	355
1T7126	357
1T7126CA	355
1T7126DD	355
1T7127	357
1T7127CA	356
1T7127DD	356
1T7128	357
1T7128CA	356
1T7128DD	356
1T7129	357
1T7129CA	356
1T7129DD	356
1T7130	357
1T7130CA	356
1T7130DD	356
1T7131	357
1T7131CA	356
1T7131DD	356
1T7132	357
1T7132CA	356
1T7132DD	356
1T7133	357
1T7133CA	356
1T7133DD	356
1T7134	357
1T7134CA	356
1T7134DD	356
1T7135	357
1T7135CA	355
1T7135DD	355
1T7136	357
1T7136CA	355
1T7136DD	355
1T7137	357
1T7137CA	355
1T7137DD	355
1T7138	357
1T7138CA	355
1T7138DD	355
1T7139	357
1T7139CA	356
1T7139DD	356
1T7140	357
1T7140CA	356
1T7140DD	356
1T7141	357
1T7141CA	356
1T7141DD	356
1T7142	357
1T7142CA	356
1T7142DD	356
1T7143	357
1T7143CA	356
1T7143DD	356
1T7144	357
1T7144CA	356
1T7144DD	356
1T7145	357
1T7145CA	356
1T7145DD	356
1T7146	357
1T7146CA	356
1T7146DD	356
1T7147	359
1T7147CA	358
1T7147DD	358

COD.	PAG.
1T7148	359
1T7148CA	358
1T7148DD	358
1T7149	359
1T7149CA	358
1T7149DD	358
1T7150	359
1T7150CA	358
1T7150DD	358
1T7151	359
1T7151CA	358
1T7151DD	358
1T7152	359
1T7152CA	358
1T7152DD	358
1T7153	359
1T7153CA	358
1T7153DD	358
1T7154	359
1T7154CA	358
1T7154DD	358
1T7155	359
1T7155CA	359
1T7155DD	359
1T7156	359
1T7156CA	359
1T7156DD	359
1T7157	359
1T7157CA	359
1T7157DD	359
1T7158	359
1T7158CA	359
1T7158DD	359
1T7159	359
1T7159CA	358
1T7159DD	358
1T7160	359
1T7160CA	358
1T7160DD	358
1T7161	359
1T7161CA	358
1T7161DD	358
1T7162	359
1T7162CA	358
1T7162DD	358
1T7163	359
1T7163CA	358
1T7163DD	358
1T7164	359
1T7164CA	358
1T7164DD	358
1T7165	359
1T7165CA	358
1T7165DD	358
1T7166	359
1T7166CA	358
1T7166DD	358
1T7167	359
1T7167CA	359
1T7167DD	359
1T7168	359
1T7168CA	359
1T7168DD	359
1T7169	359
1T7169CA	359
1T7169DD	359
1T7170	359
1T7170CA	359
1T7170DD	359
1T7171	383
1T7172EL	350
1T7173DA	439
1T7173EL	439
1T7174DA	439
1T7174EL	439
1T7175DA	439
1T7175EL	439
1T7176DA	439
1T7176EL	439
1T7177DA	439
1T7177EL	439
1T7178DA	439
1T7178EL	439
1T7179DA	452
1T7179EL	452
1T7180DA	452
1T7180EL	452
1T7181DA	452
1T7181EL	452
1T7182DA	452
1T7182EL	452
1T7183DA	452
1T7183EL	452
1T7184DA	452
1T7184EL	452
1T7185DA	439
1T7185EL	439
1T7186DA	440
1T7186EL	440
1T7187DA	440
1T7187EL	440
1T7188DA	439
1T7188EL	439
1T7189DA	440
1T7189EL	440
1T7190DA	440
1T7190EL	440
1T7191DA	452
1T7191EL	452
1T7192DA	452
1T7192EL	452
1T7193DA	452
1T7193EL	452
1T7194DA	452
1T7194EL	452
1T7195DA	452
1T7195EL	452
1T7196DA	452
1T7196EL	452
1T7197DA	427
1T7197EL	427
1T7198DA	427
1T7198EL	427
1T7199DA	427
1T7199EL	427
1T7200DA	427
1T7200EL	427
1T7201DA	427
1T7201EL	427
1T7202DA	427
1T7202EL	427
1T7203DA	427
1T7203EL	427
1T7204DA	427
1T7204EL	427
1T7205DA	427
1T7205EL	427
1T7206DA	427
1T7206EL	427
1T7207DA	427
1T7207EL	427
1T7208DA	427
1T7208EL	427
1T7209DA	427
1T7209EL	427
1T7210DA	428
1T7210EL	428
1T7211DA	428
1T7211EL	428
1T7212DA	427
1T7212EL	427
1T7213DA	428
1T7213EL	428
1T7214DA	428
1T7214EL	428
1T7215DA	427
1T7215EL	427
1T7216DA	428
1T7216EL	428
1T7217DA	428
1T7217EL	428
1T7218DA	427
1T7218EL	427
1T7219DA	428
1T7219EL	428
1T7220DA	428
1T7220EL	428
1T7221DA	415
1T7221EL	415
1T7222DA	415
1T7222EL	415
1T7223DA	415
1T7223EL	415
1T7224DA	415
1T7224EL	415
1T7225DA	415
1T7225EL	415
1T7226DA	415
1T7226EL	415
1T7227DA	415
1T7227EL	415
1T7228DA	415
1T7228EL	415
1T7229DA	415
1T7229EL	415
1T7230DA	415
1T7230EL	415
1T7231DA	415
1T7231EL	415
1T7232DA	415
1T7232EL	415
1T7233DA	415
1T7233EL	415
1T7234DA	415
1T7234EL	415
1T7235DA	415
1T7235EL	415
1T7236DA	415
1T7236EL	415
1T7237DA	415
1T7237EL	415
1T7238DA	415
1T7238EL	415
1T7239DA	415
1T7239EL	415
1T7240DA	416
1T7240EL	416
1T7241DA	416
1T7241EL	416
1T7242DA	415
1T7242EL	415
1T7243DA	416
1T7243EL	416
1T7244DA	416
1T7244EL	416
1T7245DA	415
1T7245EL	415
1T7246DA	416
1T7246EL	416
1T7247DA	416
1T7247EL	416
1T7248DA	415
1T7248EL	415
1T7249DA	416
1T7249EL	416
1T7250DA	416
1T7250EL	416
1T7251DA	415
1T7251EL	415
1T7252DA	416
1T7252EL	416
1T7253DA	416
1T7253EL	416
1T7254DA	415
1T7254EL	415
1T7255DA	416
1T7255EL	416
1T7256DA	416
1T7256EL	416
1T7257DA	440
1T7257EL	440
1T7258DA	440
1T7258EL	440

COD.	PAG.
1T7259DA	440
1T7259EL	440
1T7260DA	440
1T7260EL	440
1T7261DA	440
1T7261EL	440
1T7262DA	440
1T7262EL	440
1T7263DA	452
1T7263EL	452
1T7264DA	452
1T7264EL	452
1T7265DA	452
1T7265EL	452
1T7266DA	452
1T7266EL	452
1T7267DA	458
1T7267EL	458
1T7268DA	458
1T7268EL	458
1T7269DA	441
1T7269EL	441
1T7270DA	441
1T7270EL	441
1T7271DA	441
1T7271EL	441
1T7272DA	441
1T7272EL	441
1T7273DA	441
1T7273EL	441
1T7274DA	441
1T7274EL	441
1T7275DA	458
1T7275EL	458
1T7276DA	458
1T7276EL	458
1T7277DA	458
1T7277EL	458
1T7278DA	458
1T7278EL	458
1T7279DA	458
1T7279EL	458
1T7280DA	458
1T7280EL	458
1T7281DA	428
1T7281EL	428
1T7282DA	428
1T7282EL	428
1T7283DA	428
1T7283EL	428
1T7284DA	428
1T7284EL	428
1T7285DA	428
1T7285EL	428
1T7286DA	428
1T7286EL	428
1T7287DA	428
1T7287EL	428
1T7288DA	428
1T7288EL	428
1T7289DA	428
1T7289EL	428
1T7290DA	428
1T7290EL	428
1T7291DA	428
1T7291EL	428
1T7292DA	428
1T7292EL	428
1T7293DA	429
1T7293EL	429
1T7294DA	429
1T7294EL	429
1T7295DA	429
1T7295EL	429
1T7296DA	429
1T7296EL	429
1T7297DA	429
1T7297EL	429
1T7298DA	429
1T7298EL	429
1T7299DA	429
1T7299EL	429
1T7300DA	429
1T7300EL	429
1T7301DA	429
1T7301EL	429
1T7302DA	429
1T7302EL	429
1T7303DA	429
1T7303EL	429
1T7304DA	429
1T7304EL	429
1T7305DA	416
1T7305EL	416
1T7306DA	416
1T7306EL	416
1T7307DA	416
1T7307EL	416
1T7308DA	416
1T7308EL	416
1T7309DA	416
1T7309EL	416
1T7310DA	416
1T7310EL	416
1T7311DA	416
1T7311EL	416
1T7312DA	416
1T7312EL	416
1T7313DA	416
1T7313EL	416
1T7314DA	416
1T7314EL	416
1T7315DA	416
1T7315EL	416
1T7316DA	416
1T7316EL	416
1T7317DA	416
1T7317EL	416
1T7318DA	416
1T7318EL	416
1T7319DA	416
1T7319EL	416
1T7320DA	416
1T7320EL	416
1T7321DA	416
1T7321EL	416
1T7322DA	416
1T7322EL	416
1T7323DA	417
1T7323EL	417
1T7324DA	417
1T7324EL	417
1T7325DA	417
1T7325EL	417
1T7326DA	417
1T7326EL	417
1T7327DA	417
1T7327EL	417
1T7328DA	417
1T7328EL	417
1T7329DA	417
1T7329EL	417
1T7330DA	417
1T7330EL	417
1T7331DA	417
1T7331EL	417
1T7332DA	417
1T7332EL	417
1T7333DA	417
1T7333EL	417
1T7334DA	417
1T7334EL	417
1T7335DA	417
1T7335EL	417
1T7336DA	417
1T7336EL	417
1T7337DA	417
1T7337EL	417
1T7338DA	417
1T7338EL	417
1T7339DA	417
1T7339EL	417
1T7340DA	417
1T7340EL	417
1T7341DA	442
1T7341EL	442
1T7342DA	442
1T7342EL	442
1T7343DA	458
1T7343EL	458
1T7344DA	458
1T7344EL	458
1T7345DA	430
1T7345EL	430
1T7346DA	430
1T7346EL	430
1T7347DA	430
1T7347EL	430
1T7348DA	430
1T7348EL	430
1T7349DA	418
1T7349EL	418
1T7350DA	418
1T7350EL	418
1T7351DA	418
1T7351EL	418
1T7352DA	418
1T7352EL	418
1T7353DA	418
1T7353EL	418
1T7354DA	418
1T7354EL	418
1T7355DA	442
1T7355EL	442
1T7356DA	442
1T7356EL	442
1T7357DA	458
1T7357EL	458
1T7358DA	458
1T7358EL	458
1T7359DA	430
1T7359EL	430
1T7360DA	430
1T7360EL	430
1T7361DA	430
1T7361EL	430
1T7362DA	430
1T7362EL	430
1T7363DA	418
1T7363EL	418
1T7364DA	418
1T7364EL	418
1T7365DA	418
1T7365EL	418
1T7366DA	418
1T7366EL	418
1T7367DA	418
1T7367EL	418
1T7368DA	418
1T7368EL	418
1T7369	432
1T7370	432
1T7371	443
1T7372	443
1T7373	443
1T7374	444
1T7375	444
1T7381	431
1T7382	431
1T7383	431
1T7384	431
1T7385	419
1T7386	419
1T7387	419
1T7388	420
1T7389	420
1T7390	419
1T7391	419
1T7392	419
1T7393	420
1T7394	420
1T7395	419
1T7396	419

COD.	PAG.
1T7397	419
1T7398	420
1T7399	420
1T7400	193
1T7401	193
1T7402	506, 509, 512
1T7403EL	351, 384
1T7404	184
1T7405	184
1T7406	184
1T7407	361
1T7407CA	360
1T7407DD	360
1T7408	361
1T7408CA	360
1T7408DD	360
1T7409	361
1T7409CA	360
1T7409DD	360
1T7410	361
1T7410CA	360
1T7410DD	360
1T7411	361
1T7411CA	360
1T7411DD	361
1T7412	361
1T7412CA	360
1T7412DD	361
1T7413	361
1T7413CA	360
1T7413DD	361
1T7414	361
1T7414CA	360
1T7414DD	361
1T7415	362
1T7415CA	361
1T7415DD	361
1T7416	362
1T7416CA	361
1T7416DD	361
1T7417	362
1T7417CA	361
1T7417DD	361
1T7418	362
1T7418CA	361
1T7418DD	361
1T7419	361
1T7419CA	360
1T7419DD	360
1T7420	361
1T7420CA	360
1T7420DD	360
1T7421	361
1T7421CA	360
1T7421DD	360
1T7422	361
1T7422CA	360
1T7422DD	360
1T7423	361
1T7423CA	360
1T7423DD	361
1T7424	361
1T7424CA	360
1T7424DD	361
1T7424DD	361
1T7425CA	360
1T7425DD	361
1T7426	361
1T7426CA	360
1T7426DD	361
1T7427	362
1T7427CA	361
1T7427DD	361
1T7428	362
1T7428CA	361
1T7428DD	361
1T7429	362
1T7429CA	361
1T7429DD	361
1T7430	362
1T7430CA	361
1T7430DD	361
1T7431	350
1T7432	350
1T7433	350
1T7434	350
1T7435	350
1T7436	350
1T7437	368
1T7438	368
1T7439	352
1T7440	352
1T7441	363
1T7441CA	363
1T7441DD	363
1T7442	363
1T7442CA	363
1T7442DD	363
1T7443	363
1T7443CA	363
1T7443DD	363
1T7444	363
1T7444CA	363
1T7444DD	363
1T7445	363
1T7445CA	363
1T7445DD	363
1T7446	363
1T7446CA	363
1T7446DD	363
1T7447	363
1T7447CA	363
1T7447DD	363
1T7448	363
1T7448CA	363
1T7448DD	363
1T7449	363
1T7449CA	363
1T7449DD	363
1T7450	363
1T7450CA	363
1T7450DD	363
1T7451	363
1T7451CA	363
1T7451DD	363
1T7452	363
1T7452CA	363
1T7452DD	363
1T7453	363
1T7453CA	363
1T7453DD	363
1T7454	363
1T7454CA	363
1T7454DD	363
1T7455	363
1T7455CA	363
1T7455DD	363
1T7456	363
1T7456CA	363
1T7456DD	363
1T7457	363
1T7457CA	363
1T7457DD	363
1T7458	363
1T7458CA	363
1T7458DD	363
1T7459	363
1T7459CA	363
1T7459DD	363
1T7460	363
1T7460CA	363
1T7460DD	363
1T7461	363
1T7461CA	363
1T7461DD	363
1T7462	363
1T7462CA	363
1T7462DD	363
1T7463	363
1T7463CA	363
1T7463DD	363
1T7464	363
1T7464CA	363
1T7464DD	363
1T7465	363
1T7465CA	363
1T7465DD	363
1T7466	363
1T7466CA	363
1T7466DD	363
1T7467	363
1T7467CA	363
1T7467DD	363
1T7468	363
1T7468CA	363
1T7468DD	363
1T7469	364
1T7469CA	364
1T7469DD	364
1T7470	364
1T7470CA	364
1T7470DD	364
1T7471	364
1T7471CA	364
1T7471DD	364
1T7472	364
1T7472CA	364
1T7472DD	364
1T7473	364
1T7473CA	364
1T7473DD	364
1T7474	364
1T7474CA	364
1T7474DD	364
1T7475	364
1T7475CA	364
1T7475DD	364
1T7476	364
1T7476CA	364
1T7476DD	364
1T7477	363
1T7477CA	363
1T7477DD	363
1T7478	363
1T7478CA	363
1T7478DD	363
1T7479	363
1T7479CA	363
1T7479DD	363
1T7480	363
1T7480CA	363
1T7480DD	363
1T7481	364
1T7481CA	364
1T7481DD	364
1T7482	364
1T7482CA	364
1T7482DD	364
1T7483	364
1T7483CA	364
1T7483DD	364
1T7484	364
1T7484CA	364
1T7484DD	364
1T7485	364
1T7485CA	364
1T7485DD	364
1T7486	364
1T7486CA	364
1T7486DD	364
1T7487	364
1T7487CA	364
1T7487DD	364
1T7488	364
1T7488CA	364
1T7488DD	364
1T7489	366
1T7490	366
1T7491	366
1T7492	366
1T7493	366
1T7494	366
1T7495	366

COD.	PAG.
1T7496	366
1T7497	366
1T7498	366
1T7499	366
1T7500	366
1T7501	366
1T7506	353
1T7507	353
1T7508	353
1T7509	353
1T7510	353
1T7511	353
1T7512	353
1T7513	353
1T7514	354
1T7515	354
1T7516	354
1T7517	354
1T7518	353
1T7519	353
1T7520	353
1T7521	353
1T7522	353
1T7523	353
1T7524	353
1T7525	353
1T7526	354
1T7527	354
1T7528	354
1T7529	354
1T7530	355
1T7531	355
1T7532	355
1T7533	355
1T7534	356
1T7535	356
1T7536	356
1T7537	356
1T7538	356
1T7539	356
1T7540	356
1T7541	356
1T7542	355
1T7543	355
1T7544	355
1T7545	355
1T7546	356
1T7547	356
1T7548	356
1T7549	356
1T7550	356
1T7551	356
1T7552	356
1T7553	356
1T7554	357
1T7555	357
1T7556	357
1T7557	357
1T7558	358
1T7559	358
1T7560	358
1T7561	358
1T7562	358
1T7563	358
1T7564	358
1T7565	358
1T7566	357
1T7567	357
1T7568	357
1T7569	357
1T7570	358
1T7571	358
1T7572	358
1T7573	358
1T7574	358
1T7575	358
1T7576	358
1T7577	358
1T7578	360
1T7579	360
1T7580	360
1T7581	360
1T7582	360
1T7583	360
1T7584	360
1T7585	360
1T7586	361
1T7587	361
1T7588	361
1T7589	361
1T7590	360
1T7591	360
1T7592	360
1T7593	360
1T7594	360
1T7595	360
1T7596	360
1T7597	360
1T7598	361
1T7599	361
1T7600	361
1T7601	361
1T7606	152
1T7607	152
1T7608	152
1T7609	152
1T7610	152
1T7611	152
1T7612	152
1T7613	152
1T7618	152
1T7619	152
1T7620	152
1T7621	152
1T7622	152
1T7623	152
1T7624	152
1T7625	152
1T7630	152
1T7631	152
1T7632	152
1T7633	152
1T7634	153
1T7635	153
1T7636	153
1T7637	153
1T7642	152
1T7643	152
1T7644	152
1T7645	152
1T7646	153
1T7647	153
1T7648	153
1T7649	153
1T7654	153
1T7655	153
1T7656	153
1T7657	153
1T7658	154
1T7659	154
1T7660	154
1T7661	154
1T7666	153
1T7667	153
1T7668	153
1T7669	153
1T7670	154
1T7671	154
1T7672	154
1T7673	154
1T7678	159
1T7679	159
1T7680	159
1T7681	159
1T7682	159
1T7683	159
1T7684	159
1T7685	159
1T7686DA	158, 165
1T7702	159
1T7703	159
1T7704	159
1T7705	159
1T7706	160
1T7707	160
1T7708	160
1T7709	160
1T7726	160
1T7727	160
1T7728	160
1T7729	160
1T7730	161
1T7731	161
1T7732	161
1T7733	161
1T7746DA	154
1T7746EL	154
1T7747DA	154
1T7747EL	154
1T7748DA	154
1T7748EL	154
1T7749DA	154
1T7749EL	154
1T7750DA	155
1T7750EL	155
1T7751DA	155
1T7751EL	155
1T7752DA	155
1T7752EL	155
1T7753DA	155
1T7753EL	155
1T7754DA	155
1T7754EL	155
1T7755DA	155
1T7755EL	155
1T7756DA	155
1T7756EL	155
1T7757DA	155
1T7757EL	155
1T7758DA	154
1T7758EL	154
1T7759DA	154
1T7759EL	154
1T7760DA	154
1T7760EL	154
1T7761DA	154
1T7761EL	154
1T7762DA	155
1T7762EL	155
1T7763DA	155
1T7763EL	155
1T7764DA	155
1T7764EL	155
1T7765DA	155
1T7765EL	155
1T7766DA	155
1T7766EL	155
1T7767DA	155
1T7767EL	155
1T7768DA	155
1T7768EL	155
1T7769DA	155
1T7769EL	155
1T7770DA	155
1T7770EL	155
1T7771DA	155
1T7771EL	155
1T7772DA	155
1T7772EL	155
1T7773DA	155
1T7773EL	155
1T7774DA	155
1T7774EL	155
1T7775DA	155
1T7775EL	155
1T7776DA	155
1T7776EL	155
1T7777DA	155
1T7777EL	155
1T7778DA	156
1T7778EL	156
1T7779DA	156
1T7779EL	156

COD.	PAG.
1T7780DA	156
1T7780EL	156
1T7781DA	156
1T7781EL	156
1T7782DA	155
1T7782EL	155
1T7783DA	155
1T7783EL	155
1T7784DA	155
1T7784EL	155
1T7785DA	155
1T7785EL	155
1T7786DA	155
1T7786EL	155
1T7787DA	155
1T7787EL	155
1T7788DA	155
1T7788EL	155
1T7789DA	155
1T7789EL	155
1T7790DA	156
1T7790EL	156
1T7791DA	156
1T7791EL	156
1T7792DA	156
1T7792EL	156
1T7793DA	156
1T7793EL	156
1T7794DA	156
1T7794EL	156
1T7795DA	156
1T7795EL	156
1T7796DA	156
1T7796EL	156
1T7797DA	156
1T7797EL	156
1T7798DA	157
1T7798EL	157
1T7799DA	157
1T7799EL	157
1T7800DA	157
1T7800EL	157
1T7801DA	157
1T7801EL	157
1T7802DA	157
1T7802EL	157
1T7803DA	157
1T7803EL	157
1T7804DA	157
1T7804EL	157
1T7805DA	157
1T7805EL	157
1T7806DA	156
1T7806EL	156
1T7807DA	156
1T7807EL	156
1T7808DA	156
1T7808EL	156
1T7809DA	156
1T7809EL	156
1T7810DA	157
1T7810EL	157
1T7811DA	157
1T7811EL	157
1T7812DA	157
1T7812EL	157
1T7813DA	157
1T7813EL	157
1T7814DA	157
1T7814EL	157
1T7815DA	157
1T7815EL	157
1T7816DA	157
1T7816EL	157
1T7817DA	157
1T7817EL	157
1T7818DA	161
1T7818EL	161
1T7819DA	161
1T7819EL	161
1T7820DA	161
1T7820EL	161
1T7821DA	161
1T7821EL	161
1T7822DA	162
1T7822EL	162
1T7823DA	162
1T7823EL	162
1T7824DA	162
1T7824EL	162
1T7825DA	162
1T7825EL	162
1T7826DA	162
1T7826EL	162
1T7827DA	162
1T7827EL	162
1T7828DA	162
1T7828EL	162
1T7829DA	162
1T7829EL	162
1T7830DA	123
1T7830EL	123
1T7831DA	123
1T7831EL	123
1T7832DA	123
1T7832EL	123
1T7833DA	123
1T7833EL	123
1T7834DA	123
1T7834EL	123
1T7835DA	123
1T7835EL	123
1T7836DA	123
1T7836EL	123
1T7837DA	123
1T7837EL	123
1T7838DA	123
1T7838EL	123
1T7839DA	123
1T7839EL	123
1T7840DA	123
1T7840EL	123
1T7841DA	123
1T7841EL	123
1T7842DA	162
1T7842EL	162
1T7843DA	162
1T7843EL	162
1T7844DA	162
1T7844EL	162
1T7845DA	162
1T7845EL	162
1T7846DA	162
1T7846EL	162
1T7847DA	162
1T7847EL	162
1T7848DA	162
1T7848EL	162
1T7849DA	162
1T7849EL	162
1T7850DA	163
1T7850EL	163
1T7851DA	163
1T7851EL	163
1T7852DA	163
1T7852EL	163
1T7853DA	163
1T7853EL	163
1T7854DA	123
1T7854EL	123
1T7855DA	124
1T7855EL	124
1T7856DA	123
1T7856EL	123
1T7857DA	124
1T7857EL	124
1T7858DA	123
1T7858EL	123
1T7859DA	124
1T7859EL	124
1T7860DA	123
1T7860EL	123
1T7861DA	124
1T7861EL	124
1T7862DA	124
1T7862EL	124
1T7863DA	124
1T7863EL	124
1T7864DA	124
1T7864EL	124
1T7865DA	124
1T7865EL	124
1T7866DA	163
1T7866EL	163
1T7867DA	163
1T7867EL	163
1T7868DA	163
1T7868EL	163
1T7869DA	163
1T7869EL	163
1T7870DA	164
1T7870EL	164
1T7871DA	164
1T7871EL	164
1T7872DA	164
1T7872EL	164
1T7873DA	164
1T7873EL	164
1T7874DA	164
1T7874EL	164
1T7875DA	164
1T7875EL	164
1T7876DA	164
1T7876EL	164
1T7877DA	164
1T7877EL	164
1T7878DA	124
1T7878EL	124
1T7879DA	124
1T7879EL	124
1T7880DA	124
1T7880EL	124
1T7881DA	124
1T7881EL	124
1T7882DA	123
1T7882EL	123
1T7883DA	123
1T7883EL	123
1T7884DA	123
1T7884EL	123
1T7885DA	123
1T7885EL	123
1T7886DA	125
1T7886EL	125
1T7887DA	125
1T7887EL	125
1T7888DA	125
1T7888EL	125
1T7889DA	125
1T7889EL	125
1T7890DA	486
1T7890EL	486
1T7891DA	486
1T7891EL	486
1T7892DA	486
1T7892EL	486
1T7893DA	486
1T7893EL	486
1T7894DA	486
1T7894EL	486
1T7895DA	486
1T7895EL	486
1T7896DA	486
1T7896EL	486
1T7897DA	486
1T7897EL	486
1T7898DA	486
1T7898EL	486
1T7899DA	486
1T7899EL	486
1T7900DA	486
1T7900EL	486
1T7901DA	486

COD.	PAG.
1T7901EL	486
1T7902DA	486
1T7902EL	486
1T7903DA	486
1T7903EL	486
1T7904DA	486
1T7904EL	486
1T7905DA	486
1T7905EL	486
1T7906DA	486
1T7906EL	486
1T7907DA	486
1T7907EL	486
1T7908DA	486
1T7908EL	486
1T7909DA	486
1T7909EL	486
1T7910DA	486
1T7910EL	486
1T7911DA	486
1T7911EL	486
1T7912DA	486
1T7912EL	486
1T7913DA	486
1T7913EL	486
1T7914DA	487
1T7914EL	487
1T7915DA	487
1T7915EL	487
1T7916DA	487
1T7916EL	487
1T7917DA	487
1T7917EL	487
1T7918DA	487
1T7918EL	487
1T7919DA	487
1T7919EL	487
1T7920DA	487
1T7920EL	487
1T7921DA	487
1T7921EL	487
1T7922DA	487
1T7922EL	487
1T7923DA	487
1T7923EL	487
1T7924DA	487
1T7924EL	487
1T7925DA	487
1T7925EL	487
1T7926DA	487
1T7926EL	487
1T7927DA	487
1T7927EL	487
1T7928DA	487
1T7928EL	487
1T7929DA	487
1T7929EL	487
1T7930DA	487
1T7930EL	487
1T7931DA	487
1T7931EL	487
1T7932DA	487
1T7932EL	487
1T7933DA	487
1T7933EL	487
1T7934DA	487
1T7934EL	487
1T7935DA	487
1T7935EL	487
1T7936DA	487
1T7936EL	487
1T7937DA	487
1T7937EL	487
1T7938	352
1T7939	352
1T7940	352
1T7941	352
1T7942	352
1T7943	352
1T7944	580, 581, 812
1T7945CA	355
1T7946CA	359
1T7947CA	357
1T7948CA	362
1T7949CA	355
1T7950CA	359
1T7951CA	357
1T7952CA	362
1T7953CA	355
1T7954CA	359
1T7955CA	357
1T7956CA	362
1T7957CA	355
1T7958CA	359
1T7959CA	357
1T7960CA	362
1T7961CA	355
1T7962CA	359
1T7963CA	357
1T7964CA	362
1T7965CA	355
1T7966CA	359
1T7967CA	357
1T7968CA	362
1T7969CA	355
1T7970CA	359
1T7971CA	357
1T7972CA	362
1T7973CA	355
1T7974CA	359
1T7975CA	357
1T7976CA	362
1T7977CA	230
1T7978CA	230
1T7979CA	230
1T7980CA	230
1T7981CA	230
1T7982CA	230
1T7983CA	230
1T7984CA	230
1T7985CA	230
1T7986CA	230
1T7987CA	230
1T7988CA	230
1T7989CA	230
1T7990CA	230
1T7991CA	230
1T7992CA	230
1T7993CA	230
1T7994CA	230
1T7995CA	230
1T7996CA	230
1T7997CA	222
1T7997D	220
1T7997DA	221
1T7997EL	219
1T7998CA	222
1T7998D	220
1T7998DA	221
1T7998EL	219
1T7999CA	222
1T7999D	220
1T7999DA	221
1T7999EL	219
1T8000CA	222
1T8000D	220
1T8000DA	221
1T8000EL	219
1T8001CA	222
1T8001D	220
1T8001DA	221
1T8001EL	219
1T8002CA	222
1T8002D	220
1T8002DA	221
1T8002EL	219
1T8003CA	222
1T8003D	220
1T8003DA	221
1T8003EL	219
1T8004CA	222
1T8004D	220
1T8004DA	221
1T8004EL	219
1T8005CA	223
1T8005D	220
1T8005DA	221
1T8005EL	219
1T8006CA	223
1T8006D	220
1T8006DA	221
1T8006EL	219
1T8007CA	223
1T8007D	220
1T8007DA	221
1T8007EL	219
1T8008CA	223
1T8008D	220
1T8008DA	221
1T8008EL	219
1T8009CA	223
1T8009D	220
1T8009DA	222
1T8009EL	219
1T8010CA	223
1T8010D	220
1T8010DA	222
1T8010EL	219
1T8011CA	223
1T8011D	220
1T8011DA	222
1T8011EL	219
1T8012CA	223
1T8012D	220
1T8012DA	222
1T8012EL	219
1T8013CA	223
1T8013D	221
1T8013DA	222
1T8013EL	219
1T8014CA	223
1T8014D	221
1T8014DA	222
1T8014EL	219
1T8015CA	223
1T8015D	221
1T8015DA	222
1T8015EL	219
1T8016CA	223
1T8016D	221
1T8016DA	222
1T8016EL	219
1T8017CA	223
1T8017D	221
1T8017DA	222
1T8017EL	220
1T8018CA	223
1T8018D	221
1T8018DA	222
1T8018EL	220
1T8019CA	223
1T8019D	221
1T8019DA	222
1T8019EL	220
1T8020CA	223
1T8020D	221
1T8020DA	222
1T8020EL	220
1T8021CA	223
1T8022CA	223
1T8023CA	223
1T8024CA	223
1T8025CA	216
1T8025D	217
1T8025DA	216
1T8025EL	216
1T8026CA	216
1T8026D	217
1T8026DA	216
1T8026EL	216
1T8027CA	216
1T8027D	217
1T8027DA	216

COD.	PAG.
1T8027EL	216
1T8028CA	216
1T8028D	217
1T8028DA	216
1T8028EL	216
1T8029CA	216
1T8029D	217
1T8029DA	216
1T8029EL	216
1T8030CA	216
1T8030D	217
1T8030DA	216
1T8030EL	216
1T8031CA	216
1T8031D	217
1T8031DA	216
1T8031EL	216
1T8032CA	216
1T8032D	217
1T8032DA	216
1T8032EL	216
1T8033CA	216
1T8033D	217
1T8033DA	216
1T8033EL	216
1T8034CA	216
1T8034D	217
1T8034DA	216
1T8034EL	216
1T8035CA	216
1T8035D	217
1T8035DA	216
1T8035EL	216
1T8036CA	216
1T8036D	217
1T8036DA	216
1T8036EL	216
1T8037CA	216
1T8037D	217
1T8037DA	216
1T8037EL	216
1T8038CA	216
1T8038D	217
1T8038DA	216
1T8038EL	216
1T8039CA	216
1T8039D	217
1T8039DA	216
1T8039EL	216
1T8040CA	216
1T8040D	217
1T8040DA	216
1T8040EL	216
1T8041CA	216
1T8041D	218
1T8041DA	216
1T8041EL	216
1T8042CA	216
1T8042D	218
1T8042DA	216
1T8042EL	216
1T8043CA	216
1T8043D	218
1T8043DA	216
1T8043EL	216
1T8044CA	216
1T8044D	218
1T8044DA	216
1T8044EL	216
1T8045CA	217
1T8045D	218
1T8045DA	217
1T8045EL	217
1T8046CA	217
1T8046D	218
1T8046DA	217
1T8046EL	217
1T8047CA	217
1T8047D	218
1T8047DA	217
1T8047EL	217
1T8048CA	217
1T8048D	218
1T8048DA	217
1T8048EL	217
1T8049DA	388
1T8049EL	388
1T8050DA	388
1T8050EL	388
1T8051DA	388
1T8051EL	388
1T8052DA	388
1T8052EL	388
1T8053DA	388
1T8053EL	388
1T8054DA	388
1T8054EL	388
1T8055DA	388
1T8055EL	388
1T8056DA	388
1T8056EL	388
1T8057DA	388
1T8057EL	388
1T8058DA	388
1T8058EL	388
1T8059DA	388
1T8059EL	388
1T8060DA	388
1T8060EL	388
1T8061DA	388
1T8061EL	388
1T8062DA	388
1T8062EL	388
1T8063DA	388
1T8063EL	388
1T8064DA	388
1T8064EL	388
1T8065DA	388
1T8065EL	388
1T8066DA	388
1T8066EL	388
1T8067DA	388
1T8067EL	388
1T8068DA	388
1T8068EL	388
1T8069DA	388
1T8069EL	388
1T8070DA	388
1T8070EL	388
1T8071DA	388
1T8071EL	388
1T8072DA	388
1T8072EL	388
1T8073DA	388
1T8073EL	388
1T8074DA	388
1T8074EL	388
1T8075DA	388
1T8075EL	388
1T8076DA	388
1T8076EL	388
1T8077DA	388
1T8077EL	388
1T8078DA	388
1T8078EL	388
1T8079DA	389
1T8079EL	389
1T8080DA	389
1T8080EL	389
1T8081DA	389
1T8081EL	389
1T8082DA	389
1T8082EL	389
1T8083DA	389
1T8083EL	389
1T8084DA	389
1T8084EL	389
1T8093	120, 142, 238, 390
1T8094	120, 142, 238, 390
1T8100DA	389
1T8100EL	389
1T8101DA	389
1T8101EL	389
1T8102DA	389
1T8102EL	389
1T8103DA	389
1T8103EL	389
1T8104DA	389
1T8104EL	389
1T8105DA	389
1T8105EL	389
1T8106DA	389
1T8106EL	389
1T8107DA	389
1T8107EL	389
1T8108DA	389
1T8108EL	389
1T8109DA	389
1T8109EL	389
1T8110DA	389
1T8110EL	389
1T8111DA	389
1T8111EL	389
1T8112DA	389
1T8112EL	389
1T8113DA	389
1T8113EL	389
1T8114DA	389
1T8114EL	389
1T8115DA	389
1T8115EL	389
1T8116DA	389
1T8116EL	389
1T8117DA	389
1T8117EL	389
1T8118DA	389
1T8118EL	389
1T8119DA	389
1T8119EL	389
1T8120DA	389
1T8120EL	389
1T8121DA	389
1T8121EL	389
1T8122DA	389
1T8122EL	389
1T8123DA	389
1T8123EL	389
1T8124DA	390
1T8124EL	390
1T8125DA	390
1T8125EL	390
1T8126DA	390
1T8126EL	390
1T8127DA	390
1T8127EL	390
1T8128DA	390
1T8128EL	390
1T8129DA	390
1T8129EL	390
1T8130DA	390
1T8130EL	390
1T8131DA	390
1T8131EL	390
1T8132DA	390
1T8132EL	390
1T8133DA	390
1T8133EL	390
1T8134DA	390
1T8134EL	390
1T8135DA	390
1T8135EL	390
1T8136DA	237
1T8136EL	236
1T8137DA	237
1T8137EL	236
1T8138DA	237
1T8138EL	236
1T8139DA	237
1T8139EL	236
1T8140DA	237
1T8140EL	236
1T8141DA	237
1T8141EL	236

COD.	PAG.
1T8142DA	237
1T8142EL	236
1T8143DA	237
1T8143EL	236
1T8144DA	237
1T8144EL	236
1T8145DA	237
1T8145EL	236
1T8146DA	237
1T8146EL	236
1T8147DA	237
1T8147EL	236
1T8148DA	237
1T8148EL	236
1T8149DA	237
1T8149EL	236
1T8150DA	237
1T8150EL	236
1T8151DA	237
1T8151EL	236
1T8152DA	237
1T8152EL	236
1T8153DA	237
1T8153EL	236
1T8154DA	237
1T8154EL	236
1T8155DA	237
1T8155EL	236
1T8156DA	237
1T8156EL	236
1T8157DA	237
1T8157EL	236
1T8158DA	237
1T8158EL	236
1T8159DA	237
1T8159EL	236
1T8160DA	238
1T8160EL	236
1T8161DA	238
1T8161EL	236
1T8162DA	238
1T8162EL	236
1T8163DA	238
1T8163EL	236
1T8164DA	238
1T8164EL	236
1T8165DA	238
1T8165EL	236
1T8166DA	238
1T8166EL	237
1T8167DA	238
1T8167EL	237
1T8168DA	238
1T8168EL	237
1T8169DA	238
1T8169EL	237
1T8170DA	238
1T8170EL	237
1T8171DA	238
1T8171EL	237
1T8172DA	158, 165
1T8172EL	158, 165
1T8173CA	352, 806
1T8174CA	226
1T8174D	225
1T8174DA	226
1T8174EL	225
1T8175CA	226
1T8175D	225
1T8175DA	226
1T8175EL	225
1T8176CA	226
1T8176D	225
1T8176DA	226
1T8176EL	225
1T8177CA	226
1T8177D	225
1T8177DA	226
1T8177EL	225
1T8178D	228
1T8178DA	229
1T8178EL	227
1T8179D	228
1T8179DA	229
1T8179EL	227
1T8180D	228
1T8180DA	229
1T8180EL	227
1T8181D	228
1T8181DA	229
1T8181EL	227
1T8182D	228
1T8182DA	229
1T8182EL	227
1T8183D	228
1T8183DA	229
1T8183EL	227
1T8184D	228
1T8184DA	229
1T8184EL	227
1T8185D	228
1T8185DA	229
1T8185EL	227
1T8186D	228
1T8186DA	229
1T8186EL	227
1T8187D	228
1T8187DA	229
1T8187EL	227
1T8188D	228
1T8188DA	229
1T8188EL	227
1T8189D	228
1T8189DA	229
1T8189EL	227
1T8190	365
1T8190CA	365
1T8191	365
1T8191CA	365
1T8192	365
1T8192CA	365
1T8193	365
1T8193CA	365
1T8194	365
1T8194CA	365
1T8195	365
1T8195CA	365
1T8196	365
1T8196CA	365
1T8197	365
1T8197CA	365
1T8198	365
1T8198CA	365
1T8199	365
1T8199CA	365
1T8200	365
1T8200CA	365
1T8201	365
1T8201CA	365
1T8202	365
1T8202CA	365
1T8203	365
1T8203CA	365
1T8204	365
1T8204CA	365
1T8205	365
1T8205CA	365
1T8206DA	188
1T8206EL	188
1T8207DA	188
1T8207EL	188
1T8208DA	188
1T8208EL	188
1T8209DA	188
1T8209EL	188
1T8210DA	188
1T8210EL	188
1T8211DA	188
1T8211EL	188
1T8212DA	188
1T8212EL	188
1T8213DA	188
1T8213EL	188
1T8214DA	188
1T8214EL	188
1T8215DA	188
1T8215EL	188
1T8216DA	188
1T8216EL	188
1T8217DA	188
1T8217EL	188
1T8218DA	93
1T8218EL	93
1T8219DA	93
1T8219EL	93
1T8220DA	93
1T8220EL	93
1T8221DA	93
1T8221EL	93
1T8222DA	93
1T8222EL	93
1T8223DA	93
1T8223EL	93
1T8224DA	93
1T8224EL	93
1T8225DA	93
1T8225EL	93
1T8226DA	93
1T8226EL	93
1T8227DA	93
1T8227EL	93
1T8228DA	93
1T8228EL	93
1T8229DA	93
1T8229EL	93
1T8230DA	93
1T8230EL	93
1T8231DA	94
1T8231EL	94
1T8232DA	94
1T8232EL	94
1T8233DA	93
1T8233EL	93
1T8234DA	94
1T8234EL	94
1T8235DA	94
1T8235EL	94
1T8236DA	93
1T8236EL	93
1T8237DA	94
1T8237EL	94
1T8238DA	94
1T8238EL	94
1T8239DA	93
1T8239EL	93
1T8240DA	94
1T8240EL	94
1T8241DA	94
1T8241EL	94
1T8242DA	93
1T8242EL	93
1T8243DA	93
1T8243EL	93
1T8244DA	93
1T8244EL	93
1T8245DA	93
1T8245EL	93
1T8246DA	93
1T8246EL	93
1T8247DA	93
1T8247EL	93
1T8248DA	93
1T8248EL	93
1T8249DA	93
1T8249EL	93
1T8250DA	93
1T8250EL	93
1T8251DA	93
1T8251EL	93
1T8252DA	93
1T8252EL	93
1T8253DA	93
1T8253EL	93

COD.	PAG.
1T8254DA	93
1T8254EL	93
1T8255DA	94
1T8255EL	94
1T8256DA	94
1T8256EL	94
1T8257DA	93
1T8257EL	93
1T8258DA	94
1T8258EL	94
1T8259DA	94
1T8259EL	94
1T8260DA	93
1T8260EL	93
1T8261DA	94
1T8261EL	94
1T8262DA	94
1T8262EL	94
1T8263DA	93
1T8263EL	93
1T8264DA	94
1T8264EL	94
1T8265DA	94
1T8265EL	94
1T8266DA	102
1T8266EL	102
1T8267DA	102
1T8267EL	102
1T8268DA	102
1T8268EL	102
1T8269DA	102
1T8269EL	102
1T8270DA	102
1T8270EL	102
1T8271DA	102
1T8271EL	102
1T8272DA	102
1T8272EL	102
1T8273DA	102
1T8273EL	102
1T8274DA	102
1T8274EL	102
1T8275DA	102
1T8275EL	102
1T8276DA	102
1T8276EL	102
1T8277DA	102
1T8277EL	102
1T8278DA	102
1T8278EL	102
1T8279DA	102
1T8279EL	102
1T8280DA	102
1T8280EL	102
1T8281DA	102
1T8281EL	102
1T8290DA	95
1T8290EL	95
1T8291DA	95
1T8291EL	95
1T8292DA	95
1T8292EL	95
1T8293DA	95
1T8293EL	95
1T8294DA	95
1T8294EL	95
1T8295DA	95
1T8295EL	95
1T8296DA	95
1T8296EL	95
1T8297DA	95
1T8297EL	95
1T8298DA	95
1T8298EL	95
1T8299DA	95
1T8299EL	95
1T8300DA	95
1T8300EL	95
1T8301DA	95
1T8301EL	95
1T8302DA	96
1T8302EL	96
1T8303DA	96
1T8303EL	96
1T8304DA	96
1T8304EL	96
1T8305DA	96
1T8305EL	96
1T8306DA	96
1T8306EL	96
1T8307DA	96
1T8307EL	96
1T8308DA	96
1T8308EL	96
1T8309DA	96
1T8309EL	96
1T8310DA	96
1T8310EL	96
1T8311DA	96
1T8311EL	96
1T8312DA	96
1T8312EL	96
1T8313DA	96
1T8313EL	96
1T8314DA	108
1T8314EL	108
1T8315DA	108
1T8315EL	108
1T8316DA	108
1T8316EL	108
1T8317DA	108
1T8317EL	108
1T8318DA	108
1T8318EL	108
1T8319DA	108
1T8319EL	108
1T8320DA	108
1T8320EL	108
1T8321DA	108
1T8321EL	108
1T8322DA	108
1T8322EL	108
1T8323DA	108
1T8323EL	108
1T8324DA	108
1T8324EL	108
1T8325DA	108
1T8325EL	108
1T8326DA	95
1T8326EL	95
1T8327DA	95
1T8327EL	95
1T8328DA	95
1T8328EL	95
1T8329DA	95
1T8329EL	95
1T8330DA	95
1T8330EL	95
1T8331DA	95
1T8331EL	95
1T8332DA	95
1T8332EL	95
1T8333DA	95
1T8333EL	95
1T8334DA	95
1T8334EL	95
1T8335DA	95
1T8335EL	95
1T8336DA	95
1T8336EL	95
1T8337DA	95
1T8337EL	95
1T8338DA	96
1T8338EL	96
1T8339DA	96
1T8339EL	96
1T8340DA	96
1T8340EL	96
1T8341DA	96
1T8341EL	96
1T8342DA	96
1T8342EL	96
1T8343DA	96
1T8343EL	96
1T8344DA	96
1T8344EL	96
1T8345DA	96
1T8345EL	96
1T8346DA	96
1T8346EL	96
1T8347DA	96
1T8347EL	96
1T8348DA	96
1T8348EL	96
1T8349DA	96
1T8349EL	96
1T8350DA	108
1T8350EL	108
1T8351DA	108
1T8351EL	108
1T8352DA	108
1T8352EL	108
1T8353DA	108
1T8353EL	108
1T8354DA	108
1T8354EL	108
1T8355DA	108
1T8355EL	108
1T8356DA	108
1T8356EL	108
1T8357DA	108
1T8357EL	108
1T8358DA	108
1T8358EL	108
1T8359DA	108
1T8359EL	108
1T8360DA	108
1T8360EL	108
1T8361DA	108
1T8361EL	108
1T8370DA	118
1T8370EL	118
1T8371DA	118
1T8371EL	118
1T8372DA	118
1T8372EL	118
1T8373DA	118
1T8373EL	118
1T8374DA	118
1T8374EL	118
1T8375DA	118
1T8375EL	118
1T8376DA	120
1T8376EL	120
1T8377DA	118
1T8377EL	118
1T8378DA	118
1T8378EL	118
1T8379DA	120
1T8379EL	120
1T8380DA	118
1T8380EL	118
1T8381DA	118
1T8381EL	118
1T8382DA	120
1T8382EL	120
1T8383DA	118
1T8383EL	118
1T8384DA	118
1T8384EL	118
1T8385DA	120
1T8385EL	120
1T8386DA	118
1T8386EL	118
1T8387DA	118
1T8387EL	118
1T8388DA	120
1T8388EL	120
1T8389DA	118
1T8389EL	118
1T8390DA	118
1T8390EL	118
1T8391DA	120

COD.	PAG.
1T8391EL	120
1T8392DA	118
1T8392EL	118
1T8393DA	118
1T8393EL	118
1T8394DA	120
1T8394EL	120
1T8395DA	118
1T8395EL	118
1T8396DA	118
1T8396EL	118
1T8397DA	120
1T8397EL	120
1T8398DA	98
1T8398EL	98
1T8399DA	98
1T8399EL	98
1T8400DA	98
1T8400EL	98
1T8401DA	98
1T8401EL	98
1T8402DA	98
1T8402EL	98
1T8403DA	98
1T8403EL	98
1T8404DA	98
1T8404EL	98
1T8405DA	98
1T8405EL	98
1T8406DA	98
1T8406EL	98
1T8407DA	99
1T8407EL	99
1T8408DA	98
1T8408EL	98
1T8409DA	99
1T8409EL	99
1T8410DA	98
1T8410EL	98
1T8411DA	99
1T8411EL	99
1T8412DA	98
1T8412EL	98
1T8413DA	99
1T8413EL	99
1T8414DA	110
1T8414EL	110
1T8415DA	110
1T8415EL	110
1T8416DA	110
1T8416EL	110
1T8417DA	110
1T8417EL	110
1T8418DA	110
1T8418EL	110
1T8419DA	110
1T8419EL	110
1T8420DA	110
1T8420EL	110
1T8421DA	110
1T8421EL	110
1T8422DA	98
1T8422EL	98
1T8423DA	98
1T8423EL	98
1T8424DA	98
1T8424EL	98
1T8425DA	98
1T8425EL	98
1T8426DA	98
1T8426EL	98
1T8427DA	98
1T8427EL	98
1T8428DA	98
1T8428EL	98
1T8429DA	98
1T8429EL	98
1T8430DA	98
1T8430EL	98
1T8431DA	99
1T8431EL	99

COD.	PAG.
1T8432DA	98
1T8432EL	98
1T8433DA	99
1T8433EL	99
1T8434DA	98
1T8434EL	98
1T8435DA	99
1T8435EL	99
1T8436DA	98
1T8436EL	98
1T8437DA	99
1T8437EL	99
1T8438DA	110
1T8438EL	110
1T8439DA	110
1T8439EL	110
1T8440DA	110
1T8440EL	110
1T8441DA	110
1T8441EL	110
1T8442DA	110
1T8442EL	110
1T8443DA	110
1T8443EL	110
1T8444DA	110
1T8444EL	110
1T8445DA	110
1T8445EL	110
1T8446DA	127
1T8446EL	127
1T8447DA	127
1T8447EL	127
1T8448DA	127
1T8448EL	127
1T8449DA	127
1T8449EL	127
1T8450DA	127
1T8450EL	127
1T8451DA	127
1T8451EL	127
1T8452DA	127
1T8452EL	127
1T8453DA	127
1T8453EL	127
1T8454DA	127
1T8454EL	127
1T8455DA	127
1T8455EL	127
1T8456DA	127
1T8456EL	127
1T8457DA	127
1T8457EL	127
1T8458DA	127
1T8458EL	127
1T8459DA	127
1T8459EL	127
1T8460DA	127
1T8460EL	127
1T8461DA	127
1T8461EL	127
1T8462DA	127
1T8462EL	127
1T8463DA	127
1T8463EL	127
1T8464DA	127
1T8464EL	127
1T8465DA	127
1T8465EL	127
1T8466DA	127
1T8466EL	127
1T8467DA	127
1T8467EL	127
1T8468DA	127
1T8468EL	127
1T8469DA	127
1T8469EL	127
1T8470DA	127
1T8470EL	127
1T8471DA	127
1T8471EL	127
1T8472DA	127

COD.	PAG.
1T8472EL	127
1T8473DA	127
1T8473EL	127
1T8474DA	127
1T8474EL	127
1T8475DA	127
1T8475EL	127
1T8476DA	127
1T8476EL	127
1T8477DA	127
1T8477EL	127
1T8478DA	127
1T8478EL	127
1T8479DA	127
1T8479EL	127
1T8480DA	127
1T8480EL	127
1T8481DA	127
1T8481EL	127
1T8482DA	155
1T8482EL	155
1T8483DA	155
1T8483EL	155
1T8484DA	155
1T8484EL	155
1T8485DA	155
1T8485EL	155
1T8486DA	155
1T8486EL	155
1T8487DA	155
1T8487EL	155
1T8488DA	155
1T8488EL	155
1T8489DA	155
1T8489EL	155
1T8490DA	156
1T8490EL	156
1T8491DA	156
1T8491EL	156
1T8492DA	156
1T8492EL	156
1T8493DA	156
1T8493EL	156
1T8494DA	119
1T8494EL	119
1T8495DA	119
1T8495EL	119
1T8496DA	120
1T8496EL	120
1T8497DA	119
1T8497EL	119
1T8498DA	119
1T8498EL	119
1T8499DA	120
1T8499EL	120
1T8500DA	119
1T8500EL	119
1T8501DA	119
1T8501EL	119
1T8502DA	120
1T8502EL	120
1T8503DA	119
1T8503EL	119
1T8504DA	119
1T8504EL	119
1T8505DA	120
1T8505EL	120
1T8506DA	119
1T8506EL	119
1T8507DA	119
1T8507EL	119
1T8508DA	119
1T8508EL	119
1T8509DA	119
1T8509EL	119
1T8510DA	119
1T8510EL	119
1T8511DA	119
1T8511EL	119
1T8512DA	119
1T8512EL	119

COD.	PAG.
1T8513DA	119
1T8513EL	119
1T8514DA	119
1T8514EL	119
1T8515DA	119
1T8515EL	119
1T8516DA	119
1T8516EL	119
1T8517DA	119
1T8517EL	119
1T8518DA	156
1T8518EL	156
1T8519DA	156
1T8519EL	156
1T8520DA	156
1T8520EL	156
1T8521DA	156
1T8521EL	156
1T8522DA	156
1T8522EL	156
1T8523DA	156
1T8523EL	156
1T8524DA	156
1T8524EL	156
1T8525DA	156
1T8525EL	156
1T8526DA	156
1T8526EL	156
1T8527DA	156
1T8527EL	156
1T8528DA	156
1T8528EL	156
1T8529DA	156
1T8529EL	156
1T8530DA	156
1T8530EL	156
1T8531DA	156
1T8531EL	156
1T8532DA	156
1T8532EL	156
1T8533DA	156
1T8533EL	156
1T8534DA	156
1T8534EL	156
1T8535DA	156
1T8535EL	156
1T8536DA	156
1T8536EL	156
1T8537DA	156
1T8537EL	156
1T8538DA	157
1T8538EL	157
1T8539DA	157
1T8539EL	157
1T8540DA	157
1T8540EL	157
1T8541DA	157
1T8541EL	157
1T8542DA	101
1T8542EL	101
1T8543DA	101
1T8543EL	101
1T8544DA	101
1T8544EL	101
1T8545DA	101
1T8545EL	101
1T8546DA	101
1T8546EL	101
1T8547DA	101
1T8547EL	101
1T8548DA	101
1T8548EL	101
1T8549DA	101
1T8549EL	101
1T8550DA	111
1T8550EL	111
1T8551DA	111
1T8551EL	111
1T8552DA	111
1T8552EL	111
1T8553DA	111
1T8553EL	111
1T8554DA	101
1T8554EL	101
1T8555DA	101
1T8555EL	101
1T8556DA	101
1T8556EL	101
1T8557DA	101
1T8557EL	101
1T8558DA	101
1T8558EL	101
1T8559DA	101
1T8559EL	101
1T8560DA	101
1T8560EL	101
1T8561DA	101
1T8561EL	101
1T8562DA	111
1T8562EL	111
1T8563DA	111
1T8563EL	111
1T8564DA	111
1T8564EL	111
1T8565DA	111
1T8565EL	111
1T8566DA	119
1T8566EL	119
1T8567DA	119
1T8567EL	119
1T8568DA	119
1T8568EL	119
1T8569DA	119
1T8569EL	119
1T8570DA	119
1T8570EL	119
1T8571DA	119
1T8571EL	119
1T8572DA	119
1T8572EL	119
1T8573DA	119
1T8573EL	119
1T8574DA	119
1T8574EL	119
1T8575DA	119
1T8575EL	119
1T8576DA	119
1T8576EL	119
1T8577DA	119
1T8577EL	119
1T8578DA	118
1T8578EL	118
1T8579DA	118
1T8579EL	118
1T8580DA	118
1T8580EL	118
1T8581DA	118
1T8581EL	118
1T8582DA	118
1T8582EL	118
1T8583DA	118
1T8583EL	118
1T8584DA	120
1T8584EL	120
1T8585DA	118
1T8585EL	118
1T8586DA	118
1T8586EL	118
1T8587DA	120
1T8587EL	120
1T8588DA	118
1T8588EL	118
1T8589DA	118
1T8589EL	118
1T8590DA	120
1T8590EL	120
1T8591DA	118
1T8591EL	118
1T8592DA	118
1T8592EL	118
1T8593DA	120
1T8593EL	120
1T8594DA	118
1T8594EL	118
1T8595DA	118
1T8595EL	118
1T8596DA	120
1T8596EL	120
1T8597DA	118
1T8597EL	118
1T8598DA	118
1T8598EL	118
1T8599DA	120
1T8599EL	120
1T8600DA	118
1T8600EL	118
1T8601DA	118
1T8601EL	118
1T8602DA	120
1T8602EL	120
1T8603DA	118
1T8603EL	118
1T8604DA	118
1T8604EL	118
1T8605DA	120
1T8605EL	120
1T8606DA	119
1T8606EL	119
1T8607DA	119
1T8607EL	119
1T8608DA	120
1T8608EL	120
1T8609DA	119
1T8609EL	119
1T8610DA	119
1T8610EL	119
1T8611DA	120
1T8611EL	120
1T8612DA	119
1T8612EL	119
1T8613DA	119
1T8613EL	119
1T8614DA	120
1T8614EL	120
1T8615DA	119
1T8615EL	119
1T8616DA	119
1T8616EL	119
1T8617DA	120
1T8617EL	120
1T8618DA	118
1T8618EL	118
1T8619DA	118
1T8619EL	118
1T8620DA	118
1T8620EL	118
1T8621DA	118
1T8621EL	118
1T8622DA	118
1T8622EL	118
1T8623DA	118
1T8623EL	118
1T8624DA	120
1T8624EL	120
1T8625DA	118
1T8625EL	118
1T8626DA	118
1T8626EL	118
1T8627DA	120
1T8627EL	120
1T8628DA	118
1T8628EL	118
1T8629DA	118
1T8629EL	118
1T8630DA	120
1T8630EL	120
1T8631DA	118
1T8631EL	118
1T8632DA	118
1T8632EL	118
1T8633DA	120
1T8633EL	120
1T8634DA	118

COD.	PAG.
1T8634EL	118
1T8635DA	118
1T8635EL	118
1T8636DA	120
1T8636EL	120
1T8637DA	118
1T8637EL	118
1T8638DA	118
1T8638EL	118
1T8639DA	120
1T8639EL	120
1T8640DA	118
1T8640EL	118
1T8641DA	118
1T8641EL	118
1T8642DA	120
1T8642EL	120
1T8643DA	118
1T8643EL	118
1T8644DA	118
1T8644EL	118
1T8645DA	120
1T8645EL	120
1T8646DA	119
1T8646EL	119
1T8647DA	119
1T8647EL	119
1T8648DA	120
1T8648EL	120
1T8649DA	119
1T8649EL	119
1T8650DA	119
1T8650EL	119
1T8651DA	120
1T8651EL	120
1T8652DA	119
1T8652EL	119
1T8653DA	119
1T8653EL	119
1T8654DA	120
1T8654EL	120
1T8655DA	119
1T8655EL	119
1T8656DA	119
1T8656EL	119
1T8657DA	120
1T8657EL	120
1T8658DA	119
1T8658EL	119
1T8659DA	119
1T8659EL	119
1T8660DA	119
1T8660EL	119
1T8661DA	119
1T8661EL	119
1T8662DA	119
1T8662EL	119
1T8663DA	119
1T8663EL	119
1T8664DA	119
1T8664EL	119
1T8665DA	119
1T8665EL	119
1T8666DA	119
1T8666EL	119
1T8667DA	119
1T8667EL	119
1T8668DA	119
1T8668EL	119
1T8669DA	119
1T8669EL	119
1T8670DA	119
1T8670EL	119
1T8671DA	119
1T8671EL	119
1T8672DA	119
1T8672EL	119
1T8673DA	119
1T8673EL	119
1T8674DA	119
1T8674EL	119
1T8675DA	119
1T8675EL	119
1T8676DA	119
1T8676EL	119
1T8677DA	119
1T8677EL	119
1T8678DA	119
1T8678EL	119
1T8679DA	119
1T8679EL	119
1T8680DA	119
1T8680EL	119
1T8681DA	119
1T8681EL	119
1T8682DA	123
1T8682EL	123
1T8683DA	123
1T8683EL	123
1T8684DA	123
1T8684EL	123
1T8685DA	123
1T8685EL	123
1T8686DA	123
1T8686EL	123
1T8687DA	123
1T8687EL	123
1T8688DA	123
1T8688EL	123
1T8689DA	123
1T8689EL	123
1T8690DA	123
1T8690EL	123
1T8691DA	124
1T8691EL	124
1T8692DA	123
1T8692EL	123
1T8693DA	124
1T8693EL	124
1T8694DA	123
1T8694EL	123
1T8695DA	124
1T8695EL	124
1T8696DA	123
1T8696EL	123
1T8697DA	124
1T8697EL	124
1T8698DA	122
1T8698EL	122
1T8699DA	122
1T8699EL	122
1T8700DA	122
1T8700EL	122
1T8701DA	122
1T8701EL	122
1T8702DA	122
1T8702EL	122
1T8703DA	122
1T8703EL	122
1T8704DA	124
1T8704EL	124
1T8705DA	122
1T8705EL	122
1T8706DA	122
1T8706EL	122
1T8707DA	124
1T8707EL	124
1T8708DA	122
1T8708EL	122
1T8709DA	122
1T8709EL	122
1T8710DA	124
1T8710EL	124
1T8711DA	122
1T8711EL	122
1T8712DA	122
1T8712EL	122
1T8713DA	124
1T8713EL	124
1T8714DA	122
1T8714EL	122
1T8715DA	122
1T8715EL	122
1T8716DA	124
1T8716EL	124
1T8717DA	122
1T8717EL	122
1T8718DA	122
1T8718EL	122
1T8719DA	124
1T8719EL	124
1T8720DA	122
1T8720EL	122
1T8721DA	122
1T8721EL	122
1T8722DA	124
1T8722EL	124
1T8723DA	122
1T8723EL	122
1T8724DA	122
1T8724EL	122
1T8725DA	124
1T8725EL	124
1T8726DA	123
1T8726EL	123
1T8727DA	123
1T8727EL	123
1T8728DA	122
1T8728EL	122
1T8729DA	123
1T8729EL	123
1T8730DA	123
1T8730EL	123
1T8731DA	122
1T8731EL	122
1T8732DA	123
1T8732EL	123
1T8733DA	123
1T8733EL	123
1T8734DA	122
1T8734EL	122
1T8735DA	123
1T8735EL	123
1T8736DA	123
1T8736EL	123
1T8737DA	122
1T8737EL	122
1T8738DA	122
1T8738EL	122
1T8739DA	122
1T8739EL	122
1T8740DA	122
1T8740EL	122
1T8741DA	122
1T8741EL	122
1T8742DA	122
1T8742EL	122
1T8743DA	122
1T8743EL	122
1T8744DA	122
1T8744EL	122
1T8745DA	122
1T8745EL	122
1T8746DA	122
1T8746EL	122
1T8747DA	122
1T8747EL	122
1T8748DA	122
1T8748EL	122
1T8749DA	122
1T8749EL	122
1T8750DA	122
1T8750EL	122
1T8751DA	122
1T8751EL	122
1T8752DA	122
1T8752EL	122
1T8753DA	122
1T8753EL	122
1T8754DA	122
1T8754EL	122
1T8755DA	122
1T8755EL	122

COD.	PAG.
1T8756DA	122
1T8756EL	122
1T8757DA	122
1T8757EL	122
1T8758DA	122
1T8758EL	122
1T8759DA	122
1T8759EL	122
1T8760DA	122
1T8760EL	122
1T8761DA	122
1T8761EL	122
1T8762DA	122
1T8762EL	122
1T8763DA	122
1T8763EL	122
1T8764DA	122
1T8764EL	122
1T8765DA	122
1T8765EL	122
1T8766DA	123
1T8766EL	123
1T8767DA	123
1T8767EL	123
1T8768DA	122
1T8768EL	122
1T8769DA	123
1T8769EL	123
1T8770DA	123
1T8770EL	123
1T8771DA	122
1T8771EL	122
1T8772DA	123
1T8772EL	123
1T8773DA	123
1T8773EL	123
1T8774DA	122
1T8774EL	122
1T8775DA	123
1T8775EL	123
1T8776DA	123
1T8776EL	123
1T8777DA	122
1T8777EL	122
1T8778DA	122
1T8778EL	122
1T8779DA	122
1T8779EL	122
1T8780DA	122
1T8780EL	122
1T8781DA	122
1T8781EL	122
1T8782DA	123
1T8782EL	123
1T8783DA	123
1T8783EL	123
1T8784DA	123
1T8784EL	123
1T8785DA	123
1T8785EL	123
1T8786DA	123
1T8786EL	123
1T8787DA	123
1T8787EL	123
1T8788DA	123
1T8788EL	123
1T8789DA	123
1T8789EL	123
1T8790DA	123
1T8790EL	123
1T8791DA	123
1T8791EL	123
1T8792DA	123
1T8792EL	123
1T8793DA	123
1T8793EL	123
1T8794DA	123
1T8794EL	123
1T8795DA	123
1T8795EL	123
1T8796DA	123

COD.	PAG.
1T8796EL	123
1T8797DA	123
1T8797EL	123
1T8798DA	123
1T8798EL	123
1T8799DA	123
1T8799EL	123
1T8800DA	123
1T8800EL	123
1T8801DA	123
1T8801EL	123
1T8802DA	123
1T8802EL	123
1T8803DA	124
1T8803EL	124
1T8804DA	123
1T8804EL	123
1T8805DA	124
1T8805EL	124
1T8806DA	123
1T8806EL	123
1T8807DA	124
1T8807EL	124
1T8808DA	123
1T8808EL	123
1T8809DA	124
1T8809EL	124
1T8810DA	124
1T8810EL	124
1T8811DA	124
1T8811EL	124
1T8812DA	124
1T8812EL	124
1T8813DA	124
1T8813EL	124
1T8814DA	124
1T8814EL	124
1T8815DA	124
1T8815EL	124
1T8816DA	124
1T8816EL	124
1T8817DA	124
1T8817EL	124
1T8818DA	125
1T8818EL	125
1T8819DA	125
1T8819EL	125
1T8820DA	125
1T8820EL	125
1T8821DA	125
1T8821EL	125
1T8822DA	125
1T8822EL	125
1T8823DA	125
1T8823EL	125
1T8824DA	125
1T8824EL	125
1T8825DA	125
1T8825EL	125
1T8826DA	125
1T8826EL	125
1T8827DA	125
1T8827EL	125
1T8828DA	125
1T8828EL	125
1T8829DA	125
1T8829EL	125
1T8830DA	125
1T8830EL	125
1T8831DA	125
1T8831EL	125
1T8832DA	125
1T8832EL	125
1T8833DA	125
1T8833EL	125
1T8834DA	125
1T8834EL	125
1T8835DA	125
1T8835EL	125
1T8836DA	125
1T8836EL	125

COD.	PAG.
1T8837DA	125
1T8837EL	125
1T8838DA	125
1T8838EL	125
1T8839DA	125
1T8839EL	125
1T8840DA	125
1T8840EL	125
1T8841DA	125
1T8841EL	125
1T8842DA	125
1T8842EL	125
1T8843DA	125
1T8843EL	125
1T8844DA	125
1T8844EL	125
1T8845DA	125
1T8845EL	125
1T8846DA	125
1T8846EL	125
1T8847DA	125
1T8847EL	125
1T8848DA	125
1T8848EL	125
1T8849DA	125
1T8849EL	125
1T8850DA	157
1T8850EL	157
1T8851DA	157
1T8851EL	157
1T8852DA	157
1T8852EL	157
1T8853DA	157
1T8853EL	157
1T8854DA	157
1T8854EL	157
1T8855DA	157
1T8855EL	157
1T8856DA	157
1T8856EL	157
1T8857DA	157
1T8857EL	157
1T8858DA	157
1T8858EL	157
1T8859DA	157
1T8859EL	157
1T8860DA	157
1T8860EL	157
1T8861DA	157
1T8861EL	157
1T8862DA	157
1T8862EL	157
1T8863DA	157
1T8863EL	157
1T8864DA	157
1T8864EL	157
1T8865DA	157
1T8865EL	157
1T8866DA	157
1T8866EL	157
1T8867DA	157
1T8867EL	157
1T8868DA	157
1T8868EL	157
1T8869DA	157
1T8869EL	157
1T8870DA	162
1T8870EL	162
1T8871DA	162
1T8871EL	162
1T8872DA	162
1T8872EL	162
1T8873DA	162
1T8873EL	162
1T8874DA	163
1T8874EL	163
1T8875DA	163
1T8875EL	163
1T8876DA	163
1T8876EL	163
1T8877DA	163

COD.	PAG.
1T8877EL	163
1T8878DA	163
1T8878EL	163
1T8879DA	163
1T8879EL	163
1T8880DA	163
1T8880EL	163
1T8881DA	163
1T8881EL	163
1T8882DA	163
1T8882EL	163
1T8883DA	163
1T8883EL	163
1T8884DA	163
1T8884EL	163
1T8885DA	163
1T8885EL	163
1T8886DA	164
1T8886EL	164
1T8887DA	164
1T8887EL	164
1T8888DA	164
1T8888EL	164
1T8889DA	164
1T8889EL	164
1T8890DA	164
1T8890EL	164
1T8891DA	164
1T8891EL	164
1T8892DA	164
1T8892EL	164
1T8893DA	164
1T8893EL	164
1T8894DA	164
1T8894EL	164
1T8895DA	164
1T8895EL	164
1T8896DA	164
1T8896EL	164
1T8897DA	164
1T8897EL	164
1T8898DA	486
1T8898EL	486
1T8899DA	486
1T8899EL	486
1T8900DA	486
1T8900EL	486
1T8901DA	486
1T8901EL	486
1T8902DA	486
1T8902EL	486
1T8903DA	486
1T8903EL	486
1T8904DA	486
1T8904EL	486
1T8905DA	486
1T8905EL	486
1T8906DA	487
1T8906EL	487
1T8907DA	487
1T8907EL	487
1T8908DA	487
1T8908EL	487
1T8909DA	487
1T8909EL	487
1T8910DA	486
1T8910EL	486
1T8911DA	486
1T8911EL	486
1T8912DA	486
1T8912EL	486
1T8913DA	486
1T8913EL	486
1T8914DA	486
1T8914EL	486
1T8915DA	486
1T8915EL	486
1T8916DA	486
1T8916EL	486
1T8917DA	486
1T8917EL	486
1T8918DA	487
1T8918EL	487
1T8919DA	487
1T8919EL	487
1T8920	290
1T8921	290
1T8922	290
1T8923	290
1T8924DA	291
1T8924EL	291
1T8925DA	291
1T8925EL	291
1T8926DA	291
1T8926EL	291
1T8927DA	291
1T8927EL	291
1T8928DA	292
1T8928EL	292
1T8929DA	292
1T8929EL	292
1T8930DA	292
1T8930EL	292
1T8931DA	292
1T8931EL	292
1T8932DA	293
1T8932EL	293
1T8933DA	293
1T8933EL	293
1T8934DA	293
1T8934EL	293
1T8935DA	293
1T8935EL	293
1T8936DA	487
1T8936EL	487
1T8937DA	487
1T8937EL	487
1T8938DA	487
1T8938EL	487
1T8939DA	487
1T8939EL	487
1T8940DA	487
1T8940EL	487
1T8941DA	487
1T8941EL	487
1T8942DA	488
1T8942EL	488
1T8943DA	488
1T8943EL	488
1T8944DA	488
1T8944EL	488
1T8945DA	488
1T8945EL	488
1T8946DA	488
1T8946EL	488
1T8947DA	488
1T8947EL	488
1T8948DA	488
1T8948EL	488
1T8949DA	488
1T8949EL	488
1T8950DA	487
1T8950EL	487
1T8951DA	487
1T8951EL	487
1T8952DA	487
1T8952EL	487
1T8953DA	487
1T8953EL	487
1T8954DA	488
1T8954EL	488
1T8955DA	488
1T8955EL	488
1T8956DA	488
1T8956EL	488
1T8957DA	488
1T8957EL	488
1T8958DA	488
1T8958EL	488
1T8959DA	488
1T8959EL	488
1T8960DA	488
1T8960EL	488
1T8961DA	488
1T8961EL	488
1T8962	152
1T8963	152
1T8964	152
1T8965	152
1T8966	152
1T8967	152
1T8968	152
1T8969	152
1T8970	153
1T8971	153
1T8972	153
1T8973	153
1T8974	153
1T8975	153
1T8976	153
1T8977	153
1T8978	153
1T8979	153
1T8980	153
1T8981	153
1T8982	153
1T8983	153
1T8984	153
1T8985	153
1T8986	153
1T8987	153
1T8988	153
1T8989	153
1T8990	153
1T8991	153
1T8992	153
1T8993	153
1T8994	154
1T8995	154
1T8996	154
1T8997	154
1T8998	154
1T8999	154
1T9000	154
1T9001	154
1T9002	154
1T9003	154
1T9004	154
1T9005	154
1T9006	154
1T9007	154
1T9008	154
1T9009	154
1T9010	154
1T9011	154
1T9012	154
1T9013	154
1T9014	154
1T9015	154
1T9016	154
1T9017	154
1T9018	159
1T9019	159
1T9020	159
1T9021	159
1T9022	160
1T9023	160
1T9024	160
1T9025	160
1T9026	160
1T9027	160
1T9028	160
1T9029	160
1T9030	160
1T9031	160
1T9032	160
1T9033	160
1T9034	161
1T9035	161
1T9036	161
1T9037	161
1T9038	161
1T9039	161

COD.	PAG.
1T9040	161
1T9041	161
1T9042	161
1T9043	161
1T9044	161
1T9045	161
1T9046DA	391
1T9046EL	391
1T9047DA	391
1T9047EL	391
1T9048DA	391
1T9048EL	391
1T9049DA	391
1T9049EL	391
1T9050DA	391
1T9050EL	391
1T9051DA	391
1T9051EL	391
1T9052DA	391
1T9052EL	391
1T9053DA	391
1T9053EL	391
1T9054DA	391
1T9054EL	391
1T9055DA	391
1T9055EL	391
1T9056DA	391
1T9056EL	391
1T9057DA	391
1T9057EL	391
1T9058DA	392
1T9058EL	392
1T9059DA	392
1T9059EL	392
1T9060DA	392
1T9060EL	392
1T9061DA	392
1T9061EL	392
1T9062DA	392
1T9062EL	392
1T9063DA	392
1T9063EL	392
1T9064DA	392
1T9064EL	392
1T9065DA	392
1T9065EL	392
1T9066DA	392
1T9066EL	392
1T9067DA	392
1T9067EL	392
1T9068DA	392
1T9068EL	392
1T9069DA	392
1T9069EL	392
1T9070DA	393
1T9070EL	393
1T9071DA	393
1T9071EL	393
1T9072DA	393
1T9072EL	393
1T9073DA	393
1T9073EL	393
1T9074DA	393
1T9074EL	393
1T9075DA	393
1T9075EL	393
1T9076DA	393
1T9076EL	393
1T9077DA	393
1T9077EL	393
1T9078DA	393
1T9078EL	393
1T9079DA	393
1T9079EL	393
1T9080DA	393
1T9080EL	393
1T9081DA	393
1T9081EL	393
1T9082DA	240
1T9082EL	239
1T9083DA	240
1T9083EL	239
1T9084DA	240
1T9084EL	239
1T9085DA	240
1T9085EL	239
1T9086DA	240
1T9086EL	239
1T9087DA	240
1T9087EL	239
1T9088DA	241
1T9088EL	239
1T9089DA	241
1T9089EL	239
1T9090DA	241
1T9090EL	239
1T9091DA	241
1T9091EL	239
1T9092DA	241
1T9092EL	239
1T9093DA	241
1T9093EL	239
1T9094DA	241
1T9094EL	240
1T9095DA	241
1T9095EL	240
1T9096DA	241
1T9096EL	240
1T9097DA	241
1T9097EL	240
1T9098DA	241
1T9098EL	240
1T9099DA	241
1T9099EL	240
1T9100DA	132
1T9100EL	132
1T9101DA	132
1T9101EL	132
1T9102DA	132
1T9102EL	132
1T9103DA	132
1T9103EL	132
1T9104DA	132
1T9104EL	132
1T9105DA	132
1T9105EL	132
1T9106DA	132
1T9106EL	132
1T9107DA	132
1T9107EL	132
1T9108DA	132
1T9108EL	132
1T9109DA	132
1T9109EL	132
1T9110DA	132
1T9110EL	132
1T9111DA	132
1T9111EL	132
1T9112DA	132
1T9112EL	132
1T9113DA	132
1T9113EL	132
1T9114DA	133
1T9114EL	133
1T9115DA	132
1T9115EL	132
1T9116DA	132
1T9116EL	132
1T9117DA	133
1T9117EL	133
1T9118DA	132
1T9118EL	132
1T9119DA	132
1T9119EL	132
1T9120DA	133
1T9120EL	133
1T9121DA	132
1T9121EL	132
1T9122DA	132
1T9122EL	132
1T9123DA	133
1T9123EL	133
1T9124DA	133
1T9124EL	133
1T9125DA	133
1T9125EL	133
1T9126DA	133
1T9126EL	133
1T9127DA	133
1T9127EL	133
1T9128DA	133
1T9128EL	133
1T9129DA	133
1T9129EL	133
1T9130DA	133
1T9130EL	133
1T9131DA	133
1T9131EL	133
1T9132DA	133
1T9132EL	133
1T9133DA	133
1T9133EL	133
1T9134DA	133
1T9134EL	133
1T9135DA	133
1T9135EL	133
1T9136DA	133
1T9136EL	133
1T9137DA	133
1T9137EL	133
1T9138DA	134
1T9138EL	134
1T9139DA	133
1T9139EL	133
1T9140DA	133
1T9140EL	133
1T9141DA	134
1T9141EL	134
1T9142DA	133
1T9142EL	133
1T9143DA	133
1T9143EL	133
1T9144DA	134
1T9144EL	134
1T9145DA	133
1T9145EL	133
1T9146DA	133
1T9146EL	133
1T9147DA	134
1T9147EL	134
1T9148DA	132
1T9148EL	132
1T9149DA	132
1T9149EL	132
1T9150DA	132
1T9150EL	132
1T9151DA	132
1T9151EL	132
1T9152DA	132
1T9152EL	132
1T9153DA	132
1T9153EL	132
1T9154DA	132
1T9154EL	132
1T9155DA	132
1T9155EL	132
1T9156DA	132
1T9156EL	132
1T9157DA	132
1T9157EL	132
1T9158DA	132
1T9158EL	132
1T9159DA	132
1T9159EL	132
1T9160DA	132
1T9160EL	132
1T9161DA	132
1T9161EL	132
1T9162DA	133
1T9162EL	133
1T9163DA	132
1T9163EL	132
1T9164DA	132

COD.	PAG.
1T9164EL	132
1T9165DA	133
1T9165EL	133
1T9166DA	132
1T9166EL	132
1T9167DA	132
1T9167EL	132
1T9168DA	133
1T9168EL	133
1T9169DA	132
1T9169EL	132
1T9170DA	132
1T9170EL	132
1T9171DA	133
1T9171EL	133
1T9172DA	133
1T9172EL	133
1T9173DA	133
1T9173EL	133
1T9174DA	133
1T9174EL	133
1T9175DA	133
1T9175EL	133
1T9176DA	133
1T9176EL	133
1T9177DA	133
1T9177EL	133
1T9178DA	133
1T9178EL	133
1T9179DA	133
1T9179EL	133
1T9180DA	133
1T9180EL	133
1T9181DA	133
1T9181EL	133
1T9182DA	133
1T9182EL	133
1T9183DA	133
1T9183EL	133
1T9184DA	133
1T9184EL	133
1T9185DA	133
1T9185EL	133
1T9186DA	134
1T9186EL	134
1T9187DA	133
1T9187EL	133
1T9188DA	133
1T9188EL	133
1T9189DA	134
1T9189EL	134
1T9190DA	133
1T9190EL	133
1T9191DA	133
1T9191EL	133
1T9192DA	134
1T9192EL	134
1T9193DA	133
1T9193EL	133
1T9194DA	133
1T9194EL	133
1T9195DA	134
1T9195EL	134
1T9196DA	135
1T9196EL	135
1T9197DA	135
1T9197EL	135
1T9198DA	135
1T9198EL	135
1T9199DA	135
1T9199EL	135
1T9200DA	135
1T9200EL	135
1T9201DA	135
1T9201EL	135
1T9202DA	135
1T9202EL	135
1T9203DA	135
1T9203EL	135
1T9204DA	135
1T9204EL	135

COD.	PAG.
1T9205DA	135
1T9205EL	135
1T9206DA	135
1T9206EL	135
1T9207DA	135
1T9207EL	135
1T9208DA	135
1T9208EL	135
1T9209DA	135
1T9209EL	135
1T9210DA	135
1T9210EL	135
1T9211DA	135
1T9211EL	135
1T9212DA	135
1T9212EL	135
1T9213DA	135
1T9213EL	135
1T9214DA	135
1T9214EL	135
1T9215DA	135
1T9215EL	135
1T9216DA	136
1T9216EL	136
1T9217DA	136
1T9217EL	136
1T9218DA	136
1T9218EL	136
1T9219DA	136
1T9219EL	136
1T9220DA	136
1T9220EL	136
1T9221DA	136
1T9221EL	136
1T9222DA	136
1T9222EL	136
1T9223DA	136
1T9223EL	136
1T9224DA	136
1T9224EL	136
1T9225DA	136
1T9225EL	136
1T9226DA	136
1T9226EL	136
1T9227DA	136
1T9227EL	136
1T9228DA	136
1T9228EL	136
1T9229DA	136
1T9229EL	136
1T9230DA	136
1T9230EL	136
1T9231DA	136
1T9231EL	136
1T9232DA	136
1T9232EL	136
1T9233DA	136
1T9233EL	136
1T9234DA	136
1T9234EL	136
1T9235DA	136
1T9235EL	136
1T9236DA	136
1T9236EL	136
1T9237DA	137
1T9237EL	137
1T9238DA	136
1T9238EL	136
1T9239DA	137
1T9239EL	137
1T9240DA	136
1T9240EL	136
1T9241DA	137
1T9241EL	137
1T9242DA	136
1T9242EL	136
1T9243DA	137
1T9243EL	137
1T9244DA	137
1T9244EL	137
1T9245DA	137

COD.	PAG.
1T9245EL	137
1T9246DA	137
1T9246EL	137
1T9247DA	137
1T9247EL	137
1T9248DA	137
1T9248EL	137
1T9249DA	137
1T9249EL	137
1T9250DA	137
1T9250EL	137
1T9251DA	137
1T9251EL	137
1T9252DA	135
1T9252EL	135
1T9253DA	135
1T9253EL	135
1T9254DA	135
1T9254EL	135
1T9255DA	135
1T9255EL	135
1T9256DA	135
1T9256EL	135
1T9257DA	135
1T9257EL	135
1T9258DA	135
1T9258EL	135
1T9259DA	135
1T9259EL	135
1T9260DA	135
1T9260EL	135
1T9261DA	135
1T9261EL	135
1T9262DA	135
1T9262EL	135
1T9263DA	135
1T9263EL	135
1T9264DA	135
1T9264EL	135
1T9265DA	135
1T9265EL	135
1T9266DA	135
1T9266EL	135
1T9267DA	135
1T9267EL	135
1T9268DA	135
1T9268EL	135
1T9269DA	135
1T9269EL	135
1T9270DA	135
1T9270EL	135
1T9271DA	135
1T9271EL	135
1T9272DA	136
1T9272EL	136
1T9273DA	136
1T9273EL	136
1T9274DA	136
1T9274EL	136
1T9275DA	136
1T9275EL	136
1T9276DA	136
1T9276EL	136
1T9277DA	136
1T9277EL	136
1T9278DA	136
1T9278EL	136
1T9279DA	136
1T9279EL	136
1T9280DA	136
1T9280EL	136
1T9281DA	136
1T9281EL	136
1T9282DA	136
1T9282EL	136
1T9283DA	136
1T9283EL	136
1T9284DA	136
1T9284EL	136
1T9285DA	136
1T9285EL	136

COD.	PAG.
1T9286DA	136
1T9286EL	136
1T9287DA	136
1T9287EL	136
1T9288DA	136
1T9288EL	136
1T9289DA	136
1T9289EL	136
1T9290DA	136
1T9290EL	136
1T9291DA	136
1T9291EL	136
1T9292DA	136
1T9292EL	136
1T9293DA	137
1T9293EL	137
1T9294DA	136
1T9294EL	136
1T9295DA	137
1T9295EL	137
1T9296DA	136
1T9296EL	136
1T9297DA	137
1T9297EL	137
1T9298DA	136
1T9298EL	136
1T9299DA	137
1T9299EL	137
1T9300DA	137
1T9300EL	137
1T9301DA	137
1T9301EL	137
1T9302DA	137
1T9302EL	137
1T9303DA	137
1T9303EL	137
1T9304DA	137
1T9304EL	137
1T9305DA	137
1T9305EL	137
1T9306DA	137
1T9306EL	137
1T9307DA	137
1T9307EL	137
1T9308DA	140
1T9308EL	140
1T9309DA	140
1T9309EL	140
1T9310DA	140
1T9310EL	140
1T9311DA	140
1T9311EL	140
1T9312DA	140
1T9312EL	140
1T9313DA	140
1T9313EL	140
1T9314DA	140
1T9314EL	140
1T9315DA	140
1T9315EL	140
1T9316DA	140
1T9316EL	140
1T9317DA	140
1T9317EL	140
1T9318DA	140
1T9318EL	140
1T9319DA	140
1T9319EL	140
1T9320DA	140
1T9320EL	140
1T9321DA	140
1T9321EL	140
1T9322DA	140
1T9322EL	140
1T9323DA	140
1T9323EL	140
1T9324DA	140
1T9324EL	140
1T9325DA	141
1T9325EL	141
1T9326DA	140
1T9326EL	140
1T9327DA	141
1T9327EL	141
1T9328DA	140
1T9328EL	140
1T9329DA	141
1T9329EL	141
1T9330DA	140
1T9330EL	140
1T9331DA	141
1T9331EL	141
1T9332DA	141
1T9332EL	141
1T9333DA	141
1T9333EL	141
1T9334DA	141
1T9334EL	141
1T9335DA	141
1T9335EL	141
1T9336DA	141
1T9336EL	141
1T9337DA	141
1T9337EL	141
1T9338DA	141
1T9338EL	141
1T9339DA	141
1T9339EL	141
1T9340DA	141
1T9340EL	141
1T9341DA	141
1T9341EL	141
1T9342DA	141
1T9342EL	141
1T9343DA	141
1T9343EL	141
1T9344DA	141
1T9344EL	141
1T9345DA	141
1T9345EL	141
1T9346DA	141
1T9346EL	141
1T9347DA	141
1T9347EL	141
1T9348DA	141
1T9348EL	141
1T9349DA	142
1T9349EL	142
1T9350DA	141
1T9350EL	141
1T9351DA	142
1T9351EL	142
1T9352DA	141
1T9352EL	141
1T9353DA	142
1T9353EL	142
1T9354DA	141
1T9354EL	141
1T9355DA	142
1T9355EL	142
1T9356DA	140
1T9356EL	140
1T9357DA	140
1T9357EL	140
1T9358DA	140
1T9358EL	140
1T9359DA	140
1T9359EL	140
1T9360DA	140
1T9360EL	140
1T9361DA	140
1T9361EL	140
1T9362DA	140
1T9362EL	140
1T9363DA	140
1T9363EL	140
1T9364DA	140
1T9364EL	140
1T9365DA	140
1T9365EL	140
1T9366DA	140
1T9366EL	140
1T9367DA	140
1T9367EL	140
1T9368DA	140
1T9368EL	140
1T9369DA	140
1T9369EL	140
1T9370DA	140
1T9370EL	140
1T9371DA	140
1T9371EL	140
1T9372DA	140
1T9372EL	140
1T9373DA	141
1T9373EL	141
1T9374DA	140
1T9374EL	140
1T9375DA	141
1T9375EL	141
1T9376DA	140
1T9376EL	140
1T9377DA	141
1T9377EL	141
1T9378DA	140
1T9378EL	140
1T9379DA	141
1T9379EL	141
1T9380DA	141
1T9380EL	141
1T9381DA	141
1T9381EL	141
1T9382DA	141
1T9382EL	141
1T9383DA	141
1T9383EL	141
1T9384DA	141
1T9384EL	141
1T9385DA	141
1T9385EL	141
1T9386DA	141
1T9386EL	141
1T9387DA	141
1T9387EL	141
1T9388DA	141
1T9388EL	141
1T9389DA	141
1T9389EL	141
1T9390DA	141
1T9390EL	141
1T9391DA	141
1T9391EL	141
1T9392DA	141
1T9392EL	141
1T9393DA	141
1T9393EL	141
1T9394DA	141
1T9394EL	141
1T9395DA	141
1T9395EL	141
1T9396DA	141
1T9396EL	141
1T9397DA	142
1T9397EL	142
1T9398DA	141
1T9398EL	141
1T9399DA	142
1T9399EL	142
1T9400DA	141
1T9400EL	141
1T9401DA	142
1T9401EL	142
1T9402DA	141
1T9402EL	141
1T9403DA	142
1T9403EL	142
1T9404DA	143
1T9404EL	143
1T9405DA	143
1T9405EL	143
1T9406DA	143
1T9406EL	143
1T9407DA	143

COD.	PAG.
1T9407EL	143
1T9408DA	143
1T9408EL	143
1T9409DA	143
1T9409EL	143
1T9410DA	143
1T9410EL	143
1T9411DA	143
1T9411EL	143
1T9412DA	143
1T9412EL	143
1T9413DA	143
1T9413EL	143
1T9414DA	143
1T9414EL	143
1T9415DA	143
1T9415EL	143
1T9416DA	143
1T9416EL	143
1T9417DA	143
1T9417EL	143
1T9418DA	143
1T9418EL	143
1T9419DA	143
1T9419EL	143
1T9420DA	143
1T9420EL	143
1T9421DA	144
1T9421EL	144
1T9422DA	143
1T9422EL	143
1T9423DA	144
1T9423EL	144
1T9424DA	143
1T9424EL	143
1T9425DA	144
1T9425EL	144
1T9426DA	143
1T9426EL	143
1T9427DA	144
1T9427EL	144
1T9428DA	144
1T9428EL	144
1T9429DA	144
1T9429EL	144
1T9430DA	144
1T9430EL	144
1T9431DA	144
1T9431EL	144
1T9432DA	144
1T9432EL	144
1T9433DA	144
1T9433EL	144
1T9434DA	144
1T9434EL	144
1T9435DA	144
1T9435EL	144
1T9436DA	144
1T9436EL	144
1T9437DA	144
1T9437EL	144
1T9438DA	144
1T9438EL	144
1T9439DA	144
1T9439EL	144
1T9440DA	144
1T9440EL	144
1T9441DA	144
1T9441EL	144
1T9442DA	144
1T9442EL	144
1T9443DA	144
1T9443EL	144
1T9444DA	144
1T9444EL	144
1T9445DA	145
1T9445EL	145
1T9446DA	144
1T9446EL	144
1T9447DA	145
1T9447EL	145
1T9448DA	144
1T9448EL	144
1T9449DA	145
1T9449EL	145
1T9450DA	144
1T9450EL	144
1T9451DA	145
1T9451EL	145
1T9452DA	143
1T9452EL	143
1T9453DA	143
1T9453EL	143
1T9454DA	143
1T9454EL	143
1T9455DA	143
1T9455EL	143
1T9456DA	143
1T9456EL	143
1T9457DA	143
1T9457EL	143
1T9458DA	143
1T9458EL	143
1T9459DA	143
1T9459EL	143
1T9460DA	143
1T9460EL	143
1T9461DA	143
1T9461EL	143
1T9462DA	143
1T9462EL	143
1T9463DA	143
1T9463EL	143
1T9464DA	143
1T9464EL	143
1T9465DA	143
1T9465EL	143
1T9466DA	143
1T9466EL	143
1T9467DA	143
1T9467EL	143
1T9468DA	143
1T9468EL	143
1T9469DA	144
1T9469EL	144
1T9470DA	143
1T9470EL	143
1T9471DA	144
1T9471EL	144
1T9472DA	143
1T9472EL	143
1T9473DA	144
1T9473EL	144
1T9474DA	143
1T9474EL	143
1T9475DA	144
1T9475EL	144
1T9476DA	144
1T9476EL	144
1T9477DA	144
1T9477EL	144
1T9478DA	144
1T9478EL	144
1T9479DA	144
1T9479EL	144
1T9480DA	144
1T9480EL	144
1T9481DA	144
1T9481EL	144
1T9482DA	144
1T9482EL	144
1T9483DA	144
1T9483EL	144
1T9484DA	144
1T9484EL	144
1T9485DA	144
1T9485EL	144
1T9486DA	144
1T9486EL	144
1T9487DA	144
1T9487EL	144
1T9488DA	144
1T9488EL	144
1T9489DA	144
1T9489EL	144
1T9490DA	144
1T9490EL	144
1T9491DA	144
1T9491EL	144
1T9492DA	144
1T9492EL	144
1T9493DA	145
1T9493EL	145
1T9494DA	144
1T9494EL	144
1T9495DA	145
1T9495EL	145
1T9496DA	144
1T9496EL	144
1T9497DA	145
1T9497EL	145
1T9498DA	144
1T9498EL	144
1T9499DA	145
1T9499EL	145
1T9500DA8	95
1T9501DA8	96
1T9503DA8	95
1T9504DA8	96
1T9506DA8	98
1T9507DA8	99
1T9509DA8	98
1T9510DA8	99
1T9512CA	317
1T9512DA	317
1T9512EL	317
1T9513DA	317
1T9513EL	317
1T9514CA	317
1T9514DA	317
1T9514EL	317
1T9519DA	459
1T9519EL	459
1T9520DA	459
1T9520EL	459
1T9521DA	459
1T9521EL	459
1T9522DA	459
1T9522EL	459
1T9523	352
1T9524	351
1T9525	351
1T9526DD	350
1T9579	351
1T9580	351
1T9581	383
1T9582	383
1T9583	383
1T9584	383
1T9585DA	168
1T9586DA	168
1T9588	169
1T9589	168
1T9590	168
1T9591	169
1T9592	352
1T9593	352
1T9594D	352
1T9595	371
1T9596	371
1T9597	371
1T9598	371
1T9599	371
1T9600	371
1T9601	371
1T9602	371
1T9603DD	350
1T9604DD	350
1T9605DD	350
1TD0001EL	244
1TD0002EL	244
1TD0003EL	244
1TD0004EL	244

COD.	PAG.
1TD0005EL	244
1TD0006EL	244
1TD0007EL	244
1TD0008EL	244
1TD0017	245
1TD0018	245
1V7213	478, 480
1V7213AB	478, 480
1V7262	478, 481
1V7263	478, 481
1V7264	478, 481
1V7343	481
1V7344	479
1V7345	479
1V7523	478, 480
1V7524	478, 480
323404IP	537
323414IP	537
323424IP	538
323434IP	538
323494IP	537
323900	539
344540	517
374404E	541
374404IP	541
374414E	542
374414IP	542
374424E	542
374424IP	542
374604IP	541
49881	184, 256, 275, 324
49882	184, 256, 275, 324
49886	184, 256, 275, 324
49887	184, 256, 275, 324
49959	184, 256, 275, 324
9000-1/B-R	279
9000-1/B-ST	279
9000-1/G-R	279
9000-1/G-ST	279
9000-1/W-R	279
9000-1/W-ST	279
9000-2/B-R	279
9000-2/B-ST	279
9000-2/G-R	279
9000-2/G-ST	279
9000-2/W-R	279
9000-2/W-ST	279
9000-3/B-R	279
9000-3/B-ST	279
9000-3/G-R	279
9000-3/G-ST	279
9000-3/W-R	279
9000-3/W-ST	279
9000/BPU-D-B	252, 263, 277, 513
9000/BPU-D-G	252, 263, 277, 513
9000/BPU-D-W	252, 263, 277, 513
9000/BRU-B	253, 264, 277, 513
9000/BRU-G	253, 264, 277, 513
9000/BRU-W	253, 264, 277, 513
9001/B	280
9001/G	280
9001/W	280
9002/B	280
9002/G	280
9002/W	280
9003/B	281
9003/G	281
9003/W	281
9004-R/B	279
9004-R/G	279
9004-R/W	279
9004/B	279
9004/G	279
9004/W	279
9009/B	282
9009/G	282
9009/W	282
9010/B	280
9010/G	280
9010/W	280
9011/B	281
9011/G	281
9011/W	281
9012/B	281
9012/G	281
9012/W	281
9013/B	282
9013/G	282
9013/W	282
9014/B	282
9014/G	282
9014/W	282
9015/B	282
9015/G	282
9015/W	282
9016/B	282
9016/G	282
9016/W	282
9017/B	282
9017/G	282
9017/W	282
9018/B	281
9018/G	281
9018/W	281
9500-1/B-ST3-E	382
9500-1/B-ST6-E	382
9500-1/B-TA1	382
9500-1/W2-ST3-E	382
9500-1/W2-ST6-E	382
9500-1/W2-TA1	382
9500-2/B-ST3-E	382
9500-2/B-ST6-E	382
9500-2/B-TA1	382
9500-2/W2-ST3-E	382
9500-2/W2-ST6-E	382
9500-2/W2-TA1	382
9500-3/B-ST3-E	382
9500-3/B-ST6-E	382
9500-3/B-TA1	382
9500-3/W2-ST3-E	382
9500-3/W2-ST6-E	382
9500-3/W2-TA1	382
9501-S/B-E	384
9501-S/W-E	384
9503-S/B-E	384
9503-S/W-E	384
9504/ST3-B	383
9504/ST3-W2	383
9504/ST6-B	383
9504/ST6-B-F	383
9504/ST6-W2	383
9504/ST6-W2-F	383
9511/B-E	384
9511/W-E	384
9518-S/B-E	384
9518-S/W-E	384
S-9000/111	280
S-9000/123	281
S-9000/GP-B	283
S-9000/GP-G	283
S-9000/GP-W	283
S-9000/M-B-KIT	282
S-9000/M-G-KIT	282
S-9000/M-W-KIT	282
S-9000/T	281, 384
S-9000KIT	280
S-9001-R/6-B	283
S-9001-R/6-G	283
S-9001-R/6-W	283
S-9001/115-B	280
S-9001/115-W	280
S-9010-R/6-B	283
S-9010-R/6-G	283
S-9010-R/6-W	283
S-9011-R/6-B	283
S-9011-R/6-G	283
S-9011-R/6-W	283
S-9013-R/6-B	283
S-9013-R/6-G	283
S-9013-R/6-W	283
S-9017-R/6-B	283
S-9017-R/6-G	283
S-9017-R/6-W	283
S-9500/114-B	383
S-9500/114-W2	383
S-9500/314-B	384
S-9500/314-W2	384
S-9511/B-ST6	385
S-9511/W2-ST6	385
T1585	581
T1586	581

Requisites and information

All fixtures of the Targetti collection have been designed and produced to comply with European Standard EN60598-1 relative to the safety requisite of light fixtures.

CE **DIRECTIVES EUROPEAN COUNCIL**

All fixtures comply with the following directives:

- EMC Directive 2014/30/EU
- LV Directive 2014/35/EU
- RoHS Directive 2011/65/EU

Unless specified otherwise

- all fixtures are supplied without lamps;
- all fixtures are sold separately;
- all measurements are expressed in millimeters;
- all fixtures at low voltage are supplied without transformer;
- For products in Class III performance is only guaranteed using the electronic power supplies and drivers indicated in the catalogue.

TARGETTI SANKEY SpA
Certificated ISO 9001 n° 9130. TAR1

The Enec mark, awarding of the ISO9001 certificate and the CE brand all guarantee that the activities carried out internally in the company are governed and controlled by procedures which assure constant level of quality.

Accredited laboratory in accordance with ISO 17025.

Consorzio ecolight

Targetti Sankey Spa is a member of the Ecolight consortium that was set up in 2004 (D.Lgs. 49/2014) to comply with the provisions of the European Directive that was adopted in Italy as the European Directive 2012/19/EU for WEEE on managing, recovering and treating waste electrical and electronic equipment, used batteries and accumulators in compliance with all applicable legislation.

The colors of the products illustrated are reproduced as faithfully as possible compatibly with the technical limitations of the printed medium. The company reserves the right to make changes to the production without notice. Reproduction of this catalogue or any part of it is prohibited. The products illustrated in this catalogue are covered by one or more Italian or international patents. The company will take legal action against any imitators.

Light beam apertures

from	to	beam	
5°	10°	Narrow Spot	**NSP**
11°	25°	Spot	**SP**
26°	40°	Flood	**FL**
41°	50°	Medium Wide Flood	**MWFL**
51°	70°	Wide Flood	**WFL**
71°	120°	Very Wide Flood	**VWFL**
		Wall Washer	**WW**

Icons legend

	Class I luminaire in which the protection against electrical shock is guaranteed by the connections of the conductive elements accessible to a protective conductor (earth connection).
	Luminaire in which the connection to a protective conductor (earth connection) guarantees the immunity to radio noises.
	Class II luminaire (double insulation), protected against the accidental contact with parts under tension from the user.
	Class III luminaire, suitable for connection to very low voltage circuits.
	Solid particle and liquid ingress protection degree.
	Housing degree of protection.
	Optic degree of protection.
	Impact protection degree.
	ENEC European Norms Electrical Certification.

Particular symbols

	Weight of the single fixture.
	Cable length.
	Walk-over.
	Driver-over safe.
	LED with Ra__ where not present in the catalogue, available on request.
	Different colour temperatures available on request.
	Custom finish of your choice from the Targetti Colours range and RAL indicated in the colour chart can be downloaded on line from the download section.
	Treatment carried out on request.
	Supplied on request with an integrated or remote 110-277Vac power supply as indicated for the standard model.
	LED version with a different “Tunable White” tone available on request.
	Fixtures that have parameters below the minimum visibility threshold PstLM=1 and SVM≤0.4 (IEC TR 61547-1 and IEC TR 63158).
DBS	Dynamic Beam Shaper optical technology with remote management of the beam opening.

Please contact us for on demand treatments and versions.

Targetti in the world

TARGETTI SANKEY S.p.A.
Via Pratese, 164
50145 Firenze - Italia
Phone 055 3791.1
Fax 055 3791.266
targetti@targetti.com
www.targetti.com

Customer Care
customer@targetti.com

Customer Service
technical@targetti.com

Lighting Consulting
project@targetti.com

China
Targetti Lighting (Beijing) Co. Ltd
Room 921 Unit 3 Guanghualu SOHO
1, n.22 Guanghua Road, Chaoyang
District, Beijing China 100020.
+86 10 65388956
teresa.yan@targetti.cn

France
3F Filippi Targetti France S.A.S.
2 Rue de la Renaissance,
92160 Antony
+33 (1) 44 29 09 09
targetti.fr@targetti.com

India
Targetti India
Teamwork building 18, 2nd floor
Chinnaswamy Mudaliar road
Tasker town
560051 Bangalore
+91 80 41120016
s.karthik@targetti.com

Italy
Targetti Sankey S.p.A.
Via Pratese, 164
Firenze 50145
+39 055 37911
targetti@targetti.com

Spain
Targetti Spain S.A.U
Avda. de Roma, n°69,
Barcelona 08029
+34 93 474 61 71
targetti.es@targetti.com

U.A.E.
Targetti Sankey S.p.A. (BRANCH)
Dubai Airport Free Zone Authority
- Bldg.
6 West A - Office 732
Dubai P.O. Box 54744
+9714 609 1033
m.afsar@targetti.com

UK
Targetti Uk Limited
Coppergate House Unit 504
10 White's Row
E1 7NF London
+44 (0) 203 501 4650
m.allen@targetti.com

U.S.A.
Targetti Usa Inc.
750-A West 17th Street
Costa Mesa, CA 92626
+1 714 513 1991
targetti.usa@targetti.com

Latin America
Targetti Latin America
Cra 2 Oeste # 5-262,
Edificio Av. Belalcazar, Apt. 901
Cali, Colombia
+57 3128 317174
l.valdrighi@targetti.com

Other countries www.targetti.com