



LINEAR J STANDARD

TypologyLow voltage and mains supply halogen lamps.

Excellent colour rendering, low cost, wide diffusion and easy to use.

In addition to energy classes that reflect the limitations of the technology used that is now totally replaceable by more efficient LED models.













IP20

R7s-15

-15°C +35°C



Data sheet code: 01988

Characteristic data

Power	1000 W	Beam	320°	Dimmable	Yes	Input	230 Vac
Base	R7s-15	IP	20	Flux	19100 lm	Tc	3000 K
Ra	100						

Dimensional characteristics



L	189 mm
Ø	10 mm



Data sheet code: 01988



Lighting and photometric features

Beam opening	320°
Flux	19100 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	100
Lifespan	2000 h
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	1000 W
Input voltage	230 Vac
Frequency	50 Hz
Dimmable	Yes
Input current	4.34 A
Weighted energy consumtion	1000 kWh/1000h
Number of cycles	15000
Operating temperature	-15°C / +35°C
Equivalence with incandescent lamp	1123
Operating position	15°

Standards and Directives

2009/125/EC, 244/2009, 859/2009, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 60432-2/A1:2006
CEI EN 55015:2020	CEI EN 60432-2/A2:2012
CEI EN 60432-2:2001	

Logistics data

Number of pieces multiple pack	25
Barcode multiple pack	8011905707163

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

