



HDI-E/C - METAL HALIDE

Typology


Discharge lamps.

Features

Product reliability. This is what the entire range of Duralamp discharge lamps has in common. Used in technical and professional installations where relamping is often difficult, discharge lamps must be lamps you can depend upon.

Notes

The HYPERCOLOR range with ceramic burners: excellent control of colour uniformity, colour rendering and colour stability over time.



110±15 Vac

Ra >65



10000 h

IP20


E27

-15°C
+35°C

Characteristic data

Power	150 W	Dimmable	No	Input	110±15 Vac	Base	E27
IP	20	Flux	12500 lm	Tc	4200/NDL K	Ra	>65

Dimensional characteristics



Ø	58 mm
H	145 mm

Lighting and photometric features

Flux	12500 lm
CCT nominal colour temperature	4200/NDL K
Colour rendering index	>65
Lifespan	10000 h
Mercury	11,0 mg
Luminous Flux Maintenance at 2000h	82
Luminous Flux Maintenance at 4000h	70
Luminous Flux Maintenance at 6000h	67
Luminous Flux Maintenance at 8000h	62
Luminous Flux Maintenance at 12000h	55
Lamp survival factor at 2000h	98
Lamp survival factor at 4000h	92
Lamp survival factor at 6000h	80
Lamp survival factor at 8000h	65
Lamp survival factor at 10000h	50

Electrical characteristics

Rated power	150 W
Input voltage	110±15 Vac
undefined	50 Hz
Dimmable	No
Input current	1.5 A
Operating temperature	-15°C / +35°C
Operating position	360°

Standards and Directives

2009/125/EC, 245/2009, 347/2010, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 62035:2016
CEI EN 55015:2020	CEI EN 62035/A1:2020

Logistics data

Item net weight	208 gr
Barcode single item	8011905042011
Number of pieces multiple pack	12
Barcode multiple pack	8011905733735