



TRIPHOSPHOR CIRCULAR T9


Typology

Compact, circular and linear fluorescent lamps.

Features

The best fluorescent and triphosphorous powders for maximum light colour control and light emission over time, good colour rendering and the excellent luminous efficiency.


A wide reliable range for installation in professional contexts such and home environments.



Characteristic data

Power	32 W	Dimmable	Yes	Input	86,7 Vac	Base	G10q
IP	20	Flux	2415 lm	Tc	4100 K	Ra	>80

Dimensional characteristics



Ø	300 mm
L2	29 mm

Lighting and photometric features

Flux	2415 lm
CCT nominal colour temperature	4100 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	10000 h
Mercury	3,5 mg
Luminous Flux Maintenance at 2000h	88
Luminous Flux Maintenance at 4000h	85
Luminous Flux Maintenance at 6000h	80
Luminous Flux Maintenance at 8000h	75
Luminous Flux Maintenance at 12000h	72
Luminous Flux Maintenance at 16000h	70
Lamp survival factor at 2000h	100
Lamp survival factor at 4000h	100
Lamp survival factor at 6000h	95
Lamp survival factor at 8000h	80
Lamp survival factor at 10000h	50
Lamp survival factor at 12000h	45

Electrical characteristics

Rated power	32 W
Input voltage	86,7 Vac
Frequency	50 Hz
Dimmable	Yes
Input current	0.45 A
Operating temperature	-15°C / +35°C
Operating position	360°

Standards and Directives

2009/125/EC, 245/2009, 347/2010, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 61000-3-2:2019
CEI EN 55015:2020	CEI EN 61000-3-3:2014
CEI EN 60968:2016	CEI EN 61547:2010

Logistics data

Item net weight	190 gr
Barcode single item	8011905818166
Number of pieces multiple pack	12
Barcode multiple pack	8011905763022