



## Belt Light Profi Set | 20 meter | with 20 molded sockets



|                 |  |
|-----------------|--|
| Article number: | 585-038  |
| CHANGED_LAST:   | 21-06-2022   |
| Brand:          | Tronix Lighting  |
| Type:           | Festoon Cable Light  |
| ETIM Group:     | EG000027 - Luminaires  |
| ETIM Classes:   | EC002761 - Festive lighting  |
| SYNONYM:        | Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set |





## Feature

|  |                        |   |                     |
|--|------------------------|---|---------------------|
| Model:   | illumination cable set | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 %                 |
| Number of light centres:   | 20                     | Constant light output (CLO):  | No                  |
| Lamp type:   | LED exchangeable       | Degree of protection (IP):  | IP44                |
| With light source:   | No                     | Protection class:   | II                  |
| Colour:  | Other                  | Fire resistance according to UL94:                                    | C                   |
| Voltage type:  | AC                     | Power factor:   | 1                   |
| Nominal voltage:   | 220 ~ 240 V            | Width:  | 0 mm                |
| Connected load:  | 2500 W                 | Height/depth:   | 0 mm                |
| Battery power supply:  | No                     | Total length:   | 20 m                |
| Suitable for outdoor use:  | Yes                    | Diameter:   | 0 mm                |
| With power bridge:   | No                     | Type of wiring:   | Ending              |
| Connectable:   | No                     | Number of poles:  | 2                   |
| Type of control gear:  | Not required           | Conductor cross section:  | 1.5 mm <sup>2</sup> |
| Exchangeable control gear:   | No                     | Connection type:  | Other               |
| Rated life time L70/B50 at 25 °C:  | 0 h                    | commercial, christmas or both:  | NA                  |
| Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 %                    |   |                     |

## Packaging data

|              |            |
|--------------|------------|
| Weight       | 3.14 kg    |
| Width        | 170 mm     |
| Height       | 155 mm     |
| Length       | 495 mm     |
| Customs code | 8544429090 |

