



PING BALL

Typology

Range of LED lamps with SMD technology and color bulb.

Features

Classic shapes for immediate retro-fit of incandescent lamps in any decorative applications and festoons.
The RGB version features a fading color loop, for pleasant coloring effects.

Material


Impact-resistant globe, extremely resistant: these lamps can "bounce" if they fall on the floor.

Applications

For indoor or outdoor use inside duly protected fittings or Catenaria.

Notes


Do not use with dimmer.



Characteristic data

Power	0.5 W	Beam	270°	Dimmable	No	Input	200-240 Vac
Base	E27	IP	20	PF	0,16	LED Warranty	G2
Color	Blue						

Dimensional characteristics



Ø	45 mm
H	69 mm
H Tolerance	± 3 mm

Lighting and photometric features

Beam opening	270°
Colour of the light	Blue
Lifespan	25000 h
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	0.5 W
Input voltage	200-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,16
Input current	0.15 A
Number of cycles	100000
Operating temperature	-25°C / +35°C
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2009/125/EC, 244/2009, 859/2009, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 62031/A1/A2:2015
CEI EN 55015:2020	CEI EN 62471:2010
CEI EN 60968:2016	IEC TR 62471-2:2009
CEI EN 61000-3-2:2019	CEI EN 62560:2013
CEI EN 61000-3-3:2014	CEI EN 62560/A1:2017
CEI EN 61547:2010	CEI 34-141:2014
CEI EN 62031:2009	

Logistics data

Item net weight	22 gr
Barcode single item	8011905836573
Number of pieces multiple pack	10
Barcode multiple pack	8011905781859