



TRANSFORMERS CONSTANT VOLTAGE OUTPUT ELECTRONIC LED POWER SUPPLY

Data sheet code: DELT50A-12

Typology

Transformers constant voltage output electronic LED power supply.

Note

It is advisable not to charge the driver more than 55% of its power in order to consider the in-rush current of LED lamps.





50000 h

IP20

Screws

-25°C +35°C

G2

Characteristic data

Power	50 W	Dimmable	No	Input	200-240 Vac	Base	Screws
IP	20	PF	0,9	LED Warranty	G2		

Dimensional characteristics

L	160 mm
Н	12 mm
L2	58 mm

Lighting and photometric features

Lifector	50000 h
Lifespan	30000 II

Electrical characteristics

Rated power	50 W
Input voltage	200-240 Vac
undefined	50 Hz
Output voltage	12 Vdc
Dimmable	No
Power factor (PF)	0,9
Operating temperature	-25°C / +35°C

LED Warranty

G2	Up to 2 years
	(4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

Data sheet code: DELT50A-12



Standards and Directives

2009/125/EC, 245/2009, 347/2010, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61347-1:2016
2014/35/EU, 2015/863	CEI EN 61347-2-13:2015
CEI EN 55015:2020	CEI EN 61347-2-13/A1:2018
CEI EN 61000-3-2:2019	CEI EN 61547:2010
CEI EN 61000-3-3:2014	

Logistics data

Item net weight	245 gr
Barcode single item	8011905833343
Number of pieces multiple pack	10
Barcode multiple pack	8011905778620

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

