





G4 PRISMA BIPIN



Characteristic data

Power	1.5 W	Beam	240°	Dimmable	No	Input	12 Vdc
Base	G4	IP	20	Flux	110 lm	PF	0,85
Tc	3000 K	Ra	80	LED Warranty	G2		

Dimensional characteristics



Ø	11 mm
H	35 mm

Lighting and photometric features

Beam opening	240°
Flux	110 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	30000 h
LED lifespan	L70B20
Trigger time	<0,2 s
LM80 - Luminous flux maintenance at end of life	70
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	1.5 W
Input voltage	12 Vdc
Dimmable	No
Power factor (PF)	0,85
Weighted energy consumption	2 kWh/1000h
Energy class	A++
Number of cycles	100000
Operating temperature	-25°C / +35°C
Operating position	360°

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2009/125/EC, 244/2009, 859/2009, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 62031/A1/A2:2015
CEI EN 55015:2020	CEI EN 62471:2010
CEI EN 60968:2016	IEC TR 62471-2:2009
CEI EN 61000-3-2:2019	CEI EN 62560:2013
CEI EN 61000-3-3:2014	CEI EN 62560/A1:2017
CEI EN 61547:2010	CEI 34-141:2014
CEI EN 62031:2009	

Logistics data

Item net weight	12 gr
Barcode single item	8011905834265
Number of pieces multiple pack	10
Barcode multiple pack	8011905779542

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products