




PAR20 LED ALTAIR



Characteristic data

Power	7 W	Beam	30°	Dimmable	No	Input	100-240 Vac
Base	E27	IP	20	Flux	300 lm	PF	0,90
Tc	2800 K	Ra	80	LED Warranty	G2	Axis	564 cd

Dimensional characteristics

ø	63 mm
H	84 mm

Lighting and photometric features

Beam opening	30°
Flux	300 lm
CCT nominal colour temperature	2800 K
Colour of the light	Warm light
Colour rendering index	80
Lifespan	15000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

Electrical characteristics

Rated power	7 W
Input voltage	100-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,90
Weighted energy consumption	7 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	45

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2006/95/CE * Bassa Tensione	IEC/TR 62471-2
2004/108/CE * Compatibilità Elettromagnetica	EN 62031 * anno 2009 (+A1:2013)
2011/65/UE * RoHS	EN 62560 * anno 2013
2012/19/UE * RAEE	EN 60968 * anno 2013
EN 61547 * anno 2010	2010/30/EU * Energy Consumption
EN 55015 * anno 2014	874/2012 * Regulation for Energy Labelling
EN 61000-3-2 * anno 2007 (+A1/+A2:2011)	2009/125/CE * Progettazione Eco Compatibile
EN 61000-3-3 * anno 2014	1194/2012 * Progettazione Eco Compatibile
EN 62471 * anno 2010	

Logistics data

Barcode single item	8011905834289
Number of pieces multiple pack	10
Barcode multiple pack	8011905779566