Data sheet code: ZKRQG





ZK RECESSABLE RINGS: ORIENTABLE IP20 - SQUARE

TypologyRecessed orientable ring with interchangeable optional optics for MR16, PAR16 lamps and Module.

IP20 swivel version.

See also IP65 fixed version.

The same ring declined in two versions to fulfill different installation needs in the same environments.

Complete with front screen.

Installation

Equipped with springs for quick installation.
To be completed with TO53 ot TO10 lampholders.

Material

Painted metal body.

-25°C +35°C



Characteristic data

Color Grey						
------------	--	--	--	--	--	--

Dimensional characteristics



L	90 mm
L1	90 mm
Н	33 mm

Cutting hole	72

Electrical characteristics

Operation town earlies	3F9C / 12F9C
Operating temperature	-25°(/ +35°(

Standards and Directives

2014 / (5 / 51) 2015 / 0/2	
2011/65/EU, 2015/863	

Data sheet code: ZKRQG



Logistics data

Item net weight	100 gr
Barcode single item	8011905836832
Number of pieces multiple pack	10
Barcode multiple pack	8011905782115
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

