



LESELI HIGH POWER - SQUARE

Typology

LED source with SMD technology and high efficiency chip integrated into a recessed luminaire.

Features

Soft satin effect polycarbonate anti-glare diffuser.

Installation


Complete with springs for easy fastening into false ceilings.
Connection to the mains with terminal block.

Material

Thermally conductive body; extremely light and manageable.
White ring.

Notes


Do not use with dimmers except if otherwise indicated.



Characteristic data

Power	30 W	Beam	90°	Dimmable	No	Input	220-240 Vac
Base	Wire	IP	20	Optical compartment IP	23	Flux	3100 lm
PF	0,95	Tc	4000 K	Ra	>80	LED Warranty	G3
Axis	1400 cd	RG	RG1				

Dimensional characteristics



L	230 mm
L1	230 mm
H	60 mm

Cutting hole	200x200
--------------	---------

Lighting and photometric features

Beam opening	90°
Flux	3100 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	30 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,95
Input current	0.145 A
Weighted energy consumption	30 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry

	4000K	H(m)	D(m)	Emax(lx)		
	Ra80		94°			
Fixture Power	30W	1	2.13	1382		
Source Flux	3100lm	2	4.26	346		
Fixture Flux	3100lm	3	6.39	154		
Efficacy	103lm/W	4	8.52	86		
843700	Imax=446cd/klm	Imax	1382cd	5	10.65	55

EuLumDat file on the site

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-2:2012	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

Logistics data

Item net weight	672 gr
Barcode single item	8011905843700
Number of pieces multiple pack	6
Barcode multiple pack	8011905788988
Minimum order quantity	6