




PANTH-SLIM



Characteristic data

Power	35 W	Beam	120°	Dimmable	No	Input	100-240 Vac
Base	Terminals	IP	65	Flux	2500 lm	PF	0,9
Tc	4000 K	Ra	>70	LED Warranty	G2	Axis	1050 cd

Dimensional characteristics

L	230 mm
L1	155 mm
H	57 mm

Lighting and photometric features

Beam opening	120°
Flux	2500 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>70
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	35 W
Input voltage	100-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,9
Weighted energy consumption	35 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry



	4000K	H(m)	D1(m)	D2(m)	E _{max} (lx)
	Ra80		106°	107°	
Fixture Power	30W	1	2.64	2.68	1045
Source Flux	2572lm	2	5.29	5.36	261
Fixture Flux	2572lm	3	7.93	8.04	116
Efficacy	86lm/W	4	10.58	10.71	65
A1413 I _{max} =406cd/klm	I _{max}	5	13.22	13.39	42

EulumDat file on the site

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC
2014/35/EU * LVD
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-5:2016
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	1630 gr
Barcode single item	8011905835835
Number of pieces multiple pack	10
Barcode multiple pack	8011905781118

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products