



## SLIMFLUX NWB3 PANELS 60X60 - BASIC

### Typology

Ultra-flat LED fixtures with lateral lighting

### Features

Side heat dissipation.  
 Immediate switch-on.  
 Colour rendering: Ra>80.  
 Remote power supply included.  
 Do not use with dimmer.  
 If you want to dim or use the multicurrent power supply dimmer.  
 UGR version also available.  
 Class II fittings.

### Installation

Possibilities include: recessed, suspended, ceiling/wall.  
 Surface mounting & adjustable suspension wire kits are available as accessories.

### Material

White painted metal body.  
 Anti-yellowing PS screen.  
 LGP (Light Guide Plate) in PS anti-yellowing.

### Usage information

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

### Emergency


SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.

220-240 Vac	Ra >80		25000 h	IP20 VI IP43 VO	Free Wire	-25°C +35°C	RG0	<b>BASIC</b>	
	G2								

### Characteristic data

Power	40 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	Free Wire	IP	20	Optical compartment IP	43	Flux	3400 lm
PF	0,90	Tc	3000 K	Ra	>80	LED Warranty	G2
RG	RG0						

## Dimensional characteristics



L	595 mm
L1	595 mm
H	10 mm

## Lighting and photometric features

Beam opening	120°
Flux	3400 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Output voltage	27-42 Vdc
Dimmable	No
Power factor (PF)	0,90
Max output current	1000 mA
Weighted energy consumption	40 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## Logistics data

Item net weight	2300 gr
Barcode single item	8011905934415
Number of pieces multiple pack	5
Barcode multiple pack	8011905934941
Minimum order quantity	5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products