

PS230 | Icicle Light | 2x0,4m | White Wire | 3000K WW



| Article number: | 007-018 |
|-----------------|---|
| CHANGED_LAST: | 21-06-2022 |
| Brand: | Tronix Lighting |
| Туре: | Icicle Light 2M x 40CM |
| ETIM Group: | EG000027 - Luminaires |
| ETIM Classes: | EC002761 - Festive lighting |
| SYNONYM: | Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set |
| | |



Page: 1/3















Feature

| Model: | Curtain light | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % |
|--|---|---|-------------------------|
| Number of light centres: | 76 | Constant light output (CLO): | No |
| Lamp type: | LED not exchangeable | Degree of protection (IP): | IP65 |
| With light source: | Yes | Protection class: | II |
| Colour: | White | Fire resistance according to UL94: | C |
| Voltage type: | AC | Colour of light: | White |
| Nominal voltage: | 230 ~ 230 V | Power factor: | 0.95 |
| Connected load: | 5.5 W | Width: | 0 mm |
| Battery power supply: | No | Height/depth: | 400 mm |
| Suitable for outdoor use: | Yes | Total length: | 2 m |
| With power bridge: | No | Diameter: | 0 mm |
| Connectable: | Yes | Type of wiring: | Through wiring included |
| Type of control gear: | LED operating device voltage-controlled | Number of poles: | 2 |
| Exchangeable control gear: | No | Conductor cross section: | 0.5 mm ² |
| Energy efficiency class of the built-in lamp: | A++, A+, A (LED) | Connection type: | Other |
| Rated life time L70/B50 at 25 °C: | 20000 h | commerial, christmas or both: | NA |
| Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 % | | |

Packaging data

| Weight | 680 gr |
|--------------|------------|
| Width | 80 mm |
| Height | 120 mm |
| Length | 220 mm |
| Customs code | 9405310000 |
| | |

Page: 2/3


















Page: 3/3

guided by light







tronixlighting.com