




## Panel | 30\*60 | >100L/W | Tri-White | White Frame | Non Dim.



Article number:	174-029
CHANGED_LAST:	21-06-2022
Brand:	Tronix Lighting
Type:	30x60
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC002892 - Ceiling-/wall luminaire
SYNONYM:	Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire





## Feature

Suitable for wall mounting:	Yes	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for suspended mounting:	Yes	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for ceiling mounting:	Yes	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for built-in mounting:	Yes	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for surface mounting:	Yes	Max. number of luminaires per miniature circuit breaker B16:	122
Suitable for light line configuration:	No	Max. number of luminaires per miniature circuit breaker C16:	122
Suitable for workplace according to EN 12464-1:	No	Degree of protection (IP):	IP20
Lamp type:	LED not exchangeable	Degree of protection (NEMA):	1
With light source:	Yes	Impact strength:	IK02
Lamp holder:	Other	Protection class:	II
Material housing:	Aluminium	Luminaire with limited surface temperature, sign "D":	No
Surface protection housing:	Lacquered	Rated ambient temperature according to IEC62722-2-1:	-20 ~ 40 °C
Colour housing:	White	Suitable for emergency lighting:	Yes
Material cover:	Other	Emergency power supply integrated:	No
Type of grid:	None	With movement sensor:	No
Voltage type:	AC	With light sensor:	No
Nominal voltage:	220 ~ 240 V	Covering of the luminaire with thermally insulating material possible:	No
Nominal current:	75 ~ 82 mA	With air slots:	No
Type of control gear:	LED operating device current-controlled	Filament test according to IEC 60695-2-11:	650 °C - 30 s
With control gear:	Yes	Suitable for lamp power:	0 ~ 0 W
Exchangeable control gear:	No	Max. system power:	18 W
Dimming 0-10 V:	No	Luminaire efficacy:	100 lm/W
Dimming 1-10 V:	No	Rated luminous flux according to IEC 62722-2-1:	1800 lm
Dimming DALI-2:	No	Colour of light:	White
Dimming DALI:	No	Colour temperature:	3000 ~ 3000 K
Dimming DMX:	No	Colour rendering index CRI:	80-89
Dimming DSI:	No	Power factor:	0.9
Dimming potentiometer (integrated):	No	Stroboscope effect value SVM:	0.01
Dimming GPRS:	No	Constant light output (CLO):	No
Dimming LineSwitch:	No	Width:	295 mm
Dimming manufacturer's proprietary system:	No	Height/depth:	11 mm
Dimming mains voltage modulation:	No	Length:	595 mm
Dimming phase cut-off:	No	Outer diameter:	0 mm
Dimming phase cut-on:	No	Built-in length:	595 mm
Dimming programmable:	No	Built-in width:	295 mm
Dimming RF:	No	Built-in height/depth:	11 mm
Dimming Sine Wave Reduction:	No	Built-in diameter:	0 mm
Dimming Touch and Dim:	No	Type of wiring:	Ending
Dimming Zigbee:	No	Number of poles:	2
Dimming with push-button:	No	Conductor cross section:	0.75 mm <sup>2</sup>
Dimming depending on control gear:	Yes	Connection type:	Other
No dim function:	Yes	Total harmonic distortion:	12
Light distributor:	Diffuser lens/optic/panel	Photobiological safety according to EN 62471:	RG0
Light sharing:	Symmetric	Luminous intensity:	0 cd



Beam angle:	Extreme wide beam >80°	Colour temperature adjustable:	Positions
Colour consistency (McAdam ellipse):	SDCM6	Luminous flux adjustable:	No
Light outlet:	Indirect	Beam angle adjustable:	No
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	Operation by Bluetooth:	No
Rated life time L70/B50 at 25 °C:	83000 h	Compatible with Apple HomeKit:	No
Rated life time L80/B10 at 25 °C:	0 h	Compatible with Google Assistant:	No
Rated life time L90/B10 at 25 °C:	0 h	Compatible with Amazon Alexa:	No
Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %	IFTTT support available:	No
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %		

## Packaging data

Weight	1.46 kg
Width	312 mm
Height	34 mm
Length	660 mm
Customs code	9405494000

