



Wall Lamp | Up & Down 115x90mm | Black | 6,9W | 2700K | Dim.



Article number:	149-150
CHANGED_LAST:	21-06-2022
Brand:	Tronix Lighting
Type:	Wall Lamps
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC002892 - Ceiling-/wall luminaire
SYNONYM:	Bed lighting luminaire, Bed wall luminaire, Bulleye, Ceiling and wall luminaire, Ceiling- and wall luminaire, Ceiling-/wall luminaire, Downlighter, Facade luminaire, FL luminaire





Feature

Suitable for wall mounting:	Yes	Lumen maintenance at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for suspended mounting:	No	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for ceiling mounting:	No	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for built-in mounting:	No	Failure rate at median useful life of 75,000 h at 25 °C ambient (tq):	0 %
Suitable for surface mounting:	Yes	Max. number of luminaires per miniature circuit breaker B16:	75
Suitable for light line configuration:	No	Max. number of luminaires per miniature circuit breaker C16:	120
Suitable for workplace according to EN 12464-1:	No	Degree of protection (IP):	IP54
Lamp type:	LED not exchangeable	Degree of protection (NEMA):	2
With light source:	Yes	Impact strength:	IK06
Material housing:	Aluminium	Protection class:	I
Surface protection housing:	Powder coating	Luminaire with limited surface temperature, sign "D":	No
Colour housing:	Black	Rated ambient temperature according to IEC62722-2-1:	-20 ~ 45 °C
Material cover:	Glass transparent	Suitable for emergency lighting:	No
Type of grid:	None	Emergency power supply integrated:	No
Voltage type:	AC	With movement sensor:	No
Nominal voltage:	220 ~ 240 V	With light sensor:	No
Nominal current:	29 ~ 31 mA	Covering of the luminaire with thermally insulating material possible:	No
Type of control gear:	LED operating device current-controlled	With air slots:	No
With control gear:	Yes	Filament test according to IEC 60695-2-11:	650 °C - 30 s
Exchangeable control gear:	No	Suitable for lamp power:	0 ~ 0 W
Dimming 0-10 V:	No	Max. system power:	6.9 W
Dimming 1-10 V:	No	Luminaire efficacy:	100 lm/W
Dimming DALI-2:	No	Rated luminous flux according to IEC 62722-2-1:	692 lm
Dimming DALI:	No	Colour of light:	White
Dimming DMX:	No	Colour temperature:	2700 ~ 2700 K
Dimming DSI:	No	Colour rendering index CRI:	80-89
Dimming potentiometer (integrated):	No	Power factor:	0.9
Dimming GPRS:	No	Stroboscope effect value SVM:	0.01
Dimming LineSwitch:	No	Constant light output (CLO):	No
Dimming manufacturer's proprietary system:	No	Width:	28 mm
Dimming mains voltage modulation:	No	Height/depth:	90 mm
Dimming phase cut-off:	Yes	Length:	115 mm
Dimming phase cut-on:	No	Outer diameter:	0 mm
Dimming programmable:	No	Built-in length:	0 mm
Dimming RF:	No	Built-in width:	0 mm
Dimming Sine Wave Reduction:	No	Built-in height/depth:	0 mm
Dimming Touch and Dim:	No	Built-in diameter:	0 mm
Dimming Zigbee:	No	Type of wiring:	Ending
Dimming with push-button:	No	Number of poles:	3
Dimming depending on control gear:	No	Conductor cross section:	0.75 mm ²
No dim function:	No	Connection type:	Screwed terminal
Light distributor:	None	Photobiological safety according to EN 62471:	RG0
Light sharing:	Symmetric	Luminous intensity:	0 cd
Beam angle:	Extreme wide beam >80°	Colour temperature adjustable:	No



Colour consistency (McAdam ellipse):	SDCM3	Luminous flux adjustable:	Continuously variable
Light outlet:	Direct	Beam angle adjustable:	No
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	Operation by Bluetooth:	No
Rated life time L70/B50 at 25 °C:	50000 h	Compatible with Apple HomeKit:	No
Rated life time L80/B10 at 25 °C:	0 h	Compatible with Google Assistant:	No
Rated life time L90/B10 at 25 °C:	0 h	Compatible with Amazon Alexa:	No
Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %	IFTTT support available:	No
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %		

Packaging data

Weight	440 gr
Width	98 mm
Height	37 mm
Length	127 mm
Customs code	9405990090

