



## LESELI SLIM DS - ROUND

### Typology

LED source with SMD technology and high efficiency chip integrated into a recessed luminaire.

### Features

Downlights with extremely limited width and remote driver.

### Installation

Complete with springs for easy fastening into false ceilings.  
Connection to mains with free wires.

### Material

High dissipation die-cast aluminum body with anti-yellowing PC screen.  
White ring.

### Usage information

Can be used with multi-current dimming power supply, code DELT40D-M.

### Emergency

Can be used with standby emergency kit, code KTEMR03.

### Notes

Luminaire is Non-Dimming.




110-240 Vac	Ra >80		15000 h	IP20 VI IP43 VO	-25°C +35°C	RG0		BASIC	
	G2								

### Characteristic data

Power	24 W	Beam	120°	Dimmable	No	Input	110-240 Vac
IP	20	Optical compartment IP	43	Flux	1710 lm	PF	0,5
Tc	3000 K	Ra	>80	LED Warranty	G2	Axis	475 cd
RG	RG0						

## Dimensional characteristics



Ø	295 mm
H	8.5 mm

Cutting hole	280
--------------	-----

## Lighting and photometric features

Beam opening	120°
Flux	1710 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	15000 h
LED lifespan	L70B20
Trigger time	<0,2 s
LM80 - Luminous flux maintenance at end of life	70
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	24 W
Input voltage	110-240 Vac
undefined	50-60 Hz
Dimmable	No
Power factor (PF)	0,5
Weighted energy consumption	24 kWh/1000h
Energy class	A
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Photometry

	3000K	H(m)	D(m)	E <sub>max</sub> (lx)
	Ra80		131°	
Fixture Power	24W	1	4.36	475
Source Flux	1710lm	2	8.73	119
Fixture Flux	1710lm	3	13.09	53
Efficacy	71lm/W	4	17.46	30
954932 I <sub>max</sub> =278cd/klm	I <sub>max</sub>	475cd	21.82	19

E<sub>lum</sub>Dat file on the site

## LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-2:2012	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

## Logistics data

Item net weight	480 gr
Barcode single item	8011905954932
Number of pieces multiple pack	10
Barcode multiple pack	8011905958947
Minimum order quantity	10