



PROJECTOR JAZZ03

Typology

LED projector with COB technology for outdoor spot lighting.

Features

Sleek design that can be used in any setting; adjustable to 240°. Projector with base with integrated driver.

Material

Anthracite grey colour, powder coated anodised aluminium body.

Beam


LED Chip on Board, high efficiency, Ra 85. Adjustable from 0° to 240° on the vertical axis and 350° on the horizontal axis.

220-240 Vac	Ra >85		50000 h	IP65	Wire	-25°C +35°C	PRO		
G5h24									

Characteristic data

Power	30 W	Beam	55°	Dimmable	Yes	Input	220-240 Vac
Base	Wire	IP	65	Flux	2800 lm	PF	0,9
Tc	3000 K	Ra	>85	LED Warranty	G5h24	Axis	3250 cd
Color	Anthracite						

Dimensional characteristics



∅	100 mm
L2	95 mm
H	210 mm

Lighting and photometric features

Beam opening	55°
Flux	2800 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	>85
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	30 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	Yes
Power factor (PF)	0,9
Input current	0.14 A
Weighted energy consumption	30 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry

	3000K	H(m)	D1(m)	D2(m)	E _{max} (lx)
	Ra80		60°	59°	
Fixture Power	30W	1	1.15	1.14	3237
Source Flux	2812lm	2	2.31	2.29	809
Fixture Flux	2812lm	3	3.46	3.43	360
Efficacy	94lm/W	4	4.61	4.57	202
JZ03BWW I _{max} =1151cd/klm	I _{max}	5	5.76	5.72	129

EuLumDat file on the site

LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-1:1997	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

Logistics data

Item net weight	1700 gr
Barcode single item	8011905934170
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products