



SURFACE PROFILES: PRAP

Features

Aluminium profile for surface mounting installations. Aluminium profiles allow for a more stable installation, in case of linear installations. Recommended for indoor and outdoor (protected) applications and for high power strips in order to better heat dissipation.

CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

12 mm (PRAP20) and 15 mm (PRAP68).

MAXIMUM POWER:

20W/m 20 Series
25W/m 68 Series

Installation

Surface installation with its fixing clips. IP65 or IP68 strips the connectors rest outside the profile.

Material

6063 Aluminium profile with a white PC screen.


Accessories

Every 2 metre bar is complete with 2 sets of end caps (with and without hole) and 2 sets of mounting clips.

Packaging

Supplied in packages of 5 bars, each one measuring 2 meters, complete with screen and accessories.

Dimensional characteristics



L	2000 mm
L1	21 mm
H	13 mm

Standards and Directives

2011/65/EU, 2015/863

Logistics data

Barcode single item	8011905951412
Barcode multiple pack	8011905951726

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products