



## HB2 - HIGH BAY

### Typology

Suspension fixture for installations in large commercial and industrial spaces; uses SMD technology.  
Also available in a DALI version.

### Features

It is composed of an independent power supply system connected to the body of the fixture with small columns for improved thermal management.  
The optical unit is integrated into the aluminium body for perfect heat dissipation.  
The fixture body can be completed with an aluminium or polycarbonate reflector to obtain a different aesthetic and antiglare effect.

### Installation

Equipped with a mounting ring for suspension installation.  
For ceiling or wall installation order the accessory code that comprises the bracket and the relative accessories.

### Material

Grooved die-cast aluminium for heat dissipation.

### Applications

Professional lighting ideal for industrial environments and large indoor spaces.

### Beam

Optical system consisting of an array of lens optimised for SMDs.  
Different opening angle depending on the model.

### Notes

Optimised design to maximise heat exchange.




220-240 Vac	Ra >80		50000 h	IP65	IK08	Free Wire	-25°C +45°C	RG1	<b>PRO</b>
	 120°	G5h24	 FLICKER FREE						

### Characteristic data

Power	200 W	Beam	120°	Dimmable	Yes	Input	220-240 Vac
Base	Free Wire	IP	65	Flux	30000 lm	PF	0,92
Tc	4000 K	Ra	>80	LED Warranty	G5h24	Axis	9300 cd
IK	IK08	RG	RG1				

## Dimensional characteristics



Ø	305 mm
H	124 mm
H2	168 mm

## Lighting and photometric features

Beam opening	120°
Flux	30000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L70B20

## Electrical characteristics

Rated power	200 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	Yes
Power factor (PF)	0,92
Operating temperature	-25°C / +45°C

## Photometry

EuLumDat file on the site

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G5h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-1:1997	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

## Logistics data

Item net weight	3800 gr
Barcode single item	8011905933180
Minimum order quantity	1