



DURA BEAM -TRACK LIGHT

Typology

Professional LED projectors for track mounting.

Features

Three different dimensions and power choices to cover all requirements.

Can be used with Eurostandard PLUS tracks as well as with other brands: Staff, Nordlux, Nordic, Global, etc.

Installation

Onto an electrical track in 3 phases; fixtures equipped with a safety lock to fix to the tracks.

Material

Die-cast painted aluminium body; black or white colour.

Power supply

Electronic driver integrated in the fixture body.

Beam

High efficiency Ra>90 LED Chip on Board.

Precision optics with dichroic effect lens.

Adjustable from 0° to -90° on the vertical plane and 350° on the horizontal plane.

Notes


Do not use with dimmer.

220-240 Vac	Ra 90		35000 h	IP20	Eurostandard	-25°C +35°C	RG1	PLUS	
	G4h24								
36°									

Characteristic data

Power	30 W	Beam	36°	Dimmable	No	Input	220-240 Vac
Base	Eurostandard	IP	20	Flux	2700 lm	PF	0,90
Tc	4000 K	Ra	90	LED Warranty	G4h24	Axis	5550 cd
RG	RG1	Color	Black				

Dimensional characteristics



L	190 mm
ø	80 mm
H	168 mm

Lighting and photometric features

Beam opening	36°
Flux	2700 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	90
Lifespan	35000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	30 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,90
Input current	0.15 A
Weighted energy consumption	30 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

Photometry



	4000K	H(m)	D(m)	E _{max} (lx)
	Ra90		38°	
Fixture Power	30W	1	0.69	5560
Source Flux	2700lm	2	1.38	1390
Fixture Flux	2700lm	3	2.08	618
Efficacy	90lm/W	4	2.77	347
936990 I _{max} =2059cd/klm	I _{max}	5	3.46	222

EulumDat file on the site

LED Warranty

G4h24	Full Guarantee 4 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-5:2016	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

Logistics data

Item net weight	690 gr
Barcode single item	8011905936990
Number of pieces multiple pack	10
Minimum order quantity	1