



## **DECO LED TECNO VINTAGE TRANSPARENT GLS**

**Typology**Range of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

#### Features

Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

#### Material

Glass bulb.

#### Notes

Do not use with dimmers except if otherwise indicated.

220-240 Vac





15000 h

IP20

E27

-25°C +35°C






Data sheet code: LFA600827

G2

#### Characteristic data

Power	8 W	Beam	320°	Dimmable	No	Input	220-240 Vac
Base	E27	IP	20	Flux	1055 lm	PF	0,50
Tc	2700 K	Ra	>80	LED Warranty	G2		

#### **Dimensional characteristics**



Ø	60 mm
Н	105 mm

Data sheet code: LFA600827



## Lighting and photometric features

Beam opening	320°
Flux	1055 lm
CCT nominal colour temperature	2700 K
Colour of the light	Warm light
Colour rendering index	>80
Lifespan	15000 h
LED lifespan	L70B20
Trigger time	<0,2 s
LM80 - Luminous flux maintenance at end of life	70
Heating time up to 60% of full efficiency	Instant Full Light
Mercury	0 mg

#### **Electrical characteristics**

Rated power	8 W
Input voltage	220-240 Vac
undefined	50 Hz
Dimmable	No
Power factor (PF)	0,50
Weighted energy consumtion	8 kWh/1000h
Energy class	A++
Number of cycles	100000
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	75
Operating position	360°

#### **LED Warranty**

G2	Up to 2 years
	(4000h/year) *4000h = 11h a day x 365 days.
	Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

## **Standards and Directives**

2009/125/EC, 244/2009, 859/2009, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 62031/A1/A2:2015
CEI EN 55015:2020	CEI EN 62471:2010
CEI EN 60968:2016	IEC TR 62471-2:2009
CEI EN 61000-3-2:2019	CEI EN 62560:2013
CEI EN 61000-3-3:2014	CEI EN 62560/A1:2017
CEI EN 61547:2010	CEI 34-141:2014
CEI EN 62031:2009	

# **Logistics data**

Barcode single item	8011905922573
Number of pieces multiple pack	10

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

