



DECO LED TECNO VINTAGE AMBER GLOBE

TypologyRange of lamps "filament LED": micro-led sources - that optimise thermal management - are positioned on a glass support and completely covered with phosphor powder that unifies, amplifies and diffuses the light.

Features

Excellent colour maintenance and are light constant over time. The spectrum of Tecno Vintage lamps is particularly rich in the warm colour bands to obtain an effect as close as possible to that of the lamps to be replaced.

Material

Glass bulb.

Notes

Do not use with dimmers except if otherwise indicated.

220-240 Vac







15000 h

IP20

E27

-25°C +35°C


Data sheet code: LFG9505AM

G2

Characteristic data

| Power | 4 W | Beam | 360° | Dimmable | No | Input | 220-240 Vac |
|-------|--------|------|------|--------------|--------|-------|-------------|
| Base | E27 | IP | 20 | Flux | 200 lm | PF | 0,51 |
| Tc | 1800 K | Ra | >80 | LED Warranty | G2 | | |

Dimensional characteristics



| Ø | 95 mm |
|---|--------|
| Н | 138 mm |

Data sheet code: LFG9505AM



Lighting and photometric features

| Beam opening | 360° |
|---|--------------------|
| Flux | 200 lm |
| CCT nominal colour temperature | 1800 K |
| Colour of the light | Warm light |
| Colour rendering index | >80 |
| Lifespan | 15000 h |
| LED lifespan | L70B50 |
| Trigger time | <0,2 s |
| Heating time up to 60% of full efficiency | Instant Full Light |
| Mercury | 0 mg |

Electrical characteristics

| Rated power | 4 W |
|------------------------------------|---------------|
| Input voltage | 220-240 Vac |
| Frequency | 50 Hz |
| Dimmable | No |
| Power factor (PF) | 0,51 |
| Input current | 0.03 A |
| Weighted energy consumption | 4 kWh/1000h |
| Operating temperature | -25°C / +35°C |
| Equivalence with incandescent lamp | 21 |
| Operating position | 360° |

LED Warranty

| G2 | Up to 2 years |
|----|---|
| | (4000h/year) *4000h = 11h a day x 365 days. |
| | Without limitations on the duration of use for the first year, provided the observance of |
| | the installation conditions. |

Standards and Directives

| 2009/125/EC, 244/2009, 859/2009, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863 | CEI EN 62031/A1/A2:2015 |
|---|-------------------------|
| CEI EN 55015:2020 | CEI EN 62471:2010 |
| CEI EN 60968:2016 | IEC TR 62471-2:2009 |
| CEI EN 61000-3-2:2019 | CEI EN 62560:2013 |
| CEI EN 61000-3-3:2014 | CEI EN 62560/A1:2017 |
| CEI EN 61547:2010 | CEI 34-141:2014 |
| CEI EN 62031:2009 | |

Logistics data

| Item net weight | 55 gr |
|--------------------------------|---------------|
| Barcode single item | 8011905861698 |
| Number of pieces multiple pack | 10 |
| Barcode multiple pack | 8011905863289 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

