



## Tree Light Pro | 36V | 4m | Green Wire | 6500K CW



|                 |  |
|-----------------|--|
| Article number: | 025-141  |
| CHANGED_LAST:   | 05-07-2022   |
| Brand:          | Tronix Lighting  |
| Type:           | String Light Pro 36V   |
| ETIM Group:     | EG000027 - Luminaires  |
| ETIM Classes:   | EC002761 - Festive lighting  |
| SYNONYM:        | Bulb luminaire, Candle, Candle stick light, Chandelier, Christmas lighting, Christmas tree lighting, Curtain light, Festive lighting, Illumination cable set |





## Feature

|  |   |   |                         |
|--|---|---|-------------------------|
| Model:   | Chainlight                              | Failure rate at median useful life of 50,000 h at 25 °C ambient (tq): | 0 %                     |
| Number of light centres:   | 30                                      | Constant light output (CLO):  | No                      |
| Lamp type:   | LED not exchangeable                    | Degree of protection (IP):  | IP65                    |
| With light source:   | Yes                                     | Protection class:   | III                     |
| Colour:  | Green                                   | Fire resistance according to UL94:                                    | C                       |
| Voltage type:  | DC                                      | Colour of light:  | White                   |
| Nominal voltage:   | 36 ~ 36 V                               | Power factor:   | 0.95                    |
| Connected load:  | 1.5 W                                   | Width:  | 0 mm                    |
| Battery power supply:  | No                                      | Height/depth:   | 0 mm                    |
| Suitable for outdoor use:  | Yes                                     | Total length:   | 4 m                     |
| With power bridge:   | No                                      | Diameter:   | 0 mm                    |
| Connectable:   | Yes                                     | Type of wiring:   | Through wiring included |
| Type of control gear:  | LED operating device voltage-controlled | Number of poles:  | 2                       |
| Exchangeable control gear:   | No                                      | Conductor cross section:  | 0.5 mm <sup>2</sup>     |
| Energy efficiency class of the built-in lamp:                              | A++, A+, A (LED)                        | Connection type:  | Other                   |
| Rated life time L70/B50 at 25 °C:  | 20000 h                                 | commercial, christmas or both:  | NA                      |
| Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq): | 0 %                                     |   |                         |

## Packaging data

|              |            |
|--------------|------------|
| Weight       | 280 gr     |
| Width        | 87 mm      |
| Height       | 90 mm      |
| Length       | 180 mm     |
| Customs code | 9405310000 |

