

## Floodlight PRO | 300W | 120° | Warm White 3000K

Article number: 146-350



The Floodlights for professional use is ideal for 'heavy' applications. Think of areas where lighting is often exposed to external weather conditions. Although this luminaire has a favorable IP rating of IP66, it is also equipped with an external air pressure valve. As a result, air pressure inside and outside the luminaire always remains the same and moisture inside the luminaire has no chance.

Because there are different lens options available with a smaller beam angle, these Floodlights are also suitable for:

- Illuminating large buildings such as churches or historic buildings.
- The available asymmetrical lens is suitable for illuminating tennis courts or other sports fields.

### Features

- 3x1.0 H05RN-F power cable with schuko plug. Very flexible and strong rubber cable
- Connection gland for possibly changing (a longer) power cable
- The surge protection protects the luminaire against peak voltages
- High light efficiency of >125 Lm / W
- Optional other lenses available (see related products)
- 5 year warranty and 50.000 burning hours

## Specifications

Input voltage	100-277V	CRI value	>70	Cable length	150 cm
Power	300 Watt	IP rate	IP66	Connection type	Schuko
Luminous flux	37.500 Lm	Sensor	No	Housing material	Aluminium
Color temperature	3000K	Width	363 mm	Housing color	Black (powder paint)
Light color	Warm white	Height	370 mm	Lifetime	50.000 hours
LED type	SMD3030	Height	470 mm (incl. handle)	Certification mark	CE, RoHS
Dimmable	No	Depth	80 mm	Warranty	5 years
Beam angle	120°	Working temperature	-30°C - +50°C		



## Line Drawings



