



## SLIMFLUX TONDO UP/DOWN

### Typology

Slim LED panel.

### Features

TONDO TRASLUCIDE SUSPENSION: power supply unit integrated in ceiling rose. The power cable is one with the suspension cables, therefore invisible. Adjustable suspension wires: MAX 150 cm. Cable attachment with screw and steel cylinder.

### Material

White painted metal body; frontal methacrylate panel.



### Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Flux	4000 lm	PF	0.95	Tc	4000 K
Ra	80	LED Warranty	G3	RG	RG0	Color	White

### Dimensional characteristics

∅	593 mm
L1	33.5 mm
H	19.5 mm

### Lighting and photometric features

Flux	4000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	80
Lifespan	30000 h
LED lifespan	L70 B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0.95
Operating temperature	-25°C / +40°C

## Photometry

EulumDat file on the site

## Other Infotech

Flicker Free	Yes
--------------	-----

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-2:2012	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

## Logistics data

Item net weight	3600 gr
Barcode single item	8011905984311
Number of pieces multiple pack	5
Barcode multiple pack	8011905985752
Minimum order quantity	5
Minimum packaging	5

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products