



SLIMFLUX BL-UGR PLUS

Typology

Direct lighting LED panel.

Features

The backlit panel is composed of a metal material back compartment providing a heat sink function.

Equipped with special PMMA primary lenses, the LED sources positioned on a horizontal plate ensure lighting uniformity on the diffuser surface and ensure excellent efficiency levels.

Colour rendering: Ra>80.

UGR version.

Material

White painted aluminium body; high transmittance optical PMMA screen.

Possibilities include: recessed, suspended, ceiling/wall.

Surface mounting & adjustable suspension wire kits are available as accessories.


Consider more depth for recessed installations.

220-240 Vac	Ra >80		35000 h	IP20 VI IP43 VO	Free Wire	-25°C +40°C	RG0	UGR >19	PLUS
	G3								

Characteristic data

Power	40 W	Dimmable	No	Input	220-240 Vac	Base	Free Wire
IP	20	Optical compartment IP	43	Flux	4000 lm	PF	0,9
UGR	>19	Tc	4000 K	Ra	>80	LED Warranty	G3
RG	RG0						

Dimensional characteristics



L	595 mm
L1	595 mm
H	26 mm

Lighting and photometric features

Flux	4000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	35000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,9
Operating temperature	-25°C / +40°C

Photometry

[EuLumDat file on the site](#)

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-2:2012	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

Logistics data

Item net weight	1800 gr
Barcode single item	8011905976750
Number of pieces multiple pack	6
Barcode multiple pack	8011905985127