



FRAME WITH SPRINGS FOR RECESSED INSTALLATION OF 60X60 PANELS IN NON-MODULAR CEILINGS.

Data sheet code: LPLAF060P

SET OF 4 EXTRUDED ALUMINIUM PROFILES TO BE EASILY ASSEMBLED WITH CORNER CLIPS. WHITE COLOR.

Frames for mounting LED panels on ceilings.

Make it possible to use SLIMFLUX panels in ceilings where there is no possibility to install recessed panels; frames can hide the drivers.

Epoxy painted extruded aluminium separated into 4 bars to be assemble while mounting. Easy and fast mounting directly on the surface.

White color.


Are mounted fixing directly the frame to the surface.

IP20

Characteristic data

IP	20 Color	Color White		
----	----------	-------------	--	--

Dimensional characteristics



L	603 mm
L1	603 mm
Н	60 mm

Lighting and photometric features

Colour of the light	Warm light

Standards and Directives

2011/65/EU, 2015/863		
2011/65/EU, 2015/863		

Data sheet code: LPLAF060P



Logistics data

Item net weight	810 gr
Barcode single item	8011905988029
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

