



## PANTH EVO

### Typology

LED projector "minimal design" for outdoor and indoor applications.

### Features

It can be connected to motion or twilight sensors.  
Very small dimensions and design that meets the most demanding aesthetic requirements.  
Supplied with an orientable mounting bracket.

### Material

Painted die-cast metal body.

### Beam

120°

### Notes

Do not use with dimmer.  
Free wire for professional use (1 m long).




220-240 Vac	Ra >80		50000 h	IP65	Terminals	-25°C +35°C	RG1	PLUS	 120°
G5h24									

### Characteristic data

Power	30 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	Terminals	IP	65	Flux	3000 lm	PF	0,98
Tc	4000 K	Ra	>80	LED Warranty	G5h24	Axis	950 cd
RG	RG1	Color	White				

## Dimensional characteristics



L	189 mm
L1	29 mm
H	133 mm

## Lighting and photometric features

Beam opening	120°
Flux	3000 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	50000 h
LED lifespan	L70B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

## Electrical characteristics

Rated power	30 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,98
Input current	0.13 A
Weighted energy consumption	30 kWh/1000h
Number of cycles	100000
Operating temperature	-25°C / +35°C

## Photometry

	4000K	H(m)	D(m)	E <sub>max</sub> (lx)	
	Ra80		111°		
Fixture Power	30W	1	2.90	929	
Source Flux	2650lm	2	5.80	232	
Fixture Flux	2650lm	3	8.70	103	
Efficacy	88lm/W	4	11.60	58	
855529 I <sub>max</sub> =351cd/klm	I <sub>max</sub>	929cd	5	14.50	37

EuLumDat file on the site

## Other Infotech

Reflector	Yes
-----------	-----

## LED Warranty

65h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## Standards and Directives

2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU	CEI EN 61000-3-3:2014
874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU	CEI EN 61547:2010
2014/35/EU, 2015/863	CEI EN 62031:2009
CEI EN 55015:2020	CEI EN 62031/A1/A2:2015
CEI EN 60598-1:2015	CEI EN 62471:2010
CEI EN 60598-1/A1:2019	IEC TR 62471-2:2009
CEI EN 60598-2-5:2016	CEI EN 62493:2015
CEI EN 61000-3-2:2019	CEI 34-141:2014

## Logistics data

Item net weight	205 gr
Barcode single item	8011905855529
Number of pieces multiple pack	20
Barcode multiple pack	8011905855536
Minimum order quantity	1