



CE RoHS

UGR<19

### Description :

It adopts high brightness high quality LED as luminous body with low-voltage constant current driver, low power consumption, long lifespan, reliability and safety. The housing, which is elegant and stylish, is made of high-purity aluminum with spraying coating. Good thermal management ensures stable working of LED, and controls light attenuation effectively.

Perfect optical design ensures soft and even light. Instant lighting, no flickering, no glaring. Free of lead, mercury and other harmful substances. This product is widely used in shopping mall, hotel, restaurant and etc.

The color temperature could be preset in advance.

### Notes

- ◆ Only qualified electrician is allowed to do the installation, maintenance and inspection for safety concern. It is dangerous for non-professional operator.
- ◆ Recessed installation only.
- ◆ Do not install the product in high temperature or humid place.
- ◆ 75mm space should be left around the product for ventilation, no cover on the light at any time.
- ◆ Storage conditions: room temperature, dry environment.

### Installation :

- Picture 1. Turn off the power.
- Picture 2. Drill a suitable mounting hole on ceiling according to size requirement of different item.
- Picture 3. Use switch to select desired color temperature.
- Picture 4. Connect input end of LED converter to commercial power(220-240V), and make sure connecting way is right.
- Picture 5. Put LED driver at suitable place on ceiling.
- Picture 6. Pinch both springs, then push light into installation hole, hangers rebound and chuck automatically. Make sure the light fixed well.
- Picture 7. Double-check if everything is well-connected, then turn on the power.

