



3 Phase Track | Black | Track Spot GU10 | 50mm



Article number:	169-153
CHANGED_LAST:	01-09-2022
Brand:	Tronix Lighting
Type:	High Bay Ufo
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC001744 - Downlight/spot/floodlight
SYNONYM:	Building site lighting luminaire, Downlight, Downlight/spot/floodlight, Floodlight, Light-track luminaire, Light-track spot, Projector, Spot, Spot luminaire/floodlight





Feature

Suitable for surface mounting:	Yes	Reflector:	None
Suitable for built-in mounting:	No	Light distributor:	None
Suitable for wall mounting:	No	Light outlet:	Direct
Suitable for suspended mounting:	No	Energy efficiency class of the built-in lamp:	A++, A+, A (LED)
Suitable for ceiling mounting:	Yes	Rated life time L70/B50 at 25 °C:	0 h
Suitable for traverse mounting:	No	Rated life time L80/B10 at 25 °C:	0 h
Suitable for pedestal/floor mounting:	No	Lumen maintenance at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Suitable for light-track mounting:	Yes	Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
Suitable for clamp-mounting:	No	Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
Suitable for low voltage cable system:	No	Failure rate at median useful life of 35,000 h at 25 °C ambient (tq):	0 %
Adjustability:	Rotating and swivelling	Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %
With movement sensor:	No	Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	0 %
With light sensor:	No	Constant light output (CLO):	No
Lamp type:	LED exchangeable	Degree of protection (IP):	IP20
With light source:	No	Degree of protection (NEMA):	1
Suitable for number of lamps:	1	Impact strength:	IK02
Lamp holder:	GU10	Protection class:	I
Material housing:	Aluminium	Rated ambient temperature according to IEC62722-2-1:	-20 ~ 45 °C
Surface protection:	Powder coating	Suitable for lamp power:	0 ~ 0 W
Colour housing:	Black	Max. system power:	0 W
Material cover:	None	Colour temperature:	0 ~ 0 K
Surface brushed:	No	Luminous flux:	0 ~ 0 lm
Voltage type:	AC	Rated luminous flux according to IEC 62722-2-1:	0 lm
Nominal voltage:	230 ~ 230 V	Luminous intensity:	0 cd
LED nominal current at constant current:	0 ~ 0 mA	Width:	0 mm
Type of control gear:	Not required	Height/depth:	0 mm
With control gear:	No	Length:	212 mm
Exchangeable control gear:	No	Outer diameter:	60 mm
Dimming depending on control gear:	No	Built-in width:	0 mm
Dimming 0-10 V:	No	Built-in height/depth:	0 mm
Dimming 1-10 V:	No	Built-in length:	0 mm
Dimming DALI-2:	No	Built-in diameter:	0 ~ 0 mm
Dimming DALI:	No	Type of wiring:	Ending
Dimming DMX:	No	Number of poles:	3
Dimming DSI:	No	Conductor cross section:	0 mm ²
Dimming potentiometer (integrated):	No	Connectable conductor cross section:	0 ~ 0 mm ²
Dimming GPRS:	No	Connection type:	Other
Dimming LineSwitch:	No	Luminaire with limited surface temperature, sign "D":	No
Dimming manufacturer's proprietary system:	No	Emergency power supply integrated:	No
Dimming mains voltage modulation:	No	Filament test according to IEC 60695-2-11:	650 °C - 30 s
Dimming phase cut-off:	No	Luminaire efficacy:	0 lm/W
Dimming phase cut-on:	No	Photobiological safety according to EN 62471:	RG0
Dimming programmable:	No	Suitable for workplace according to EN 12464-1:	No
Dimming RF:	No	Covering of the luminaire with thermally insulating material possible:	No



Dimming Sine Wave Reduction:	No	IFTTT support available:	No
Dimming Touch and Dim:	No	Compatible with Apple HomeKit:	No
Dimming Zigbee:	No	Compatible with Google Assistant:	No
Dimming with push-button:	No	Compatible with Amazon Alexa:	No
No dim function:	Yes		

Packaging data

Weight	400 gr
Width	97 mm
Height	81 mm
Length	230 mm
Customs code	9405114090

