



LIDER D micro

reflektor / spotlight

Charakterystyka:
reflektor typu shoplight LED, do montażu na szynoprzewodzie

Opis techniczny:
obudowa i uchwyt reflektora wykonane z odlewu aluminiowego, malowane proszkowo w kolorze czarnym, białym lub szarym, odbłyśnik, statecznik elektroniczny EVG

Montaż:
na szynoprzewodzie

Zastosowanie:
obiekty handlowe, biurowe, pomieszczenia reprezentacyjne, galerie, muzea, salony samochodowe

type	product	kolor/colour	(Ra)		temperatura barwowa/colour temperature						kąt świecenia/beam angle		max moc oprawy/ maximum power	max strumień oprawy/ maximum lumen output
			>80	>90	2500K	2700K	3000K	3500K	4000K	5000K	24°	36°		
Reflector	LIDER D micro	□ ■ ■ WH GY BK	8	9	25	27	30	35	40	50	24	36	max 20W	max 1872lm

przykład oznaczenia zamawianego produktu/example code: **RLDCOWH84036VE805000**



Characteristics:
shop-light lamp LED, assembled on the bus-duct

Technical description:
fitting and handle of the lamp made from aluminium casting pulverised in black, white or grey colour, reflecting element, electronic ballast EVG

Mounting:
on the bus-duct

Application:
commercial and office facilities, elegant halls, galleries, museum, car showrooms