



DURADISK LED

Typology

GX53 LED lamp with matt screen.

Features

Compactness and flexibility of use.
No problem of contact with wood due to heat.

Installation

Triple mounting options: surface, flush recessed, semi-recessed.

Material


Body and screen in plastic material.

Applications

Recessed in shelves, under-cabinet, walkways, etc.

Notes


Do not use with dimmer.



Characteristic data

Power	7 W	Beam	120°	Dimmable	No	Input	220-240 Vac
Base	GX53	IP	20	Flux	600 lm	PF	0,5
Tc	4000 K	Ra	>80	LED Warranty	G2		

Dimensional characteristics



Ø	75 mm
H	28 mm
H2	16 mm

Lighting and photometric features

Beam opening	120°
Flux	600 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	25000 h
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	7 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	No
Power factor (PF)	0,5
Input current	0.061 A
Weighted energy consumption	7 kWh/1000h
Operating temperature	-25°C / +35°C
Equivalence with incandescent lamp	48

Other Infotech

Reflector	Yes
-----------	-----

LED Warranty

G2	Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

Standards and Directives

2009/125/EC, 244/2009, 859/2009, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863	CEI EN 62031/A1/A2:2015
CEI EN 55015:2020	CEI EN 62471:2010
CEI EN 60968:2016	IEC TR 62471-2:2009
CEI EN 61000-3-2:2019	CEI EN 62560:2013
CEI EN 61000-3-3:2014	CEI EN 62560/A1:2017
CEI EN 61547:2010	CEI 34-141:2014
CEI EN 62031:2009	

Logistics data

Item net weight	45 gr
Barcode single item	8011905839079
Number of pieces multiple pack	10
Barcode multiple pack	8011905784355

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products