



DECO LED SENSOR

Typology

LED lamp with a built-in double twilight sensor.

Features

With an automatic ON/OFF switch it remains lit from dusk to dawn with very low energy consumption.

Double sensor to improve sensitivity and to ensure it does not turn off at the wrong

Standby energy consumption <1W.

Material

Body in thermal plastic and aluminum embedded.

Applications

Suitable for use in transparent, clear outdoor globes.
A lamp that turns ON automatically to be used in areas that are not frequented often, ideal in gardens and entrance ways to improve personal safety.

Notes

Do not use with dimmer.

Keep this lamp away from incandescent light sources that could interfere with the correct functioning of the light sensor.

220-240 Vac





25000 h

IP20

E27

-25°C +35°C


G2

Data sheet code: A6075-SR

Characteristic data

| Power | 10 W | Beam | 200° | Dimmable | No | Input | 220-240 Vac |
|-------|------|--------------|------|----------|---------|-------|-------------|
| Base | E27 | IP | 20 | Flux | 1060 lm | Tc | 4000 K |
| Ra | >80 | LED Warranty | G2 | | | | |

Dimensional characteristics



| Ø | 60 mm |
|---|--------|
| Н | 126 mm |

Data sheet code: A6075-SR



Lighting and photometric features

| Beam opening | 200° |
|-------------------------------------------|--------------------|
| Flux | 1060 lm |
| CCT nominal colour temperature | 4000 K |
| Colour of the light | Natural light |
| Colour rendering index | >80 |
| Lifespan | 25000 h |
| LED lifespan | L70B50 |
| Trigger time | <0,2 s |
| Heating time up to 60% of full efficiency | Instant Full Light |
| Mercury | 0 mg |

Electrical characteristics

| Rated power | 10 W |
|------------------------------------|---------------|
| Input voltage | 220-240 Vac |
| Frequency | 50 Hz |
| Dimmable | No |
| Weighted energy consumption | 10 kWh/1000h |
| Number of cycles | 100000 |
| Operating temperature | -25°C / +35°C |
| Equivalence with incandescent lamp | 75 |

LED Warranty

| G2 | Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of |
|----|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| | the installation conditions. |

Standards and Directives

| 2009/125/EC, 1194/2012, 2015/1428, 2010/30/EU, 874/2012, 2011/65/EU, 2012/19/EU, 2014/30/EU, 2014/35/EU, 2015/863 | CEI EN 62031/A1/A2:2015 |
|-------------------------------------------------------------------------------------------------------------------|-------------------------|
| CEI EN 55015:2020 | CEI EN 62471:2010 |
| CEI EN 60968:2016 | IEC TR 62471-2:2009 |
| CEI EN 61000-3-2:2019 | CEI EN 62560:2013 |
| CEI EN 61000-3-3:2014 | CEI EN 62560/A1:2017 |
| CEI EN 61547:2010 | CEI 34-141:2014 |
| CEI EN 62031:2009 | |

Logistics data

| Barcode single item | 8011905939830 |
|--------------------------------|---------------|
| Number of pieces multiple pack | 10 |
| Barcode multiple pack | 8011905958664 |

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

