

COMPACT LED HYGIENIC N 4400LM PLX II IP65 620X620 840 (42W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	647543
Rated power of the luminaire [W]*:	43
Luminous flux [lm]*:	4400
Colour temperature [K]:	4000
Luminaire color temperature [K]:	3500
Ingress protection:	IP65
Impact resistance:	IK07
Colour rendering index:	>80
SDCM:	≤ 3
Energy efficiency class:	E

CHARACTERISTICS

COMPACT LED HYGIENIC is a modified version of the proven COMPACT LED EVO model. The material composition of the diffuser and the body has been enriched with silver ions (2%). Silver ions effectively block the development of pathogens on the luminaire surface and reduce their amount (>99%) over 24 hours of contact. The effectiveness of reducing pathogens is confirmed by the BIOMASTER Certificate. The given color temperature value applies to the light source - LED module. The housing, especially the diffuser, has a slightly straw-colored shade due to the addition of silver ions to the plastic compared to the standard COMPACT LED EVO.

APPLICATION

COMPACT LED HYGIENIC is designed for rooms requiring special protection against pathogens, such as hospitals, patient rooms, medical clinics. The luminaire has received a certificate confirming that it is suitable for use in clean rooms with a stated air cleanliness class ISO 3 - 9 according to CLEANROOM ISO 14644-1:2015.

COMPACT LED HYGIENIC N 4400LM PLX II IP65 620X620 840 (42W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	647543	Material of the body:	ABS with the addition of silver ions (2%)
EAN:	5905963647543	Colour of the body:	white
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	620/620/66
Rated power of the luminaire [W]:	43	Impact resistance:	IK07
Nominal power [W]:	42	Ingress protection:	IP65
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous flux [lm]:	4400	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	102	Net weight of the luminaire [kg]:	3.490
Energy efficiency class:	E	Warranty [years]:	5
Electrical protection class:	II	Category type:	louvres
Colour temperature [K]:	4000	AC voltage range [V]:	220 - 240
Luminaire color temperature [K]:	3500	LED lifespan L70B50 [h]:	125000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	82000
SDCM:	≤ 3	LED lifespan L90B10 [h]:	40000
Power factor:	0.95	CE certificate:	182/2020
Beam angle [°]:	120	PZH certificate:	B-BK-60212-0620/20
Diffuser material:	PC with the addition of silver ions (2%)	Manual:	Download PDF
Diffuser type:	OPAL		

COMPACT LED HYGIENIC N 4400LM PLX II IP65 620X620 840 (42W)

DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
630033	Plasterboard mounting brackets (4 pcs)
904349	Safety suspension (modular ceiling)
999543	Plasterboard recessing kit 630x630 white



Plasterboard mounting brackets (4 pcs) (630033)



Safety suspension (modular ceiling) (904349)



Plasterboard recessing kit 630x630 white (999543)

Card creation date: 14 December 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 182/2020