



SLIMFLUX BL - BASIC

Typology

Direct lighting LED panel.

Features

The backlit panel is composed of a metal material back compartment providing a heat sink function.

Colour rendering: Ra>80.

Do not use with dimmer.

Installation

Possibilities include: recessed, suspended, ceiling/wall.

Surface mounting & adjustable suspension wire kits are available as accessories.

Consider more depth for recessed installations.

Material

Painted white aluminium body; high-transmittance PMMA primary optics.

Notes


Providing greater visual comfort, improved definition of detail and reduction of stress.

| | | | | | | | | | |
|-------------|---------------------|--|---------|--------------------|-----------|----------------|-----|--------------|--|
| 220-240 Vac | Ra >80 | | 25000 h | IP20 VI IP43 VO | Free Wire | -20°C +45°C | RG0 | BASIC | |
| G2 | FLICKER FREE | | | | | | | | |

Characteristic data

| | | | | | | | |
|-------|--------|------------------------|-----|--------------|-------------|------|-----------|
| Power | 30 W | Dimmable | No | Input | 220-240 Vac | Base | Free Wire |
| IP | 20 | Optical compartment IP | 43 | Flux | 3600 lm | PF | >0,9 |
| Tc | 4000 K | Ra | >80 | LED Warranty | G2 | RG | RG0 |

Dimensional characteristics



| | |
|----|--------|
| L | 595 mm |
| L1 | 595 mm |
| H | 25 mm |

Lighting and photometric features

| | |
|-------------------------------------------|--------------------|
| Flux | 3600 lm |
| CCT nominal colour temperature | 4000 K |
| Colour of the light | Natural light |
| Colour rendering index | >80 |
| Lifespan | 25000 h |
| LED lifespan | L70B20 |
| Trigger time | <0,2 s |
| Heating time up to 60% of full efficiency | Instant Full Light |

Electrical characteristics

| | |
|-----------------------|---------------|
| Rated power | 30 W |
| Input voltage | 220-240 Vac |
| Frequency | 50-60 Hz |
| Dimmable | No |
| Power factor (PF) | >0,9 |
| Operating temperature | -20°C / +45°C |

Other Infotech

| | |
|--------------|-----|
| Flicker Free | Yes |
|--------------|-----|

LED Warranty

| | |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| G2 | Up to 2 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions. |
|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Logistics data

| | |
|--------------------------------|---------------|
| Item net weight | 1060 gr |
| Barcode single item | 8011905983505 |
| Number of pieces multiple pack | 8 |
| Barcode multiple pack | 8011905983505 |
| Minimum order quantity | 8 |
| Minimum packaging | 8 |