



PRODUCT DATASHEET

Code No. ALP-6060-28W (4000K) UGR

Part No. HL0018084

Product Description

Model	Power	Input Voltage	led Type	led Qty	Luminous	CCT	CRI	Dimension
ALP-6060-28W UGR	28W	AC220-240V 50/60Hz	SMD 4014	224	3600-3800 lm	4000K	>80	595x595x9 mm

Product Features

- * Ultra flat LED appliances with thickness: 9mm.
- * Directly replace 595x595mm grille lamp with excellent light distribution.
- * Installation recessed ,suspended or ceiling type with frame optional.
- * Color temperature optional from 2700k to 6500k.
- * Heat Dissipation from side and back to keep long work time to 50000 hours
- * White painted AL body with transparent cover.
- * High color rendering : RA>80 to protect the eyes.
- * Switch-on Immediate.
- * IP20 for indoor use.
- * Adjustable height if suspended installation.
- * Fuse for mains protection.
- * MS material LGP (light guide plate) keep high efficiency light output
- * The lumen output upto 130lm/w, More energy-efficient

For Driver

- *Input voltage: AC220-240V 50/60Hz
- *Frequency 50/60Hz
- *Input Current 0.5A max
- *Output current 600mA+5%
- *Output voltage 38-65 Vdc
- *Output power 30W max
- *Dimension: 135*45*30 mm
- *Die Casting PVC flame retardant housing safe and stable.

Photoelectric & Technical parameter

- *Dimmable: No
- *Power Factor:>0.5
- *Number of ON-OFF cycles 100000
- *No UV, IR or mercury
- *Working temperature: -10°C - 45°C
- *Power Efficiency: 89%
- *Lamp start time: <0,1s
- *UGR<19
- *Flicker Free
- *Beam Angle :85°
- *Applied standard:
EN 55015:2013+A1
EN 61547:2009
EN 61000-3-2:2014
EN61000-3-3:2013

Packing & Shipping info.

- *Single pack dimensions: 650x30x625 mm
- *5 PCS with one master box
- *Master carton size: 67x18.5x66 cm
- *Weight: 12.9kg /master carton