



## PRODUCT DATASHEET

Code No. ALP-30120-28W (4000K)

Part No. HL0018085

### Product Description

Model	Power	Input Voltage	led Type	led Qty	Luminous	CCT	CRI	Dimension
ALP-30120-28W	28W	AC220-240V 50/60Hz	SMD 4014	252	3700-3900 lm	4000K	>80	295x1195x9 mm

### Product Features

- \* Ultra flat LED appliances with thickness: 9mm.
- \* Directly replace 1195x295mm grille lamp with excellent light distribution.
- \* Installation recessed ,suspended or ceiling type with frame optional.
- \* Color temperature optional from 2700k to 6500k.
- \* Heat Dissipation from side and back to keep long work time to 50000 hours
- \* White painted AL body with transparent cover.
- \* High color rendering : RA>80 to protect the eyes.
- \* Switch-on Immediate.
- \* IP20 for indoor use.
- \* Adjustable height if suspended installation.
- \* Fuse for mains protection.
- \* MS material LGP (light guide plate) keep high efficiency light output
- \* The lumen output upto 130lm/w, More energy-efficient

### For Driver

- \*Input voltage: AC220-240V 50/60Hz
- \*Frequency 50/60Hz
- \*Input Current 0.5A max
- \*Output current 600mA+5%
- \*Output voltage 38-65 Vdc
- \*Output power 30W max
- \*Dimension: 135\*45\*30 mm
- \*Die Casting PVC flame retardant housing safe and stable.

### **Photoelectric & Technical parameter**

- \*Dimmable: No
- \*Power Factor:>0.5
- \*Number of ON-OFF cycles 100000
- \*No UV, IR or mercury
- \*Working temperature: -10°C - 45°C
- \*Power Efficiency: 89%
- \*Lamp start time: <0,1s
- \*UGR>19
- \*Flicker Free
- \*Beam Angle :120°
- \*Applied standard:  
EN 55015:2013+A1  
EN 61547:2009  
EN 61000-3-2:2014  
EN61000-3-3:2013

### **Packing & Shipping info.**

- \*Single pack dimensions: 1250x30x330 mm
- \*5 PCS with one master box
- \*Master carton size: 127x18x35 cm
- \*Weight: 12.7kg /master carton