



SLIMFLUX SL UGR - PRO

Typology

Ultra-flat LED fixtures with lateral lighting.

Features

Side heat dissipation.
 Immediate switch-on.
 Colour rendering: Ra>80 or Ra>90.
 Remote power supply included.
 Do not use with dimmer.
 If you want to dim or use the multicurrent power supply dimmer.
 UGR version.
 Class II fittings.

Installation

Possibilities include: recessed, suspended, ceiling/wall.
 Surface mounting & adjustable suspension wire kits are available as accessories.

Material

White painted aluminium body; high transmittance optical PMMA screen.

Usage information

SLIMFLUX 60x60 panels can be used with multi-current dimming power supply, code DELT40D-M.

Emergency

SLIMFLUX panels can be used with standby emergency kit, code KTEMR03.

Notes


This panel does NOT include the driver: please select the required product from the range.
 Providing greater visual comfort, improved definition of detail and reduction of stress.

220-240 Vac	Ra >80		15000 h	IP20 VI IP43 VO	Connector	-20°C +45°C	RG0	UGR <19	PRO
	G5h24								

Characteristic data

Power	37 W	Dimmable	No	Input	220-240 Vac	Base	Connector
IP	20	Optical compartment IP	43	Flux	4350 lm	PF	0,95
UGR	<19	Tc	4000 K	Ra	>80	LED Warranty	G5h24
RG	RG0						

Dimensional characteristics



L	620 mm
L1	620 mm
H	9 mm

Lighting and photometric features

Flux	4350 lm
CCT nominal colour temperature	4000 K
Colour of the light	Natural light
Colour rendering index	>80
Lifespan	15000 h
LED lifespan	L80B20
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light
UGR	<19

Electrical characteristics

Rated power	37 W
Input voltage	220-240 Vac
Frequency	50-60 Hz
Dimmable	No
Power factor (PF)	0,95
Operating temperature	-20°C / +45°C

Photometry

EulumDat file on the site

Other Infotech

Flicker Free	Yes
--------------	-----

LED Warranty

G5h24	<p>Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.</p>
-------	--

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC (Compatibilità Elettromagnetica)
2014/35/EU * LVD (Bassa Tensione)
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-2:2012
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Item net weight	2200 gr
Barcode single item	8011905973933
Number of pieces multiple pack	5
Minimum order quantity	1