



Garden Light | Ø115mm | Head Part | 15W | 3000K | IP65 | Dim



Article number:	149-330
CHANGED_LAST:	21-06-2022
Brand:	Tronix Lighting
Type:	Garden Light
ETIM Group:	EG000027 - Luminaires
ETIM Classes:	EC000301 - Luminaire bollard
SYNONYM:	Bollard, Bollard luminaire, Luminaire bollard, Orientation luminaire, Pedestal luminaire, Stele





Feature

Type of luminaire:	Bollard luminaire	Impact strength:	IK06
With base plate:	No	Protection class:	I
With light sensor:	No	Suitable for lamp power:	0 ~ 0 W
With movement sensor:	No	Max. system power:	15 W
Lamp type:	LED not exchangeable	Rated luminous flux according to IEC 62722-2-1:	1425 lm
With light source:	Yes	Luminaire efficacy:	0 lm/W
Lamp holder:	None	Luminous intensity:	0 cd
Material housing:	Aluminium	Colour of light:	White
Surface protection:	Powder coating	Colour temperature:	3000 ~ 3000 K
Colour housing:	Black	Colour rendering index CRI:	80-89
Material cover:	Plastic, opal	Power factor:	0.9
Voltage type:	AC	Colour temperature adjustable:	No
Nominal voltage:	220 ~ 240 V	Luminous flux adjustable:	Continuously variable
LED nominal current at constant current:	350 ~ 350 mA	Beam angle adjustable:	No
Type of control gear:	LED operating device current-controlled	Width:	0 mm
With control gear:	Yes	Height/depth:	0 mm
Exchangeable control gear:	No	Length:	250 mm
Light distributor:	Reflector	Diameter:	115 mm
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)	Type of wiring:	Ending
Rated life time L70/B50 at 25 °C:	30000 h	Number of poles:	3
Lumen maintenance at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Conductor cross section:	0.75 mm ²
Lumen maintenance at median useful life of 100,000 h at 25 °C ambient (tq):	0 %	Connection type:	Other
Failure rate at median useful life of 50,000 h at 25 °C ambient (tq):	0 %	Compatible with Apple HomeKit:	No
Failure rate at median useful life of 100,000 h at 25 °C ambient (tq):	0 %	Compatible with Google Assistant:	No
Constant light output (CLO):	No	Compatible with Amazon Alexa:	No
Degree of protection (IP):	IP65	IFTTT support available:	No
Degree of protection (NEMA):	3		

Packaging data

Weight	1.48 kg
Width	130 mm
Height	130 mm
Length	312 mm
Customs code	9405119090

