

## Straight aluminium columns

ø114 mm at the base

**Anodising:** 10 colours, each with the option of chemical brightening

**Finish:** brushed, anodised aluminium, option of elastomer protection in the colour of the column up to the height of 350 mm (other height on customer's request)

**Diameter of the column ending:** ø60 mm

**Luminaire mounting:** directly on the column, luminaires with mounting ø60 mm with weight and surface parameters not exceeding the data from the strength table included in the technical data sheet



Column type	SAL-2,5/B60	SAL-3/B60	SAL-3,5/B60	SAL-4/B60	SAL-4,5/B60	SAL-5/B60
Height of the column H [mm]	2 500	3 000	3 500	4 000	4 500	5 000
Code	42126/C...	42120/C...	42101/C...	42102/C...	42103/C...	42127/C...
Net weight [kg]	7,1	8,3	9,8	11,4	12,9	13,6
Approximate unit volume [m³]*	0,056	0,067	0,078	0,09	0,1	0,11
Recommended luminaires for column top mounting	ISKRA LED ALFA, ISKRA LED ALFA PROG, ELBA LED, AURIS LED, ATLANTIS LED, MIRA LED, ELBA, OPA-1, OP, OZ					
Recommended extension arms and luminaires	WA-14/1, WA-41 f42 - OW LED					
Concrete footing / reinforcement basket type	B-50 / Z-50					
Threaded anchor ending	4xM14					
Concrete footing / reinforcement basket code	311150 / 311205					
Fasteners	4006					
Dimension of the base plate (side / bolt spacing / thickness) [mm]	224 / 180 / 8					

\* For order of more than 10 pcs stated volume may change according to packing /C... - choice of anodising colour

Cracow, Poland



Luminaire: ISKRA LED ALFA  
Column: SAL-4/B60

