

Product code: 470058 EAN: 5907777470058

LED line® Panel Easy Fix AURA 18W 4000K 1650lm round



Product description

Mounting clips can be moved along the mounting bracket allowing the product to fit into most existing mounting holes. Manufacturer issues a 3-year warranty for this product. Possible installation methods: recessed and surface. The installation method can be adjusted to the individual's needs. FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight. Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Possible installation methods: recessed and surface. The installation method can be adjusted to the individual's needs.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



IP protection rating



Lamp's diameter



LGP



Material (housing)



LED quantity



Power Factor



Ambient temperature suitable for operation



IEC protection class



Manufacturer issues a 3-year warranty for this product.



Mounting clips can be moved along the mounting bracket allowing the product to fit into most existing mounting holes.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



The power supply system used allows for smooth adjustment of light intensity using an appropriate dimmer.



Voltage range and voltage type



Beam angle



Material (cover)



LED type



Compatible dimmer type



Number of on/off cycles




Mounting hole diameter

Name of the parameter	Value
Colour of the light	White
Correlated colour temperature	4000 K
Wattage	18 W
Luminous efficacy	92 lm/W
Luminous flux	1650 lm
IP protection rating	20
Warranty (years)	3
Flicker Free	YES
Supply voltage range and voltage type	220-260 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96
Lamp's diameter	217
Beam angle	120 °
LGP	GLASS
Material (cover)	polystyrene
Material (housing)	Polyamid
LED type	SMD2835
LED quantity	84


Name of the parameter	Value
Compatible dimmer type	TRIAC
Lifespan	30000
Power Factor	0,9
Number of on/off cycles	50000
Ambient temperature suitable for operation	-5 ÷ 40 °C
Mounting hole diameter	60-185 mm
For indoor use	YES
IEC protection class	II
Full box quantity	20 pc
Lamp's warm-up time to 60%	1
Height	15 mm
EPREL ID	632220
Energy class	A++
Product code	470058

Luminous [cd/klm]




C0 - C180 C90 - C270

Pre-packaging




Width [mm]	222
Height [mm]	232
Length [mm]	42
Weight [kg]	0,35

Cumulative packaging



Number of pieces	20
Width [mm]	250
Height [mm]	445
Length [mm]	465
Weight [kg]	11
Volume [m ³]	0,05173125

Europallet



Number of pieces	420
Bulk quantity	21
Weight [kg]	231
Weight [kg]	231
Pallet height [mm]	1479
Quantity in 1 layer	7
Number of layers	3