




















Product code: 241444 EAN: 5901583241444

LED line® strip 150 SMD 12V RGB 7,2W IP67



Product description


Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years. This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use. This LED strip produces light from RGB colour palette. Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre. Manufacturer issues a 3-year warranty for this product.

	Manufacturer issues a 3-year warranty for this product.		Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.
	This LED strip produces light from RGB colour palette.		Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.
	This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.		
	IP protection rating		Lifespan
	Voltage range and voltage type		LED type
	Beam angle		Laminate (thickness)
	Compatible dimmer type		Cutting section
	LED quantity (1m)		Number of on/off cycles
	Type of adhesive tape		IEC protection class
	Ambient temperature suitable for operation		


Name of the parameter	Value
Colour of the light	RGB
IP protection rating	67
Warranty (years)	3
Minimum purchase quantity	5
Lifetime L70B50	30000
Wattage (lm)	7,2 W
Wavelength	620, 520, 465nm
Current (lm)	0,6
Supply voltage range and voltage type	12 DC
Metres per roll	5

Name of the parameter	Value
The lumen maintenance factor	>0,7
Beam angle	120 °
LED type	SMD5050
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	30
Cutting section	10
Type of adhesive tape	Piankowa
Lifespan	100000
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	40 pc
Lamp's warm-up time to 60%	1
Width	12 mm
Height	5 mm
Product weight with packaging (g)	>0,7 g
Master carton weight (kg)	9,76
Product code	241444

Luminous [cd/klm]




Cumulative packaging



Number of pieces **100**

Europallet



Number of pieces	2400
Bulk quantity	60
Weight [kg]	300
Weight [kg]	300
Pallet height [mm]	1800
Quantity in 1 layer	6
Number of layers	10