



MARAMA

Typology

LED table lamp, dimmable and cordless.
Elegant and essential design, perfect for both modern and classical settings.
Diffused light directed downwards.

Features

Dimmable version with the possibility of changing the light colour from very warm to natural (1800K-4000K).
Marama is operated by a touch on the top of the diffuser: the touch activates on/off, light intensity and choice of desired colour temperature.

Material

Powder-coated aluminium; frosted polycarbonate screen.

Usage information


Battery: battery life of up to 12 hours at full light output and up to 5 days at the lowest output.
Equipped with large capacity 6600mAh rechargeable lithium battery.
Type-C charging cable included (can be used with any cable with Type-C jack).
Charger USB C not included.
Battery charging time: 5~6 hours.

Accessories

Type-C charging cable included (can be used with any cable with Type-C jack).

Notes

Indoors and outdoors protected from direct rain.



Characteristic data

Power	2 W	Dimmable	Yes	Input	5 Vdc	IP	53
Flux	100 lm	Tc	1800-4000 K	Ra	90	LED Warranty	G3
RG	RG0	Color	Black				

Dimensional characteristics



ø	120 mm
ø1	100 mm
H	350 mm

Lighting and photometric features

Flux	100 lm
CCT nominal colour temperature	1800-4000 K
Colour of the light	CCT
Colour rendering index	90
LED lifespan	L70B50
Trigger time	<0,2 s
Heating time up to 60% of full efficiency	Instant Full Light

Electrical characteristics

Rated power	2 W
Input voltage	5 Vdc
Dimmable	Yes
Input current	2 A
Operating temperature	-25°C / +45°C

Photometry

EulumDat file on the site

LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

European Directives

2009/125/EC * Ecodesign
2011/65/EU * RoHS
2012/19/EU * RAEE
2014/30/EU * EMC (Compatibilità Elettromagnetica)
2014/35/EU * LVD (Bassa Tensione)
2015/863 * Amending RoHS
2017/1369 * Regulation for Energy Labelling
2019/2015 * Regulation for Energy Labelling
2019/2020 * Regulation for Ecodesign
2021/340 * Amending Reg. Energy Labelling
2021/341 * Amending Reg. Ecodesign

Product standards

CEI EN 55015:2020 (+A11:2020)
CEI EN 60598-1:2022
CEI EN 60598-2-4:2019
CEI EN 61000-3-2:2019 (+A1:2021)
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
CEI EN 61547:2010
CEI EN 62031:2021 (+A11:2022)
CEI EN 62471:2010
IEC/TR 62471-2:2009
CEI EN 62493:2015
CEI 34-141:2014

Logistics data

Barcode single item	8011905988166
Number of pieces multiple pack	10
Barcode multiple pack	8011905988463
Minimum order quantity	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products