





Typology LED, dimmable, cordless table lamp with dedicated charging base.

Simply place the lamp on the base to start charging.

MARAMA WITH CHARGING BASE

Elegant and essential design, perfect for both modern and classical settings. Diffused light directed downwards.

MAR2 models are built to be charged only with their own base, a good deterrent for those who want to take possession of it!

Data sheet code: MAR23000DIMCO

Features

Warm white dimmable version.

Marama is operated by a touch on the top of the diffuser: the touch activates on/off and light intensity.

Material

Powder-coated aluminium; frosted polycarbonate screen.

Usage information

Battery: battery life of up to 12 hours at full light output and up to 5 days at the lowest output.

Equipped with large capacity 6600mAh rechargeable lithium battery.

Accessories

MAR2 charges with the dedicated charging base supplied. Also available a 6-station multiple charging base code ZK-MAR6P (up to 7 multiple bases can be connected in series for a total of 42 lamps charging simultaneously).

Indoors and outdoors protected from direct rain.

5 Vdc

Ra 90



IP53

-25°C +45°C

RG0





G3

Characteristic data

Power	2 W	Dimmable	Yes	Input	5 Vdc	IP	53
Flux	100 lm	Tc	3000 K	Ra	90	LED Warranty	G3
RG	RG0	Color	Corten				



Dimensional characteristics



Ø	120 mm
ø1	100 mm
Н	335 mm

Lighting and photometric features

Flux	100 lm
CCT nominal colour temperature	3000 K
Colour of the light	Warm light
Colour rendering index	90
LED lifespan	L70B20

Electrical characteristics

Rated power	2 W
Input voltage	5 Vdc
Dimmable	Yes
Input current	2 A
Operating temperature	-25°C / +45°C

Photometry

EuLumDat file on the site

LED Warranty

G3	Up to 3 years
	(4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.

Data sheet code: MAR23000DIMCO



European Directives

Product standards

2009/125/EC * Ecodesign	CEI EN 55015:2020 (+A11:2020)
2011/65/EU * RoHS	CEI EN 60598-1:2022
2012/19/EU * RAEE	CEI EN 60598-2-4:2019
2014/30/EU * EMC (Compatibilità Elettromagnetica)	CEI EN 61000-3-2:2019 (+A1:2021)
2014/35/EU * LVD (Bassa Tensione)	CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
2015/863 * Amending RoHS	CEI EN 61547:2010
2017/1369 * Regulation for Energy Labelling	CEI EN 62031:2021 (+A11:2022)
2019/2015 * Regulation for Energy Labelling	CEI EN 62471:2010
2019/2020 * Regulation for Ecodesign	IEC/TR 62471-2:2009
2021/340 * Amending Reg. Energy Labelling	CEI EN 62493:2015
2021/341 * Amending Reg. Ecodesign	CEI 34-141:2014

Logistics data

Barcode single item	8011905994334
Number of pieces multiple pack	10
Barcode multiple pack	8011905994389
Minimum order quantity	1
Minimum packaging	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products

