Data sheet code: MAR21840CCTWH





MARAMA WITH CHARGING BASE

Typology LED, dimmable, cordless table lamp with dedicated charging base. Simply place the lamp on the base to start charging. Elegant and essential design, perfect for both modern and classical settings. Diffused light directed downwards. MAR2 models are built to be charged only with their own base, a good deterrent for those who want to take possession of it!

Features

Dimmable version with the possibility of changing the light colour from very warm to natural (1800K-4000K).

Marama is operated by a touch on the top of the diffuser: the touch activates on/off, light intensity and choice of desired colour temperature.

Material

Powder-coated aluminium; frosted polycarbonate screen.

Usage information

Battery: battery life of up to 12 hours at full light output and up to 5 days at the lowest output.

Equipped with large capacity 6600mAh rechargeable lithium battery.

Accessories

MAR2 charges with the dedicated charging base supplied. Also available a 6-station multiple charging base code ZK-MAR6P (up to 7 multiple bases can be connected in series for a total of 42 lamps charging simultaneously).

Notes

Indoors and outdoors protected from direct rain.




-25°C PLUS 5 Vdc Ra 90 IP53 RG0 G3 +45°C

Characteristic data

Power	2 W	Dimmable	Yes	Input	5 Vdc	IP	53
Flux	100 lm	Tc	1800-4000 K	Ra	90	LED Warranty	G3
RG	RGO	Color	White				



Dimensional characteristics



Ø	120 mm
ø1	100 mm
Н	335 mm

Lighting and photometric features

Flux	100 lm
CCT nominal colour temperature	1800-4000 K
Colour of the light	100
Colour rendering index	90
LED lifespan	L70B50

Electrical characteristics

Rated power	2 W
Input voltage	5 Vdc
Dimmable	Yes
Input current	2 A
Operating temperature	-25°C / +45°C

Photometry

EuLumDat file on the site

LED Warranty

	*4000h = 11h a day x 365 days.tions on the duration of use for the first year, provided the observance of
--	---





Data sheet code: MAR21840CCTWH

European Directives	Product standards
2009/125/EC * Ecodesign	CEI EN 55015:2020 (+A11:2020)
2011/65/EU * RoHS	CEI EN 60598-1:2022
2012/19/EU * RAEE	CEI EN 60598-2-4:2019
2014/30/EU * EMC (Compatibilità Elettromagnetica)	CEI EN 61000-3-2:2019 (+A1:2021)
2014/35/EU * LVD (Bassa Tensione)	CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)
2015/863 * Amending RoHS	CEI EN 61547:2010
2017/1369 * Regulation for Energy Labelling	CEI EN 62031:2021 (+A11:2022)
2019/2015 * Regulation for Energy Labelling	CEI EN 62471:2010
2019/2020 * Regulation for Ecodesign	IEC/TR 62471-2:2009
2021/340 * Amending Reg. Energy Labelling	CEI EN 62493:2015
2021/341 * Amending Reg. Ecodesign	CEI 34-141:2014

.

Logistics data

Barcode single item	8011905994341
Number of pieces multiple pack	10
Barcode multiple pack	8011905994402
Minimum order quantity	1
Minimum packaging	1

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibilityderiving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products



Datasheet 22/03/2023 Page 3 of 3 Scheda tecnica