



## MARAMA WITH CHARGING BASE

### Typology

LED, dimmable, cordless table lamp with dedicated charging base. Simply place the lamp on the base to start charging.

Elegant and essential design, perfect for both modern and classical settings.

Diffused light directed downwards.

MAR2 models are built to be charged only with their own base, a good deterrent for those who want to take possession of it!

### Features

Dimmable version with the possibility of changing the light colour from very warm to natural (1800K-4000K).

Marama is operated by a touch on the top of the diffuser: the touch activates on/off, light intensity and choice of desired colour temperature.

### Material

Powder-coated aluminium; frosted polycarbonate screen.

### Usage information

Battery: battery life of up to 12 hours at full light output and up to 5 days at the lowest output.

Equipped with large capacity 6600mAh rechargeable lithium battery.


### Accessories

MAR2 charges with the dedicated charging base supplied.

Also available a 6-station multiple charging base code ZK-MAR6P (up to 7 multiple bases can be connected in series for a total of 42 lamps charging simultaneously).

### Notes

Indoors and outdoors protected from direct rain.



### Characteristic data

Power	2 W	Dimmable	Yes	Input	5 Vdc	IP	53
Flux	100 lm	Tc	1800-4000 K	Ra	90	LED Warranty	G3
RG	RG0	Color	Black				

## Dimensional characteristics



Ø	120 mm
Ø1	100 mm
H	335 mm

## Lighting and photometric features

Flux	100 lm
CCT nominal colour temperature	1800-4000 K
Colour of the light	CCT
Colour rendering index	90
LED lifespan	L70B50

## Electrical characteristics

Rated power	2 W
Input voltage	5 Vdc
Dimmable	Yes
Input current	2 A
Operating temperature	-25°C / +45°C

## Photometry

EulumDat file on the site

## LED Warranty

G3	Up to 3 years (4000h/year) *4000h = 11h a day x 365 days. Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
----	--

## European Directives

2009/125/EC \* Ecodesign  
 2011/65/EU \* RoHS  
 2012/19/EU \* RAEE  
 2014/30/EU \* EMC (Compatibilità Elettromagnetica)  
 2014/35/EU \* LVD (Bassa Tensione)  
 2015/863 \* Amending RoHS  
 2017/1369 \* Regulation for Energy Labelling  
 2019/2015 \* Regulation for Energy Labelling  
 2019/2020 \* Regulation for Ecodesign  
 2021/340 \* Amending Reg. Energy Labelling  
 2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
 CEI EN 60598-1:2022  
 CEI EN 60598-2-4:2019  
 CEI EN 61000-3-2:2019 (+A1:2021)  
 CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
 CEI EN 61547:2010  
 CEI EN 62031:2021 (+A11:2022)  
 CEI EN 62471:2010  
 IEC/TR 62471-2:2009  
 CEI EN 62493:2015  
 CEI 34-141:2014

## Logistics data

Barcode single item	8011905994358
Number of pieces multiple pack	10
Barcode multiple pack	8011905994426
Minimum order quantity	1
Minimum packaging	1