

www.1-light.eu

09 Track Lights>Adjustable LED Linear Track Light

65024T/B/W



10X5W COB linear track light spot +-45° adjustable, ideal for shops and showrooms.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.











## Downloads









#### Dimensions



### Related items







40003A/B

### **Physical Specification**

09 Track Lights
Adjustable LED Linear Track Light
65024T/B/W
Black
Aluminium + Plastic
Rectangular
580mm

Width	60mm
Height	80mm
Track mounted	Yes
Indoor	Yes
Adjustable	1 Direction

# Electrical Characteristics

Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10x5W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	1200mA
Voltage	38V
Power(Watts)	45,6W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux
LED Number	10

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	39,6-50,4W
Power Factor	0,9
Constant Current	Yes
1200mA	33-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	LIFUD
Protection	Short Circuit Protection
Illumination Data	
Illumination Data  Colour Temperature	3000K
	3000K 10x580lm
Colour Temperature	
Colour Temperature  Lumen Output	10x580lm
Colour Temperature  Lumen Output  Light Efficiency	10x580lm 116lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	10x580lm 116lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	10x580lm 116lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	10x580lm 116lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	10x580lm 116lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	10x580lm 116lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	10x580lm  116lm/W  80  30°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	10x580lm  116lm/W  80  30°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	10x580lm  116lm/W  80  30°  51,5cm  9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	10x580lm  116lm/W  80  30°  51,5cm  9cm  13cm

Barcode	5291889058854
HS Code	9405413990

Certification & Warranty	
Warranty	3 Years
Weee Directive	Yes



