

4 *ST / AT / D2 / D2R / DA

4.1 → **1.1** → **3.2** → **3.4**

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

4.2

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

4.3

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

4.4

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

4.5

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

4.6

LiFePO4/C 3.2V 3.0Ah
LiFePO4/C 6.4V 1.5Ah

LiFePO4/C 3.2V 1.5Ah

4.7

LiFePO4/C 3.2V 1.5Ah

4.8 → **1.7** → **1.8** → **1.9**

4.8 → **1.7** → **1.8** → **1.9**

PRIMO Q	M
t _c	105°C

PRIMO Q	CB
t _c	92°C

PRIMO Q	CBA / CBM
t _c	88°C

PRIMO Q	2 LED
t _c	90°C

TM TECHNOLOGIE Sp. z o.o., Morawica 355, 32-084 Morawica, gm. Liszki, Poland, tel.: +48 12 444 60 60, fax: +48 12 350 57 34, www.tmtechnologie.pl

IP20 LED 3h

210 ± 250 V AC
50 / 60 Hz
186 ± 254 V DC

TM TECHNOLOGIE
emergency & evacuation lighting

TM.PRIMO Q

*ST / AT / D2 / D2R / DA

! ±1 [mm]

PRIMO Q	A	B
30	399	192
40	499	242

**PRIMO Q RADIO

1

1.1

1.2 CBA / CBM / D2 / D2R / DA

TM-PROG

85**

≤50mm

186 ± 254 V DC

