




## MULTICURRENT DIMMABLE DRIVERS DALI / PUSH

### Features

Can be used with fittings with replaceable remote driver.  
220÷240 V 50/60 Hz  
Lifetime 50000 h.



### Characteristic data

Power	40 W	Dimmable	DALI	Input	220-240 Vac	Base	Screws
IP	20	PF	0,95	LED Warranty	G5h24		

### Dimensional characteristics

L	147 mm
L1	44 mm
H	30 mm

### Lighting and photometric features

Lifespan	50000 h
----------	---------

### Electrical characteristics

Rated power	40 W
Input voltage	220-240 Vac
Frequency	50 Hz
Dimmable	DALI
Power factor (PF)	0,95
Operating temperature	-25°C / +35°C

### Other Infotech

ENEC	Yes
------	-----

## LED Warranty

65h24	Full Guarantee 5 years (24h/24h) Without limitations on the duration of use for the first year, provided the observance of the installation conditions.
-------	---

## European Directives

2009/125/EC \* Ecodesign  
2011/65/EU \* RoHS  
2012/19/EU \* RAEE  
2014/30/EU \* EMC (Compatibilità Elettromagnetica)  
2014/35/EU \* LVD (Bassa Tensione)  
2015/863 \* Amending RoHS  
2017/1369 \* Regulation for Energy Labelling  
2019/2015 \* Regulation for Energy Labelling  
2019/2020 \* Regulation for Ecodesign  
2021/340 \* Amending Reg. Energy Labelling  
2021/341 \* Amending Reg. Ecodesign

## Product standards

CEI EN 55015:2020 (+A11:2020)  
CEI EN 61000-3-2:2019 (+A1:2021)  
CEI EN 61000-3-3:2014 (+EC1:2014/+EC2:2016/+A1:2021/+A2:2022)  
CEI EN 61347-1:2016 (+A1:2021)  
CEI EN 61347-2-13:2015 (+A1:2018)  
CEI EN 61547:2010

## Logistics data

Item net weight	400 gr
Barcode single item	8011905863210
Minimum order quantity	1